```
(RPAQQ MEDLEYDIR-INITCOMS
       ([P (LOAD? (CONCAT (OR (UNIX-GETENV "MEDLEYDIR")
                              "")
                          "/sources/MEDLEYDIR.LCOM"))
          (MEDLEY-INIT-VARS 'GREET)
          (KEYACTION 'LOCK '(LOCKTOGGLE . IGNORE]
        (FILES BACKGROUND-YIELD)
        (VARS  ;; settings for new users

              (DWIMWAIT 180)
              (HELPDEPTH 4)
              (HELPTIME 1)
              (FILING.ENUMERATION.DEPTH 1)
              [LOGINDIR (DIRECTORYNAME (OR (UNIX-GETENV "LOGINDIR")
                                           (UNIX-GETENV "HOME"]
              [USERGREETFILES `((,LOGINDIR "INIT" COM)
                                (,LOGINDIR "INIT"]
              (COPYRIGHTFLG 'NEVER)
              (COPYRIGHTSRESERVED NIL)
              (AUTOBACKTRACEFLG 'ALWAYS)
              (MAXLEVEL 30000)
              (MAXLOOP 30000))
        (FNS INTERLISPMODE)
        (ALISTS (FONTDEFS))))

(LOAD? (CONCAT (OR (UNIX-GETENV "MEDLEYDIR")
                   "")
               "/sources/MEDLEYDIR.LCOM"))

(MEDLEY-INIT-VARS 'GREET)

(KEYACTION 'LOCK '(LOCKTOGGLE . IGNORE))

(FILESLOAD BACKGROUND-YIELD)

(RPAQQ DWIMWAIT 180)

(RPAQQ HELPDEPTH 4)

(RPAQQ HELPTIME 1)

(RPAQQ FILING.ENUMERATION.DEPTH 1)

(RPAQ LOGINDIR (DIRECTORYNAME (OR (UNIX-GETENV "LOGINDIR")
                                  (UNIX-GETENV "HOME"))))

(RPAQ USERGREETFILES `((,LOGINDIR "INIT" COM)
                       (,LOGINDIR "INIT")))

(RPAQQ COPYRIGHTFLG NEVER)

(RPAQQ COPYRIGHTSRESERVED NIL)

(RPAQQ AUTOBACKTRACEFLG ALWAYS)

(RPAQQ MAXLEVEL 30000)

(RPAQQ MAXLOOP 30000)

(DEFINEQ

(INTERLISPMODE
  [LAMBDA (OLD?)                                          (* N.H.Briggs " 2-Feb-88 14:26")
    (PROCESSPROP 'EXEC 'PROFILE (XCL:COPY-PROFILE (if OLD?
                                                      then "OLD-INTERLISP-T"
                                                      else "INTERLISP")))
    (XCL:SET-DEFAULT-EXEC-TYPE (if OLD?
                                   then "OLD-INTERLISP-T"
                                   else "INTERLISP"))
    (SETQ *DEFAULT-MAKEFILE-ENVIRONMENT* (LIST :READTABLE (if OLD?
                                                             then "OLD-INTERLISP-FILE"
                                                             else "INTERLISP")
                                               :PACKAGE "INTERLISP"])
```

)

(ADDTOVAR **FONTDEFS**)

(ADDTOVAR **FONTDEFS**)

FUNCTION INDEX

INTERLISPMODE 1

VARIABLE INDEX