

File created: 28-Jun-93 22:43:05 {DSK}<python>RELEASE>loops>2.0>src>LOOPSPRINT.;4

changes to: (ALISTS (PRETTYPRINTMACROS @)
(PRETTYPRINTMACROS _@)
(PRETTYPRINTMACROS _)
(PRETTYPRINTMACROS SEND)
(PRETTYPRINTMACROS _IV)
(PRETTYPRINTMACROS _Proto)
(PRETTYPRINTMACROS _New)
(PRETTYPRINTMACROS _Super)
(PRETTYPRINTMACROS _!)
(PRETTYPRINTMACROS _Process)
(PRETTYPRINTMACROS _Process!)
(PRETTYPRINTMACROS \LOOPS-PRINT-EVAL-MARKER))
(FNS PrintLoopsEvalAtLoad)
(VARS LOOPSPRINTCOMS)

previous date: 14-Jun-93 23:50:45 {DSK}<python>RELEASE>loops>2.0>src>LOOPSPRINT.;3

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

::
:: Copyright (c) 1983, 1984, 1985, 1986, 1987, 1988, 1990, 1991, 1993 by Venue & Xerox Corporation. All rights reserved.

(RPAQQ LOOPSPRINTCOMS
[

;;; Functions for handling READ macros

```
(DECLARE%: DONTCOPY (PROP MAKEFILE-ENVIRONMENT LOOPSPRINT)
  (PROP FILETYPE LOOPSPRINT))
(INITVARS (LoopsReadMacroChar '%#))
(GLOBALVARS LoopsReadMacroChar)
(ADDVARS (GLOBALVARS LoopsReadMacroChar))
(FNS HashMacro PPDefault SETALLSYNTAX $& $ $C)
;; Used to include the following: (COMS (P (SETALLSYNTAX LoopsReadMacroChar '(MACRO FIRST HashMacro))) (ADVICE
;; HPINITRDTRL)
```

;;; Printing of classes and instances

```
(FNS PrintClass PrintInstance)
(DECLARE%: EVAL@COMPILE DONTCOPY (EXPORT (FUNCTIONS TTYStream?))
  (FILES (LOADCOMP)
    LOOPSDATATYPES))
(P (DEFPRINT 'class 'PrintClass)
  (DEFPRINT 'instance 'PrintInstance))
```

;;; Prettyprinting functions

;; PPObj is Called by the PrettyPrinter on instances. ObjectAlwaysPPFlag and ObjectDontPPFlag are used to determine if the PrettyPrint
;; macro should be applied recursively within the scope of a pretty printing operation. ObjectDontPPFlag is bound to NIL in Object.PP to
;; supress recursive prettyprinting on files and if objects don't have special PP Methods of there own.

```
(INITVARS (ObjectAlwaysPPFlag)
  (ObjectDontPPFlag)
  (WritingToEtherNet))
(FUNCTIONS WITH.PP.OUTPUT)
(SPECVARS ObjectAlwaysPPFlag ObjectDontPPFlag WritingToEtherNet)
(FNS EntityAddress PrettyPrintLoopsForm PrettyPrintClass PrintDefInstances PrettyPrintInstance
  PrttyClasses PrttyInstances PrintLoopsEvalAtLoad PPC PPObj)
(INITVARS (UnnamedInstances NIL))
(GLOBALVARS UnnamedInstances)
(ALISTS (PRETTYPRINTYPEMACROS instance)
  (PRETTYPRINTMACROS @ _@ _ SEND _IV _Proto _New _Super _! _Process _Process!
    \LOOPS-PRINT-EVAL-MARKER))
```

;;; Set up macros so that references to classes and instances seen by HPRINT don't recur into their structure.

```
(FNS HPRINTCLASS HPRINTINSTANCE HREADCLASS HREADINSTANCE)
(ADDVARS (HPRINTMACROS (class . HPRINTCLASS)
  (instance . HPRINTINSTANCE)))
(DECLARE%: DONTVAL@LOAD DONTVAL@COMPILE DONTCOPY COMPILEVARS (ADDVARS (NLAMA $&
  (NLAML $C $)
  (LAMA])
```

;;; Functions for handling READ macros

(DECLARE%: DONTCOPY

(* * Get object given name)

(GetObjectRec name)]

(\$C

[NLAMBDA (name)

(* sml " 4-Apr-86 15:25")

(* * Get class, given the name. If the class doesn't exist, create it.

- This is an attempt to take care of forward references in files. See the fn PrintClass to see how classes print out.)

(OR (GetClassRec name)
(NewClass name])

)

;; Used to include the following: (COMS (P (SETALLSYNTAX LoopsReadMacroChar '(MACRO FIRST HashMacro))) (ADVICE HPINITRDTBL)

;;; Printing of classes and instances

(DEFINEQ

(**PrintClass**

[LAMBDA (classRec file)

; Edited 15-Aug-90 12:49 by jds

;;; This is called by the LISP PRINT function when it sees an instance of the data type class

(CONS (CONCAT LoopsReadMacroChar ",")
(LIST (if (OR (NULL file)
(TTYStream? file)
(DISPLAYSTREAMP file))
then
'\$
else
'\$C)
(fetch (class className) of classRec]))

; for local human consumption

; Dumping to a file

(**PrintInstance**

[LAMBDA (instanceRec file)

; Edited 4-Jun-87 18:33 by sml

;;; This is called by the LISP PRINT function when it sees an instance of the data type instance

(DECLARE (SPECVARS WritingToEtherNet FileEntities OutInstances))
(PROG (entity uid uidString) ; (NOT (EQP FILERDTBL (GETREADTABLE)))
[COND
(OR WritingToEtherNet OutInstances) ; Force items being saved to have a uid
(SETQ uid (UID instanceRec)))
(OR (NULL file)
(TTYStream? file)
(DISPLAYSTREAMP file)) ; for local human consumption
(RETURN (_ instanceRec PrintOn file)))
(T
(SETQ uid (UID instanceRec)
(RETURN (COND
(OutInstances ; This case when dumping instances to a file with INSTANCES
(AND (_ instanceRec SaveInstance? file (CAR OutInstances))
(TCONC OutInstances instanceRec)) ; Recursive dump of instances referred to
(LIST (CONCAT LoopsReadMacroChar ",")
'\$&
(ClassName instanceRec)
uid))
(T

;;; Internal or ethernetPrinting printing * WritingToEtherNet set when writing to EtherNet

(LIST (CONCAT LoopsReadMacroChar ",")
'\$&
(ClassName instanceRec)
uid))

)

(DECLARE%: EVAL@COMPILE DONTCOPY

;; FOLLOWING DEFINITIONS EXPORTED

(DEFMACRO **TTYStream?** (s)
'(EQ (GETSTREAM T 'OUTPUT)
(GETSTREAM ,s 'OUTPUT)))

;; END EXPORTED DEFINITIONS

(FILESLOAD (LOADCOMP)
LOOPSDATATYPES)

)

(DEFPRINT 'class 'PrintClass)

(DEFPRINT 'instance 'PrintInstance)

;;; Prettyprinting functions

;; PPObj is Called by the PrettyPrinter on instances. ObjectAlwaysPPFlag and ObjectDontPPFlag are used to determine if the PrettyPrint macro should be applied recursively within the scope of a pretty printing operation. ObjectDontPPFlag is bound to NIL in Object.PP to suppress recursive prettyprinting on files and if objects don't have special PP Methods of their own.

(RPAQ? ObjectAlwaysPPFlag)

(RPAQ? ObjectDontPPFlag)

(RPAQ? WritingToEtherNet)

```
(DEFMACRO WITH.PP.OUTPUT (stream &BODY forms)
  [Once-Only (stream)
    \ (RESETLST
      [if (WINDOWP ,stream)
        then [RESETSAVE NIL (LIST (FUNCTION WINDOWPROP)
                                   ,stream
                                   'PROCESS
                                   (WINDOWPROP ,stream 'PROCESS])
              (RESETSAVE (TTYDISPLAYSTREAM ,stream))
              (if (NOT (TTY.PROCESSP))
                  then (RESETSAVE (TTY.PROCESS (THIS.PROCESS)
                                         ,@forms)))]])
```

(DECLARE%: DOEVAL@COMPILE DONTCOPY

```
(SPECVARS ObjectAlwaysPPFlag ObjectDontPPFlag WritingToEtherNet)
)
```

(DEFINEQ

(EntityAddress

```
[LAMBDA (E)
  (LOC E)]
```

(* dbg%: "11-NOV-82 02:29")

(PrettyPrintLoopsForm

[LAMBDA (form)

(* smL " 2-May-86 16:30")

(* * Pretty-print the Loops form)

```
(PRIN1 "(")
(PRI2 (CAR form))
(SPACES 1)
(PRINTDEF (CDR form)
  (POSITION)
  T T)
(PRI1 ")")
NIL]
```

(PrettyPrintClass

[LAMBDA (className file)

; Edited 25-Jun-87 13:57 by smL

;;; Called to prettyPrint a class definition on a file by the FILEPKGTYPE CLASSES and by the PP: method in Class

```
(DECLARE (SPECVARS className))
(LET ((class (GetClassRec className)))
  (COND
    ((NULL class)
     (HELPHECK className " is not defined as a class.
      Type OK to ignore this class and go on.))
    (T (_ class FileOut file)
     className])
```

(PrintDefInstances

[LAMBDA (instances file)

(* dbg%: " 5-OCT-82 10:50")

(* * Does the INSTANCES command for the LISP file pkg.)

```
(TERPRI file)
(PRI1 "[DEFINSTANCES " file)
(for inst instRec in instances do (SETQ instRec (GetObjectRec inst))
  (PRI2 (CONS (ClassName instRec)
              (GetObjectNames instRec))
        file)
  (SPACES 1 file))
(PRI1 "]" file)
```

```
(TERPRI file)
(TERPRI file)
instances])
```

(PrettyPrintInstance

[LAMBDA (self file)

```
; Edited 9-Mar-88 11:55 by jrb:
(* PrettyPrint an self definition on file.)
```

```
(if self
  then (if (CL:SYMBOLP self)
            then (SETQ self ($! self)))
        (_ self FileOut file))
self])
```

(PrttyClasses

[LAMBDA (classes)

(* smL "15-Aug-86 10:21")

(* * Used by CLASSES command to print out rereadable versions of class definitions on files)

```
(PRINT (CONS 'DEFCLASSES classes))
(TERPRI)
(for className in classes do (PrettyPrintClass className (OUTPUT]))
```

(PrttyInstances

[LAMBDA (instances)

(* smL "15-Aug-86 10:23")

(* * Prettyprint a list of named instances to a file. OutInstances is bound here, although usually a free variable when printing an instance)

```
(LET [(OutInstances (LCONC NIL (for name obj in instances collect obj
                                when (SETQ obj (OR (GetObjectRec name)
                                                    (NULL (HELPCHECK name " not defined as an instance.
                                                         Type OK to ignore and go on."))
                                (DECLARE (SPECVARS OutInstances))
                                (for obj in (CAR OutInstances) do (PrettyPrintInstance obj (OUTPUT))
                                (TERPRI)
                                (TERPRI]))
```

(PrintLoopsEvalAtLoad

```
[LAMBDA (FORM)
  (PRIN1 "#,")
  (PRIN2 (CADR FORM))
  NIL])
```

; Edited 28-Jun-93 16:20 by sybalsky:mv:envos

(PPC

[LAMBDA (className)

(* smL "11-Apr-86 17:11")

(* * PrettyPrint the class)

```
(LET ((class (GetClassRec className)))
  (if class
    then (_ class PP)
    else (ERROR "No such class" className]))
```

(PPObj

[LAMBDA (instance)

; Edited 2-Dec-87 16:22 by jrb:

;;; Called by the PrettyPrinter on instances.

```
[LET ((FOO *STANDARD-OUTPUT*)
      (COND
        (ObjectAlwaysPPFlag
         (_ instance PP *STANDARD-OUTPUT*))
        (ObjectDontPPFlag
         (PRIN2 instance))
        ((EQ *STANDARD-OUTPUT* *TERMINAL-IO*)
         (_ instance PP *STANDARD-OUTPUT*))
        (T
         (PRIN2 instance]
NIL])
```

; Don't suppress PPing

; Suppress PPing

; Displaying for the user, so PP it

; No reason to PP to a file, so dont

)

(RPAQ? UnnamedInstances NIL)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS UnnamedInstances)

)

(ADDTOVAR PRETTYPRINTYPEMACROS (instance . PPObj))

```
(ADDTOVAR PrettyPrintMacros (@ . PrettyPrintLoopsForm)
  (_@ . PrettyPrintLoopsForm)
  (_ . PrettyPrintLoopsForm)
  (SEND . PrettyPrintLoopsForm)
  (_IV . PrettyPrintLoopsForm)
  (_Proto . PrettyPrintLoopsForm)
  (_New . PrettyPrintLoopsForm)
  (_Super . PrettyPrintLoopsForm)
  (_! . PrettyPrintLoopsForm)
  (_Process . PrettyPrintLoopsForm)
  (_Process! . PrettyPrintLoopsForm)
  NIL)
```

;;; Set up macros so that references to classes and instances seen by HPRINT don't recur into their structure.

```
(DEFINEQ
```

```
(HPRINTCLASS
```

```
  [LAMBDA (EXPR FILE) (* dgb%: "18-MAR-83 16:35")
```

```
    (* Used by HPRINT to print out an expression which will be read back in as a class)
```

```
    (PRIN1 ' (HREADCLASS)
```

```
      FILE)
```

```
    (PRIN2 (ClassName EXPR]))
```

```
(HPRINTINSTANCE
```

```
  [LAMBDA (EXPR FILE) (* dgb%: "18-MAR-83 16:36")
```

```
    (* Used by HPRINT to print out an expression referring to an instance, provided instance is dumped eleewhere)
```

```
    (PRIN1 ' (HREADINSTANCE)
```

```
      FILE)
```

```
    (PRIN2 (UID EXPR]))
```

```
(HREADCLASS
```

```
  [LAMBDA (FILE) (* dgb%: "13-DEC-82 15:13")
```

```
    (GetObjectRec (HREAD FILE]))
```

```
(HREADINSTANCE
```

```
  [LAMBDA (FILE) (* dgb%: " 8-Oct-84 13:28")
```

```
    (GetObjectRec (HREAD FILE]))
```

```
)
```

```
(ADDTOVAR HPRINTMACROS (class . HPRINTCLASS)
  (instance . HPRINTINSTANCE))
```

```
(DECLARE%: DONTEVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVAR
```

```
(ADDTOVAR NLAMA $%)
```

```
(ADDTOVAR NLAML $C $)
```

```
(ADDTOVAR LAMA )
```

```
)
```

```
(PUTPROPS LOOPSPRINT COPYRIGHT ("Venue & Xerox Corporation" 1983 1984 1985 1986 1987 1988 1990 1991 1993))
```

FUNCTION INDEX

\$2	HPRINTINSTANCE6	PrettyPrintClass4	PrintLoopsEvalAtLoad5
\$&2	HREADCLASS6	PrettyPrintInstance5	PrttyClasses5
\$C3	HREADINSTANCE6	PrettyPrintLoopsForm4	PrttyInstances5
EntityAddress4	PPC5	PrintClass3	SETALLSYNTAX2
HashMacro2	PPDefault2	PrintDefInstances4	
HPRINTCLASS6	PPObj5	PrintInstance3	

VARIABLE INDEX

HPRINTMACROS6	ObjectAlwaysPPFlag4	PRETTYPRINTMACROS6	UnnamedInstances5
LoopsReadMacroChar2	ObjectDontPPFlag4	PRETTYPRINTYPEMACROS5	WritingToEtherNet4

MACRO INDEX

TTYStream?3	WITH.PP.OUTPUT4
-------------------	-----------------------

PROPERTY INDEX

LOOPSPRINT2
