```
;;
;; Copyright (c) 1985, 1987, 1990, 1995 by Venue & Xerox Corporation.


(RPAQQ KEYBOARDEDITORCOMS
       ((FILES VIRTUALKEYBOARDS)
        (COMS  ;; Editor for Configurations -- the description of the physical key layout, which keys are assignable, etc.

               (FNS EDITCONFIGURATION VKBD.CONF.CHANGE-KEY-VALUE VKBD.CONF.DISPLAY-FIELD-VALUE
                    VKBD.CONF.DISPLAY-INFO-KEYBOARD VKBD.CONF.DISPLAY-KEY-INFO VKBD.CONF.EDIT-DEFAULT-ASSIGNMENTS
                    VKBD.CONF.ICONFN VKBD.CONF.PARSE-CONFIGURATION)
               (BITMAPS VKBD.CONF.ICON))

        ;; EEditor for keyboard layouts per se:

        (FNS EDITKEYBOARD VKBD.EDIT.ADD-SUBITEM-TO-BACKGROUND-MENU VKBD.EDIT.CREATE-COMMAND-MENU
             VKBD.EDIT.CREATE-NON-CHAR-ASSIGMENTS-MENU VKBD.EDIT-KEYBOARD-COMMAND VKBD.EDIT.ASSIGN-CHARACTER
             VKBD.EDIT.ASSIGN-NON-CHARACTER VKBD.EDIT.CREATE-CHARACTER-SETS-MENU
             VKBD.EDIT.CREATE-CHARACTERS-MENU VKBD.EDIT.CREATE-DISPLAY VKBD.EDIT.DEFINE-COMMAND
             VKBD.EDIT.DO-MENU-COMMAND VKBD.EDIT.ICONFN VKBD.EDIT.INVERT-IF-LOCKED VKBD.EDIT.KEYBOARD-REPAINTFN
             VKBD.EDIT.LARGE-WINDOW-REPAINTFN VKBD.EDIT.MAKE-CURRENT-KEY VKBD.EDIT.QUIT-COMMAND
             VKBD.EDIT.STOP-COMMAND VKBD.EDIT.SWITCH-CHAR-SET-COMMAND VKBD.EDIT.SWITCH-CHARACTER-SET
             VKBD.EDIT.ROTATED-NUMBER)
        (INITVARS (VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS T)
               (VKBD.EDIT.MAX-NUMBER-OF-CASHED-MENUS 15)
               (VKBD.EDITOR-WINDOW-HEIGHT 450)
               (VKBD.EDITOR-WINDOW-WIDTH 512)
               (VKBD.EDIT.DISPLAY-CHAR-SETS-NAMES T))
        (VARS VKBD.EDIT.BACKGROUND-MENU-SUBITEMS (VKBD.EDIT.CASH-MENUES NIL)
              VKBD.EDIT.CHAR-SET-NAMES VKBD.EDIT.MENU-ITEMS VKBD.EDIT.NON-CHAR-ASSIGNMENTS)
        (BITMAPS VKBD.EDIT.ICON VKBD.EDIT.MASK)
        (GLOBALVARS VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS VKBD.EDIT.BACKGROUND-MENU-SUBITEMS
              VKBD.EDIT.MAX-NUMBER-OF-CASHED-MENUS VKBD.EDITOR-WINDOW-HEIGHT VKBD.EDITOR-WINDOW-WIDTH
              VKBD.EDIT.DISPLAY-CHAR-SETS-NAMES VKBD.EDIT.CASH-MENUES VKBD.EDIT.CHAR-SET-NAMES
              VKBD.EDIT.MENU-ITEMS VKBD.EDIT.NON-CHAR-ASSIGNMENTS VKBD.CONF.ICON VKBD.EDIT.ICON VKBD.EDIT.MASK)
        (P (VKBD.EDIT.ADD-SUBITEM-TO-BACKGROUND-MENU (LIST "Edit" '(ADD.PROCESS '(VKBD.EDIT-KEYBOARD-COMMAND
                                                                                 T))
                                                           "Calls the keyboard editor. Will prompt for name for
                                                           the new keyboard, and will use the default keyboard
                                                           as the initial keyboard"
                                                           VKBD.EDIT.BACKGROUND-MENU-SUBITEMS)
                      "Keyboard")))))

(FILESLOAD VIRTUALKEYBOARDS)
```

;; Editor for Configurations -- the description of the physical key layout, which keys are assignable, etc.

```
(DEFINEQ
```

(EDITCONFIGURATION
```
  [LAMBDA (CONFIGNAME)                                              ; Edited 30-Jun-87 10:03 by jds
```
    ;; Edit a keyboard configuration, given the config's name or a handle on the config somehow.
```
    (VKBD.CONF.DISPLAY-INFO-KEYBOARD CONFIGNAME])
```

(VKBD.CONF.CHANGE-KEY-VALUE
```
  [LAMBDA (ITEM MENU MOUSEKEY)                                      (* sm "14-Aug-85 18:05")
    (PROG (MAINW CONF WINDOW PROMPTW KEY)
          (SETQ WINDOW (WFROMMENU MENU))
          [SETQ PROMPTW (CAR (WINDOWPROP WINDOW 'PROMPTWINDOW]
          (SETQ MAINW (MAINWINDOW WINDOW T))
          (SETQ CONF (VKBD.GET-CONFIGURATION MAINW))
          (SETQ KEY (WINDOWPROP MAINW 'VKBD.CONF.CURRENT-KEY))
          (SELECTQ (CADR ITEM)
              (KEYID (PROG (NEW)
                           (SETQ NEW (CAR (TTYINEDIT (LIST KEY)
                                                     PROMPTW NIL "Enter new ID :")))
                           (DSUBST NEW KEY CONF)
                           (WINDOWPROP MAINW 'VKBD.CONF.CURRENT-KEY NEW)
                           (SETQ KEY NEW)))
              (REGIONS (PROG (CURRENT-REGIONS NEW-REGIONS)
                           (SETQ CURRENT-REGIONS (FASSOC KEY (fetch (KEYBOARDCONFIGURATION KEYREGIONS)
                                                                    of CONF)))
```

```
                                    (SETQ NEW-REGIONS (CAR (TTYINEDIT (LIST (CDR CURRENT-REGIONS))
                                                                      PROMPTW NIL "Enter new region(s) :")))
                                    (RPLACD CURRENT-REGIONS NEW-REGIONS)))
                    (DEFAULT (PROG (CURRENT-DEFAULT ASSIGNMENTS NEW)
                               (SETQ ASSIGNMENTS (fetch (KEYBOARDCONFIGURATION DEFAULTASSIGNMENT) of CONF))
                               (SETQ CURRENT-DEFAULT (FASSOC KEY ASSIGNMENTS))
                               (SETQ ASSIGNMENTS (REMOVE CURRENT-DEFAULT ASSIGNMENTS))
                               (SETQ NEW (CAR (TTYINEDIT (LIST (CDR CURRENT-DEFAULT))
                                                          PROMPTW NIL "Enter new default(s):")))
                               (replace (KEYBOARDCONFIGURATION DEFAULTASSIGNMENT) of CONF
                                  with (CONS (CONS KEY NEW)
                                             ASSIGNMENTS))
                               (WINDOWPROP MAINW 'VKBD.KEYBOARD (VKBD.CREATE-DEFAULT-KEYBOARD CONF))))
                    (NAMES (PROG (CURRENT NEW MAPPING)
                             (SETQ CURRENT (VKBD.KEY-ID-TO-KEY-NAMES KEY CONF))
                             (SETQ MAPPING (fetch (KEYBOARDCONFIGURATION KEYNAMESMAPPING) of CONF))
                             (for N in CURRENT do (SETQ MAPPING (REMOVE (LIST N KEY)
                                                                         MAPPING)))
                             (SETQ NEW (CAR (TTYINEDIT (LIST CURRENT
                                                        PROMPTW NIL "Enter new NAME(s) :")))
                             (for N in (MKLIST NEW) do (pushnew MAPPING (LIST N KEY)))
                             (replace (KEYBOARDCONFIGURATION KEYNAMESMAPPING) of CONF with MAPPING)))
                    (LABEL (PROG (OLD-LABEL LABELS NEW)
                             (SETQ LABELS (fetch (KEYBOARDCONFIGURATION KEYLABELS) of CONF))
                             (SETQ OLD-LABEL (FASSOC KEY LABELS))
                             (if OLD-LABEL
                                 then (SETQ LABELS (REMOVE OLD-LABEL LABELS))
                                      (SETQ OLD-LABEL (CADR OLD-LABEL)))
                             (SETQ NEW (CAR (TTYINEDIT (LIST OLD-LABEL
                                                        PROMPTW NIL "Enter new LABEL :")))
                             (replace (KEYBOARDCONFIGURATION KEYLABELS) of CONF
                                with (if NEW
                                         then (CONS (LIST KEY NEW)
                                                    LABELS)
                                         else LABELS))))
                    (ASSIGNABLE [PROG (ASS-KEYS)
                                  (SETQ ASS-KEYS (fetch (KEYBOARDCONFIGURATION ASSIGNABLEKEYS) of CONF))
                                  (if (FMEMB KEY ASS-KEYS)
                                      then (DREMOVE KEY ASS-KEYS)
                                    else (replace (KEYBOARDCONFIGURATION ASSIGNABLEKEYS) of CONF
                                             with (CONS KEY ASS-KEYS)])
                    (PROGN (PROMPTPRINT "ILLEGAL FIELD VALUE IN <VKBD.CONF.CHANGE-KEY-VALUE>")
                           (RETURN NIL)))
               (CLEARW PROMPTW)
               (VKBD.CONF.DISPLAY-FIELD-VALUE KEY (CADR ITEM)
                     CONF WINDOW MENU])
```

(**VKBD.CONF.DISPLAY-FIELD-VALUE**
```
  [LAMBDA (KEY FIELD CONF WINDOW MENU)                                    ; Edited 11-Jun-90 16:40 by mitani
    (PROG (X Y)
         [for ITEM in (fetch ITEMS of MENU) when (EQ (CADR ITEM)
                                                      FIELD)
             do (SETQ Y (fetch (REGION BOTTOM) of (MENUITEMREGION ITEM MENU]
         (SETQ X (IPLUS (fetch MENUREGIONLEFT of MENU)
                        (fetch IMAGEWIDTH of MENU)
                        5))
         (DSPFILL (CREATEREGION X Y (IDIFFERENCE (fetch (REGION WIDTH) of (WINDOWPROP WINDOW 'REGION))
                                                  Y)
                        (fetch ITEMHEIGHT of MENU))
             (DSPTEXTURE NIL WINDOW)
             'REPLACE WINDOW)
         (MOVETO X Y WINDOW)
         (PRIN1 (SELECTQ FIELD
                    (KEYID KEY)
                    (REGIONS (VKBD.GET-KEY-REGIONS KEY CONF))
                    (DEFAULT (CDR (VKBD.FETCH-KEY-ASSIGNMENT KEY (MAINWINDOW WINDOW))))
                    (NAMES (VKBD.KEY-ID-TO-KEY-NAMES KEY CONF))
                    (LABEL (CADR (FASSOC KEY (fetch (KEYBOARDCONFIGURATION KEYLABELS) of CONF))))
                    (ASSIGNABLE (if (FMEMB KEY (fetch (KEYBOARDCONFIGURATION ASSIGNABLEKEYS) of CONF))
                                    then T
                                  else NIL))
                    (PROMPTPRINT "ILLEGAL FIELD VALUE FOR DISPLAY CONFIGURATION FIELD VALUE!"))
                WINDOW])
```

(**VKBD.CONF.DISPLAY-INFO-KEYBOARD**
```
  [LAMBDA (CONFIGURATION)                                                 ; Edited 25-May-95 11:34 by rmk:
    (PROG (WINDOW ATT-WINDOW MENU VALIDATED-CONFIG)
         (COND
            ((NOT (SETQ VALIDATED-CONFIG (VKBD.GET-CONFIGURATION CONFIGURATION)))

             ;; Make sure the configuration name is legit.

             (ERROR CONFIGURATION "is not the name of a known keyboard configuration.")))
         (SETQ WINDOW (VKBD.CREATE-KEYBOARD-DISPLAY (VKBD.CREATE-DEFAULT-KEYBOARD VALIDATED-CONFIG)
                        NIL
                        'VKBD.CONF.DISPLAY-KEY-INFO NIL T))
```

```
(SETQ MENU (create MENU
                        ITEMS _ '(("Key ID" KEYID)
                                   ("Key regions" REGIONS)
                                   ("Default assignment" DEFAULT)
                                   ("Key names" NAMES)
                                   ("Key Label" LABEL)
                                   ("Assignable? " ASSIGNABLE))
                        MENUBORDERSIZE _ 0
                        MENUOUTLINESIZE _ 0
                        MENUFONT _ BOLDFONT
                        WHENSELECTEDFN _ 'VKBD.CONF.CHANGE-KEY-VALUE))
      (SETQ ATT-WINDOW (CREATEW (CREATEREGION 0 0 (fetch (REGION WIDTH) of (WINDOWPROP WINDOW 'REGION))
                                               (IPLUS 10 (fetch IMAGEHEIGHT of MENU)))
                           NIL NIL T))
      (ATTACHWINDOW ATT-WINDOW WINDOW 'TOP 'JUSTIFY)
      (OPENW ATT-WINDOW)
      (ADDMENU MENU ATT-WINDOW (create POSITION
                                    XCOORD _ 0
                                    YCOORD _ 0))
      (GETPROMPTWINDOW ATT-WINDOW 2 BOLDFONT)
      (WINDOWPROP WINDOW 'ICONFN 'VKBD.CONF.ICONFN))
```

(**VKBD.CONF.DISPLAY-KEY-INFO**
```
  [LAMBDA (KEY WINDOW MOUSEKEY)                                (* sm "14-Aug-85 15:38")
    (PROG (CONFIGURATION OLD-KEY ATT-WINDOW)
          (if (SETQ OLD-KEY (WINDOWPROP WINDOW 'VKBD.CONF.CURRENT-KEY))
              then (VKBD.ERASE-FRAME OLD-KEY WINDOW 2))
          (WINDOWPROP WINDOW 'VKBD.CONF.CURRENT-KEY KEY)
          (VKBD.FRAME-KEY KEY WINDOW BLACKSHADE 2)
          (SETQ CONFIGURATION (VKBD.GET-CONFIGURATION WINDOW))
          (SETQ ATT-WINDOW (CAR (ATTACHEDWINDOWS WINDOW)))
          (for F in '(KEYID REGIONS DEFAULT NAMES LABEL ASSIGNABLE)
              do (VKBD.CONF.DISPLAY-FIELD-VALUE KEY F CONFIGURATION ATT-WINDOW (CAR (WINDOWPROP ATT-WINDOW
                                                                                        'MENU])
```

(**VKBD.CONF.EDIT-DEFAULT-ASSIGNMENTS**
```
  [LAMBDA (CONFIGURATION)                                       (* sm "15-Aug-85 10:25")
    (PROG (DUMMY-CONFIGURATION DUMMY-KEYBOARD)
          (SETQ CONFIGURATION (VKBD.GET-CONFIGURATION CONFIGURATION))
          (SETQ DUMMY-CONFIGURATION (COPY CONFIGURATION))
          (replace (KEYBOARDCONFIGURATION ASSIGNABLEKEYS) of DUMMY-CONFIGURATION with (fetch (KEYBOARDCONFIGURATION
                                                                                          KEYSIDLIST)
                                                                             of DUMMY-CONFIGURATION))
          (replace (KEYBOARDCONFIGURATION KEYLABELS) of DUMMY-CONFIGURATION with NIL)
          (SETQ DUMMY-KEYBOARD (create VIRTUALKEYBOARD
                                    KEYBOARDNAME _ "DEFAULT ASIGNMENTS"
                                    KEYASSIGNMENTS _ (fetch (KEYBOARDCONFIGURATION DEFAULTASSIGNMENT)
                                                        of CONFIGURATION)
                                    KEYBOARDCONFIGURATION _ DUMMY-CONFIGURATION))
          (EDITKEYBOARD DUMMY-KEYBOARD)
          (replace (KEYBOARDCONFIGURATION DEFAULTASSIGNMENT) of CONFIGURATION with (fetch (VIRTUALKEYBOARD
                                                                                       KEYASSIGNMENTS)
                                                                          of DUMMY-KEYBOARD])
```

(**VKBD.CONF.ICONFN**
```
  [LAMBDA (WINDOW ICON)                                         (* sm "15-Aug-85 11:02")
    [COND
        ((NULL ICON)
         (SETQ ICON (TITLEDICONW (create TITLEDICON
                                      ICON _ VKBD.CONF.ICON
                                      MASK _ VKBD.EDIT.MASK
                                      TITLEREG _ (CREATEREGION 5 15 80 75))
                          (CONCAT "EDIT CONFIGURATION: " (fetch (KEYBOARDCONFIGURATION CONFIGURATIONNAME)
                                                              of (VKBD.GET-CONFIGURATION WINDOW)))
                          (FONTCREATE 'GACHA 8]
        ICON])
```

(**VKBD.CONF.PARSE-CONFIGURATION**
```
  [LAMBDA (CONFIGURATION)                                       (* sm " 5-Aug-85 17:05")
    (PROG (ERROR-FLAG REGS IDS)
          (SETQ CONFIGURATION (VKBD.GET-CONFIGURATION CONFIGURATION))
          (if (NULL CONFIGURATION)
              then (PRINTOUT T T CONFIGURATION " NOT A CONFIGURATION. ")
                   (RETURN NIL))
          (SETQ IDS (fetch (KEYBOARDCONFIGURATION KEYSIDLIST) of CONFIGURATION))
          (SETQ REGS (fetch (KEYBOARDCONFIGURATION KEYREGIONS) of CONFIGURATION))
          (if (NULL IDS)
              then (PRINTOUT T T "Null Id list. ")
                   (RETURN NIL))
          (if (LESSP (LENGTH REGS)
                     (LENGTH IDS))
              then (PRINTOUT T T "KEYS WITHOUT REGIONS : ")
                   (for K in IDS when (NOT (FASSOC K REGS)) do (PRINTOUT T " " K))
```

```
                        (SETQ ERROR-FLAG T))
         (for R in REGS do (for R1 in (CDR R) when (NOT (REGIONP R1)) DO (SETQ ERROR-FLAG T)
                                                              (PRINTOUT T T "KEY : " (CAR R)
                                                                        " -- " R1 " NOT A REGION")))
         (for KEY in (fetch (KEYBOARDCONFIGURATION ASSIGNABLEKEYS) of CONFIGURATION)
            when (NOT (FMEMB KEY IDS)) do (SETQ ERROR-FLAG T)
                                          (PRINTOUT T T "KEY :" KEY " IS IN THE ASSIGNABLE KEYS BUT NOT IN KEY
                                                 IDS"))
         (for ASS in (fetch (KEYBOARDCONFIGURATION DEFAULTASSIGNMENT) of CONFIGURATION)
            when (NOT (FMEMB (CAR ASS)
                             IDS))
            do (SETQ ERROR-FLAG T)
               (PRINTOUT T T "KEY : " (CAR ASS)
                         " HAS ASSIGNMENT BUT IS NOT IN ID LIST"))
         (for ID in IDS when (NOT (FASSOC ID (fetch (KEYBOARDCONFIGURATION DEFAULTASSIGNMENT) of CONFIGURATION)))
            do (SETQ ERROR-FLAG T)
               (PRINTOUT T T "KEY :" ID " DOES NOT HAVE ASSIGNMENT."))
         (RETURN (NOT ERROR-FLAG])

)

(RPAQQ VKBD.CONF.ICON
```



```
)
```

;; EEditor for keyboard layouts per se:

(DEFINEQ

(**EDITKEYBOARD**
```
  [LAMBDA (KEYBOARD SOURCE-KEYBOARD CONFIGURATION-NAME)              ; Edited 25-May-95 14:22 by rmk:
                                                                    (* sm " 1-Aug-85 17:55")
     (PROG (VKBD.EDIT-WINDOW CURRENT-EVENT KEYBOARD-TO-EDIT COMPLETE-KEYBOARD)
           (COND
              ((NULL KEYBOARD)
               (RETURN NIL)))
           (IF (LITATOM KEYBOARD)
               THEN (SETQ KEYBOARD-TO-EDIT (FINDVIRTUALKEYBOARD KEYBOARD CONFIGURATION-NAME))
                    (IF (NULL KEYBOARD-TO-EDIT)
                        THEN [IF (AND (NULL SOURCE-KEYBOARD)
                                      CONFIGURATION-NAME)
                                 THEN (SETQ KEYBOARD-TO-EDIT (VKBD.CREATE-DEFAULT-KEYBOARD CONFIGURATION-NAME))
                                 ELSE [SETQ KEYBOARD-TO-EDIT (COPY (IF (AND SOURCE-KEYBOARD (ATOM SOURCE-KEYBOARD)
                                                                      )
                                                                      THEN (FASSOC SOURCE-KEYBOARD
                                                                                   VKBD.KNOWN-KEYBOARDS]
                                      (IF (NULL KEYBOARD-TO-EDIT)
                                          THEN (SETQ KEYBOARD-TO-EDIT (COPY (FASSOC 'DEFAULT VKBD.KNOWN-KEYBOARDS
                                                                                ]
                             (REPLACE KEYBOARDNAME OF KEYBOARD-TO-EDIT WITH KEYBOARD))
               ELSE (SETQ KEYBOARD-TO-EDIT KEYBOARD))
           (SETQ VKBD.EDIT-WINDOW (VKBD.EDIT.CREATE-DISPLAY KEYBOARD-TO-EDIT))
           (WINDOWPROP VKBD.EDIT-WINDOW 'VKBD.KEYBOARD (COPY KEYBOARD-TO-EDIT))
           (WINDOWPROP VKBD.EDIT-WINDOW 'VKBD.ORIGINAL-KEYBOARD KEYBOARD-TO-EDIT)
           (WINDOWPROP VKBD.EDIT-WINDOW 'VKBD.EDITOR-RETURN-EVENT (SETQ CURRENT-EVENT (CREATE.EVENT "VKBD.EDIT"))
                   )
           (AWAIT.EVENT CURRENT-EVENT)
           (CLOSEW VKBD.EDIT-WINDOW)
           (RETURN (WINDOWPROP VKBD.EDIT-WINDOW 'VKBD.KEYBOARD])
```

(**VKBD.EDIT.ADD-SUBITEM-TO-BACKGROUND-MENU**
```
  [LAMBDA (SUBITEM MAINITEMLABEL)                                   (* sm "15-Aug-85 14:14")
     (PROG (MAINITEM OLD)
           (SETQ MAINITEM (SASSOC MAINITEMLABEL BackgroundMenuCommands))
           [COND
              (MAINITEM (COND
                          [(AND (CDDDR MAINITEM)
                                (EQ (CAR (CADDDR MAINITEM))
                                    'SUBITEMS))
                           (COND
                              ((SETQ OLD (SASSOC (CAR SUBITEM)
                                                 (CADDDR MAINITEM)))
                               (RPLACD OLD (CDR SUBITEM)))
                              (T (NCONC1 (CADDDR MAINITEM)
                                         SUBITEM]
                          (T (RPLACD (CDDR MAINITEM)
                                     (LIST (LIST 'SUBITEMS SUBITEM]
```

```
        (SETQ BackgroundMenu NIL])
```

(**VKBD.EDIT.CREATE-COMMAND-MENU**
```
  [LAMBDA NIL                                              (* sm " 1-Aug-85 17:22")
    (create MENU
            ITEMS _ VKBD.EDIT.MENU-ITEMS
            MENUFONT _ (FONTCREATE 'HELVETICA 12 'BOLD)
            CENTERFLG _ T
            MENUROWS _ 1
            WHENSELECTEDFN _ 'VKBD.EDIT.DO-MENU-COMMAND])
```

(**VKBD.EDIT.CREATE-NON-CHAR-ASSIGMENTS-MENU**
```
  [LAMBDA NIL                                              (* sm "13-Aug-85 11:09")
    (create MENU
            ITEMS _ VKBD.EDIT.NON-CHAR-ASSIGNMENTS
            MENUFONT _ (FONTCREATE 'GACHA 8)
            MENUROWS _ (ADD1 (IQUOTIENT (SUB1 (LENGTH VKBD.EDIT.NON-CHAR-ASSIGNMENTS))
                                        4))
            CENTERFLG _ T
            WHENSELECTEDFN _ 'VKBD.EDIT.ASSIGN-CHARACTER])
```

(**VKBD.EDIT-KEYBOARD-COMMAND**
```
  [LAMBDA (NEW-KEYBOARD? ASK-FOR-INITIAL?)                 (* sm "14-Aug-85 15:11")
    (PROG (NEW-NAME KEYBOARD INITIAL-KEYBOARD)
          (if (NOT NEW-KEYBOARD?)
              then (SETQ KEYBOARD (VKBD.POP-UP-KEYBOARDS-MENU "Select the keyboard that you want to edit"))
                   (if KEYBOARD
                       then (if (EQ KEYBOARD 'DEFAULT)
                                then (PROMPTPRINT "Can not edit the default keyboard.")
                                else (EDITKEYBOARD KEYBOARD)))
              else [SETQ NEW-NAME (MKATOM (PROMPTFORWORD "Enter name for new keyboard :" NIL NIL PROMPTWINDOW NIL
                                                        'TTY]
                   (if NEW-NAME
                       then (if ASK-FOR-INITIAL?
                                then (SETQ INITIAL-KEYBOARD (VKBD.POP-UP-KEYBOARDS-MENU "Select the keyboard to be
                                                                   used as initial keyboard for the editing"))
                                     (if INITIAL-KEYBOARD
                                         then (EDITKEYBOARD NEW-NAME INITIAL-KEYBOARD))
                                else (EDITKEYBOARD NEW-NAME 'DEFAULT])
```

(**VKBD.EDIT.ASSIGN-CHARACTER**
```
  [LAMBDA (ITEM MENU MOUSE-KEY)                            (* sm "15-Aug-85 10:02")
    (PROG (WINDOW KEY SHIFTED CURRENT-KEY-INFO KEY-ASSIGNMENT KEYBOARD)
          (SETQ WINDOW (MAINWINDOW (WFROMMENU MENU)
                             T))
          (SETQ KEYBOARD (WINDOWPROP WINDOW 'VKBD.KEYBOARD))
          (SETQ CURRENT-KEY-INFO (WINDOWPROP WINDOW 'VKBD.CURRENT-KEY))
          (if CURRENT-KEY-INFO
              then (SETQ KEY (CAR CURRENT-KEY-INFO))
                   (SETQ SHIFTED (CADR CURRENT-KEY-INFO))
                   (SETQ KEY-ASSIGNMENT (VKBD.FETCH-KEY-ASSIGNMENT KEY WINDOW))
                   [if (AND VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS (MEMBER ITEM VKBD.EDIT.NON-CHAR-ASSIGNMENTS))
                       then (VKBD.EDIT.ASSIGN-NON-CHARACTER KEY-ASSIGNMENT ITEM)
                     else (if (NULL KEY-ASSIGNMENT)
                              then (replace (VIRTUALKEYBOARD KEYASSIGNMENTS) of KEYBOARD
                                        with (CONS (LIST KEY (LIST (CADR ITEM)
                                                                   (CADR ITEM)
                                                                   'NOLOCKSHIFT))
                                                    (fetch (VIRTUALKEYBOARD KEYASSIGNMENTS) of KEYBOARD)))
                            else (RPLACD (CDR KEY-ASSIGNMENT)
                                         NIL)
                                 (if (OR (NULL (CDR KEY-ASSIGNMENT))
                                         (ATOM (CADR KEY-ASSIGNMENT)))
                                     then [RPLACD KEY-ASSIGNMENT (LIST (LIST (CADR ITEM)
                                                                            (CADR ITEM)
                                                                            'NOLOCKSHIFT]
                                   else (if SHIFTED
                                            then (RPLACA (CDADR KEY-ASSIGNMENT)
                                                         (CADR ITEM))
                                          else (RPLACA (CADR KEY-ASSIGNMENT)
                                                       (CADR ITEM]
                   (VKBD.DISPLAY-KEY KEY WINDOW)
              else (FLASHWINDOW PROMPTWINDOW)
                   (PRINTOUT PROMPTWINDOW T "There is no current selected key. Character was not assigned."])
```

(**VKBD.EDIT.ASSIGN-NON-CHARACTER**
```
  [LAMBDA (KEY-ASSIGNMENT NEW-ASSIGNMENT)                  (* sm "13-Aug-85 10:16")
    (RPLACD KEY-ASSIGNMENT (SELECTQ NEW-ASSIGNMENT
                                (SHIFT '(1SHIFTDOWN . 1SHIFTUP))
                                (CTRL '(CTRLDOWN . CTRLUP))
                                (META '(METADOWN . METAUP))
                                (LOCK '(LOCKDOWN . LOCKUP))
```

```
                                      (LOCKDOWN '(LOCKDOWN))
                                      (LOCKUP '(LOCKUP))
                                      (EVENT '(EVENT . EVENT))
                                      NIL])
```

(**VKBD.EDIT.CREATE-CHARACTER-SETS-MENU**
```
  [LAMBDA NIL                                                    (* sm "15-Aug-85 12:13")
    (if VKBD.EDIT.DISPLAY-CHAR-SETS-NAMES
        then [create MENU
                    ITEMS _ VKBD.EDIT.CHAR-SET-NAMES
                    MENUFONT _ BIGFONT
                    ITEMWIDTH _ (ITIMES 29 16)
                    ITEMHEIGHT _ (ADD1 (IQUOTIENT (ITIMES 25 16)
                                                (LENGTH VKBD.EDIT.CHAR-SET-NAMES]
        else (create MENU
                    ITEMS _ (for I from 1 to 256 bind ROTATED-I collect (PROGN (SETQ ROTATED-I
                                                                      (SUB1 (VKBD.EDIT.ROTATED-NUMBER I 16
                                                                            16)))
                                                                   (LIST (OCTALSTRING ROTATED-I)
                                                                        ROTATED-I)))
                    MENUCOLUMNS _ 16
                    CENTERFLG _ T
                    ITEMHEIGHT _ 25
                    ITEMWIDTH _ 29])
```

(**VKBD.EDIT.CREATE-CHARACTERS-MENU**
```
  [LAMBDA (CHAR-SET-NUMBER FONT)                                 ; Edited  6-Jul-2023 16:23 by rmk
                                                                 (* sm "15-Aug-85 12:15")
    (PROG (EXISTING-MENU-INFO NEW-MENU)
          [SETQ EXISTING-MENU-INFO (for CHARSET-FONT-MENU in VKBD.EDIT.CASH-MENUES
                                        thereis (AND (EQP (CAR CHARSET-FONT-MENU)
                                                          CHAR-SET-NUMBER)
                                                     (EQ (CADR CHARSET-FONT-MENU)
                                                         FONT]
          (if EXISTING-MENU-INFO
              then (RETURN (CADDR EXISTING-MENU-INFO)))
          (PRINTOUT PROMPTWINDOW T "Retrieving bitmaps for character set " (OCTALSTRING CHAR-SET-NUMBER))
          (SETQ NEW-MENU (create MENU
                                ITEMS _ (for I from 0 to 255 bind CODE bind ROTATED-I
                                            collect (SETQ ROTATED-I (SUB1 (VKBD.EDIT.ROTATED-NUMBER (ADD1 I)
                                                                          16 16)))
                                                    (SETQ CODE (LOGOR (LLSH CHAR-SET-NUMBER 8)
                                                                      I))
                                                    (LIST (GETCHARBITMAP CODE FONT)
                                                          CODE))
                                MENUCOLUMNS _ 16
                                CENTERFLG _ T
                                ITEMHEIGHT _ 25
                                ITEMWIDTH _ 29
                                WHENSELECTEDFN _ 'VKBD.EDIT.ASSIGN-CHARACTER))
          (PROMPTPRINT "... Done. ")
          (push VKBD.EDIT.CASH-MENUES (LIST CHAR-SET-NUMBER FONT NEW-MENU))
          (if (GREATERP (LENGTH VKBD.EDIT.CASH-MENUES)
                        VKBD.EDIT.MAX-NUMBER-OF-CASHED-MENUS)
              then (RPLACD (LAST VKBD.EDIT.CASH-MENUES)
                           NIL))
          (RETURN NEW-MENU])
```

(**VKBD.EDIT.CREATE-DISPLAY**
```
  [LAMBDA (KEYBOARD)                                             ; Edited 25-May-95 14:07 by rmk:
                                                                 (* sm "13-Aug-85 12:37")
    (PROG (WINDOW LARGE-WINDOW BM WPOS REGION-WIDTH REGION-HEIGHT NON-CHAR-WINDOW COMMAND-MENU NON-CHAR-MENU)
          (SETQ BM (VKBD.CREATE-KEYBOARD-BITMAP (fetch (VIRTUALKEYBOARD KEYBOARDCONFIGURATION) of KEYBOARD)))
          (if VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS
              then (SETQ NON-CHAR-MENU (VKBD.EDIT.CREATE-NON-CHAR-ASSIGMENTS-MENU)))
          (SETQ COMMAND-MENU (VKBD.EDIT.CREATE-COMMAND-MENU))
          [SETQ REGION-WIDTH (MAX VKBD.EDITOR-WINDOW-WIDTH (IPLUS 8 (BITMAPWIDTH BM]
          (SETQ REGION-HEIGHT (MIN SCREENHEIGHT (IPLUS (fetch IMAGEHEIGHT of COMMAND-MENU)
                                                       (if VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS
                                                           then (fetch IMAGEHEIGHT of NON-CHAR-MENU)
                                                           else 0)
                                                       (BITMAPHEIGHT BM)
                                                       VKBD.EDITOR-WINDOW-HEIGHT 20)))
          (SETQ WPOS (GETBOXPOSITION REGION-WIDTH REGION-HEIGHT NIL NIL NIL "Specify region for Keyboard Editor
                      window"))
          (SETQ WINDOW (VKBD.CREATE-KEYBOARD-DISPLAY KEYBOARD WPOS 'VKBD.EDIT.MAKE-CURRENT-KEY BM T))
          (WINDOWPROP WINDOW 'REPAINTFN 'VKBD.EDIT.KEYBOARD-REPAINTFN)
          (WINDOWPROP WINDOW 'ICONFN 'VKBD.EDIT.ICONFN)
          (SETQ LARGE-WINDOW (CREATEW (CREATEREGION 0 0 VKBD.EDITOR-WINDOW-WIDTH VKBD.EDITOR-WINDOW-HEIGHT)
                                      (CONCAT "Edit of Keyboard : " (fetch (VIRTUALKEYBOARD KEYBOARDNAME)
                                                                        of KEYBOARD)
                                              " for "
                                              (fetch (VIRTUALKEYBOARD KEYBOARDCONFIGURATION) of KEYBOARD))
                                      NIL T))
```

```
                    (WINDOWPROP LARGE-WINDOW 'CLOSEFN 'VKBD.EDIT.STOP-COMMAND)
                    (ATTACHWINDOW LARGE-WINDOW WINDOW 'TOP 'CENTER)
                    (if VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS
                        then (ATTACHMENU NON-CHAR-MENU LARGE-WINDOW 'TOP 'JUSTIFY))
                    (OPENW LARGE-WINDOW)
                    (WINDOWPROP LARGE-WINDOW 'RESHAPEFN 'DON'T)
                    (ATTACHMENU COMMAND-MENU LARGE-WINDOW 'TOP 'JUSTIFY)
                    (WINDOWPROP WINDOW 'VKBD.CHAR-SET-MENU (VKBD.EDIT.CREATE-CHARACTER-SETS-MENU))
                    (VKBD.EDIT.LARGE-WINDOW-REPAINTFN LARGE-WINDOW)
                    (VKBD.EDIT.SWITCH-CHARACTER-SET 0 LARGE-WINDOW)
                    (WINDOWADDPROP LARGE-WINDOW 'REPAINTFN 'VKBD.EDIT.LARGE-WINDOW-REPAINTFN)
                    (RETURN WINDOW])
```

(**VKBD.EDIT.DEFINE-COMMAND**
```
  [LAMBDA (WINDOW)                                          (* sm " 5-Aug-85 09:26")
    (DEFINEKEYBOARD (WINDOWPROP WINDOW 'VKBD.KEYBOARD))
    (PRINTOUT PROMPTWINDOW "Keyboard " (fetch (VIRTUALKEYBOARD KEYBOARDNAME) of (WINDOWPROP WINDOW
                                                                          'VKBD.KEYBOARD))
           " was added to the set of known keyboards."])
```

(**VKBD.EDIT.DO-MENU-COMMAND**
```
  [LAMBDA (ITEM MENU KEY)                                   (* sm " 1-Aug-85 17:34")
    (APPLY* (CADR ITEM)
            (MAINWINDOW (WFROMMENU MENU)
                 T])
```

(**VKBD.EDIT.ICONFN**
```
  [LAMBDA (WINDOW ICON)                                     (* sm "15-Aug-85 11:10")
    [COND
        ((NULL ICON)
         (SETQ ICON (TITLEDICONW (create TITLEDICON
                                    ICON _ VKBD.EDIT.ICON
                                    MASK _ VKBD.EDIT.MASK
                                    TITLEREG _ (CREATEREGION 5 25 80 65))
                        [CONCAT "EDIT KEYBOARD: " (fetch (VIRTUALKEYBOARD KEYBOARDNAME)
                                                       of (WINDOWPROP WINDOW 'VKBD.KEYBOARD]
                                  (FONTCREATE 'GACHA 8]
    ICON])
```

(**VKBD.EDIT.INVERT-IF-LOCKED**
```
  [LAMBDA (KEY WINDOW)                                      (* sm "13-Aug-85 10:01")
    (PROG (KEY-ASSIGNMENT)
          (SETQ KEY-ASSIGNMENT (VKBD.FETCH-KEY-ASSIGNMENT KEY WINDOW))
          (if (AND (VKBD.CHAR-ASSIGNMENTP KEY-ASSIGNMENT)
                   (EQ (VKBD.LOCK/NOLOCK KEY-ASSIGNMENT)
                       'LOCKSHIFT))
              then (VKBD.INVERT-LOCK-KEYS WINDOW])
```

(**VKBD.EDIT.KEYBOARD-REPAINTFN**
```
  [LAMBDA (W)                                               (* sm " 5-Aug-85 16:12")
    (PROG (CURRENT-KEY)
          (VKBD.KEYBOARD-WINDOW-REPAINTFN W)
          (if (SETQ CURRENT-KEY (WINDOWPROP W 'VKBD.CURRENT-KEY))
              then (VKBD.FRAME-KEY (CAR CURRENT-KEY)
                            W BLACKSHADE 2)
                   (if (CADR CURRENT-KEY)
                       then (VKBD.INVERT-SHIFT-KEYS W))
                   (VKBD.EDIT.INVERT-IF-LOCKED (CAR CURRENT-KEY)
                        W])
```

(**VKBD.EDIT.LARGE-WINDOW-REPAINTFN**
```
  [LAMBDA (W)                                               (* sm "13-Aug-85 12:43")
    (for I from 0 to 20 as Y from 390 by -25 do (MOVETO 10 Y W)
                                                 (PRIN1 (OCTALSTRING I)
                                                        W))
    (for I from 0 by 16 to 255 as X from 40 by 29 do (MOVETO X 420 W)
                                                      (PRIN1 (OCTALSTRING I)
                                                             W])
```

(**VKBD.EDIT.MAKE-CURRENT-KEY**
```
  [LAMBDA (KEY WINDOW MOUSEKEY)                             (* sm " 7-Aug-85 17:51")
    (PROG (CURRENT-KEY SHIFTED CURRENT-KEY-ASSIGNMENT CURRENT-KEY-INFO LOCKED)
          (SETQ SHIFTED (WINDOWPROP WINDOW 'VKBD.SHIFT-DOWN))
          (SETQ CURRENT-KEY-INFO (WINDOWPROP WINDOW 'VKBD.CURRENT-KEY))
          (if (VKBD.LOCK-KEYP KEY WINDOW)
              then (if (CADR CURRENT-KEY-INFO)
                       then (SETQ CURRENT-KEY-ASSIGNMENT (VKBD.FETCH-KEY-ASSIGNMENT (CAR CURRENT-KEY-INFO)
                                                              WINDOW))
                            (SETQ LOCKED (EQ (VKBD.LOCK/NOLOCK CURRENT-KEY-ASSIGNMENT)
                                             'LOCKSHIFT))
```

```
                              (RPLACA (CDDADR CURRENT-KEY-ASSIGNMENT)
                                      (if LOCKED
                                          then 'NOLOCKSHIFT
                                          else 'LOCKSHIFT))
                              (VKBD.INVERT-LOCK-KEYS WINDOW))
               elseif (VKBD.ASSIGNABLE-KEYP KEY WINDOW)
                 then (if CURRENT-KEY-INFO
                          then (VKBD.ERASE-FRAME (CAR CURRENT-KEY-INFO)
                                       WINDOW 2)
                               (if (CADR CURRENT-KEY-INFO)
                                   then (VKBD.INVERT-SHIFT-KEYS WINDOW)
                                        (VKBD.EDIT.INVERT-IF-LOCKED (CAR CURRENT-KEY-INFO)
                                                 WINDOW)))
                      (VKBD.FRAME-KEY KEY WINDOW BLACKSHADE 2)
                      (if SHIFTED
                          then (VKBD.INVERT-SHIFT-KEYS WINDOW)
                               (VKBD.EDIT.INVERT-IF-LOCKED KEY WINDOW))
                      (WINDOWPROP WINDOW 'VKBD.CURRENT-KEY (LIST KEY SHIFTED])
```

(**VKBD.EDIT.QUIT-COMMAND**
```
  [LAMBDA (WINDOW)                                          (* sm " 2-Aug-85 15:12")
    [REPLACE KEYASSIGNMENTS OF (WINDOWPROP WINDOW 'VKBD.ORIGINAL-KEYBOARD) WITH (FETCH KEYASSIGNMENTS
                                                                                      OF (WINDOWPROP WINDOW
                                                                                               'VKBD.KEYBOARD]
    (NOTIFY.EVENT (WINDOWPROP WINDOW 'VKBD.EDITOR-RETURN-EVENT])
```

(**VKBD.EDIT.STOP-COMMAND**
```
  [LAMBDA (WINDOW)                                          (* sm " 2-Aug-85 13:04")
    (NOTIFY.EVENT (WINDOWPROP (MAINWINDOW WINDOW T)
                        'VKBD.EDITOR-RETURN-EVENT])
```

(**VKBD.EDIT.SWITCH-CHAR-SET-COMMAND**
```
  [LAMBDA (MAIN-WINDOW)                                     (* sm " 5-Aug-85 09:28")
    (PROG (LARGE-WINDOW NEW-NUMBER)
          (SETQ LARGE-WINDOW (CAR (ATTACHEDWINDOWS MAIN-WINDOW)))
          [SETQ NEW-NUMBER (MENU (WINDOWPROP MAIN-WINDOW 'VKBD.CHAR-SET-MENU)
                                 (create POSITION
                                         XCOORD _ [IPLUS 34 (fetch (REGION LEFT) of (WINDOWPROP LARGE-WINDOW
                                                                                         'REGION]
                                         YCOORD _ (IPLUS 9 (fetch (REGION BOTTOM) of (WINDOWPROP LARGE-WINDOW
                                                                                          'REGION]
          (if NEW-NUMBER
              then (VKBD.EDIT.SWITCH-CHARACTER-SET NEW-NUMBER LARGE-WINDOW])
```

(**VKBD.EDIT.SWITCH-CHARACTER-SET**
```
  [LAMBDA (SET-NUMBER WINDOW)                               (* sm " 6-Aug-85 14:08")
    (PROG (MENU OLDCURSOR FONT)
          (if (WINDOWPROP WINDOW 'MENU)
              then (DELETEMENU (CAR (WINDOWPROP WINDOW 'MENU))
                          NIL WINDOW))
          (WINDOWPROP WINDOW 'TITLE (CONCAT "Character set " (OCTALSTRING SET-NUMBER)))
          [SETQ FONT (FONTCREATE (fetch (KEYBOARDCONFIGURATION KEYBOARDDISPLAYFONT) of (VKBD.GET-CONFIGURATION
                                                                                          (MAINWINDOW WINDOW]
          (ADDMENU (VKBD.EDIT.CREATE-CHARACTERS-MENU SET-NUMBER FONT)
                  WINDOW
                  (create POSITION
                         XCOORD _ 30
                         YCOORD _ 5])
```

(**VKBD.EDIT.ROTATED-NUMBER**
```
  [LAMBDA (NUM ROW-NUM COL-NUM)                             (* edited%: " 3-Jun-85 12:47")
    (IPLUS (ITIMES (IMOD (SUB1 NUM)
                         COL-NUM)
                   ROW-NUM)
           (ADD1 (IQUOTIENT (SUB1 NUM)
                            COL-NUM])
```

```
)
```

```
(RPAQ? VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS T)
```

```
(RPAQ? VKBD.EDIT.MAX-NUMBER-OF-CASHED-MENUS 15)
```

```
(RPAQ? VKBD.EDITOR-WINDOW-HEIGHT 450)
```

```
(RPAQ? VKBD.EDITOR-WINDOW-WIDTH 512)
```

```
(RPAQ? VKBD.EDIT.DISPLAY-CHAR-SETS-NAMES T)
```

```
(RPAQQ VKBD.EDIT.BACKGROUND-MENU-SUBITEMS
       (SUBITEMS ("New Keyboard, default initial" '(ADD.PROCESS '(VKBD.EDIT-KEYBOARD-COMMAND T))
                          "Calls the keyboard editor. Will prompt for name for the new keyboard, and will use the
```

```
                              default keyboard as the initial keyboard")
              ("New keyboard, other initial" '(ADD.PROCESS '(VKBD.EDIT-KEYBOARD-COMMAND T T))
                      "Calls the keyboard editor. Will prompt for name for the new keyboard, and will pop up a
                      menu of the current known keyboards. The selected one will be used as the initial
                      keyboard")
              ("Existing keyboard" '(ADD.PROCESS '(VKBD.EDIT-KEYBOARD-COMMAND))
                      "Will let you select a keyboard from list of the known keyboards, and will calls the
                      keyboard editor on the selected keyboard.")))
```

(RPAQQ **VKBD.EDIT.CASH-MENUES** NIL)

(RPAQQ **VKBD.EDIT.CHAR-SET-NAMES**
```
       (("ASCII/ISO/CCITT Roman Alphabet and Punctuation" 0)
        ("JIS Symbols 1 – Punctuation and Symbols not in Char set 0" 33)
        ("JIS Symbols 2 – Punctuation and Symbols not in Char set 0" 34)
        ("Extended Latin" 35)
        ("JIS Hiragana" 36)
        ("JIS Katakana" 37)
        ("Greek" 38)
        ("Cyrillic" 39)
        ("Symbols 3 – Miscellaneous Japanese Symbols" 116)
        ("General and Technical Symbols 2" 238)
        ("General and Technical Symbols 1" 239)
        ("Ligatures, Graphical Entities, and Field Format Symbols" 240)
        ("Accented Characters" 241)))
```

(RPAQQ **VKBD.EDIT.MENU-ITEMS** (("CharSet" VKBD.EDIT.SWITCH-CHAR-SET-COMMAND "Pops up a menu of all possible
```
                              character set number. Selecting one will switch the displayed character
                              set.")
              ("Stop" VKBD.EDIT.STOP-COMMAND "Exit from the keyboard editor. Returns the new
                              keyboard, but does not modify the original one.")
              ("Quit" VKBD.EDIT.QUIT-COMMAND "Exit from the keyboard editor. Modifies the
                              roriginal keyboard and returns it .")
              ("Define" VKBD.EDIT.DEFINE-COMMAND "Adds the edited keyboard in its current state
                              to the set of known keyboards.")))
```

(RPAQQ **VKBD.EDIT.NON-CHAR-ASSIGNMENTS** (SHIFT CTRL META LOCK LOCKDOWN LOCKUP EVENT))

(RPAQQ **VKBD.EDIT.ICON**

)

(RPAQQ **VKBD.EDIT.MASK**

)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS VKBD.EDIT.ALLOW-NON-CHAR-ASSIGNMENTS VKBD.EDIT.BACKGROUND-MENU-SUBITEMS
```
       VKBD.EDIT.MAX-NUMBER-OF-CASHED-MENUS VKBD.EDITOR-WINDOW-HEIGHT VKBD.EDITOR-WINDOW-WIDTH
       VKBD.EDIT.DISPLAY-CHAR-SETS-NAMES VKBD.EDIT.CASH-MENUES VKBD.EDIT.CHAR-SET-NAMES VKBD.EDIT.MENU-ITEMS
       VKBD.EDIT.NON-CHAR-ASSIGNMENTS VKBD.CONF.ICON VKBD.EDIT.ICON VKBD.EDIT.MASK)
```
)

(**VKBD.EDIT.ADD-SUBITEM-TO-BACKGROUND-MENU** (LIST "Edit" '(ADD.PROCESS '(**VKBD.EDIT-KEYBOARD-COMMAND** T))
```
                                        "Calls the keyboard editor. Will prompt for name for the new
                                        keyboard, and will use the default keyboard as the initial
                                        keyboard" VKBD.EDIT.BACKGROUND-MENU-SUBITEMS)
```
        "Keyboard")

FUNCTION INDEX

VARIABLE INDEX