

File created: 6-Nov-91 16:12:40 {DSK}<python>RELEASE>loops>2.0>patches>LMPATCH.;2

changes to: (FUNCTIONS |SubclassResponsibility|)

previous date: 6-Nov-91 15:53:14 {DSK}<python>RELEASE>loops>2.0>patches>LMPATCH.;1

Read Table: XCL

Package: INTERLISP

Format: XCCS

; Copyright (c) 1991 by Venue. All rights reserved.

(RPAQQ LMPATCHCOMS
(

;;; Patches courtesy of Tom Lipkis @ Savoir

;; This one makes STREQUAL run MUCH faster in LOOPS; it checks for equality from the END of strings first.

(COMS (FNS |FastSTREQUAL|)
(DECLARE\ : DONTVAL@LOAD DOCOPY (P (MOVD? 'STREQUAL 'OLDSTREQUAL)
(MOVD ' |FastSTREQUAL| 'STREQUAL))))

;; These use COMPILER-LET instead of MACROLET to handle the LOOPS method inheritance macros; it conses a LOT less as a result

(FUNCTIONS LOOPS-FUNCALL |Method| |_Super| |_Super?| |_SuperFringe| |SubclassResponsibility|)

;; These improve copying performance; CopyDeepDescr is iterative instead of straight recursive, CopyInstance used to force UID creation
;; which was making LoopsWindow active values stay around even after their Window was collected

(FNS |CopyDeepDescr| |CopyInstance|)

;; Improves performance dumping instance files

(METHODS |Object.SaveInstance?|))

;;; Patches courtesy of Tom Lipkis @ Savoir

;; This one makes STREQUAL run MUCH faster in LOOPS; it checks for equality from the END of strings first.

(DEFINEQ

(|FastSTREQUAL|

; Edited 10-Jun-88 16:16 by TAL

(LAMBDA (X Y)
(DECLARE (LOCALVARS . T))
(AND (STRINGP X)
(STRINGP Y)
(PROG ((LEN (|ffetch| (STRINGP LENGTH) |of| X)))
(COND
((NEQ LEN (|ffetch| (STRINGP LENGTH) |of| Y))
(RETURN)))
(RETURN (PROG ((BASEX (|ffetch| (STRINGP BASE) |of| X))
(BNX (|ffetch| (STRINGP OFFST) |of| X))
(FATPX (|ffetch| (STRINGP FATSTRINGP) |of| X))
(BASEY (|ffetch| (STRINGP BASE) |of| Y))
(BNY (|ffetch| (STRINGP OFFST) |of| Y))
(FATPY (|ffetch| (STRINGP FATSTRINGP) |of| Y)))
(COND
((OR (NEQ 0 BNX)
(NEQ 0 BNY)
FATPX FATPY)
(GO SLOWLP))))
LP (COND
((EQ 0 LEN)
(RETURN T)))
(|add| LEN -1)
(COND
((NEQ (\\GETBASEBYTE BASEX LEN)
(\\GETBASEBYTE BASEY LEN))
(RETURN)))
(GO LP)
SLOWLP
(COND
((EQ 0 LEN)
(RETURN T))
((NEQ (\\GETBASECHAR FATPX BASEX BNX)
(\\GETBASECHAR FATPY BASEY BNY))
(RETURN)))
(T (|add| BNX 1)
(|add| BNY 1)
(|add| LEN -1)
(GO SLOWLP))))))

)

(DECLARE\ : DONTVAL@LOAD DOCOPY

(MOVD? 'STREQUAL 'OLDSTREQUAL)

```
(MOVD ' |FastSTREQUAL| ' STREQUAL)
)
```

;; These use COMPILER-LET instead of MACROLET to handle the LOOPS method inheritance macros; it conses a LOT less as a result

```
(DEFMACRO LOOPS-FUNCALL (FN &REST ARGS)
```

;; The optimizer for this doesn't make sure FN is evaluated first, but that's ok for loops and save a GENSYM and binding

```
' (APPLY* ,FN ,@ARGS))
```

```
(DEFDEFINER (|Method| (:NAME (CL:LAMBDA (|method-body|)
                                   (CL:MULTIPLE-VALUE-BIND (|class-name| |selector|)
                                                             (PARSE-METHOD-BODY |method-body|)
                                                             (|MethName| |class-name| |selector|))))))
  METHOD-FNS (&WHOLE |method-body|)
  (CL:MULTIPLE-VALUE-BIND (|class-name| |selector| |args| |declarations| |forms| |doc| |qualifiers|
                          |method-type|)
    (PARSE-METHOD-BODY |method-body|)
    (CL:ASSERT (|class?| ($! |class-name|)))
    (LET (|function-name| |function-type| |body|)
      ;; Compute the name of the function
      (SETQ |function-name| (|MethName| |class-name| |selector|))
      ;; Compute the type of the function
      (SETQ |function-type| (OR (LISTGET |qualifiers| :FUNCTION-TYPE)
                                :IL))
      (CL:CHECK-TYPE |function-type| (CL:MEMBER :CL :IL))
      ;; Get the body of the function, with the top level comments removed
      (SETQ |body| '(CL:COMPILER-LET ((|*ArgsOfMethodBeingCompiled*| ' ,|args|)
                                       (|*ClassNameOfMethodOwner*| ' ,|class-name|)
                                       (|*SelectorOfMethodBeingCompiled*| ' ,|selector|)
                                       (|*SelfOfMethodBeingCompiled*| ' , (CAR |args|)))
                        ,. |forms|)))
      ;; Build the function definition form
      '(PROGN , (CL:ECASE |function-type|
                      (:CL '(CL:DEFUN ,|function-name| ,|args|
                                ,@|declarations| ,|body|))
                      (:IL '(DEFINEQ (,|function-name| (LAMBDA ,|args|
                                                                ,@|declarations|
                                                                ,|body|))))))
        (INSTALL-METHOD-FN ' ,|class-name| ' ,|selector| ' ,|function-name| ' , (CDR |args|)
                              ' ,|doc|)
        ' ,|function-name|))))
```

```
(DEFMACRO | Super| (&REST |Send-Super-Args|)
  (DECLARE (CL:SPECIAL |*ArgsOfMethodBeingCompiled*| |*ClassNameOfMethodOwner*|
            |*SelectorOfMethodBeingCompiled*| |*SelfOfMethodBeingCompiled*|))
  (COND
    ((NULL |Send-Super-Args|)
     ; Args default to args of the method
     '(LOOPS-FUNCALL (|FindSuperMethod| ,|*SelfOfMethodBeingCompiled*| ' ,|*SelectorOfMethodBeingCompiled*|
                      (LOADTIMECONSTANT (|OldClass| ,|*ClassNameOfMethodOwner*|)))
      ,. |*ArgsOfMethodBeingCompiled*|))
    ((NEQ |*SelectorOfMethodBeingCompiled*| (CADR |Send-Super-Args|))
     ; Selectors must match
     (ERROR "Selector to _Super does not match method selector" (CADR |Send-Super-Args|)))
    ((NEQ |*SelfOfMethodBeingCompiled*| (CAR |Send-Super-Args|))
     ; Self must match
     (ERROR "Can't _Super to other than first arg of method" (CDR |Send-Super-Args|)))
    (T
     ; Args differ
     (APPEND '(LOOPS-FUNCALL (|FindSuperMethod| ,|*SelfOfMethodBeingCompiled*| '
                               (LOADTIMECONSTANT (|OldClass| ,|*ClassNameOfMethodOwner*|)))
              ,|*SelfOfMethodBeingCompiled*|)
              (CDDR |Send-Super-Args|))))
```

```
(DEFMACRO | Super?| (&REST |Send-Super-Args|)
  (DECLARE (CL:SPECIAL |*ArgsOfMethodBeingCompiled*| |*ClassNameOfMethodOwner*|
            |*SelectorOfMethodBeingCompiled*| |*SelfOfMethodBeingCompiled*|))
  (COND
    ((NULL |Send-Super-Args|)
     ; Args default to args of the method
     '(LOOPS-FUNCALL (|FindSuperMethod| ,|*SelfOfMethodBeingCompiled*| ' ,|*SelectorOfMethodBeingCompiled*|
                      (LOADTIMECONSTANT (|OldClass| ,|*ClassNameOfMethodOwner*|)))
      (FUNCTION NIL)
      ,. |*ArgsOfMethodBeingCompiled*|))
    ((NEQ |*SelectorOfMethodBeingCompiled*| (CADR |Send-Super-Args|))
     ; Selectors must match
     (ERROR "Selector to _Super does not match method selector" (CADR |Send-Super-Args|)))
    ((NEQ |*SelfOfMethodBeingCompiled*| (CAR |Send-Super-Args|))
     ; Self must match
     (ERROR "Can't _Super to other than first arg of method" (CDR |Send-Super-Args|)))
    (T
     ; Args differ
     (APPEND '(LOOPS-FUNCALL (|FindSuperMethod| ,|*SelfOfMethodBeingCompiled*| '
                               (LOADTIMECONSTANT (|OldClass| ,|*ClassNameOfMethodOwner*|)))
              ,|*SelfOfMethodBeingCompiled*|)
              (CDDR |Send-Super-Args|))))
```

```

(ERROR "Can't _Super? to other than first arg of method" (CDR |Send-Super-Args|)))
(T ; Args differ
  (APPEND `(LOOPS-FUNCALL (|FindSuperMethod| ,|*SelfOfMethodBeingCompiled*| '
                        |*SelectorOfMethodBeingCompiled*|
                        (LOADTIMECONSTANT (|OldClass| ,|*ClassNameOfMethodOwner*|))
                        (FUNCTION NIL))
            ,|*SelfOfMethodBeingCompiled*|)
    (CDDR |Send-Super-Args|))))

(DEFMACRO |SuperFringe| (&REST |Send-Super-Args|)
  (DECLARE (CL:SPECIAL |*ArgsOfMethodBeingCompiled*| |*ClassNameOfMethodOwner*|
            |*SelectorOfMethodBeingCompiled*| |*SelfOfMethodBeingCompiled*|))
  (COND
    ((NULL |Send-Super-Args|) ; Args default to args of the method
     `(|for| |cls| |in| (|fetch| |localSupers| |of| (LOADTIMECONSTANT (|OldClass| ,|*ClassNameOfMethodOwner*|)))
       |do| (LOOPS-FUNCALL (OR (|FetchMethod| |cls| ' ,|*SelectorOfMethodBeingCompiled*|)
                              (FUNCTION NIL))
                           ,. |*ArgsOfMethodBeingCompiled*|)))
    ((NEQ |*SelectorOfMethodBeingCompiled*| (CADR |Send-Super-Args|))
     ; Selectors must match
     (ERROR "Selector to _Super does not match method selector" (CADR |Send-Super-Args|)))
    ((NEQ |*SelfOfMethodBeingCompiled*| (CAR |Send-Super-Args|))
     ; Self must match
     (ERROR "Can't _SuperFringe to other than first arg of method" (CDR |Send-Super-Args|)))
    (T `(|for| |cls| |in| (|fetch| |localSupers| |of| (LOADTIMECONSTANT (|OldClass| ,|*ClassNameOfMethodOwner*|)))
        |bind| (|argList| _ (MAPCAR ' (, (CAR |Send-Super-Args|)
                                     ,. (CDDR |Send-Super-Args|))
                                   (FUNCTION EVAL)))
        |do| (APPLY (OR (|FetchMethod| |cls| ' ,|*SelectorOfMethodBeingCompiled*|)
                       (FUNCTION NIL))
                   |argList|))))))

(DEFMACRO |SubclassResponsibility| ()
  (DECLARE (CL:SPECIAL |*ArgsOfMethodBeingCompiled*| |*ClassNameOfMethodOwner*|
            |*SelectorOfMethodBeingCompiled*| |*SelfOfMethodBeingCompiled*|))
  `(HELPCHECK (CONCAT "Method " ,|*SelectorOfMethodBeingCompiled*| " of class " ,|*ClassNameOfMethodOwner*|
                     " needs to be defined in class "
                     (_ ,|*SelfOfMethodBeingCompiled*| |ClassName|)))

```

;; These improve copying performance; CopyDeepDescr is iterative instead of straight recursive, CopyInstance used to force UID creation which was
 ;; making LoopsWindow active values stay around even after their Window was collected

(DEFINEQ

```

(|CopyDeepDescr|
  (LAMBDA (|descr| |newObjAlist|) ; Edited 14-Jun-88 12:52 by TAL
    (DECLARE (LOCALVARS . T))
    ;; Copies instances active values and lists, but bottoms out on anything else
    (SELECTQ (TYPENAME |descr|)
      (|instance| (OR (CDR (FASSOC |descr| |newObjAlist|))
                     (_ |descr| |CopyDeep| |newObjAlist|)))
      (|annotatedValue|
       (|create| |annotatedValue|
        |annotatedValue| _ (|CopyDeepDescr| (|fetch| |annotatedValue| |of| |descr|)
                                             |newObjAlist|)))
      (LISTP (|bind| \t2 |val| |for| |valTail| |on| |descr|
                  |do| (COND
                       (\t2 (FRPLACD \t2 (SETQ \t2 (LIST (|CopyDeepDescr| (CAR |valTail|)
                                                                           |newObjAlist|))))
                       (T (SETQ |val| (SETQ \t2 (LIST (|CopyDeepDescr| (CAR |valTail|)
                                                                           |newObjAlist|))))))
                       (COND
                        ((AND (CDR |valTail|)
                             (NLISTP (CDR |valTail|)))
                         (FRPLACD \t2 (|CopyDeepDescr| (CDR |valTail|)
                                                         |newObjAlist|)))
                        (T (yield| |val|)))
                       (T (yield| |val|)))
      |descr|)))

```

```

(|CopyInstance|
  (LAMBDA (|oldInstance|) ; Edited 16-Sep-88 17:26 by TAL

```

;; make a new instance with the same contents as self, or copy into an instance if given

```

(LET ((|newInstance| (_ (|Class| |oldInstance|)
                       |CreateInstance|)))

```

;; Creating UID for copy loses big. E.g., AVs as default IV value in class generally have UID. When IV is first accessed, AV is copied and
 ;; stored in instance. If copy has UID it will never go away, and in the case of LispWindowAV this causes the window, bitmap, stream, etc. to
 ;; stay around also.

```

#(|(COND ((AND (fetch OBJUID of oldInstance) (NULL (fetch OBJUID of newInstance))) (* ; "Old one not temporary, but new one has non OBJUID yet")
  (UID newInstance)))#

```

```
;; Copy IVSource down one layer of list structure.
```

```
(|FillIVs| |newInstance| (|Class| |oldInstance|)
  (MAPCAR (|IVSource| |oldInstance|)
    (FUNCTION APPEND)))
|newInstance|))
```

```
)
```

```
;; Improves performance dumping instance files
```

```
(|\\BatchMethodDefs|)
```

```
(METH |Object| |SaveInstance?| (|file| |outInstances|)
  "Save this instance if referred to by another unless it is already on this list to be saved"
  (|category| (|Object|)))
```

```
(|Method| ((|Object| |SaveInstance?|) |self| |file| |outInstances|)
```

```
; edited: 26-Oct-84 15:36
```

```
"Save this instance if referred to by another unless it is already on this list to be saved"
```

```
(COND
  ((|type?| |instance| |self|)
   (NOT (FMEMB |self| |outInstances|)))
  (T (NOT (MEMBER |self| |outInstances|)))))
```

```
(|\\UnbatchMethodDefs|)
```

```
(PUTPROPS LMPATCH COPYRIGHT ("Venue" 1991))
```

FUNCTION INDEX

CopyDeepDescr3	CopyInstance3	FastSTREQUAL1
---------------	--------	--------------	--------	--------------	--------

MACRO INDEX

LOOPS-FUNCALL2	_Super2	_SuperFringe3
SubclassResponsibility3	_Super?2		

DEFINER INDEX

Method2
--------	--------