

File created: 9-Jun-2021 19:40:59 {DSK}<Users>kaplan>Local>medley3.5>git-medley>sources>ABASIC.;2

changes to: (FNS NIL ZERO)

previous date: 16-May-90 11:43:16 {DSK}<Users>kaplan>Local>medley3.5>git-medley>sources>ABASIC.;1

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

::
:: Copyright (c) 1982-1987, 1990, 2021 by Venue & Xerox Corporation.

(RPAQQ **ABASICCOMS**

```
[ (FNS EVALQT \SystemERROR)
  (FNS NIL EQ TRUE ZERO CL:IDENTITY DUMMYDEF NOTIMP)
  (P (DUMMYDEF (WINDOWWORLD NIL)))
  (FNS EQUAL NEQ NULL NOT)
  (COMS ; Belong on ACODE except they would clobber 10-versions in
        ; ABC
        (FNS LAPRD DEFC CGETD))
  (FNS NCONC \NCONC2 SORT MERGE SORT1 FASSOC FLAST FLENGTH FMEMB FNTH LIST LIST* COUNT)
  (FNS CHANGENAME1 CHANGENAME1A)
  (FNS CDDR CDAR CADR CAAR CDDDR CDDAR CDADR CDAAR CADDR CADAR CAAAR CDDDDR CAAAAR CDDAR CDDADR
    CDDAAR CDAAR CADADR CDADDR CDADAR CAADDR CDAADR CAADAR CADDR CADAAR CADDR CAAADR)
  (FNS SYSTEMTYPE)
  (COMS ; Because can't have bignums in code at makeinit time
        (VARS (\IMAX.FLOAT (FIX MAX.FLOAT))
              (\IMIN.FLOAT (FIX MIN.FLOAT)))
        (GLOBALVARS \IMAX.FLOAT \IMIN.FLOAT))
  (DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVARS
    (ADDVARS (NLAMA DUMMYDEF)
              (NLAML)
              (LAMA LIST* LIST NCONC NOTIMP ZERO NIL]))
```

(DEFINEQ

EVALQT

```
[LAMBDA NIL ; (* Imm "11-MAR-80 15:57")
  (PROG (EVALQTX)
    EVALQTL
    (PRIN1 ' _ T)
    (PRINT [COND
      ((NULL (SETQ EVALQTX (READ T)))
       (GO EVALQTL))
      ((OR (LISTP EVALQTX)
            (NULL (READ T)))
       (EVAL EVALQTX))
      (T (APPLY EVALQTX (READ T)
                  T)
        (GO EVALQTL))])
```

(**SystemERROR**

```
[LAMBDA NIL ; (* Imm "6-MAY-80 20:41")
  (SELECTQ (GETTOPVAL '\SystemErrorVAL)
    (0 (RAID))
    (1 (LISPERROR "FILE SYSTEM RESOURCES EXCEEDED"))
    (RAID))
```

)

(DEFINEQ

NIL

```
[LAMBDA NIL ; Edited 9-Jun-2021 19:40 by rmk:
  NIL])
```

(**EQ**

```
[LAMBDA (X) ; (* Imm%: 26 JUN 75 726)
  X])
```

(**TRUE**

```
[LAMBDA NOBIND ; (* Imm "4-OCT-83 03:05")
  T])
```

(**ZERO**

```
[LAMBDA NIL ; Edited 9-Jun-2021 19:40 by rmk:
  0])
```

(* bvm%: " 3-Nov-86 22:37")

(* Imm " 4-OCT-83 03:08")

(* Imm " 5-MAR-80 20:17")

```
(* bvm%: " 7-Jul-86 22:41")
; tortured logic to optimize performance
```

; can't be EQUAL and not EQ

- ; If comparing against bignum, avoid floating overflow when coercing a too-large bignum to floatp

; both small, not EQ

: BIGNUM \FLOATP

```
(NOT (GREATERP X \IMAX.FLOAT))
(NOT (LESSP X \IMIN.FLOAT))
```

```

                                (FEQP X Y)))
                                (\SMALLP
                                NIL)
                                (\FIXP
                                NIL)
                                (PROGN
                                (EQ (\BIGNUM.COMPARE X Y)
                                0])
                                (NUMBERP Y)
                                NIL)
                                ((STRINGP X)
                                (STREQUAL X Y))
                                (T (\EXTENDED.EQP X Y]))

```

```

; BIGNUM \SMALLP
; BIGNUM \FIXP
; BIGNUM BIGNUM

```

```

(NEQ
 [LAMBDA (X Y)
  (NOT (EQ X Y))]

```

```

(NULL
 [LAMBDA (X)
  (EQ X NIL)]

```

```

(NOT
 [LAMBDA (X)
  (EQ X NIL)]

```

```

)

```

:: Belong on ACODE except they would clobber 10-versions in ABC

```

(DEFINEQ

```

```

(LAPRD
 [LAMBDA (FN)
  (PROG (X Y)
    (RETURN (COND
              ((OR (NEQ (PEEKC)
                          '% )
                  [NOT (LITATOM (SETQ X (SETQ Y (READ)
                                (NOT (LISTP (SETQ X (GETP X 'CODEREADER]
                                (ERROR ' "Bad compiled function" FN))
                                (T (APPLY* (CAR X)
                                              FN]))

```

```

(* wsh%: "20-JUL-79 12:27")

```

```

(DEFC

```

```

[LAMBDA (NM DF)
  ;; Put in a new definition (DF) for the name NM.
  (PROG ((PROP 'CODE))
    (COND
      ((OR (NULL DFNFLG)
          (EQ DFNFLG T))
       ;; OK to redefine it.
       [COND
        ((GETD NM)
         (VIRGINFN NM T)
         (COND
          ((NULL DFNFLG)
           (PRINT (CONCAT NM " redefined")
                   T T)
           (SAVEDEF NM]
        (PUTD NM DF T)

      )
      (T ;; DFNFLG is PROP, so save the definition.
       (PUTPROP NM PROP DF)

    ))
  (RETURN DF))

```

```

; Edited 10-Nov-87 13:01 by jds

```

```

; NOTE: this call to PRINT is changed to LISPXPRINT later in
; the loadup.

```

```

; NOTE: this call to PUTD is changed to /PUTD later in the
; loadup.

```

```

; NOTE: this call to PUTPROP is changed to /PUTPROP later in
; the loadup.

```

```

(CGGETD
 [LAMBDA (X)
  (COND
    ((LITATOM X)
     (GETD X))
    (T X])

```

)

(DEFINEQ

(NCONC

```

[LAMBDA N
  (AND (NEQ N 0)
    (PROG ((L (ARG N N))
      (J N)
      X)
      LP (COND
        ((EQ (SETQ J (SUB1 J))
          0)
        (RETURN L))
        ((LISTP (SETQ X (ARG N J)))
        (FRPLACD (LAST X)
          L)
        (SETQ L X)))
      (GO LP]))

```

(\NCONC2

```

[LAMBDA (X Y)
  (COND
    ((LISTP X)
    (RPLACD (LAST X)
      Y)
    X)
    (T Y]))

```

(* Imm "15-APR-82 22:10")

(SORT

```

[LAMBDA (DATA COMPAREFN)
  (DECLARE (LOCALVARS . T))
  (COND
    [(NLISTP DATA)
    (COND
      (DATA (ERROR ' "DATA NOT LIST:" DATA]
      (T (OR COMPAREFN (SETQ COMPAREFN (FUNCTION ALPHORDER)))
      (FRPLACD (LAST DATA)
        NIL)
      (SORT1 DATA NIL COMPAREFN))

```

(* Imm%: "11-NOV-76 23:48:23")

(MERGE

```

[LAMBDA (A B COMPAREFN)
  (PROG (ATAIL BTAIL)
    [COND
      ((NULL B)
      (RETURN A))
      ((NULL A)
      (RETURN B))
      ((NLISTP B)
      (ERRORX (LIST 4 B)))
      ((NLISTP A)
      (ERRORX (LIST 4 A)))
      ([NOT (SELECTQ COMPAREFN
        (T (ALPHORDER (CAAR A)
          (CAAR B)))
        (NIL (ALPHORDER (CAR A)
          (CAR B)))
        (APPLY* COMPAREFN (CAR A)
          (CAR B)

```

(* Imm "6-MAY-80 21:36")

; MERGE will work if either arg is NIL.

; No possible meaning here; user must be in error.

```

;; (CAR A) must be before (CAR B) at LOOP (see comment below). If not, swap A and B. --- The SELECTQ compares the next
;; things on A and B.

```

```

  (SETQ A (PROG1 B (SETQ B A)
  (SETQ ATAIL A)

```

```

;; It is desirable to make the value of the merged list available to the user not only as the return from MERGE, but also on both the CONSES
;; given as arguments. To this end, the MERGE is actually performed on the lists A and (CONS (CAR B) (CDR B)), so that when we return, the
;; original B may be smashed with (CAR A) and (CDR A).

```

```

  (SETQ BTAIL (CONS (CAR B)
    (CDR B)))

```

```

;; Whenever we pass LOOP, we know that ATAIL is LISTP, BTAIL is LISTP, and (CAR ATAIL) belongs before (CAR BTAIL). We therefore look to
;; see if there is anything more on ATAIL; if not, tie on BTAIL and return. Otherwise, compare (CADR ATAIL) to (CAR BTAIL). If ATAIL wins, just
;; take one CDR and go around. But if BTAIL wins, then we swap variable/structures: ATAIL is rplacd'd to the structure that was on BTAIL, and
;; BTAIL is bound to the old CDR of ATAIL. We then take the CDR and go around. Observe that this swapping preserves the assumptions made
;; at LOOP.

```

```

  LOOP
    [COND
      [(NLISTP (CDR ATAIL))
      (FRPLACD ATAIL BTAIL)
      (RETURN (FRPLACA (FRPLACD B (CDR A))
        (CAR A)
      [(SELECTQ COMPAREFN

```

```

(NIL (ALPHORDER (CADR ATAIL)
                (CAR BTAIL)))
(T (ALPHORDER (CAADR ATAIL)
              (CAAR BTAIL)))
(APPLY* COMPAREFN (CADR ATAIL)
              (CAR BTAIL)
(T (FRPLACD ATAIL (PROG1 BTAIL
                  (SETQ BTAIL (CDR ATAIL))))
(SETQ ATAIL (CDR ATAIL))
(GO LOOP])

```

(SORT1

```

[LAMBDA (DATA END COMPAREFN)
  (DECLARE (LOCALVARS . T))
  (COND

```

(* Imm%: "11-NOV-76 23:49:27")

```

    ((OR (EQ DATA END)
         (EQ (CDR DATA)
              END))

```

```

    DATA)
    (T (PROG ((L DATA)
              (A DATA)
              TM)

```

; Split DATA by setting A to one cell before its midpoint. DATA
; remains EQ to the original list.

```

    LP (COND
        ((AND (NEQ (SETQ L (CDR L))
                   END)
              (NEQ (SETQ L (CDR L))
                   END))
        (SETQ A (CDR A))
        (GO LP)))
    (SETQ TM (SORT1 DATA (CDR A)
                   COMPAREFN))
    (SORT1 (SETQ L (CDR A))
          END COMPAREFN)

```

;; Merge DATA thru A with L (= (CDR A)) up to END. This is a little tricky because DATA must remain EQ to its original value.

```

    ALP (COND
        ((EQ TM L)
         (RETURN DATA)))

```

; Exhausted first list.

```

    BLP (COND
        ((SELECTQ COMPAREFN
                  (T [ALPHORDER (COND
                                ((LISTP (CAR TM))
                                 (CAAR TM))
                                (T (CAR TM)))
                        (COND
                            ((LISTP (CAR L))
                             (CAAR L))
                            (T (CAR L))
                        (APPLY* COMPAREFN (CAR TM)
                                         (CAR L)))
                        (SETQ TM (CDR TM))
                        (GO ALP)))

```

;; Move first element of second list (L = (CDR A)) to before first element of first list (TM). This must be done by exchanging the CARs and
;; then patching up the CDRs, to retain the EQ property. This is a 'critical section' in that data will be lost if a hard interrupt occurs, but it
;; cannot be interrupted by ^H because it does no function calls.

;; NOT TRUE IN INTERLISP-D--THIS SECTION IS AN UNPROTECTED CRITICAL REGION.

```

    [COND
      [(EQ TM A)
       [FRPLACA TM (PROG1 (CAR L)
                          (FRPLACA L (CAR TM)))]
       (SETQ L (CDR (SETQ TM (SETQ A L)
                          (T [FRPLACD A (PROG1 (CDR L)
                                                (FRPLACA TM (PROG1 (CAR L)
                                                                    (FRPLNODE2 L TM)
                                                                    (FRPLACD TM L))))))
       (SETQ TM L)
       (SETQ L (CDR A)]
    (COND
      ((NEQ L END)
       (GO BLP)))
    (RETURN DATA])

```

; Special case.

; Exhausted second list.

(FASSOC

```

[LAMBDA (KEY ALST)
  (COND

```

(* Imm " 5-MAR-80 20:55")

```

    ((NULL ALST)
     NIL)
    ((EQ KEY (CAAR ALST))
     (CAR ALST))
    (T (FASSOC KEY (CDR ALST]))

```

(FLAST

```
[LAMBDA (X)
  (PROG ((Y X))
    (GO LP0)
    LP (SETQ X Y)
      (SETQ Y (CDR X))
    LP0 (COND
      (Y (GO LP)))
    (RETURN X])
```

(* Imm "5-MAR-80 20:57")

(FLENGTH

```
[LAMBDA (X)
  (PROG ((N 0)
    Y)
    (SETQ Y X)
    (GO LP0)
    LP (SETQ X Y)
      (SETQ N (ADD1 N))
      (SETQ Y (CDR X))
    LP0 (COND
      (Y (GO LP)))
    (RETURN N])
```

(* Imm%: "11-NOV-76 23:53:54")

(FMEMB

```
[LAMBDA (X Y)
  (PROG NIL
    LP (RETURN (COND
      ((NULL Y)
        NIL)
      ((EQ (CAR Y)
        X)
        Y)
      (T (SETQ Y (CDR Y))
        (GO LP]))
```

(* Imm "27-MAR-80 12:53")

(FNTH

```
[LAMBDA (X N)
  (COND
    ((IGREATERP 1 N)
      (CONS NIL X))
    (T (PROG ((X0 X))
      (DECLARE (LOCALVARS X0))
      LP (COND
        ((NULL X)
          (RETURN NIL))
        ((NOT (IGREATERP N 1))
          (RETURN X))
        (SETQ N (SUB1 N))
        (SETQ X (CDR X))
        (GO LP]))
```

(* Imm "6-MAY-80 22:29")

(LIST

```
[LAMBDA N
  (PROG ((J N)
    L)
    LP (COND
      ((EQ 0 J)
        (RETURN L)))
      (SETQ L (CONS (ARG N J)
        L))
      (SETQ J (SUB1 J))
      (GO LP])
```

(* JonL "24-Apr-84 14:49")

(LIST*

```
[LAMBDA NARGS
  (COND
    ((EQ 0 NARGS)
      NIL)
    ((EQ 1 NARGS)
      (ARG NARGS 1))
    (T (bind (VAL _ (ARG NARGS NARGS)) for I from (SUB1 NARGS) by -1 until (ILEQ I 0)
      do (push VAL (ARG NARGS I)) finally (RETURN VAL]))
```

(* JonL "27-Sep-84 21:19")

(COUNT

```
[LAMBDA (X)
  (PROG ((N 0))
    LP (COND
      ((NLISTP X)
        (RETURN N))
      (T (SETQ N (IPLUS (COUNT (CAR X))
        1 N))
        (SETQ X (CDR X))
```

(* Imm%: 24 JUN 75 32)

```
(GO LP])
```

```
)
```

```
(DEFINEQ
```

```
(CHANGENAME1
```

```
[LAMBDA (DEF X Y)
```

```
(* rmk%: "15-APR-80 17:29")
```

```
; This isn't on ACODE because it would smash the 10 version in
```

```
; ABC
```

```
(COND
```

```
((EXPRP DEF)
```

```
(NLSETQ (ESUBST Y X DEF)))
```

```
((CCODEP DEF)
```

```
[COND
```

```
((LITATOM DEF)
```

```
(SETQ DEF (GETD DEF]
```

```
(CHANGENAME1A DEF X Y (CHANGECCODE X X DEF])
```

```
(CHANGENAME1A
```

```
[LAMBDA (DEF OLD NEW MAP)
```

```
(* Imm "20-MAY-80 09:43")
```

```
(COND
```

```
((AND MAP (find X in (CDR MAP) suchthat (find Y in (CDR X) suchthat Y)))
```

```
(CHANGECCODE NEW MAP DEF)
```

```
(UNDOSAVE (LIST 'CHANGENAME1A DEF NEW OLD MAP))
```

```
T])
```

```
)
```

```
(DEFINEQ
```

```
(CDDR
```

```
[LAMBDA (X)
```

```
(CDR (CDR X])
```

```
(CDAR
```

```
[LAMBDA (X)
```

```
(CDR (CAR X])
```

```
(CADR
```

```
[LAMBDA (X)
```

```
(CAR (CDR X])
```

```
(CAAR
```

```
[LAMBDA (X)
```

```
(CAR (CAR X])
```

```
(CDDDR
```

```
[LAMBDA (X)
```

```
(CDR (CDDR X])
```

```
(CDDAR
```

```
[LAMBDA (X)
```

```
(CDR (CDAR X])
```

```
(CDADR
```

```
[LAMBDA (X)
```

```
(CDR (CADR X])
```

```
(CDAAR
```

```
[LAMBDA (X)
```

```
(CDR (CAAR X])
```

```
(CADDR
```

```
[LAMBDA (X)
```

```
(CAR (CDDR X])
```

```
(CADAR
```

```
[LAMBDA (X)
```

```
(CAR (CDAR X])
```

```
(CAADR
```

```
[LAMBDA (X)
```

```
(CAR (CADR X])
```

```
(CAAAR
  [LAMBDA (X)
    (CAR (CAAR X)])

(CDDDDR
  [LAMBDA (X)
    (CDDR (CDDR X)])

(CAAAAR
  [LAMBDA (X)
    (CAAR (CAAR X)])

(CDDDAR
  [LAMBDA (X)
    (CDDR (CDAR X)])

(CDDADR
  [LAMBDA (X)
    (CDDR (CADR X)])

(CDDAAR
  [LAMBDA (X)
    (CDDR (CAAR X)])

(CDAAAR
  [LAMBDA (X)
    (CDAR (CAAR X)])

(CADADR
  [LAMBDA (X)
    (CADR (CADR X)])

(CDADDR
  [LAMBDA (X)
    (CDAR (CDDR X)])

(CDADAR
  [LAMBDA (X)
    (CDAR (CDAR X)])

(CAADDR
  [LAMBDA (X)
    (CAAR (CDDR X)])

(CDAADR
  [LAMBDA (X)
    (CDAR (CADR X)])

(CAADAR
  [LAMBDA (X)
    (CAAR (CDAR X)])

(CADDDR
  [LAMBDA (X)
    (CADR (CDDR X)])

(CADAAR
  [LAMBDA (X)
    (CADR (CAAR X)])

(CADDAR
  [LAMBDA (X)
    (CADR (CDAR X)])

(CAAADR
  [LAMBDA (X)
    (CAAR (CADR X)])

)

(DEFINEQ
```


(SYSTEMTYPE

[LAMBDA NIL

(* Imm "17-AUG-81 15:50")
; let the macro decide**(SYSTEMTYPE]**)

)

;; Because can't have bignums in code at makeinit time

(RPAQ \IMAX.FLOAT (FIX MAX.FLOAT))

(RPAQ \IMIN.FLOAT (FIX MIN.FLOAT))

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS \IMAX.FLOAT \IMIN.FLOAT)

)

(DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVARS

(ADDTOTVAR **NLAMA** DUMMYDEF)(ADDTOTVAR **NLAML**)(ADDTOTVAR **LAMA** LIST* LIST NCONC NOTIMP ZERO NIL)

)

(RPAQ ABASICCOMS

[(FNS EVALQT \SystemERROR)

(FNS NIL EVQ TRUE ZERO CL:IDENTITY DUMMYDEF NOTIMP)

(P (DUMMYDEF (WINDOWWORLDP NIL)))

(FNS EQUAL NEQ NULL NOT)

(COMS

; Belong on ACODE except they would clobber 10-versions in
; ABC

(FNS LAPRD DEFC CGETD))

(FNS NCONC \NCONC2 SORT MERGE SORT1 FASSOC FLAST FLENGTH FMEMB FNTH LIST LIST* COUNT)

(FNS CHANGENAME1 CHANGENAME1A)

(FNS CDDR CDAR CADR CAAR CDDDR CDDAR CDADR CDAAR CADDR CADAR CAADR CAAAR CDDDDR CAAAAR CDDAR CDDADR
CDDAAR CDAAR CADADR CDADDR CDADAR CAADDR CDAADR CAADAR CADDR CADAAR CADDR CAAADR)

(FNS SYSTEMTYPE)

(COMS

; Because can't have bignums in code at makeinit time

(VARS (\IMAX.FLOAT (FIX MAX.FLOAT))

(\IMIN.FLOAT (FIX MIN.FLOAT)))

(GLOBALVARS \IMAX.FLOAT \IMIN.FLOAT))

(DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVARS (ADDVARS (NLAMA DUMMYDEF)

(NLAML)

(LAMA LIST* LIST NCONC NOTIMP]))

(DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVARS

(ADDTOTVAR **NLAMA** DUMMYDEF)(ADDTOTVAR **NLAML**)(ADDTOTVAR **LAMA** LIST* LIST NCONC NOTIMP)

)

(PUTPROPS **ABASIC COPYRIGHT** ("Venue & Xerox Corporation" 1982 1983 1984 1985 1986 1987 1990 2021))

FUNCTION INDEX

CAAAAR8	CADAR7	CDADDR8	CDDR7	EVQ1	LIST*6	SORT15
CAAADR8	CADDAR8	CDADR7	CGETD3	FASSOC5	MERGE4	SYSTEMTYPE ..9
CAAAR8	CADDDR8	CDAR7	CHANGENAME1 .7	FLAST5	NCONC4	TRUE1
CAADAR8	CADDR7	CDDAAR8	CHANGENAME1A 7	FLLENGTH6	NEQ3	ZERO1
CAADDR8	CADR7	CDDADR8	COUNT6	FMEMB6	NILL1	\NCONC24
CAADR7	CDAAAR8	CDDAR7	DEFC3	FNTH6	NOT3	\SystemERROR 1
CAAR7	CDAADR8	CDDDAR8	DUMMYDEF2	CL:IDENTITY .2	NOTIMP2	
CADAAR8	CDAAR7	CDDDDR8	EQUAL2	LAPRD3	NULL3	
CADADR8	CDADAR8	CDDDR7	EVALQT1	LIST6	SORT4	

VARIABLE INDEX

\IMAX.FLOAT .9 \IMIN.FLOAT .9
