```
28-Feb-92 11:55:34 {DSK}-cusr-local-lde-lispcore-sources-ERROR-RUNTIME-AFTER-FASL.;2
 File created:
  changes to:
               (FUNCTIONS CONDITIONS:CONTINUE CONDITIONS:MUFFLE-WARNING USE-VALUE STORE-VALUE)
previous date:
               16-May-90 16:26:16 {DSK}<usr>local>lde>lispcore>sources>ERROR-RUNTIME-AFTER-FASL.;1
 Read Table:
               XCL
   Package:
               INTERLISP
      Format:
                XCCS
; Copyright (c) 1987, 1988, 1990, 1992 by Venue & Xerox Corporation. All rights reserved.
(RPAQQ ERROR-RUNTIME-AFTER-FASLCOMS ((PROP FILETYPE ERROR-RUNTIME-AFTER-FASL)
;;; These functions must be PavCompiled.
                                           (FUNCTIONS SI:: CREATE-CONDITION-CASE-LITERALS)
;;; These don't need to be, but depend on the previous stuff.
                                           (FUNCTIONS ABORT CONDITIONS:CONTINUE CONDITIONS:MUFFLE-WARNING USE-VALUE
                                                   STORE-VALUE)))
(PUTPROPS ERROR-RUNTIME-AFTER-FASL FILETYPE : COMPILE-FILE)
;;; These functions must be PavCompiled.
(CL:DEFUN SI::CREATE-CONDITION-CASE-LITERALS (SI::TYPE-LIST)
   (LET ((SI::CATCH-TAG (LIST NIL)))
                                                                        use a separate CONS for the catch tag so that you don't get a
                                                                        circular structure (you could save one by making the tag be the handler binding itself, then smashing its CDR with the closure).
         (LIST* SI::CATCH-TAG SI::TYPE-LIST #'(CL:LAMBDA (SI::CONDITION)
                                                          (CL:THROW SI::CATCH-TAG SI::CONDITION)))))
;;; These don't need to be, but depend on the previous stuff.
(DEFINE-PROCEED-FUNCTION ABORT : REPORT "Abort"
   (CONDITION XCL: *CURRENT-CONDITION*))
(DEFINE-PROCEED-FUNCTION CONDITIONS:CONTINUE (CONDITION XCL: *CURRENT-CONDITION*))
(DEFINE-PROCEED-FUNCTION CONDITIONS:MUFFLE-WARNING (CONDITION XCL: *CURRENT-CONDITION*))
(DEFINE-PROCEED-FUNCTION USE-VALUE : REPORT "Use a different value"
   XCL::VALUE
   (CONDITION XCL: *CURRENT-CONDITION*))
(DEFINE-PROCEED-FUNCTION STORE-VALUE : REPORT "Store a new value and use it"
   XCL::VALUE
   (CONDITION XCL: *CURRENT-CONDITION*))
```

(PUTPROPS ERROR-RUNTIME-AFTER-FASL COPYRIGHT ("Venue & Xerox Corporation" 1987 1988 1990 1992))

FUNCTION INDEX	
ABORT	CONDITIONS:MUFFLE-WARNING
PROPERTY INDEX	
ERROR-RUNTIME-AFTER-FASL1	