

File created: 17-Mar-87 17:03:54 {DSK}<XAVIER>TRANSOR.;16

changes to: (VARS TRANSORCOMS)  
(FNS PRECH1 TRANSOUT)

previous date: 17-Mar-87 17:00:04 {DSK}<XAVIER>TRANSOR.;15

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

#### (RPAQQ TRANSORCOMS

```
((FNS TRANSOR TRANSOR-PROCEED TRANSORFORM TRANSORFNS TRANSFORM TRANSIT TRANXT TRANSEXIT KEEPLIST TRANSERR
  TRANSOUT PPASS1 TRANSLIST TRANSLIST1 PRETEXT WACHADOON PRECH PRECH1 PRECH2 RETAIL LNC PRESCAN)
  TRANSORMACROS TRANSOREMARKS TRANSORGLOBS (VARS (MAXLOOP 1530)
    (TESTRAN)
    (USERMACROS (APPEND TRANSORMACROS USERMACROS))
    (GLOBALVARS (APPEND TRANSORGLOBS GLOBALVARS))
    (EDITCOMSA (UNION ' (NLAM NLAMIT DOTHES DOTHIS XFORMER
      CONTINUE)
      EDITCOMSA))
    (EDITCOMSL (UNION ' (REMARK)
      EDITCOMSL))
    (TRANSITCONSES ' (ORR NIL XFORMER))
    (PRESCARRAY (ARRAY 127 127)))

  (INITVARS (NLISTPCOMS)
    (LAMBDA (COMS)
      (TRANSOUTREADTABLE FILERDTBL))
    (DECLARE%: DOEVAL@LOAD DOEVAL@COMPILE DONTCOPY (PROP BLKLIBRARYDEF TAILP))
    (PROP FILEGROUP TRANSOR)
    (BLOCKS (PRECHBLOCK PRECH PRECH1 PRECH2 RETAIL LNC (ENTRIES PRECH)
      (BLKLIBRARY TAILP MEMB LAST LENGTH ASSOC GETP))
      (TRANSITBLOCK TRANSIT WACHADOON (ENTRIES TRANSIT WACHADOON)
        (GLOBALVARS WACHADID WHENTODOIT TRANSITCONSES LAMBDA (COMS)
          (BLKLIBRARY TAILP MEMB LAST LENGTH ASSOC GETP))
        (TRANXTBLOCK TRANXT (ENTRIES TRANXT)
          (BLKLIBRARY TAILP MEMB LAST LENGTH ASSOC GETP))
        (NIL PRESCAN (GLOBALVARS PRESCARRAY)))
      (DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVAR (ADDVARS (NLAMA)
        (NLAML TRANSERR KEEPLIST
          TRANSOR-PROCEED)
        (LAMA)))

    (EDITHIST TRANSOR)))
```

(DEFINEQ

#### (TRANSOR

```
[LAMBDA (SOURCEFILE)
  (RESETFORM (SETREADTABLE FILERDTBL)
    (PROG (INPUTFILE OUTPUTFILE LISTFILE LISTING NAMEFIELD EXPRESSION TMP)
      (DECLARE%: (SPECVARS LISTFILE LISTING))
      (COND
        ((NLISTP TRANSFORMATIONS)
          (ERROR "No transformations loaded." "" T))
        ((NULL (SETQ INPUTFILE (INFILEP SOURCEFILE)))
          (ERROR "Cannot find file:" SOURCEFILE T)))
      (SETQ NAMEFIELD (FILENAMEFIELD INPUTFILE 'NAME))
      (COND
        ((NULL (SETQ OUTPUTFILE (OPENSTREAM (SETQ TMP (PACKFILENAME 'NAME NAMEFIELD 'EXTENSION
          "TRAN"))
          'OUTPUT]
          (ERROR "Cannot open file:" TMP T))
          ((NULL (SETQ LISTFILE (OPENSTREAM (SETQ TMP (PACKFILENAME 'NAME NAMEFIELD 'EXTENSION
          "LSTRAN"))
          'OUTPUT]
          (ERROR "Cannot open file:" TMP T)))

      (SETQ INPUTFILE (OPENSTREAM INPUTFILE 'INPUT))
      (PRIN1 ' " (PRIN1 (QUOTE %")
        Transoring of " OUTPUTFILE)
      (PRINT (FULLNAME INPUTFILE)
        OUTPUTFILE)
      (PRIN1 ' " done on " OUTPUTFILE)
      (PRIN1 (DATE)
        OUTPUTFILE)
      (PRIN1 ' " %") T) " OUTPUTFILE)
      (TERPRI OUTPUTFILE)
      (TERPRI OUTPUTFILE)
      (PRIN1 ' " Listing from TRANSORing of file " LISTFILE)
      (PRINT (FULLNAME INPUTFILE)
        LISTFILE)
      (PRIN1 ' " done on " LISTFILE)
      (PRIN1 (DATE)
        LISTFILE)
      (TERPRI LISTFILE)
      (TERPRI LISTFILE))
```

(\* All the preliminary error checks ok.  
Open files, print headers.)

```

LP (COND
  ([NULL (NLSETQ (PROG NIL
                  (* Rebind HELPCLOCK so that when over-read EOF no error
                    message or BREAK will occur.)
                  (SETQ EXPRESSION (READ INPUTFILE)
                    (GO DONE)))
   [SELECTQ EXPRESSION
    (STOP

```

(\* Only check for STOP, no check for NIL. Foreign files never have STOPs on them and rarely have extra parens or NIL's. Extra NIL's on a file usually indicate that the reading machinery is screwed up, probably because user forgot to perform (ESCAPE)%, or, even worse, there is a different ESCAPE character.  
I therefore must ERRORSET protect the READ above anyway, and try to keep reading until can read no further.)

```

      (GO DONE))
    (COND
      ((NLISTP EXPRESSION)
       (TRANSERR NIL "NLISTP expression on file - expression discarded:" (EXPRESSION))
       (GO LP])
      (SETQ EXPRESSION (TRANSFORM EXPRESSION))
      (TRANSOUT EXPRESSION OUTPUTFILE)
      (GO LP)
    DONE
    (AND (OPENP INPUTFILE)
          (CLOSEF INPUTFILE))
    (ENDFILE OUTPUTFILE)
    (TRANSLIST LISTING LISTFILE)
    (CLOSEF LISTFILE)
    (RETURN (LIST (FULLNAME OUTPUTFILE)
                  (FULLNAME LISTFILE]))

```

**(TRANSOR-PROCEED**

; Edited 6-Mar-87 14:37 by DJVB

```

[NLAMBDA (FLG)
  (PROG ((L L)
    STOPPEDUP WHERETOGONEXT CONTINUEL CONTINUETAIL TRANSITL TRANSITAIL OLDLENGTH)
    (DECLARE%: (SPECVARS L STOPPEDUP WHERETOGONEXT CONTINUEL CONTINUETAIL TRANSITL TRANSITAIL OLDLENGTH))
    LP (COND
      ([ERSETQ (SETQ L
                    (EDITL L (SELECTQ FLG
                                   (DOTHIS '[(IF (TAILP (CAR L)
                                                         (CADR L))
                                   ((REMARK TAILP/DOTHIS)
                                    1)
                                   NIL)
                                   MARK
                                   (ORR (NX UP (E (PROG (LISPPX HIST)
                                                         (SETQ STOPPEDUP (%##)))
                                                         T))
                                   (!NX UP (E (PROG (LISPPX HIST)
                                                         (SETQ STOPPEDUP (%##)))
                                                         T))
                                   NIL)
                                   (LPQ (COMS (TRANSIT)
                                              (TRANXT]))
                                   (DOTHESE '[(MARK (ORR ((IF (NOT (TAILP (CAR L)
                                                                    (CADR L))
                                                                    NX UP (E (PROG (LISPPX HIST)
                                                                    (SETQ STOPPEDUP (%##)))
                                                                    T))
                                                                    (!NX UP (E (PROG (LISPPX HIST)
                                                                    (SETQ STOPPEDUP (%##)))
                                                                    T))
                                                                    NIL)
                                                                    — 1 (LPQ (COMS (TRANSIT)
                                                                    (TRANXT]))
                                                                    (TRANSFORM '[(LPQ (COMS (TRANSIT)
                                                                    (TRANXT]))
                                                                    (OKCOMS '[(LPQ (COMS (TRANXT)
                                                                    (TRANSIT]))
                                                                    (HELP])
                                                                    (SETQ FLG 'OKCOMS)
                                                                    (GO LP))
                                                                    (T (TRANSERR TRANSERROR "Fail return to TRANSOR from EDITOR. Show Jim Goodwin." (CURRENTFORM
                                                                                                                                                                CURRENTCOMS
                                                                                                                                                                ]))

```

**(TRANSORFORM**

; Edited 6-Mar-87 14:36 by DJVB

```

[LAMBDA (FORM)
  (PROG (LISTFILE LISTING)
    (DECLARE%: (SPECVARS LISTFILE LISTING))
    (SETQ FORM (TRANSFORM FORM))
    (AND LISTING (ERSETQ (TRANSLIST LISTING)))
    in TXTEST.)
    (RETURN FORM])

```

(\* ERRORSET so user can abort with ^E, especially when used

**(TRANSORFNS**

```

[LAMBDA (FNLIST)
  (PROG (LISTING LISTFILE DEF)
    (DECLARE%: (SPECVARS LISTING LISTFILE))
    [MAPC FNLIST (FUNCTION (LAMBDA (FN)
      (COND
        ([AND (LITATOM FN)
          (EXPRP (SETQ DEF (VIRGINFN FN)
            (TRANSFORM DEF FN))
          (T (PRINT (CONS FN ' (NOT FOUND))
            T T])
        (ERSETQ (TRANSLIST LISTING))
        (RETURN FNLIST))

```

; Edited 6-Mar-87 14:36 by DJVB

**(TRANSFORM**

```

[LAMBDA (SOURCEEXPR FNAME)

```

; Edited 6-Mar-87 14:37 by DJVB

(\* TRANSFORM is the entry to the translator. It returns the translated SOURCEEXPR, and resets LISTING and uses LISTFILE freely (see KEEPLIST)%.

The source expression is embedded one level so that top-level embeds will work

(i.e. the case where the source expression is (FOO --) and the transformation for FOO is MBD)%.

-

FNAME is provided only by TRANSORFNS. Thus if not provided, SOURCEEXPR is a FORM from TRANSORFORM or TRANSOR's file, and we begin translation at SOURCEEXPR, but if FNAME is given, SOURCEEXPR is a LAMBDA expression and we do a 3 command first, to get to a FORM.

RETAIL also checks this top-level expression. If the top level is

(NIL &) it is of no interest to user. But if FNAME was given, top level is

(FNAME &) and should be printed, otherwise user will see only a LAMBDA expression and not know where it came from.)

```

(PROG (L PASS1 HELPCLOCK)
  (DECLARE%: (SPECVARS L PASS1))
  [COND
    [FNAME (SETQ L (LIST (CADDR SOURCEEXPR)
      SOURCEEXPR
      (LIST FNAME SOURCEEXPR)
      (T (SETQ L (LIST SOURCEEXPR (LIST NIL SOURCEEXPR)
        (WACHADOON T)
        (TRANSOR-PROCEED TRANSFORM)
        (MAPC (DREVERSE PASS1)
          (FUNCTION PPASS1))
        (RETURN (COND
          (FNAME (CADR L))
          (T (CAR L))

```

**(TRANSIT**

```

[LAMBDA NIL
  (PROG ((HERE (CAR L))
    TMP)
    (WACHADOON)
    [COND
      ((TAILP HERE (CADR L))
        (TRANSERR TRANSERROR "The function TRANSIT reached a TAILP position; show Jim Goodwin."
          (CURRENTFORM CURRENTCOMS))
        (SETQ L (CONS (SETQ HERE (CAR HERE))
          (CDR L)
          (SETQ CURRENTFORM HERE)
          (SETQ CONTINUEL)
          [SETQ WHERETOGONEXT ' (ORR 2 NX !NX ((E (TRANSEXIT

```

(\* DJVB " 3-Feb-87 13:21")

(\* The call to TRANSEXIT above causes the exits from PROCEED which occur because of dropoff.)

```

(SETQ OLDLENGTH (LENGTH (CADR L)))
(SETQ TRANSITL L)
[COND
  ((AND LASTAIL (EQ (CAR LASTAIL)
    HERE))
    (SETQ TRANSITAIL LASTAIL))
  ((OR [NULL (SETQ TRANSITAIL (MEMB HERE (CADR L)
    (MEMB HERE (CDR TRANSITAIL)))
    (HELP "The editor lost LASTAIL, and with it its sense of direction." "Show Jim Goodwin.")
  [SETQ CURRENTCOMS (COND
    ([AND STOPPEDUP (EQ HERE (CAR STOPPEDUP))
      (OR (LISTP HERE)
        (EQ STOPPEDUP (%## UP] (* Exit on match with STOPPEDUP.)
      (RETFROM 'TRANSOR-PROCEED))
    ((NLISTP HERE)
      NLISTPCOMS)
    ((LITATOM (CAR HERE))

```

(\* If user commands cause an error it will be trapped by the ORR and XFORMER will be executed.

XFORMER is a TRANSORMACRO which makes a remark on the error.

Don't make the list if no commands.)

```

(GETP (CAR HERE)

```

```

      'XFORM))
      ((LISTP (CAR HERE))
       LAMBDA COMS)
      (T ' ((COMSQ (REMARK ILLCAR)
                   DO THESE])
      (RETURN (COND
                (CURRENTCOMS (FRPLACA (CDR TRANSITCONSES)
                                       CURRENTCOMS)

```

(\* If CURRENTCOMS is NIL, return NIL; otherwise effectively embed CURRENTCOMS in orr such that if CURRENTCOMS fail, xformer will be executed. Xformer is a transormacro which calls TRANSERR appropriately for a faulty transformation.)

```
TRANSITCONSES])
```

**(TRANXT**

```

[LAMBDA NIL
 (PROG (NEWFORM NEWLENGTH TMP NEWTAIL)
  (COND
   (CONTINUEL (SETQ L CONTINUEL)
               (SETQ LASTAIL CONTINUETAIL)
               (RETURN)))
  (SETQ NEWFORM (CAR TRANSITAIL))
  (SETQ NEWLENGTH (LENGTH (CADR TRANSITL)))
  (COND
   ((NEQ NEWLENGTH OLDLENGTH)
    (GO DELETED))
   ((OR (EQ NEWFORM CURRENTFORM)
        (EQ WHERETOGONEXT 'NLAMIT))

```

(\* If containing list still points at same EQ structure, or if he's declared he's done with whatever is there, no problem.)

```

)
  ((AND (LISTP NEWFORM)
        (EDITFINDP NEWFORM (SETQ TMP (CONS '== CURRENTFORM)
                                             T))

```

(\* Net effect was an MBD. If we went on from here in normal fashion, we would embed it again and again. Find original expression and go on from there.)

```

  (SETQ WHERETOGONEXT (CONS TMP WHERETOGONEXT)))
  ((AND (LISTP CURRENTFORM)
        (EDITFINDP CURRENTFORM (CONS '== NEWFORM)
                                  T))

```

(\* Net effect was XTR. If we went on normally, we'd miss the form extracted. Set continuation commands to NIL so we stay where we are)

```

  (SETQ WHERETOGONEXT))
  (T

```

(\* User did a %: or DELETE where effect was (%: NIL)%. Assume the stuff he put in place of old does not need translation. perform NLAM for him.)

```
(SETQQ WHERETOGONEXT NLAM)))
```

(\* Ready to return. Fix up L, smashing CAR to point to right thing. In normal case, (EQ CURRENTFORM NEWFORM)%, it already does and this FRPLACA is a NOP.)

```

ZIPPO
  (SETQ L (FRPLACA TRANSITL NEWFORM))
  (SETQ LASTAIL TRANSITAIL)

```

(\* Finally, return the commands which will locate the next form to translate.)

```
(RETURN WHERETOGONEXT)
```

```

DELETED
  (COND
   ((NEQ (SUB1 OLDLENGTH)
          NEWLENGTH)

```

(\* This could happen if user cheated by doing a !0 and deleting several things or inserting things.)

```

  (TRANSERR OUTOFBOUNDS "Your transformations cheated and changed something out of bounds."
    (CURRENTFORM CURRENTCOMS)))
  [(NOT (TAILP TRANSITAIL (CADR L)))]

```

(\* User deleted the form, but it was the last form on its containing list.)

```

  (RETURN ' (ORR !NX ((E (TRANSEXIT)
    (T

```

(\* User deleted the form, but was not last thing, thus NEWFORM is already bound to the NX thing after the one we just %'translated' by deleting it. Set WHERETOGONEXT to NIL so we do not move at all.)

```

  (SETQ WHERETOGONEXT)
  (GO ZIPPO))

```

**(TRANSEXIT**

```
[LAMBDA NIL
```

(\* DJVB " 3-Feb-87 13:22")

```

(COND
  (STOPPEDUP (TRANSERR TRANSERROR "The function TRANSEXIT missed the exit. Show Jim Goodwin." (CURRENTFORM
    CURRENTCOMS
  ]
  (RETFROM 'TRANSOR-PROCEED])

```

**(KEEPLIST**

```

[NLAMBDA (REMNAME)
  (PROG (TMP)
    [COND
      ((NLISTP LISTING) (* Initialize if first remark in this LISTING.)
        (SETQ LISTING (LIST 1)))
      (T (FRPLACA LISTING (ADD1 (CAR LISTING)
        (SETQ PASS1 (CONS (CONS (CAR LISTING)
          (CONS REMNAME L))
          PASS1)) (* Save pass2 stuff for TRANSLIST.)
        [COND
          (TESTRAN (* Skip pass2 if testing)
            NIL)
          ([NULL (SETQ TMP (FASOC REMNAME (CDR LISTING)
            (NCONC1 LISTING (LIST REMNAME (CAR LISTING)
            (T (NCONC1 TMP (CAR LISTING)
            (RETURN])) (* First use of this remark.)

```

**(TRANSERR**

```

[NLAMBDA (REM MESS VARS)
  (AND REM (APPLY (FUNCTION KEEPLIST)
    (LIST REM)))
  [AND MESS (NLSETQ (PROGN (TERPRI T)
    (TERPRI T)
    (PRIN1 ' "
      TRANSOR made a translation error: " T)
    (PRIN1 MESS T)
    (TERPRI T]
  (AND VARS (NLSETQ (PROGN (PRINTLEVEL 3)
    [MAPC VARS (FUNCTION (LAMBDA (X)
      (PRIN2 X T T)
      (PRIN1 '": " T)
      (PRINT (EVALV X]
    (PRINTLEVEL 1000)
    (TERPRI T]))

```

**(TRANSOUT**

```

[LAMBDA (XPR FILE) ; Edited 17-Mar-87 16:37 by DJVB
  (RESETFORM (OUTPUT FILE)
    (RESETFORM (SETREADTABLE TRANSOUTREADTABLE)
      (COND
        ((EQ FILE 'NIL%:))
        ((EQ 'DEFINEQ (CAR XPR)) (* Special formatting for function lists.)
          (PRIN1 ' "(DEFINEQ")
          (TERPRI)
          [MAPC (CDR XPR)
            (FUNCTION (LAMBDA (X)
              (TERPRI)
              (PRIN1 ' %()
              (PRINT (CAR X))
              (PRINTDEF (CADR X)
                NIL T)
              (PRIN1 ' %))
              (TERPRI]
          (PRIN1 ' %))
          (TERPRI))
        [(AND (EQ 'PROGN (CAR XPR))
          (EQ 'DEFUN (CAADR XPR))) (* Special formatting for commonlisp function lists.)
          (MAPC (CDR XPR)
            (FUNCTION (LAMBDA (X)
              (TERPRI)
              (COND
                ((EQ (CAR X)
                  'DEFUN)
                  (PRIN1 " (DEFUN "
                  (AND LAMBDAFONT FONTCHANGEFLG (CHANGEFONT LAMBDAFONT))
                  (PRIN2 (CADR X))
                  (AND LAMBDAFONT FONTCHANGEFLG (CHANGEFONT DEFAULTFONT))
                  (PRIN2 (CADDR X))
                  (PRINTDEF (CDDDR X)
                    6 T T)
                  (PRIN1 " )"))
                  (T (PRINTDEF XPR)))
              (TERPRI]
          (T (TERPRI)
            (PRINTDEF XPR)
            (TERPRI]))

```

**(PPASS1**

```

[LAMBDA (P1)
  (PRIN1 (CAR P1)
    LISTFILE)
  (PRIN1 ' ". " LISTFILE)
  (PRIN1 (CADR P1)
    LISTFILE)
  (PRIN1 ' " at " LISTFILE)
  (PRECH (CDDR P1)
    NIL LISTFILE T)
  (TERPRI LISTFILE])

```

**(TRANSLIST**

```

[LAMBDA (LISTING LISTFILE)
  (PROG (OLDO)
    (COND
      (TESTRAN
        (RETURN))
      ((EQ LISTFILE 'NIL%:)
        (RETURN)))
    (SETQ OLDO (OUTPUT LISTFILE))
    [COND
      ((NULL LISTING)

```

(\* TRANSLIST must dump the second half of the listing prettily.)

(\* See TXTEST.)

(\* See KEEPLIST for discussion of format of LISTING.)

(\* User would like to know if this happens rather than just wondering where his output went.)

```

  (PRIN1 ' "
    ")))
  (T (PRIN1 ' "
    No REMARKS -- empty listing.

```

## Index of Remarks

```

      ")
      (MAPC (SORT (CDR LISTING)
                  T)
            (FUNCTION TRANSLIST1]
      (TERPRI)
      (OUTPUT OLD0)
      (RETURN])

```

## (TRANSLIST1

```

[LAMBDA (L1)
  (PRIN1 (CAR L1))
  (PRIN1 ' " at ")
  (MAPRINT (CDR L1)
            NIL NIL ' " .
            " ' " , ")
  (PREMTEXT (CAR L1))
  (TERPRI])

```

(\* Name of remark.)

## (PREMTEXT

```

[LAMBDA (RNAME)
  (PROG (TXT)
    [COND
      ((OR (SETQ TXT (ASSOC RNAME USERNOTES))
            (SETQ TXT (ASSOC RNAME TRANSOREMARKS)))
        (SETQ TXT (CADR TXT)))
      (T (SETQQ TXT
                (SPACES 5)
                [COND
                  ((EQ (CADR TXT)
                        ' %%)

```

(\* The text of this remark was not defined in the TRANSFORMATIONS file.)]

(\* Lower-case the comment before using it, if he is testing and it hasn't been dumped before.)

```

      (RPLACD TXT (COMMENT3 (CDDR TXT)
                            NIL T])
      (MAPRINT (CDR TXT))
      (TERPRI])

```

## (WACHADOON

```

[LAMBDA (FLG)
  (OR TESTRAN (PROG ((NOW (CLOCK)))
                    (COND
                      (FLG (SETQ WACHADID)
                           (SETQ WHENTODOIT NOW)
                           (RETURN))
                      ((ILESSP NOW WHENTODOIT)
                       (RETURN)))
                    (PRECH L WACHADID T)
                    (SETQ WACHADID L)
                    (SETQ WHENTODOIT (IPLUS 180000 NOW]))

```

## (PRECH

```

[LAMBDA (ECH OLDECH FILE PRYFLG)
  (PROG ((OLD0 (OUTPUT FILE))
        X)
    [SETQ X (PRECH1 (RETAIL (COND
                            (OLDECH (LNC ECH OLDECH))
                            (T ECH]
        (COND
          (PRYFLG (PRINTDEF X))
          (T (PRINT X)))
        (TERPRI)
        (OUTPUT OLD0)
        (RETURN])

```

(\* Function to Print a Reversed Edit CHain in my special format.)

## (PRECH1

```

[LAMBDA (RECH)
  (PROG (LASTALE (N -2)
        LST)
    [COND
      ((NULL (CDR RECH))
       (RETURN (MKSTRING (PRECH2 (CAR RECH)
                                   4]
       (SETQ LASTALE (SOME (CAR RECH)
                           (FUNCTION (LAMBDA (E)

```

; Edited 17-Mar-87 14:24 by DJVB

```

                                (ADD1VAR N)
                                (EQ E (CADR RECH])
(AND (MINUSP N)
      (GO OUT))
(SETQ LST (CONS (COND
                  ((NLISTP (CAAR RECH))
                   (CAAR RECH))
                  (T (PRECH2 (CAAR RECH)
                              3)))
                  LST))
[SELECTQ N
  (0)
  (1 (SETQ LST (CONS (COND
                      ((NLISTP (CADAR RECH))
                       (CADAR RECH))
                      (T ' &))
                      LST)))
  (COND
    [(AND (EQ 'DEFUN (CAAR RECH))
           (LITATOM (CADAR RECH)))]
    (SETQ LST (CONS [COND
                      [(EQ N 2)
                       (COND
                        ((NLISTP (CADDAR RECH))
                         (CADDAR RECH))
                        (T ' &)]
                      (T (PACK* ' |...| (SUB1 N)
                          ' |...|)]
                      (CONS (CADAR RECH)
                           LST]
                           LST]
                           (T (SETQ LST (CONS (PACK* ' |...| N ' |...|)
                                               LST]
                                               LST]
                           OUT (SETQ LST (CONS (PRECH1 (CDR RECH))
                                                LST))
  [COND
    ((CDR LASTALE)
     (SETQ LST (CONS '--- LST]
     (RETURN (DREVERSE LST])

```

(\* DJVB put in for TO-COMMONLISP to identify DEFUNs)

**(PRECH2**

```

[LAMBDA (X LEVEL)
  (COND
    ((NLISTP X)
     X)
    ((EQ (CAR X)
          COMMENTFLG)
     '***COMMENT***)
    ((ILESSP LEVEL 1)
     ' &)
    (T (MAPCAR X [FUNCTION (LAMBDA (XELT)
                              (SUB1VAR LEVEL)
                              (COND
                                ((MINUSP LEVEL)
                                 '---)
                                (T (PRECH2 XELT LEVEL)]
                              (FUNCTION (LAMBDA (TAIL)

```

(\* At last!!!! I get to use the second functional argument to a mapping function.

To implement a triangular PRINTLEVEL, step the LEVEL down in the first function and select hyphens when it hits bottom; cut off the rest of the MAP by checking for bottom here.)

```

(AND (NULL (MINUSP LEVEL))
      (CDR TAIL])

```

**(RETAIL**

```

[LAMBDA (L)
  (DECLARE%: (SPECVARS L))
  (PROG (RES)
    [SETQ RES (LIST (COND
                     ((TAILP (CAR L)
                              (CADR L))
                      (CAAR L))
                     (T (CAR L)]
    [MAP (CDR L)
      (FUNCTION (LAMBDA (TAIL)
        (COND
          [(NULL (CDR TAIL))

```

; Edited 6-Mar-87 14:39 by DJVB

(\* At end. If top-most expression is (NIL &amp;) don't include it. Otherwise is from TRANSORFNS, so include it. See TRANSFORM.)

```

(AND (CAAR TAIL)
      (SETQ RES (CONS (CAR TAIL)
                      RES]
      (MEMB (CAR TAIL)

```



(CADR TAIL))

(\* If not a TAIL, must be MEMB, otherwise edit chain screwed up.  
We want every one that's MEMB.)

```
(SETQ RES (CONS (CAR TAIL)
                RES])
```

(RETURN RES])

**(LNC**

[LAMBDA (L1 L2)

(\* LNC is for Last New Cons. Returns last tail of L1 such that it is not common with L2.  
L1 is the edit chain representing TRANSOR's current location; L2 is the chain from the last call to WACHADOON.  
Value is (LAST L1) if nothing in common, i.e. we are transoring an entirely different source expression.)

```
(PROG (X)
  (COND
    ((NLISTP L1)
     (HELP))
    ((NEQ (SETQ X (LAST L1))
          (LAST L2))
     source expression.)
    (RETURN X)))
  LP (COND
      ((TAILP (CDR L1)
              L2)
       (RETURN L1)))
    (SETQ L1 (CDR L1))
    (GO LP])
```

(\* Quick check for commonest case, we are in a totally different

**(PRESCAN**

[LAMBDA (FILE CHARLST PRESCANFN)

(\* DJVB "22-NOV-83 21:41")

(\* FIX UP TO ALLOW NULL'S (ZERO'S) IN CHARLST. AT PRESENT JUST FILTERS %'EM ALL OUT, IF YOU PUT 0 IN CHARLST GIVES ILLEGAL SETA.)

(\* PRESCAN is for pre-digesting files from alien environments where special characters, etc., are all different.

-  
FILE is input file; output goes to next higher version. -  
CHARLST is list of dot-pairs of character codes (old . new)%, so that you can for example replace all tabs in a file with spaces by including (9 . 32) on CHARLST. -  
PRESCANFN is function for user. If the new character code for any character is NIL, then PRESCANFN is called giving the character code as its first argument. PRESCANFN can then do what it needs to process the upcoming file information. The second argument to PRESCANFN is the input file, and the third is the output file.

-  
Original impetus for this was MIT Lisp's special recognition of semicolon%: any line beginning with semicolon was comment, a la macro files. With (59) on CHARLST, where 59 is character code for semicolon, PRESCANFN can process those lines, making them into regular comments. Note that no output is done for these special characters unless PRESCANFN does it.)

```
(PROG ((INF (INPUT (INFILE FILE)))
      [OUTF (OUTPUT (OUTFILE (NAMEFIELD FILE T)
                          (I 127))
      TOP (COND
          ((NOT (ZEROP I))
           (SETA PRESCARRAY I I)
           (SUB1VAR I)
           (GO TOP)))
      [MAPC CHARLST (FUNCTION (LAMBDA (PR)
                              (SETA PRESCARRAY (CAR PR)
                                      (OR (CDR PR)
                                          0])
```

```
(SELECTQ (SYSTEMTYPE)
  ((TENEX TOPS-20)
   (D-ASSEM::ASSEMBLE NIL (CQ INF)
    (FASTCALL IFSET)
    (HRRZI 1 %, FCHAR (FX))
    (PUSHN)
    (HRRZ 1 %, FILEN (FX))
    (PUSHN)
    (VARS (HRRZ 2 %, OUTF))
    (FASTCALL IFSET)
    (HRRZ 1 %, FILEN (FX))
    (PUSHN)
    (CQ PRESCARRAY)
    (SKIP 4 (TIMES %, 1))
    (XWD 2 1)
    (add 4 %, 1)
```

(\* Store ptr to single-character buffer for input file on -2&lt;np&gt;.)

(\* Store input jfn on -1&lt;np&gt;.)

(\* Store output jfn on 0&lt;np&gt;.)

(\* Ac4 now has PRESCARRAY<2> i.e. indirect ref thru 4 will get Nth element of PRESCARRAY, where N is in ac2.  
Note ac4 must be saved on CP since LH is bits, RH is ptr.)

```
LOOP
  (NREF (MOVE 1 %, -1))
  (JSYS 40)
```

(\* BIN)

```

(JUMPE 2 %, DONE)
MIDDLE
(SKIPG 0 %, @ 4)
(JRST SPECIAL)
(MOVE 2 %, @ 4)
LOUT
(NREF (MOVE 1 %, 0))
(JSYS 41) (* BOUT)
(JRST LOOP)
DONE
(JSYS 20) (* GTSTS)
(TLNE 2 %, 512)
(JRST DONE!) (* Filter NULL's.)
(JRST LOOP)
SPECIAL
(MOVE 1 %, 2)
(CLISP% (SETQ CP (CONS %, (CONS 4 CP)))
  push CP %, 4)
(CQ (SETQ I (LOC (AC)))
  (APPLY* PRESCANFN I INF OUTF))
(CLISP% (PROG1 (CAR CP)
  (SETQ CP (CDR CP)))
  pop CP %, 4)
(NREF (HRRZ 2 %, @ -2)) (* If single-char buff. empty,)
(JUMPE 2 %, LOOP) (* Then next char. must be read from file,)
(NREF (HLRM 2 %, @ -2))

(* Else clear buff. to prevent next call to PRESCANFN from seeing it with READC or whatever,)

(JRST MIDDLE) (* And be sure the char from buff gets matched and output.)
DONE!
(POPNN 3)))
(VAX (SETQ INF (\GETOFD INF 'INPUT))
  (SETQ OUTF (\GETOFD OUTF 'OUTPUT))
  [CLISP% (PROG ($$VAL AC AT)
    $$LP
    (COND
      ((\EOFP INF)
        (RETURN $$VAL))
      ((ZEROP (SETQ AC (BIN INF)))
        (GO $$ITERATE)))
    (COND
      ((SETQ AT (ELT PRESCARRAY AC))
        (BOUT OUTF AT))
      (T (APPLY* PRESCANFN AC INF OUTF)))
    $$ITERATE
    (GO $$LP))
    until
    (\EOFP INF)
    bind AC AT unless (ZEROP (SETQ AC (BIN INF)))
    do
    (COND
      ((SETQ AT (ELT PRESCARRAY AC))
        (BOUT OUTF AT))
      (T (APPLY* PRESCANFN AC INF OUTF]))
    (D (SETQ INF (GETSTREAM INF 'INPUT))
      (SETQ OUTF (GETSTREAM OUTF 'OUTPUT))
      [CLISP% (PROG ($$VAL AC AT)
        $$LP
        (COND
          ((EOFP INF)
            (RETURN $$VAL))
          ((ZEROP (SETQ AC (BIN INF)))
            (GO $$ITERATE)))
          (COND
            ((SETQ AT (ELT PRESCARRAY AC))
              (BOUT OUTF AT))
            (T (APPLY* PRESCANFN AC INF OUTF)))
          $$ITERATE
          (GO $$LP))
          until
          (EOFP INF)
          bind AC AT unless (ZEROP (SETQ AC (BIN INF)))
          do
          (COND
            ((SETQ AT (ELT PRESCARRAY AC))
              (BOUT OUTF AT))
            (T (APPLY* PRESCANFN AC INF OUTF]))
            (HELP))
            (CLOSEF INF)
            (RETURN (CLOSEF OUTF))
          )
          (RPAQQ TRANSORMACROS
            ((REMARK (TXT)
              (E (KEEPLIST TXT)

```

```

    T))
(NLAM NIL (E (SETQ WHERE TO GONEXT NLAMIT)
    T))
[NLAMIT NIL (ORR NX !NX ((E (TRANSEXIT)
    (DOTHESE NIL (E (TRANSOR-PROCEED DOTHESE)
    T)
    NLAM)
    (DOTHIS NIL (E (TRANSOR-PROCEED DOTHIS)
    T)
    NLAM)
    (XFORMER NIL (E (TRANSERR TRANSFORMATIONERROR "FAULTY TRANSFORMATION" (CURRENTFORM CURRENTCOMS)
    T))))))

(RPAQQ TRANSOREMARKS
  ((TRANSFORMATIONERROR (* The TRANSFORMATIONS specified for this form failed to work properly. The TTY
    message '%FAULTY TRANSFORMATION' was printed, any commands remaining in the
    transformation after the erroneous one were skipped, and translation continued
    as if the transformation had been normally completed. The user should treat the
    translated form with caution and amend his transformation to avoid future
    problems.))
    (TRANSERROR (* TRANSOR got confused at this point. The TTY message '%SHOW JIM GOODWIN' was printed and
    translation continued with the next form, but the user should treat the compromised area
    of code with caution.))
    (BLAMBDA1 (* Non-atomic CAR of form, but not an open lambda. Either a parenthesis error or computed CAR
    of form. Computed CAR of form is no longer legal in BBN-LISP; APPLY* is used instead. If
    computed CAR of form was intended, the translation to APPLY* will run ok. See manual for
    discussion of APPLY*.))
    (BLAMBDA2 (* Open LAMBDA with wrong number of args. What can it mean?))
    (BLAMBDA3 (* Lambda-expression without forms. What can it mean?))
    (ILLCAR (* Illegal data-type encountered as CAR of form Expression treated as list of forms.))
    (TAILP/DOTHS (* When the transormacro DOTHS is executed at a TAILP position, TRANSOR does a 1 command
    first, assuming that the current position is a list of forms and CAR of it is the form
    intended. The user should make sure that this is what was intended by the
    TRANSFORMATIONS which called DOTHS, i.e. the TRANSFORMATIONS for the form containing
    this one.)))))

(RPAQQ TRANSORGLOBALS (USERNOTES USERNOTES TESTFORM TESTFORM TRANSFORMATIONS TRANSFORMATIONS XFORMSFNS
  XFORMSVARS XFORMSVARS DUMPFIL TRANSFORMATIONS TRANSFORMATIONS TRANSFORMATIONS
  TRANSFORMATIONS))

(RPAQQ MAXLOOP 1530)

(RPAQQ TESTRAN NIL)

(RPAQ USERMACROS (APPEND TRANSORMACROS USERMACROS))

(RPAQ GLOBALVARS (APPEND TRANSORGLOBALS GLOBALVARS))

(RPAQ EDITCOMSA (UNION ' (NLAM NLAMIT DOTHESE DOTHS XFORMER CONTINUE)
  EDITCOMSA))

(RPAQ EDITCOMSL (UNION ' (REMARK)
  EDITCOMSL))

(RPAQQ TRANSITCONSES (ORR NIL XFORMER))

(RPAQ PRESCARRAY (ARRAY 127 127))

(RPAQ? NLISTPCOMS )

(RPAQ? LAMBDA COMS )

(RPAQ? TRANSOUTREADTABLE FILERDTBL)

(DECLARE%: DOEVAL@LOAD DOEVAL@COMPILE DONTCOPY

(PUTPROPS TAILP BLKLIBRARYDEF [LAMBDA (.BLKVAR.X .BLKVAR.Y)
  (* True if .BLKVAR.X is A tail of .BLKVAR.Y .BLKVAR.X and .BLKVAR.Y
  non-null.)
  (* Included with editor for block compilation purposes.)
  (AND .BLKVAR.X (PROG NIL LP (COND ((NLISTP .BLKVAR.Y)
    (RETURN NIL))
    ((EQ .BLKVAR.X .BLKVAR.Y)
    (RETURN .BLKVAR.X))))
    (SETQ .BLKVAR.Y (CDR .BLKVAR.Y))
    (GO LP])
  )

(PUTPROPS TRANSOR FILEGROUP (TRANSOR TSET))

(DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY

(BLOCK%: PRECHBLOCK PRECH PRECH1 PRECH2 RETAIL LNC (ENTRIES PRECH)
  (BLKLIBRARY TAILP MEMB LAST LENGTH ASSOC GETP))

(BLOCK%: TRANSITBLOCK TRANSIT WACHADOON (ENTRIES TRANSIT WACHADOON)
  (GLOBALVARS WACHADID WHENTODOIT TRANSITCONSES LAMBDA COMS NLISTPCOMS)

```

```

      (BLKLIBRARY TAILP MEMB LAST LENGTH ASSOC GETP))

(BLOCK%: TRANXTBLOCK TRANXT (ENTRIES TRANXT)
  (BLKLIBRARY TAILP MEMB LAST LENGTH ASSOC GETP))

(BLOCK%: NIL PRESCAN (GLOBALVARS PRESCARRAY))
)

(DECLARE%: DONTEVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVARS

(ADDTOVAR NLAMA )

(ADDTOVAR NLAML TRANSERR KEEPLIST TRANSOR-PROCEED)

(ADDTOVAR LAMA )
)

(DECLARE%: DONTCOPY

(ADDTOVAR EDITHISTALIST
  (TRANSOR (" 5-Feb-87 16:18:06" DJVB {DSK}<XAVIER>TRANSOR.;11 (TRANSOR)
    (FIXED TO WORK WITH NEW FILE RULES IN LYRIC))
    (" 6-Feb-87 15:24:20" DJVB {DSK}<XAVIER>TRANSOR.;12 (TRANSOR))
    (" 6-Mar-87 14:41:26" DJVB {DSK}<XAVIER>TRANSOR.;13 (TRANSOR TRANSOR-PROCEED TRANSORFORM
      TRANSORFNS TRANSFORM RETAIL))
    ("17-Mar-87 17:01:53" DJVB {DSK}<XAVIER>TRANSOR.;15 (PRECH1 TRANSOUT)
      (ADDED SPLIT READ/WRITE READTABLES AND PP FOR DEFUN))))
)

(PUTPROPS TRANSOR COPYRIGHT (NONE))

```

---

FUNCTION INDEX

KEEPLIST .....5	PRECH2 .....8	TRANSEXIT .....4	TRANSOR .....1	TRANXT .....4
LNC .....9	PREMTEXT .....7	TRANSFORM .....3	TRANSOR-PROCEED ...2	WACHADOON .....7
PPASS1 .....6	PRESCAN .....9	TRANSIT .....3	TRANSORFNS .....3	
PRECH .....7	RETAIL .....8	TRANSLIST .....6	TRANSORFORM .....2	
PRECH1 .....7	TRANSERR .....5	TRANSLIST1 .....7	TRANSOUT .....5	

---

VARIABLE INDEX

EDITCOMSA .....11	LAMBDAOMS .....11	PRESCARRAY .....11	TRANSOREMARKS ...11	TRANSOUTREADTABLE 11
EDITCOMSL .....11	MAXLOOP .....11	TESTRAN .....11	TRANSORGLOBALS ...11	USERMACROS .....11
EDITHISTALIST ....12	NLISTPCOMS .....11	TRANSITCONSES ....11	TRANSORMACROS ...10	

---

PROPERTY INDEX

TAILP .....11	TRANSOR .....11
---------------	-----------------

---