

File created: 8-Apr-92 22:04:29 {DSK}<usr>local>lde>lispcore>sources>PROFILE.;2

changes to: (PROFILES "COMMON-LISP")
(IL:VARS IL:PROFILECOMS)

previous date: 16-May-90 21:15:43 {DSK}<usr>local>lde>lispcore>sources>PROFILE.;1

Read Table: XCL

Package: XEROX-COMMON-LISP

Format: XCCS

; Copyright (c) 1986, 1987, 1990, 1992 by Venue & Xerox Corporation. All rights reserved.

```
(IL:RPAQQ IL:PROFILECOMS
  ;; The profile type
  (IL:DEFINE-TYPES PROFILES)
  (IL:FUNCTIONS DEFPROFILE)
  (IL:TYPES PROFILE)
  (IL:STRUCTURES PROFILE-CLAUSE VARIABLE-DEFINITION)
  (IL:VARIABLES *PROFILE* *PROFILE-NAME* *PROFILE-VARIABLES* *PROFILES*)
  (IL:FUNCTIONS FIND-VARIABLE-DEFINITION IN-PROFILE INSTALL-PROFILE MAKE-VARIABLE-DEFINITION PROFILIZE
    PROFILE-ENTRY-VALUE PROFILE-ENTRY-VALUE-NAME PROFILE-NAME PROFILE-P PROFILE-VALUE-TYPE-CHECK
    SETF-PROFILE-ENTRY-VALUE SETF-PROFILE-ENTRY-VALUE-NAME SETF-PROFILE-NAME MAKE-PROFILE
    COPY-PROFILE RESTORE-PROFILE SAVE-PROFILE WITH-PROFILE FIND-PROFILE SETF-FIND-PROFILE
    LIST-ALL-PROFILES PROFILE-VALUES PROFILE-VARIABLES)
  (IL:SETFS FIND-PROFILE PROFILE-ENTRY-VALUE PROFILE-ENTRY-VALUE-NAME PROFILE-NAME)
  (PROFILES "READ-PRINT" "LISP" "INTERLISP" "OLD-INTERLISP-T" "XEROX-COMMON-LISP" "COMMON-LISP")
  (IL:DECLARE\ IL:DONTCOPY IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE (IL:LOCALVARS . T))
  (IL:PROP (IL:MAKEFILE-ENVIRONMENT IL:FILETYPE)
    IL:PROFILE)))
```

;; The profile type

```
(DEF-DEFINE-TYPE PROFILES "interaction profiles")

(DEFDEFINER (DEFPROFILE (:NAME (LAMBDA (WHOLE)
  (LET ((NAME-CLAUSE (SECOND WHOLE)))
    (IF (CONSP NAME-CLAUSE)
      (STRING (CAR NAME-CLAUSE))
      (STRING NAME-CLAUSE)))))
  PROFILES (NAME-CLAUSE &REST VARIABLE-CLAUSES)
  "Creates a new named profile. name . clauses or (name (:nicknames n1 n2...)) clauses"
  (LET ((NAME (IF (CONSP NAME-CLAUSE)
    (STRING (CAR NAME-CLAUSE))
    (STRING NAME-CLAUSE)))
    (NICKNAMES (AND (CONSP NAME-CLAUSE)
      (MAPCAR #'STRING (CDADR NAME-CLAUSE)))))
    `(LET ((PROFILE (MAKE-PROFILE ,NAME ,@(MAPCAR #'(LAMBDA (CLAUSE)
      `` ,CLAUSE)
      VARIABLE-CLAUSES))))
      (INSTALL-PROFILE PROFILE ,NAME ',NICKNAMES))))))

(DEFETYPE PROFILE ()
  `(SATISFIES PROFILE-P))
```

```
(DEFSTRUCT (PROFILE-CLAUSE (:TYPE LIST)
  (:CONSTRUCTOR NIL))
  VARIABLE
  NAME
  TYPE
  COERCION-FUNCTION
  NAME-FUNCTION)
```

```
(DEFSTRUCT (VARIABLE-DEFINITION (:TYPE LIST)
  (:CONSTRUCTOR NIL))
  VARIABLE
  TYPE
  COERCION-FUNCTION
  NAME-FUNCTION)
```

```
(DEFPARAMETER *PROFILE* "XCL"
  "The default or current profile.")
```

```
(DEFPARAMETER *PROFILE-NAME* NIL)
```

```
(DEFPARAMETER *PROFILE-VARIABLES*
  ' ((*PROFILE-NAME* T IDENTITY IDENTITY))
```

```

(*EVAL-FUNCTION* (MEMBER IL:EVAL EVAL)
  IDENTITY IDENTITY)
(*EXEC-PROMPT* STRING STRING IDENTITY)
(*DEBUGGER-PROMPT* STRING STRING IDENTITY)
(*READTABLE* READTABLE IL:FIND-READTABLE IL:READTABLE-NAME)
(*READ-BASE* (INTEGER 2 36)
  IDENTITY IDENTITY)
(*READ-SUPPRESS* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PACKAGE* PACKAGE FIND-PACKAGE PACKAGE-NAME)
(*READ-DEFAULT-FLOAT-FORMAT* (MEMBER SINGLE-FLOAT DOUBLE-FLOAT LONG-FLOAT SHORT-FLOAT)
  IDENTITY IDENTITY)
(*PRINT-ESCAPE* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-PRETTY* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-CIRCLE* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-BASE* (INTEGER 2 36)
  IDENTITY IDENTITY)
(*PRINT-RADIX* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-CASE* (MEMBER :DOWNCASE :UPCASE :CAPITALIZE)
  IDENTITY IDENTITY)
(*PRINT-GENSYM* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-LEVEL* (OR NULL FIXNUM)
  IDENTITY IDENTITY)
(*PRINT-LENGTH* (OR NULL FIXNUM)
  IDENTITY IDENTITY)
(*PRINT-ARRAY* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-STRUCTURE* (MEMBER NIL T)
  IDENTITY IDENTITY)))

(DEFGLOBALVAR *PROFILES* (MAKE-HASH-TABLE :TEST 'EQUAL)
  "Where profiles live.")

(DEFUN FIND-VARIABLE-DEFINITION (VARIABLE)
  (DOLIST (ENTRY *PROFILE-VARIABLES* NIL)
    (IF (EQ VARIABLE (VARIABLE-DEFINITION-VARIABLE ENTRY))
      (RETURN ENTRY))))

(DEFUN IN-PROFILE (PROFILE)
  "Makes profile the current profile and resets *profile*"
  (SETQ *PROFILE* (PROFILIZE PROFILE))
  (RESTORE-PROFILE *PROFILE*))

(DEFUN INSTALL-PROFILE (PROFILE PROFILE-NAME PROFILE-NICKNAMES)
  (DOLIST (NAME (CONS PROFILE-NAME PROFILE-NICKNAMES))
    (IF (AND (FIND-PROFILE NAME)
      (FBOUNDP 'WARN))
      (WARN "Resetting profile ~s." NAME)
      (SETF (FIND-PROFILE NAME)
        PROFILE))))
  ; Make the name and all nicknames point at the new profile.

(DEFUN MAKE-VARIABLE-DEFINITION (CLAUSE &AUX (DEFINITION NIL))
  "Add a new profile variable entry based on clauses.  clauses is bounded by a keyword or nil."
  (DOLIST (DEFAULT ' (NIL
    IGNORE ; variable
    T ; value
    IDENTITY ; type
    IDENTITY ; coercion-function
    IDENTITY ; name-function
  )
    ; Defaults for a definition's slots.
  )
    ; Maps on defaults to always fill all the slots.
    (IF (EQ DEFAULT ' IGNORE)
      (POP CLAUSE) ; Ignore the value slot
      (PUSH
        (IF (NULL CLAUSE)
          DEFAULT ; Push onto the new entry
          (POP CLAUSE) ; If we're at the end of the clause:
        ) ; ...use the default.
        ) ; ...otherwise use the next element of the clause.
      )
    )
  (SETQ DEFINITION (NREVERSE DEFINITION))
  (PUSH DEFINITION
    *PROFILE-VARIABLES*)
  DEFINITION)
  ; Flip the push built list.
  ; Put the new definition onto the global list of definitions.

```

```

(DEFUN PROFILIZE (NAME-OR-PROFILE)
  (ETYPESCASE NAME-OR-PROFILE
    ((OR STRING SYMBOL) (OR (FIND-PROFILE NAME-OR-PROFILE)
      (ERROR "Not the name of an existing profile ~s" NAME-OR-PROFILE)))
    (PROFILE NAME-OR-PROFILE)))

(DEFUN PROFILE-ENTRY-VALUE (VARIABLE &OPTIONAL (PROFILE *PROFILE*))
  "Returns the value of the variable in the current profile or its binding."
  (GETF (PROFILIZE PROFILE)
    VARIABLE
    (EVAL VARIABLE)))

(DEFUN PROFILE-ENTRY-VALUE-NAME (VARIABLE &OPTIONAL (PROFILE *PROFILE*))
  "Get the name of the value in a variable or the name of the current binding."
  (FUNCALL (VARIABLE-DEFINITION-NAME-FUNCTION (FIND-VARIABLE-DEFINITION VARIABLE))
    (GETF (PROFILIZE PROFILE)
      VARIABLE
      (EVAL VARIABLE))))

(DEFUN PROFILE-NAME (&OPTIONAL (PROFILE *PROFILE*))
  "Returns the name of the profile as a string."
  (PROFILE-ENTRY-VALUE '*PROFILE-NAME* (PROFILIZE PROFILE)))

(DEFUN PROFILE-P (OBJECT)
  "Returns true if the object seems to be a profile. Is true only of profiles, never their names."
  (AND (CONSP OBJECT)
    (SYMBOLP (FIRST OBJECT))
    (EVENP (LENGTH OBJECT))
    T))

(DEFUN PROFILE-VALUE-TYPE-CHECK (DEFINITION VALUE)
  "Returns correct or corrected value."
  (LET ((COERCION-FUNCTION (VARIABLE-DEFINITION-COERCION-FUNCTION DEFINITION))
    (TYPE (VARIABLE-DEFINITION-TYPE DEFINITION)))
    (LOOP (IF (TYPEP VALUE TYPE) ; Is it of the right type?
      (RETURN VALUE) ; ...just return it

      )
      (COND
        (COERCION-FUNCTION (SETQ VALUE (FUNCALL COERCION-FUNCTION VALUE))
          ; Perhaps it was a name, coerce it.
          (IF (TYPEP VALUE TYPE) ; Is it NOW of the right type?
            (RETURN VALUE) ; ...just return it

            )))
        )))
    ;; Otherwise we were given something that can't either use or coerce; complain, fix and retry
    (CERROR "Give new value" "Profile slot ~s's value ~s not a(n) ~s" (VARIABLE-DEFINITION-VARIABLE
      DEFINITION)
      VALUE TYPE)
    (FORMAT *QUERY-IO* "Give new value expression (will be evaluated)~%"
      (SETQ VALUE (EVAL (READ)))))

(DEFUN SETF-PROFILE-ENTRY-VALUE (VARIABLE PROFILE VALUE)
  (SETQ PROFILE (PROFILIZE PROFILE))
  (LET ((TYPE (VARIABLE-DEFINITION-TYPE (FIND-VARIABLE-DEFINITION VARIABLE))))
    (ASSERT (TYPEP VALUE TYPE)
      (VALUE)
      "Profile slot ~s's value ~s not a(n) ~s" VARIABLE VALUE TYPE)
    (SETF (GETF PROFILE VARIABLE)
      VALUE)))

(DEFUN SETF-PROFILE-ENTRY-VALUE-NAME (VARIABLE PROFILE NAME)
  (SETQ PROFILE (PROFILIZE PROFILE))
  (SETF (PROFILE-ENTRY-VALUE VARIABLE PROFILE)
    (FUNCALL (VARIABLE-DEFINITION-COERCION-FUNCTION (FIND-VARIABLE-DEFINITION VARIABLE))
      NAME)))

(DEFUN SETF-PROFILE-NAME (PROFILE NAME)
  (SETF (PROFILE-ENTRY-VALUE '*PROFILE-NAME* PROFILE)
    (STRING NAME)))

(DEFUN MAKE-PROFILE (PROFILE-NAME &REST CLAUSES)
  "Creates a profile with slots described by the clauses. Clauses is an alist of variables and values, similar
  to defstruct's."
  (LET ((PROFILE NIL))
    (DOLIST (CLAUSE CLAUSES)
      (LET* ((VARIABLE (PROFILE-CLAUSE-VARIABLE CLAUSE))

```

```

(NAME (PROFILE-CLAUSE-NAME CLAUSE)) ; Name of the value to be used (or the value itself).
(DEFINITION (OR (FIND-VARIABLE-DEFINITION VARIABLE)
                (MAKE-VARIABLE-DEFINITION CLAUSE))))

```

;; These are pushed on in reverse order so the final prop list format of the profile will be correct.

```

(PUSH (PROFILE-VALUE-TYPE-CHECK DEFINITION (EVAL NAME))
      PROFILE)
(PUSH VARIABLE PROFILE))
(CONS ' *PROFILE-NAME* (CONS PROFILE-NAME PROFILE)))

```

```

(DEFUN COPY-PROFILE (&OPTIONAL (PROFILE *PROFILE*))
  "Copies the given profile."
  (COPY-SEQ (PROFILIZE PROFILE)))

```

```

(DEFUN RESTORE-PROFILE (&OPTIONAL (PROFILE *PROFILE*))
  "Set profile variables from given profile."
  (SETQ PROFILE (PROFILIZE PROFILE))
  (MAPC #'SET (PROFILE-VARIABLES PROFILE)
        (PROFILE-VALUES PROFILE))
  PROFILE)

```

```

(DEFUN SAVE-PROFILE (&OPTIONAL (PROFILE *PROFILE*))
  "Save current values of bindings into profile."
  (IL:FOR X IL:ON (PROFILIZE PROFILE) IL:BY CDDR IL:DO (SETF (CADR X)
                                                              (EVAL (CAR X))))
  PROFILE)

```

```

(DEFMACRO WITH-PROFILE (PROFILE-FORM &BODY FORMS)
  "Bind all the special IO variables to the values in the profile and execute the body forms."
  `(LET ((*PROFILE* ,PROFILE-FORM)
        (SETQ *PROFILE* (PROFILIZE *PROFILE*))
        (PROGV (PROFILE-VARIABLES *PROFILE*)
                (PROFILE-VALUES *PROFILE*)
                ,@FORMS)))

```

```

(DEFUN FIND-PROFILE (NAME)
  (GETHASH (STRING NAME)
           *PROFILES*))

```

```

(DEFUN SETF-FIND-PROFILE (NAME PROFILE)
  (SETQ NAME (STRING NAME))
  (SETQ PROFILE (PROFILIZE PROFILE))
  (SETF (GETHASH NAME *PROFILES*)
        PROFILE)
  (SETF (PROFILE-NAME PROFILE)
        NAME)
  NAME)

```

```

(DEFUN LIST-ALL-PROFILES ()
  (LET ((PROFILES NIL))
    (MAPHASH #'(LAMBDA (NAME VALUE)
                  (PUSHNEW VALUE PROFILES :TEST #'EQ) ; Avoid repeats due to nicknames
                  ))
    *PROFILES*)
  (MAPCAR #'(LAMBDA (PROFILE)
                (PROFILE-NAME PROFILE) ; Convert to name strings
                ))
  PROFILES)))

```

```

(DEFUN PROFILE-VALUES (PROFILE)
  (IL:FOR X IL:IN (CDR (PROFILIZE PROFILE)) IL:BY CDDR IL:COLLECT X))

```

```

(DEFUN PROFILE-VARIABLES (&OPTIONAL (PROFILE *PROFILE*))
  (IL:FOR X IL:IN (PROFILIZE PROFILE) IL:BY CDDR IL:COLLECT X))

```

```

(DEFSETF FIND-PROFILE SETF-FIND-PROFILE)

```

```

(DEFSETF PROFILE-ENTRY-VALUE SETF-PROFILE-ENTRY-VALUE)

```

```

(DEFSETF PROFILE-ENTRY-VALUE-NAME SETF-PROFILE-ENTRY-VALUE-NAME)

```

```

(DEFSETF PROFILE-NAME SETF-PROFILE-NAME)

```

```

(DEFPROFILE "READ-PRINT" (*READTABLE* "LISP")
  (*READ-BASE* 10)
  (*READ-SUPPRESS* NIL)
  (*PACKAGE* "USER")
  (*READ-DEFAULT-FLOAT-FORMAT* 'SINGLE-FLOAT)
  (*PRINT-ESCAPE* T)
  (*PRINT-PRETTY* NIL)
  (*PRINT-CIRCLE* NIL)
  (*PRINT-BASE* 10)
  (*PRINT-RADIX* NIL)
  (*PRINT-CASE* :UPCASE)
  (*PRINT-GENSYM* T)
  (*PRINT-LEVEL* NIL)
  (*PRINT-LENGTH* NIL)
  (*PRINT-ARRAY* NIL)
  (*PRINT-STRUCTURE* NIL))

(DEFPROFILE "LISP" (*READTABLE* "LISP")
  (*PACKAGE* "USER")
  (*EVAL-FUNCTION* 'EVAL)
  (*EXEC-PROMPT* "> ")
  (*DEBUGGER-PROMPT* "?: "))

(DEFPROFILE ("INTERLISP" (:NICKNAMES "IL")) (*READTABLE* "INTERLISP")
  (*PACKAGE* "INTERLISP")
  (*EVAL-FUNCTION* 'IL:EVAL)
  (*EXEC-PROMPT* "_ ")
  (*DEBUGGER-PROMPT* "_: "))

(DEFPROFILE "OLD-INTERLISP-T" (*READTABLE* "OLD-INTERLISP-T")
  (*PACKAGE* "INTERLISP")
  (*EVAL-FUNCTION* 'IL:EVAL)
  (*EXEC-PROMPT* "_ ")
  (*DEBUGGER-PROMPT* "_: "))

(DEFPROFILE ("XEROX-COMMON-LISP" (:NICKNAMES "XCL")) (*READTABLE* "XCL")
  (*PACKAGE* "CL-USER")
  (*EVAL-FUNCTION* 'EVAL)
  (*EXEC-PROMPT* "> ")
  (*DEBUGGER-PROMPT* "?: "))

(DEFPROFILE ("COMMON-LISP" (:NICKNAMES "CL")) (*READTABLE* "LISP")
  (*PACKAGE* "CL-USER")
  (*EVAL-FUNCTION* 'EVAL)
  (*EXEC-PROMPT* "> ")
  (*DEBUGGER-PROMPT* "?: "))

(IL:DECLARE\ : IL:DONTCOPY IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE

(IL:DECLARE\ : IL:DOEVAL@COMPILE IL:DONTCOPY

(IL:LOCALVARS . T)
)
)

(IL:PUTPROPS IL:PROFILE IL:MAKEFILE-ENVIRONMENT (:READTABLE "XCL" :PACKAGE "XCL"))

(IL:PUTPROPS IL:PROFILE IL:FILETYPE COMPILE-FILE)

(IL:PUTPROPS IL:PROFILE IL:COPYRIGHT ("Venue & Xerox Corporation" 1986 1987 1990 1992))

```

FUNCTION INDEX

COPY-PROFILE	4	PROFILE-ENTRY-VALUE	3	RESTORE-PROFILE	4
FIND-PROFILE	4	PROFILE-ENTRY-VALUE-NAME	3	SAVE-PROFILE	4
FIND-VARIABLE-DEFINITION	2	PROFILE-NAME	3	SETF-FIND-PROFILE	4
IN-PROFILE	2	PROFILE-P	3	SETF-PROFILE-ENTRY-VALUE	3
INSTALL-PROFILE	2	PROFILE-VALUE-TYPE-CHECK	3	SETF-PROFILE-ENTRY-VALUE-NAME	3
LIST-ALL-PROFILES	4	PROFILE-VALUES	4	SETF-PROFILE-NAME	3
MAKE-PROFILE	3	PROFILE-VARIABLES	4		
MAKE-VARIABLE-DEFINITION	2	PROFILIZE	3		

PROFILE INDEX

"COMMON-LISP"	5	"LISP"	5	"READ-PRINT"	5
"INTERLISP"	5	"OLD-INTERLISP-T"	5	"XEROX-COMMON-LISP"	5

SETF INDEX

FIND-PROFILE	4	PROFILE-ENTRY-VALUE	4	PROFILE-ENTRY-VALUE-NAME	4	PROFILE-NAME	4
--------------	---	---------------------	---	--------------------------	---	--------------	---

VARIABLE INDEX

PROFILE	1	*PROFILE-NAME*	1	*PROFILE-VARIABLES*	1	*PROFILES*	2
-----------	---	----------------	---	---------------------	---	------------	---

STRUCTURE INDEX

PROFILE-CLAUSE	1	VARIABLE-DEFINITION	1
----------------	---	---------------------	---

PROPERTY INDEX

IL:PROFILE	5
------------	---

TYPE INDEX

PROFILE	1
---------	---

MACRO INDEX

WITH-PROFILE	4
--------------	---

DEFINER INDEX

DEFPROFILE	1
------------	---

DEFINE-TYPE INDEX

PROFILES	1
----------	---