

File created: 12-Jun-90 17:31:06 {DSK}<usr>local>lde>lispcore>library>TCPHTE.;3

changes to: (VARS TCPHTECOMS)

previous date: 11-Feb-89 11:06:54 {DSK}<usr>local>lde>lispcore>library>TCPHTE.;2

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

```
::  
;; Copyright (c) 1985, 1987, 1988, 1989, 1990 by Venue & Xerox Corporation. All rights reserved.
```

```
(RPAQQ TCPHTECOMS  
  ((PROP MAKEFILE-ENVIRONMENT TCPHTE)  
   (RECORDS HOSTS.TXT.ENTRY)  
   (FNS \HTE.PARSE.ENTRY \HTE.READ.FILE \HTE.READ; \HTE.READLINE)  
   (INITVARS (HOSTS.TEXT.DIRECTORIES)  
              (\HTE.RDTBL))  
   (DECLARE%: EVAL@COMPILE DONTCOPY (GLOBALVARS \HTE.RDTBL \IP.HOSTNAMES)  
      (RECORDS HTELINE))))  
  
(PUTPROPS TCPHTE MAKEFILE-ENVIRONMENT (:PACKAGE "IL" :READTABLE "INTERLISP"))  
  
(DECLARE%: EVAL@COMPILE  
  
(DATATYPE HOSTS.TXT.ENTRY (HTE.TYPE HTE.ADDRESSES HTE.NAMES HTE.MACHINE.TYPE HTE.OS.TYPE HTE.PROTOCOLS))  
)  
  
(/DECLAREDATATYPE 'HOSTS.TXT.ENTRY ' (POINTER POINTER POINTER POINTER POINTER POINTER)  
  ;---field descriptor list elided by lister---  
  ' 12)  
  
(DEFINEQ  
  
(\HTE.PARSE.ENTRY  
  [LAMBDA (ENTRY) ; Edited 11-Feb-89 11:04 by akw:  
    (DECLARE (GLOBALVARS NETWORKOSTYPES))  
    (LET* [(NAMES (for NAME in (fetch (HTELINE NAMES) of ENTRY) collect (MKATOM (U-CASE NAME)  
      (OSTYPE (CAR (fetch (HTELINE OS.TYPE) of ENTRY))  
      (MKATOM (U-CASE)))  
      (HTE.ENTRY (create HOSTS.TXT.ENTRY  
        HTE.TYPE _ (CAR (fetch (HTELINE TYPE) of ENTRY))  
        HTE.ADDRESSES _ (for X in (fetch (HTELINE ADDRESSES) of ENTRY) collect (\IP.READ.STRING.ADDRESS X))  
        HTE.NAMES _ NAMES  
        HTE.MACHINE.TYPE _ [MKATOM (U-CASE (CAR (fetch (HTELINE MACHINE.TYPE) of ENTRY)  
        HTE.OS.TYPE _ [AND OSTYPE (SETQ OSTYPE (MKATOM (U-CASE OSTYPE)  
        HTE.PROTOCOLS _ (for PROTOENTRY in (fetch (HTELINE PROTOCOLS) of ENTRY) bind SLASH  
          when (SETQ SLASH (STRPOS '/ PROTOENTRY))  
          collect (CONS (SUBATOM PROTOENTRY 1 (SUB1 SLASH))  
            (SUBATOM PROTOENTRY (ADD1 SLASH))  
        (for NAME in NAMES do (PUTHASH NAME HTE.ENTRY \IP.HOSTNAMES]))  
  
(\HTE.READ.FILE  
  [LAMBDA (FILE WANTEDTYPES) ; Edited 24-May-88 16:57 by bvm  
    (DECLARE (GLOBALVARS \IP.HOSTNAMES \TCP.LAST.HOSTS.FILE.DATE \TCP.LAST.HOSTS.FILE.READ))  
    [OR WANTEDTYPES (SETQ WANTEDTYPES ' (HOST]  
    (CL:WITH-OPEN-FILE (STREAM FILE)  
      (LET ((FILENAME (FULLNAME STREAM))  
          (DATE (GETFILEINFO STREAM 'ICREATIONDATE))  
          ENTRY)  
        (PRINTOUT PROMPTWINDOW T "Reading " FILENAME " of " (GDATE DATE (DATEFORMAT NO.SECONDS)))  
        (CLRHASH \IP.HOSTNAMES)  
        (until (EOFP STREAM) when (AND (SETQ ENTRY (\HTE.READLINE STREAM WANTEDTYPES))  
          (FMEMB (CAR (fetch (HTELINE TYPE) of ENTRY))  
            WANTEDTYPES))  
          do (\HTE.PARSE.ENTRY ENTRY))  
        (SETQ \TCP.LAST.HOSTS.FILE.DATE DATE)  
        (SETQ \TCP.LAST.HOSTS.FILE.READ FILENAME]))  
  
(\HTE.READ;  
  [LAMBDA (FL RDTBL) ; Edited 24-May-88 14:45 by bvm  
    (until (SELCHARQ (READCCODE FL)  
      ((CR LF EOL)  
        T)  
      NIL))  
    NIL))  
  
(\HTE.READLINE
```

```

[LAMBDA (STREAM WANTEDTYPES)
  (while (EQ (PEEKCCODE STREAM T)
    (CHARCODE " ;"))
    do (\HTE.READ; STREAM))
  (AND (NOT (EOFP STREAM))
    (for FIELD# from 1 bind FIELDCONTENTS DONE (RDTBL _ (COND
      (\HTE.RDTBL)
      (T (SETQ \HTE.RDTBL (COPYREADTABLE 'ORIG))
        (SETSEPR (CHARCODE (SPACE TAB % ,))
          NIL \HTE.RDTBL)
        (SETBRK (CHARCODE (" : " " ; " CR LF))
          NIL \HTE.RDTBL)
        (READTABLEPROP \HTE.RDTBL 'CASEINSENSITIVE T)
        \HTE.RDTBL)))
      until DONE collect [SETQ FIELDCONTENTS (until (SELCHARQ (SKIPSEPRCODES STREAM RDTBL)
        ( " : " ; End of field
          (READCCODE STREAM)
          T)
        ( " ; " ; end of line
          (\HTE.READ; STREAM)
          (SETQ DONE T))
        ((CR LF)
          ; end of line--consume the terminator
          (READCCODE STREAM)
          (SETQ DONE T))
        (NIL ; Eof
          (SETQ DONE T))
        NIL)
      collect ; Read up to the next field delimiter
      (if (EQ FIELD# 1)
        then
          ; Canonicalize the type field
          (READ STREAM RDTBL)
        else (RSTRING STREAM RDTBL])
      (if (AND (EQ FIELD# 1)
        WANTEDTYPES
        (NOT (FMEMB (CAR FIELDCONTENTS)
          WANTEDTYPES)))
        then ; Don't care about this line
          (OR DONE (\HTE.READ; STREAM))
          (RETURN NIL))
      FIELDCONTENTS])
    )
  )
(RPAQ? HOSTS.TEXT.DIRECTORIES )
(RPAQ? \HTE.RDTBL )
(DECLARE%: EVAL@COMPILE DONTCOPY
(DECLARE%: DOEVAL@COMPILE DONTCOPY
(GLOBALVARS \HTE.RDTBL \IP.HOSTNAMES)
)
(DECLARE%: EVAL@COMPILE
(RECORD HTELINE (TYPE ADDRESSES NAMES MACHINE.TYPE OS.TYPE PROTOCOLS))
)
)
(PUTPROPS TCPHTE COPYRIGHT ("Venue & Xerox Corporation" 1985 1987 1988 1989 1990))

```

FUNCTION INDEX

\HTE.PARSE.ENTRY1 \HTE.READ.FILE1 \HTE.READ;1 \HTE.READLINE1

RECORD INDEX

HOSTS.TXT.ENTRY1 HTELINE2

VARIABLE INDEX

HOSTS.TEXT.DIRECTORIES ..2 \HTE.RDTBL2

PROPERTY INDEX

TCPHTE1