

Complementos de Programação de Computadores – Aula 5b

Input e Output com Streams

Mestrado Integrado em Electrónica Industrial e Computadores

Luís Paulo Reis

lpreis@dsi.uminho.pt

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,
Universidade do Minho, Portugal

(Slides Baseados em P.Deitel e H.Deitel 2010)



Outline (I)

- **21.1 Introduction**
- **21.2 Streams**
- **21.3 Stream Output**
 - 21.3.1 Stream-Insertion Operator
 - 21.3.2 Cascading Stream-Insertion/Extraction Operators
 - 21.3.3 Output of `char*` Variables
 - 21.3.4 Character Output with Member Function `put`; Cascading `puts`
- **21.4 Stream Input**
 - 21.4.1 Stream-Extraction Operator
 - 21.4.2 `get` and `getline` Member Functions
 - 21.4.3 `istream` Member Functions `peek`, `putback` and `ignore`
 - 21.4.4 Type-Safe I/O
- **21.5 Unformatted I/O with `read`, `gcount` and `write`**

Outline (II)

- **21.6 Stream Manipulators**
 - 21.6.1 Integral Stream Base: `dec`, `oct`, `hex` and `setbase`
 - 21.6.2 Floating-Point Precision (`precision`, `setprecision`)
 - 21.6.3 Field Width (`setw`, `width`)
 - 21.6.4 User-Defined Manipulators
- **21.7 Stream Format States**
 - 21.7.1 Format State Flags
 - 21.7.2 Trailing Zeros and Decimal Points (`ios::showpoint`)
 - 21.7.3 Justification (`ios::left`, `ios::right`, `ios::internal`)
 - 21.7.4 Padding (`fill`, `setfill`)
 - 21.7.5 Integral Stream Base (`ios::dec`, `ios::oct`, `ios::hex`, `ios::showbase`)
 - 21.7.6 Floating-Point Numbers; Scientific Notation (`ios::scientific`, `ios::fixed`)
 - 21.7.7 Uppercase/Lowercase Control (`ios::uppercase`)
 - 21.7.8 Setting and Resetting the Format Flags (`flags`, `setiosflags`, `resetiosflags`)
- **21.8 Stream Error States**
- **21.9 Tying an Output Stream to an Input Stream**



Objectives

- To understand how to use C++ object-oriented stream input/output
- To be able to format inputs and outputs
- To understand the stream I/O class hierarchy
- To understand how to input/output objects of user-defined types
- To be able to create user-defined stream manipulators
- To be able to determine the success or failure of input/output operations
- To be able to tie output streams to input streams



21.1 Introduction


- **Many C++ I/O features are object-oriented**
 - Use references, function overloading and operator overloading
- **C++ uses type safe I/O**
 - Each I/O operation is automatically performed in a manner sensitive to the data type
- **Extensibility**
 - Users may specify I/O of user-defined types as well as standard types

21.2 Streams

- **Stream: A transfer of information in the form of a sequence of bytes**
- **I/O Operations:**
 - Input: A stream that flows from an input device (i.e.: keyboard, disk drive, network connection) to main memory
 - Output: A stream that flows from main memory to an output device (i.e.: screen, printer, disk drive, network connection)
- **I/O operations are a bottleneck**
 - The time for a stream to flow is many times larger than the time it takes the CPU to process the data in the stream
- **Low-level I/O**
 - Unformatted, Individual byte unit of interest
 - High speed, high volume, but inconvenient for people
- **High-level I/O**
 - Formatted, Bytes grouped into meaningful units: integers, characters, etc.
 - Good for all I/O except high-volume file processing


21.2 Stream Input/Output Classes and Objects

- **iostream library:**
 - `<iostream.h>`: Contains `cin`, `cout`, `cerr` and `clog` objects
 - `<iomanip.h>`: Contains *parameterized stream manipulators*
- **ios: istream and ostream inherit from ios**
 - `iostream` inherits from `istream` and `ostream`.
- **<< (left-shift operator)**
 - Overloaded as *stream insertion operator*
- **>> (right-shift operator)**
 - Overloaded as *stream extraction operator*
 - Both operators used with `cin`, `cout`, `cerr`, `clog`, and with user-defined stream objects



21.2 Stream Input/Output Classes and Objects

- **istream: input streams**
 - `cin >> grade;`
 - `cin` knows what type of data is to be assigned to `grade` (based on the type of `grade`)
- **ostream: output streams**
 - `cout << grade;`
 - `cout` knows the type of data to output
 - `cerr << errorMessage;`
 - Unbuffered - prints `errorMessage` immediately
 - `clog << errorMessage;`
 - Buffered - prints `errorMessage` as soon as output buffer is full or flushed



21.3 Stream Output

- **ostream: performs formatted and unformatted output**
 - Uses `put` for characters and `write` for unformatted output
 - Output of integers in decimal, octal and hexadecimal
 - Varying precision for floating points
 - Formatted text outputs

Stream-Insertion Operator

- **<< is overloaded to output built-in types**
 - Can also be used to output user-defined types
 - `cout << '\n';`
 - Prints newline character
 - `cout << endl;`
 - `endl` is a stream manipulator that issues a newline character and flushes the output buffer
 - `cout << flush;`
 - `flush` flushes the output buffer



```
1 // Fig. 21.3: fig21_03.cpp
2 // Outputting a string using stream insertion.
3 #include <iostream>
4
5 using std::cout;
6
7 int main()
8 {
9     cout << "welcome to C++!\n";
10
11     return 0;
12 } // end function main
```

fig21_03.cpp

Welcome to C++!

Program Output



```

1 // Fig. 21.5: fig21_05.cpp
2 // Using the endl stream manipulator.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 int main()
9 {
10     cout << "Welcome to ";
11     cout << "C++!";
12     cout << endl; // end line stream manipulator
13
14     return 0;
15 } // end function main

```

Welcome to C++!

fig21_05.cpp

Program Output



```

1 // Fig. 21.6: fig21_06.cpp
2 // Outputting expression values.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 int main()
9 {
10     cout << "47 plus 53 is ";
11
12     // parentheses not needed; used for clarity
13     cout << ( 47 + 53 ); // expression
14     cout << endl;
15
16     return 0;
17 } // end function main

```

47 plus 53 is 100

fig21_06.cpp

Program Output



21.3.2 Cascading Stream-Insertion/Extraction Operators

- **<< : Associates from left to right, and returns a reference to its left-operand object (i.e. cout).**

– This enables cascading:

```
cout << "How" << " are" << " you?";
```

Make sure to use parenthesis:

```
cout << "1 + 2 = " << (1 + 2);
```

NOT

```
cout << "1 + 2 = " << 1 + 2;
```



```
1 // Fig. 21.7: fig21_07.cpp
2 // Cascading the overloaded << operator.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 int main()
9 {
10     cout << "47 plus 53 is " << ( 47 + 53 ) << endl;
11
12     return 0;
13 } // end function main
```

47 plus 53 is 100

fig21_07.cpp

Program Output

21.3.3 Output of char * Variables

- << will output a variable of type char * as a string
- To output the address of the first character of that string, cast the variable as type void *



```
1 // Fig. 21.8: fig21_08.cpp
2 // Printing the address stored in a char* variable
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 int main()
9 {
10     const char *string = "test";
11
12     cout << "Value of string is: " << string
13         << "\nValue of static_cast< void * >( string ) is: "
14         << static_cast< void * >( string ) << endl;
15     return 0;
16 } // end function main
```

fig21_08.cpp

```
Value of string is: test
Value of static_cast< void * >( string ) is: 0046C070
```

Program Output



21.3.4 Character Output with Member Function `put`; Cascading `puts`

- **`put` member function**
 - Outputs one character to specified stream
`cout.put('A');`
 - Returns a reference to the object that called it, so may be cascaded
`cout.put('A').put('\n');`
 - May be called with an ASCII-valued expression
`cout.put(65);`
 - Outputs A

21.4 Stream Input

- **`>>` (stream-extraction)**
 - Used to perform stream input
 - Normally ignores whitespaces (spaces, tabs, newlines)
 - Returns zero (`false`) when EOF is encountered, otherwise returns reference to the object from which it was invoked (i.e. `cin`)
- **`>>` controls the state bits of the stream**
 - `failbit` set if wrong type of data input
 - `badbit` set if the operation fails

21.4.1 Stream-Extraction Operator

- **>> and << have relatively high precedence**
 - Conditional and arithmetic expressions must be contained in parentheses
- **Popular way to perform loops**
 - while (cin >> grade)
 - Extraction returns 0 (false) when EOF encountered, and loop ends



```
1 // Fig. 21.9: fig21_09.cpp
2 // Calculating the sum of two integers input from the keyboard
3 // with cin and the stream-extraction operator.
4 #include <iostream>
5
6 using std::cout;
7 using std::cin;
8 using std::endl;
9
10 int main()
11 {
12     int x, y;
13
14     cout << "Enter two integers: ";
15     cin >> x >> y;
16     cout << "Sum of " << x << " and " << y << " is: "
17         << ( x + y ) << endl;
18
19     return 0;
20 } // end function main
```

fig21_09.cpp

```
Enter two integers: 30 92
Sum of 30 and 92 is: 122
```

Program Output



```

1 // Fig. 21.10: fig21_10.cpp
2 // Avoiding a precedence problem between the stream-insertion
3 // operator and the conditional operator.
4 // Need parentheses around the conditional expression.
5 #include <iostream>
6
7 using std::cout;
8 using std::cin;
9 using std::endl;
10
11 int main()
12 {
13     int x, y;
14
15     cout << "Enter two integers: ";
16     cin >> x >> y;
17     cout << x << ( x == y ? " is" : " is not" )
18         << " equal to " << y << endl;
19
20     return 0;
21 } // end function main

```

fig21_10.cpp

```

Enter two integers: 7 5
7 is not equal to 5
Enter two integers: 8 8
8 is equal to 8

```

Program Output



```

1 // Fig. 21.11: fig21_11.cpp
2 // Stream-extraction operator returning false on end-of-file.
3 #include <iostream>
4
5 using std::cout;
6 using std::cin;
7 using std::endl;
8
9 int main()
10 {
11     int grade, highestGrade = -1;
12
13     cout << "Enter grade (enter end-of-file to end): ";
14     while ( cin >> grade ) {
15         if ( grade > highestGrade )
16             highestGrade = grade;
17
18         cout << "Enter grade (enter end-of-file to end): ";
19     } // end while
20
21     cout << "\n\nHighest grade is: " << highestGrade << endl;
22     return 0;
23 } // end function main

```

fig21_11.cpp

```

Enter grade (enter end-of-file to end): 67
Enter grade (enter end-of-file to end): 87
Enter grade (enter end-of-file to end): 73
Enter grade (enter end-of-file to end): 95
Enter grade (enter end-of-file to end): 34
Enter grade (enter end-of-file to end): 99
Enter grade (enter end-of-file to end): ^Z
Highest grade is: 99

```

Program Output



21.4.2 get and getLine Member Functions

- `cin.eof()`: returns true if end-of-file has occurred on `cin`
- `cin.get()`: inputs a character from stream (even white spaces) and returns it
- `cin.get(c)`: inputs a character from stream and stores it in `c`



```

1 // Fig. 21.12: fig21_12.cpp
2 // Using member functions get, put and eof.
3 #include <iostream>
4
5 using std::cout;
6 using std::cin;
7 using std::endl;
8
9 int main()
10 {
11     char c;
12
13     cout << "Before input, cin.eof() is " << cin.eof()
14         << "\nEnter a sentence followed by end-of-file:\n";
15
16     while ( ( c = cin.get() ) != EOF )
17         cout.put( c );
18
19     cout << "\nEOF in this system is: " << c;
20     cout << "\nAfter input, cin.eof() is " << cin.eof() << endl;
21     return 0;
22 } // end function main

```

fig21_12.cpp

Program Output

```

Before input, cin.eof() is 0
Enter a sentence followed by end-of-file:
Testing the get and put member functions
Testing the get and put member functions
^Z
EOF in this system is: -1
After input cin.eof() is 1

```



21.4.2 get and getline Member Functions

- **cin.get(array, size):**
 - Accepts 3 arguments: array of characters, the size limit, and a delimiter (default of ‘\n’).
 - Uses the array as a buffer
 - When the delimiter is encountered, it remains in the input stream
 - Null character is inserted in the array
 - Unless delimiter flushed from stream, it will stay there

- **cin.getline(array, size)**
 - Operates like cin.get(buffer, size) but it discards the delimiter from the stream and does not store it in array
 - Null character inserted into array



```

1 // Fig. 21.13: fig21_13.cpp
2 // Contrasting input of a string with cin and cin.get.
3 #include <iostream>
4
5 using std::cout;
6 using std::cin;
7 using std::endl;
8
9 int main()
10 {
11     const int SIZE = 80;
12     char buffer1[ SIZE ], buffer2[ SIZE ];
13
14     cout << "Enter a sentence:\n";
15     cin >> buffer1;
16     cout << "\nThe string read with cin was:\n"
17          << buffer1 << "\n\n";
18
19     cin.get( buffer2, SIZE );
20     cout << "The string read with cin.get was:\n"
21          << buffer2 << endl;
22
23     return 0;
24 } // end function main

```

fig21_13.cpp

Program Output

```

Enter a sentence:
Contrasting string input with cin and cin.get

The string read with cin was:
Contrasting

The string read with cin.get was:
string input with cin and cin.get

```



```

1 // Fig. 21.14: fig21_14.cpp
2 // Character input with member function getline.
3 #include <iostream>
4
5 using std::cout;
6 using std::cin;
7 using std::endl;
8
9 int main()
10 {
11     const SIZE = 80;
12     char buffer[ SIZE ];
13
14     cout << "Enter a sentence:\n";
15     cin.getline( buffer, SIZE );
16
17     cout << "\nThe sentence entered is:\n" << buffer << endl;
18     return 0;
19 } // end function main

```

fig21_14.cpp

Enter a sentence:
Using the getline member function

The sentence entered is:
Using the getline member function

Program Output



21.4.3 istream Member Functions peek, putback and ignore

- **ignore member function**
 - Skips over a designated number of characters (default of one)
 - Terminates upon encountering a designated delimiter (default is EOF, skips to the end of the file)
- **putback member function**
 - Places the previous character obtained by get back in to the stream
- **peek**
 - Returns the next character from the stream without removing it



21.4.4 Type-Safe I/O

- **<< and >> operators**
 - Overloaded to accept data of different types
 - When unexpected data encountered, error flags set
 - Program stays in control

21.5 Unformatted I/O with read, gcount and write

- **read and write member functions**
 - Unformatted I/O
 - Input/output raw bytes to or from a character array in memory
 - Since the data is unformatted, the functions will not terminate at a `\n` character for example
 - Instead, like `getline`, they continue to process a designated number of characters
 - If fewer than the designated number of characters are read, then the failbit is set
- **gcount:**
 - Returns the total number of characters read in the last input operation

```

1 // Fig. 21.15: fig21_15.cpp
2 // Unformatted I/O with read, gcount and write.
3 #include <iostream>
4
5 using std::cout;
6 using std::cin;
7 using std::endl;
8
9 int main()
10 {
11     const int SIZE = 80;
12     char buffer[ SIZE ];
13
14     cout << "Enter a sentence:\n";
15     cin.read( buffer, 20 );
16     cout << "\nThe sentence entered was:\n";
17     cout.write( buffer, cin.gcount() );
18     cout << endl;
19     return 0;
20 } // end function main

```

fig21_15.cpp

Enter a sentence:
Using the read, write and gcount member functions
The sentence entered was:
Using the read, writ

Program Output



21.6 Stream Manipulators

- **Stream manipulator capabilities**
 - Setting field widths
 - Setting precisions
 - Setting and unsetting format flags
 - Setting the fill character in fields
 - Flushing streams
 - Inserting a newline in the output stream and flushing the stream
 - Inserting a null character in the output stream and skipping whitespace in the input stream



21.6.1 Integral Stream Base: dec, oct, hex and setbase

- **oct, hex or dec:**

- Change base of which integers are interpreted from the stream.

Example:

```
int n = 15;  
cout << hex << n;  
– Prints "F"
```

- **setbase:**

- Changes base of integer output
- Load <iomanip>
- Accepts an integer argument (10, 8, or 16)
cout << setbase(16) << n;
– Parameterized stream manipulator - takes an argument



```
1 // Fig. 21.16: fig21_16.cpp  
2 // Using hex, oct, dec and setbase stream manipulators.  
3 #include <iostream>  
4  
5 using std::cout;  
6 using std::cin;  
7 using std::endl;  
8  
9 #include <iomanip>  
10  
11 using std::hex;  
12 using std::dec;  
13 using std::oct;  
14 using std::setbase;  
15  
16 int main()  
17 {  
18     int n;  
19  
20     cout << "Enter a decimal number: ";  
21     cin >> n;  
22
```

fig21_16.cpp
(Part 1 of 2)

```

23 cout << n << " in hexadecimal is: "
24     << hex << n << '\n'
25     << dec << n << " in octal is: "
26     << oct << n << '\n'
27     << setbase( 10 ) << n << " in decimal is: "
28     << n << endl;
29
30 return 0;
31 } // end function main

```

fig21_16.cpp
(Part 2 of 2)

```

Enter a decimal number: 20
20 in hexadecimal is: 14
20 in octal is: 24
20 in decimal is: 20

```

Program Output



21.6.2 Floating-Point Precision (precision, setprecision)

- **precision**
 - Member function
 - Sets number of digits to the right of decimal point
`cout.precision(2);`
 - `cout.precision()` returns current precision setting
- **setprecision**
 - Parameterized stream manipulator
 - Like all parameterized stream manipulators, `<iomanip>` required
 - Specify precision:
`cout << setprecision(2) << x;`
- **For both methods, changes last until a different value is set**



```

1 // Fig. 21.17: fig21_17.cpp
2 // Controlling precision of floating-point values
3 #include <iostream>
4
5 using std::cout;
6 using std::cin;
7 using std::endl;
8
9 #include <iomanip>
10
11 using std::ios;
12 using std::setiosflags;
13 using std::setprecision;
14
15 #include <cmath>
16
17 int main()
18 {
19     double root2 = sqrt( 2.0 );
20     int places;
21
22     cout << setiosflags( ios::fixed )
23         << "Square root of 2 with precisions 0-9.\n"
24         << "Precision set by the "
25         << "precision member function:" << endl;
26

```

fig21_17.cpp
(Part 1 of 2)



```

27     for ( places = 0; places <= 9; places++ ) {
28         cout.precision( places );
29         cout << root2 << '\n';
30     } // end for
31
32     cout << "\nPrecision set by the "
33         << "setprecision manipulator:\n";
34
35     for ( places = 0; places <= 9; places++ )
36         cout << setprecision( places ) << root2 << '\n';
37
38     return 0;
39 } // end function main

```

fig21_17.cpp (Part 2
of 2)



Square root of 2 with precisions 0-9.

Precision set by the precision member function:

```
1
1.4
1.41
1.414
1.4142
1.41421
1.414214
1.4142136
1.41421356
1.414213562
```

Precision set by the setprecision manipulator:

```
1
1.4
1.41
1.414
1.4142
1.41421
1.414214
1.4142136
1.41421356
1.414213562
```

Program Output



21.6.3 Field Width(setw, width)

- **ios width member function**
 - Sets field width (number of character positions a value should be output or number of characters that should be input)
 - Returns previous width
 - If values processed are smaller than width, fill characters inserted as padding
 - Values are not truncated - full number printed
 - `cin.width(5);`
- **setw stream manipulator**
`cin >> setw(5) >> string;`
- **Remember to reserve one space for the null character**



```

1 // fig21_18.cpp
2 // Demonstrating the width member function
3 #include <iostream>
4
5 using std::cout;
6 using std::cin;
7 using std::endl;
8
9 int main()
10 {
11     int w = 4;
12     char string[ 10 ];
13
14     cout << "Enter a sentence:\n";
15     cin.width( 5 );
16
17     while ( cin >> string ) {
18         cout.width( w++ );
19         cout << string << endl;
20         cin.width( 5 );
21     } // end while
22
23     return 0;
24 } // end function main

```

fig21_18.cpp



```

Enter a sentence:
This is a test of the width member function
This
    is
    a
test
    of
the
width
    h
memb
    er
func
    tion

```

Program Output



21.6.4 User-Defined Manipulators

- We can create our own stream manipulators
 - bell
 - ret (carriage return)
 - tab
 - endl
- Parameterized stream manipulators
 - Consult installation manuals



```
1 // Fig. 21.19: fig21_19.cpp
2 // Creating and testing user-defined, nonparameterized
3 // stream manipulators.
4 #include <iostream>
5
6 using std::ostream;
7 using std::cout;
8 using std::flush;
9
10 // bell manipulator (using escape sequence \a)
11 ostream& bell( ostream& output ) { return output << '\a'; }
12
13 // ret manipulator (using escape sequence \r)
14 ostream& ret( ostream& output ) { return output << '\r'; }
15
16 // tab manipulator (using escape sequence \t)
17 ostream& tab( ostream& output ) { return output << '\t'; }
18
19 // endl manipulator (using escape sequence \n
20 // and the flush member function)
21 ostream& endl( ostream& output )
22 {
23     return output << '\n' << flush;
24 } // end function endl
25
```

fig21_19.cpp
(Part 1 of 2)



```

26 int main()
27 {
28     cout << "Testing the tab manipulator:" << endl
29         << 'a' << tab << 'b' << tab << 'c' << endl
30         << "Testing the ret and bell manipulators:"
31         << endl << ".....";
32     cout << bell;
33     cout << ret << "----" << endl;
34     return 0;
35 } // end function main

```

fig21_19.cpp
(Part 2 of 2)

```

Testing the tab manipulator:
a      b      c
Testing the ret and bell manipulators:
----.....

```

Program Output



21.7 Stream Format States

- **Format flags**
 - Specify formatting to be performed during stream I/O operations
- **setf, unsetf and flags**
 - Member functions that control the flag settings
- **Format State Flags**
 - Defined as an enumeration in class `ios`
 - Can be controlled by member functions
 - `flags` - specifies a value representing the settings of all the flags
 - Returns long value containing prior options
 - `setf` - one argument, "ors" flags with existing flags
 - `unsetf` - unsets flags
 - `setiosflags` - parameterized stream manipulator used to set flags
 - `resetiosflags` - parameterized stream manipulator, has same functions as `unsetf`
- **Flags can be combined using bitwise OR (|)**



21.7.1 Format State Flags

Format state flag	Description
<code>ios::skipws</code>	Skip whitespace characters on an input stream.
<code>ios::left</code>	Left-justify output in a field. Padding characters appear to the right if necessary.
<code>ios::right</code>	Right-justify output in a field. Padding characters appear to the left if necessary.
<code>ios::internal</code>	Indicate that a number's sign should be left-justified in a field and a number's magnitude should be right-justified in that same field (i.e., padding characters appear between the sign and the number).
<code>ios::dec</code>	Specify that integers should be treated as decimal (base 10) values.
<code>ios::oct</code>	Specify that integers should be treated as octal (base 8) values.
<code>ios::hex</code>	Specify that integers should be treated as hexadecimal (base 16) values.
<code>ios::showbase</code>	Specify that the base of a number is to be output ahead of the number (a leading 0 for octals; a leading 0x or 0X for hexadecimal).
<code>ios::showpoint</code>	Specify that floating-point numbers should be output with a decimal point. This is normally used with <code>ios::fixed</code> to guarantee a certain number of digits to the right of the decimal point.
<code>ios::uppercase</code>	Specify that uppercase letters (i.e., X and A through F) should be used in the hexadecimal integer and that uppercase E should be used when representing a floating-point value in scientific notation.
<code>ios::showpos</code>	Specify that positive and negative numbers should be preceded by a + or - sign, respectively.
<code>ios::scientific</code>	Specify output of a floating-point value in scientific notation.
<code>ios::fixed</code>	Specify output of a floating-point value in fixed-point notation with a specific number of digits to the right of the decimal point.

Fig. 21.20 Format state flags.

21.7.2 Trailing Zeros and Decimal Points (`ios::showpoint`)

- `ios::showpoint`
 - Forces a float with an integer value to be printed with its decimal point and trailing zeros

```
cout.setf(ios::showpoint)
```

```
cout << 79;
```

79 will print as 79.00000

- Number of zeros determined by precision settings


```

1 // Fig. 21.21: fig21_21.cpp
2 // Controlling the printing of trailing zeros and decimal
3 // points for floating-point values.
4 #include <iostream>
5
6 using std::cout;
7 using std::endl;
8
9 #include <iomanip>
10
11 using std::ios;
12
13 #include <cmath>
14
15 int main()
16 {
17     cout << "Before setting the ios::showpoint flag\n"
18         << "9.9900 prints as: " << 9.9900
19         << "\n9.9000 prints as: " << 9.9000
20         << "\n9.0000 prints as: " << 9.0000
21         << "\n\nAfter setting the ios::showpoint flag\n";
22     cout.setf( ios::showpoint );
23     cout << "9.9900 prints as: " << 9.9900
24         << "\n9.9000 prints as: " << 9.9000
25         << "\n9.0000 prints as: " << 9.0000 << endl;
26     return 0;
27 } // end function main

```

fig21_21.cpp



Before setting the ios::showpoint flag

9.9900 prints as: 9.99

9.9000 prints as: 9.9

9.0000 prints as: 9

After setting the ios::showpoint flag

9.9900 prints as: 9.99000

9.9000 prints as: 9.90000

9.0000 prints as: 9.00000

Program Output



21.7.3 Justification (`ios::left`, `ios::right`, `ios::internal`)

- `ios::left` – Fields to left-justified with padding characters to the right
 - `ios::right` - Default setting - Fields right-justified with padding characters to the left
 - Character used for padding (Default character is space)set by
 - `fill` member function
 - `setfill` parameterized stream manipulator
 - **internal flag**
 - Number's sign left-justified, Number's magnitude right-justified
 - Intervening spaces padded with the fill character
 - **static data member `ios::adjustfield`**
 - Contains `left`, `right` and `internal` flags
 - `ios::adjustfield` must be the second argument to `setf` when setting the `left`, `right` or `internal` justification flags
- `cout.setf(ios::left, ios::adjustfield);`



```

1 // Fig. 21.22: fig21_22.cpp
2 // Left-justification and right-justification.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 #include <iomanip>
9
10 using std::ios;
11 using std::setw;
12 using std::setiosflags;
13 using std::resetiosflags;
14
15 int main()
16 {
17     int x = 12345;
18
19     cout << "Default is right justified:\n"
20          << setw(10) << x << "\n\nUSING MEMBER FUNCTIONS"
21          << "\nUse setf to set ios::left:\n" << setw(10);
22

```

fig21_22.cpp
(Part 1 of 2)

```

23 cout.setf( ios::left, ios::adjustfield );
24 cout << x << "\nUse unsetf to restore default:\n";
25 cout.unsetf( ios::left );
26 cout << setw( 10 ) << x
27     << "\n\nUSING PARAMETERIZED STREAM MANIPULATORS"
28     << "\nUse setiosflags to set ios::left:\n"
29     << setw( 10 ) << setiosflags( ios::left ) << x
30     << "\nUse resetiosflags to restore default:\n"
31     << setw( 10 ) << resetiosflags( ios::left )
32     << x << endl;
33 return 0;
34 } // end function main

```

fig21_22.cpp
(Part 2 of 2)

```

Default is right justified:
    12345

```

USING MEMBER FUNCTIONS

Use setf to set ios::left:

```
12345
```

Use unsetf to restore default:

```
12345
```

USING PARAMETERIZED STREAM MANIPULATORS

Use setiosflags to set ios::left:

```
12345
```

Use resetiosflags to restore default:

```
12345
```

Program Output



```

1 // Fig. 21.23: fig21_23.cpp
2 // Printing an integer with internal spacing and
3 // forcing the plus sign.
4 #include <iostream>
5
6 using std::cout;
7 using std::endl;
8
9 #include <iomanip>
10
11 using std::ios;
12 using std::setiosflags;
13 using std::setw;
14
15 int main()
16 {
17     cout << setiosflags( ios::internal | ios::showpos )
18         << setw( 10 ) << 123 << endl;
19     return 0;
20 } // end function main

```

fig21_23.cpp

```
+      123
```

Program Output



21.7.4 Padding (fill, setfill)

- **fill member function**

- Specifies the fill character
 - Space is default
 - Returns the prior padding character
- ```
cout.fill('*');
```

- **setfill manipulator**

- Also sets fill character
- ```
cout << setfill ('*');
```



```
1 // Fig. 21.24: fig21_24.cpp
2 // Using the fill member function and the setfill
3 // manipulator to change the padding character for
4 // fields larger than the values being printed.
5 #include <iostream>
6
7 using std::cout;
8 using std::endl;
9
10 #include <iomanip>
11
12 using std::ios;
13 using std::setw;
14 using std::hex;
15 using std::dec;
16 using std::setfill;
17
18 int main()
19 {
20     int x = 10000;
21
```

fig21_24.cpp
(Part 1 of 2)



```

22 cout << x << " printed as int right and left justified\n"
23     << "and as hex with internal justification.\n"
24     << "Using the default pad character (space):\n";
25 cout.setf( ios::showbase );
26 cout << setw( 10 ) << x << '\n';
27 cout.setf( ios::left, ios::adjustfield );
28 cout << setw( 10 ) << x << '\n';
29 cout.setf( ios::internal, ios::adjustfield );
30 cout << setw( 10 ) << hex << x;
31
32 cout << "\n\nusing various padding characters:\n";
33 cout.setf( ios::right, ios::adjustfield );
34 cout.fill( '*' );
35 cout << setw( 10 ) << dec << x << '\n';
36 cout.setf( ios::left, ios::adjustfield );
37 cout << setw( 10 ) << setfill( '%' ) << x << '\n';
38 cout.setf( ios::internal, ios::adjustfield );
39 cout << setw( 10 ) << setfill( '^' ) << hex << x << endl;
40 return 0;
41 } // end function main

```

fig21_24.cpp
(Part 1 of 2)

```

10000 printed as int right and left justified
and as hex with internal justification.
Using the default pad character (space):
    10000
10000
0x    2710

Using various padding characters:
*****10000
10000%%%%%%%%
0x^^^^2710

```

Program Output



21.7.5- Integral Stream Base (ios::dec, ios::oct, ios::hex, ios::showbase)

- **ios::basefield** static member
 - Used similarly to ios::adjustfield with setf
 - Includes the ios::oct, ios::hex and ios::dec flag bits
 - Specify that integers are to be treated as octal, hexadecimal and decimal values
 - Default is decimal
 - Default for stream extractions depends on form inputted
 - Integers starting with 0 are treated as octal
 - Integers starting with 0x or 0X are treated as hexadecimal
 - Once a base specified, settings stay until changed

```

1 // Fig. 21.25: fig21_25.cpp
2 // Using the ios::showbase flag
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 #include <iomanip>
9
10 using std::ios;
11 using std::setiosflags;
12 using std::oct;
13 using std::hex;
14
15 int main()
16 {
17     int x = 100;
18
19     cout << setiosflags( ios::showbase )
20         << "Printing integers preceded by their base:\n"
21         << x << '\n'
22         << oct << x << '\n'
23         << hex << x << endl;
24     return 0;
25 } // end function main

```

fig21_25.cpp

```

Printing integers preceded by their base:
100
0144
0x64

```

Program Output

nho - Escola de Engenharia | 59



21.7.6 Floating-Point Numbers; Scientific Notation (`ios::scientific`, `ios::fixed`)

- **`ios::scientific`**
 - Forces output of a floating point number in scientific notation:
 - 1.946000e+009
- **`ios::fixed`**
 - Forces floating point numbers to display a specific number of digits to the right of the decimal (specified with `precision`)
- **static data member `ios::floatfield`**
 - Contains `ios::scientific` and `ios::fixed`
 - Used similarly to `ios::adjustfield` and `ios::basefield` in `setf`
 - `cout.setf(ios::scientific, ios::floatfield);`
 - `cout.setf(0, ios::floatfield)` restores default format for outputting floating-point numbers



```

1 // Fig. 21.26: fig21_26.cpp
2 // Displaying floating-point values in system default,
3 // scientific, and fixed formats.
4 #include <iostream>
5
6 using std::cout;
7 using std::endl;
8 using std::ios;
9
10 int main()
11 {
12     double x = .001234567, y = 1.946e9;
13
14     cout << "Displayed in default format:\n"
15         << x << '\t' << y << '\n';
16     cout.setf( ios::scientific, ios::floatfield );
17     cout << "Displayed in scientific format:\n"
18         << x << '\t' << y << '\n';
19     cout.unsetf( ios::scientific );
20     cout << "Displayed in default format after unsetf:\n"
21         << x << '\t' << y << '\n';
22     cout.setf( ios::fixed, ios::floatfield );
23     cout << "Displayed in fixed format:\n"
24         << x << '\t' << y << endl;
25     return 0;
26 } // end function main

```

fig21_26.cpp

Program Output

```

Displayed in default format:
0.00123457      1.946e+009
Displayed in scientific format:
1.234567e-003   1.946000e+009
Displayed in default format after unsetf:
0.00123457      1.946e+009
Displayed in fixed format:
0.001235      1946000000.000000

```



Programação



21.7.7 Uppercase/Lowercase Control (ios::uppercase)

- **ios::uppercase**
 - Forces uppercase E to be output with scientific notation
4.32E+010
 - Forces uppercase X to be output with hexadecimal numbers, and causes all letters to be uppercase
75BDE



```

1 // Fig. 21.27: fig21_27.cpp
2 // Using the ios::uppercase flag
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 #include <iomanip>
9
10 using std::setiosflags;
11 using std::ios;
12 using std::hex;
13
14 int main()
15 {
16     cout << setiosflags( ios::uppercase )
17         << "Printing uppercase letters in scientific\n"
18         << "notation exponents and hexadecimal values:\n"
19         << 4.345e10 << '\n' << hex << 123456789 << endl;
20     return 0;
21 } // end function main

```

fig21_27.cpp

```

Printing uppercase letters in scientific
notation exponents and hexadecimal values:
4.345E+010
75BCD15

```

Program Output



21.7.8 Setting and Resetting the Format Flags (flags, setiosflags, resetiosflags)

- **flags member function**
 - Without argument, returns the current settings of the format flags (as a long)
 - With a long argument, sets the format flags as specified:
 - Returns prior settings
- **setf member function**
 - Sets the format flags provided in its argument
 - Returns the previous flag settings as a long value
 - Unset the format using unsetf member function

```
long previousFlagSettings = cout.setf( ios::showpoint | ios::showpos );
```
- **setf with two long arguments**

```
cout.setf( ios::left, ios::adjustfield );
```

clears the bits of ios::adjustfield then sets ios::left

 - This version of setf can be used with
 - ios::basefield (ios::dec, ios::oct, ios::hex)
 - ios::floatfield (ios::scientific, ios::fixed)
 - ios::adjustfield (ios::left, ios::right, ios::internal)
- **Unsetf** – Resets specified flags, Returns previous settings




```

1 // Fig. 21.28: fig21_28.cpp
2 // Demonstrating the flags member function.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7 using std::ios;
8
9
10 int main()
11 {
12     int i = 1000;
13     double d = 0.0947628;
14
15     cout << "The value of the flags variable is: "
16         << cout.flags()
17         << "\nPrint int and double in original format:\n"
18         << i << '\t' << d << "\n\n";
19     long originalFormat =
20         cout.flags( ios::oct | ios::scientific );
21     cout << "The value of the flags variable is: "
22         << cout.flags()
23         << "\nPrint int and double in a new format\n"
24         << "specified using the flags member function:\n"
25         << i << '\t' << d << "\n\n";

```

fig21_28.cpp
(Part 1 of 2)



```

26     cout.flags( originalFormat );
27     cout << "The value of the flags variable is: "
28         << cout.flags()
29         << "\nPrint values in original format again:\n"
30         << i << '\t' << d << endl;
31     return 0;
32 } // end function main

```

fig21_28.cpp
(Part 2 of 2)

```

The value of the flags variable is: 513
Print int and double in original format:
1000    0.0947628

The value of the flags variable is: 12000
Print int and double in a new format
specified using the flags member function:
1750    9.476280e-002

The value of the flags variable is: 513
Print values in original format again:
1000    0.0947628

```

Program Output



21.8 Stream Error States

- **eofbit** - Set for an input stream after end-of-file encountered
 - `cin.eof()` returns true if end-of-file has been encountered on `cin`
- **failbit** - Set for a stream when a format error occurs
 - `cin.fail()` - returns true if a stream operation has failed
 - Normally possible to recover from these errors
- **badbit** - Set when an error occurs that results in data loss
 - `cin.bad()` returns true if stream operation failed
 - normally nonrecoverable
- **Goodbit** - Set for a stream if neither **eofbit**, **failbit** or **badbit** are set
 - `cin.good()` returns true if the `bad`, `fail` and `eof` functions would all return false.
 - I/O operations should only be performed on “good” streams

21.8 Stream Error States

- **rdstate** - Returns the state of the stream
 - Stream can be tested with a `switch` statement that examines all of the state bits
 - Easier to use `eof`, `bad`, `fail`, and `good` to determine state
- **clear** - Used to restore a stream's state to “good”
 - `cin.clear()` clears `cin` and sets `goodbit` for the stream
 - `cin.clear(ios::failbit)` actually sets the `failbit`
 - Might do this when encountering a problem with a user-defined type
- **Other operators**
 - `operator!` - Returns true if `badbit` or `failbit` set
 - `operator void*` - Returns false if `badbit` or `failbit` set
 - Useful for file processing

```

1 // Fig. 21.29: fig21_29.cpp
2 // Testing error states.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7 using std::cin;
8
9 int main()
10 {
11     int x;
12     cout << "Before a bad input operation:"
13         << "\ncin.rdstate(): " << cin.rdstate()
14         << "\n    cin.eof(): " << cin.eof()
15         << "\n    cin.fail(): " << cin.fail()
16         << "\n    cin.bad(): " << cin.bad()
17         << "\n    cin.good(): " << cin.good()
18         << "\n\nExpects an integer, but enter a character: ";
19     cin >> x;
20
21     cout << "\nAfter a bad input operation:"
22         << "\ncin.rdstate(): " << cin.rdstate()
23         << "\n    cin.eof(): " << cin.eof()
24         << "\n    cin.fail(): " << cin.fail()
25         << "\n    cin.bad(): " << cin.bad()
26         << "\n    cin.good(): " << cin.good() << "\n\n";
27

```

fig21_29.cpp
(Part 1 of 2)



```

28     cin.clear();
29
30     cout << "After cin.clear()"
31         << "\ncin.fail(): " << cin.fail()
32         << "\ncin.good(): " << cin.good() << endl;
33     return 0;
34 } // end function main

```

fig21_29.cpp
(Part 2 of 2)

Program Output

Before a bad input operation:

```

cin.rdstate(): 0
cin.eof(): 0
cin.fail(): 0
cin.bad(): 0
cin.good(): 1

```

Expects an integer, but enter a character: A

After a bad input operation:

```

cin.rdstate(): 2
cin.eof(): 0
cin.fail(): 1
cin.bad(): 0
cin.good(): 0

```

After cin.clear()

```

cin.fail(): 0
cin.good(): 1

```



- **tie member function**
 - Synchronize operation of an `istream` and an `ostream`
 - Outputs appear before subsequent inputs
 - Automatically done for `cin` and `cout`
- **`istream.tie(&ostream);`**
 - Ties `istream` to `ostream`
 - `cin.tie(&cout)` done automatically
- **`istream.tie(0);`**
 - Unties `istream` from an output stream

Complementos de Programação de Computadores – Aula 5b

Input e Output com Streams

Mestrado Integrado em Electrónica Industrial e Computadores

Luís Paulo Reis

lpreis1970@gmail.com / lpreis@dsi.uminho.pt

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,
Universidade do Minho, Portugal

(Slides Baseados em P.Deitel e H.Deitel 2010)

