

Complementos de Programação de Computadores – Aula 2

Classes e Abstracção de Dados

Mestrado Integrado em Electrónica Industrial e Computadores

Luís Paulo Reis

lpreis1970@gmail.com / lpreis@dsi.uminho.pt

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,
Universidade do Minho, Portugal

(Slides Baseados em P.Deitel e H.Deitel 2010 e Paulo Cortez, 2011)



Outline

- 16.1 Introduction
- 16.2 Implementing a Time Abstract Data Type with a Class
- 16.3 Class Scope and Accessing Class Members
- 16.4 Separating Interface from Implementation
- 16.5 Controlling Access to Members
- 16.6 Access Functions and Utility Functions
- 16.7 Initializing Class Objects: Constructors
- 16.8 Using Default Arguments with Constructors
- 16.9 Using Destructors
- 16.10 Calling Constructors and Destructors
- 16.11 Using Data Members and Member Functions
- 16.12 A Trap: Returning a Reference to a private Data Member
- 16.13 Assignment by Default Memberwise Copy
- 16.14 Software Reusability

Objectives

- To understand the software engineering concepts of **encapsulation** and data hiding
- To understand the notions of **data abstraction** and abstract data types (ADTs)
- To be able to create **C++ ADTs**, namely **classes**
- To understand how to **create, use, and destroy class objects**
- To be able to control access to object data members and member functions
- To begin to appreciate the value of **object orientation**

16.1 Introduction

- **Object-oriented programming (OOP)**
 - *Encapsulates* data (attributes) and functions (behavior) into packages called **classes**
 - Data and functions closely related!
- **Information hiding**
 - Implementation details are hidden within the classes themselves
- **Unit of C++ programming: the class**
 - A class is like a blueprint – reusable
 - Objects are *instantiated* (created) from the class
 - For example, a house is an instance of a “blueprint class”
 - C programmers concentrate on functions

16.2 Implementing a Time Abstract Data Type with a Class

- **Classes**

- Model objects that have attributes (data members) and behaviors (member functions)
- Defined using keyword `class`

```

1 class Time {
2 public:
3     Time();
4     void setTime( int, int, int );
5     void printMilitary();
6     void printStandard();
7 private:
8     int hour;        // 0 - 23
9     int minute;      // 0 - 59
10    int second;      // 0 - 59
11 }; // end class Time
    
```

Public: and Private: are member-access specifiers

Time is the constructor

setTime, printMilitary, and printStandard are member functions.

hour, minute, and second are data members

- **Format**

- Body delineated with braces (`{` and `}`)
- Class definition terminates with a semicolon



16.2 Implementing a Time Abstract Data Type with a Class (II)

Member functions and data

Public - accessible wherever the program has access to an object of class Time

Private - accessible only to member functions of the class

Protected - discussed later...

- **Constructor**

- Special member function that initializes data members of a class object
- Constructors cannot return values
- Same name as the class

- **Definitions**

- Once class defined, can be used as a data type

```

Time sunset,           // object of type Time
  arrayOfTimes[ 5 ],   // array of Time objects
  *pointerToTime,      // pointer to a Time object
  &dinnerTime = sunset; // reference to a Time object
    
```

Note: The class name becomes the new type specifier



16.2 Implementing a Time Abstract Data Type with a Class (III)

- **Binary scope resolution operator (::)**
 - Specifies which class owns the member function
 - Different classes can have the same name for member functions
- **Format for definition class member functions:**
`ReturnType ClassName :: MemberFunctionName() { ... }`
- **If member function is defined *inside* the class**
 - Scope resolution operator and class name are not needed
 - Defining a function outside a class does not change it being `public` or `private`
- **Classes encourage software reuse**
 - Inheritance allows new classes to be derived from old ones
- **In following program**
 - `Time` constructor initializes the data members to 0
 - Ensures that the object is in a consistent state when it is created



```

1 // Fig. 16.2: fig16_02.cpp
2 // Time class.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 // Time abstract data type (ADT) definition
9 class Time {
10 public:
11     Time(); // constructor
12     void setTime( int, int, int ); // set hour, minute, second
13     void printMilitary(); // print military time format
14     void printStandard(); // print standard time format
15 private:
16     int hour; // 0 - 23
17     int minute; // 0 - 59
18     int second; // 0 - 59
19 }; // end class Time
20
21 // Time constructor initializes each data member to zero.
22 // Ensures all Time objects start in a consistent state.
23 Time::Time() { hour = minute = second = 0; }
24

```

fig16_02.cpp (Part
1 of 3)

```

25 // Set a new Time value using military time. Perform validity
26 // checks on the data values. Set invalid values to zero.
27 void Time::setTime( int h, int m, int s )
28 {
29     hour = ( h >= 0 && h < 24 ) ? h : 0;
30     minute = ( m >= 0 && m < 60 ) ? m : 0;
31     second = ( s >= 0 && s < 60 ) ? s : 0;
32 } // end function setTime
33
34 // Print Time in military format
35 void Time::printMilitary()
36 {
37     cout << ( hour < 10 ? "0" : "" ) << hour << ":"
38         << ( minute < 10 ? "0" : "" ) << minute;
39 } // end function printMilitary
40
41 // Print Time in standard format
42 void Time::printStandard()
43 {
44     cout << ( ( hour == 0 || hour == 12 ) ? 12 : hour % 12 )
45         << ":" << ( minute < 10 ? "0" : "" ) << minute
46         << ":" << ( second < 10 ? "0" : "" ) << second
47         << ( hour < 12 ? " AM" : " PM" );
48 } // end function printStandard
49

```

fig16_02.cpp (Part
2 of 3)



```

50 // Driver to test simple class Time
51 int main()
52 {
53     Time t; // instantiate object t of class Time
54
55     cout << "The initial military time is ";
56     t.printMilitary();
57     cout << "\nThe initial standard time is ";
58     t.printStandard();
59
60     t.setTime( 13, 27, 6 );
61     cout << "\n\nMilitary time after setTime is ";
62     t.printMilitary();
63     cout << "\nStandard time after setTime is ";
64     t.printStandard();
65
66     t.setTime( 99, 99, 99 ); // attempt invalid settings
67     cout << "\n\nAfter attempting invalid settings:"
68         << "\nMilitary time: ";
69     t.printMilitary();
70     cout << "\nStandard time: ";
71     t.printStandard();
72     cout << endl;
73     return 0;
74 } // end function main

```

fig16_02.cpp (Part
3 of 3)



```
The initial military time is 00:00
The initial standard time is 12:00:00 AM

Military time after setTime is 13:27
Standard time after setTime is 1:27:06 PM

After attempting invalid settings:
Military time: 00:00
Standard time: 12:00:00 AM
```

Program Output



16.3 Class Scope and Accessing Class Members

- **Class scope**
 - Data members and member functions
- **File scope**
 - Nonmember functions
- **Function scope**
 - Variables defined in member functions, destroyed after function completes
- **Inside a scope**
 - Members accessible by all member functions
 - Referenced by name
- **Outside a scope**
 - Use handles
 - An object name, a reference to an object or a pointer to an object
- **Accessing class members**
 - Same as `structs`
 - Dot (.) for objects and arrow (→) for pointers
 - Example: `t.hour` is the hour element of `t`
 - `TimePtr->hour` is the hour element



```

1 // Fig. 16.3: fig16_03.cpp
2 // Demonstrating the class member access operators . and ->
3 //
4 // CAUTION: IN FUTURE EXAMPLES WE AVOID PUBLIC DATA!
5 #include <iostream>
6
7 using std::cout;
8 using std::endl;
9
10 // Simple class Count
11 class Count {
12 public:
13     int x;
14     void print() { cout << x << endl; }
15 }; // end class Count
16
17 int main()
18 {
19     Count counter,           // create counter object
20     *counterPtr = &counter; // pointer to counter
21
22
23     cout << "Assign 7 to x and print using the object's name: ";
24     counter.x = 7;           // assign 7 to data member x
25     counter.print();         // call member function print
26

```

fig16_03.cpp (Part
1 of 2)



```

27     cout << "Assign 10 to x and print using a pointer: ";
28     counterPtr->x = 10; // assign 10 to data member x
29     counterPtr->print(); // call member function print
30     return 0;
31 } // end function main

```

fig16_03.cpp (Part
2 of 2)

Assign 7 to x and print using the object's name: 7
Assign 10 to x and print using a pointer: 10

Program Output



16.4 Separating Interface from Implementation

- Separating interface from implementation
 - Easier to modify programs
 - C++ programs can be split into
 - Header files** – contains class definitions and function prototypes
 - Source-code files** – contains member function definitions
- Program Outline:
 - Using the same Time class as before, create a header file
 - Create a source code file
 - Load the header file to get the class definitions
 - Define the member functions of the class



```
1 // Fig. 16.4: time1.h
2 // Declaration of the Time class.
3 // Member functions are defined in time1.cpp
4
5 // prevent multiple inclusions of header file
6 #ifndef TIME1_H
7 #define TIME1_H
8
9 // Time abstract data type definition
10 class Time {
11 public:
12     Time(); // constructor
13     void setTime( int, int, int ); // set hour, minute, second
14     void printMilitary(); // print military time format
15     void printStandard(); // print standard time format
16 private:
17     int hour; // 0 - 23
18     int minute; // 0 - 59
19     int second; // 0 - 59
20 }; // end class Time
21
22 #endif
```

time1.h


```

23 // Fig. 16.4: time1.cpp
24 // Member function definitions for Time class.
25 #include <iostream>
26
27 using std::cout;
28
29 #include "time1.h"
30
31 // Time constructor initializes each data member to zero.
32 // Ensures all Time objects start in a consistent state.
33 Time::Time() { hour = minute = second = 0; }
34
35 // Set a new Time value using military time. Perform validity
36 // checks on the data values. Set invalid values to zero.
37 void Time::setTime( int h, int m, int s )
38 {
39     hour   = ( h >= 0 && h < 24 ) ? h : 0;
40     minute = ( m >= 0 && m < 60 ) ? m : 0;
41     second = ( s >= 0 && s < 60 ) ? s : 0;
42 } // end function setTime
43

```

time1.cpp (Part 1
of 2)



```

44 // Print Time in military format
45 void Time::printMilitary()
46 {
47     cout << ( hour < 10 ? "0" : "" ) << hour << ":"
48         << ( minute < 10 ? "0" : "" ) << minute;
49 } // end function printMilitary
50
51 // Print time in standard format
52 void Time::printStandard()
53 {
54     cout << ( ( hour == 0 || hour == 12 ) ? 12 : hour % 12 )
55         << ":" << ( minute < 10 ? "0" : "" ) << minute
56         << ":" << ( second < 10 ? "0" : "" ) << second
57         << ( hour < 12 ? " AM" : " PM" );
58 } // end function printStandard

```

time1.cpp (Part 2
of 2)



```

59 // Fig. 16.4: fig16_04.cpp
60 // Driver for Time1 class
61 // NOTE: Compile with time1.cpp
62 #include <iostream>
63
64 using std::cout;
65 using std::endl;
66
67 #include "time1.h"
68
69 // Driver to test simple class Time
70 int main()
71 {
72     Time t; // instantiate object t of class Time
73
74     cout << "The initial military time is ";
75     t.printMilitary();
76     cout << "\nThe initial standard time is ";
77     t.printStandard();
78
79     t.setTime( 13, 27, 6 );
80     cout << "\n\nMilitary time after setTime is ";
81     t.printMilitary();
82     cout << "\nStandard time after setTime is ";
83     t.printStandard();
84

```

fig16_04.cpp (Part
1 of 2)



```

85     t.setTime( 99, 99, 99 ); // attempt invalid settings
86     cout << "\n\nAfter attempting invalid settings:\n"
87         << "Military time: ";
88     t.printMilitary();
89     cout << "\nStandard time: ";
90     t.printStandard();
91     cout << endl;
92     return 0;
93 } // end function main

```

fig16_04.cpp (Part
2 of 2)

```

The initial military time is 00:00
The initial standard time is 12:00:00 AM

Military time after setTime is 13:27
Standard time after setTime is 1:27:06 PM

After attempting invalid settings:
Military time: 00:00
Standard time: 12:00:00 AM

```

Program Output



16.5 Controlling Access to Members

- Purpose of `public`
 - Give clients a view of the *services* the class provides (interface)
- Purpose of `private`
 - Default setting
 - Hide details of how the class accomplishes its tasks (implementation)
 - `Private` members only accessible through the `public` interface using `public` member functions



```
1 // Fig. 16.5: fig16_05.cpp
2 // Demonstrate errors resulting from attempts
3 // to access private class members.
4 #include <iostream>
5
6 using std::cout;
7
8 #include "time1.h"
9
10 int main()
11 {
12     Time t;
13
14     // Error: 'Time::hour' is not accessible
15     t.hour = 7;
16
17     // Error: 'Time::minute' is not accessible
18     cout << "minute = " << t.minute;
19
20     return 0;
21 } // end function main
```

fig16_05.cpp



Borland C++ command-line compiler error messages

```
Time1.cpp:  
Fig16_05.cpp:  
Error E2247 Fig16_05.cpp 15:  
    'Time::hour' is not accessible in function main()  
Error E2247 Fig16_05.cpp 18:  
    'Time::minute' is not accessible in function main()  
  
*** 2 errors in Compile ***
```

Microsoft Visual C++ compiler error messages

```
Compiling...  
Fig16_05.cpp  
D:\Fig16_05.cpp(15) : error C2248: 'hour' : cannot access private  
member declared in class 'Time'  
D:\Fig16_05\time1.h(18) : see declaration of 'hour'  
D:\Fig16_05.cpp(18) : error C2248: 'minute' : cannot access private  
member declared in class 'Time'  
D:\time1.h(19) : see declaration of 'minute'  
Error executing cl.exe.  
  
test.exe - 2 error(s), 0 warning(s)
```

Program Output

16.6 Access Functions and Utility Functions

- **Utility functions**
 - private functions that support the operation of public functions
 - Not intended to be used directly by clients
- **Access functions**
 - public functions that read/display data or check conditions
 - For a container, it could call the isEmpty function
- **Next**
 - Program to take in monthly sales and output the total
 - Implementation not shown, only access functions

```

1 // Fig. 16.6: salesp.h
2 // SalesPerson class definition
3 // Member functions defined in salesp.cpp
4 #ifndef SALESP_H
5 #define SALESP_H
6
7 class SalesPerson {
8 public:
9     SalesPerson();           // constructor
10    void getSalesFromUser();  // get sales figures from keyboard
11    void setSales( int, double ); // User supplies one month's
12                                // sales figures.
13    void printAnnualSales();
14
15 private:
16    double totalAnnualSales(); // utility function
17    double sales[ 12 ];        // 12 monthly sales figures
18 }; // end class SalesPerson
19
20 #endif

```

salesp.h



```

21 // Fig. 16.6: salesp.cpp
22 // Member functions for class SalesPerson
23 #include <iostream>
24
25 using std::cout;
26 using std::cin;
27 using std::endl;
28
29 #include <iomanip>
30
31 using std::setprecision;
32 using std::setiosflags;
33 using std::ios;
34
35 #include "salesp.h"
36
37 // Constructor function initializes array
38 SalesPerson::SalesPerson()
39 {
40     for ( int i = 0; i < 12; i++ )
41         sales[ i ] = 0.0;
42 } // end SalesPerson constructor
43

```

salesp.cpp (Part 1
of 3)



```

44 // Function to get 12 sales figures from the user
45 // at the keyboard
46 void SalesPerson::getSalesFromUser()
47 {
48     double salesFigure;
49
50     for ( int i = 1; i <= 12; i++ ) {
51         cout << "Enter sales amount for month " << i << ": ";
52
53         cin >> salesFigure;
54         setSales( i, salesFigure );
55     } // end for
56 } // end function getSalesFromUser
57
58 // Function to set one of the 12 monthly sales figures.
59 // Note that the month value must be from 0 to 11.
60 void SalesPerson::setSales( int month, double amount )
61 {
62     if ( month >= 1 && month <= 12 && amount > 0 )
63         sales[ month - 1 ] = amount; // adjust for subscripts 0-11
64     else
65         cout << "Invalid month or sales figure" << endl;
66 } // end function setSales
67

```

salesp.cpp (Part 2
of 3)



```

68 // Print the total annual sales
69 void SalesPerson::printAnnualSales()
70 {
71     cout << setprecision( 2 )
72         << setiosflags( ios::fixed | ios::showpoint )
73         << "\nThe total annual sales are: $"
74         << totalAnnualSales() << endl;
75 } // end function printAnnualSales
76
77 // Private utility function to total annual sales
78 double SalesPerson::totalAnnualSales()
79 {
80     double total = 0.0;
81
82     for ( int i = 0; i < 12; i++ )
83         total += sales[ i ];
84
85     return total;
86 } // end function totalAnnualSales

```

salesp.cpp (Part 3
of 3)



```

87 // Fig. 16.6: fig16_06.cpp
88 // Demonstrating a utility function
89 // Compile with salesp.cpp
90 #include "salesp.h"
91
92 int main()
93 {
94     SalesPerson s;          // create SalesPerson object s
95
96     s.getSalesFromUser();    // note simple sequential code
97     s.printAnnualSales();    // no control structures in main
98     return 0;
99 } // end function main

```

fig16_06.cpp

```

Enter sales amount for month 1: 5314.76
Enter sales amount for month 2: 4292.38
Enter sales amount for month 3: 4589.83
Enter sales amount for month 4: 5534.03
Enter sales amount for month 5: 4376.34
Enter sales amount for month 6: 5698.45
Enter sales amount for month 7: 4439.22
Enter sales amount for month 8: 5893.57
Enter sales amount for month 9: 4909.67
Enter sales amount for month 10: 5123.45
Enter sales amount for month 11: 4024.97
Enter sales amount for month 12: 5923.92

The total annual sales are: $60120.59

```

Program Output



16.7 Initializing Class Objects: Constructors

- **Constructor function**
 - Can initialize class members
 - Same name as the class, no return type
 - Member variables can be initialized by the constructor or set afterwards
- **Defining objects**
 - Initializers can be provided
 - Initializers passed as arguments to the class' constructor
- **Format**

Type *ObjectName*(*value1*, *value2*, ...);

 - Constructor assigns *value1*, *value2*, etc. to its member variables
 - If not enough values specified, rightmost parameters set to their default (specified by programmer)

myClass *myObject*(3, 4.0);



16.8 Using Default Arguments with Constructors

- **Default constructor**
 - One per class
 - Can be invoked without arguments
 - Has default arguments
- **Default arguments**
 - Set in default constructor function prototype (in class definition)
 - Do not set defaults in the function definition, outside of a class
 - Example:
 `SampleClass(int = 0, float = 0);`
 - Constructor has same name as class



```
1 // Fig. 16.7: time2.h
2 // Declaration of the Time class.
3 // Member functions are defined in time2.cpp
4
5 // preprocessor directives that
6 // prevent multiple inclusions of header file
7 #ifndef TIME2_H
8 #define TIME2_H
9
10 // Time abstract data type definition
11 class Time {
12 public:
13     Time( int = 0, int = 0, int = 0 ); // default constructor
14     void setTime( int, int, int ); // set hour, minute, second
15     void printMilitary();           // print military time format
16     void printStandard();          // print standard time format
17 private:
18     int hour;    // 0 - 23
19     int minute;  // 0 - 59
20     int second;  // 0 - 59
21 }; // end class Time
22
23 #endif
```

time2.h




```

24 // Fig. 16.7: time2.cpp
25 // Member function definitions for Time class.
26 #include <iostream>
27
28 using std::cout;
29
30 #include "time2.h"
31
32 // Time constructor initializes each data member to zero.
33 // Ensures all Time objects start in a consistent state.
34 Time::Time( int hr, int min, int sec )
35 { setTime( hr, min, sec ); }
36
37 // Set a new Time value using military time. Perform validity
38 // checks on the data values. Set invalid values to zero.
39 void Time::setTime( int h, int m, int s )
40 {
41     hour   = ( h >= 0 && h < 24 ) ? h : 0;
42     minute = ( m >= 0 && m < 60 ) ? m : 0;
43     second = ( s >= 0 && s < 60 ) ? s : 0;
44 } // end function setTime
45

```

time2.cpp (Part 1
of 2)



```

46 // Print Time in military format
47 void Time::printMilitary()
48 {
49     cout << ( hour < 10 ? "0" : "" ) << hour << ":"
50         << ( minute < 10 ? "0" : "" ) << minute;
51 } // end function printMilitary
52
53 // Print Time in standard format
54 void Time::printStandard()
55 {
56     cout << ( ( hour == 0 || hour == 12 ) ? 12 : hour % 12 )
57         << ":" << ( minute < 10 ? "0" : "" ) << minute
58         << ":" << ( second < 10 ? "0" : "" ) << second
59         << ( hour < 12 ? " AM" : " PM" );
60 } // end function printStandard

```

time2.cpp (Part 2
of 2)



```

61 // Fig. 16.7: fig16_07.cpp
62 // Demonstrating a default constructor
63 // function for class Time.
64 #include <iostream>
65
66 using std::cout;
67 using std::endl;
68
69 #include "time2.h"
70
71 int main()
72 {
73     Time t1,           // all arguments defaulted
74         t2( 2 ),       // minute and second defaulted
75         t3( 21, 34 ),  // second defaulted
76         t4( 12, 25, 42 ), // all values specified
77         t5( 27, 74, 99 ); // all bad values specified
78
79     cout << "Constructed with:\n"
80         << "all arguments defaulted:\n  ";
81     t1.printMilitary();
82     cout << "\n  ";
83     t1.printStandard();
84

```

fig16_07.cpp (Part
1 of 2)



```

85     cout << "\nhour specified; minute and second defaulted:"
86         << "\n  ";
87     t2.printMilitary();
88     cout << "\n  ";
89     t2.printStandard();
90
91     cout << "\nhour and minute specified; second defaulted:"
92         << "\n  ";
93     t3.printMilitary();
94     cout << "\n  ";
95     t3.printStandard();
96
97     cout << "\nhour, minute, and second specified:"
98         << "\n  ";
99     t4.printMilitary();
100    cout << "\n  ";
101    t4.printStandard();
102
103    cout << "\nall invalid values specified:"
104        << "\n  ";
105    t5.printMilitary();
106    cout << "\n  ";
107    t5.printStandard();
108    cout << endl;
109
110    return 0;
111 } // end function main

```

fig16_07.cpp (Part
2 of 2)



Constructed with:

all arguments defaulted:

00:00

12:00:00 AM

hour specified; minute and second defaulted:

02:00

2:00:00 AM

hour and minute specified; second defaulted:

21:34

9:34:00 PM

hour, minute, and second specified:

12:25

12:25:42 PM

all invalid values specified:

00:00

12:00:00 AM

Program Output



16.9 Using Destructors

- **Destructor**
 - Member function of class
 - Performs termination housekeeping before the system reclaims the object's memory
 - Complement of the constructor
 - Name is *tilde* (~) followed by the class name
 - ~Time
 - Recall that the constructor's name is the class name
 - Receives no parameters, returns no value
 - One destructor per class - no overloading allowed



16.10 Calling Constructors and Destructors

- **Constructors and destructors called automatically**
 - Order depends on scope of objects
- **Global scope objects**
 - Constructors called before any other function (including `main`)
 - Destructors called when `main` terminates (or `exit` function called)
 - Destructors not called if program terminates with `abort`
- **Automatic local objects**
 - Constructors called when objects defined
 - Destructors called when objects leave scope (when the block in which they are defined is exited)
 - Destructors not called if program ends with `exit` or `abort`
- **static local objects**
 - Constructors called when execution reaches the point where the objects are defined
 - Destructors called when `main` terminates or the `exit` function is called
 - Destructors not called if the program ends with `abort`



```
1 // Fig. 16.8: create.h
2 // Definition of class CreateAndDestroy.
3 // Member functions defined in create.cpp.
4 #ifndef CREATE_H
5 #define CREATE_H
6
7 class CreateAndDestroy {
8 public:
9     CreateAndDestroy( int ); // constructor
10    ~CreateAndDestroy(); // destructor
11 private:
12     int data;
13 }; // end class CreateAndDestroy
14
15 #endif
```

create.h

```

16 // Fig. 16.8: create.cpp
17 // Member function definitions for class CreateAndDestroy
18 #include <iostream>
19
20 using std::cout;
21 using std::endl;
22
23 #include "create.h"
24
25 CreateAndDestroy::CreateAndDestroy( int value )
26 {
27     data = value;
28     cout << "Object " << data << " constructor";
29 } // end CreateAndDestroy constructor
30
31 CreateAndDestroy::~CreateAndDestroy()
32 { cout << "Object " << data << " destructor " << endl; }

```

create.cpp



```

33 // Fig. 16.8: fig16_08.cpp
34 // Demonstrating the order in which constructors and
35 // destructors are called.
36 #include <iostream>
37
38 using std::cout;
39 using std::endl;
40
41 #include "create.h"
42
43 void create( void ); // prototype
44
45 CreateAndDestroy first( 1 ); // global object
46
47 int main()
48 {
49     cout << " (global created before main)" << endl;
50
51     CreateAndDestroy second( 2 ); // local object
52     cout << " (local automatic in main)" << endl;
53
54     static CreateAndDestroy third( 3 ); // local object
55     cout << " (local static in main)" << endl;
56
57     create(); // call function to create objects
58

```

fig16_08.cpp (Part
1 of 2)



```

59 CreateAndDestroy fourth( 4 ); // local object
60 cout << " (local automatic in main)" << endl;
61 return 0;
62 } // end function main
63
64 // Function to create objects
65 void create( void )
66 {
67 CreateAndDestroy fifth( 5 );
68 cout << " (local automatic in create)" << endl;
69
70 static CreateAndDestroy sixth( 6 );
71 cout << " (local static in create)" << endl;
72
73 CreateAndDestroy seventh( 7 );
74 cout << " (local automatic in create)" << endl;
75 } // end function create

```

fig16_08.cpp (Part
2 of 2)



Object 1	constructor	(global created before main)
Object 2	constructor	(local automatic in main)
Object 3	constructor	(local static in main)
Object 5	constructor	(local automatic in create)
Object 6	constructor	(local static in create)
Object 7	constructor	(local automatic in create)
Object 7	destructor	
Object 5	destructor	
Object 4	constructor	(local automatic in main)
Object 4	destructor	
Object 2	destructor	
Object 6	destructor	
Object 3	destructor	
Object 1	destructor	

Program Output



16.11 Using Data Members and Member Functions

- **Classes provide `public` member functions**
 - Set (i.e., write) or *get* (i.e., read) values of private data members
 - Adjustment of bank balance (a private data member of class `BankAccount`) by member function `computeInterest`
- **Naming**
 - Member function that *sets* `interestRate` typically named `setInterestRate`
 - Member function that *gets* `interestRate` would typically be called `getInterestRate`

16.11 Using Data Members and Member Functions (II)

- **Do *set* and *get* capabilities effectively make data members `public`?**
 - No!
 - Programmer decides what the function can set and what information the function can get
- **`public` set functions should**
 - Check attempts to modify data members
 - Ensure that the new value is appropriate for that data item
 - Example: an attempt to *set* the day of the month to 37 would be rejected
 - Programmer must include these features

```

1 // Fig. 16.9: time3.h
2 // Declaration of the Time class.
3 // Member functions defined in time3.cpp
4
5 // preprocessor directives that
6 // prevent multiple inclusions of header file
7 #ifndef TIME3_H
8 #define TIME3_H
9
10 class Time {
11 public:
12     Time( int = 0, int = 0, int = 0 ); // constructor
13
14     // set functions
15     void setTime( int, int, int ); // set hour, minute, second
16     void setHour( int ); // set hour
17     void setMinute( int ); // set minute
18     void setSecond( int ); // set second
19
20     // get functions
21     int getHour(); // return hour
22     int getMinute(); // return minute
23     int getSecond(); // return second
24

```

time3.h (Part 1 of 2)



```

25 void printMilitary(); // output military time
26 void printStandard(); // output standard time
27
28 private:
29     int hour; // 0 - 23
30     int minute; // 0 - 59
31     int second; // 0 - 59
32 }; // end class Time
33
34 #endif

```

time3.h (Part 2 of 2)




```

35 // Fig. 16.9: time3.cpp
36 // Member function definitions for Time class.
37 #include <iostream>
38
39 using std::cout;
40
41 #include "time3.h"
42
43 // Constructor function to initialize private data.
44 // Calls member function setTime to set variables.
45 // Default values are 0 (see class definition).
46 Time::Time( int hr, int min, int sec )
47     { setTime( hr, min, sec ); }
48
49 // Set the values of hour, minute, and second.
50 void Time::setTime( int h, int m, int s )
51 {
52     setHour( h );
53     setMinute( m );
54     setSecond( s );
55 } // end function setTime
56
57 // Set the hour value
58 void Time::setHour( int h )
59     { hour = ( h >= 0 && h < 24 ) ? h : 0; }
60

```

time3.cpp (Part 1
of 3)



```

61 // Set the minute value
62 void Time::setMinute( int m )
63     { minute = ( m >= 0 && m < 60 ) ? m : 0; }
64
65 // Set the second value
66 void Time::setSecond( int s )
67     { second = ( s >= 0 && s < 60 ) ? s : 0; }
68
69 // Get the hour value
70 int Time::getHour() { return hour; }
71
72 // Get the minute value
73 int Time::getMinute() { return minute; }
74
75 // Get the second value
76 int Time::getSecond() { return second; }
77
78 // Print time in military format
79 void Time::printMilitary()
80 {
81     cout << ( hour < 10 ? "0" : "" ) << hour << ":"
82         << ( minute < 10 ? "0" : "" ) << minute;
83 } // end function printMilitary
84

```

time3.cpp (Part 2
of 3)



```

85 // Print time in standard format
86 void Time::printStandard()
87 {
88     cout << ( ( hour == 0 || hour == 12 ) ? 12 : hour % 12 )
89         << ":" << ( minute < 10 ? "0" : "" ) << minute
90         << ":" << ( second < 10 ? "0" : "" ) << second
91         << ( hour < 12 ? " AM" : " PM" );
92 } // end function printStandard

```

time3.cpp (Part 3 of 3)

```

93 // Fig. 16.9: fig16_09.cpp
94 // Demonstrating the Time class set and get functions
95 #include <iostream>
96
97 using std::cout;
98 using std::endl;
99
100 #include "time3.h"
101
102 void incrementMinutes( Time &, const int );
103
104 int main()
105 {
106     Time t;
107
108     t.setHour( 17 );
109     t.setMinute( 34 );
110     t.setSecond( 25 );
111

```



```

112     cout << "Result of setting all valid values:\n"
113         << " Hour: " << t.getHour()
114         << " Minute: " << t.getMinute()
115         << " Second: " << t.getSecond();
116
117     t.setHour( 234 ); // invalid hour set to 0
118     t.setMinute( 43 );
119     t.setSecond( 6373 ); // invalid second set to 0
120
121     cout << "\n\nResult of attempting to set invalid hour and"
122         << " second:\n Hour: " << t.getHour()
123         << " Minute: " << t.getMinute()
124         << " Second: " << t.getSecond() << "\n\n";
125
126     t.setTime( 11, 58, 0 );
127     incrementMinutes( t, 3 );
128
129     return 0;
130 } // end function main
131
132 void incrementMinutes( Time &tt, const int count )
133 {
134     cout << "Incrementing minute " << count
135         << " times:\nStart time: ";
136     tt.printStandard();
137

```

fig16_09.cpp (Part 1 of 2)



```

138 for ( int i = 0; i < count; i++ ) {
139     tt.setMinute( ( tt.getMinute() + 1 ) % 60 );
140
141     if ( tt.getMinute() == 0 )
142         tt.setHour( ( tt.getHour() + 1 ) % 24 );
143
144     cout << "\nminute + 1: ";
145     tt.printStandard();
146 } // end for
147
148 cout << endl;
149 } // end function incrementMinutes

```

fig16_09.cpp (Part 2 of 2)

Result of setting all valid values:
Hour: 17 Minute: 34 Second: 25

Result of attempting to set invalid hour and second:
Hour: 0 Minute: 43 Second: 0

Incrementing minute 3 times:
Start time: 11:58:00 AM
minute + 1: 11:59:00 AM
minute + 1: 12:00:00 PM
minute + 1: 12:01:00 PM

Program Output



16.12 A Subtle Trap: Returning a Reference to a Private Data Member

- **Reference to an object**
 - Alias for the name of the object
 - May be used on the left side of an assignment statement
 - Reference can receive a value, which changes the original object as well
- **One way to use this capability (unfortunately!)**
 - Have a public member function of a class return a non-const reference to a private data member
 - This reference can be modified, which changes the original data



```

1 // Fig. 16.10: time4.h
2 // Declaration of the Time class.
3 // Member functions defined in time4.cpp
4
5 // preprocessor directives that
6 // prevent multiple inclusions of header file
7 #ifndef TIME4_H
8 #define TIME4_H
9
10 class Time {
11 public:
12     Time( int = 0, int = 0, int = 0 );
13     void setTime( int, int, int );
14     int getHour();
15     int &badSetHour( int ); // DANGEROUS reference return
16 private:
17     int hour;
18     int minute;
19     int second;
20 }; // end class Time
21
22 #endif

```

time4.h



```

23 // Fig. 16.10: time4.cpp
24 // Member function definitions for Time class.
25 #include "time4.h"
26
27 // Constructor function to initialize private data.
28 // Calls member function setTime to set variables.
29 // Default values are 0 (see class definition).
30 Time::Time( int hr, int min, int sec )
31 { setTime( hr, min, sec ); }
32
33 // Set the values of hour, minute, and second.
34 void Time::setTime( int h, int m, int s )
35 {
36     hour = ( h >= 0 && h < 24 ) ? h : 0;
37     minute = ( m >= 0 && m < 60 ) ? m : 0;
38     second = ( s >= 0 && s < 60 ) ? s : 0;
39 } // end function setTime
40
41 // Get the hour value
42 int Time::getHour() { return hour; }
43

```

time4.cpp (Part 1
of 2)



```

44 // POOR PROGRAMMING PRACTICE:
45 // Returning a reference to a private data member.
46 int &Time::badSetHour( int hh )
47 {
48     hour = ( hh >= 0 && hh < 24 ) ? hh : 0;
49
50     return hour; // DANGEROUS reference return
51 } // end function badSetHour
52 // Fig. 16.10: fig16_10.cpp
53 // Demonstrating a public member function that
54 // returns a reference to a private data member.
55 // Time class has been trimmed for this example.
56 #include <iostream>
57
58 using std::cout;
59 using std::endl;
60
61 #include "time4.h"
62
63 int main()
64 {
65     Time t;
66     int &hourRef = t.badSetHour( 20 );
67
68     cout << "Hour before modification: " << hourRef;
69     hourRef = 30; // modification with invalid value
70     cout << "\nHour after modification: " << t.getHour();
71

```

time4.cpp



```

72 // Dangerous: Function call that returns
73 // a reference can be used as an lvalue!
74 t.badSetHour( 12 ) = 74;
75 cout << "\n\n*****\n"
76     << "POOR PROGRAMMING PRACTICE!!!!!!\n"
77     << "badSetHour as an lvalue, Hour: "
78     << t.getHour()
79     << "\n*****" << endl;
80
81 return 0;
82 }

```

fig16_10.cpp

Hour before modification: 20
Hour after modification: 30

```

*****
POOR PROGRAMMING PRACTICE!!!!!!
badSetHour as an lvalue, Hour: 74
*****

```

Program Output



16.13 Assignment by Default Memberwise Copy

- **Assignment operator (=)**
 - Sets variables equal, i.e., $x = y$;
 - Can be used to assign an object to another object of the same type
 - Memberwise copy — member by member copy
`myObject1 = myObject2;`
- **Objects may be**
 - Passed as function arguments
 - Returned from functions (call-by-value default)
 - Use pointers for call by reference



```
1 // Fig. 16.11: fig16_11.cpp
2 // Demonstrating that class objects can be assigned
3 // to each other using default memberwise copy
4 #include <iostream>
5
6 using std::cout;
7 using std::endl;
8
9 // Simple Date class
10 class Date {
11 public:
12     Date( int = 1, int = 1, int = 1990 ); // default constructor
13     void print();
14 private:
15     int month;
16     int day;
17     int year;
18 }; // end class Date
19
20 // Simple Date constructor with no range checking
21 Date::Date( int m, int d, int y )
22 {
23     month = m;
24     day = d;
25     year = y;
26 } // end Date constructor
27
```

fig16_11.cpp (Part
1 of 2)



```

28 // Print the Date in the form mm-dd-yyyy
29 void Date::print()
30 { cout << month << '-' << day << '-' << year; }
31
32 int main()
33 {
34     Date date1( 7, 4, 1993 ), date2; // d2 defaults to 1/1/90
35
36     cout << "date1 = ";
37     date1.print();
38     cout << "\ndate2 = ";
39     date2.print();
40
41     date2 = date1; // assignment by default memberwise copy
42     cout << "\n\nAfter default memberwise copy, date2 = ";
43     date2.print();
44     cout << endl;
45
46     return 0;
47 } // end function main

```

fig16_11.cpp (Part
2 of 2)

```

date1 = 7-4-1993
date2 = 1-1-1990

```

Program Output

```

After default memberwise copy, date2 = 7-4-1993

```



16.14 Software Reusability

- **Object-oriented programmers**
 - Concentrate on implementing useful classes
- **Tremendous opportunity to capture and catalog classes**
 - Accessed by large segments of the programming community
 - Class libraries exist for this purpose
- **Software**
 - Constructed from existing, well-defined, carefully tested, portable, widely available components
 - Speeds development of powerful, high-quality software



Complementos de Programação de Computadores – Aula 2

Classes e Abstracção de Dados

Mestrado Integrado em Electrónica Industrial e Computadores

Luís Paulo Reis

lpreis1970@gmail.com / lpreis@dsi.uminho.pt

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,
Universidade do Minho, Portugal

(Slides Baseados em P.Deitel e H.Deitel 2010 e Paulo Cortez, 2011)

