

Complementos de Programação de Computadores – Aula 6b

Tratamento de Exceções

Mestrado Integrado em Electrónica Industrial e Computadores

Luís Paulo Reis

lpreis@dsi.uminho.pt

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,
Universidade do Minho, Portugal

(Slides Baseados em P.Deitel e H.Deitel 2010)



Outline

- 23.1 Introduction
- 23.2 When Exception Handling Should Be Used
- 23.3 Other Error-Handling Techniques
- 23.4 Basics of C++ Exception Handling: try, throw, catch
- 23.5 A Simple Exception-Handling Example: Divide by Zero
- 23.6 Throwing an Exception
- 23.7 Catching an Exception
- 23.8 Rethrowing an Exception
- 23.9 Exception Specifications
- 23.10 Processing Unexpected Exceptions
- 23.11 Stack Unwinding
- 23.12 Constructors, Destructors and Exception Handling
- 23.13 Exceptions and Inheritance
- 23.14 Processing new Failures
- 23.15 Class auto_ptr and Dynamic Memory Allocation
- 23.16 Standard Library Exception Hierarchy

Objectives

- To use `try`, `throw` and `catch` to watch for, indicate and handle exceptions, respectively
- To process uncaught and unexpected exceptions
- To be able to process new failures
- To use `auto_ptr` to prevent memory leaks
- To understand the standard exception hierarchy.

23.1 Introduction

- **Errors can be dealt with at place error occurs**
 - Easy to see if proper error checking implemented
 - Harder to read application itself and see how code works
- **Exception handling**
 - Makes clear, robust, fault-tolerant programs
 - C++ removes error handling code from "main line" of program
- **Common failures**
 - new not allocating memory
 - Out of bounds array subscript
 - Division by zero
 - Invalid function parameters

23.1 Introduction (II)

- **Exception handling - catch errors before they occur**
 - Deals with synchronous errors (i.e., Divide by zero)
 - Does not deal with asynchronous errors - disk I/O completions, mouse clicks - use interrupt processing
 - Used when system can recover from error
 - Exception handler - recovery procedure
 - Typically used when error dealt with in different place than where it occurred
 - Useful when program cannot recover but must shut down cleanly
- **Exception handling should not be used for program control**
 - Not optimized, can harm program performance

23.1 Introduction (III)

- **Exception handling improves fault-tolerance**
 - Easier to write error-processing code
 - Specify what type of exceptions are to be caught
- **Most programs support only single threads**
 - Techniques in this chapter apply for multithreaded OS as well (windows NT, OS/2, some UNIX)
- **Exception handling another way to return control from a function or block of code**

23.2 When Exception Handling Should Be Used

- **Error handling should be used for**
 - Processing exceptional situations
 - Processing exceptions for components that cannot handle them directly
 - Processing exceptions for widely used components (libraries, classes, functions) that should not process their own exceptions
 - Large projects that require uniform error processing

23.3 Other Error-Handling Techniques

- **Use assert**
 - If assertion false, the program terminates
- **Ignore exceptions**
 - Use this "technique" on casual, personal programs - not commercial!
- **Abort the program**
 - Appropriate for nonfatal errors give appearance that program functioned correctly
 - Inappropriate for mission-critical programs, can cause resource leaks
- **Set some error indicator**
 - Program may not check indicator at all points where error could occur

23.3 Other Error-Handling Techniques (II)

- **Test for the error condition**
 - Issue an error message and call `exit`
 - Pass error code to environment
- **`setjump` and `longjump`**
 - In `<setjmp>`
 - Jump out of deeply nested function calls back to an error handler.
 - Dangerous - unwinds the stack without calling destructors for automatic objects (more later)
- **Specific errors**
 - Some have dedicated capabilities for handling them
 - If `new` fails to allocate memory `new_handler` function executes to deal with problem

23.4 Basics of C++ Exception Handling: `try`, `throw`, `catch`

- **A function can throw an exception object if it detects an error**
 - Object typically a character string (error message) or class object
 - If exception handler exists, exception caught and handled
 - Otherwise, program terminates
- **Format**
 - Enclose code that may have an error in `try` block
 - Follow with one or more `catch` blocks
 - Each `catch` block has an exception handler
 - If exception occurs and matches parameter in `catch` block, code in `catch` block executed
 - If no exception thrown, exception handlers skipped and control resumes after `catch` blocks
 - `throw` point - place where exception occurred
 - Control cannot return to `throw` point

23.5 A Simple Exception-Handling Example: Divide by Zero

- Look at the format of try and catch blocks
- Afterwards, we will cover specifics

```
1 // Fig. 23.1: fig23_01.cpp
2 // A simple exception handling example.
3 // Checking for a divide-by-zero exception.
4 #include <iostream>
5
6 using std::cout;
7 using std::cin;
8 using std::endl;
9
10 // Class DivideByZeroException to be used in exception
11 // handling for throwing an exception on a division by zero.
12 class DivideByZeroException {
13 public:
14     DivideByZeroException()
15         : message( "attempted to divide by zero" ) { }
16     const char *what() const { return message; }
17 private:
18     const char *message;
19 }; // end class DivideByZeroException
20
21 // Definition of function quotient. Demonstrates throwing
22 // an exception when a divide-by-zero exception is encountered.
23 double quotient( int numerator, int denominator )
24 {
25     if ( denominator == 0 )
26         throw DivideByZeroException();
27 }
```

fig23_01.cpp (Part 1
of 3)

```

28     return static_cast< double > ( numerator ) / denominator;
29 } // end function quotient
30
31 // Driver program
32 int main()
33 {
34     int number1, number2;
35     double result;
36
37     cout << "Enter two integers (end-of-file to end): ";
38
39     while ( cin >> number1 >> number2 ) {
40
41         // the try block wraps the code that may throw an
42         // exception and the code that should not execute
43         // if an exception occurs
44         try {
45             result = quotient( number1, number2 );
46             cout << "The quotient is: " << result << endl;
47         } // end try

```

fig23_01.cpp (Part 2 of 3)



```

48     catch ( DivideByZeroException ex ) { // exception handler
49         cout << "Exception occurred: " << ex.what() << '\n';
50     } // end catch
51
52     cout << "\nEnter two integers (end-of-file to end): ";
53 } // end while
54
55 cout << endl;
56 return 0; // terminate normally
57 } // end function main

```

fig23_01.cpp (Part 3 of 3)

Program Output

```

Enter two integers (end-of-file to end): 100 7
The quotient is: 14.2857

Enter two integers (end-of-file to end): 100 0
Exception occurred: attempted to divide by zero

Enter two integers (end-of-file to end): 33 9
The quotient is: 3.66667

Enter two integers (end-of-file to end): ^Z

```



23.6 Throwing an Exception

- **throw** – indicates an exception has occurred
 - Usually has one operand (sometimes zero) of any type
 - If operand an object, called an exception object
 - Conditional expression can be thrown
 - Code referenced in a try block can throw an exception
 - Exception caught by closest exception handler
 - Control exits current try block and goes to catch handler (if it exists)
 - Example (inside function definition)

```
if ( denominator == 0 )  
    throw DivideByZeroException();
```

 - Throws a `dividebyzeroexception` object
- **Exception not required to terminate program**
 - However, terminates block where exception occurred

23.7 Catching an Exception

- **Exception handlers are in catch blocks**
 - Format: `catch(exceptionType parameterName){`
 exception handling code
 }
 - Caught if argument type matches throw type
 - If not caught then `terminate` called which (by default) calls `abort`
 - Example:

```
catch ( DivideByZeroException ex) {  
    cout << "Exception occurred: " << ex.what() << '\n'  
}
```

 - Catches exceptions of type `DivideByZeroException`
- **Catch all exceptions**

```
catch( . . . )
```

 - catches all exceptions
 - You do not know what type of exception occurred
 - There is no parameter name - cannot reference the object

23.7 Catching an Exception (II)

- **If no handler matches thrown object**
 - Searches next enclosing `try` block
 - If none found, `terminate` called
 - If found, control resumes after last `catch` block
 - If several handlers match thrown object, first one found is executed
- **catch parameter matches thrown object when**
 - They are of the same type
 - Exact match required - no promotions/conversions allowed
 - The `catch` parameter is a `public` base class of the thrown object
 - The `catch` parameter is a base-class pointer/ reference type and the thrown object is a derived-class pointer/ reference type
 - The `catch` handler is `catch(...)`
 - Thrown `const` objects have `const` in the parameter type

23.7 Catching an Exception (III)

- **Unreleased resources**
 - Resources may have been allocated when exception thrown
 - `catch` handler should `delete` space allocated by `new` and close any opened files
- **catch handlers can throw exceptions**
 - Exceptions can only be processed by outer `try` blocks

23.8 Rethrowing an Exception

- **Rethrowing exceptions**

- Used when an exception handler cannot process an exception
- Rethrow exception with the statement:
 throw;
 - No arguments
 - If no exception thrown in first place, calls terminate
- Handler can always rethrow exception, even if it performed some processing
- Rethrown exception detected by next enclosing try block



```
1 // Fig. 23.2: fig23_02.cpp
2 // Demonstration of rethrowing an exception.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 #include <exception>
9
10 using std::exception;
11
12 void throwException()
13 {
14     // Throw an exception and immediately catch it.
15     try {
16         cout << "Function throwException\n";
17         throw exception(); // generate exception
18     } // end try
19     catch( exception e )
20     {
21         cout << "Exception handled in function throwException\n";
22         throw; // rethrow exception for further processing
23     } // end catch
24
25     cout << "This also should not print\n";
26 } // end function throwException
27
```

fig23_02.cpp (Part 1
of 2)



```

28 int main()
29 {
30     try {
31         throwException();
32         cout << "This should not print\n";
33     } // end try
34     catch ( exception e )
35     {
36         cout << "Exception handled in main\n";
37     } // end catch
38
39     cout << "Program control continues after catch in main"
40         << endl;
41     return 0;
42 } // end function main

```

fig23_02.cpp (Part 2 of 2)

```

Function throwException
Exception handled in function throwException
Exception handled in main
Program control continues after catch in main

```

Program Output



23.9 Exception Specifications

- **Exception specification (throw list)**

- Lists exceptions that can be thrown by a function

Example:

```

int g( double h ) throw ( a, b, c )
{
    // function body
}

```

- Function can throw listed exceptions or derived types
- If other type thrown, function unexpected called
- throw() (i.e., no throw list) states that function will not throw any exceptions
 - In reality, function can still throw exceptions, but calls unexpected (more later)
- If no throw list specified, function can throw any exception



23.10 Processing Unexpected Exceptions

- **Function unexpected**
 - Calls the function specified with `set_unexpected`
 - Default: `terminate`
- **Function terminate**
 - Calls function specified with `set_terminate`
 - Default: `abort`
- **set_terminate and set_unexpected**
 - Prototypes in `<exception>`
 - Take pointers to functions (i.e., Function name)
 - Function must return `void` and take no arguments
 - Returns pointer to last function called by `terminate` or `unexpected`

23.11 Stack Unwinding

- **Function-call stack unwound when exception thrown and not caught in a particular scope**
 - Tries to catch exception in next outer `try/catch` block
 - Function in which exception was not caught terminates
 - Local variables destroyed
 - Control returns to place where function was called
 - If control returns to a `try` block, attempt made to catch exception
 - Otherwise, further unwinds stack
 - If exception not caught, `terminate` called

```

1 // Fig. 23.3: fig23_03.cpp
2 // Demonstrating stack unwinding.
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 #include <stdexcept>
9
10 using std::runtime_error;
11
12 void function3() throw ( runtime_error )
13 {
14     throw runtime_error( "runtime_error in function3" );
15 } // end function function3
16
17 void function2() throw ( runtime_error )
18 {
19     function3();
20 } // end function function2
21
22 void function1() throw ( runtime_error )
23 {
24     function2();
25 } // end function function1
26

```

fig23_03.cpp (Part 1 of 2)



```

27 int main()
28 {
29     try {
30         function1();
31     } // end try
32     catch ( runtime_error e )
33     {
34         cout << "Exception occurred: " << e.what() << endl;
35     } // end catch
36
37     return 0;
38 } // end function main

```

fig23_03.cpp (Part 2 of 2)

Exception occurred: runtime_error in function3

Program Output



23.12 Constructors, Destructors and Exception Handling

- **What to do with an error in a constructor?**
 - A constructor cannot return a value - how do we let the outside world know of an error?
 - Keep defective object and hope someone tests it
 - Set some variable outside constructor
 - A thrown exception can tell outside world about a failed constructor
 - catch handler must have a copy constructor for thrown object

23.12 Constructors, Destructors and Exception Handling (II)

- **Thrown exceptions in constructors**
 - Destructors called for all completed base-class objects and member objects before exception thrown
 - If the destructor that is originally called due to stack unwinding ends up throwing an exception, `terminate` called
 - If object has partially completed member objects when exception thrown, destructors called for completed objects
- **Resource leak**
 - Exception comes before code that releases a resource
 - One solution: initialize local object when resource acquired
 - Destructor will be called before exception occurs
- **catch exceptions from destructors**
 - Enclose code that calls them in `try` block followed by appropriate `catch` block

23.13 Exceptions and Inheritance

- Exception classes can be derived from base classes
- If `catch` can get a pointer/reference to a base class, can also `catch` pointers/references to derived classes

23.14 Processing new Failures

- **If new could not allocate memory**
 - Old method - use `assert` function
 - If `new` returns 0, `abort` (Does not allow program to recover)
 - Modern method (header `<new>`)
 - `new` throws `bad_alloc` exception
 - Method used depends on compiler
 - On some compilers: use `new(nothrow)` instead of `new` to have `new` return 0 when it fails
 - Function `set_new_handler(functionName)` – sets which function is called when `new` fails.
 - Function can return no value and take no arguments
 - `new` will not throw `bad_alloc`
- **new : Loop that tries to acquire memory**
- **A new handler function should either:**
 - Make more memory available by deleting other dynamically allocated memory and return to the loop in operator `new`
 - Throw an exception of type `bad_alloc`
 - Call function `abort` or `exit` (header `<cstdlib>`) to terminate program

```

1 // Fig. 23.4: fig23_04.cpp
2 // Demonstrating new returning 0
3 // when memory is not allocated
4 #include <iostream>
5
6 using std::cout;
7
8 int main()
9 {
10     double *ptr[ 50 ];
11
12     for ( int i = 0; i < 50; i++ ) {
13         ptr[ i ] = new double[ 5000000 ];
14
15         if ( ptr[ i ] == 0 ) { // new failed to allocate memory
16             cout << "Memory allocation failed for ptr[ "
17                 << i << " ]\n";
18             break;
19         } // end if
20         else
21             cout << "Allocated 5000000 doubles in ptr[ "
22                 << i << " ]\n";
23     } // end for
24
25     return 0;
26 } // end function main

```

fig23_04.cpp

Program Output

```

Allocated 5000000 doubles in ptr[ 0 ]
Allocated 5000000 doubles in ptr[ 1 ]
Allocated 5000000 doubles in ptr[ 2 ]
Allocated 5000000 doubles in ptr[ 3 ]
Memory allocation failed for ptr[ 4 ]

```



Programação

```

1 // Fig. 23.5: fig23_05.cpp
2 // Demonstrating new throwing bad_alloc
3 // when memory is not allocated
4 #include <iostream>
5
6 using std::cout;
7 using std::endl;
8
9 #include <new>
10
11 using std::bad_alloc;
12
13 int main()
14 {
15     double *ptr[ 50 ];
16
17     try {
18         for ( int i = 0; i < 50; i++ ) {
19             ptr[ i ] = new double[ 5000000 ];
20             cout << "Allocated 5000000 doubles in ptr[ "
21                 << i << " ]\n";
22         } // end for
23     } // end try

```

fig23_05.cpp (Part 1 of 2)




```

24 catch ( bad_alloc exception ) {
25     cout << "Exception occurred: "
26         << exception.what() << endl;
27 } // end catch
28
29 return 0;
30 } // end function main

```

fig23_05.cpp (Part 2 of 2)

Program Output

```

Allocated 5000000 doubles in ptr[ 0 ]
Allocated 5000000 doubles in ptr[ 1 ]
Allocated 5000000 doubles in ptr[ 2 ]
Allocated 5000000 doubles in ptr[ 3 ]
Exception occurred: Allocation Failure

```



```

1 // Fig. 23.6: fig23_06.cpp
2 // Demonstrating set_new_handler
3 #include <iostream>
4
5 using std::cout;
6 using std::cerr;
7
8 #include <new>
9 #include <cstdlib>
10
11 using std::set_new_handler;
12
13 void customNewHandler()
14 {
15     cerr << "customNewHandler was called";
16     abort();
17 } // end function customNewHandler
18
19 int main()
20 {
21     double *ptr[ 50 ];
22     set_new_handler( customNewHandler );
23
24     for ( int i = 0; i < 50; i++ ) {
25         ptr[ i ] = new double[ 5000000 ];
26     }

```

fig23_06.cpp (Part 1 of 2)



```

27     cout << "Allocated 5000000 doubles in ptr[ "
28         << i << " ]\n";
29 } // end for
30
31 return 0;
32 } // end function main

```

fig23_06.cpp (Part 2 of 2)
Program Output

```

Allocated 5000000 doubles in ptr[ 0 ]
Allocated 5000000 doubles in ptr[ 1 ]
Allocated 5000000 doubles in ptr[ 2 ]
Allocated 5000000 doubles in ptr[ 3 ]
customNewHandler was called

```



23.15 Class auto_ptr and Dynamic Memory Allocation

- **Pointers to dynamic memory**
 - Memory leak can occur if exceptions happens before delete command
 - Use class template auto_ptr (header <memory>) to resolve this
 - auto_ptr objects act just like pointers
 - Automatically deletes what it points to when it is destroyed (leaves scope)
 - Can use * and -> like normal pointers



```

1 // Fig. 23.7: fig23_07.cpp
2 // Demonstrating auto_ptr
3 #include <iostream>
4
5 using std::cout;
6 using std::endl;
7
8 #include <memory>
9
10 using std::auto_ptr;
11
12 class Integer {
13 public:
14     Integer( int i = 0 ) : value( i )
15     { cout << "Constructor for Integer " << value << endl; }
16     ~Integer()
17     { cout << "Destructor for Integer " << value << endl; }
18     void setInteger( int i ) { value = i; }
19     int getInteger() const { return value; }
20 private:
21     int value;
22 }; // end class Integer
23

```

fig23_07.cpp (Part 1 of 2)



```

24 int main()
25 {
26     cout << "Creating an auto_ptr object that points "
27         << "to an Integer\n";
28
29     auto_ptr< Integer > ptrToInteger( new Integer( 7 ) );
30
31     cout << "Using the auto_ptr to manipulate the Integer\n";
32     ptrToInteger->setInteger( 99 );
33     cout << "Integer after setInteger: "
34         << ( *ptrToInteger ).getInteger()
35         << "\nTerminating program" << endl;
36
37     return 0;
38 } // end function main

```

fig23_07.cpp (Part 2 of 2)

```

Creating an auto_ptr object that points to an Integer
Constructor for Integer 7
Using the auto_ptr to manipulate the Integer
Integer after setInteger: 99
Terminating program
Destructor for Integer 99

```

Program Output



23.16 Standard Library Exception Hierarchy

- **Exceptions fall into categories**
 - Hierarchy of exception classes
 - Base class exception (header `<exception>`)
 - Function `what()` issues appropriate error message
 - Derived classes: `runtime_error` and `logic_error` (header `<stdexcept>`)
- **Class `logic_error`**
 - Errors in program logic, can be prevented by writing proper code
 - Derived classes:
 - `invalid_argument` - invalid argument passed to function
 - `length_error` - length larger than maximum size allowed was used
 - `out_of_range` - out of range subscript

23.16 Standard Library Exception Hierarchy (II)

- **Class `runtime_error`**
 - Errors detected at execution time
 - Derived classes:
 - `overflow_error` - arithmetic overflow
 - `underflow_error` - arithmetic underflow
- **Other classes derived from exception**
 - Exceptions thrown by C++ language features
 - `new` - `bad_alloc`
 - `dynamic_cast` - `bad_cast`
 - `typeid` - `bad_typeid`
 - Put `std::bad_exception` in throw list
 - `unexpected()` will throw `bad_exception` instead of calling function set by `set_unexpected`

Complementos de Programação de Computadores – Aula 6b

Tratamento de Exceções

Mestrado Integrado em Electrónica Industrial e Computadores

Luís Paulo Reis

lpreis1970@gmail.com / lpreis@dsi.uminho.pt

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,
Universidade do Minho, Portugal

(Slides Baseados em P.Deitel e H.Deitel 2010)

