

Programação – Aula Teórica 10

Estruturas, Uniões e Enumerações

Luís Paulo Reis

lpreis@dsi.uminho.pt

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,
Universidade do Minho, Portugal

(Slides Baseados em Deitel e Deitel 2010 e L.P.Reis et al., 2006)



Structures, Unions and Enumerations

Outline

10.1 Introduction

10.2 Structure Definitions

10.3 Initializing Structures

10.4 Accessing Members of Structures

10.5 Using Structures with Functions

10.6 typedef

10.7 Example: High-Performance Card Shuffling and Dealing Simulation

10.8 Unions

10.9 Bitwise Operators

10.10 Bit Fields

10.11 Enumeration Constants

Objectives

- **In this lesson, you will learn:**
 - To be able to create and use structures, unions and enumerations
 - To be able to pass structures to functions call by value and call by reference
 - To be able to manipulate data with the bitwise operators
 - To be able to create bit fields for storing data compactly

10.1 Introduction

- **Structures**
 - Collections of related variables (aggregates) under one name
 - Can contain variables of different data types
 - Commonly used to define records to be stored in files
 - Combined with pointers, can create linked lists, stacks, queues, and trees

10.2 Structure Definitions

- **Example**

```
struct card {  
    char *face;  
    char *suit;  
};
```

- struct introduces the definition for structure card
- card is the structure name and is used to declare variables of the structure type
- card contains two members of type char *
 - These members are face and suit

10.2 Structure Definitions

- **struct information**
 - A struct cannot contain an instance of itself
 - Can contain a member that is a pointer to the same structure type
 - A structure definition does not reserve space in memory
 - Instead creates a new data type used to define structure variables
- **Definitions**
 - Defined like other variables:

```
card oneCard, deck[ 52 ], *cPtr;
```
 - Can use a comma separated list:

```
struct card {  
    char *face;  
    char *suit;  
} oneCard, deck[ 52 ], *cPtr;
```

10.2 Structure Definitions



Fig. 10.1) A possible storage alignment for a variable of type struct example showing an undefined area in memory. §

- **Valid Operations**
 - Assigning a structure to a structure of the same type
 - Taking the address (&) of a structure
 - Accessing the members of a structure
 - Using the `sizeof` operator to determine the size of a structure

10.3 Initializing Structures

- **Initializer lists**

- Example:

- ```
card oneCard = { "Three", "Hearts" };
```

- **Assignment statements**

- Example:

- ```
card threeHearts = oneCard;
```

- Could also define and initialize threeHearts as follows:

- ```
card threeHearts;
```

- ```
threeHearts.face = "Three";
```

- ```
threeHearts.suit = "Hearts";
```



## 10.4 Accessing Members of Structures

- **Accessing structure members**
  - Dot operator (.) used with structure variables

```
card myCard;
printf("%s", myCard.suit);
```
  - Arrow operator (->) used with pointers to structure variables

```
card *myCardPtr = &myCard;
printf("%s", myCardPtr->suit);
```
  - `myCardPtr->suit` is equivalent to  
`( *myCardPtr ).suit`

```
1 /* Fig. 10.2: fig10_02.c
2 Using the structure member and
3 structure pointer operators */
4 #include <stdio.h>
5
6 /* card structure definition */
7 struct card {
8 char *face; /* define pointer face */
9 char *suit; /* define pointer suit */
10 }; /* end structure card */
11
12 int main()
13 {
14 struct card a; /* define struct a */
15 struct card *aPtr; /* define a pointer to card */
16
17 /* place strings into card structures */
18 a.face = "Ace";
19 a.suit = "Spades";
20
21 aPtr = &a; /* assign address of a to aPtr */
22
```

```
23 printf("%s%s\n%s%s\n%s%s\n", a.face, " of ", a.suit,
24 aPtr->face, " of ", aPtr->suit,
25 (*aPtr).face, " of ", (*aPtr).suit);
26
27 return 0; /* indicates successful termination */
28
29 } /* end main */
```

Ace of Spades  
Ace of Spades  
Ace of Spades

## 10.5 Using Structures With Functions

- **Passing structures to functions**
  - Pass entire structure
    - Or, pass individual members
  - Both pass call by value
- **To pass structures call-by-reference**
  - Pass its address
  - Pass reference to it
- **To pass arrays call-by-value**
  - Create a structure with the array as a member
  - Pass the structure

## 10.6 typedef

- **typedef**
  - Creates synonyms (aliases) for previously defined data types
  - Use typedef to create shorter type names
  - Example:

```
typedef struct Card *CardPtr;
```
  - Defines a new type name CardPtr as a synonym for type struct Card \*
  - typedef does not create a new data type
    - Only creates an alias

## 10.7 Example: High-Performance Card-shuffling and Dealing Simulation

- **Pseudocode:**
  - Create an array of card structures
  - Put cards in the deck
  - Shuffle the deck
  - Deal the cards

```

1 /* Fig. 10.3: fig10_03.c
2 The card shuffling and dealing program using structures */
3 #include <stdio.h>
4 #include <stdlib.h>
5 #include <time.h>
6
7 /* card structure definition */
8 struct card {
9 const char *face; /* define pointer face */
10 const char *suit; /* define pointer suit */
11 }; /* end structure card */
12
13 typedef struct card Card;
14
15 /* prototypes */
16 void fillDeck(Card * const wDeck, const char * wFace[],
17 const char * wSuit[]);
18 void shuffle(Card * const wDeck);
19 void deal(const Card * const wDeck);
20
21 int main()
22 {
23 Card deck[52]; /* define array of Cards */
24

```

```

25 /* initialize array of pointers */
26 const char *face[] = { "Ace", "Deuce", "Three", "Four", "Five",
27 "Six", "Seven", "Eight", "Nine", "Ten",
28 "Jack", "Queen", "King"};
29
30 /* initialize array of pointers */
31 const char *suit[] = { "Hearts", "Diamonds", "Clubs", "Spades"};
32
33 srand(time(NULL)); /* randomize */
34
35 fillDeck(deck, face, suit); /* load the deck with cards */
36 shuffle(deck); /* put cards in random order */
37 deal(deck); /* deal all 52 cards */
38
39 return 0; /* indicates successful termination */
40
41 } /* end main */
42
43 /* place strings into card structures */
44 void fillDeck(Card * const wDeck, const char * wFace[],
45 const char * wSuit[])
46 {
47 int i; /* counter */
48

```



```

49 /* loop through wDeck */
50 for (i = 0; i <= 51; i++) {
51 wDeck[i].face = wFace[i % 13];
52 wDeck[i].suit = wSuit[i / 13];
53 } /* end for */
54
55 } /* end function fillDeck */
56
57 /* shuffle cards */
58 void shuffle(Card * const wDeck)
59 {
60 int i; /* counter */
61 int j; /* variable to hold random value between 0 - 51 */
62 Card temp; /* define temporary structure for swapping Cards */
63
64 /* loop through wDeck randomly swapping Cards */
65 for (i = 0; i <= 51; i++) {
66 j = rand() % 52;
67 temp = wDeck[i];
68 wDeck[i] = wDeck[j];
69 wDeck[j] = temp;
70 } /* end for */
71
72 } /* end function shuffle */
73

```



Escoc  
Univ

```
74 /* deal cards */
75 void deal(const Card * const wDeck)
76 {
77 int i; /* counter */
78
79 /* loop through wDeck */
80 for (i = 0; i <= 51; i++) {
81 printf("%5s of %-8s%c", wDeck[i].face, wDeck[i].suit,
82 (i + 1) % 2 ? '\t' : '\n');
83 } /* end for */
84
85 } /* end function deal */
```



|                   |                   |
|-------------------|-------------------|
| Four of Clubs     | Three of Hearts   |
| Three of Diamonds | Three of Spades   |
| Four of Diamonds  | Ace of Diamonds   |
| Nine of Hearts    | Ten of Clubs      |
| Three of Clubs    | Four of Hearts    |
| Eight of Clubs    | Nine of Diamonds  |
| Deuce of Clubs    | Queen of Clubs    |
| Seven of Clubs    | Jack of Spades    |
| Ace of Clubs      | Five of Diamonds  |
| Ace of Spades     | Five of Clubs     |
| Seven of Diamonds | Six of Spades     |
| Eight of Spades   | Queen of Hearts   |
| Five of Spades    | Deuce of Diamonds |
| Queen of Spades   | Six of Hearts     |
| Queen of Diamonds | Seven of Hearts   |
| Jack of Diamonds  | Nine of Spades    |
| Eight of Hearts   | Five of Hearts    |
| King of Spades    | Six of Clubs      |
| Eight of Diamonds | Ten of Spades     |
| Ace of Hearts     | King of Hearts    |
| Four of Spades    | Jack of Hearts    |
| Deuce of Hearts   | Jack of Clubs     |
| Deuce of Spades   | Ten of Diamonds   |
| Seven of Spades   | Nine of Clubs     |
| King of Clubs     | Six of Diamonds   |
| Ten of Hearts     | King of Diamonds  |

# 10.8 Unions

- **union**
  - Memory that contains a variety of objects over time
  - Only contains one data member at a time
  - Members of a union share space
  - Conserves storage
  - Only the last data member defined can be accessed
- **union definitions (same as struct):**

```
union Number {
 int x;
 float y;
};
union Number value;
```
- **Valid union operations**
  - Assignment to union of same type: =
  - Taking address: &
  - Accessing union members: .
  - Accessing members using pointers: ->

```
1 /* Fig. 10.5: fig10_05.c
2 An example of a union */
3 #include <stdio.h>
4
5 /* number union definition */
6 union number {
7 int x; /* define int x */
8 double y; /* define double y */
9 }; /* end union number */
10
11 int main()
12 {
13 union number value; /* define union value */
14
15 value.x = 100; /* put an integer into the union */
16 printf("%s\n%s\n%s%d\n%s%f\n\n",
17 "Put a value in the integer member",
18 "and print both members.",
19 "int: ", value.x,
20 "double:\n", value.y);
21 }
```



```

22 value.y = 100.0; /* put a double into the same union */
23 printf("%s\n%s\n\n%s%d\n\n%s%f\n",
24 "Put a value in the floating member",
25 "and print both members.",
26 "int: ", value.x,
27 "double:\n", value.y);
28
29 return 0; /* indicates successful termination */
30
31 } /* end main */

```

Put a value in the integer member and print both members.

```
int: 100
```

double:

[illegible]

Put a value in the floating member  
and print both members.

```
int: 0
```

double:

100.000000

# 10.9 Bitwise Operators

- **All data represented internally as sequences of bits**
  - Each bit can be either 0 or 1
  - Sequence of 8 bits forms a byte

| Operator |                      | Description                                                                                                                                                 |
|----------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| &        | bitwise AND          | The bits in the result are set to 1 if the corresponding bits in the two operands are both 1.                                                               |
|          | bitwise inclusive OR | The bits in the result are set to 1 if at least one of the corresponding bits in the two operands is 1.                                                     |
| ^        | bitwise exclusive OR | The bits in the result are set to 1 if exactly one of the corresponding bits in the two operands is 1.                                                      |
| <<       | left shift           | Shifts the bits of the first operand left by the number of bits specified by the second operand; fill from the right with 0 bits.                           |
| >>       | right shift          | Shifts the bits of the first operand right by the number of bits specified by the second operand; the method of filling from the left is machine dependent. |
| ~        | one's complement     | All 0 bits are set to 1 and all 1 bits are set to 0.                                                                                                        |

Fig. 10.6 The bitwise operators.



```
1 /* Fig. 10.7: fig10_07.c
2 Printing an unsigned integer in bits */
3 #include <stdio.h>
4
5 void displayBits(unsigned value); /* prototype */
6
7 int main()
8 {
9 unsigned x; /* variable to hold user input */
10
11 printf("Enter an unsigned integer: ");
12 scanf("%u", &x);
13
14 displayBits(x);
15
16 return 0; /* indicates successful termination */
17
18 } /* end main */
19
20 /* display bits of an unsigned integer value */
21 void displayBits(unsigned value)
22 {
23 unsigned c; /* counter */
24
```



```

25 /* define displayMask and left shift 31 bits */
26 unsigned displayMask = 1 << 31;
27
28 printf("%7u = ", value);
29
30 /* loop through bits */
31 for (c = 1; c <= 32; c++) {
32 putchar(value & displayMask ? '1' : '0');
33 value <<= 1; /* shift value left by 1 */
34
35 if (c % 8 == 0) { /* output space after 8 bits */
36 putchar(' ');
37 } /* end if */
38
39 } /* end for */
40
41 putchar('\n');
42 } /* end function displayBits */

```

Enter an unsigned integer: 65000  
 65000 = 00000000 00000000 11111101 11101000

# 10.9 Bitwise Operators

| Bit 1 | Bit 2 | Bit 1 & Bit 2 |
|-------|-------|---------------|
| 0     | 0     | 0             |
| 1     | 0     | 0             |
| 0     | 1     | 0             |
| 1     | 1     | 1             |

Fig. 10.8 Results of combining two bits with the bitwise AND operator &.

```
1 /* Fig. 10.9: fig10_09.c
2 Using the bitwise AND, bitwise inclusive OR, bitwise
3 exclusive OR and bitwise complement operators */
4 #include <stdio.h>
5
6 void displayBits(unsigned value); /* prototype */
7
8 int main()
9 {
10 unsigned number1; /* define number1 */
11 unsigned number2; /* define number2 */
12 unsigned mask; /* define mask */
13 unsigned setBits; /* define setBits */
14
15 /* demonstrate bitwise & */
16 number1 = 65535;
17 mask = 1;
18 printf("The result of combining the following\n");
19 displayBits(number1);
20 displayBits(mask);
21 printf("using the bitwise AND operator & is\n");
22 displayBits(number1 & mask);
23
```

```
24 /* demonstrate bitwise | */
25 number1 = 15;
26 setBits = 241;
27 printf("\nThe result of combining the following\n");
28 displayBits(number1);
29 displayBits(setBits);
30 printf("using the bitwise inclusive OR operator | is\n");
31 displayBits(number1 | setBits);
32
33 /* demonstrate bitwise exclusive OR */
34 number1 = 139;
35 number2 = 199;
36 printf("\nThe result of combining the following\n");
37 displayBits(number1);
38 displayBits(number2);
39 printf("using the bitwise exclusive OR operator ^ is\n");
40 displayBits(number1 ^ number2);
41
42 /* demonstrate bitwise complement */
43 number1 = 21845;
44 printf("\nThe one's complement of\n");
45 displayBits(number1);
46 printf("is\n");
47 displayBits(~number1);
48
```

```
49 return 0; /* indicates successful termination */
50
51 } /* end main */
52
53 /* display bits of an unsigned integer value */
54 void displayBits(unsigned value)
55 {
56 unsigned c; /* counter */
57
58 /* declare displayMask and left shift 31 bits */
59 unsigned displayMask = 1 << 31;
60
61 printf("%10u = ", value);
62
63 /* loop through bits */
64 for (c = 1; c <= 32; c++) {
65 putchar(value & displayMask ? '1' : '0');
66 value <<= 1; /* shift value left by 1 */
67
68 if (c % 8 == 0) { /* output a space after 8 bits */
69 putchar(' ');
70 } /* end if */
71
72 } /* end for */
73
74 putchar('\n');
75 } /* end function displayBits */
```

The result of combining the following

65535 = 00000000 00000000 11111111 11111111

1 = 00000000 00000000 00000000 00000001

using the bitwise AND operator & is

1 = 00000000 00000000 00000000 00000001

The result of combining the following

15 = 00000000 00000000 00000000 00001111

241 = 00000000 00000000 00000000 11110001

using the bitwise inclusive OR operator | is

255 = 00000000 00000000 00000000 11111111

The result of combining the following

139 = 00000000 00000000 00000000 10001011

199 = 00000000 00000000 00000000 11000111

using the bitwise exclusive OR operator ^ is

76 = 00000000 00000000 00000000 01001100

The one's complement of

21845 = 00000000 00000000 01010101 01010101

is

4294945450 = 11111111 11111111 10101010 10101010

# 10.9 Bitwise Operators

| Bit 1 | Bit 2 | Bit 1   Bit 2 |
|-------|-------|---------------|
| 0     | 0     | 0             |
| 1     | 0     | 1             |
| 0     | 1     | 1             |
| 1     | 1     | 1             |

Fig. 10.11 Results of combining two bits with the bitwise inclusive OR operator |.

| Bit 1 | Bit 2 | Bit 1 ^ Bit 2 |
|-------|-------|---------------|
| 0     | 0     | 0             |
| 1     | 0     | 1             |
| 0     | 1     | 1             |
| 1     | 1     | 0             |

Fig. 10.12 Results of combining two bits with the bitwise exclusive OR operator ^.

```
1 /* Fig. 10.13: fig10_13.c
2 Using the bitwise shift operators */
3 #include <stdio.h>
4
5 void displayBits(unsigned value); /* prototype */
6
7 int main()
8 {
9 unsigned number1 = 960; /* initialize number1 */
10
11 /* demonstrate bitwise left shift */
12 printf("\nThe result of left shifting\n");
13 displayBits(number1);
14 printf("8 bit positions using the ");
15 printf("left shift operator << is\n");
16 displayBits(number1 << 8);
17
18 /* demonstrate bitwise right shift */
19 printf("\nThe result of right shifting\n");
20 displayBits(number1);
21 printf("8 bit positions using the ");
22 printf("right shift operator >> is\n");
23 displayBits(number1 >> 8);
24
```



```
25 return 0; /* indicates successful termination */
26
27 } /* end main */
28
29 /* display bits of an unsigned integer value */
30 void displayBits(unsigned value)
31 {
32 unsigned c; /* counter */
33 /* declare displayMask
34 and left shift 31 bits */
35 unsigned displayMask = 1 << 31;
36
37 printf("%7u = ", value);
38
39 /* loop through bits */
40 for (c = 1; c <= 32; c++) {
41 putchar(value & displayMask ? '1' : '0');
42 value <= 1; /* shift value left by 1 */
43
44 if (c % 8 == 0) { /* output a space after 8 bits */
45 putchar(' ');
46 } /* end if */
47
48 } /* end for */
49
50 putchar('\n');
51 } /* end function displayBits */
```

The result of left shifting

960 = 00000000 00000000 00000011 11000000  
8 bit positions using the left shift operator << is  
245760 = 00000000 00000011 11000000 00000000

The result of right shifting

960 = 00000000 00000000 00000011 11000000  
8 bit positions using the right shift operator >> is  
3 = 00000000 00000000 00000000 00000011

## 10.9 Bitwise Operators

| Bitwise assignment operators |                                           |
|------------------------------|-------------------------------------------|
| &=                           | Bitwise AND assignment operator.          |
| =                            | Bitwise inclusive OR assignment operator. |
| ^=                           | Bitwise exclusive OR assignment operator. |
| <<=                          | Left-shift assignment operator.           |
| >>=                          | Right-shift assignment operator.          |

Fig. 10.14 The bitwise assignment operators.

# 10.9 Bitwise Operators

| Operator                          | Associativity | Type           |
|-----------------------------------|---------------|----------------|
| () [] . ->                        | left to right | Highest        |
| + - ++ -- ! & * ~ sizeof (type)   | right to left | Unary          |
| * / %                             | left to right | multiplicative |
| + -                               | left to right | additive       |
| << >>                             | left to right | shifting       |
| < <= > >=                         | left to right | relational     |
| == !=                             | left to right | equality       |
| &                                 | left to right | bitwise AND    |
| ^                                 | left to right | bitwise OR     |
|                                   | left to right | bitwise OR     |
| &&                                | left to right | logical AND    |
|                                   | left to right | logical OR     |
| ?:                                | right to left | conditional    |
| = += -= *= /= &=  = ^= <<= >>= %= | right to left | assignment     |
| ,                                 | left to right | comma          |

Fig. 10.15 Operator precedence and associativity.

## 10.10 Bit Fields

- **Bit field**
  - Member of a structure whose size (in bits) has been specified
  - Enable better memory utilization
  - Must be defined as `int` or `unsigned`
  - Cannot access individual bits
- **Defining bit fields**
  - Follow `unsigned` or `int` member with a colon (`:`) and an integer constant representing the width of the field
  - Example:

```
struct BitCard {
 unsigned face : 4;
 unsigned suit : 2;
 unsigned color : 1;
};
```

## 10.10 Bit Fields

- **Unnamed bit field**

- Field used as padding in the structure
- Nothing may be stored in the bits

```
struct Example {
 unsigned a : 13;
 unsigned : 3;
 unsigned b : 4;
}
```

- Unnamed bit field with zero width aligns next bit field to a new storage unit boundary

```

> 1 /* Fig. 10.16: fig10_16.c
2 Representing cards with bit fields in a struct */
3
4 #include <stdio.h>
5
6 /* bitCard structure definition with bit fields */
7 struct bitCard {
8 unsigned face : 4; /* 4 bits; 0-15 */
9 unsigned suit : 2; /* 2 bits; 0-3 */
10 unsigned color : 1; /* 1 bit; 0-1 */
11 }; /* end struct bitCard */
12
13 typedef struct bitCard Card;
14
15 void fillDeck(Card * const wDeck); /* prototype */
16 void deal(const Card * const wDeck); /* prototype */
17
18 int main()
19 {
20 Card deck[52]; /* create array of cards */
21
22 fillDeck(deck);
23 deal(deck);
24
25 return 0; /* indicates successful termination */
26

```



Escoc  
Univ

```
27 } /* end main */
28
29 /* initialize cards */
30 void fillDeck(Card * const wDeck)
31 {
32 int i; /* counter */
33
34 /* loop through wDeck */
35 for (i = 0; i <= 51; i++) {
36 wDeck[i].face = i % 13;
37 wDeck[i].suit = i / 13;
38 wDeck[i].color = i / 26;
39 } /* end for */
40
41 } /* end function fillDeck */
42
43 /* output cards in two column format; cards 0-25 subscripted with
44 k1 (column 1); cards 26-51 subscripted k2 (column 2) */
45 void deal(const Card * const wDeck)
46 {
47 int k1; /* subscripts 0-25 */
48 int k2; /* subscripts 26-51 */
49
```

```

50 /* loop through wDeck */
51 for (k1 = 0, k2 = k1 + 26; k1 <= 25; k1++, k2++) {
52 printf("Card:%3d Suit:%2d color:%2d ",
53 wDeck[k1].face, wDeck[k1].suit, wDeck[k1].color);
54 printf("Card:%3d Suit:%2d color:%2d\n",
55 wDeck[k2].face, wDeck[k2].suit, wDeck[k2].color);
56 } /* end for */
57
58 } /* end function deal */

```

|          |         |          |          |         |          |
|----------|---------|----------|----------|---------|----------|
| Card: 0  | Suit: 0 | Color: 0 | Card: 0  | Suit: 2 | Color: 1 |
| Card: 1  | Suit: 0 | Color: 0 | Card: 1  | Suit: 2 | Color: 1 |
| Card: 2  | Suit: 0 | Color: 0 | Card: 2  | Suit: 2 | Color: 1 |
| Card: 3  | Suit: 0 | Color: 0 | Card: 3  | Suit: 2 | Color: 1 |
| Card: 4  | Suit: 0 | Color: 0 | Card: 4  | Suit: 2 | Color: 1 |
| Card: 5  | Suit: 0 | Color: 0 | Card: 5  | Suit: 2 | Color: 1 |
| Card: 6  | Suit: 0 | Color: 0 | Card: 6  | Suit: 2 | Color: 1 |
| Card: 7  | Suit: 0 | Color: 0 | Card: 7  | Suit: 2 | Color: 1 |
| Card: 8  | Suit: 0 | Color: 0 | Card: 8  | Suit: 2 | Color: 1 |
| Card: 9  | Suit: 0 | Color: 0 | Card: 9  | Suit: 2 | Color: 1 |
| Card: 10 | Suit: 0 | Color: 0 | Card: 10 | Suit: 2 | Color: 1 |
| Card: 11 | Suit: 0 | Color: 0 | Card: 11 | Suit: 2 | Color: 1 |
| Card: 12 | Suit: 0 | Color: 0 | Card: 12 | Suit: 2 | Color: 1 |
| Card: 0  | Suit: 1 | Color: 0 | Card: 0  | Suit: 3 | Color: 1 |
| Card: 1  | Suit: 1 | Color: 0 | Card: 1  | Suit: 3 | Color: 1 |
| Card: 2  | Suit: 1 | Color: 0 | Card: 2  | Suit: 3 | Color: 1 |
| Card: 3  | Suit: 1 | Color: 0 | Card: 3  | Suit: 3 | Color: 1 |
| Card: 4  | Suit: 1 | Color: 0 | Card: 4  | Suit: 3 | Color: 1 |
| Card: 5  | Suit: 1 | Color: 0 | Card: 5  | Suit: 3 | Color: 1 |
| Card: 6  | Suit: 1 | Color: 0 | Card: 6  | Suit: 3 | Color: 1 |
| Card: 7  | Suit: 1 | Color: 0 | Card: 7  | Suit: 3 | Color: 1 |
| Card: 8  | Suit: 1 | Color: 0 | Card: 8  | Suit: 3 | Color: 1 |
| Card: 9  | Suit: 1 | Color: 0 | Card: 9  | Suit: 3 | Color: 1 |
| Card: 10 | Suit: 1 | Color: 0 | Card: 10 | Suit: 3 | Color: 1 |
| Card: 11 | Suit: 1 | Color: 0 | Card: 11 | Suit: 3 | Color: 1 |
| Card: 12 | Suit: 1 | Color: 0 | Card: 12 | Suit: 3 | Color: 1 |



# 10.11 Enumeration Constants

- **Enumeration**
  - Set of integer constants represented by identifiers
  - Enumeration constants are like symbolic constants whose values are automatically set
    - Values start at 0 and are incremented by 1
    - Values can be set explicitly with =
    - Need unique constant names
  - Example:

```
enum Months { JAN = 1, FEB, MAR, APR, MAY, JUN, JUL, AUG,
 SEP, OCT, NOV, DEC};
```

    - Creates a new type enum Months in which the identifiers are set to the integers 1 to 12
  - Enumeration variables can only assume their enumeration constant values (not the integer representations)

```

1 /* Fig. 10.18: fig10_18.c
2 Using an enumeration type */
3 #include <stdio.h>
4
5 /* enumeration constants represent months of the year */
6 enum months { JAN = 1, FEB, MAR, APR, MAY, JUN,
7 JUL, AUG, SEP, OCT, NOV, DEC };
8
9 int main()
10 {
11 enum months month; /* can contain any of the 12 months */
12
13 /* initialize array of pointers */
14 const char *monthName[] = { "", "January", "February", "March",
15 "April", "May", "June", "July", "August", "September", "October",
16 "November", "December" };
17
18 /* loop through months */
19 for (month = JAN; month <= DEC; month++) {
20 printf("%2d%11s\n", month, monthName[month]);
21 } /* end for */
22
23 return 0; /* indicates successful termination */
24 } /* end main */

```

|    |           |
|----|-----------|
| 1  | January   |
| 2  | February  |
| 3  | March     |
| 4  | April     |
| 5  | May       |
| 6  | June      |
| 7  | July      |
| 8  | August    |
| 9  | September |
| 10 | October   |
| 11 | November  |
| 12 | December  |

# Questões?

# Programação – Aula Teórica 10

## Estruturas, Uniões e Enumerações

**Luís Paulo Reis**

[lpreis@dsi.uminho.pt](mailto:lpreis@dsi.uminho.pt)

Professor Associado do Departamento de Sistemas de Informação, Escola de Engenharia,  
Universidade do Minho, Portugal

(Slides Baseados em Deitel e Deitel 2010 e L.P.Reis et al., 2006)

