


# Appendix K - Block Diagrams

Schematic-level layout of the three internal buses that connect the chips inside the Intuition Engine: the video compositor, the audio mixer, and the main system bus. Each diagram is drawn at the granularity a programmer needs to reason about cross-chip interactions, not at the granularity an engineer would use to fabricate the silicon.

## K.1 The video compositor


The compositor has six layers. Each layer comes from one of the six video engines. Layers are listed in back-to-front order; a higher layer covers the lower ones where it draws non-transparent pixels.



Each engine writes into its own framebuffer (in main VRAM or in its private aperture); the compositor reads all six on every output line and resolves them into a single stream of RGBA pixels.

## K.2 The audio mixer


The audio mixer has ten engine inputs (plus the SFX channels) and one stereo output stream.



The SoundChip's own filter, the SID family's resonant filter, and the engine-internal effects all feed the mix before the global overdrive / filter / reverb stage; the global effects apply once per output sample to the summed signal.

## K.3 The system bus


Every CPU and every device hangs off one shared 64-bit physical bus. The bus carries 64-bit physical addresses and supports 8, 16, 32, and 64-bit transfers through CPU and device adapters. It arbitrates simultaneous accesses on a round-robin basis; there is no priority encoding above the CPU / DMA distinction.



IE32, M68K, and x86 are 32-bit bus clients. The 8-bit CPUs (6502, Z80) reach the bus through an address translator that turns their 16-bit address space into selected low-window bus addresses, with the bank registers described in Chapters 26 and 27 selecting which translation applies.

## K.4 Coprocessor channels


The coprocessor block (Chapter 31) is a many-to-many channel between the main CPU and a pool of worker CPUs. Each worker listens on its own ring buffer; the main CPU posts work items into the ring and reads the result back.



Six worker types share the protocol: an IE64 worker, an IE32 worker, a 6502 worker, a Z80 worker, an M68K worker, and an x86 worker. The main CPU is whichever one boots the machine; all the others are available as workers when not booted.

## K.5 Bus translation for the small CPUs

The 6502 and Z80 see the same overall bus through a 16-bit-to- 64-bit translator. In practice their documented apertures target the low memory and MMIO window. The translator has two independent functions:



The bank registers at \$F700-\$F705 (low/hi pairs for apertures 1, 2, 3) and \$F7F0 (aperture 0) are captured before the translator runs. A write to \$F700 does not reach \$F0700; it loads the low byte of bank register 1.