# µA78L00 SERIES
POSITIVE-VOLTAGE REGULATORS

- **3-Terminal Regulators**
- **Output Current up to 100 mA**
- **No External Components**
- **Internal Thermal-Overload Protection**
- **Internal Short-Circuit Current Limiting**
- **Direct Replacements for Fairchild µA78L00 Series**

D PACKAGE
(TOP VIEW)

OUTPUT	1	8	INPUT
COMMON	2	7	COMMON
COMMON	3	6	COMMON
NC	4	5	NC

NC – No internal connection

LP PACKAGE
(TOP VIEW)

INPUT
COMMON
OUTPUT

TO–226AA

PK PACKAGE
(TOP VIEW)

INPUT

COMMON

OUTPUT

description

This series of fixed-voltage integrated-circuit voltage regulators is designed for a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation. In addition, they can be used with power-pass elements to make high-current voltage regulators. One of these regulators can deliver up to 100 mA of output current. The internal limiting and thermal-shutdown features of these regulators make them essentially immune to overload. When used as a replacement for a zener diode-resistor combination, an effective improvement in output impedance can be obtained, together with lower bias current.

The µA78L00C series is characterized for operation over the virtual junction temperature range of 0°C to 125°C.

AVAILABLE OPTIONS

T_J	$V_{O(NOM)}$ (V)	PACKAGED DEVICES						CHIP FORM (Y)
		SMALL OUTLINE (D)		PLASTIC CYLINDRICAL (LP)		SOT-89 (PK)		
		OUTPUT VOLTAGE TOLERANCE						
		5%	10%	5%	10%	5%	10%	
0°C to 125°C	2.6	µA78L02ACD	–	µA78L02ACLP	µA78L02CLP	µA78L02ACPK	µA78L02CPK	µA78L02Y
	5	µA78L05ACD	µA78L05CD	µA78L05ACLP	µA78L05CLP	µA78L05ACPK	µA78L05CPK	µA78L05Y
	6.2	µA78L06ACD	µA78L06CD	µA78L06ACLP	µA78L06CLP	µA78L06ACPK	µA78L06CPK	µA78L06Y
	8	µA78L08ACD	µA78L08CD	µA78L08ACLP	µA78L08CLP	µA78L08ACPK	µA78L08CPK	µA78L08Y
	9	µA78L09ACD	µA78L09CD	µA78L09ACLP	µA78L09CLP	µA78L09ACPK	µA78L09CPK	µA78L09Y
	10	µA78L10ACD	–	µA78L10ACLP	µA78L10CLP	µA78L10ACPK	µA78L10CPK	µA78L10Y
	12	µA78L12ACD	µA78L12CD	µA78L12ACLP	µA78L12CLP	µA78L12ACPK	µA78L12CPK	µA78L12Y
	15	µA78L15ACD	µA78L15CD	µA78L15ACLP	µA78L15CLP	µA78L15ACPK	µA78L15CPK	µA78L15Y

D and LP packages are available taped and reeled. Add the suffix R to the device type (e.g., µA78L05ACDR). The PK package is only available taped and reeled (e.g., µA78L02ACPKR). Chip forms are tested at T_A = 25°C.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

TEXAS INSTRUMENTS

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

schematic

NOTE: Resistor values shown are nominal.

absolute maximum ratings over operating temperature range (unless otherwise noted)†

		μA78Lxx	UNIT
Input voltage, V_I	μA78L02AC, μA78L05C–μA78L09C, μA78L10AC	30	V
	μA78L12C, μA78L12AC, μA78L15C, μA78L15AC	35	
Package thermal impedance, θ_{JA} (see Notes 1 and 2)	D package	97	°C
	LP package	156	
	PK package	52	
Virtual junction temperature range, T_J		0 to 150	°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds		260	°C
Storage temperature range, T_{stg}		−65 to 150	°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. Maximum power dissipation is a function of T_J(max), θ_{JA}, and T_A. The maximum allowable power dissipation at any allowable ambient temperature is $P_D = (T_J(max) - T_A)/\theta_{JA}$. Operating at the absolute maximum T_J of 150°C can impact reliability. Due to variations in individual device electrical characteristics and thermal resistance, the built-in thermal-overload protection may be activated at power levels slightly above or below the rated dissipation.
2. The package thermal impedance is calculated in accordance with JESD 51, except for through-hole packages, which use a trace length of zero.

recommended operating conditions

		MIN	MAX	UNIT
Input voltage, V_I	μA78L02AC	4.75	20	V
	μA78L05C, μA78L05AC	7	20	
	μA78L06C, μA78L06AC	8.5	20	
	μA78L08C, μA78L08AC	10.5	23	
	μA78L09C, μA78L09AC	11.5	24	
	μA78L10AC	12.5	25	
	μA78L12C, μA78L12AC	14.5	27	
	μA78L15C, μA78L15AC	17.5	30	
Output current, I_O			100	mA
Operating virtual junction temperature, T_J		0	125	°C

μA78L00 SERIES
POSITIVE-VOLTAGE REGULATORS

electrical characteristics at specified virtual junction temperature, V_I = 9 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	μA78L02C MIN	μA78L02C TYP	μA78L02C MAX	UNIT
Output voltage	V_I = 4.75 V to 20 V, I_O = 1 mA to 40 mA	25°C	2.5	2.6	2.7	V
		0°C to 125°C	2.45		2.75	
	I_O = 1 mA to 70 mA	0°C to 125°C	2.45		2.75	
Input voltage regulation	V_I = 4.75 V to 20 V	25°C		20	100	mV
	V_I = 5 V to 20 V			16	75	
Ripple rejection	V_I = 6 V to 20 V, f = 120 Hz	25°C	43	51		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		12	50	mV
	I_O = 1 mA to 40 mA			6	25	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		30		μV
Dropout voltage		25°C		1.7		V
Bias current		25°C		3.6	6	mA
		125°C			5.5	
Bias current change	V_I = 5 V to 20 V	0°C to 125°C			2.5	mA
	I_O = 1 mA to 40 mA				0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 10 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	μA78L05C MIN	μA78L05C TYP	μA78L05C MAX	μA78L05AC MIN	μA78L05AC TYP	μA78L05AC MAX	UNIT
Output voltage	V_I = 7 V to 20 V, I_O = 1 mA to 40 mA	25°C	4.6	5	5.4	4.8	5	5.2	V
		0°C to 125°C	4.5		5.5	4.75		5.25	
	I_O = 1 mA to 70 mA	0°C to 125°C	4.5		5.5	4.75		5.25	
Input voltage regulation	V_I = 7 V to 20 V	25°C		32	200		32	150	mV
	V_I = 8 V to 20 V			26	150		26	100	
Ripple rejection	V_I = 8 V to 18 V, f = 120 Hz	25°C	40	49		41	49		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		15	60		15	60	mV
	I_O = 1 mA to 40 mA			8	30		8	30	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		42			42		μV
Dropout voltage		25°C		1.7			1.7		V
Bias current		25°C		3.8	6		3.8	6	mA
		125°C			5.5			5.5	
Bias current change	V_I = 8 V to 20 V	0°C to 125°C			1.5			1.5	mA
	I_O = 1 mA to 40 mA				0.2			0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

TEXAS
INSTRUMENTS

POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

electrical characteristics at specified virtual junction temperature, V_I = 12 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	μA78L06C MIN	μA78L06C TYP	μA78L06C MAX	μA78L06AC MIN	μA78L06AC TYP	μA78L06AC MAX	UNIT
Output voltage	V_I = 8.5 V to 20 V, I_O = 1 mA to 40 mA	25°C	5.7	6.2	6.7	5.95	6.2	6.45	V
		0°C to 125°C	5.6		6.8	5.9		6.5	
	I_O = 1 mA to 70 mA	0°C to 125°C	5.6		6.8	5.9		6.5	
Input voltage regulation	V_I = 8.5 V to 20 V	25°C		35	200		35	175	mV
	V_I = 9 V to 20 V			29	150		29	125	
Ripple rejection	V_I = 10 V to 20 V, f = 120 Hz	25°C	39	48		40	48		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		16	80		16	80	mV
	I_O = 1 mA to 40 mA			9	40		9	40	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		46			46		μV
Dropout voltage		25°C		1.7			1.7		V
Bias current		25°C		3.9	6		3.9	6	mA
		125°C			5.5			5.5	
Bias current change	V_I = 9 V to 20 V	0°C to 125°C			1.5			1.5	mA
	I_O = 1 mA to 40 mA				0.2			0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 14 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	μA78L08C MIN	μA78L08C TYP	μA78L08C MAX	μA78L08AC MIN	μA78L08AC TYP	μA78L08AC MAX	UNIT
Output voltage	V_I = 10.5 V to 23 V, I_O = 1 mA to 40 mA	25°C	7.36	8	8.64	7.7	8	8.3	V
		0°C to 125°C	7.2		8.8	7.6		8.4	
	I_O = 1 mA to 70 mA	0°C to 125°C	7.2		8.8	7.6		8.4	
Input voltage regulation	V_I = 10.5 V to 23 V	25°C		42	200		42	175	mV
	V_I = 11 V to 23 V			36	150		36	125	
Ripple rejection	V_I = 13 V to 23 V, f = 120 Hz	25°C	36	46		37	46		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		18	80		18	80	mV
	I_O = 1 mA to 40 mA			10	40		10	40	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		54			54		μV
Dropout voltage		25°C		1.7			1.7		V
Bias current		25°C		4	6		4	6	mA
		125°C			5.5			5.5	
Bias current change	V_I = 5 V to 20 V	0°C to 125°C			1.5			1.5	mA
	I_O = 1 mA to 40 mA				0.2			0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 16 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	μA78L09C			μA78L09AC			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Output voltage	V_I = 12 V to 24 V, I_O = 1 mA to 40 mA	25°C	8.3	9	9.7	8.6	9	9.4	V
		0°C to 125°C	8.1		9.9	8.55		9.45	
	I_O = 1 mA to 70 mA	0°C to 125°C	8.1		9.9	8.55		9.45	
Input voltage regulation	V_I = 12 V to 24 V	25°C		45	225		45	175	mV
	V_I = 13 V to 24 V			40	175		40	125	
Ripple rejection	V_I = 15 V to 25 V, f = 120 Hz	25°C	36	45		38	45		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		19	90		19	90	mV
	I_O = 1 mA to 40 mA			11	40		11	40	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		58			58		μV
Dropout voltage		25°C		1.7			1.7		V
Bias current		25°C		4.1	6		4.1	6	mA
		125°C			5.5			5.5	
Bias current change	V_I = 13 V to 24 V	0°C to 125°C			1.5			1.5	mA
	I_O = 1 mA to 40 mA				0.2			0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 14 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	μA78L10AC			UNIT
			MIN	TYP	MAX	
Output voltage	V_I = 13 V to 25 V, I_O = 1 mA to 40 mA	25°C	9.6	10	10.4	V
		0°C to 125°C	9.5		10.5	
	I_O = 1 mA to 70 mA	0°C to 125°C	9.5		10.5	
Input voltage regulation	V_I = 13 V to 25 V	25°C		51	175	mV
	V_I = 14 V to 25 V			42	125	
Ripple rejection	V_I = 15 V to 25 V, f = 120 Hz	25°C	37	44		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		20	90	mV
	I_O = 1 mA to 40 mA			11	40	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		62		μV
Dropout voltage		25°C		1.7		V
Bias current		25°C		4.2	6	mA
		125°C			5.5	
Bias current change	V_I = 14 V to 25 V	0°C to 125°C			1.5	mA
	I_O = 1 mA to 40 mA				0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 19 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	µA78L12C			µA78L12AC			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Output voltage	V_I = 14 V to 27 V, I_O = 1 mA to 40 mA	25°C	11.1	12	12.9	11.5	12	12.5	V
		0°C to 125°C	10.8		13.2	11.4		12.6	
	I_O = 1 mA to 70 mA	0°C to 125°C	10.8		13.2	11.4		12.6	
Input voltage regulation	V_I = 14.5 V to 27 V	25°C		55	250		55	250	mV
	V_I = 16 V to 27 V			49	200		49	200	
Ripple rejection	V_I = 15 V to 25 V, f = 120 Hz	25°C	36	42		37	42		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		22	100		22	100	mV
	I_O = 1 mA to 40 mA			13	50		13	50	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		70			70		µV
Dropout voltage		25°C		1.7			1.7		V
Bias current		25°C		4.3	6.5		4.3	6.5	mA
		125°C			6			6	
Bias current change	V_I = 16 V to 27 V	0°C to 125°C			1.5			1.5	mA
	I_O = 1 mA to 40 mA				0.2			0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-µF capacitor across the input and a 0.1-µF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 23 V, I_O = 40 mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_J†	µA78L15C			µA78L15AC			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Output voltage	V_I = 17.5 V to 30 V, I_O = 1 mA to 40 mA	25°C	13.8	15	16.2	14.4	15	15.6	V
		0°C to 125°C	13.5		16.5	14.25		15.75	
	I_O = 1 mA to 70 mA	0°C to 125°C	13.5		16.5	14.25		15.75	
Input voltage regulation	V_I = 17.5 V to 30 V	25°C		65	300		65	300	mV
	V_I = 20 V to 30 V			58	250		58	250	
Ripple rejection	V_I = 18.5 V to 28.5 V, f = 120 Hz	25°C	33	39		34	39		dB
Output voltage regulation	I_O = 1 mA to 100 mA	25°C		25	150		25	150	mV
	I_O = 1 mA to 40 mA			15	75		15	75	
Output noise voltage	f = 10 Hz to 100 kHz	25°C		82			82		µV
Dropout voltage		25°C		1.7			1.7		V
Bias current		25°C		4.6	6.5		4.6	6.5	mA
		125°C			6			6	
Bias current change	V_I = 10 V to 30 V	0°C to 125°C			1.5			1.5	mA
	I_O = 1 mA to 40 mA				0.2			0.1	

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-µF capacitor across the input and a 0.1-µF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 9 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	μA78L02Y			UNIT
		MIN	TYP	MAX	
Output voltage			2.6		V
Input voltage regulation	V_I = 4.75 V to 20 V		20		mV
	V_I = 5 V to 20 V		16		
Ripple rejection	V_I = 6 V to 20 V, f = 120 Hz		51		dB
Output voltage regulation	I_O = 1 mA to 100 mA		12		mV
	I_O = 1 mA to 40 mA		6		
Output noise voltage	f = 10 Hz to 100 kHz		30		μV
Dropout voltage			1.7		V
Bias current			3.6		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 10 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	μA78L05Y			UNIT
		MIN	TYP	MAX	
Output voltage			5		V
Input voltage regulation	V_I = 7 V to 20 V		32		mV
	V_I = 8 V to 20 V		26		
Ripple rejection	V_I = 8 V to 18 V, f = 120 Hz		49		dB
Output voltage regulation	I_O = 1 mA to 100 mA		15		mV
	I_O = 1 mA to 40 mA		8		
Output noise voltage	f = 10 Hz to 100 kHz		42		μV
Dropout voltage			1.7		V
Bias current			3.8		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 12 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	μA78L06Y			UNIT
		MIN	TYP	MAX	
Output voltage			6.2		V
Input voltage regulation	V_I = 8.5 V to 20 V		35		mV
	V_I = 9 V to 20 V		29		
Ripple rejection	V_I = 10 V to 20 V, f = 120 Hz		48		dB
Output voltage regulation	I_O = 1 mA to 100 mA		16		mV
	I_O = 1 mA to 40 mA		9		
Output noise voltage	f = 10 Hz to 100 kHz		46		μV
Dropout voltage			1.7		V
Bias current			3.9		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 14 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	μA78L08Y			UNIT
		MIN	TYP	MAX	
Output voltage			8		V
Input voltage regulation	V_I = 10.5 V to 23 V		42		mV
	V_I = 11 V to 23 V		36		
Ripple rejection	V_I = 13 V to 23 V, f = 120 Hz		46		dB
Output voltage regulation	I_O = 1 mA to 100 mA		18		mV
	I_O = 1 mA to 40 mA		10		
Output noise voltage	f = 10 Hz to 100 kHz		54		μV
Dropout voltage			1.7		V
Bias current			4		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 16 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	μA78L09Y			UNIT
		MIN	TYP	MAX	
Output voltage			9		V
Input voltage regulation	V_I = 12 V to 24 V		45		mV
	V_I = 13 V to 24 V		40		
Ripple rejection	V_I = 15 V to 25 V, f = 120 Hz		45		dB
Output voltage regulation	I_O = 1 mA to 100 mA		19		mV
	I_O = 1 mA to 40 mA		11		
Output noise voltage	f = 10 Hz to 100 kHz		58		μV
Dropout voltage			1.7		V
Bias current			4.1		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 14 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	μA78L10Y			UNIT
		MIN	TYP	MAX	
Output voltage			10		V
Input voltage regulation	V_I = 13 V to 25 V		51		mV
	V_I = 14 V to 25 V		42		
Ripple rejection	V_I = 15 V to 25 V, f = 120 Hz		44		dB
Output voltage regulation	I_O = 1 mA to 100 mA		20		mV
	I_O = 1 mA to 40 mA		11		
Output noise voltage	f = 10 Hz to 100 kHz		62		μV
Dropout voltage			1.7		V
Bias current			4.2		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-μF capacitor across the input and a 0.1-μF capacitor across the output.

**TEXAS
INSTRUMENTS**

µA78L00 SERIES
POSITIVE-VOLTAGE REGULATORS

SLVS010I – JANUARY 1976 – REVISED JULY 1999

electrical characteristics at specified virtual junction temperature, V_I = 19 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	µA78L12Y MIN	µA78L12Y TYP	µA78L12Y MAX	UNIT
Output voltage			12		V
Input voltage regulation	V_I = 14.5 V to 27 V		55		mV
	V_I = 16 V to 27 V		49		
Ripple rejection	V_I = 15 V to 25 V, f = 120 Hz		42		dB
Output voltage regulation	I_O = 1 mA to 100 mA		22		mV
	I_O = 1 mA to 40 mA		13		
Output noise voltage	f = 10 Hz to 100 kHz		70		µV
Dropout voltage			1.7		V
Bias current			4.3		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-µF capacitor across the input and a 0.1-µF capacitor across the output.

electrical characteristics at specified virtual junction temperature, V_I = 23 V, I_O = 40 mA, T_J = 25°C (unless otherwise noted)

PARAMETER	TEST CONDITIONS†	µA78L15Y MIN	µA78L15Y TYP	µA78L15Y MAX	UNIT
Output voltage			15		V
Input voltage regulation	V_I = 17.5 V to 30 V		65		mV
	V_I = 20 V to 30 V		58		
Ripple rejection	V_I = 18.5 V to 28.5 V, f = 120 Hz		39		dB
Output voltage regulation	I_O = 1 mA to 100 mA		25		mV
	I_O = 1 mA to 40 mA		15		
Output noise voltage	f = 10 Hz to 100 kHz		82		µV
Dropout voltage			1.7		V
Bias current			4.6		mA

† Pulse-testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33-µF capacitor across the input and a 0.1-µF capacitor across the output.

TEXAS INSTRUMENTS

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

## APPLICATION INFORMATION

**Figure 1. Fixed-Output Regulator**

Figure 2. Positive Regulator in Negative Configuration (V$_I$ Must Float)

Figure 3. Adjustable-Output Regulator

$$I_O = (V_O/R1) + I_O \text{ Bias Current}$$

**Figure 4. Current Regulator**

APPLICATION INFORMATION

Figure 5. Regulated Dual Supply

operation with a load common to a voltage of opposite polarity

In many cases, a regulator powers a load that is not connected to ground but, instead, is connected to a voltage source of opposite polarity (e.g., operational amplifiers, level-shifting circuits, etc.). In these cases, a clamp diode should be connected to the regulator output as shown in Figure 6. This protects the regulator from output polarity reversals during startup and short-circuit operation.


Figure 6. Output Polarity-Reversal-Protection Circuit

reverse-bias protection

Occasionally, the input voltage to the regulator can collapse faster than the output voltage. This can occur, for example, when the input supply is crowbarred during an output overvoltage condition. If the output voltage is greater than approximately 7 V, the emitter-base junction of the series-pass element (internal or external) could break down and be damaged. To prevent this, a diode shunt can be employed as shown in Figure 7.


Figure 7. Reverse-Bias-Protection Circuit

TEXAS INSTRUMENTS
POST OFFICE BOX 655303 ● DALLAS, TEXAS 75265

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.

Texas Instruments

This file is the datasheet for the following electronic components:

MA78L09ACPK - http://www.ti.com/product/ma78l09acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L06Y - http://www.ti.com/product/ma78l06y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L08ACD - http://www.ti.com/product/ma78l08acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L08ACLP - http://www.ti.com/product/ma78l08aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L08ACPK - http://www.ti.com/product/ma78l08acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L06ACLP - http://www.ti.com/product/ma78l06aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L06ACPK - http://www.ti.com/product/ma78l06acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L08CD - http://www.ti.com/product/ma78l08cd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

78L05 - http://www.ti.com/product/78l05?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L00 - http://www.ti.com/product/ma78l00?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L08CLP - http://www.ti.com/product/ma78l08clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L08CPK - http://www.ti.com/product/ma78l08cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L06CD - http://www.ti.com/product/ma78l06cd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L02CPK - http://www.ti.com/product/ma78l02cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L06ACD - http://www.ti.com/product/ma78l06acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L09ACLP - http://www.ti.com/product/ma78l09aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L02CLP - http://www.ti.com/product/ma78l02clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L02ACPK - http://www.ti.com/product/ma78l02acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L02Y - http://www.ti.com/product/ma78l02y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L06CLP - http://www.ti.com/product/ma78l06clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L06CPK - http://www.ti.com/product/ma78l06cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L05ACD - http://www.ti.com/product/ma78l05acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L08Y - http://www.ti.com/product/ma78l08y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L05ACLP - http://www.ti.com/product/ma78l05aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L00D - http://www.ti.com/product/ma78l00d?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L00LP - http://www.ti.com/product/ma78l00lp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L00PK - http://www.ti.com/product/ma78l00pk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L09ACD - http://www.ti.com/product/ma78l09acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L02ACD - http://www.ti.com/product/ma78l02acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L02ACLP - http://www.ti.com/product/ma78l02aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L10CPK - http://www.ti.com/product/ma78l10cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L12CPK - http://www.ti.com/product/ma78l12cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L12CLP - http://www.ti.com/product/ma78l12clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L12CD - http://www.ti.com/product/ma78l12cd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L12ACPK - http://www.ti.com/product/ma78l12acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L12ACLP - http://www.ti.com/product/ma78l12aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L12ACD - http://www.ti.com/product/ma78l12acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L10Y - http://www.ti.com/product/ma78l10y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L12Y - http://www.ti.com/product/ma78l12y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L10CLP - http://www.ti.com/product/ma78l10clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L10ACPK - http://www.ti.com/product/ma78l10acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L10ACLP - http://www.ti.com/product/ma78l10aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L10ACD - http://www.ti.com/product/ma78l10acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L09Y - http://www.ti.com/product/ma78l09y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L09CPK - http://www.ti.com/product/ma78l09cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L09CLP - http://www.ti.com/product/ma78l09clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L09CD - http://www.ti.com/product/ma78l09cd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L05Y - http://www.ti.com/product/ma78l05y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L15ACD - http://www.ti.com/product/ma78l15acd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L05CLP - http://www.ti.com/product/ma78l05clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L15Y - http://www.ti.com/product/ma78l15y?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L15CPK - http://www.ti.com/product/ma78l15cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L15CLP - http://www.ti.com/product/ma78l15clp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L15CD - http://www.ti.com/product/ma78l15cd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L15ACPK - http://www.ti.com/product/ma78l15acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L05CPK - http://www.ti.com/product/ma78l05cpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L05CD - http://www.ti.com/product/ma78l05cd?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L15ACLP - http://www.ti.com/product/ma78l15aclp?HQS=TI-null-null-dscatalog-df-pf-null-wwe

MA78L05ACPK - http://www.ti.com/product/ma78l05acpk?HQS=TI-null-null-dscatalog-df-pf-null-wwe