Sparc4D: A Compact Explicit 4D Representation for Dynamic Scenes

Di Yang[1] Zhihao Li[2] Yanhai Xiong[1,*] Yufei Wang[2,*,†]
[1]College of William & Mary [2]SparcAI Inc.
dyang06@wm.edu zhihao.li@sparclab.ai yxiong05@wm.edu yufei.wang@sparclab.ai

Abstract

A compact dynamic-scene representation must retain both the surfaces seen over time and the appearance needed to render them from new viewpoints. We present Sparc4D, a feed-forward autoencoder that encodes a monocular video with known cameras into a sparse 4D scene state. Static features are shared across the clip. Spatially anchored temporal slots store the time-varying features with a median $5.0\times$ fewer values than per-frame storage, with negligible change in novel-view quality. A sparse decoder produces 2D Gaussian surfels, while stored source pixels preserve fine texture through geometric reprojection. The state includes one full source frame and dynamic-region pixels sampled every fourth frame, alongside learned features and sparse occupancy. For a 32-frame MultiCamVideo clip, it averages 0.67M 32-bit-equivalent values on random windows and 0.66M on the first-32 protocol. On first-32, Sparc4D reaches 21.97 dB, compared with 20.40 dB for MoVieS. On randomly placed windows, the two reach 17.39 and 17.26 dB. Without fine-tuning on real data, Sparc4D transfers to DyCheck and Neu3D, where stored texture improves LPIPS while slightly reducing PSNR. Frozen Sparc4D features also support a manipulation policy that reaches 81.3% success on ManiSkill3 StackCube from 1,000 demonstrations.

1. Introduction

Feed-forward reconstruction methods can recover dynamic scenes from monocular video and render them from new viewpoints. The scene representation must retain information across time and stay small enough to store and reuse. Pixel-aligned Gaussian methods such as MoVieS [25] can produce large outputs when motion is materialized across a clip. Compact Gaussian predictors such as C4G [16] reduce the number of primitives and trade reconstruction fidelity for size. We ask how a monocular video can be encoded into a compact 4D scene state that supports explicit novel-view rendering.

Video tokenizers [30, 54] compress image sequences, but their pixel-space outputs do not by themselves provide an explicit 3D rendering interface. Sparse 3D autoencoders [47, 48] provide such structure for individual assets. Dynamic scenes add a choice of what to share over time and what to vary. Storing a separate reconstruction for every frame repeats static content, while compressing the whole scene into one low-resolution latent loses fine appearance. We therefore store static and dynamic content differently, and store fine texture separately from the latent.

Sparc4D lifts a posed video into sparse 3D observations using estimated depth. Static observations share one latent representation across the clip. Dynamic observations are first encoded per frame, then compressed into a small number of temporal slots at each occupied latent cell. A finer appearance code retains texture separately from the 32^3 latent. The decoder reconstructs 2D Gaussian surfels [13] for explicit rendering. Sparse occupancy is stored with the features.

Fine texture follows a second storage path: one full source frame preserves static detail, and dynamic-region pixels sampled every fourth frame refresh moving surfaces. These stored pixels are reprojected onto decoded geometry, following image-based rendering and depth-image-based video coding [3, 8, 10, 41]. The complete state therefore combines learned spatial features with sparse stored texture. Decoding reads only this state and the cameras.

We evaluate reconstruction quality and state size on MultiCamVideo [2], including a C4G model fine-tuned on the same training split. We also test reduced-output MoVieS variants and zero-shot transfer to DyCheck [11] and Neu3D [20]. We analyze temporal compression, regional reconstruction and stored texture. Finally, we train a manipulation policy on frozen encoder features to test whether the static and dynamic features retain information useful for control.

The contributions are:

- A sparse 4D scene representation that shares static fea-

*Corresponding author. †Project lead.
Preprint. Work in progress. 2026 Sep 26th.

tures and compresses dynamic features into spatially anchored temporal slots.
- A surfel decoder that combines fine-grid appearance codes with stored static and dynamic texture, using explicit geometry to render both paths into new views.
- Experiments showing that temporal slots compress time-varying features with negligible change in novel-view reconstruction quality, and that Sparc4D matches or exceeds the PSNR of MoVieS, 4DGT and C4G with a smaller state.

2. Related Work

Dynamic scene reconstruction. Dynamic radiance fields model time-varying scenes through deformation [32, 33, 35], scene flow [21], or image-based rendering [22]. Gaussian splatting [15] supports deformable and time-varying primitives [29, 46, 52]. Shape of Motion and MoSca regularize motion using low-dimensional bases or scaffolds [19, 44]. These methods optimize a scene-specific representation. We instead learn an encoder and decoder shared across scenes.

Feed-forward reconstruction. Image-based reconstruction networks predict 3D representations in one pass [4, 6, 12, 49, 56]. VGGT and MonST3R estimate geometry and cameras from static or dynamic inputs [42, 55]. For dynamic reconstruction, L4GM and STORM predict time-dependent Gaussians [37, 51]. MoVieS attaches motion to pixel-aligned Gaussians [25], 4DGT predicts space-time Gaussians from monocular video [50], and C4G uses timestamp-conditioned queries to decode a compact Gaussian set [16]. We compare with the latter three using their public weights and additionally fine-tune C4G on our training split at its original output budget. We compare methods by the size of their encoded scene state and its reconstruction quality.

Scene and video compression. Video tokenizers such as MAGVIT-v2 and Cosmos encode image sequences into spatiotemporal latents [30, 54]. TRELLIS, TRELLIS.2, Sparc3D and XCube use structured or hierarchical sparse representations for 3D assets [23, 38, 47, 48]. SceneTok encodes static scenes into tokens decoded by a diffusion model [1]. We adapt the TRELLIS.2 shape autoencoder to dynamic scenes and add a temporal bottleneck based on learned queries [14, 27]. Structured 4D latents have also been used for robot planning [24]; Section 4.5 relates a policy built on Sparc4D features to their StackCube result.

Image-based rendering. View-dependent texture mapping, unstructured lumigraphs and learned image-based rendering use reference images to texture scene geometry [3, 8, 39, 43]. Depth-image-based video coding similarly combines stored images and geometry to synthesize new views [10, 41]. Our stored texture follows this principle, but uses geometry reconstructed from the stored 4D state rather than transmitted depth maps. For evaluation, we also adopt the distinction between observed and unobserved regions motivated by DyCheck [11].

3. Method

Fig. 1 summarizes Sparc4D, including the temporal slots (Sec. 3.2) and the stored texture (Sec. 3.4).

3.1. Scene observations

The input is a monocular clip of $T = 32$ RGB frames $\{I_t\}$ at 256×256, recorded by one moving *source camera* with known intrinsics and world-to-camera poses. We estimate depth using Depth Anything 3 [26], conditioned on these cameras. A pixel $\mathbf{x}$ is lifted into world coordinates as

$$\mathbf{p}_t(\mathbf{x}) = \mathbf{R}_t^\top \left(D_t(\mathbf{x}) \mathbf{K}^{-1} \tilde{\mathbf{x}} - \mathbf{t}_t \right), \tag{1}$$

where D_t is estimated depth, $(\mathbf{R}_t, \mathbf{t}_t)$ is the camera pose, and $\tilde{\mathbf{x}}$ is the homogeneous pixel coordinate. Each point carries RGB, a depth-derived normal and its position.

Static and dynamic observations serve different roles in the state. We pool static points across the clip, but retain dynamic points separately for each frame. To separate them, we test whether another frame sees through a point's expected position. Foreground object masks [58] extend these motion seeds to whole objects, including intervals when an object briefly stops. Appendix A gives the test and mask parameters.

We voxelize the observations inside a scene-adaptive cube at 512^3 resolution. A larger, coarser cube stores static points outside this region. We call the three resulting voxel sets the static, coarse and dynamic *layers* of the scene. An equirectangular environment map stores more distant observations by ray direction [7]. Pixels covered by neither surfels nor the map receive the source video's mean colour. Each occupied voxel stores mean RGB, mean normal and a within-voxel point offset. Octant colour residuals retain sub-voxel variation before encoding.

3.2. Shared static features and temporal slots

We initialize the sparse encoder–decoder from the TRELLIS.2 shape autoencoder [48]. It maps a 512^3 sparse voxel grid to a 32-channel latent on a 32^3 grid. The static, coarse and per-frame dynamic layers are encoded as separate batches with the same network weights. The static and coarse latents are stored once per clip. The decoder uses the input occupancy hierarchy for sparse upsampling; this hierarchy is part of the stored state.




Figure 1. **Overview of Sparc4D.** A shared sparse autoencoder encodes static, coarse and per-frame dynamic observations from a posed monocular clip. Static/coarse codes are stored once. Dynamic latent and appearance codes are compressed into temporal slots by independent attention modules on the 32^3 and 128^3 grids, with two slots per cell. Two learned queries pool temporal features per cell before cross-cell mixing. At observed time t, separate cell-local readouts recover dynamic codes, with appearance injected at 128^3. The three layers first merge at joint 2DGS rasterization. Stored texture is reprojected through the rendered depth and changes colour only, before background compositing. Decoding uses stored state and cameras. Photos show MultiCamVideo inputs and complete model outputs. Surfels are schematic.

The dynamic layer requires time-varying features, but need not store a separate latent for every frame. A *cell* is one position of the 32^3 latent grid. Let $\mathcal{U}$ be the union of dynamic cells over the clip, and $\mathbf{z}_{u,t}$ the latent of cell u at time t. We compress the available per-frame features into two slots per cell. The slots are two vectors with the channel width of the latent, obtained by pooling by multihead attention with two learnable seed vectors [18]:

$$\begin{aligned} \mathbf{k}_{u,t} &= \mathbf{W}\mathbf{z}_{u,t} + \phi_t(t) + \phi_p(u), \\ \mathbf{A}_u &= \mathrm{Attn}(\mathbf{Q} + \phi_p(u), \{\mathbf{k}_{u,t}\}_{t\in\mathcal{T}_u}), \\ \{\mathbf{S}_u\}_{u\in\mathcal{U}} &= \mathrm{Proj}(\mathrm{Mix}(\{\mathbf{A}_u\}_{u\in\mathcal{U}})), \\ \hat{\mathbf{z}}_{u,t} &= \mathrm{Dec}(\phi_t(t) + \phi_p(u), \mathbf{S}_u). \end{aligned} \tag{2}$$

Here $\mathcal{T}_u$ contains the frames in which cell u is occupied, and ϕ_t, ϕ_p embed time and position. Two learned queries $\mathbf{Q}$ first pool features within each cell. Self-attention then mixes the slots across cells, and a projection reduces each slot to 32 channels. To recover a latent, a query at (u,t) attends to the two stored slots of u. The decoded latent $\hat{\mathbf{z}}_{u,t}$ replaces $\mathbf{z}_{u,t}$ in the sparse decoder. The state therefore stores $2|\mathcal{U}|$ latent vectors rather than all per-frame vectors.

3.3. Appearance and surfel decoding

A cell of the 32^3 latent grid spans 16^3 input voxels. We provide a finer path for texture by storing a 4-channel appearance code on the 128^3 grid. For encoder and decoder features $\mathbf{e}_u$ and $\mathbf{g}_u$ at this resolution,

$$\mathbf{a}_u = \mathbf{W}_e\,\mathrm{LN}(\mathbf{e}_u), \qquad \mathbf{g}_u \leftarrow \mathbf{g}_u + \gamma\mathbf{W}_d\mathbf{a}_u, \tag{3}$$

where LN is layer normalization and γ is a fixed gain. Static appearance codes are shared across the clip. Dynamic appearance codes use the temporal-slot construction in Eq. 2, with two 4-channel slots per occupied 128^3 cell; the decoded appearance code is written $\hat{\mathbf{a}}_{u,t}$.

Each decoded voxel emits four 2D Gaussian surfels (2DGS) [13, 34] with degree-1 spherical-harmonics colour. The 2DGS head turns the decoder output into centre offsets, scales, rotations and opacity, as residuals from a camera-facing base configuration. The base uses the source camera at time t. The surfels of the three layers are rasterized together with gsplat [53]. Appendix A.1 gives the parameterization. Dynamic decoding uses the occupancy of frame t, so t is one of the 32 input timestamps (an *observed time*).

3.4. Stored source-pixel texture

The learned feature grids reconstruct surfaces and low-frequency appearance; stored texture retains source detail without expanding every grid cell. We store the first source frame in full and dynamic-region pixels every fourth frame. We store the pixels where the decoded dynamic layer's source-view opacity exceeds 0.5, dilated by two pixels. Pixels already stored in the first frame are not counted again.

For a target camera c (any viewpoint to be rendered) at time t, rasterization gives a colour image and median depth $\hat{d}_c$. We back-project a target pixel using $\hat{d}_c$ and project the resulting point into a stored frame. If its projected depth agrees with the depth rendered in that stored frame's source view, we use the sampled stored colour. Otherwise, or if the point falls outside the stored region, we retain the surfel colour. Both depth maps are rendered from the decoded state.

Static pixels use the first source frame. Dynamic pixels use the two stored dynamic frames that bracket t. Each frame passes the same projection and depth test, and the accepted colours are blended by temporal distance. Stored texture changes only colour; geometry and coverage come from the surfels. The projection and consistency test are specified in Appendix A.3.

3.5. Training

For each training sample, we select a 32-frame window and one source camera. Its frames form the input. We supervise frame 0, a random time t and the two stored dynamic frames bracketing t. At each of these times we render the source view and four of the remaining nine cameras. The image loss combines L_1, SSIM and LPIPS and is computed after stored texture is applied; replaced pixels supervise only opacity. Depth and normal losses supervise geometry, while a temporal loss matches inter-frame image differences. The temporal slots also receive feature-reconstruction losses. Occupancy and KL losses follow TRELLIS.2 [17, 48].

Sparc4D is initialized from the pretrained TRELLIS.2 model and trained for 30,000 steps on randomly placed 32-frame windows, with one clip per GPU on eight A800 GPUs. Appendix B gives the full objective, optimization settings, and ablation protocol.

3.6. State size

We count the stored features, sparse occupancy, environment map, background colour and stored texture. The unit is a *32-bit-equivalent value*: feature values count as one each, while occupancy entropy in bits is divided by 32. Each stored 8-bit RGB channel is counted as one 32-bit value. Shared network weights and externally supplied cameras are excluded.

Let $\mathcal{C}$ and $\mathcal{U}$ denote static/coarse cells and dynamic union cells on the 32^3 grid. Their 128^3 counterparts store appearance. With occupancy cost B_{occ} bits, environment texel set $\mathcal{E}$ and additional dynamic-pixel set $\mathcal{P}_{\mathrm{dyn}}$, the reported size is

$$N = 32|\mathcal{C}| + 64|\mathcal{U}| + 4|\mathcal{C}^{128}| + 8|\mathcal{U}^{128}| + B_{\mathrm{occ}}/32 + 4|\mathcal{E}| + 3 + 3 \cdot 256^2 + 3|\mathcal{P}_{\mathrm{dyn}}|. \quad (4)$$

Occupancy is estimated from octree symbols. For dynamic occupancy, we use the smaller estimate from independent frames or consecutive-frame XOR masks. Appendix C details this accounting. Table 10 separates the learned state from its stored texture.

4. Experiments

We ask four questions. What reconstruction quality does a compact state support? Do temporal slots reduce time-varying storage without losing quality? Does the model transfer from synthetic training to real videos? Do the learned features support robotic control?

4.1. Data and protocol

Dataset and split. MultiCamVideo (MCV) [2] contains 3,400 Unreal Engine scenes. Each scene is rendered at four focal lengths by ten synchronized cameras for 81 frames at 15 fps. A scene–focal-length pair forms one clip, giving 13,600 clips. Frames are resized to 256^2.

The held-out test set contains 101 scenes, selected by clustering DINOv2 scene features [31], with all four focal lengths of each scene, giving 404 clips. All MultiCamVideo results in this paper use this test set. Appendix E.1 gives the construction details.

Windows and cameras. The cameras coincide at the start of each video and then move apart. We therefore evaluate two window placements. The *first-32* protocol uses frames 0–31. The *random-window* protocol fixes one randomly sampled start in $[0, 49]$ for each clip. The source camera is fixed by the clip's test-list index modulo ten; the other nine cameras are targets. All methods render every target at all 32 timestamps, giving 116,352 target images per protocol.

Metrics. We report image-averaged PSNR, SSIM [45] and AlexNet-LPIPS [57]. Alongside full-image scores, we evaluate pixels classified as observed by a method-independent visibility mask. The mask uses estimated depth and foreground segmentation; dynamic foreground requires same-time source visibility. A third setting, *uniform fill*, assigns the same source-mean colour to all methods outside the mask. These settings separate reconstruction on observed regions from differences in unobserved-region rendering. Appendix E.2 specifies the masks and masked metrics.

Baselines and comparison scope. We evaluate MoVieS [25], 4DGT [50] and C4G [16] with released weights. Their training data differ from ours, so these models serve as zero-shot references. For a same-data comparison at a similar representation size, we fine-tune C4G on the MultiCamVideo training split for 30,000 steps, keeping its 2,048-Gaussian output budget. Sparc4D is trained for the same number of steps on the same split. All methods render at 256^2; input settings and coordinate alignment are given in Appendix E.3. Following VideoTok4D [5], #Floats counts the FP32 per-sequence state for 32 frames. Shared network weights are excluded, and time-conditioned Gaussians are materialized at every evaluated timestamp.

4.2. Novel-view reconstruction

On random windows, Sparc4D reaches 17.39 dB with a 0.67M-value state (Table 1). MoVieS obtains 17.26 dB; the paired per-clip difference is $+0.12 \pm 0.18$ dB (95% CI). On first-32, Sparc4D reaches 21.97 dB versus 20.40 dB for MoVieS (Table 2).

On co-visible pixels, Sparc4D obtains 19.02 dB and 0.290 LPIPS; MoVieS obtains 18.55 dB and 0.296. The paired LPIPS difference is -0.005 ± 0.008, so these perceptual scores are comparable. Uniform-fill evaluation preserves the PSNR ordering. With a smaller state than MCV-fine-tuned C4G (0.67M versus 0.92M), Sparc4D has higher full-image PSNR and lower LPIPS. Section 4.6 separates the contributions of learned features and stored texture.

Figures 2 and 3 compare the complete method with the released baselines on fixed examples selected near the median per-clip PSNR difference. The same scenes and crop locations are used for all methods; Appendix E.6 gives the selection procedure.

4.3. Size–quality comparison

We evaluate whether reducing the output of a pixel-aligned reconstructor can reach a similar size–quality tradeoff. We give MoVieS fewer input frames or a lower input resolution, or prune its Gaussians by opacity, and evaluate all variants on the first-32 protocol (Table 2).

With four input frames, MoVieS obtains 20.04 dB with 28.5M output values; its single-frame variant obtains 18.97 dB with 7.1M. Sparc4D reaches 21.97 dB and 0.199 LPIPS with 0.66M values, about $11\times$ smaller than the single-frame variant. Lowering the input resolution or pruning by opacity reduces quality more strongly at comparable sizes.

4.4. Transfer to real videos

We evaluate zero-shot transfer to DyCheck iPhone [11] and Neu3D [20](Table 3) without real-data fine-tuning. DyCheck uses official co-visibility masks, whereas Neu3D uses full-image metrics; Appendix E.4 and Appendix E.5 give the full protocols.

On DyCheck, Sparc4D reaches 13.82 dB mPSNR, close to MoVieS at 13.95 dB, with higher mLPIPS (0.543 versus 0.488). On Neu3D, it reaches 16.57 dB across nine target cameras and 18.54 dB on cam00; 4DGT reaches 17.33 and 19.51 dB.

Table 4 isolates the effect of stored texture using identical model weights and inputs. On both real datasets, additional texture progressively improves LPIPS while slightly reducing PSNR.

4.5. Downstream manipulation

We evaluate the learned scene features on StackCube in ManiSkill3 [40], where a robot must grasp the red cube and stack it on the green cube (Fig. 4). After adapting the autoencoder to ManiSkill scenes, we freeze its encoder and train a flow-matching action policy on static features and the dynamic latents of the three most recent frames. Four calibrated RGB-D views provide the observations; robot masks and causal SAM 2 tracking [36] separate the static and dynamic layers. This control interface uses per-frame latents without temporal-slot compression or stored texture.

With 1,000 demonstrations, the policy reaches 81.3% success, close to the 84.0% reported by Li et al. [24]; adding 2,000 demonstrations raises it to 84.0% (Table 5). Our scene representation averages 426 static and 236 dynamic tokens, with the static features shared across the observation history. The rollout in Fig. 4 illustrates control from these features.

4.6. Representation analysis

Ablations. We first vary the number of temporal slots while holding the checkpoint, training schedule and absence of appearance codes fixed (Table 8). Increasing K from 2 to 10 raises PSNR by 0.04 dB on average (paired 95% CI: ± 0.01 dB), while dynamic-slot storage increases from 21.1K to 105.6K values per clip. The small quality gain in this 12k-step setting motivates the two-slot configuration used by the model.

Each configuration in Table 9 is trained for 10k steps from a shared 20k-step geometry-only checkpoint; Appendix B.1 gives the details.

The appearance pathway improves PSNR by 0.18 dB over geometry only, while increasing the appearance-code capacity adds another 0.06 dB. The motion mask changes PSNR by -0.04 dB, and the combined configuration differs by only $+0.01$ dB from the appearance-code configuration.

Stored-texture ablation. Table 6 varies only the stored texture of the trained model. Removing stored texture lowers PSNR from 17.39 to 16.82 dB and raises LPIPS from 0.370 to 0.469; most of this difference comes from the first

Method	Trained on MCV	#Floats	Full image PSNR↑	Full image SSIM↑	Full image LPIPS↓	AbsRel↓	Co-visible PSNR↑	Co-visible SSIM↑	Co-visible LPIPS↓	Uniform fill PSNR↑	Uniform fill SSIM↑	Uniform fill LPIPS↓
MoVieS	–	719M	*17.26*	*0.512*	**0.366**	0.615 (0.272)	*18.55*	*0.530*	*0.296*	*16.43*	*0.498*	*0.411*
4DGT	–	26.9M	14.35	0.403	0.550	0.640 (0.370)	15.14	0.411	0.538	14.49	0.412	0.546
C4G	–	*0.92M*	13.64	0.369	0.596	0.543 (0.450)	14.76	0.394	0.566	14.21	0.393	0.572
C4G	✓	*0.92M*	16.51	0.466	0.584	*0.356 (0.346)*	17.14	0.470	0.561	15.65	0.444	0.564
Sparc4D	✓	**0.67M**	**17.39**	**0.519**	*0.370*	**0.259 (0.170)**	**19.02**	**0.541**	**0.290**	**16.62**	**0.509**	**0.405**

Table 1. **Novel-view synthesis on MultiCamVideo** (404 random-window test clips, 9 target cameras × 32 frames, 256^2). Best and second-best results are shown in bold and underlined italics, respectively. Sparc4D denotes the complete method, including stored texture. #Floats follows [5]: time-conditioned Gaussian outputs are materialized at every timestamp, and other methods count their per-sequence state (Eq. 4 for ours); shared network weights are excluded. C4G is shown with released weights and after fine-tuning for 30,000 steps on the MCV training split, the number of steps used to train Sparc4D. AbsRel uses DA3 pseudo ground truth, also our input depth; parentheses give median-scale-aligned error. Co-visible metrics use the shared visibility mask. Uniform fill assigns the same colour outside that mask for all methods.




Figure 2. **Qualitative comparison, first-32 protocol.** Two fixed test scenes at frame 16, using the median-distance target camera. Orange and blue boxes mark dynamic and static 64^2 crops, enlarged below at identical coordinates for all methods. Sparc4D is the complete model; baseline images use released weights. Camera distance is shown in metres.

frame. Shorter intervals change PSNR by at most 0.03 dB but enlarge the state by up to 2.5×. Blending the two bracketing frames outperforms both single-frame reuse and no reuse across time.

Temporal compression. Table 7 compares temporal slots with per-frame dynamic features. The slots need a median 5.0× fewer values for these features, while paired PSNR changes by only $+0.006 \pm 0.005$ dB. Appendix 11 gives the component-wise storage breakdown and compression factors.

Voxelization and appearance. In the region analysis, the dynamic region of a target image is where the current-frame dynamic input voxels project, and the static region is the rest of the scene cube (Appendix E.2). Table 17 locates where dynamic detail is lost. Voxelizing current-frame dynamic pixels at 512^3 lowers source-view dynamic PSNR




Figure 3. **Qualitative comparison, random-window protocol.** Same layout and method settings as Fig. 2.

Table 2. **Size and quality** on the first-32 protocol. MoVieS uses its native motion-parameter output count here, rather than the time-materialized count in Table 1; Appendix C explains both. Our size includes all stored texture. MoVieS variants use f inputs at resolution r, or retain the k highest-opacity Gaussians.

Method	Size	PSNR↑	SSIM↑	LPIPS↓
MoVieS, 32f, 224	228M	20.40	0.643	0.207
MoVieS, 8f, 224	57.0M	20.28	0.642	0.203
MoVieS, 4f, 224	28.5M	20.04	0.628	*0.201*
MoVieS, 2f, 224	14.3M	19.61	0.619	0.219
MoVieS, 1f, 224	7.1M	18.97	0.619	0.232
MoVieS, 8f, 112	14.3M	16.90	0.435	0.558
MoVieS, top 200k	28.4M	16.25	0.485	0.491
MoVieS, top 50k	7.1M	14.96	0.434	0.642
Sparc4D	**0.66M**	**21.97**	**0.686**	**0.199**

from 27.27 dB (direct pixel rendering) to 18.12 dB. The learned state recovers 20.75 dB without stored texture. At target views, MoVieS leads in dynamic regions (16.76 versus 16.36 dB) by transporting primitives from multiple input frames to time t (Sec. 5).

Static and dynamic reconstruction. On first-32, stored texture matters most in static regions: it raises PSNR from 21.43 to 25.41 dB, above the 21.79 dB of MoVieS (Table 16). In dynamic regions, refreshing the stored pixels every fourth frame raises PSNR from 18.36 to 19.32 dB. It exceeds MoVieS by 0.34 ± 0.32 dB in paired PSNR, with similar LPIPS (0.153 versus 0.150).




Figure 4. **StackCube manipulation.** A successful rollout of the policy trained on 1,000 demonstrations, shown from one fixed camera. The robot grasps the red cube and places it on the green cube.

Texture benefit over time. The benefit of stored texture decreases later in the window (Table 18). The same trend holds when all source frames are stored. Growing source–target separation and reprojection error therefore appear to limit the benefit more than the spacing of stored frames. Dynamic refresh helps primarily at earlier timestamps.

Appendix F shows that Sparc4D preserves the DA3 depth structure more closely than the evaluated baselines.

Method	Training data	#Floats	DyCheck			Neu3D (9 targets)			Neu3D cam00
			mPSNR↑	mSSIM↑	mLPIPS↓	PSNR↑	SSIM↑	LPIPS↓	PSNR↑
MoVieS	8 public datasets (∼174K scenes)	719M	**13.95**	*0.345*	**0.488**	15.61	0.445	0.304	17.01
4DGT	∼300 h real monocular video	26.9M	11.84	0.277	0.599	**17.33**	**0.530**	**0.281**	**19.51**
C4G	Spring, Kubric, RE10K	*0.92M*	13.52	**0.351**	0.634	11.78	0.285	0.588	13.41
C4G (MCV fine-tuned)	+ MultiCamVideo	*0.92M*	13.34	0.340	0.747	15.75	0.443	0.579	16.21
Sparc4D	MultiCamVideo (synthetic)	**0.67M**	*13.82*	0.323	*0.543*	*16.57*	*0.465*	*0.291*	*18.54*

Table 3. **Zero-shot generalization to real videos.** Best and second-best results are shown in bold and underlined italics. None of the methods is fine-tuned on DyCheck or Neu3D. DyCheck uses official co-visibility evaluation; Neu3D reports nine target cameras and cam00 separately. #Floats repeats the MCV reference size for context rather than a measured real-data average.

Table 4. **Stored texture on real videos.** All rows use the same model weights and inputs. DyCheck uses official masked metrics; Neu3D uses full-image metrics over nine target cameras.

Configuration	DyCheck		Neu3D	
	mPSNR↑	mLPIPS↓	PSNR↑	LPIPS↓
w/o stored texture	14.16	0.617	16.65	0.394
w/o dynamic texture	13.98	0.555	16.59	0.319
Sparc4D	13.82	0.543	16.57	0.291

Table 5. **StackCube success and scene size.** Tokens are active cells per timestamp; d is their feature dimension. Protocols and counting details are in Appendix H.

Method	Demos	Tokens	d	Success
Li et al. [24]	1,000	∼5,700	8	84.0%
Sparc4D features	1,000	661	32	81.3%
+ additional demos	3,000	661	32	84.0%

Table 6. **Stored-texture ablation** (404 random-window clips). All rows use the same 30k-step backbone. Interval is the spacing between stored dynamic-texture frames; the first full source frame is retained except in "w/o stored texture."

Configuration	Size	PSNR↑	LPIPS↓	Dyn. LPIPS↓
w/o stored texture	0.17M	16.82	0.469	0.345
w/o dynamic texture	0.36M	17.31	0.384	0.292
Dynamic texture interval: 1	1.69M	17.42	0.367	0.258
Dynamic texture interval: 2	1.01M	17.41	0.368	0.260
Dynamic texture interval: 8	0.50M	17.34	0.371	0.266
Interval 4, no reuse across time	0.67M	17.33	0.380	0.284
Interval 4, preceding frame only	0.67M	17.35	0.370	0.263
Sparc4D (interval: 4)	0.67M	17.39	0.370	0.262

5. Limitations

The decoder uses per-frame dynamic occupancy and renders only at observed timestamps. It does not transport dynamic surfaces across time, so content hidden from the source camera at a query time is not recovered from other frames. Its cross-time reprojection assumes locally consistent geometry rather than explicit motion, so depth errors and fast motion can produce incorrect texture matches. State size varies with occupied volume and dynamic image area, and our entropy-based ledger is not an implemented codec.

Table 7. **Temporal compression ablation** on random windows. Both variants use the same trained weights and stored texture, which is included in the total state. "Per-frame" bypasses temporal-slot compression for dynamic latent and appearance features; dynamic occupancy is unchanged. Sizes are mean 32-bit-equivalent values per 32-frame clip.

Representation	Storage ↓		Reconstruction		
	Time-varying features	Total state	PSNR↑	Dyn. PSNR↑	Dyn. LPIPS↓
Per-frame	354.5K	0.96M	17.38	16.23	0.263
Temporal slots	**79.4K**	**0.67M**	17.39	16.24	0.262

6. Conclusion

Sparc4D encodes a monocular video into a sparse explicit 4D state with shared static features and spatially anchored temporal slots. Fine-grid appearance codes and stored source texture complete a 0.67M-value state that matches or exceeds the novel-view PSNR of the evaluated feed-forward reconstructors. The model transfers from synthetic training to DyCheck and Neu3D without real-data fine-tuning. Its frozen features also support a StackCube manipulation policy.

References

[1] Mohammad Asim, Christopher Wewer, and Jan Eric Lenssen. SceneTok: A compressed, diffusable token space for 3D scenes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 2

[2] Jianhong Bai, Menghan Xia, Xiao Fu, Xintao Wang, Lianrui Mu, Jinwen Cao, Zuozhu Liu, Haoji Hu, Xiang Bai, Pengfei Wan, and Di Zhang. ReCamMaster: Camera-controlled generative rendering from a single video. In *Proceedings of*

the IEEE/CVF International Conference on Computer Vision (ICCV), 2025. 1, 4

[3] Chris Buehler, Michael Bosse, Leonard McMillan, Steven Gortler, and Michael Cohen. Unstructured lumigraph rendering. In *Proceedings of SIGGRAPH*, pages 425–432, 2001. 1, 2

[4] David Charatan, Sizhe Lester Li, Andrea Tagliasacchi, and Vincent Sitzmann. pixelSplat: 3D Gaussian splats from image pairs for scalable generalizable 3D reconstruction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[5] Xinyi Chen, Hanxin Zhu, Xijun Wang, Xingrui Wang, Sen Liang, Xin Li, and Zhibo Chen. VideoTok4D: A 4D-aware video tokenizer for compact world representation. *arXiv preprint arXiv:2609.12874*, 2026. 5, 6, 14

[6] Yuedong Chen, Haofei Xu, Chuanxia Zheng, Bohan Zhuang, Marc Pollefeys, Andreas Geiger, Tat-Jen Cham, and Jianfei Cai. MVSplat: Efficient 3D Gaussian splatting from sparse multi-view images. In *European Conference on Computer Vision (ECCV)*, 2024. 2

[7] Paul Debevec. Rendering synthetic objects into real scenes: Bridging traditional and image-based graphics with global illumination and high dynamic range photography. In *Proceedings of SIGGRAPH*, pages 189–198, 1998. 2

[8] Paul E. Debevec, Camillo J. Taylor, and Jitendra Malik. Modeling and rendering architecture from photographs: A hybrid geometry- and image-based approach. In *Proceedings of SIGGRAPH*, pages 11–20, 1996. 1, 2

[9] David Eigen, Christian Puhrsch, and Rob Fergus. Depth map prediction from a single image using a multi-scale deep network. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2014. 16

[10] Christoph Fehn. Depth-image-based rendering (DIBR), compression, and transmission for a new approach on 3D-TV. In *Stereoscopic Displays and Virtual Reality Systems XI*, pages 93–104, 2004. 1, 2

[11] Hang Gao, Ruilong Li, Shubham Tulsiani, Bryan Russell, and Angjoo Kanazawa. Monocular dynamic view synthesis: A reality check. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. 1, 2, 5

[12] Yicong Hong, Kai Zhang, Jiuxiang Gu, Sai Bi, Yang Zhou, Difan Liu, Feng Liu, Kalyan Sunkavalli, Trung Bui, and Hao Tan. LRM: Large reconstruction model for single image to 3D. In *International Conference on Learning Representations (ICLR)*, 2024. 2

[13] Binbin Huang, Zehao Yu, Anpei Chen, Andreas Geiger, and Shenghua Gao. 2D Gaussian splatting for geometrically accurate radiance fields. In *SIGGRAPH 2024 Conference Papers*, 2024. 1, 3, 12, 13

[14] Andrew Jaegle, Felix Gimeno, Andy Brock, Oriol Vinyals, Andrew Zisserman, and Joao Carreira. Perceiver: General perception with iterative attention. In *International Conference on Machine Learning (ICML)*, 2021. 2

[15] Bernhard Kerbl, Georgios Kopanas, Thomas Leimkühler, and George Drettakis. 3D Gaussian splatting for real-time radiance field rendering. *ACM Transactions on Graphics*, 42 (4), 2023. 2

[16] Mungyeom Kim, Minkyeong Jeon, Honggyu An, Jaewoo Jung, Hyuna Ko, Jisang Han, Hyeonseo Yu, Donghwan Shin, Sunghwan Hong, Takuya Narihira, et al. Learning global motion with compact Gaussians for feed-forward 4D reconstruction. *arXiv preprint arXiv:2605.31595*, 2026. 1, 2, 5

[17] Diederik P. Kingma and Max Welling. Auto-encoding variational Bayes. In *International Conference on Learning Representations (ICLR)*, 2014. 4, 13

[18] Juho Lee, Yoonho Lee, Jungtaek Kim, Adam Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *International Conference on Machine Learning (ICML)*, 2019. 3

[19] Jiahui Lei, Yijia Weng, Adam W. Harley, Leonidas Guibas, and Kostas Daniilidis. MoSca: Dynamic Gaussian fusion from casual videos via 4D motion scaffolds. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2

[20] Tianye Li, Mira Slavcheva, Michael Zollhoefer, Simon Green, Christoph Lassner, Changil Kim, Tanner Schmidt, Steven Lovegrove, Michael Goesele, Richard Newcombe, and Zhaoyang Lv. Neural 3D video synthesis from multi-view video. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 1, 5, 15

[21] Zhengqi Li, Simon Niklaus, Noah Snavely, and Oliver Wang. Neural scene flow fields for space-time view synthesis of dynamic scenes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021. 2

[22] Zhengqi Li, Qianqian Wang, Forrester Cole, Richard Tucker, and Noah Snavely. DynIBaR: Neural dynamic image-based rendering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023. 2

[23] Zhihao Li, Yufei Wang, Heliang Zheng, Yihao Luo, and Bihan Wen. Sparc3d: Sparse representation and construction for high-resolution 3d shapes modeling. *Advances in Neural Information Processing Systems*, 38:118582–118600, 2026. 2

[24] Zhiyi Li, Peilin Wu, Xiaoshen Han, Ruojin Cai, and Yilun Du. Structured 4d latent predictive model for robot planning. *arXiv preprint arXiv:2607.01166*, 2026. 2, 5, 8, 16

[25] Chenguo Lin, Yuchen Lin, Panwang Pan, Yifan Yu, Tao Hu, Honglei Yan, Katerina Fragkiadaki, and Yadong Mu. MoVieS: Motion-aware 4D dynamic view synthesis in one second. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026. 1, 2, 5

[26] Haotong Lin, Sili Chen, Jun Hao Liew, Donny Y. Chen, Zhenyu Li, Guang Shi, Jiashi Feng, and Bingyi Kang. Depth anything 3: Recovering the visual space from any views. *arXiv preprint arXiv:2511.10647*, 2025. 2

[27] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020. 2

[28] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations (ICLR)*, 2019. 13

[29] Jonathon Luiten, Georgios Kopanas, Bastian Leibe, and Deva Ramanan. Dynamic 3D Gaussians: Tracking by persistent dynamic view synthesis. In *International Conference on 3D Vision (3DV)*, 2024. 2

[30] NVIDIA. Cosmos world foundation model platform for physical AI. *arXiv preprint arXiv:2501.03575*, 2025. 1, 2

[31] Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. DINOv2: Learning robust visual features without supervision. *Transactions on Machine Learning Research*, 2024. 4

[32] Keunhong Park, Utkarsh Sinha, Jonathan T. Barron, Sofien Bouaziz, Dan B. Goldman, Steven M. Seitz, and Ricardo Martin-Brualla. Nerfies: Deformable neural radiance fields. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021. 2

[33] Keunhong Park, Utkarsh Sinha, Peter Hedman, Jonathan T. Barron, Sofien Bouaziz, Dan B. Goldman, Ricardo Martin-Brualla, and Steven M. Seitz. HyperNeRF: A higher-dimensional representation for topologically varying neural radiance fields. *ACM Transactions on Graphics*, 40(6), 2021. 2

[34] Hanspeter Pfister, Matthias Zwicker, Jeroen van Baar, and Markus Gross. Surfels: Surface elements as rendering primitives. In *Proceedings of SIGGRAPH*, pages 335–342, 2000. 3, 12

[35] Albert Pumarola, Enric Corona, Gerard Pons-Moll, and Francesc Moreno-Noguer. D-NeRF: Neural radiance fields for dynamic scenes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021. 2

[36] Nikhila Ravi et al. SAM 2: Segment anything in images and videos. *arXiv preprint arXiv:2408.00714*, 2024. 5

[37] Jiawei Ren, Kevin Xie, Ashkan Mirzaei, Hanxue Liang, Xiaohui Zeng, Karsten Kreis, Ziwei Liu, Antonio Torralba, Sanja Fidler, Seung Wook Kim, and Huan Ling. L4GM: Large 4D Gaussian reconstruction model. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. 2

[38] Xuanchi Ren, Jiahui Huang, Xiaohui Zeng, Ken Museth, Sanja Fidler, and Francis Williams. XCube: Large-scale 3D generative modeling using sparse voxel hierarchies. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[39] Gernot Riegler and Vladlen Koltun. Free view synthesis. In *European Conference on Computer Vision (ECCV)*, 2020. 2

[40] Stone Tao, Fanbo Xiang, Arth Shukla, Yuzhe Qin, Xander Hinrichsen, Xiaodi Yuan, Chen Bao, Xinsong Lin, Yulin Liu, Tse-kai Chan, Yuan Gao, Xuanlin Li, Tongzhou Mu, Nan Xiao, Arnav Gurha, Viswesh Nagaswamy Rajesh, Yong Woo Choi, Yen-Ru Chen, Zhiao Huang, Roberto Calandra, Rui Chen, Shan Luo, and Hao Su. ManiSkill3: Gpu parallelized robotics simulation and rendering for generalizable embodied ai. *arXiv preprint arXiv:2410.00425*, 2025. 5

[41] Gerhard Tech, Ying Chen, Karsten Müller, Jens-Rainer Ohm, Anthony Vetro, and Ye-Kui Wang. Overview of the multiview and 3D extensions of high efficiency video coding. *IEEE Transactions on Circuits and Systems for Video Technology*, 26(1):35–49, 2016. 1, 2

[42] Jianyuan Wang, Minghao Chen, Nikita Karaev, Andrea Vedaldi, Christian Rupprecht, and David Novotny. VGGT: Visual geometry grounded transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2

[43] Qianqian Wang, Zhicheng Wang, Kyle Genova, Pratul P. Srinivasan, Howard Zhou, Jonathan T. Barron, Ricardo Martin-Brualla, Noah Snavely, and Thomas Funkhouser. IBRNet: Learning multi-view image-based rendering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021. 2

[44] Qianqian Wang, Vickie Ye, Hang Gao, Jake Austin, Zhengqi Li, and Angjoo Kanazawa. Shape of motion: 4D reconstruction from a single video. *arXiv preprint arXiv:2407.13764*, 2024. 2

[45] Zhou Wang, Alan C. Bovik, Hamid R. Sheikh, and Eero P. Simoncelli. Image quality assessment: From error visibility to structural similarity. *IEEE Transactions on Image Processing*, 13(4):600–612, 2004. 4

[46] Guanjun Wu, Taoran Yi, Jiemin Fang, Lingxi Xie, Xiaopeng Zhang, Wei Wei, Wenyu Liu, Qi Tian, and Xinggang Wang. 4D Gaussian splatting for real-time dynamic scene rendering. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[47] Jianfeng Xiang, Zelong Lv, Sicheng Xu, Yu Deng, Ruicheng Wang, Bowen Zhang, Dong Chen, Xin Tong, and Jiaolong Yang. Structured 3D latents for scalable and versatile 3D generation. *arXiv preprint arXiv:2412.01506*, 2024. 1, 2

[48] Jianfeng Xiang, Xiaoxue Chen, Sicheng Xu, Ruicheng Wang, Zelong Lv, Yu Deng, Hongyuan Zhu, Yue Dong, Hao Zhao, Nicholas Jing Yuan, and Jiaolong Yang. Native and compact structured latents for 3D generation. *Tech report*, 2025. 1, 2, 4, 13

[49] Haofei Xu, Songyou Peng, Fangjinhua Wang, Hermann Blum, Daniel Barath, Andreas Geiger, and Marc Pollefeys. DepthSplat: Connecting Gaussian splatting and depth. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. 2

[50] Zhen Xu, Zhengqin Li, Zhao Dong, Xiaowei Zhou, Richard Newcombe, and Zhaoyang Lv. 4DGT: Learning a 4D Gaussian transformer using real-world monocular videos. *arXiv preprint arXiv:2506.08015*, 2025. 2, 5

[51] Jiawei Yang, Jiahui Huang, Yuxiao Chen, Yan Wang, Boyi Li, Yurong You, Apoorva Sharma, Maximilian Igl, Peter Karkus, Danfei Xu, Boris Ivanovic, Yue Wang, and Marco Pavone. STORM: Spatio-temporal reconstruction model for large-scale outdoor scenes. In *International Conference on Learning Representations (ICLR)*, 2025. 2

[52] Ziyi Yang, Xinyu Gao, Wen Zhou, Shaohui Jiao, Yuqing Zhang, and Xiaogang Jin. Deformable 3D Gaussians for high-fidelity monocular dynamic scene reconstruction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. 2

[53] Vickie Ye, Ruilong Li, Justin Kerr, Matias Turkulainen, Brent Yi, Zhuoyang Pan, Otto Seiskari, Jianbo Ye, Jeffrey

Hu, Matthew Tancik, and Angjoo Kanazawa. gsplat: An open-source library for Gaussian splatting. *Journal of Machine Learning Research*, 26(34):1–17, 2025. 3

[54] Lijun Yu, José Lezama, Nitesh B. Gundavarapu, Luca Versari, Kihyuk Sohn, David Minnen, Yong Cheng, Agrim Gupta, Xiuye Gu, Alexander G. Hauptmann, Boqing Gong, Ming-Hsuan Yang, Irfan Essa, David A. Ross, and Lu Jiang. Language model beats diffusion – tokenizer is key to visual generation. In *International Conference on Learning Representations (ICLR)*, 2024. 1, 2

[55] Junyi Zhang, Charles Herrmann, Junhwa Hur, Varun Jampani, Trevor Darrell, Forrester Cole, Deqing Sun, and Ming-Hsuan Yang. MonST3R: A simple approach for estimating geometry in the presence of motion. In *International Conference on Learning Representations (ICLR)*, 2025. 2

[56] Kai Zhang, Sai Bi, Hao Tan, Yuanbo Xiangli, Nanxuan Zhao, Kalyan Sunkavalli, and Zexiang Xu. GS-LRM: Large reconstruction model for 3D Gaussian splatting. In *European Conference on Computer Vision (ECCV)*, 2024. 2

[57] Richard Zhang, Phillip Isola, Alexei A. Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018. 4

[58] Peng Zheng, Dehong Gao, Deng-Ping Fan, Li Liu, Jorma Laaksonen, Wanli Ouyang, and Nicu Sebe. Bilateral reference for high-resolution dichotomous image segmentation. *CAAI Artificial Intelligence Research*, 3, 2024. 2, 12

A. Observation preprocessing and decoding

Depth and points. We run pose-conditioned Depth Anything 3 on overlapping 32-frame chunks of the full video. Consecutive chunks are aligned in scale using the median depth ratio on their overlap. Normals are computed from depth gradients, and sky pixels flagged by the depth model are excluded from the point cloud.

Motion seeds. Let $(\mathbf{x}', \zeta')$ be the projection of $\mathbf{p}_t(\mathbf{x})$ into another frame t'. The point is marked dynamic if, for some $|t - t'| \in \{1, 2, 4, 8, 16\}$,

$$\frac{D_{t'}(\mathbf{x}') - \zeta'}{\max(\zeta', 0.05\,\mathrm{m})} > 0.08. \tag{5}$$

We set $D_{t'} = \infty$ on sky. Connected components smaller than 48 pixels are removed, and the mask is dilated by four pixels.

Object masks. RMBG-2.0 (BiRefNet [58]) provides foreground components. An 8-connected component c is selected if it contains at least $\max(16, 0.02|c|)$ motion-seed pixels and covers at most 35% of the image. Selections propagate forward and backward to components overlapping a selected region by at least 30% of their area. Selected regions are dilated by two pixels.

Spatial layout. The scene cube has side length $s = \mathrm{clip}(3\tilde{d}, 4\,\mathrm{m}, 32\,\mathrm{m})$, where $\tilde{d}$ is median camera-to-point distance. Its centre is the median of the nearest 30% of points. A 512^3 grid gives voxel widths of approximately 0.8–6.3 cm. A concentric 64 m cube at the same grid resolution stores outlying static points with 12.5 cm voxels. Points beyond that cube contribute to a 1024×512 equirectangular map by viewing direction relative to the camera-trajectory centre. Only sampled texels are stored.

Voxel features. Each voxel has nine base features: mean RGB, mean normal and mean within-voxel point offset. For each of eight octants we append the difference between its mean RGB and the voxel mean, plus an occupancy flag.

A.1. Surfel parameterization

Each output voxel $\mathbf{v}$ (integer coordinates, voxel size h, cube origin $\mathbf{o}$) emits four 2D Gaussian surfels [13, 34] with degree-1 spherical-harmonics colour. The head predicts residuals $(\boldsymbol{\delta}, \boldsymbol{\ell}, \hat{\mathbf{q}}, \omega)$ around a base configuration that depends on the source camera centre $\mathbf{c}_t^{\mathrm{src}}$ at the rendered time t:

$$\begin{aligned} \boldsymbol{\mu} &= \mathbf{o} + h\left(\mathbf{v} + \tfrac{1}{2} + \tanh\boldsymbol{\delta}\right), & \alpha &= \sigma(\omega + 2), \\ \mathbf{s} &= \mathrm{cap}\Big(\rho\,\tfrac{\mathrm{softplus}(\boldsymbol{\ell}+b)}{\mathrm{softplus}(b)}\Big), & \rho &= \frac{0.55\,\|\mathbf{c}_t^{\mathrm{src}} - \bar{\mathbf{v}}\|}{f}, \\ \mathbf{q} &= \mathrm{norm}\big(\hat{\mathbf{q}} + \mathbf{1}_w\big) \otimes \mathbf{q}_{\mathrm{face}}\big(\mathbf{c}_t^{\mathrm{src}} - \bar{\mathbf{v}}\big), \end{aligned} \tag{6}$$

where $\bar{\mathbf{v}}$ is the voxel centre and ρ is the world-space footprint of 0.55 pixels at focal length f. We set $b = \log(e - 1)$ and $\mathrm{cap}(s) = s\,s_{\max}/(s + s_{\max})$ with $s_{\max}$ four voxels; $\mathbf{1}_w$ is the identity quaternion, and $\mathbf{q}_{\mathrm{face}}(\mathbf{n})$ turns the surfel normal towards $\mathbf{n}$. With a zero-initialized output layer, each voxel starts as a camera-facing disk of about one pixel.

A.2. Appearance and slot modules

$\mathbf{W}_d$ and the octant-feature input projection are zero-initialized and scaled by a fixed gain $\gamma = 10$, so both residual pathways start at zero. $\mathbf{W}_e$ uses the default initialization. Gradients in the gained layers are scaled by $1/\gamma^2$ before clipping.

The temporal modules use width 256 and eight attention heads. Two learned queries pool the observed tokens of each cell. Three self-attention blocks mix all slots, followed by projection to the stored channel dimension. Three cross-attention blocks decode each (u, t) query. Latent slots have 32 channels; appearance slots have 4. Both receive the normalized feature-matching losses in Appendix B.

A.3. Stored-texture reprojection

Additional-keyframe ablations store k full frames at $\mathcal{K} = \{\mathrm{round}(31i/(k-1))\}_{i=0}^{k-1}$.

Given target depth $\hat{d}_c$, a pixel is back-projected to $\mathbf{X} = \pi_c^{-1}(\mathbf{x}, \hat{d}_c(\mathbf{x}))$ and projected into stored frame τ as $(\mathbf{y}, \zeta) = \pi_\tau(\mathbf{X})$, where π denotes calibrated camera projection and ζ is the depth of $\mathbf{X}$ in frame τ. We accept the sampled colour $I_\tau(\mathbf{y})$ when

$$|\zeta - \hat{d}_\tau(\mathbf{y})| < 0.03\zeta + 0.02\,\mathrm{m}, \tag{7}$$

where $\hat{d}_\tau$ is rendered from the same decoded state in the source view of frame τ. Otherwise the surfel colour is retained. Static pixels try keyframes in order of source-camera distance to the target camera. From full keyframes, pixels where the dynamic layer alone has opacity above 0.5 take colour only at the keyframe's own timestamp. At other times they use the dynamic texture below.

Dynamic stored texture. Dynamic texture is stored at $t = 4, 8, \ldots, 28$. A dynamic pixel at time t blends the stored frames $\tau^- \le t < \tau^+$ by temporal proximity. Only samples that satisfy Eq. 7 and have target opacity above 0.5 are used; source depth is rendered at each stored timestamp. Frame 0 serves as τ^- for $t < 4$, and only τ^- is available for $t > 28$. Texture is applied before environment-map compositing.

B. Training details

The supervised timestamps are $\{0, t, \tau^-, \tau^+\}$. If two coincide or τ^+ falls outside the window, random timestamps fill the gap. The four target cameras are drawn at random from the nine non-source cameras. The loss is

$$\mathcal{L} = \tfrac{1}{4}\textstyle\sum_q \mathcal{L}_q + 0.5\,\mathcal{L}_{\Delta t} + \mathcal{L}_{\text{lat}} + \mathcal{L}_{\text{lat}}^{\text{app}} + 0.1\,\mathcal{L}_{\text{occ}} + 10^{-6}\,\mathcal{L}_{\text{KL}}, \tag{8}$$

$$\mathcal{L}_q = \mathcal{L}_{\text{rgb}}^{\text{src}} + \tfrac{1}{4}\textstyle\sum_v \mathcal{L}_{\text{rgb}}^{v} + 0.3\left(\mathcal{L}_d^{\text{src}} + \tfrac{1}{4}\textstyle\sum_v \mathcal{L}_d^{v}\right) + 0.05\,\mathcal{L}_n, \tag{9}$$

where v runs over the four supervising target cameras. We use

$$\mathcal{L}_{\text{rgb}} = \|\hat{I} - I\|_1 + 0.2(1 - \text{SSIM}) + \lambda_{\text{LPIPS}}\,\text{LPIPS}_{\text{VGG}}$$

on images composited over the mean-colour background after stored-texture replacement.

$\mathcal{L}_d$ is an L_1 loss on log depth against the per-camera depth estimate, restricted to pixels inside the scene cube and covered by surfels. $\mathcal{L}_n$ is the 2DGS normal-consistency term [13]. $\mathcal{L}_{\Delta t} = \text{mean}_{a<b}\|(\hat{I}_a - \hat{I}_b) - (I_a - I_b)\|_1$ penalizes temporal differences that do not match the ground truth. $\mathcal{L}_{\text{lat}}$ and $\mathcal{L}_{\text{lat}}^{\text{app}}$ are the relative squared errors between slot-decoded and per-frame latents and appearance codes. For the appearance code, the loss uses a random subset of 65,536 rows. $\mathcal{L}_{\text{occ}}$ and $\mathcal{L}_{\text{KL}}$ are the occupancy and KL terms of TRELLIS.2 [17, 48].

Final model. The final model combines object-level motion masks, 4-channel appearance codes with slot-compressed dynamic codes, and training with stored texture.

Optimization. We use AdamW [28] ($\beta = (0.9, 0.95)$, no weight decay), a learning rate of 3×10^{-5} with 200 warm-up steps and cosine decay to 10^{-5}, a $10\times$ learning rate for the slot modules, $\lambda_{\text{LPIPS}} = 0.6$, and global gradient-norm clipping at 1.0. The model has 836M trainable parameters, almost all in the TRELLIS.2 backbone.

B.1. Ablation configurations

The appearance-code configuration adds a 16-channel 128^3 code and sub-voxel colour input. The larger-code configuration increases this to 32 channels and adds a 16-channel 256^3 code. The motion-mask configuration additionally uses object-level dynamic masks. The combined configuration keeps the 16-channel 128^3 code. It adds object-level masks, slot-compressed dynamic appearance, random windows across the 81-frame clips, and $\lambda_{\text{LPIPS}} = 0.6$. The final model further reduces the appearance code to four channels and is trained with stored texture.

Table 8. **Number of temporal slots** K on MultiCamVideo (404 test clips, full image). All variants start from the same checkpoint and are trained for 12k steps without appearance codes; only K differs. Dynamic-slot size is the mean number of 32-bit values per clip. ΔPSNR is the per-clip paired difference to K=2 (mean ± 95% CI).

K	Dyn. slot #Floats	PSNR↑	SSIM↑	LPIPS↓	ΔPSNR
2	**21.1K**	16.76	*0.492*	*0.475*	–
3	*31.7K*	*16.78*	**0.493**	*0.475*	+0.02 ± 0.01
10	105.6K	**16.80**	**0.493**	**0.474**	+0.04 ± 0.01

Table 9. **Learned-architecture ablation** (404 random-window clips). Each row is trained for 10k steps from a shared 20k-step geometry-only checkpoint (30k steps in total). ΔPSNR gives paired per-clip differences to the corresponding parent configuration (mean ± 95% CI). All rows omit stored texture.

Configuration	#Floats	PSNR↑	SSIM↑	LPIPS↓	ΔPSNR
Geometry only	76.2K	16.76	0.492	0.475	–
+ appearance code	0.87M	16.94	0.500	0.448	+0.18 ± 0.04
+ larger code	3.52M	**16.99**	**0.502**	*0.442*	+0.06 ± 0.01
+ motion mask	3.58M	*16.96*	**0.502**	0.444	−0.04 ± 0.01
Combined config.	0.42M	16.95	*0.501*	**0.430**	+0.01 ± 0.03

Table 10. **State size of Sparc4D** in thousands of 32-bit-equivalent values per 32-frame clip (random-window protocol; first-32 values in parentheses). Occupancy uses empirical entropy divided by 32. The first full frame adds $256^2 \times 3$ values; dynamic texture cost depends on the retained pixel area.

Component	Mean	Median
Static + coarse latent	14.7	12.1
Dynamic temporal slots	22.7	16.3
Static appearance code	27.1	22.8
Dynamic appearance slots	56.7	38.5
Occupancy, static + coarse	6.3	5.1
Dynamic occupancy (32f)	27.8	19.9
Environment map	10.4	0.0
State without stored texture	165.7 (158.8)	129.7 (130.7)
Subtotal with first-frame texture	362.3 (355.4)	326.3 (327.3)
Dyn. source pixels, every 4th fr.	308.8 (302.0)	256.0 (238.1)
Sparc4D (complete state)	671.2 (657.4)	588.0 (568.9)

C. Representation-size accounting

Occupancy is represented as a 32^3 bitmap followed by 8-bit child masks at four finer octree levels. Its cost is the zeroth-order empirical entropy of these symbols. Each environment texel counts as four values. Dynamic-texture masks are not stored, because the decoder recomputes them from the dynamic geometry. Scene-layout metadata such as cube

origin and scale are omitted.

Temporal-compression ablation. For Table 7, the per-frame variant bypasses the slots at inference and stores dynamic latent and appearance features at every timestamp, at a cost of

$$N_{\mathrm{pf}} = 32 \sum_{t=1}^{T} |\mathcal{U}_t| + 4 \sum_{t=1}^{T} |\mathcal{U}_t^{128}|, \tag{10}$$

where $\mathcal{U}_t$ and $\mathcal{U}_t^{128}$ are the occupied dynamic cells at time t on the 32^3 latent and 128^3 appearance grids, respectively. With temporal slots, the corresponding cost is

$$N_{\mathrm{slot}} = 64|\mathcal{U}| + 8|\mathcal{U}^{128}|, \tag{11}$$

where $\mathcal{U}$ and $\mathcal{U}^{128}$ are the temporal unions of occupied dynamic cells.

Table 11. **Temporal feature storage** over the 404 random-window test clips. Sizes are mean 32-bit-equivalent values per clip. Compression factors are computed per clip and reported as their median and mean. Total state includes stored texture.

Component	Per-frame	Slots	Median	Mean
Dynamic latent	182.1K	22.7K	8.8×	8.7×
Dynamic appearance	172.5K	56.7K	3.5×	3.8×
Time-varying features	354.5K	79.4K	5.0×	5.2×
Total state	0.96M	0.67M	1.4×	1.4×

For the combined time-varying feature state, the 10th–90th percentile range of the per-clip compression ratio is 3.3×–7.4×.

For MoVieS, the materialized output contains 1,605,632 Gaussians at 32×224^2 input pixels. The reduced-output study in Table 2 counts its native prediction tensors: 14 static parameters and 4×32 query-time motion parameters per Gaussian, or 142 values. For the cross-method tables, we follow the VideoTok4D reporting convention [5]. It materializes the time-conditioned representation at every evaluated timestamp, which gives 719M FP32 values for a 32-frame sequence. For 4DGT we count the predicted Gaussian parameters. For C4G we count the outputs of 2,048 Gaussians at each of the 32 queried timestamps.

Two size conventions. Table 12 adds the stored size, which counts what must be kept to render any observed timestamp. Sparc4D is smallest under this convention. Its dense decoded output, about 0.39M surfels per timestamp, exceeds that of C4G when materialized.

Table 12. **Representation size under two conventions**, in values per 32-frame clip. Materialized sizes use a common 14 values per primitive (position, scale, rotation, opacity and one RGB colour) at each of the 32 timestamps. With its degree-1 spherical-harmonics colour, Sparc4D would count 22 values per surfel (277M). For Sparc4D, materialized sizes are averaged over the 24 clips of Table 13. †Upper bound without lifetime culling. ‡Estimated from the architecture: 12 context frames × 256 tokens × 2,048 channels.

Method	Stored	Materialized
MoVieS	228M	719M
4DGT	26.9M	301M†
C4G	6.3M‡	**0.92M**
Sparc4D	**0.67M**	176M

D. Runtime and memory

Table 13 reports runtime on one A800 GPU with batch size 1, as the median over 24 test clips. Each clip has 32 input frames and is rendered at 32 timestamps from 10 cameras, giving 320 images at 256^2. MoVieS and 4DGT decode inside their renderers, and C4G decodes all timestamps during encoding.

Table 13. **Runtime and memory per clip.** For Sparc4D, rendering includes stored-texture reprojection.

Method	Encode	Decode	Render	Per image	Memory	Params
MoVieS (bf16)	2.13 s	–	2.42 s	7.6 ms	15.7 GB	1041M
4DGT	1.10 s	–	7.55 s	23.6 ms	9.8 GB	1223M
C4G	2.29 s	–	0.09 s	0.3 ms	5.3 GB	1014M
Sparc4D (fp32)	0.40 s	1.70 s	1.84 s	5.8 ms	4.8 GB	836M

E. Evaluation details

E.1. Split and camera separation

We compute a DINOv2 environment feature for each scene and cluster the 3,400 scenes with k-means ($k = 120$). Test scenes are drawn from clusters assigned to the test side, and each has cosine similarity below 0.62 to every scene in the remaining clusters. This gives 101 test scenes, each rendered at four focal lengths (404 clips).

The remaining 3,299 scenes (13,196 clips) form the training set.

The four focal lengths are 18, 24, 35 and 50 mm. The ten cameras coincide at frame 0 and separate over time. Measured over 404 test clips, mean pairwise separation is 0.93 m at frame 31 and 2.10 m at frame 80. In first-32, 70% of target images are within 0.5 m of the source camera; in random windows, 35% are. The two protocols therefore cover different view-separation regimes.

E.2. Visibility masks and image metrics

MultiCamVideo provides no co-visibility masks. We construct a shared mask from estimated depth and foreground segmentation, independently of each reconstruction method. A target pixel is back-projected using its estimated depth. Depth scale is aligned to the source using a median depth ratio before projecting the point into source frames.

A background pixel is accepted if at least one source frame sees a background surface at the projected position with depth agreement within 10%. An RMBG foreground pixel is accepted only through the source frame at the same time. This restriction avoids treating a moving point as static across frames. Sky and points beyond 40 m are checked by direction. The resulting masks cover on average 83% of target pixels for first-32 and 64% for random windows.

For mask M and RGB intensities in $[0, 1]$, we use

$$\mathrm{mPSNR} = -10 \log_{10} \frac{\sum_{\mathbf{x}} M(\mathbf{x}) \|\hat{I}(\mathbf{x}) - I(\mathbf{x})\|^2}{3 \sum_{\mathbf{x}} M(\mathbf{x})}. \quad (12)$$

mSSIM and mLPIPS average their spatial metric maps inside the mask. Images with less than 1% observed pixels are omitted from masked averages, about 2% of random-window images. Masked and uniform-fill scores use stored 8-bit renderings.

For region analysis, current-frame dynamic input voxels are rendered as camera-facing disks into each target camera. We threshold opacity at 0.5 and dilate by two pixels. The static region lies inside the scene cube. Dynamic-region LPIPS uses the region's bounding box, padded by eight pixels and resized to 128^2.

E.3. Baseline configurations

MoVieS receives all 32 frames at 224^2, together with ground-truth cameras and timestamps. 4DGT receives all 32 frames at 560^2 and ground-truth cameras. Its timestamps use frame index divided by five rather than the dataset's physical rate of 15 fps. We select this setting by source-view reconstruction quality.

C4G is pose-free and receives 12 frames spread uniformly over the window at 224^2, matching its training context count. We align its arbitrary reconstruction scale to the estimated depth of its first context frame using a median ratio. Target cameras are expressed relative to that frame. The fine-tuned model also keeps C4G's architecture and 12-frame input.

E.4. DyCheck preprocessing

We use the *apple*, *block*, *paper-windmill*, *space-out*, *spin*, *teddy* and *wheel* sequences. The handheld video supplies 32 input frames from every second timestamp of a non-overlapping 64-timestamp window. At 30 fps this gives the 15 fps input sampling used in training. Targets are fixed-camera images present in the official validation split at those input times. Windows with no target image are dropped.

We centre-crop the half-resolution 360×480 images to 360^2 and resize to 256^2. Images are resampled to the intrinsics of the first handheld frame in each window. Official co-visibility masks use nearest-neighbour resampling. Source depth and foreground masks are prepared as for MultiCamVideo. The baselines use Appendix E.3' settings; all receive known cameras except pose-free C4G.

Table 14. **mPSNR per DyCheck sequence.** The texture-free variant is an ablation of Sparc4D.

Sequence	MoVieS	w/o stored texture	Sparc4D
apple	*15.54*	**15.62**	15.38
block	14.84	**15.37**	*15.06*
paper-windmill	**15.79**	*14.73*	14.44
space-out	*14.16*	**14.36**	14.07
spin	**13.49**	*13.48*	13.11
teddy	11.38	**12.76**	*12.23*
wheel	**12.94**	*11.72*	11.46

E.5. Neu3D preprocessing

We evaluate six Neu3D [20] scenes using 24 non-overlapping 32-frame windows. For each window, a fixed central camera supplies the monocular input. At the same timestamps, the targets are cam00 and eight cameras sampled at approximately uniform index intervals, for nine target cameras in total. We report full-image PSNR, SSIM and LPIPS over all nine targets, and PSNR separately for cam00. Cam00 is the conventional Neu3D test camera and is approximately 10 cm from the input camera. All methods use the settings in Appendix E.3.

E.6. Qualitative selection

For each protocol, clips are ranked by how close their paired PSNR difference between Sparc4D and MoVieS lies to the median difference. We use the target view at timestamp 16 from the camera at median distance from the source. The figures show the two highest-ranked clips from distinct scenes in which this view has at least 60% observed pixels and at least 1,024 observed foreground pixels. The dynamic crop is centred on the largest observed foreground component. The static crop is the most textured observed background window. Both crops are computed from the ground truth and the visibility mask, and all methods share them.

F. Depth consistency

MultiCamVideo does not provide ground-truth depth. We compare rendered target-view depth with per-camera DA3

estimates using AbsRel, RMSE and δ_1, the fraction of pixels whose depth ratio is within 1.25 [9]. We also report median-scaled AbsRel and δ_1. Each method is evaluated where it renders a surface and the reference is valid; coverage is reported alongside the errors.

Table 15. **Rendered depth vs. the per-camera depth estimate** at target views (test set, per-image average). "aligned": per-image median scaling. C4G-FT: C4G fine-tuned on MultiCamVideo.

					aligned		
	Method	AbsRel↓	δ_1 ↑	RMSE↓	AbsRel↓	δ_1 ↑	cov.
First-32	4DGT	0.624	0.141	8.56	0.344	0.621	*0.92*
	C4G	0.505	0.538	6.34	0.476	0.586	0.91
	C4G-FT	*0.267*	*0.592*	*5.16*	0.291	0.598	**0.98**
	MoVieS	0.561	0.513	6.21	*0.250*	*0.717*	*0.92*
	Sparc4D	**0.157**	**0.848**	**2.66**	**0.115**	**0.885**	0.89
Random	4DGT	0.640	0.155	8.40	0.370	0.598	0.81
	C4G	0.543	0.522	6.12	0.450	0.596	*0.84*
	C4G-FT	*0.356*	*0.524*	*5.43*	0.346	0.545	**0.97**
	MoVieS	0.615	0.505	5.84	*0.272*	*0.704*	0.75
	Sparc4D	**0.259**	**0.784**	**2.92**	**0.170**	**0.831**	0.75

Rendered depth from Sparc4D is more consistent with the DA3 reference than the evaluated baselines. Because DA3 also supplies our input depth and depth supervision, this comparison measures agreement with DA3.

G. Additional reconstruction diagnostics

Table 16. **Static and dynamic regions**, first-32 protocol. Regions are defined in Appendix E.2.

	Dynamic		Static
Method	PSNR↑	LPIPS↓	PSNR↑
4DGT	16.19	0.345	18.56
C4G	14.32	0.434	15.97
MoVieS	*19.02*	**0.150**	21.79
w/o stored texture	17.53	0.276	21.43
w/o dynamic texture	18.36	0.201	*25.41*
4 full frames, no dyn. texture	18.47	0.193	**25.53**
Sparc4D	**19.32**	*0.153*	*25.41*

H. Downstream manipulation protocol

Setup. The autoencoder receives 4,000 adaptation steps on ManiSkill scenes before policy training. Four 256^2 RGB-D views, sampled on a ring around the workspace, are fused into a fixed 2.4 m cube. Static features pool the first three frames of each observation window. Simulator depth and robot-link silhouettes are used; SAM 2 tracks objects causally from boxes obtained by clustering non-robot points above the table, without object-pose or object-segmentation labels. The policy also observes the end-effector pose and gripper state. It is trained for 60,000 steps with batch size 64. It predicts eight-step action chunks with ten Euler steps and replans after each chunk. The additional 2,000 demonstrations randomize motion-planning waypoints and initial joint-motion prefixes.

Table 17. **Rendering ladder** on random windows (8 timestamps per clip). Only the Sparc4D row uses stored texture. Rows 1–3 directly render input pixels or voxels as mean-colour disks. "dyn." denotes the dynamic region and "stat." the static region inside the scene cube.

	Source, dyn.		Target, dyn.		Target, stat.
Rendering	PSNR↑	LPIPS↓	PSNR↑	LPIPS↓	PSNR↑
Current-frame pixels	27.27	0.048	14.90	0.338	14.75
Input voxels, 512^3	18.12	0.272	14.67	0.419	15.39
Input voxels, dyn. 1024^3	20.15	0.212	14.81	0.387	15.39
Learned state, per-frame dyn.	20.75	0.209	15.88	0.344	18.37
Learned state, temporal slots	20.23	0.218	15.88	0.347	18.37
Sparc4D (with stored texture)	–	–	16.36	0.264	19.21
MoVieS	21.93	0.089	16.76	0.257	18.36

Table 18. **PSNR by frame index within the window** (random windows, mean over 9 target cameras, computed from 8-bit renders).

t	0	4	8	16	24	31
w/o stored texture	17.71	17.44	17.18	16.72	16.38	16.11
w/o dynamic texture	**19.67**	18.18	17.76	17.10	16.66	16.33
Sparc4D	**19.67**	*18.49*	*17.92*	*17.17*	16.68	16.30
All 32 full frames	*19.60*	**18.50**	**17.94**	**17.20**	*16.71*	*16.36*
MoVieS	18.18	17.93	17.67	*17.17*	**16.81**	**16.50**

Evaluation. Success is measured within 200 control steps over 100 initial states and three sampling seeds per trained policy. Li et al. [24] report results with fixed 512^2 cameras and joint-position control; ours use randomized cameras and end-effector increments.

Scene size. Our counts average 306 held-out windows: 425.9 static and 235.5 dynamic cells per timestamp, or 661.4 in total. The three-frame policy context contains 1,132.5 cells. The same encoder and reference windows are used for both data budgets. The approximately 5,700 cells for Li et al. come from three initial states with their fixed cameras. These counts include scene-latent cells only.