
Determining the Version of TextEdit

You can determine the version of **TextEdit** using the **Gestalt** selector gestaltTextEditVersion. When you call **Gestalt** with this selector, the result returned in the response parameter identifies the current version of **TextEdit**. If the **Gestalt** function returns the gestaltUndefSelectorErr result code, an earlier version of **TextEdit** without **Script Manager** compatibility is installed.

<u>gestaltTE1</u>	U.S. system software version 6.0.4 containing TextEdit on a Macintosh IIci
<u>gestaltTE2</u>	version 6.0.4 non-Roman script system containing a Script Manager -compatible version of TextEdit including the new measuring hook <u>nWIDTHHook</u> for the Macintosh IIci
<u>gestaltTE3</u>	version 6.0.4 non-Roman script system containing a Script Manager -compatible version of TextEdit including the new measuring hook <u>nWIDTHHook</u> for Macintosh Plus, Macintosh SE, Macintosh SE/30, Macintosh II, Macintosh Portable, Macintosh IIfx, or Macintosh IIfx}
<u>gestaltTE4</u>	system software versions 6.0.5 and later, which contain a Script Manager -compatible version of TextEdit including the new measuring hook <u>nWIDTHHook</u> & the outline-highlighting & text-buffering features, on any Macintosh
<u>gestaltTE5</u>	system software version 7.0, which contains a Script Manager -compatible version of TextEdit including two new measuring hooks, <u>nWIDTHHook</u> & <u>TextWidthHook</u> , outline highlighting, text buffering, new features for inline input, & } capability to disable inline input

TextEdit is **Script Manager**-compatible if the returned value is gestaltTE2 or greater. **TextEdit** contains the new measuring hook nWIDTHHook if the returned value is gestaltTE2 or greater.

The outline-highlighting and text-buffering features of **TextEdit**, included with the function **TEFeatureFlag**, are available if the returned value is gestaltTE4 or greater. Outline highlighting, text buffering, new features for inline input, and the capability to disable inline input, included with the function **TEFeatureFlag**, are available if the returned value is gestaltTE5 or greater.

The new measuring hook TextWidthHook is available if the returned value is gestaltTE5 or greater.

For more on the **TEFeatureFlag** function, see **TEFeatureFlag**. For more on **TextEdit**'s width measuring hooks, see TextEdit Width Hooks.