



# Polynomials and Regularisation

Jan 7th 2020

# Today's Lesson

## Learning Objectives

- Describe the phases of the CRISP-DM data science process
- Use the CRISP-DM framework to analyze and plan out data science projects

## Activities

- Reflecting on Your Data Science Experience
- Data Science Process Overview
- Revisiting Your Data Science Experience
- Reviewing Your Projects
- Exit Ticket



# Linear Regression Recap

**Task:** Take turns with a neighbor, answering the questions below:

- What is Linear Regression?
- How does it work?
- How do we know if the results are good or bad?
- What requirements should your data meet?

5 minutes

We will then come back to the large group and I'll pick some of you to share your answers with the rest of the class.




# Polynomial Regression

- Problems Linear Regression can't solve on its own
- Polynomial transformation of predictors
- Interactions
- Feature explosion



# Polynomial Regression

- Some problems just can't be solved with a straight line
- We need models as complex as our problems in order to generate good predictions
- Example: If  $y = x^2$  we need to have  $x^2$  as a feature
- PolynomialFeatures generates



# Feature Interactions

- PolynomialFeatures generates the n-way interactions for all your predictions
- Example: If you want the interaction of 3 variables together (AxBxC) you will need a degree 3 polynomial transformation  $(A+B+C)^3$

Classifying Polynomials by Degree		
Name	Degree	Example
Constant	0	$-9$
Linear	1	$x - 4$
Quadratic	2	$x^2 + 3x - 1$
Cubic	3	$x^3 + 2x^2 + x + 1$
Quartic	4	$2x^4 + x^3 + 3x^2 + 4x - 1$
Quintic	5	$7x^5 + x^4 - x^3 + 3x^2 + 2x - 1$

SQUARE OF SUM

$$(a + b)^2 = a^2 + 2ab + b^2$$

CUBE OF SUM

$$(a + b)^3 = a^3 + 3a^2b + 3ab^2 + b^3$$

# Feature Explosion

- This can get out of hand very quickly
- Example: Just 10 Features with a 3rd degree polynomial would lead to 1000 features
- When the number of features is too high:
  - Coefficients become unstable
  - Chance of multicollinearity increases massively
  - Chance of overfitting explodes
  - Dimensionality becomes a course



# Polynomial Regression Recap

**Task:** Take turns with a neighbor, answering the questions below:

- When is polynomial regression useful?
- When could it be dangerous?
- How do you think you could contain the risks?

5 minutes

We will then come back to the large group and I'll pick some of you to share your answers with the rest of the class.





# Regularisation


- MSE
- Complexity penalty
- Scaling
- Ridge Regression
- LASSO Regression
- Elastic net
- Bias / Variance tradeoff



# Mean Squared Error (MSE)

$$\frac{1}{n} \sum_{i=1}^n (Y_i - \hat{Y}_i)^2$$

- \*  $n$  is the number of data points
- \*  $Y_i$  represents observed values
- \*  $\hat{Y}_i$  represents predicted values



# Complexity Penalty

- Regularisation in Regression means not only trying to minimise MSE but also the size of the coefficients

$$\sum_{i=1}^M (y_i - \hat{y}_i)^2 = \sum_{i=1}^M \left( y_i - \sum_{j=0}^p w_j \times x_{ij} \right)^2 + \lambda \sum_{j=0}^p w_j^2$$

Cost function for ridge regression

- Because the size of the coefficients matter **feature scaling** is required.
- Although you will be scaling all datasets, you will use the **patterns from your training** dataset only
-

# Ridge Regression - L2 Reg

- Penalty based on the squared coefficients.
- This will lead to reducing largest coefficients first

$$\sum_{i=1}^M (y_i - \hat{y}_i)^2 = \sum_{i=1}^M \left( y_i - \sum_{j=0}^p w_j \times x_{ij} \right)^2 + \lambda \sum_{j=0}^p w_j^2$$

Cost function for ridge regression

- It will bring irrelevant features' coefficients close to zero but not exactly zero

# LASSO Regression - L1 Reg

- Penalty based on the absolute value of the coefficients.
- This will lead to reducing most irrelevant coefficients first

$$\sum_{i=1}^M (y_i - \hat{y}_i)^2 = \sum_{i=1}^M \left( y_i - \sum_{j=0}^p w_j \times x_{ij} \right)^2 + \lambda \sum_{j=0}^p |w_j|$$

Cost function for Lasso regression

- It will bring irrelevant features' coefficients exactly to zero. Hence, we can use LASSO as feature selection tool.
- Because of all of the above we call this type of regression LASSO: Least Absolute Shrinkage and Selection Operator

## Elastic net - L2 and L1 Reg

- Combines L2 and L1 penalties in a proportion that you can regulate with a hyperparameter in sklearn

$$(\|y - X\beta\|^2 + \lambda_2 \|\beta\|^2 + \lambda_1 \|\beta\|_1).$$

- Will bring some coefficients to zero but could also just reduce them if that leads to a better model

# Information Criteria

- Measure information loss
- Balances the goodness of fit and the complexity of a model
- Akaike Information Criterion  $AIC = 2k - 2 \ln(\hat{L})$
- Bayesian Information Criterion  $BIC = \ln(n)k - 2 \ln(\hat{L})$ .
- Lower is better

# Solving fitting issues

- **Polynomial transformations** will improve performance on the training dataset
- Convenient when previously underfitting
- **Regularisation** will decrease performance in the training dataset
- Convenient when previously overfitting (as it would likely improve performance on the test dataset)

	Underfitting	Just right	Overfitting
Symptoms	<ul style="list-style-type: none"><li>• High training error</li><li>• Training error close to test error</li><li>• High bias</li></ul>	<ul style="list-style-type: none"><li>• Training error slightly lower than test error</li></ul>	<ul style="list-style-type: none"><li>• Very low training error</li><li>• Training error much lower than test error</li><li>• High variance</li></ul>
Regression illustration			
Classification illustration			
Deep learning illustration			
Possible remedies	<ul style="list-style-type: none"><li>• Complexify model</li><li>• Add more features</li><li>• Train longer</li></ul>		<ul style="list-style-type: none"><li>• Perform regularization</li><li>• Get more data</li></ul>



# Regularisation Recap

**Task:** Take turns with a neighbor, answering the questions below:

- When is regularisation useful?
- What assumptions need to be met by your data before you apply it?
- What negative consequences could it have if done wrong?
- How would you choose between different types of regularisation?

5 minutes

We will then come back to the large group and I'll pick some of you to share your answers with the rest of the class.



## Delivering Value

Your job is not to create high performance models

They pay you to **solve problems**

# Summary + Exit Ticket

Presented by Dan Sanz

 FLATIRON SCHOOL