



## List 13158

HY-PRO® SYNCHRO AL US-AL-SFT



| EDP Number |   | Thread Size | Class of Fit | Overall Length | Thread Length | Neck Length | Shank Diameter | Square Width | Square Length |
|------------|---|-------------|--------------|----------------|---------------|-------------|----------------|--------------|---------------|
|            |   |             |              | L (mm)         | Lc (mm)       | L1 (mm)     | d (mm)         | k (mm)       | lk (mm)       |
| 1315800108 | ● | M3 x 0.5    | 6H           | 49.20          | 4.10          | 16.00       | 3.58           | 2.79         | 4.76          |
| 1315800208 | ● | M4 x 0.7    | 6H           | 54.00          | 5.60          | 19.10       | 4.27           | 3.33         | 6.35          |
| 1315800308 | ● | M5 x 0.8    | 6H           | 60.30          | 6.40          | 22.20       | 4.93           | 3.86         | 6.35          |
| 1315800408 | ● | M6 x 1      | 6H           | 63.50          | 8.00          | 25.40       | 6.48           | 4.85         | 7.94          |
| 1315800508 | ● | M8 x 1.25   | 6H           | 69.10          | 10.00         | 28.60       | 8.08           | 6.05         | 9.53          |
| 1315800608 | ● | M10 x 1.25  | 6H           | 74.60          | 12.00         | 31.80       | 9.68           | 7.26         | 11.11         |
| 1315800708 | ● | M10 x 1.5   | 6H           | 74.60          | 12.00         | 31.80       | 9.68           | 7.26         | 11.11         |
| 1315800808 | ● | M12 x 1.5   | 6H           | 85.70          | 14.00         | 49.10       | 9.32           | 6.99         | 11.11         |
| 1315800908 | ● | M12 x 1.75  | 6H           | 85.70          | 14.00         | 49.10       | 9.32           | 6.99         | 11.11         |

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

| P            |        |      |             |           | M               |     |         | K            | N           |         | S            | H        |                |              |              |              |         |
|--------------|--------|------|-------------|-----------|-----------------|-----|---------|--------------|-------------|---------|--------------|----------|----------------|--------------|--------------|--------------|---------|
| Steel        |        |      |             |           | Stainless Steel |     |         | Cast Iron    | Non-Ferrous |         | HRSA         |          | Hardened Steel |              |              |              |         |
| Carbon Steel |        |      | Alloy Steel | Die Steel |                 |     |         |              | Aluminum    |         | Nickel Alloy | Titanium |                |              |              |              |         |
| Low          | Medium | High |             |           |                 |     |         |              | 6061        | Casting |              |          |                |              |              |              | Inconel |
| 1010         | 1035   | 1065 | 4140        | Die Steel | 300             | 400 | 17-4 PH | 6061<br>7075 |             |         |              |          | ~35<br>HRC     | 35-45<br>HRC | 45-50<br>HRC | 50-70<br>HRC |         |
| 1018         | 1045   |      | 4340        |           |                 |     |         |              |             |         |              |          |                |              |              |              |         |
|              |        |      |             |           |                 |     |         |              |             |         |              |          |                |              |              |              |         |
|              |        |      |             |           |                 |     |         |              |             |         |              |          |                |              |              |              |         |

○ Good ⊗ Best

