



lonut Spalatelu



## **Method Overloading**

- Method overloading means providing two or more separate methods in a class with the same name but different parameters
- Method return type may or may not be different
- Both static and instance methods can be overloaded
- Usually overloading happens inside a single class, but a method can also be treated as overloaded in the subclass of that class
- This is because a subclass inherits one version of the method from the parent class and then the subclass can have another overloaded version of the method





- Methods will be considered overloaded if both of the following rules:
  - Methods must have the same method name
  - Methods must have different parameters
- If methods follow the rules above then may or may not:
  - Have different return types
  - Have different access modifiers
  - Throw different checked or unchecked exceptions



## **Method Overriding**

- Method overriding means defining a method in a child class that already exists in the parent class with same signature
- By extending the parent class the child class gets all the methods defined in the parent class (inherited methods)
- Method overriding is also known as Runtime Polymorphism and Dynamic Method Dispatch, because the method that is going to be called is decided at runtime by the JVM





- Methods are overridden if we follow these rules:
  - Signatures must be the same
  - Return type:
    - If is a primitive or void in the parent class then both return types must match exactly
    - If is a class in the parent class then return type can be a subclass of the one in the parent class
  - It can't have a lower access modifier
  - It can't throw a broader checked exception than the method in the parent class
  - If there is an unchecked exception in the parent class there is no restriction
  - Method from the parent class cannot be final






- There are some important points about method overriding to keep in mind
  - Only inherited methods can be overridden, in other words methods can be overridden only in child classes
  - Constructors and private methods cannot be overridden
  - A subclass can use super.methodName() syntax to call the superclass version of an overridden method



## **Method Overriding vs Overloading**



```
OVERLOADING
                            same name
                        different parameters
class Dog {
   public void bark()
       System. out. println ("woof");
   public void bark(int number)
       for(int i = 0; i < number; i++) {</pre>
           System.out.println("woof");
```





Method Overloading	Method Overriding
Provides functionality to reuse a method name with different parameters.	Used to override a behavior which the class has inherited from the parent class.
Usually in a single class but may also be used in a child class.	Always in two classes that have a child-parent or IS-A relationship.
Must have different parameters.	Must have the same parameters and same name.
May have different return types.	Must have the same return type or covariant return type (child class).
May have different access modifiers(private, protected, public).	Must NOT have a lower modifier but may have a higher modifier.
May throw different exceptions.	Must NOT throw a new or broader checked exception.

## **Questions**



