

***BPMN***  
***Business Process Model***  
***and Notation***

# Modeling Language Components

---

- A modeling language consists of three parts:
  - **Syntax**
    - Set of modeling elements and rules to combine them
      - BPMN syntax includes activities, events, gateways, sequence flows
  - **Semantics**
    - Bind syntactical elements with textual descriptions to a precise meaning
      - Behavior of BPMN elements
  - **Notation**
    - Defines graphical symbols for elements

# Business Process Model and Notation (BPMN)

---

- Object Management Group (OMG) standard
  - <http://www.omg.org>
  - <http://www.omg.org/specs/bpmn>
  - version 1.0 (2006)
  - version 1.1 (2007)
  - version 1.2 (2009)
  - version 2.0 (2011)
- Provide a notation to describe Business Process understandable by:
  - BP analysts
  - IT developers
  - BP workers and managers

# Why BPMN

---


- Business people are very comfortable with visualizing Business Processes in a flow-chart format
- BPMN *execution semantics* is fully formalized
- BPMN 2.0 has a *formal definition* (metamodel)
  - Precise definition of the constructs and rules for creating models

# BPMN Metamodel

---

- Metamodeling has the following benefits
  - Formalization of models and entities
  - Formalization of relationship between elements
  - Interoperability
- It is not necessary for the modeler to handle the metamodel
- Is the modeling tool that ensures the model is compliant with metamodel

# BPMN Metamodel (partial)




# BPMN Semantic

---

- To describe how the BPMN elements behave, the theoretical concept of **token** is used
  - The “**simulated**” behavior of elements can be defined by describing how they interact with a token
  - The token is not part of the BPMN specification
  - BPMN modeling tools are not required to implement any form of token
- The token will traverse the sequence flows and pass through the elements in the process
  - Token traverse sequence flows instantaneously, so there is no time associated with them
  - When arrives at an element, the token may continue instantaneously or can be delayed depending on the element
- We use this notation for tokens





# Sequence Flow

---

- Sequence flow connects model elements showing their ***order of execution***
- Each sequence flow has only one source and only one target
  - Model elements can have one or more incoming sequence flow and one or more outgoing sequence flow but usually they have one
- Source and target can be activities, events, gateways





Start Event

# Start Event

---

- Beginning of the process
  - It has no incoming flows
- A process may have zero, one or more start events
  - If not present, all activities without incoming flows start together
  - If an end event is present, at least one start event is mandatory



End Event

# End Event

---

- Where the flow of the process ends
  - It has no outgoing flows
- A process may have zero, one or more end events
  - If not present, all activities that do not have any outgoing flows mark the end of a process path
    - In this case, the Process ends when all parallel paths have completed
- If a start event is present, at least one end event is mandatory

A rectangular button with rounded corners, a light gray gradient, and a thin black border. The word "Task" is centered on the button in a black, sans-serif font.

Task

# Task


---

- Unit of work (atomic activity), the job to be performed
- A task is used when the work in the process cannot be broken down to a finer level of detail

# Our First BPMN Model

---

- A simple BPMN model generally has
  1. A start point
  2. An end point
  3. Some activities
  4. Connections between activities



# Gateway

---

- Used to control how sequence flows interact as they converge and diverge within a process
- ***Split gateway***
  - Point where the process flow diverges
  - Has one incoming sequence flow and multiple outgoing sequence flows
- ***Merging gateway***
  - Point where the process flow converges
  - Has multiple incoming sequence flows and one outgoing sequence flow



Exclusive Gateway




Exclusive Gateway

# Exclusive Gateway

- ***Diverging Exclusive Gateway***

- Creates alternative paths within a process flow
- The decision is considered as a question with a defined set of alternative answers
- Only one of the paths can be taken (XOR)
- The default path (if defined) is taken if none of the conditional expressions evaluate to true





Exclusive Gateway




Exclusive Gateway

# Exclusive Gateway

- ***Converging Exclusive Gateway***

- Used to merge alternative paths
- Each incoming token is routed to the outgoing sequence flow without synchronization



# Exclusive Gateway Example

---


- Order shipment
  - *When a purchase order is received, check stock availability. If the item is available, confirm order and ship product, otherwise reject order.*



# Exclusive Gateway Example

---

- Order shipment
  - *When a purchase order is received, check stock availability. If the item is available, confirm order and ship product, otherwise reject order*






# Parallel Gateway

- ***Diverging Parallel Gateway***

- Creates parallel paths without checking any conditions
- Each outgoing sequence flow receives a token






# Parallel Gateway

- ***Converging Parallel Gateway***

- Used to synchronize (combine) parallel flows and to create parallel flows
- Waits for all incoming flows before routing the token to the outgoing flows (AND)



# Parallel Gateway Example


---

- Boarding security check
  - *Having the boarding pass, go to security check for luggage and security screening. When passed both go to boarding*

# Parallel Gateway Example

---

- Boarding security check
  - *Having the boarding pass, go to security check for luggage and security screening. When passed both go to boarding*






Inclusive Gateway

# Inclusive Gateway

- ***Diverging Inclusive Gateway***

- Used to create alternative but also parallel paths within a process flow
- Unlike the exclusive gateway, all condition expressions are evaluated
  - All Sequence Flows with a true evaluation will be traversed by a token (OR)
  - The default path (if defined) is taken if none of the conditional expressions evaluate to true






# Inclusive Gateway

- ***Converging Inclusive Gateway***

- Used to merge a combination of alternative and parallel paths
- Token arriving at an inclusive gateway may be synchronized with some other tokens that arrive later at the gateway
  - When all the expected tokens have arrived the token moves to the outgoing sequence flow



# Inclusive Gateway Example

---


- Order decomposition
  - *When an order is received, get product of type A from warehouse A and products of type B from warehouse B.*



# Inclusive Gateway Example

---

- Order decomposition
  - *When an order is received, get product of type A from warehouse A and products of type B from warehouse B.*





# Resource Modeling

---

- Organizational resource are mapped in pools and lanes
- **Pools**
  - Independent organizational entities (**do not share** any common system that allows them to communicate implicitly)
    - Customer is independent from the Supplier
- **Lanes**
  - Multiple resource classes in the same organization (**share** common systems)
    - Sales department and marketing Department

# Pools and Lanes





# Message Flow

---

- Used to show the flow of messages between two participants
  - Participants are prepared to send and receive the messages
- Message flow only connects two separate pools
  - Message flow can be attached to pools, activities, or message events
  - Message flow cannot connect two objects within the same pool

# Artifacts

---


- Additional information that is not directly related to the sequence flows or message flows
  - Associations, groups, text annotations
- Association is used to associate artifacts with process elements

-----  
Association

# Text Annotation

---

- Provides additional information for the reader of a BPMN diagram
  - Does not affect the flow of the process



# Data Objects

---

- Represent data and document exchanged in the process
- Can be used to show input and output of activities
- BPMN defines 5 kind of data objects

# Data Objects

---

- **Data object**

- Information traversing the process (email, letters, documents)



Data Object

- **Collection data object**

- Collection of information



Collection Data Object

- **Data input**

- External input necessary to start the activity



Data Input

- **Data output**

- Outcome of the activity or the process



Data Output

- **Data store**

- Place where the process can read and write data (database)



Data Store



# BPMN Process Type

---

- *Orchestration*
  - *Collaborations*
  - *Choreographies*
- 
- BPMN uses the terms collaboration and choreography when modeling the interaction between processes

# Orchestration Example

---

- BP ***internal*** to a specific organization
- Generally called workflow or BPM process




Image from “Business Process Model and Notation (BPMN)”, <http://www.omg.org/spec/BPMN/2.0>

# Collaboration

---

- Collaboration shows ***interactions*** between two or more participants
  - A pool represents one of the participants in the collaboration
- Collaboration can be shown as two or more processes communicating with each other
  - The message exchanged between the participants is shown by a message flow

# Collaboration Example





Image from "Business Process Model and Notation (BPMN)", <http://www.omg.org/spec/BPMN/2.0>

# Specialized Task

---

- ***Send/Receive message***

- Task that send/receive a message to/from an external participant (within the process)



- ***User activity***

- Task performed by a human with the assistance of a software application




- ***Manual activity***

- Task performed without the aid of any application




- ***Service calling***

- Task that uses some sort of external service identified with an URI



- ***Script***

- Task performed by a business process engine




# Event Definition

---

- The “Event” is the composition of
  - *Position*
    - Start, Intermediate, End
  - *Nature*
    - Catch, Throw
  - *Impact*
    - Interrupting, Non-Interrupting
  - *Type*
    - Message, Timer, etc.

# Event Symbol



# Event Position

---

- Start event
  - initial point of execution flow



Start Event

- Intermediate event
  - may occur between start and end of the execution flow



Intermediate Event

- End event
  - stop of the execution flow



End Event



# Event Nature

---

- ***Catch event***
























- All start events and some intermediate events
- When the event is triggered, the token is generated

- ***Throw event***

- All end events and some intermediate events are throwing events that may eventually be caught by another event
- Typically, the trigger carries information from the scope where the throw event occurred into the scope of the catching events














# Events Definition

## Events

	Events							
		Start			Intermediate			End
	Standard	Event Sub-Process Interrupting	Event Sub-Process Non-Interrupting	Catching	Boundary Interrupting	Boundary Non-Interrupting	Throwing	Standard
<b>None:</b> Untyped events, indicate start point, state changes or final states.								
<b>Message:</b> Receiving and sending messages.								
<b>Timer:</b> Cyclic timer events, points in time, time spans or timeouts.								
<b>Escalation:</b> Escalating to an higher level of responsibility.								




























# Events Definition

## Events

	Start			Intermediate			End
	Standard	Event Sub-Process Interrupting	Event Sub-Process Non-Interrupting	Catching	Boundary Interrupting	Boundary Non-Interrupting	Throwing
<b>Conditional:</b> Reacting to changed business conditions or integrating business rules.							
<b>Link:</b> Off-page connectors. Two corresponding link events equal a sequence flow.							
<b>Error:</b> Catching or throwing named errors.							
<b>Cancel:</b> Reacting to cancelled transactions or triggering cancellation.							

# Events Definition

## Events

		Start			Intermediate			End
	Standard	Event Sub-Process Interrupting	Event Sub-Process Non-Interrupting	Catching	Boundary Interrupting	Boundary Non-Interrupting	Throwing	Standard
<b>Compensation:</b> Handling or triggering compensation.								
<b>Signal:</b> Signalling across different processes. A signal thrown can be caught multiple times.								
<b>Multiple:</b> Catching one out of a set of events. Throwing all events defined								
<b>Parallel Multiple:</b> Catching all out of a set of parallel events.								
<b>Terminate:</b> Triggering the immediate termination of a process.								




# Event-Based Gateway

---

- Alternative paths are based on events that occur, rather than the evaluation of expressions
  - Usually the receipt of a message determines the path that will be taken
- When the first event is triggered, then the corresponding path is activated
  - All remaining paths will no longer be valid
  - The event gateway is thus a race condition where the first event that is triggered wins
- Event gateways can be used to start the process according to the event occurred

# Event-Based Gateway

---



# Demo - Shipment Process of a Hardware Retailer

---

- When goods are ready to be sent, the warehouse worker starts packaging the goods and a clerk decides if this is a normal postal or a special shipment.
- If a special shipment is required, the clerk selects a carrier and prepares the paperwork.
- Otherwise a normal post shipment is fine and in this case the clerk checks if an extra insurance is necessary.
- If the extra insurance is required, the logistics manager prepares that insurance. In any case, the clerk has to fill in a postal label for the shipment.

# Demo - Shipment Process of a Hardware Retailer

---

- When goods are ready to be sent, the warehouse worker starts packaging the goods and a clerk decides if this is a normal postal or a special shipment.
- If a special shipment is required, the clerk selects a carrier and prepares the shipment.
- Otherwise a normal shipment is fine and in this case the clerk checks if extra insurance is necessary.
- If the extra insurance is required, the logistics manager prepares that insurance. In any case, the clerk has to fill in a postal label for the shipment.



Participants



# Demo - Shipment Process of a Hardware Retailer

---

- When goods are ready to be sent, the warehouse worker starts packaging the goods and a clerk decides if this is a normal postal or a special shipment.
- If a special shipment is required, the clerk selects a carrier and prepares the paperwork.
- Otherwise a normal post shipment is fine and in this case the clerk checks if an extra insurance is necessary.
- If the extra insurance is required, the logistics manager prepares that insurance. In any case, the clerk has to fill in a postal label for the shipment.



Activities

# Demo - Shipment Process of a Hardware Retailer

