

Computer & Network Security – prof. Giuseppe Bianchi – 3rd midterm, February 2, 2023

Name+Surname:_____ Univ. Code:_____

Q1. Determine whether the following statements are true or false or Not-applicable/meaningless (i.e. the sentence is badly formulated or refers to something impossible/wrong).

In ECDSA, for providing IND-CPA (semantic) security, the nonce used must be always fresh	V	F	N/A
In ECIES, for providing IND-CPA (semantic) security, the nonce used must be always fresh	V	F	N/A
In El Gamal, for providing IND-CPA security, the nonce used must be always fresh	V	F	N/A
ECDSA security relies on the hardness of the factorization problem over elliptic curves	V	F	N/A
The order of an elliptic curve group built on $\mathbb{Z}_p$ with p prime is either p or a multiple of p	V	F	N/A
In a (4,4) secret sharing scheme using arithmetic modulo n , n must be a prime number	V	F	N/A
The Shamir secret sharing is unconditionally secure	V	F	N/A
A verifiable secret sharing using the Pedersen Commitment is unconditionally secure	V	F	N/A
The Pedersen Commitment is perfectly hiding	V	F	N/A
Unlike Shamir, a trivial secret sharing scheme cannot be ideal	V	F	N/A

Q2. Part 1: Describe the Boneh-Franklin's Identity Based Encryption scheme

Part 2: Show how the user private key can be computed via a PKG system distributed among two parties so that neither party is able, alone, to know the users' private keys.

Name+Surname:_____ Univ. Code:_____

Q3. Let P be an EC point. What is the minimum number of EC sums/doubles necessary to compute $[193]P$?

Q4 Assume arithmetic modulus 100. A Linear secret sharing scheme involving 4 parties is described by the following access control matrix:

A:	1	1	0	0
B:	0	1	1	0
C:	0	0	1	1
D:	0	0	0	1

Assume that the following shares are revealed: $A \rightarrow 15$, $B \rightarrow 27$, $C \rightarrow 33$, $D \rightarrow 41$

What is the secret?

Q5. Consider the Elliptic curve $EC(\mathbb{Z}_7)$: $y^2 = x^3 + x$ defined over the modular integer field $\mathbb{Z}_7$.

- A.** Verify that (0,0) is a point of the curve, and (*without any computation*) determine $(0,0)+(0,0)$.
- B.** find all the remaining points of the curve.

Computer & Network Security – prof. Giuseppe Bianchi – 3rd midterm, February 2, 2023

Name+Surname:_____

Univ. Code:_____

Q6. A Shamir Secret Sharing scheme uses a non-prime modulus $p=35$ (if you need modular inverses see table on the right). Of the 5 participating parties $P_1, \dots, P_5$, with respective x coordinates $x_i = \{1, 2, 3, 4, 5\}$, parties P_1 , P_2 and P_4 aim at reconstructing the secret.

a) compute the Lagrange Interpolation coefficients for parties 1, 2, 4.

b) Reconstruct the secret, assuming that the shares are:

$P_1 \rightarrow 33$

$P_2 \rightarrow 4$

$P_4 \rightarrow 21$

c) Does the knowledge of the two shares P_1 and P_2 leak information about the secret?

x	$1/x \bmod 35$
1	1
2	18
3	12
4	9
6	6
8	22
9	4
11	16
12	3
13	27
16	11
17	33
18	2
19	24
22	8
23	32
24	19
26	31
27	13
29	29
31	26
32	23
33	17
34	34

Computer & Network Security – prof. Giuseppe Bianchi – 3rd midterm, February 2, 2023

Name+Surname:_____ Univ. Code:_____

Q7 An RSA system has the following parameters: modulo $n=253$, public key $e=3$. Assume we are NOT able neither to factorize n nor gather or compute the corresponding private key d . Despite this, we wish to compute the RSA signature $19^d \bmod n$ for message $m=19$.

1) Show how this is possible if we know that $19^{5d} = 10 \bmod n$, and

2) numerically compute the signature.

[here a few modular inverses with might (might not) be useful: $\{3, 5, 10, 19, 100\}^{-1} \bmod n \rightarrow \{169, 152, 76, 40, 210\}$]