



Data Dictionary

BrokerVerse OOTB database

Prepared by – **iorta TechNXT**

Version – **1.0**

Date – **03 October 2026**

TABLE OF CONTENTS

1. Document Control.....	4
2. Acronyms.....	4
3. About this document.....	5
3.1 Sources.....	5
3.2 The companion workbook.....	6
3.3 Database at a glance.....	6
4. Conventions.....	7
4.1 Naming.....	7
4.2 Identifiers.....	7
4.3 Money, rates and shares.....	8
4.4 Dates and the business time zone.....	8
4.5 Audit columns.....	8
4.6 Status, soft delete and cancellation.....	9
4.7 JSON document columns.....	9
4.8 Keys, constraints and indexes.....	9
4.9 References without a foreign key.....	10
5. Data model by functional area.....	11
5.1 Overview.....	11
5.2 Party and client.....	11
5.3 Product and rating.....	12
5.4 Sales and quotation.....	13
5.5 Placement.....	13
5.6 Policy and endorsement.....	14
5.7 Billing, receipts and payments.....	15
5.8 Remittance and insurer accounting.....	16
5.9 Commission.....	16
5.10 Claims.....	17
5.11 Renewals.....	18
5.12 General ledger and period end.....	18
5.13 Bank and insurer reconciliation.....	19
5.14 Credit control.....	20
5.15 Reinsurance.....	20
5.16 Incentives.....	21
5.17 Security and audit.....	21
5.18 Configuration and schedules.....	22
6. Status lifecycles.....	23

6.1 Sales, placement and policy.....	23
6.2 Money and accounting.....	23
6.3 Claims, renewals and other areas.....	24
7. Personal data and retention.....	26
7.1 Personal data under the Data Privacy Act.....	26
7.2 Tables and columns holding personal data.....	26
7.3 Protection in the database.....	28
7.4 Retention.....	28
8. Appendix A: Table list.....	30
8.1 Party and client.....	30
8.2 Product and rating.....	30
8.3 Sales and quotation.....	31
8.4 Placement.....	31
8.5 Policy and endorsement.....	32
8.6 Billing, receipts and payments.....	32
8.7 Remittance and insurer accounting.....	33
8.8 Commission.....	33
8.9 Claims.....	34
8.10 Renewals.....	34
8.11 General ledger and period end.....	34
8.12 Bank and insurer reconciliation.....	35
8.13 Credit control.....	36
8.14 Reinsurance.....	37
8.15 Incentives.....	37
8.16 Security and audit.....	37
8.17 Configuration and schedules.....	38
9. Document Sign-Off.....	40

1. Document Control

Date	Version	Author & Business Unit Info	Reviewed By & Business Unit Info	Approved By & Business Unit Info	Change History
03 October 2026	1.0	iorta TechNXT			Initial issue

2. Acronyms

Acronym / Symbol	Definition / Meaning
OOTB	Out of the box
BIR	Bureau of Internal Revenue
IC	Insurance Commission
DPA	Data Privacy Act of 2012 (Republic Act No. 10173)
NPC	National Privacy Commission
FK	Foreign key
PK	Primary key
GL	General ledger
JV	Journal voucher
OR	Official receipt
PV	Payment voucher
DN	Debit note
EWT	Expanded withholding tax
WHT	Withholding tax
VAT	Value-added tax
DST	Documentary stamp tax
LGT	Local government tax
FST	Fire service tax
LGU	Local government unit

TIN	Tax identification number
ATC	Alphanumeric tax code
TOTP	Time-based one-time password
JSON	JavaScript Object Notation
LOB	Line of business
SLA	Service level agreement

3. About this document

This data dictionary describes the database of BrokerVerse OOTB: what each functional area stores, the key tables and how they relate, the conventions every table follows, the main status lifecycles and the columns that hold personal data. It is written for the broker's finance, operations and IT staff who read reports, run data migration and reconcile figures, and for the support team that maintains the system after go-live.

The column-level detail is in the companion workbook

BrokerVerse_Data_Dictionary.xlsx. This document summarises it and explains the model. Where the two differ, the workbook is the more detailed reference.

3.1 Sources

All facts come from the application and the database:

- the migration files in `backend/src/db/migrations` (80 files, `0001_core.sql` to `0216_claim_settlement_repair_shop.sql`), including the comments written next to the columns;
- the seed files in `backend/src/db/seeds` and the seed step `backend/src/db/seed.js`;
- the module code in `backend/src/modules` (status vocabularies, validation, posting) and the scheduled jobs in `backend/src/jobs`;

- the catalogue of a fully migrated and loaded PostgreSQL test database (golive): tables, columns, keys, indexes, constraints and row counts.

Row counts in this document and in the workbook are those of the loaded test database, which holds reference data and the sample data set. They show the relative weight of the tables, not production volumes. A production database starts with reference data only.

3.2 The companion workbook

Sheet	Content
Summary	Counts of tables, columns, keys, indexes, constraints and settings; columns by data type; tables and rows by functional area.
Tables	One row per table and view: functional area, owning module, description, primary key, rows in the test database, number of columns, the migration that created it, retention class and whether it holds personal data.
Columns	One row per column (2,797 rows): position, data type, length or precision, nullable, default, primary key, foreign key target, uniqueness, personal data class, the migration that added it and a business description.
Relationships	All 292 foreign keys: child and parent table and columns, delete and update rule, functional areas and whether an index supports the key.
Indexes	All 520 indexes: kind, method, columns or expression and the condition of partial indexes.
Reference values	Status vocabularies from the code, allowed values of CHECK constraints, values documented in the migrations, all 404 application settings with group, label and seeded value, master types and master records, document number series, roles, tax codes, bank transaction types, the month-end checklist, scheduled jobs and posting rule events.

3.3 Database at a glance

Item	Value (loaded test database)
Database engine	PostgreSQL, schema public
Migrations applied	80 (0001_core.sql to 0216_claim_settlement_repair_shop.sql)
Tables	167
Views	2 (bank_account_links, bank_book_lines)
Columns	2,756 in tables, 2,797 including the views
Foreign keys	292 (244 no action, 44 cascade, 4 set null)
Indexes	520 (167 primary keys, 111 further unique, 40 partial, 1 GIN)
CHECK constraints	174
Application settings	404 keys in 42 groups
Rows in all tables	7,669
Columns holding personal data	137 in 41 tables

4. Conventions

4.1 Naming

- Tables and columns are lower case with underscores (journal_vouchers, premium_total). Table names are plural nouns (policies, receipts); line and child tables add a suffix (receipt_lines, posting_rule_lines, renewal_notices).
- A foreign-key column is named after the parent with _id (policy_id, client_id, insurance_company_id). Where a table refers to the same parent more than once, the column says the role: renewed_from, new_policy_id, reversal_of, booking_jv_id, accrual_jv_id, owner_user_id, handler_user_id.
- Stamps end in _at (date and time) and _by (user): approved_at, approved_by. Calendar dates end in _date (jv_date, due_date, loss_date). Flags start with is_ or read as a yes or no question (is_open_item, allow_manual, per_participant).
- Readable document numbers end in _number (policy_number, receipt_number, jv_number). Rates and shares say their unit where it matters: _pct and _percent hold percent, commission_rate holds a fraction.
- Codes taken from settings or masters keep the code of the source (branch_code, account_code, gl_account_code, type_code).

4.2 Identifiers

Kind	How it works
Text key with prefix (61 tables)	Business records. The database generates a prefix and random hexadecimal characters, for example pol_ + 16 characters for a policy, qt_ for a quotation, or_ for a receipt, jv_ for a journal voucher. The ids cannot be guessed and never collide across tables. commission_referrers and reinsurers use a readable code instead (for example ref-dacruz, RE001).
Sequential number (83 tables)	Masters, lines and logs (integer or bigint from a sequence): countries, banks, insurers, products, journal_lines, audit_log, login_history, claim_history, risk_participants.
Natural or composite key (the other tables)	Codes that are themselves the key: app_settings(key), gl_accounts(code), tax_codes(code), accounting_periods(period), fiscal_years(code), master_types(code), sequences(name, period), opening_balances(fiscal_year, account_code), role_permissions(role_id, permission_id).

Business numbers (QT-2026-00001, POL-2026-00001, OR-2026-00019, JV-, BS-, PS-, REM-, DN-, BRC-, MEC-) are separate unique columns, never primary keys. Every number comes from a series of the Document Numbering master (document_numbering, 60 series). The SQL function next_document_number() locks the counter row in sequences until the transaction ends, so two users never receive the same number and a cancelled save gives its number back. The pattern tokens are

{PREFIX} {YYYY} {YY} {MM} {FY} {BRANCH} {LOB} {SEQ}; the reset rule is yearly, fiscal_yearly, monthly or never.

4.3 Money, rates and shares

- Amounts are numeric: 232 columns are numeric(14,2) and 61 are numeric(16,2) (sums insured, credit limits, bank statement and reconciliation figures, statement and certificate totals, treaty capacity). The application rounds every result to two decimals with half away from zero, the same rule as PostgreSQL round(numeric, 2).
- The currency of a document is in a currency column (PHP by default) where a document can be in another currency; journal_lines carry currency_code, exchange_rate and foreign_amount. All ledger amounts are in PHP.
- Commission rates are fractions: commission_rate 0.15 means 15% (insurance_companies, commission_rates, insurer_rate_tables, risk_participants). Tax rates in tax_codes.rate and premium_charge_rules.rate are percent (12 means 12%). Co-insurance shares (share_percent, offered_share) are percent from 0 to 100.
- Debit and credit are separate non-negative columns on journal_lines and bank_statement_lines; a journal line has either a debit or a credit (CHECK constraint).

4.4 Dates and the business time zone

- Calendar dates (inception, expiry, due, loss, receipt, voucher, statement and period dates) are date columns (120 columns). They carry no time and cannot shift with the time zone.
- Instants (creation, approval, posting, sending) are timestamptz (363 columns): stored as an absolute point in time and shown in local time.
- "Today" is the business date in the time zone of the setting general.timezone, seeded as **Asia/Manila**. Date columns that default to today use the function numbering_business_date() (migration 0145_business_date_defaults.sql), so a record created between 00:00 and 08:00 Manila time gets the Manila date, not the date of the server clock, which runs on UTC. Document numbering, period assignment, reports and scheduled jobs use the same business date.
- Accounting periods are keyed YYYY-MM; period 13 of a fiscal year is the year-end adjustment period. A journal falls in the period of its jv_date.
- The screens show dates as DD/MM/YYYY (general.date_format). This document writes dates as 03 October 2026.

4.5 Audit columns

Column	Tables	Meaning
created_at	126	Date and time the row was created.
created_by	100	User id of the creator.
updated_at	94	Date and time of the last change; set by the application, and by triggers on users, roles, commission_rates

Column	Tables	Meaning
		and document_numbering.
updated_by	63	User id of the last change.
Maker-checker stamps	many	submitted_by / submitted_at, approved_by / approved_at, rejected_by / rejected_at, posted_by / posted_at, decided_by / decided_at.

Every create, update, approval, posting and sign-in related event is also written to audit_log (who, when, which record, action, values before and after, IP address). Domain histories add detail where it is needed: claim_history, claim_field_changes, renewal_activities, renewal_notices, collection_actions, period_status_history, bank_reconciliation_history, remittance_approvals.history, login_history, password_history and job_runs.

4.6 Status, soft delete and cancellation

- Almost every business table has a status column (110 tables). Statuses are stored as lower-case codes in most tables; some older modules store the label (Accrued, Paid, Active). The screens map codes to labels, for example a quotation with status sent shows as **PendingCustomer**. The values of each status column are in the workbook, sheet Reference values.
- Masters are not deleted while in use: they become inactive, and generic master records get the status deleted; unique indexes on codes are partial (WHERE status <> 'deleted') so a code can be reused after deletion.
- Leads, quotations and bank statements carry deleted_at (soft delete). A draft quotation is the only business record deleted physically.
- Financial documents are never deleted. A receipt is cancelled, a journal is reversed or corrected by another journal (reversal_of, reversed_by_jv, correction_of), a BIR Form 2307 certificate is cancelled (cancelled_at), a debit note collection is reversed.

4.7 JSON document columns

103 columns are jsonb. They hold the parts of a record whose structure depends on the product or the screen: the full document of a quotation, broker slip, placement or policy (doc), vehicle and cover selections, claim details, endorsement changes, configuration values (app_settings.value), master record fields (master_records.data) and before and after values of the audit trail. Anything that is searched, totalled, joined or reported on is kept in ordinary columns. The workbook marks each JSON column and describes its content.

4.8 Keys, constraints and indexes

- **Foreign keys.** 292 foreign keys. 244 use no action: a referenced record cannot be deleted while it is used. 44 cascade: lines and histories that have no meaning without their parent (journal lines, receipt lines, claim history, renewal notices, role grants, match items). 4 set the reference to empty when the parent goes. 47 foreign keys point to users; other user columns (created_by, approved_by) hold the user id without a foreign key.

- **Supporting indexes.** 69 foreign keys have no index whose first column is the foreign-key column. They are on small master and set-up tables or are maker-checker stamp columns. The sheet Relationships flags them.
- **CHECK constraints.** 174 constraints protect allowed values (statuses, kinds, rate bases), number ranges (rates, shares, instalment counts) and rules that span columns (a journal line has a debit or a credit, a limit is for a role or for a user, a delegation ends after it starts).
- **Unique and partial indexes.** Business numbers and codes are unique. Partial unique indexes enforce rules such as one active instalment plan per bill, one pending warranty extension per policy, one lead insurer per co-insured record and one open renewal per policy.
- **Triggers.** `jv_check_posting` refuses to post a journal that is unbalanced, has fewer than two lines or falls in a period that does not accept postings. `accounting_period_lock_guard` refuses to reopen a period locked by the year-end close. Further triggers keep `updated_at`, derive the normal balance of a GL account and mirror number series prefixes into settings.

4.9 References without a foreign key

Some tables refer to more than one kind of parent, so the reference is a pair of columns without a foreign key:

Table	Columns	Refers to
<code>risk_participants</code>	<code>entity_type</code> , <code>entity_id</code>	A broker slip, quotation, placement or policy (co-insurance participants).
<code>package_sections</code>	<code>entity_type</code> , <code>entity_id</code>	A bundle quotation or a package policy.
<code>journal_vouchers</code>	<code>reference_type</code> , <code>reference_id</code>	The source document of a journal (Policy, Receipt, Disbursement, Commission, Endorsement, Claim ...).
<code>documents</code>	<code>entity</code> , <code>entity_id</code>	The record a stored file belongs to.
<code>audit_log</code> , <code>notifications</code> , <code>email_outbox</code> , <code>agent_events</code>	<code>entity</code> , <code>entity_id</code>	The record the entry is about.
<code>remittance_approvals</code>	<code>entity</code> , <code>entity_id</code>	A remittance or a remittance work item.
<code>payment_links</code>	<code>target_type</code> , <code>target_id</code>	A bundle quotation, quotation or policy.
<code>bank_statement_lines</code> , <code>bank_statements</code> , <code>bank_rec_matches</code>	<code>bank_account_id</code>	A bank account master record (master_records, type bank-account).

5. Data model by functional area

5.1 Overview

Functional area	Tables	Key tables
Party and client	10	clients, insurance_companies
Product and rating	15	products, product_templates, premium_charge_rules
Sales and quotation	9	leads, quotes, payment_links
Placement	4	broker_slips, insurer_offers, placements, risk_participants
Policy and endorsement	4	policies, endorsements
Billing, receipts and payments	16	receivables, receipts, receipt_applications, disbursements
Remittance and insurer accounting	12	remittances, direct_bill_items, commission_debit_notes
Commission	4	commissions, commission_rates
Claims	4	claims, claim_settlement_movements
Renewals	7	renewals, renewal_quotes
General ledger and period end	20	journal_vouchers, journal_lines, gl_accounts, posting_rules, accounting_periods
Bank and insurer reconciliation	13 + 2 views	bank_statements, bank_rec_matches, bank_reconciliations, insurer_statements
Credit control	7	collection_items, premium_instalment_plans
Reinsurance	7	reinsurance_treaties, cessions, reinsurance_recoveries
Incentives	3	incentive_programs, incentive_results
Security and audit	16	users, roles, audit_log
Configuration and schedules	16	app_settings, master_records, document_numbering, scheduled_jobs

5.2 Party and client

The client is the insured party. A client is created from a lead when a quotation is converted, by bulk upload or directly on the client screen. Individual and corporate clients share one table (`client_type`); identity, contact and address fields are columns, further screen fields are in extra. Insurers (principals) carry the commission rate used when the rate matrix has no rate, the premium payment warranty days, the remittance terms and the default billing mode. The address masters (countries → states → cities → districts, and postal_codes) feed the address fields. Branches and signatories are printed on documents.

Table	Holds
clients	Insured parties: code, type, names, birth date, contact, address, TIN, owner, credit limit.
insurance_companies	Insurers: code, name, TIN, contact, default commission rate, premium warranty days, remittance terms days, default billing mode.

Table	Holds
banks	Banks and mortgagees. Bank accounts of the broker are master records of type bank-account.
branches, signatories	Broker branches and the persons who sign documents.
countries, states, cities, districts, postal_codes	Address masters.

From	To	Meaning
clients.lead_id	leads	Lead the client was converted from (unique when set).
clients.owner_user_id	users	Account executive who owns the client.
states.country_id, cities.state_id, districts.city_id	address masters	Province within a country, city within a province, district within a city.

5.3 Product and rating

Products are the lines sold (motor, fire, marine, casualty, engineering, accident, employee benefits). Each product has policy types and, for motor, the cover options for bodily injury, property damage and personal accident. The product configurator keeps versioned templates with their components (covers, rating factors, taxes, rules, documents) and the risk definitions per line. Premium charges (VAT or premium tax, DST, FST, LGT) are computed from premium_charge_rules and the LGT rates per province or city. Packaged products combine several products in one bundle; insurer rate tables price each section for the quick quote comparison.

Table	Holds
products, policy_types, coverages	Product catalogue, policy types per product, motor cover options.
product_templates, product_components	Versioned product templates and their components (JSON).
product_risk_mappings, product_risk_sections	Risk fields and risk sections per product or line.
premium_charge_rules, lgu_tax_rates	Tax and charge rules with effective dates; LGT rate per LGU.
package_bundles, package_bundle_sections, insurer_rate_tables	Bundles, their sections and the insurer rates used to price them.
vehicle_brands, vehicle_models, vehicle_variants	Vehicle make, model and variant lists for motor quotations.

From	To	Meaning
policy_types.product_id	products	Policy type of a product.
coverages.policy_type_id	policy_types	Cover option of a policy type.
product_templates.product_id, parent_id	products, product_templates	Template of a product; version derived from an earlier one.
product_components.template_id	product_templates	Component of a template (deleted with it).
package_bundle_sections.bundle_id, product_id	package_bundles, products	Section of a bundle and its product.
insurer_rate_tables.insurance_company_id, product_id	insurance_companies, products	Rate of an insurer for a product.
lgu_tax_rates.city_id	cities	City whose LGT rate applies.

5.4 Sales and quotation

A lead is a prospect with its contact data, product interest, source and owner. A quotation (quotes) is prepared for a lead or a client, for a product, policy type and insurer; motor quotations keep the vehicle and cover selections, all quotations keep the full document in doc with the premium breakdown. The customer accepts through an e-mailed approval link (only the hash of the token is checked) or staff record the answer in quote_customer_responses. Converting an accepted quotation issues the policy. Packaged products have their own bundle quotations with one priced section per product. Payment links let a client pay a quotation, a bundle quotation or a policy's open premium online through a gateway; every gateway notification is logged in payment_events.

Table	Holds
leads	Prospects: number, type, names, contact, address, product interest, source, status, owner.
quotes	Quotations: number, lead or client, product, insurer, vehicle and covers, premium, taxes, commission, approval link, status.
quote_customer_responses	Customer answers recorded by staff, with channel, outcome and evidence.
package_quotes, package_sections	Bundle quotations and their priced sections (also the sections of a package policy).
payment_gateways, payment_links, payment_events	Online payment set-up, payment requests and the gateway notification log.
agent_events	Calendar events and reminders of a user.

From	To	Meaning
quotes.lead_id, client_id	leads, clients	Prospect or client quoted.
quotes.product_id, policy_type_id, insurance_company_id	masters	What is quoted and with which insurer.
quotes.broker_slip_id	broker_slips	Broker slip the quotation was prepared from (placement journey).
quotes.policy_id	policies	Policy issued from the quotation.
quote_customer_responses.quote_id	quotes	Response to a quotation.
package_quotes.bundle_id, policy_id	package_bundles, policies	Bundle quoted; package policy issued.
payment_links.gateway_code, receipt_id	payment_gateways, receipts	Gateway used; official receipt created from the payment.
payment_events.link_id	payment_links	Notification about a payment link.

5.5 Placement

Placement is the journey for risks that need terms from several insurers. A broker slip describes the risk and the covers requested and is sent to several insurers; each answer is an insurer offer (premium, rate, taxes, deductibles, validity, share offered) or a decline. The selected offers become a quotation or a placement slip, the firm order to the chosen insurers. When the risk is co-insured, risk_participants holds the lead insurer and the co-insurers with their shares, premium, taxes and

commission; the same table serves the broker slip, quotation, placement and policy. The policy is issued when every participant has bound.

Table	Holds
broker_slips	Broker slips (BS-): client or lead, product, risk details, requested covers, response due date, status.
insurer_offers	Offers (OFR-) or declines from each insurer on a slip; the selected flag.
placements	Placement slips (PS-): lead insurer, premium, taxes, billing mode, binding and issue stamps, policy issued.
risk_participants	Co-insurance participants: insurer, lead flag, share, premium, taxes, commission, binding confirmation.

From	To	Meaning
insurer_offers.broker_slip_id	broker_slips	Offer on a slip (deleted with the slip).
broker_slips.quote_id	quotes	Quotation slip prepared from the selected offers.
placements.broker_slip_id, quote_id	broker_slips, quotes	Origin of the placement.
placements.policy_id	policies	Policy issued from the placement.
risk_participants.insurance_company_id	insurance_companies	Participating insurer; the parent record is given by entity_type and entity_id.

5.6 Policy and endorsement

The policy is the central record. It points to the client, product, policy type, insurer (the lead insurer when co-insured), the quotation or placement it came from and the policy it renews. `billing_mode` decides the money flow: **broker** (the broker bills and collects the premium and remits it to the insurer) or **direct** (the insurer bills the client and the broker bills its commission to the insurer). Endorsements change an issued policy, re-price it and may raise their own bill or return premium; a cancellation is an endorsement. Front-office staff capture premium payments on a policy in `policy_payments` until Accounting confirms them and issues the official receipt.

Table	Holds
policies	Policies: number, client, product, insurer, term, sum insured, premium, taxes, commission, billing mode, payment status, renewal links, status.
endorsements	Endorsements and cancellations: type, changes, premium change, billing link, status.
package_endorsements	Changes of one section of a package policy and the additional premium.
policy_payments	Payments captured on a policy awaiting confirmation by Accounting.

From	To	Meaning
policies.client_id, product_id, policy_type_id, insurance_company_id	masters and clients	Insured, product and insurer of the policy.

From	To	Meaning
policies.quote_id, placement_id, lead_id	quotes, placements, leads	Origin of the policy.
policies.renewed_from	policies	Expiring policy this one renews (renewed_to holds the reverse link).
endorsements.policy_id, receivable_id	policies, receivables	Policy changed; bill raised for the additional premium.
policy_payments.policy_id, receivable_id, receipt_id	policies, receivables, receipts	Payment captured, bill paid and receipt issued on confirmation.

5.7 Billing, receipts and payments

Issuing a broker-billed policy, endorsement or renewal raises a premium bill (receivables, INV-) and its booking journal. For a co-insured policy receivable_participants splits the bill per insurer. An official receipt (receipts, OR-) has lines per policy, and receipt applications allocate the money to the bills and link the posting journal. Return premium and cancellations reduce a bill through receivable_credits; small differences are written off with a reason from write_off_reasons. Payments out are payment vouchers (disbursements, PV-) that settle invoice lists (amounts due to insurers, clients or referrers) and may be paid by cheque (checkbooks). Petty cash funds have their own requests, payments, receipts and replenishments.

Table	Holds
receivables	Premium bills: number, policy, client, amount, balance, due date, ageing, booking journal, status.
receivable_participants	Insurer shares of a co-insured bill: gross, commission, taxes, due to insurer.
receivable_credits	Return premium and cancellation credits applied to a bill, with the refund part.
receipts, receipt_lines, receipt_applications	Official receipts, their lines per policy and the application to bills.
write_off_reasons	Write-off reasons with GL account and maximum amount.
disbursements, invoice_lists, checkbooks	Payment vouchers, the invoice lists they settle and cheques.
petty_cash_funds, petty_cash_requests, petty_cash_request_lines, petty_cash_disbursements, petty_cash_receipts, petty_cash_replenishments	Petty cash.

From	To	Meaning
receivables.policy_id, client_id, booking_jv_id	policies, clients, journal_vouchers	Bill of a policy and the journal that booked it.
receipt_lines.receipt_id	receipts	Line of a receipt (deleted with it).
receipt_applications.receipt_id, receipt_line_id, receivable_id, journal_id	receipts, receivables, journal_vouchers	Money of a receipt line applied to a bill, and the posting journal.
receivable_credits.receivable_id, journal_id	receivables, journal_vouchers	Credit on a bill and its journal.
invoice_lists.disbursement_id	disbursements	Invoice list settled by a payment voucher.
checkbooks.disbursement_id,	disbursements, invoice_lists	Cheque issued for a voucher.

From	To	Meaning
invoice_list_id		
petty_cash_*.fund_id	petty_cash_funds	Movements of a petty cash fund.

5.8 Remittance and insurer accounting

Broker-billed premium collected from clients is remitted to the insurers net of commission. A remittance (REM-) has lines per policy; for a co-insured policy remittance_allocations splits each collection by insurer share. Settlements, adjustments and exceptions are remittance work items, and remittance_approvals is the multi-level approval register with SLA and history. Refunds due from an insurer on premium already remitted are held in insurer_refund_credits and netted against the next remittance. For direct-billed policies the broker's commission is a receivable from the insurer: direct_bill_items are billed on commission debit notes (DN-) and settled by debit note collections (cash plus EWT supported by BIR Form 2307). The client's own payment to the insurer is recorded in direct_bill_client_payments for follow-up only; it posts no journal.

Table	Holds
remittances, remittance_lines	Remittance bills to insurers and the policies included.
remittance_allocations	Co-insurance split of each collection by insurer.
remittance_items, remittance_approvals, remittance_delegations	Work items, approval requests and approval delegations.
insurer_refund_credits	Refunds due from insurers, netted against later remittances.
direct_bill_items, commission_debit_notes, commission_debit_note_lines, commission_debit_note_collections	Direct-bill commission receivable, debit notes and their collection.
direct_bill_client_payments	Client payments made directly to the insurer (no journal).

From	To	Meaning
remittance_lines.remittance_id, policy_id	remittances, policies	Policy in a remittance (deleted with the remittance).
remittances.insurance_company_id	insurance_companies	Insurer paid.
remittance_allocations.receipt_application_id, invoice_list_id	receipt_applications, invoice_lists	Collection split and the invoice list that remitted it.
direct_bill_items.debit_note_id, policy_id, booking_jv_id	commission_debit_notes, policies, journal_vouchers	Commission item billed on a debit note, its policy and booking journal.
commission_debit_note_lines.debit_note_id, item_id	commission_debit_notes, direct_bill_items	Lines of a debit note.
commission_debit_note_collections.debit_note_id, journal_id	commission_debit_notes, journal_vouchers	Collection against a debit note and its journal.

5.9 Commission

Commission (commissions) here is the referrer commission (comsub) paid to sub-agents and external referrers. One line is created per policy or endorsement and per referrer in the referral chain (chain_position); the line shows the brokerage the broker earns, the comsub (a fixed amount plus a percent of net premium),

withholding tax and the net payable. The line links to its accrual and payment journals and to the payment voucher that paid it. When premium is returned or a policy cancelled, `commission_adjustments` records the reduction, reversal or clawback. The broker's own commission rate for a new policy comes from `commission_rates` (insurer, product, line, new or renewal, effective dates), else from the insurer's default rate.

Table	Holds
<code>commissions</code>	Referrer commission lines: basis, rates, comsub, withholding, net, journals, voucher, status.
<code>commission_adjustments</code>	Reductions, reversals and clawbacks of commission lines.
<code>commission_rates</code>	Broker commission rate matrix with effective dates.
<code>commission_referrers</code>	Referrers and sub-agents: hierarchy, withholding rate, payout bank account.

From	To	Meaning
<code>commissions.policy_id, endorsement_id, referrer_id</code>	<code>policies, endorsements, commission_referrers</code>	Source and payee of the commission line.
<code>commissions.accrual_jv_id, payment_jv_id, disbursement_id</code>	<code>journal_vouchers, disbursements</code>	Accrual and payment journals and the paying voucher.
<code>commission_adjustments.commission_id</code>	<code>commissions</code>	Line adjusted.
<code>commission_referrers.parent_referrer_id</code>	<code>commission_referrers</code>	Referrer hierarchy.

5.10 Claims

A claim belongs to a policy and client and carries the loss details, the estimate, approved and settled amounts and the handler. Motor claims keep driver and third-party details in JSON. Every status change is in `claim_history` and every field change in `claim_field_changes`. Settlement cash is recorded in `claim_settlement_movements`: funds received from each insurer and payments to the claimant, each with its journal. Recoveries from reinsurers are in the reinsurance area.

Table	Holds
<code>claims</code>	Claims: number, policy, client, loss date, type, place, amounts, handler, adjuster, settlement, status.
<code>claim_history, claim_field_changes</code>	Status history and field-level change trail.
<code>claim_settlement_movements</code>	Funds received from insurers and paid to claimants, with journals.

From	To	Meaning
<code>claims.policy_id, client_id</code>	<code>policies, clients</code>	Policy and insured of the claim.
<code>claim_history.claim_id, claim_field_changes.claim_id</code>	<code>claims</code>	Histories (deleted with the claim).
<code>claim_settlement_movements.claim_id, insurance_company_id, journal_id</code>	<code>claims, insurance_companies, journal_vouchers</code>	Settlement cash movement, paying insurer and journal.

5.11 Renewals

The renewal pipeline job creates a renewal case for each policy approaching expiry. The case tracks notices sent, contact attempts, the renewal quotation (re-rating with loading and discounts), approval and the outcome: the renewal policy or a lapse. Renewal batches send notices and quotations for many policies at once through the background queue. Win-back campaigns target lapsed business.

Table	Holds
renewals	Renewal cases: expiring policy, client, old and new premium, notice stage, contact attempts, type, status, renewal policy.
renewal_quotes	Renewal quotations with loading, discount and variance.
renewal_notices, renewal_activities	Notices sent and contact activities.
renewal_batches, renewal_batch_policies	Batch runs and the policies in them.
winback_campaigns	Win-back campaigns.

From	To	Meaning
renewals.policy_id, new_policy_id	policies	Expiring policy and the renewal policy issued.
renewal_quotes.renewal_id, renewal_notices.renewal_id, renewal_activities.renewal_id	renewals	Quotation, notices and activities of a case (deleted with it).
renewal_batch_policies.batch_id, policy_id, renewal_id	renewal_batches, policies, renewals	Policy in a batch run.

5.12 General ledger and period end

Every system journal is built from a posting rule: the rule of a business event (for example policy.issue.broker_billed, receipt.apply, remittance.settlement) has versions with an effective date and lines that name a GL account or an account role. Account roles resolve to GL accounts through the Account Determination settings accounting.account.<role>. A line marked per participant is split across co-insurers by share. Changes to posting rules and account determination wait for a second user's approval (accounting_config_changes). Journal vouchers hold balanced journal lines on the chart of accounts; open-item accounts are matched debit to credit in entry_matches. Periods 1 to 12 and the adjustment period 13 of each fiscal year are opened, soft-closed, closed and locked; the month-end close run posts accruals and recurring journals, checks the checklist and closes the period. The year-end close posts the closing entries, carries the balances into opening_balances of the next year and locks the year. Tax codes hold VAT, EWT with ATC, DST and LGT; BIR Form 2307 certificates are kept per payee or payor and quarter.

Table	Holds
gl_accounts	Chart of accounts: type, category, financial statement group, normal balance, open-item and manual-use flags.
journal_vouchers, journal_lines	Journals and their debit and credit lines with client, policy, insurer, branch and department tags.
entry_matches	Open-item matching of debit and credit lines, with write-off.
posting_rules, posting_rule_lines, accounting_config_changes	Posting rule versions, their lines and pending configuration changes.

Table	Holds
fiscal_years, accounting_periods, period_status_history	Fiscal years, periods and every period status change.
period_close_checklist, period_close_runs, period_close_run_checks, period_close_entries	Month-end checklist, close runs, check results and close journals.
recurring_journals, recurring_journal_runs	Recurring and accrual journal templates and their occurrences.
year_end_runs, opening_balances	Year-end close runs and the opening balances they carry forward (or loaded at go-live).
tax_codes, bir_2307_certificates	Tax codes and BIR Form 2307 certificates.

From	To	Meaning
journal_lines.jv_id	journal_vouchers	Lines of a journal (deleted with a draft journal).
journal_lines.policy_id, client_id	policies, clients	Subsidiary-ledger tags of a line.
journal_vouchers.posting_rule_id	posting_rules	Rule version the journal was built from.
journal_vouchers.reversal_of, reversed_by_jv, correction_of	journal_vouchers	Reversal and correction chain.
entry_matches.debit_line_id, credit_line_id	journal_lines	Lines matched as an open item.
posting_rule_lines.rule_id	posting_rules	Lines of a rule version.
accounting_periods.fiscal_year, opening_balances.fiscal_year	fiscal_years	Periods and opening balances of a year.
period_close_runs.period	accounting_periods	Period closed by a run.
year_end_runs.closing_jv_id, transfer_jv_id	journal_vouchers	Closing and retained-earnings transfer journals.

5.13 Bank and insurer reconciliation

Bank statements are imported with a statement format (or keyed) into bank_statements and bank_statement_lines; a line hash refuses duplicates. Matches link bank lines to the journal lines on the GL cash account of the bank account (the view bank_book_lines gives that book side). Unmatched bank items such as charges and interest are posted with a bank transaction type. The monthly bank reconciliation stores the statement figures and, once approved, locks the matches cleared up to its date. Insurer statements of account (premium remittance confirmations or commission statements) are imported with a per-insurer column mapping and matched line by line to remittance lines, debit note lines or policies; differences are resolved with a note or an adjustment journal posted on approval.

Table	Holds
bank_statement_formats, bank_transaction_types, bank_match_rules	File layouts, bank-side transaction types and automatic matching rules.
bank_statements, bank_statement_lines	Imported or keyed statements and their lines.
bank_rec_matches, bank_rec_match_items	Matches and the bank and book lines in each.
bank_reconciliations, bank_reconciliation_history	Monthly reconciliation statements and their status history.
bank_account_links, bank_book_lines (views)	Bank accounts with their GL account; posted lines on bank cash accounts.
insurer_statement_formats, insurer_statements, insurer_statement_lines, insurer_statement_resolutions	Insurer statement layouts, imported statements, lines with match results and resolutions.

From	To	Meaning
bank_statement_lines.statement_id	bank_statements	Line of a statement.
bank_rec_match_items.match_id, bank_line_id, journal_line_id	bank_rec_matches, bank_statement_lines, journal_lines	Bank side and book side of a match.
bank_reconciliation_history.rec_id	bank_reconciliations	Status change of a reconciliation.
insurer_statement_lines.statements_id, policy_id	insurer_statements, policies	Line of an insurer statement and the policy it concerns.
insurer_statement_resolutions.line_id, journal_id	insurer_statement_lines, journal_vouchers	Resolution of a line and the adjustment journal.

5.14 Credit control

Credit control applies to broker-billed business. Collection items follow up open bills with assignments, commitments and escalation; every call, e-mail or visit is a collection action. A premium bill can be split into instalments without changing the bill in the ledger. The premium warranty monitor lists policies whose premium is unpaid near or past the warranty deadline; Accounting sends reminders, requests a deadline extension (approved by a second user holding approve:credit-control) or requests the cancellation of a breached policy, which creates a draft cancellation endorsement for Operations. A client credit limit is checked when a new policy is issued and every policy issued beyond it is logged for Accounting to acknowledge.

Table	Holds
collection_items, collection_actions	Follow-up of open bills and the actions taken.
premium_instalment_plans, premium_instalments	Instalment plans of a bill and their due dates and amounts.
premium_warranty_extensions, premium_warranty_actions	Warranty deadline extension requests and monitor actions.
client_credit_exceptions	Policies issued beyond a client's credit limit (clients.credit_limit).

From	To	Meaning
collection_items.receivable_id	receivables	Bill followed up (one item per bill).
collection_actions.collection_id	collection_items	Actions on an item (deleted with it).
premium_instalment_plans.receivable_id, policy_id	receivables, policies	Bill split into instalments.
premium_instalments.plan_id	premium_instalment_plans	Instalments of a plan.
premium_warranty_actions.extension_id	premium_warranty_extensions	Action taken on an extension request.
client_credit_exceptions.client_id, policy_id	clients, policies	Client over limit and the policy that took it there.

5.15 Reinsurance

Reinsurers and treaties (type, capacity, share, retention) are set up in the reinsurance module. A cession passes part of a policy's sum insured and premium to a treaty or, facultatively, to one reinsurer. Recoveries claim the reinsured part of a loss. Bordereaux report cessions or claims to reinsurers, and reconciliations compare the broker's figures with the reinsurer's statement, with exceptions to resolve.

Table	Holds
reinsurers, reinsurance_treaties	Reinsurers and treaties.
cessions	Treaty and facultative cessions per policy.
reinsurance_recoveries	Claim recoveries from reinsurers.
reinsurance_bordereaux, reinsurance_reconciliations, reinsurance_exceptions	Bordereaux, statement reconciliations and their exceptions.

From	To	Meaning
cessions.policy_id, treaty_id, facultative_reinsurer_id	policies, reinsurance_treaties, reinsurers	Policy ceded and where.
reinsurance_recoveries.claim_id, cession_id, treaty_id	claims, cessions, reinsurance_treaties	Claim recovered under a cession.
reinsurance_exceptions.reconciliation_id	reinsurance_reconciliations	Exception found in a reconciliation.

5.16 Incentives

Incentive programmes define the measure (premium, policies, conversion), targets, tiers and eligibility. A calculation batch computes the results of a period for every participant and goes through maker-checker approval before payment.

Table	Holds
incentive_programs	Programmes: measure, target, stretch target, structure, eligibility, frequency.
incentive_calculations	Calculation batches with approval, journals and payment.
incentive_results	Result and payout per programme, participant and period.

From	To	Meaning
incentive_results.program_id, calculation_id, agent_user_id	incentive_programs, incentive_calculations, users	Result of a participant in a programme and batch.

5.17 Security and audit

Users sign in with a username and password (bcrypt hash only) and, where required by role, a second factor (TOTP secret stored encrypted). Roles carry permissions (read:<module>, write:<module>, approve:<area>) and may inherit another role. Refresh tokens are rotated and revoked by family. The access control tables add the authority matrix (approval limits per role or user and transaction type, effective once a second administrator approves), segregation-of-duties rules, out-of-office delegations and periodic access reviews. audit_log and login_history are the audit trail.

Table	Holds
users, roles, permissions, user_roles, role_permissions	Users, roles, permissions and their assignments.
refresh_tokens, password_resets, password_history, login_history	Sessions, reset codes (hash only), previous password hashes, sign-in attempts.
authority_transaction_types, authority_limits	Authority matrix.
sod_rules, user_delegations	Segregation-of-duties rules and delegations.
access_reviews, access_review_items	Access reviews and the decision per user.
audit_log	Audit trail of every change.

From	To	Meaning
user_roles.user_id, role_id	users, roles	Role assigned to a user.
role_permissions.role_id, permission_id	roles, permissions	Permission granted to a role.
authority_limits.role_code, user_id, transaction_type	roles, users, authority_transaction_types	Limit of a role or user for a transaction type.
sod_rules.role_a, role_b	roles	Conflicting pair of roles.
access_review_items.review_id, user_id	access_reviews, users	User reviewed in a campaign.

5.18 Configuration and schedules

Business parameters are keys of app_settings (404 keys in 42 groups), edited in Master > Configuration and System Settings; the workbook lists every key with its group, label and seeded value. Masters without a table of their own are records of master_records described by master_types (fields, unique keys, screen). Document number series and their counters are in document_numbering and sequences. Scheduled jobs and their run history, the background queue, notifications, the e-mail outbox, stored files and the report catalogue complete the platform tables.

Table	Holds
app_settings	Configuration keys with JSON value, group, label and type.
master_types, master_records	Master screen registry and generic master records.
currencies	Currencies with base flag, decimals and exchange rate.
document_numbering, sequences	Number series and their counters per period.
scheduled_jobs, job_runs, job_queue	Cron jobs, run history and the background queue.
notifications, email_outbox, documents	In-app notifications, queued e-mails, registry of stored files.
report_definitions, report_schedules, generated_reports	Report catalogue, e-mailed schedules and generated files.
schema_migrations	Applied migration files.

From	To	Meaning
master_records.type_code	master_types	Record of a master type.
job_runs.job_id	scheduled_jobs	Run of a job.
report_schedules.report_code, job_id	report_definitions, scheduled_jobs	Report sent by a schedule and the job that runs it.

6. Status lifecycles

The tables below give the main status flows. The values are the codes stored in the database; screen labels are given where they differ. The complete vocabularies, including the allowed values enforced by CHECK constraints, are in the workbook, sheet Reference values.

6.1 Sales, placement and policy

Record	Status flow	Notes
Lead (leads.status)	New → Contacted → Qualified → QuoteGenerated → Converted; or Lost	QuoteGenerated is set when the first quotation is created; Converted when the lead becomes a client.
Quotation (quotes.status)	draft (Draft) → sent (PendingCustomer) → accepted (CustomerAccepted) → submitted (SubmittedToInsurer) → approved → converted (ConvertedToPolicy); or rejected, dropped, expired	Sending e-mails the approval link. A recorded customer response sets accepted, rejected or back to draft (quotations.customer_response_status). Conversion is allowed from the statuses in quotations.convertible_statuses (CustomerAccepted, Approved). The quotation expiry job sets expired.
Broker slip (broker_slips.status)	draft → submitted → responses-in → closed; or cancelled	
Insurer offer (insurer_offers.status)	pending → offered or declined	The chosen offers carry selected.
Placement slip (placements.status)	draft → sent → bound → issued; or declined, cancelled	Bound when every participant has confirmed (risk_participants.confirmed_at).
Policy (policies.status)	active → expired, renewed or cancelled	The policy expiry job sets expired; issuing the renewal sets renewed; a cancellation endorsement sets cancelled. payment_status follows the premium: Pending, Reviewing, Partial, Completed, Refunded.
Endorsement (endorsements.status)	draft → submitted (PendingCustomer) → approved → completed; or cancel-initiated, rejected, cancelled	
Payment capture (policy_payments.status)	submitted → confirmed or rejected	Confirmation by Accounting issues the official receipt.
Payment link (payment_links.status)	pending → paid, failed, expired, cancelled or review	apply_status: not_applied → applied, awaiting_issue or error.

6.2 Money and accounting

Record	Status flow	Notes
Premium bill (receivables.status)	open → partial → paid; or credited, written-off, cancelled	
Official receipt (receipts.status)	posted → cancelled	Receipt applications: applied → reversed.
Payment voucher (disbursements.status)	draft → for-approval → approved → paid; or rejected	Cheque (checkbooks.status): Pending → Approved →

Record	Status flow	Notes
		Printed; or Cancelled. Invoice list: open → in-voucher → paid; or cancelled.
Remittance (remittances.status)	draft → for-approval → approved → settled; or rejected	
Direct-bill item (direct_bill_items.status)	unbilled → billed → collected; or cancelled	
Commission debit note (commission_debit_notes.status)	draft → for-approval → open → partial → collected; or rejected, cancelled	
Commission line (commissions.status)	Accrued → Eligible → Approved → Paid	Eligible once the premium is collected. A reversal after payment sets the clawback flag.
Journal voucher (journal_vouchers.status)	draft → for-approval → approved → posted; or rejected; posted → reversed	The trigger refuses an unbalanced journal or one in a period that does not accept postings.
Accounting period (accounting_periods.status)	open → soft_closed → closed → locked	Locked only by the year-end close; a locked period cannot be reopened.
Month-end close run (period_close_runs.status)	draft → in-progress → blocked or ready → pending-approval → soft-closed or closed; or cancelled	A blocking automatic check that fails gives blocked.
Year-end close run (year_end_runs.status)	draft → checked → closed → reversed; or cancelled	
Bank reconciliation (bank_reconciliations.status)	draft → prepared → approved; or cancelled	An approved reconciliation can be reopened with remarks.
Insurer statement (insurer_statements.status)	draft → submitted → approved; or cancelled	Adjustment journals post on approval.
Posting rule version (posting_rules.approval_status)	pending → approved or rejected	Configuration changes: pending → approved, rejected or withdrawn.

6.3 Claims, renewals and other areas

Record	Status flow	Notes
Claim (claims.status)	registered → in-review → pending-approval → approved → settled → closed; or rejected	Every change is written to claim_history.
Renewal case (renewals.status)	pipeline → notice-1 → notice-2 → final-notice → quoted → pending-approval → renewed; or lapsed	renewal_type records whether the renewal was regular, in the grace period or after lapse.
Instalment plan / warranty extension	plan: active or cancelled; extension: pending → approved or rejected	
Cession (cessions.status)	Pending → Confirmed; or Rejected, Cancelled	Recovery: Pending → Processing → Recovered; or Disputed, Rejected.
Incentive calculation (incentive_calculations.status)	Calculated → Pending Approval → Approved → Paid; or Rejected	
Authority limit (authority_limits.status)	pending → active → retired; or rejected	A changed limit is a new pending row that retires the old one on approval.
Access review	review: open → closed; item:	

Record	Status flow	Notes
	pending → keep or revoke	
User (users.status)	active, inactive, locked	The dormant accounts job deactivates users who have not signed in for access.dormant_days.

7. Personal data and retention

7.1 Personal data under the Data Privacy Act

BrokerVerse processes personal information of clients, prospects, claimants, drivers and third parties, referrers and staff users. The workbook classifies every column in the column **Personal data (RA 10173)** using four classes:

Class	Meaning	Columns
Personal information	Information from which the identity of an individual is apparent or can be reasonably ascertained (Section 3(g) of RA 10173): names, addresses, e-mail, phone, IP address, plate number.	90
Sensitive personal information	Section 3(l) of RA 10173: age (date of birth), government-issued identifiers such as the TIN, and health or offence-related details that claims may contain.	9
Credential / security secret	Password hashes, second-factor secrets, reset codes, tokens. Not personal information in themselves but must be protected as security data.	9
May contain personal information	Free text, JSON documents and stored files that hold personal information depending on what users enter or upload.	29

The classification is an assessment made for this document from the column names, their use in the code and the test data. The broker's Data Protection Officer should confirm it and record it in the register of processing activities.

7.2 Tables and columns holding personal data

In the table, Personal, Sensitive, Credential and May contain refer to the four classes above.

Table	Columns holding personal data
clients	Personal: first_name, last_name, company_name, display_name, email, phone, gender, address, city, state, country, postal_code, preferred_name, house_no, barangay, road, soi, moo Sensitive: tin, birth_date May contain: extra
signatories	Personal: name, designation, signature_key
agent_events	May contain: description
leads	Personal: first_name, last_name, company_name, display_name, email, phone, gender, address, city, state, country, postal_code, preferred_name, house_no, barangay, road, soi, moo Sensitive: birth_date, tax_number May contain: notes, extra

Table	Columns holding personal data
package_quotes	Personal: insured_name
payment_events	May contain: payload
payment_links	Personal: payer_name, payer_email, payer_mobile Credential: token
quote_customer_responses	May contain: remarks, attachment_key
quotes	Personal: vehicle, approval_sent_to Credential: approval_token May contain: doc
broker_slips	Personal: insured_name May contain: doc
placements	Personal: insured_name May contain: doc
endorsements	May contain: changes
policies	Personal: insured_name May contain: details, doc
policy_payments	May contain: proof_key
checkbooks	Personal: customer_name
disbursements	Personal: payee_name, referrer_name
petty_cash_receipts	Personal: requester_name
petty_cash_requests	Personal: requester_name
receipts	Personal: customer_name
commission_debit_note_lines	Personal: insured_name
direct_bill_client_payments	May contain: proof_key
remittance_lines	Personal: insured_name
commission_referrers	Personal: name, email, phone, bank_name, bank_account_no Sensitive: tin
claim_field_changes	May contain: old_value, new_value
claims	Personal: loss_address Sensitive: driver, third_party May contain: description, details, policy_info, adjuster, settlement
renewal_notices	Personal: recipient
renewals	May contain: coverage_details
bir_2307_certificates	Personal: payee_name, payee_address, payor_name, payor_address Sensitive: payee_tin, payor_tin
insurer_statement_lines	Personal: insured_name
collection_actions	May contain: notes
cessions	Personal: insured
reinsurance_recoveries	Personal: insured
access_review_items	Personal: last_login_at
audit_log	Personal: username, ip May contain: before_data, after_data
login_history	Personal: username, ip, user_agent
password_history	Credential: password_hash
password_resets	Credential: code, code_hash
refresh_tokens	Personal: device_id Credential: jti
users	Personal: username, display_name, first_name, last_name, email, phone, employee_code, department, designation, reporting_to, last_login_at Credential: password_hash, totp_secret, totp_pending_secret
documents	May contain: storage_key, file_name
email_outbox	Personal: to_address, cc May contain: body_html

7.3 Protection in the database

- Passwords are stored only as bcrypt hashes; reset codes only as keyed hashes; the second-factor secret is encrypted with AES-256-GCM using the key in DATA_ENCRYPTION_KEY. Payment gateway credentials are not stored in the database but read from the environment.
- Access to the data in the application follows the role permissions; the authority matrix, segregation-of-duties rules and access reviews control who may approve and who holds which roles.
- Every change to a record is in audit_log with the user, time, IP address and the values before and after. Because the audit trail copies record values, it holds personal information too.
- The database has no column-level encryption or masking of client data; protection relies on database access control, encryption of the storage and of backups, and the application's permissions. See the Architecture, Infrastructure, Security and Privacy document.

7.4 Retention

The system has two kinds of retention. Operational rows are deleted by the daily housekeeping job after the number of days set in System Settings > Housekeeping (0 means keep forever). Business and financial records are never deleted by the system.

Table	Rows deleted	Setting	Seeded days
job_runs	Job run history	housekeeping.job_runs_days	90
email_outbox	Sent e-mails	housekeeping.email_outbox_sent_days	180
email_outbox	Failed e-mails	housekeeping.email_outbox_failed_days	730
login_history	Sign-in attempts	housekeeping.login_history_days	365
refresh_tokens	Expired or revoked sessions	housekeeping.refresh_tokens_days	30
password_resets	Used or expired reset codes	housekeeping.password_resets_days	7
notifications	Read notifications	housekeeping.notifications_read_days	180
job_queue	Completed background jobs	housekeeping.job_queue_done_days	30
audit_log	Audit entries	housekeeping.audit_log_days	0 (keep); when set, never less than 2,557 days (7 years)
generated_reports	Generated report files	reports.retention_days (daily reports job)	90

Each table also carries a retention class in the workbook (sheet Tables):

Class	Tables	Handling
Financial	56	Ledger, bills, receipts, payments, commissions, remittances, reconciliations, tax certificates. Kept for the

Class	Tables	Handling
		statutory record-keeping period; cancelled or reversed, never deleted.
Transaction	25	Leads, quotations, placements, policies, endorsements, claims, renewals, reinsurance. Kept for the life of the policy or claim plus the regulatory period.
Reference	61	Masters, settings, posting rules, number series, roles. Kept while in use; changes audited.
Log / audit	21	Audit trail, histories, sign-in history, job runs. Kept for the audit period.
Temporary	6	Tokens, reset codes, outbox, queue, notifications, generated files. Purged by housekeeping.

Recommendation, to be confirmed by the broker's Data Protection Officer and finance: set the retention period of financial and transaction records to the longest period required by the BIR, the Insurance Commission and the broker's own policy, and apply the DPA principle of proportionality to prospects that never became clients (leads with no quotation or policy). The application has no anonymisation or erasure function for clients and leads; a data subject's request for erasure or blocking is handled by the support team with a reviewed database script, keeping the records that a statutory retention period still requires.

8. Appendix A: Table list

This appendix lists every table and view with a one-line description and the number of rows in the loaded test database. The columns of each table are in the workbook, sheet Columns.

8.1 Party and client

Table	Description	Rows
banks	Banks and mortgagees	6
branches	Broker branches	1
cities	Cities and municipalities	49
clients	Clients (insured parties) with KYC fields and owner	68
countries	Countries	5
districts	Districts / barangays with postal code	26
insurance_companies	Insurers (principals): contact, default commission rate, credit terms, billing mode	13
postal_codes	Postal code lookup (province, city, district)	26
signatories	Authorised signatories for documents	0
states	Provinces / states	17

8.2 Product and rating

Table	Description	Rows
coverages	BI / PD / PA cover options with amount and premium	11
insurer_rate_tables	Insurer rates per product for the quick quote comparison of packaged products: rate basis, minimum premium, deductible, commission	0
lgu_tax_rates	Local government (LGT) tax rates per province or city with effective dates	10
package_bundle_sections	Sections of a bundle: product, default sum insured, rate, minimum premium and the insurers that may carry it	0
package_bundles	Packaged product bundles (for example a multi-line SME cover): segment, term, discount, online issue	0
policy_types	Policy types per product	14
premium_charge_rules	Premium charge rules (VAT, premium tax, DST, FST, LGT, other): method, rate, unit size, minimum and effective dates	6
product_components	Template components: covers, rating tables, rules, documents (JSONB data)	48
product_risk_mappings	Product / line-of-business risk definitions	8
product_risk_sections	Risk sections of a mapping with default rates	4
product_templates	Versioned product templates	13

Table	Description	Rows
	(config JSONB, rates, limits, insurers)	
products	Insurance products / lines	19
vehicle_brands	Vehicle makes	8
vehicle_models	Vehicle models per make	19
vehicle_variants	Vehicle variants (body type, seating)	20

8.3 Sales and quotation

Table	Description	Rows
agent_events	Calendar events and reminders of a user (open items screen)	0
leads	Leads / prospects (individual or corporate), owner, status	61
package_quotes	Bundle quotations: client, location, premium, discount, taxes, commission and status	0
package_sections	Priced sections of a bundle quotation or package policy, each with its insurer, premium, taxes and commission	0
payment_events	Every notification received from a payment gateway (or simulated), valid or not: the payments log	0
payment_gateways	Online payment gateways (Dragonpay, PayMongo, sandbox): mode, methods, fee handling, link validity; credentials stay in the environment	3
payment_links	Payment links sent to a client to pay a package quotation, quotation or policy premium online, and the result	0
quote_customer_responses	Customer responses to a quotation recorded by staff (phone, Viber, meeting, signed form) as evidence of the status change	72
quotes	Quotations: vehicle / coverage JSONB, premium, taxes, commission, approval token hash	72

8.4 Placement

Table	Description	Rows
broker_slips	Broker slips (BS-): a client risk sent to several insurers for terms	48
insurer_offers	Insurer offers (OFR-) on a broker slip: premium, rate, taxes, deductibles, validity, share, or a decline	118
placements	Placement slips (PS-): firm	23

Table	Description	Rows
	order to the chosen insurers, binding per participant, policy issue	
risk_participants	Co-insurance participants of a broker slip, quotation, placement or policy: lead, share, premium and commission	219

8.5 Policy and endorsement

Table	Description	Rows
endorsements	Policy endorsements and cancellations, premium delta, billing link	8
package_endorsements	Endorsements of one section of a package policy: change of sum insured and the additional premium billed	0
policies	Issued policies: term, premium, insurer, billing mode, details / doc JSONB	82
policy_payments	Premium payments captured on a policy, awaiting finance confirmation	18

8.6 Billing, receipts and payments

Table	Description	Rows
checkbooks	Cheques issued (instrument, approval, printing)	19
disbursements	Payment vouchers (PV-) to insurers, agents, clients; approval and payment	27
invoice_lists	Invoice lists (IL-) settled by a disbursement	55
petty_cash_disbursements	Petty cash payments (VAT, WHT, journal)	3
petty_cash_funds	Petty cash funds (size, limits, custodian, available cash)	1
petty_cash_receipts	Receipts into a petty cash fund	0
petty_cash_replenishments	Fund replenishments from bank	3
petty_cash_request_lines	Lines of a petty cash request	6
petty_cash_requests	Petty cash requests and approval	3
receipt_applications	Application of receipt lines to bills, with journal link	58
receipt_lines	Receipt lines per policy (premium, taxes, EWT, discounts)	58
receipts	Official receipts (OR-) header: payer, amount, mode, status	58
receivable_credits	Return premium and cancellation credits applied to a bill, with the refund part and journal	4

Table	Description	Rows
receivable_participants	Per-insurer split of a co-insured bill: share, gross, commission, taxes, due to insurer	22
receivables	Premium bills (INV-) per policy / endorsement / renewal with balance and ageing	66
write_off_reasons	Write-off reasons with GL account and maximum amount	4

8.7 Remittance and insurer accounting

Table	Description	Rows
commission_debit_note_collections	Insurer payments against a debit note (cash, EWT, Form 2307)	2
commission_debit_note_lines	Policies / items on a debit note	6
commission_debit_notes	Commission debit notes (DN-) to insurers for direct-billed policies	4
direct_bill_client_payments	Client's premium payment made directly to the insurer on a direct-billed policy, with the insurer's receipt reference and proof; no journal is posted	6
direct_bill_items	Commission receivable items booked for direct-billed policies	6
insurer_refund_credits	Refunds due from insurers on returned premium already remitted; netted against the next remittance	0
remittance_allocations	Premium collected on a co-insured policy, split for remittance to each insurer	19
remittance_approvals	Multi-level approval requests with SLA and history	44
remittance_delegations	Approval delegations (period, transaction types, amount limit)	0
remittance_items	Remittance work items (settlements, adjustments, transfers, exceptions)	44
remittance_lines	Policies included in a remittance	52
remittances	Premium remittances / bills to insurers (REM-): gross, commission, net due, approval, settlement	22

8.8 Commission

Table	Description	Rows
commission_adjustments	Commission reversed or clawed back when premium is returned or a policy cancelled	1
commission_rates	Commission rate matrix: rate per insurer, product, line and	25

Table	Description	Rows
	policy type with effective dates	
commission_referrers	Referrers / sub-agents (no sign-in): hierarchy, WHT rate, bank account	2
commissions	Commission lines per policy / endorsement and referrer: accrual, eligibility, approval, payment	33

8.9 Claims

Table	Description	Rows
claim_field_changes	Field-level audit trail of claim edits	79
claim_history	Claim status history	35
claim_settlement_movements	Claim settlement cash: funds received from each insurer and payments to the claimant, with journal	2
claims	Claims: loss details, estimate, approved and settled amounts, handler, lifecycle status	8

8.10 Renewals

Table	Description	Rows
renewal_activities	Contact and follow-up activities on a renewal	37
renewal_batch_policies	Policies in a renewal batch and their notice status	0
renewal_batches	Batch renewal notice runs	0
renewal_notices	Renewal notices sent (stage, method, recipient, status)	11
renewal_quotes	Renewal quotations (loading, discount, variance)	1
renewals	Renewal cases of expiring policies (status, notices, contact, premium old / new)	13
winback_campaigns	Win-back campaigns for lapsed business	0

8.11 General ledger and period end

Table	Description	Rows
accounting_config_changes	Pending, approved or rejected changes to posting rules and account determination (maker-checker); a change takes effect only on approval by a different user	0
accounting_periods	Periods 1 to 12 and adjustment period 13 per fiscal year: dates and status (open, soft_closed, closed, locked)	13

Table	Description	Rows
bir_2307_certificates	BIR Form 2307 certificates issued and received, per payee and quarter	0
entry_matches	Open-item matching of debit and credit journal lines	0
fiscal_years	Fiscal years (FY2026): dates and status	1
gl_accounts	Chart of accounts (type, statement group, normal balance, open-item flag)	129
journal_lines	Journal lines: account, debit / credit, branch, department, client / policy tags	804
journal_vouchers	Journal vouchers (JV-): source, status, maker-checker, reversal / correction links	194
opening_balances	Opening balances per fiscal year and account: carried forward by the year-end close or loaded at go-live	0
period_close_checklist	Month-end checklist items (automatic or manual, severity)	12
period_close_entries	Journals created by a close run and their automatic reversal	0
period_close_run_checks	Checklist results of a close run and sign-off of manual items	60
period_close_runs	Month-end close runs (MEC-): steps, preparer, approval	5
period_status_history	Every change of an accounting period status, with source and user	5
posting_rule_lines	Lines of a posting rule: side, account or account role, amount key, split per co-insurer	146
posting_rules	Posting rule versions per business event (effective date, entry type, narration)	37
recurring_journal_runs	Journals generated from a recurring template per occurrence	0
recurring_journals	Recurring and accrual journal templates (frequency, lines, auto-post, auto-reverse)	0
tax_codes	Tax codes: VAT, expanded withholding with ATC, DST, LGT; rate and GL account	26
year_end_runs	Year-end close runs (YEC-): closing and transfer journals, net income, reversal	0

8.12 Bank and insurer reconciliation

Table	Description	Rows
bank_account_links	View: bank account masters with their GL cash account	view
bank_book_lines	View: posted journal lines on bank cash accounts, the book side of bank matching	view

Table	Description	Rows
bank_match_rules	Automatic matching rules (reference, amount-date, one-to-many, many-to-one)	6
bank_rec_match_items	Bank and book lines of a match	152
bank_rec_matches	Matches between bank lines and cash-account journal lines, with difference treatment	76
bank_reconciliation_history	Status history of a reconciliation	15
bank_reconciliations	Monthly bank reconciliation statements (BRC-): figures, preparer, approver	5
bank_statement_formats	Bank statement file layouts (columns, date format, sign convention)	4
bank_statement_lines	Statement lines (amount, reference, line hash), status and adjustment journal	78
bank_statements	Imported or keyed bank statements per bank account and period, with file hash	6
bank_transaction_types	Bank-side transaction types (charges, interest, direct credits) and their GL account role	7
insurer_statement_formats	Column mapping of an insurer's statement export (CSV or XLSX)	3
insurer_statement_lines	Lines of an insurer statement with their match to the broker's remittance line, debit note line or policy and the differences	17
insurer_statement_resolutions	How a statement difference, or a broker record missing on the statement, was settled: note or adjustment journal	9
insurer_statements	Imported insurer statement of account (ISR): premium remittance confirmation or commission statement, totals, sign-off	3

8.13 Credit control

Table	Description	Rows
client_credit_exceptions	Policies issued beyond a client's credit limit: exposure before and after, and Accounting's acknowledgement	0
collection_actions	Collection actions: calls, e-mails, commitments	5
collection_items	Collection follow-up items for open bills (commitment, escalation, assignee)	66
premium_instalment_plans	Instalment plan of a premium bill: frequency, number of instalments, first due date and	4

Table	Description	Rows
	down payment	
premium_instalments	Instalments of a plan: sequence, due date and amount	16
premium_warranty_actions	Premium warranty monitor actions: reminders, extension decisions and cancellation requests	6
premium_warranty_extensions	Requests to extend the premium payment warranty deadline of a policy (maker-checker)	0

8.14 Reinsurance

Table	Description	Rows
cessions	Cessions of policies to treaties / facultative reinsurers	3
reinsurance_bordereaux	Premium / claims bordereaux (entries JSONB, file)	0
reinsurance_exceptions	Reconciliation exceptions and resolution	0
reinsurance_reconciliations	Reinsurer statement reconciliations	0
reinsurance_recoveries	Claim recoveries from reinsurers	0
reinsurance_treaties	Treaties (type, capacity, share, retention, approval)	1
reinsurers	Reinsurers (rating, capacity, contact)	1

8.15 Incentives

Table	Description	Rows
incentive_calculations	Incentive calculation batches with maker-checker and payment	1
incentive_programs	Incentive programmes (metric, targets, tiers, eligibility)	1
incentive_results	Incentive results and payouts per participant	2

8.16 Security and audit

Table	Description	Rows
access_review_items	One user in an access review: the roles held, last sign-in and the reviewer's decision to keep or revoke	0
access_reviews	Periodic access review (recertification) campaign: scope, reviewer, due date and closure	0
audit_log	Who did what to which record, with before / after JSON and IP	1,515
authority_limits	Authority matrix: approval	24

Table	Description	Rows
	limit per role or per user and transaction type, effective once approved by another administrator	
authority_transaction_types	Transactions that need an approver and are limited by amount or percent (authority matrix rows)	9
login_history	Every sign-in attempt: user, IP, user agent, success, reason, method	26
password_history	Previous password hashes for the history rule (last N kept)	24
password_resets	One-time password reset codes (HMAC hash only), expiry and attempts	0
permissions	Permission codes read:<module>, write:<module> and approve:<area> granted to roles	64
refresh_tokens	Refresh-token register (jti, family, expiry, rotation / revocation reason)	14
role_permissions	Grant of permissions to roles	176
roles	Role catalogue: System Administrator, Sales & Marketing, Processing Team, Operations, Claims, Accounting, Accounting Manager and custom roles; a role may inherit another	7
sod_rules	Segregation-of-duties rules: pairs of roles one person should not hold together, with block or warn	5
user_delegations	Out-of-office delegation: the delegate may approve with the delegator's authority for the listed transaction types and dates	0
user_roles	Assignment of roles to users	13
users	User accounts: bcrypt password hash, status, lockout counter, 2FA (encrypted TOTP secret), token version	13

8.17 Configuration and schedules

Table	Description	Rows
app_settings	Configuration keys (JSONB value, group, label, type); every business parameter	404
currencies	Currencies (base flag, decimals, exchange rate)	5
document_numbering	Document number series: prefix, pattern, width, reset rule, start number	60
documents	Registry of stored files: storage key, name, type, size,	125

Table	Description	Rows
	owning entity, uploader	
email_outbox	Queued e-mails (to, subject, HTML body, status, attempts, error)	260
generated_reports	Generated report files (code, parameters, format, storage key, rows)	39
job_queue	Background work queue (renewal notice batches); status, progress, attempts	0
job_runs	Run history of scheduled and manual job runs (status, output, error)	0
master_records	Generic master records (JSONB data) for masters without their own table	295
master_types	Master screen registry: fields, storage table, keys of each configurable master	53
notifications	In-app notifications per user or per permission audience	497
report_definitions	Report catalogue (parameters, query, columns, roles, permission)	39
report_schedules	E-mailed report schedules (cron, format, recipients)	0
scheduled_jobs	Cron jobs (code, cron, handler, params, enabled, last status)	16
schema_migrations	Applied migration files	80
sequences	Document-number counters per series and reset period (year, fiscal year, month or ALL)	33

9. Document Sign-Off

Serial Number	Description	Owner	Status
1	No open items at the time of issue	iorta TechNXT	Closed

Sign Off Date	Signature	Approved By	Department & Project Role



Transforming Insurance with AI Innovation



10+
COUNTRIES
Global Presence



8
GLOBAL OFFICES
Strategically Located



11+
MARKETS SERVED
Across Continents



100%
COMMITMENT
To Excellence



MALAYSIA



INDIA



PHILIPPINES



THAILAND



VIETNAM



USA



ETHIOPIA



CAMBODIA



HONGKONG



SINGAPORE



Scan More Details