



Test Strategy

BrokerVerse OOTB product

Prepared by – **iorta TechNXT**

Version – **1.0**

Date – **04 October 2026**

TABLE OF CONTENTS

1. Document Control.....	3
2. Acronyms.....	3
3. Introduction.....	4
3.1 Purpose.....	4
3.2 Audience.....	5
3.3 Related documents.....	5
4. Test approach.....	6
4.1 Principles.....	6
4.2 Flow of testing across environments.....	6
5. Test levels.....	7
5.1 Unit and component tests (front end).....	8
5.2 API and integration tests (backend).....	8
5.3 System integration test.....	8
5.4 User acceptance test.....	9
5.5 Go-live rehearsal, environment comparison and masking verification....	9
6. Test types.....	10
7. Environments.....	12
7.1 Environment set by broker size.....	12
7.2 Environment rules for testing.....	12
8. Test data.....	13
9. Entry and exit criteria.....	14
10. Defect management.....	15
10.1 Severity and priority.....	15
10.2 Life cycle.....	15
10.3 Triage.....	15
11. Continuous integration gates.....	16
12. Roles and responsibilities.....	17
13. Tools.....	18
14. Risks.....	19
15. Document Sign-Off.....	20

1. Document Control

Date	Version	Author & Business Unit Info	Reviewed By & Business Unit Info	Approved By & Business Unit Info	Change History
04 October 2026	1.0.1	iorta TechNXT			Version 1.0.1: release figures aligned (UAT scenario of 433 steps, go-live rehearsal of 52 checks). Version 1.0: initial issue: test levels, test types, environments by broker size, test data and masking, entry and exit criteria, defect management, CI gates, roles, tools and risks

2. Acronyms

Acronym / Symbol	Definition / Meaning
OOTB	Out of the box
QA	Quality assurance
CI	Continuous integration
API	Application programming interface
SIT	System integration test
UAT	User acceptance test
Pre-Prod	Pre-production environment
Dev	Development environment
RTM	Requirements traceability matrix
IC	Insurance Commission
BIR	Bureau of Internal Revenue
NPC	National Privacy Commission

AMLC	Anti-Money Laundering Council
AML	Anti-money laundering
CFT	Countering the financing of terrorism
DPA	Data Privacy Act of 2012
PII	Personally identifiable information
WCAG	Web Content Accessibility Guidelines
CAB	Change advisory board
PSGC	Philippine Standard Geographic Code
CTPL	Compulsory third party liability
COC	Certificate of cover
EOPT	Ease of Paying Taxes Act
CAS	Computerized accounting system
EIS	Electronic Invoicing System
DAT	BIR validation data file

3. Introduction

3.1 Purpose

This strategy says how BrokerVerse OOTB is tested: by iorta TechNXT for every product release, and with the broker for every implementation. It sets the test levels, the test types, the environments and data used at each level, when a test phase may start and end, how defects are handled, which automated checks gate a release, and who does what.

The Test Plan applies this strategy to one broker implementation (scope per module, schedule, cycles, resources and sign-off). The Test Summary Report records the results of a test cycle. The test cases, the traceability to the process catalogue and the defect register are in the workbook BrokerVerse_Test_Cases.xlsx.

3.2 Audience

Reader	Uses this document to
QA lead and testers (iorta TechNXT)	Plan and run each level, keep the evidence, report results
Developers	Know which automated tests a change needs and which CI checks must pass
Broker project manager and key users	Know what they test in UAT, with which data, and what sign-off means
Delivery head and project manager	Plan the test phases and the go/no-go evidence
Broker Data Protection Officer and compliance officer	Check how personal data is protected in test environments and how regulatory functions are tested

3.3 Related documents


Document	Folder	What it adds
Test Plan	05_Delivery	The plan of an implementation: scope per module, schedule by phase, cycles, resources, suspension and sign-off
Test Cases workbook (with the Requirements Traceability sheet)	05_Delivery	Every test case; traceability from the process catalogue to test cases and automated test files; defect register
Test Summary Report	05_Delivery	Results of the latest cycle, counts per test file area and coverage by module
Implementation Approach and Plan	05_Delivery	Phases and timelines by broker size
Environment Strategy and Production Rollout	04_Onboarding_and_Go_Live	Environment roles, refresh, masking, release pipeline and cutover runbook
Data Migration and Cutover Plan	04_Onboarding_and_Go_Live	Mock loads, reconciliation and go/no-go
UAT and Go-Live Acceptance Certificates	03_Contracts	Sign-off forms and the severity scale of the SOW
Production Support Approach and Standards	06_Support	Severity P1 to P4 after go-live
docs/onboarding/UAT_SCRIPTS.md	Repository	UAT scripts per role, run by the key users

4. Test approach

4.1 Principles

- **Test the delivered product, configured.** BrokerVerse OOTB is configured, not customised. Each implementation tests the broker's configuration and data on the released code; it does not retest the product from scratch.
- **Automate every business rule.** A rule of the product (a premium tax, a posting, a maker-checker control, a regulatory deadline) is covered by an automated API test that runs on every change. A defect is fixed together with the test that would have found it.
- **Evidence or it did not happen.** A test case is Pass only with recorded evidence: the automated test that passed, the run log of a scripted scenario, a screen check or a signed UAT script. Without evidence it is Not Run.
- **Same build everywhere.** The artefacts built once by CI (web-<sha>, backend-<sha>) are the ones tested in SIT and UAT, rehearsed in Pre-Prod and deployed in Production.
- **Real personal data only where it must be.** Synthetic data in Dev and SIT; the broker's data in UAT only under production-grade protection; restored production copies masked before people without production access use them.
- **Regulatory functions are tested against the rule and confirmed by the broker.** iorta TechNXT tests that the system applies the delivered rule (for example the AMLC covered transaction threshold or the NPC 72-hour clock). The broker's compliance officer, tax adviser and Data Protection Officer confirm the values against the rules in force.

4.2 Flow of testing across environments



Test levels and the environments they run in

5. Test levels

Level	What it proves	Tool and location	Who	When
Unit and component (front end)	Screen logic: menu permissions, help routes, number and date formats, form checks, rule editors, theme engine and contrast	jest through craco: <code>brokerverse/src/**/*.test.js, *.test.jsx</code>	Developers	Every pull request and push (CI)
API and integration (backend)	Every business rule through the HTTP API against a real PostgreSQL 16 database: postings, approvals, permissions, regulatory rules, scheduled jobs, files produced	vitest with supertest: <code>backend/test/*.test.js</code> ; each file builds the schema from the migrations and seeds it (<code>test/helpers.js</code>)	Developers	Every pull request and push (CI); before each release tag
System integration (end to end)	The full broking cycle of a Philippine broker across roles, with one user per role, from set-up to month-end close and reports	<code>backend/scripts/uat-scenario.js</code> (433 steps in 12 phases on the merged release, run <code>log docs/e2e/UAT_SCENARIO_RUN.md</code>); life-cycle plan <code>docs/e2e/E2E_TEST_PLAN.md</code> ; screen check of every menu per role	iorta TechNXT QA	SIT cycles; each release candidate
User acceptance	The configured system works for the broker's people with the broker's data	<code>docs/onboarding/UAT_SCRIPTS.md</code> per role, plus broker scenarios agreed in discovery	Broker key users, supported by iorta TechNXT	UAT cycles 1 and 2
Go-live rehearsal	Configuration promotion, smoke test, transaction reset, migration with reconciliation, new and migrated business side by side, go-live lock	<code>npm run rehearsal:golive</code> (<code>backend/scripts/golive-rehearsal.js</code> , 52 checks, run <code>log docs/e2e/GOLIVE_REHEARSAL_RUN.md</code>)	iorta TechNXT migration lead and DevOps	In Pre-Prod before go-live; before each major release
Environment comparison	Configuration and masters of two environments are mirrored apart from environment-specific values	Master > Go-Live Data Load > Compare environments, or <code>npm run compare:environments</code> (exit code 0 mirrored, 1 differences, 2 could not run)	DevOps, System Administrator	After each promotion: Dev or SIT to UAT, UAT to Production, Pre-Prod against Production
Masking verification	A restored copy holds no unmasked e-mail address, mobile number or TIN	<code>npm run mask:data -- --verify-only</code> (exit code 4 when personal data is left) after <code>--execute</code>	DevOps, Data Protection Officer	Every copy of production data used outside Production
Cutover verification	Production after the final load: counts and totals reconciled, trial balance and receivables control account agreed, lock on	Go-Live Data Load reconciliation workbook; smoke test of the deployment checklist	Migration lead, Accounting Manager	Cutover weekend
Hypercare checks	First live receipts, remittances, bank imports, scheduled jobs and first month-end close	Production monitoring, job run history, month-end checklist	Project team, broker key users	Go-live to hypercare exit

5.1 Unit and component tests (front end)

Front-end tests run with `CI=true npx craco test --watchAll=false` in `brokerverse/`. They cover pure logic and small rendered components without a server: menu permissions and the enterprise side menu tree, `canOpen` for typed addresses, help routes from screen to manual section, My Work grouping and due logic, Product Configurator rule logic, integrations and compliance screens with mocked services, theme engine (CSS variables, WCAG contrast, sign-in picture), Philippine address fields, number, date and table alignment utilities.

5.2 API and integration tests (backend)

Backend tests run with `npx vitest run` in `backend/`, one file after another (`fileParallelism: false`) against the database in `TEST_DATABASE_URL` (default `brokerverse_test` on `127.0.0.1:5432`). Each file resets the schema, applies every migration and the reference seeds, starts the application in memory and signs in. A migration that does not apply on an empty database therefore fails the suite. Tests use real SQL, real posting rules and real permissions; external providers (SMS, CTPL authentication, insurer APIs, EIS, screening provider, payment gateways) are exercised through their built-in test modes.

Rules for developers:

1. Each new endpoint, posting rule, approval, setting or scheduled job has at least one positive and one negative test (wrong role, wrong state, missing data, maker equals checker).
2. A regulatory rule is tested at its boundary (for example PHP 500,000.00 covered transaction, 72 hours to notify the NPC, licence expiring within 90 days).
3. Money is asserted to the centavo, and every posting is asserted to balance.
4. A test never depends on another file or on the order of tests within another file.

5.3 System integration test

The scripted scenario `backend/scripts/uat-scenario.js` drives the public API with one persona per role and synthetic Philippine data over six months: personas and masters, retail package business, corporate non-package business with requests for quotation and co-insurance, billing and collection, endorsements, renewals and claims, remittances, commission and petty cash, reinsurance and incentives, bank and insurer reconciliation, month-end close, reports and dashboards. It can be pointed at any environment (`API_BASE`), is repeatable (`UAT_SEED`) and writes a run log. It is completed by:

- the life-cycle plan `docs/e2e/E2E_TEST_PLAN.md` (one motor policy through its whole life);
- a screen check of every menu screen for the administrator and for each role user (access granted and refused, console errors, failed requests, clipped content);
- the broker-specific flows agreed in discovery (lines, placement journeys, integrations switched on).

5.4 User acceptance test

Key users run the UAT scripts of their role with the broker's own products, insurers and data, in UAT. iorta TechNXT supports, logs defects and re-tests. The scripts cover the delivered roles: System Administrator, Sales & Marketing, Processing Team, Operations, Claims, Accounting, Accounting Manager and Compliance Officer (AML/CFT), and the cross-role scripts for compliance registers, BIR, distribution, integrations and branding.

5.5 Go-live rehearsal, environment comparison and masking verification

The go-live rehearsal (`npm run rehearsal:golive`) runs between a SOURCE environment (UAT) and a TARGET going live (Pre-Prod restored from Production, or Production before go-live). It needs `CONFIRM_RESET=yes` and refuses to run on a TARGET whose go-live lock is on unless explicitly allowed. A run passes when every check passes; the run log is kept as go/no-go evidence.

The environment comparison downloads the configuration workbook with current data from both sides and compares them on the natural keys of the workbench. Expected differences (secrets, addresses, numbering counters unless `INCLUDE_NUMBERING=yes`, environment name) are reported as environment-specific and do not fail the comparison.

The masking tool masks a copy in one transaction and then scans every text and JSON column. It refuses a database marked as production. Production is registered once with `--register-production`; a copy restored from it is re-marked and masked in one step with `--remark-copy --confirm-database=<copy> --restore-source=<backup>`. The verification scan must end with exit code 0 before testers sign in. Procedure: docs/onboarding/DATA_MASKING.md.

6. Test types

Type	Scope	How it is tested	Evidence
Functional	Every screen and process of the roles	Test cases with steps and expected results; API tests; UAT scripts	Test Cases workbook; vitest and jest results
Negative and validation	Wrong input, wrong state, missing permission, duplicates	API tests for each refusal (status code and message); screen checks for field messages	vitest results
Regulatory	IC (licences, insurer authority, complaints under RA 11765, annual statement, production report, premium held in trust), BIR (premium taxes, 2307, 0619-E, 1601-EQ, 1604-E, 2551Q, DAT files, EOPT invoices, CAS books, EIS), NPC (consent, data subject requests, breach register and 72-hour clock, masking by role, encryption), AMLC (customer due diligence, risk rating, EDD, screening, covered and suspicious transactions, report files), CTPL (COC series and authentication)	API tests at the boundary of each rule; each test case carries its regulatory reference; values confirmed by the broker's compliance officer, tax adviser and DPO	Regulatory reference column of the Test Cases workbook; Philippine Regulatory Compliance Matrix
Accounting	Every posting rule balances; sub-ledgers tie to the ledger; period controls	API tests on journals and balances; month-end checklist in the UAT scenario	vitest results; trial balance at the end of the scenario
Role-based access and segregation of duties	Deny by default on every endpoint; maker and checker different users; authority matrix limits; masking by view:pii	Permission probes per role in API tests; screen check per role user; typed addresses refused	role-access, access-control, user-access tests; screen check
Security	Authentication, tokens, password policy, logout, two-step verification, rate limits, injection probes, uploads, headers, secrets at start-up, dependency audit	API tests (security, hardening); npm audit in CI (high and critical fail the build); external penetration test before the first production go-live	CI audit job; penetration test report
Performance	Response times and month-end volumes	Timings observed in the functional runs; load test with the broker's concurrent users and volumes on a production-sized server before go-live	Load test report (go-live condition)
Data migration	Configuration and migration workbooks: validation, errors	Go-live workbench tests; mock loads; rehearsal	Reconciliation workbook of each load

Type	Scope	How it is tested	Evidence
	workbook, load, reload without duplicates, reconciliation of counts and totals, opening balances		
Integration	E-mail outbox, bank statement import, payment links, bank payment files, SMS and Viber, CTPL authentication and LTO feed, insurer API, screening provider, EIS	Test modes of each connector in API tests and SIT; live test per provider during onboarding	Outbox and inbox records; provider acceptance
Accessibility and contrast	Text contrast of every theme (WCAG 2.1 contrast on buttons, header and table header); keyboard access to the help panel (F1) and menu search (/)	Contrast checks of the theme engine (front end) and of the branding API (themes failing contrast are refused or flagged); manual keyboard check in UAT	jest and vitest results; UAT script
Usability and layout	Screens at 1440 x 900 without clipped content or horizontal scroll; skeleton loading while data loads	Screen sweep per role	Screen check log
Regression	Everything already delivered	Full backend and front-end suites on every change; UAT scenario on each release candidate; re-test of fixed defects	CI history; Test Summary Report
Installation and deployment	Migrations forward-only, seeds, smoke test after deploy, rollback	deploy.yml smoke test (health, version equals the commit, sign-in page); automatic rollback on failure; rollback.yml	Pipeline run

7. Environments

7.1 Environment set by broker size

The environment set follows the Environment Strategy and Production Rollout Plan.

Environment	Small broker	Medium broker	Large broker	Testing done there
Dev	Own instance	Own instance	Own instance	Unit and API tests by developers; configuration build and SIT for small and medium brokers
SIT	Done in Dev	Done in Dev	Own instance, separate from UAT	Configuration build, SIT cycles, mock loads 1 and 2
UAT	Own instance	Own instance	Own instance	UAT cycles 1 and 2, mock loads with the broker's data, training
Pre-Prod	Temporary	Temporary	Temporary	Go-live rehearsal (last mock load), comparison with Production, rehearsal of each major release
Production	Own instance	Own instance	Own instance with high availability	Smoke test, cutover verification, hypercare checks
CI service database	Every size	Every size	Every size	Full backend suite on PostgreSQL 16 for each pull request and push

7.2 Environment rules for testing

- Each environment shows its name (APP_ENVIRONMENT) in About BrokerVerse (Help panel) and on exported workbooks, so evidence states where it was taken.
- E-mail sending (notification.email_enabled) is off in Dev and SIT, and in UAT until the broker agrees the recipients. Copies made with the masking tool have it switched off.
- Connectors stay in test mode outside Production unless a provider test is planned.
- The transaction reset (CONFIRM_RESET=yes npm run reset:transactions -- --execute) is used between cycles and before mock loads; it refuses to run while golive.locked is on and is never run in Production after go-live.
- Refreshes follow the refresh policy of the Environment Strategy and are recorded in the environment sheet.

8. Test data

Data	Source	Used in	Rules
Reference data	Migrations and seeds: Philippine masters (PSGC 2Q 2026 regions, provinces, cities and municipalities, barangays; ZIP codes; banks; government ID types; salutations; holidays; IC insurer list), chart of accounts, tax codes, motor tariff, roles	Every environment	Never edited by tests; changes come by migration
Demo data	SEED_SAMPLE_DATA=true	Dev, training	Never in Production (SEED_SAMPLE_DATA=false)
Synthetic test data	backend/scripts/uat-scenario.js (fictional Philippine names, TINs, mobile numbers and addresses; seed brokerverse-uat)	Dev, SIT, release candidates	Repeatable; load once on a database without business records
Automated test data	Created by each test file on a fresh schema	CI, developer machines	Isolated per file
Broker extracts	The broker's old system, through the configuration and migration workbooks	SIT (large brokers), UAT, Pre-Prod	Treated as production data: access limited, environment protected as Production
Masked copies	Production backup restored, then npm run mask:data with --remark-copy and --execute, then --verify-only	Pre-Prod used by testers without production access, training copies, support reproduction	Deterministic pseudonyms (secret MASK_SALT, never stored); passwords reset, sessions ended, outbox emptied, e-mail off; files purged or replaced; verification exit code 0

No real client, payee or employee data may be used in Dev, in SIT for a small or medium broker, in CI, in screenshots attached to defects, or in training material. A defect raised from UAT or Production quotes record numbers and request IDs, not personal details.

9. Entry and exit criteria

Level	Entry criteria	Exit criteria
Unit and API (per change)	Pull request opened	CI green: backend lint and full suite, front-end lint, tests and build, dependency audit without high or critical finding
SIT	Release candidate tag deployed; configuration of the cycle loaded; persona users created; SIT test cases mapped in the Test Cases workbook; environment comparison against the source environment run	Every end-to-end flow passed (UAT scenario without failed step, life-cycle plan passed); no open severity 1 or 2 defect; screen check without refused request for granted screens; SIT exit report signed
UAT cycle 1	SIT exit; configuration promoted to UAT and compared; mock load reconciled; key users trained and holding one user per role; UAT scripts issued	Every UAT script executed; defects logged with severity
UAT cycle 2 and sign-off	Fixes of cycle 1 deployed by the pipeline; re-test list agreed	All UAT scripts passed or accepted with a workaround; no open severity 1 or 2 defect; severity 3 and 4 items listed with owner and date; UAT Sign-off Certificate signed
Go-live rehearsal	UAT sign-off; Pre-Prod restored from a production backup; masked if testers without production access take part; release tag equal to the one going live	Every rehearsal check passed; reconciliation agreed; environment comparison shows environment-specific differences only; timings recorded for the cutover plan
Cutover verification	Go decision; final extract received	Counts and totals agree with the old system (default: exact); trial balance and receivables control account agreed; go-live lock on; smoke test passed
Hypercare	Go-live	No open severity 1 or 2 issue; first month-end close completed; handover accepted

10. Defect management


10.1 Severity and priority

Severity follows the scale of the Implementation SOW and the UAT certificates; after go-live a defect becomes a support ticket with the matching production priority.

Severity	Meaning	Production priority	Release rule
1 Critical	A core process cannot be completed, financial postings are wrong, or personal data is exposed, with no workaround	P1	Blocks exit of SIT, UAT and go-live
2 High	A core process is seriously degraded with no acceptable workaround	P2	Blocks exit of SIT, UAT and go-live
3 Medium	A function fails and a workaround exists	P3	Listed in the certificate with owner and target
4 Low	Cosmetic issue, wording or documentation	P4	Listed with owner and target

Priority (High, Medium, Low) orders the fixing work within a severity, for example a severity 3 defect on the month-end close before a severity 3 defect on a report rarely used.

10.2 Life cycle



Defect life cycle

Each defect is recorded on the sheet Defects and Observations of the Test Cases workbook (or the project's tracker with the same fields): ID (BV-DEF-nnn for a defect, BV-OBS-nnn for an observation), title, module, severity, status, type (Defect, Gap, Observation), description with steps, the request ID from the error message, environment and build, workaround, target and linked test cases. A fix is accepted only with an automated test that fails before the fix and passes after it, and with the re-test of the linked test cases on a deployed build.

10.3 Triage

The QA lead and the development lead triage new defects daily during SIT and UAT, with the broker's project manager for UAT defects. A disputed severity goes to the project managers, then to the steering committee.

11. Continuous integration gates

`.github/workflows/ci.yml` runs on every pull request and every push, and on release tags:

Job	Steps	Gate
Backend lint and tests	Node.js 22; npm ci; npm run lint; npm test against a postgres:16 service database brokerverse_test	Required check
Front-end lint, tests and build	npm ci --legacy-peer-deps; npm run lint; npx craco test --watchAll=false with CI=true; environment-neutral production build; build output checks (no %PUBLIC_URL%, loads /env-config.js, no API address in the bundle)	Required check
Backend release artefact	deploy/package-backend.sh packages backend-<sha>	Required for deployment
Dependency audit	npm audit --omit=dev --audit-level=high for backend and front end	High and critical findings fail
Deploy to Dev, UAT, Production	deploy.yml with the artefacts of the same run: push to brokerverse-platform to Dev; tag vX.Y.Z-rc.N to UAT; tag vX.Y.Z to Production; SIT and Pre-Prod by manual promotion	Runs only after all four jobs pass; required reviewers per environment; two reviewers for Production

Each deployment takes a backup first (Pre-Prod and Production), applies migrations and seeds, switches the release and runs the smoke test (`/api/health`, `/api/version` equal to the deployed commit, sign-in page). A failed smoke test rolls back automatically. `rollback.yml` rolls back by hand.

12. Roles and responsibilities

Role	Responsibilities in testing
iorta TechNXT QA lead	Owns this strategy and the Test Plan; maintains the Test Cases workbook and the traceability; runs SIT; triages defects; writes the Test Summary Report; recommends exit
iorta TechNXT testers	Execute SIT test cases and screen checks; support UAT; re-test fixes; keep evidence
iorta TechNXT developers	Write unit and API tests with each change; keep CI green; fix defects with a test
iorta TechNXT DevOps lead	Environments, pipeline, refreshes, masking of copies, environment comparison, go-live rehearsal runs
iorta TechNXT migration lead	Mock loads, reconciliation, rehearsal, cutover verification
iorta TechNXT project manager	Schedule, resources, status reporting, entry and exit decisions with the broker
Broker project manager	UAT schedule, testers, defect priorities, sign-off coordination
Broker key users (one per team)	Run UAT scripts and broker scenarios; confirm results; sign UAT for their process
Broker System Administrator	Users and roles for testing; configuration checks; environment comparison review
Broker Accounting Manager	Accounting, tax and reconciliation results; cutover sign-off of balances
Broker compliance officer, Data Protection Officer, tax adviser	Confirm regulatory values and outputs (AML settings, AMLC file layout, IC registers and forms, BIR forms and DAT files, breach criteria, masking)
Steering committee	Resolves disputes; go/no-go decision

13. Tools

Need	Tool
Backend tests	vitest and supertest, PostgreSQL 16
Front-end tests	jest through craco, React Testing Library
End-to-end scenario	backend/scripts/uat-scenario.js (Node.js)
Go-live rehearsal	npm run rehearsal:golive
Environment comparison	Master > Go-Live Data Load > Compare environments; npm run compare:environments
Transaction reset	npm run reset:transactions (dry run, then --execute)
Data masking	npm run mask:data (--register-production, --remark-copy, --execute, --verify-only)
Screen checks	Chromium at 1440 x 900, one user per role
CI and deployment	GitHub Actions: ci.yml, deploy.yml, rollback.yml
Test management	BrokerVerse_Test_Cases.xlsx (test cases, traceability, requirements traceability, defects), or the project tracker with the same fields
Evidence	Run logs in docs/e2e, CI run history, signed UAT scripts, reconciliation workbooks

14. Risks

Risk	Effect	Mitigation
Key users not available for UAT	UAT late or shallow	Named key users at 50% during UAT in the SOW; UAT dates fixed at kick-off
Broker data arrives late or dirty	Mock loads fail; UAT on incomplete data	Data request at mobilisation; errors workbook per load; at least two mock loads before the rehearsal
Real personal data in a lower environment	Data Privacy Act breach	Masking tool with verification; environment protected as Production once broker data is loaded; breach register
Regulatory value wrong for the broker (threshold, form layout, ATC)	Wrong filing	Values confirmed in writing by the compliance officer, tax adviser and DPO; regulatory reference on each test case
Third-party provider not ready (SMTP, SMS, CTPL authentication, insurer API, banks, EIS)	Integration cases blocked	Connectors tested in test mode; live tests planned per provider; Blocked status with reason
No load test before go-live	Slow month-end in Production	Load test on a production-sized server is a go-live condition
No external penetration test	Unknown vulnerabilities	Penetration test before the first production go-live; findings triaged as defects
Configuration drift between environments	UAT result not valid for Production	Promotion with the configuration workbook; environment comparison after each promotion and before go-live
Features merged late (work in progress)	Untested scope	A feature joins a release only with its automated tests in CI and its test cases in the workbook; otherwise it stays out of the release

15. Document Sign-Off

Serial Number	Description	Owner	Status
1	Load test on a production-sized server and external penetration test not yet run; both are go-live conditions of the first broker	iorta TechNXT QA lead	Open

Sign Off Date	Signature	Approved By	Department & Project Role



Insurance technology for the Philippines



10+

COUNTRIES

Global Presence



8

GLOBAL OFFICES

Strategically Located



11+

MARKETS SERVED

Across Continents



100%

COMMITMENT

To Excellence



MALAYSIA



INDIA



PHILIPPINES



THAILAND



VIETNAM



USA



ETHIOPIA



CAMBODIA



HONGKONG



SINGAPORE



Scan More Details