



Business Continuity and Disaster Recovery Plan

BrokerVerse OOTB

Prepared by – **iorta TechNXT**

Version – **1.0**

Date – **03 October 2026**

TABLE OF CONTENTS

1. Document Control.....	4
2. Acronyms.....	4
3. Introduction.....	5
3.1 Purpose.....	5
3.2 Sources and labels.....	5
3.3 Scope.....	5
4. What must be recovered.....	7
4.1 Critical business processes.....	7
4.2 Service tiers.....	7
5. Recovery objectives.....	8
5.1 Objectives by scenario.....	8
5.2 Objectives by hosting option.....	8
5.3 Availability target.....	9
6. Backup scheme.....	10
6.1 Backups.....	10
6.2 Why the encryption key matters.....	10
7. Restore procedures.....	11
7.1 Common steps for every restore.....	11
7.2 Business checks after a restore.....	11
7.3 Database: point-in-time recovery.....	11
7.4 Database: snapshot or logical dump.....	12
7.5 File store.....	12
7.6 Region or site loss.....	12
7.7 Front end and secrets.....	12
7.8 Release rollback.....	13
8. Scenarios.....	14
8.1 Region or data centre outage.....	14
8.2 Database corruption or wrong mass change.....	14
8.3 Ransomware or destructive attack.....	14
8.4 Key person loss.....	15
8.5 Vendor exit or failure.....	15
8.6 Third-party outages.....	15
9. Manual workarounds while the system is down.....	16
10. Roles and responsibilities.....	17
11. Communication.....	18
12. DR drills and evidence.....	19

12.1 Drill calendar.....	19
12.2 Evidence kept.....	19
13. Maintaining this plan.....	20
14. Document Sign-Off.....	21

1. Document Control

Date	Version	Author & Business Unit Info	Reviewed By & Business Unit Info	Approved By & Business Unit Info	Change History
03 October 2026	1.0	iorta TechNXT			Initial issue

2. Acronyms

Acronym / Symbol	Definition / Meaning
OOTB	Out of the box
BCP	Business continuity plan
DR	Disaster recovery
RTO	Recovery time objective
RPO	Recovery point objective
PITR	Point-in-time recovery
WAL	Write-ahead log
AZ	Availability zone
DNS	Domain Name System
CDN	Content delivery network
PHT	Philippine time (UTC+8)
DPO	Data Protection Officer
NPC	National Privacy Commission
IC	Insurance Commission
BIR	Bureau of Internal Revenue
OR	Official receipt
CAB	Change advisory board
L1, L2, L3	Support levels 1, 2 and 3
P1	Severity 1 (critical)

3. Introduction

3.1 Purpose

This plan sets out how BrokerVerse OOTB and the broking work that depends on it continue, or are restored, after a disruption: the failure of a server, a database or a whole hosting region, a corrupted database, a ransomware attack, the loss of a key person, or the end of the relationship with iorta TechNXT. It gives the recovery objectives per hosting option, the backup scheme, the restore procedures, the drill plan and the evidence kept, the roles and the communication.

It is written for the broker's management, IT head, Accounting Manager and DPO, and for the iorta TechNXT support and DevOps teams.

3.2 Sources and labels

The recovery objectives and the backup scheme come from the Architecture, Infrastructure, Security and Data Privacy document (chapter on high availability, backup and recovery), the Solution Architecture documents 07 (high availability), 08 (RTO and RPO) and 09 (backup and recovery), the Hosting and Infrastructure Services Agreement and the Production Support Approach and Standards.

- **Recommended** marks a procedure or a value that iorta TechNXT advises and that is not built into the code or the deployment package.
- **[to confirm]** marks a fact that must be completed for each broker (names, telephone numbers, partner details) or decided by iorta TechNXT management.

Nothing in the code sets an RTO or RPO. The objectives in this plan become binding only when the broker accepts them in the Order Form and the environment is provisioned to meet them.

3.3 Scope

In scope	Out of scope
The BrokerVerse production environment: web	The broker's own office network, devices,

In scope	Out of scope
front end, API instances, PostgreSQL database, file store, secrets, scheduled jobs and outgoing e-mail	telephony and premises
The DR environment or cross-region backups, where the Order Form includes them	The insurers', banks' and payment gateways' own systems
The iorta TechNXT support and engineering service for BrokerVerse	The broker's corporate business continuity plan, which this plan feeds into
Manual workarounds for the broker's critical business processes while the system is down	Recovery of data deleted by users beyond what the backups hold

4. What must be recovered

4.1 Critical business processes

The broker ranks its processes at the start of the engagement. The ranking below is the default proposal.

Rank	Process	Maximum tolerable outage (proposal)	Why
1	Official receipts and payment capture	1 business day	Clients pay daily; receipts must follow the BIR rules on the day of payment
2	Policy issuance, including motor and CTPL	1 business day	Clients need cover and the certificate of cover to register vehicles
3	Claims notification and status	1 business day	Loss advice to insurers is time-bound
4	Remittance to insurers	3 business days	Remittance is due on the insurer's terms; a short delay is usually acceptable if insurers are told
5	Endorsements, renewals and quotations	3 business days	Renewal notices run 60, 30 and 15 days before expiry, so a short outage does not cause a lapse
6	Month-end close, bank and insurer reconciliation, BIR working papers	5 business days, except around filing deadlines	Close and filing dates are known in advance
7	Reports, dashboards, incentives, reinsurance	5 business days	Not needed for the day's transactions

Recommended: Avoid releases and DR drills in the last three business days of the month and in the week before a BIR filing deadline.

4.2 Service tiers

Tier	Content	Where it lives	Recovered from
1	Core transactions: clients, policies, bills, receipts, journals, remittances, claims, the audit trail	PostgreSQL	Standby, PITR, snapshots, logical dumps
2	Documents: KYC images, claim photos, uploaded statements, generated PDFs	File store at UPLOAD_DIR	File store backups
3	Derived data: notifications, e-mail outbox, generated reports	PostgreSQL and file store	Recreated by the jobs; not restored on their own
4	Code and configuration as code: front-end build, API image, deployment scripts	Git repository, image registry, front-end bucket	Rebuilt from the release tag
Keys	JWT_SECRET, DATA_ENCRYPTION_KEY, database and SMTP credentials, payment gateway keys	Secret store	Versioned secret store and the sealed escrow copy

Settings, number series, posting rules and master data live in the database (Tier 1), so a database restore brings the configuration back with the data.

5. Recovery objectives

5.1 Objectives by scenario

These are the objectives proposed in architecture document 08 and written into the Hosting and Infrastructure Services Agreement. They assume the recommended production topology: at least two API instances in two availability zones, a managed PostgreSQL database with a standby, and a shared file store.

Scenario	RPO	RTO
API instance failure	0	Under 5 minutes
Availability zone failure	0	Under 15 minutes
Database instance failure (with standby)	0	Under 15 minutes
Logical corruption or wrong mass change	15 minutes or less	4 hours or less
Loss of uploaded files	24 hours or less	4 hours or less
Regional or site outage	24 hours or less	24 hours or less (warm standby: 8 hours)
Front end deleted	0	Under 1 hour
Loss of secrets	Not applicable	Under 1 hour

5.2 Objectives by hosting option

The same objectives apply on every option only if the option is built to the recommended topology. The table shows what each option delivers as offered.

Scenario	A: AWS Singapore	B: Azure Singapore	C: Philippine partner	Broker-hosted
API instance or AZ failure	RPO 0, RTO under 15 minutes (two ECS tasks in two AZs)	RPO 0, RTO under 15 minutes (two replicas across zones)	RPO 0, RTO under 15 minutes (two API VMs behind the proxy pair)	As the broker builds it
Database failure	RPO 0, RTO under 15 minutes (RDS Multi-AZ)	RPO 0, RTO under 15 minutes (zone-redundant Flexible Server)	RPO 0 with synchronous replica; RTO under 15 minutes with Patroni, about 1 hour with a manual runbook [to confirm with the partner]	As the broker builds it
Logical corruption	RPO 15 minutes (5 achievable), RTO 4 hours, by PITR	Same, by Flexible Server PITR	RPO 15 minutes with WAL archiving (pgBackRest or WAL-G); RTO 4 hours	Depends on the broker's WAL archiving; daily dump alone gives RPO 24 hours
Region or site outage, pilot light	RPO 24 hours, RTO 24 hours from cross-region copies	Same, from geo-redundant backup storage	Same, from the off-site copy in a second Philippine site	Broker's own DR site
Region or site outage, warm standby	RPO 24 hours or better, RTO 8 hours	Same	Same	Broker's own DR site

- **When iorta TechNXT hosts**, the price includes production, one UAT environment, daily backups, monitoring and patching. A DR environment or cross-region backups are included for the Enterprise size and are an Order Form option for the other sizes. Without them, the regional objectives do not apply and a region or site loss means rebuilding production from the last backup held in the same region, if it survives.

- **The demo deployment** on one EC2 host with PM2 has no redundancy and does not meet these objectives. It is for demonstration and UAT only.
- **When the broker hosts**, the broker owns the objectives. iorta TechNXT supplies this plan, the deployment guide and support at day rates.

5.3 Availability target

Hosted production has an availability target of 99.5% a month, measured in service hours (08:00 to 18:00 PHT, Monday to Friday, except Philippine regular holidays) by an external health check every 5 minutes, excluding planned maintenance. A DR invocation counts as unavailability unless the outage is excluded under the Hosting Agreement.

6. Backup scheme

6.1 Backups

Backup	Frequency	Retention	Location
Automated database backups with PITR	Continuous; backup window 02:00 to 03:00 PHT	35 days	Same region, encrypted
Database snapshots	Daily	35 days	Same region
Monthly snapshot copy	Monthly	12 months; yearly copy of year-end records 10 years if the broker instructs	Second region or second Philippine site
Snapshot before each release with database changes, before go-live imports and before each year-end close	On event	At least 30 days	Same region
Logical dump (pg_dump -Fc)	Monthly	12 months	Write-once storage
File store	Daily; weekly copy to the second region or site	Daily 35 days; monthly 12 months	Same region and second region or site
Front-end bucket versions	Each publish	90 days	Same region
API container images	Each release	Last 10 releases	Registry, replicated to the recovery region
Secrets	On change	All versions	Secret store with a sealed escrow copy under dual control

Note: The application contains no backup automation. Backups are configured in the hosting platform (AWS Backup and RDS, Azure Backup and Flexible Server, pgBackRest or WAL-G and the backup server under option C). The `deploy/README.md` checklist requires daily snapshots kept at least 30 days, a backup of the upload volume and of `DATA_ENCRYPTION_KEY`, and one restore test before go-live.

6.2 Why the encryption key matters

`DATA_ENCRYPTION_KEY` encrypts the two-step verification secrets. A database restored without the same key works, but every user with two-step verification must have it reset by an administrator and enrol again. No business data is lost. The key is therefore backed up with the database: versioned in the secret store, with a sealed escrow copy held under dual control by the broker and iorta TechNXT.

`JWT_SECRET` signs sessions and file links. Restoring with a new value only signs every user out.

7. Restore procedures

Detailed command-level steps are in architecture document 09. The procedures below are the order of work and the checks; L3 engineering carries them out, L2 coordinates and the broker confirms.

7.1 Common steps for every restore

1. Declare the incident as P1 and open the bridge (chapter on communication).
2. Stop writes: set the API to zero instances or block traffic at the load balancer, and set `SCHEDULER_ENABLED=false` on any instance that stays up, so jobs do not run against a half-restored database.
3. Take a snapshot of the current state, even if damaged, for evidence and for the root-cause analysis.
4. Agree the recovery point with the broker's Accounting Manager: the last time before the damage, in PHT.
5. Restore (sections below).
6. Start one API instance. On start it checks the configuration, applies any pending migration under the advisory lock and runs the idempotent seed; `/api/health` answers 200 when ready.
7. Check `GET /api/version`: expected commit, no pending migration.
8. Run the smoke test of `deploy/README.md` section 4 and the business checks below.
9. Re-enable the scheduler on one instance, scale out, open traffic.
10. Tell users what was restored to which point and what must be re-entered.

7.2 Business checks after a restore

Check	Who
Last official receipt, payment voucher and journal voucher numbers match the broker's paper or bank evidence	Accounting
Trial balance is balanced; sub-ledger tie-out of the month-end checklist passes	Accounting Manager
Last policies, endorsements and claims entered before the recovery point are present	Processing Team, Claims
Document Numbering counters are past the last numbers used; no number is reused	System Administrator
A sample of KYC images and claim documents opens	Operations
E-mail Outbox has no flood of old messages queued for resend	System Administrator
Sign-in works for a user with two-step verification	System Administrator

Recommended: Transactions entered after the recovery point are re-entered from source documents. Official receipt numbers issued in that window are re-entered with the same numbers where the series allows, or recorded with a cross-reference memo approved by the Accounting Manager, so the BIR sequence stays explainable.

7.3 Database: point-in-time recovery

Used for logical corruption, a wrong mass change or a bad release.

1. Restore the managed database to a new instance at the agreed recovery point (RDS or Flexible Server PITR; pgBackRest or WAL-G restore under option C).
2. Point DATABASE_URL of one API instance at the new instance; keep the old instance stopped, not deleted, until the root-cause analysis is done.
3. Common steps 6 to 10.

7.4 Database: snapshot or logical dump

Used when PITR is not available (beyond 35 days, or a broker-hosted installation with daily dumps only).

1. Restore the snapshot to a new instance, or create an empty PostgreSQL 16 database with time zone Asia/Manila and run pg_restore of the dump.
2. Compare row counts of the main tables with the dump's own record.
3. Common steps 6 to 10.

7.5 File store

1. Restore the file store backup of the agreed day to the same path, or to a new volume mounted at UPLOAD_DIR on every API instance.
2. Files uploaded after that backup are listed from the database (records whose stored file is missing) and re-uploaded by users from their originals.

7.6 Region or site loss

1. The Incident Manager and the broker's IT head decide to invoke DR (chapter on roles).
2. In the recovery region or second site: restore the database from the latest cross-region copy, the file store from its latest copy, pull the API image of the running release from the replicated registry and the secrets from the secret store or the escrow copy.
3. Publish the front-end build of the release (or restore the bucket copy) and point DNS or the CDN origin to the recovery site.
4. Common steps 6 to 10. Update PUBLIC_BASE_URL and CORS_ORIGINS if the address changes, and re-register payment gateway webhook addresses if they change.
5. Fail back to the primary region in a planned window once it is stable, using the same procedure in reverse with a fresh backup.

7.7 Front end and secrets

- Front end: re-run the deployment workflow on the release commit, or restore the previous bucket object versions, then invalidate the CDN.
- Secrets: restore the previous version from the secret store; if the store is lost, open the sealed escrow copy under dual control and record who opened it.

7.8 Release rollback

Migrations only add to the schema, so the previous API image runs on the newer schema. Redeploy the previous image tag and front-end build. Restore the pre-release snapshot only if data written by the new release must be undone.

8. Scenarios

8.1 Region or data centre outage

Item	Response
Trigger	Provider status page or partner notice; health checks failing from outside; no AZ in the region usable
First hour	P1 declared; provider's estimate of restoration obtained; broker told
Decision	Invoke DR if the provider gives no restoration within 4 hours or no estimate at all, or earlier if a critical deadline is at risk [threshold to confirm with the broker]
Recovery	Region or site loss procedure; objectives 24 hours (pilot light) or 8 hours (warm standby)
Without a DR option	Wait for the provider; continuity relies on the manual workarounds below
Data residency	A recovery region outside the Philippines is a transfer the broker must have documented in advance. Under option C both sites are in the Philippines

8.2 Database corruption or wrong mass change

Item	Response
Trigger	Users report wrong balances or missing records; trial balance out of balance; failed migration; a mass update by script went wrong
Containment	Stop writes at once; find the first wrong transaction with Master > Audit Trail, audit_log and request ids
Recovery	PITR to just before the first wrong change; RPO 15 minutes, RTO 4 hours
Alternative	For a small, well-identified error, a reviewed data correction under change control instead of a restore (Production Support Approach, data corrections)

8.3 Ransomware or destructive attack

Item	Response
Trigger	Encrypted or deleted files, unknown administrator activity, ransom note, alarm on mass deletion
Containment	Isolate the environment; revoke cloud and database credentials; rotate JWT_SECRET to sign every user out; disable affected accounts; block addresses at the WAF
Evidence	Preserve logs, login_history, audit_log, monitoring data and a snapshot before any clean-up
Recovery	Rebuild clean infrastructure from code; restore from a point before the compromise, preferring the write-once monthly dump and the cross-region copies, which an attacker with production credentials cannot alter
Before reopening	Root cause found and closed; all secrets rotated; administrator passwords and two-step enrolments reset
Privacy	Treated as a possible personal data breach: notice to the broker's DPO within [24] hours of discovery; the DPO decides on notification to the NPC within 72 hours
Ransom	iorta TechNXT does not negotiate or pay on the broker's behalf; any decision is the broker's, with legal advice

Recommended: Keep backup deletion rights in a separate account or role from production administration, and use object lock or write-once storage for the monthly dumps.

8.4 Key person loss

Risk	Control
Loss of the iorta TechNXT engineer who knows a module	Code standards and the Technical Reference; module pattern shared by every module; knowledge base of known errors; at least two engineers trained on each module [to confirm named backups]
Loss of the iorta TechNXT DevOps engineer	Deployment as code in the repository and deploy;; runbooks in architecture document 09; cloud access through named roles, never a personal account; break-glass access under dual control
Loss of the broker's System Administrator	A second System Administrator named at go-live; user manual and role guides; iorta TechNXT L2 covers in the meantime
Loss of the broker's Accounting Manager	A second user with the Accounting Manager role, so maker-checker approvals can continue
Loss of the person holding the escrow copy	Two named holders on each side, recorded in the secret escrow register

8.5 Vendor exit or failure

Item	Response
Planned exit (end of contract)	Exit and Transition Plan: data returned in an agreed format, transition assistance, deletion within 30 days after the broker confirms the export, certificate of deletion
iorta TechNXT unable to continue	Broker-hosted installation: the broker already holds the database, files and keys. Hosted installation: the broker asks for an immediate export under the Exit and Transition Plan; with a perpetual licence and the optional source code escrow, the release events of the Escrow Agreement apply
Technology	React, Node.js 22 and PostgreSQL 16, with no proprietary middleware; any competent team in the Philippines can operate it with the Technical Reference and deployment guide
Hosting provider exit	The application runs on any option without code change; moving between AWS, Azure and a local partner is a planned migration from backups

8.6 Third-party outages

Dependency	Effect	Workaround
SMTP mailbox	E-mails wait in the E-mail Outbox; transactions continue	Resend from the outbox when the mailbox is back; send urgent documents from a normal mailbox
Payment gateway	Payment links fail; no automatic receipts	Clients pay by bank transfer or cheque; Accounting records the receipt
Bank portal	Transfers to insurers cannot be executed	Approved remittances wait; cheques where the insurer accepts them
Insurer systems	No effect on BrokerVerse (exchange is by file and e-mail)	Not applicable

9. Manual workarounds while the system is down

Process	Workaround	Catch-up after recovery
Collecting premium	Issue pre-numbered manual official receipts from the BIR-registered manual series kept for this purpose [to confirm the broker holds one]	Record each receipt in BrokerVerse with the manual receipt reference
Motor policy and CTPL	Request the policy or certificate directly from the insurer's own portal or underwriter	Record the issued policy (Record Issued Policy journey) with the insurer's number
Claims notification	E-mail the preliminary loss advice to the insurer from a normal mailbox	Register the claim with the actual notification date
Remittance	Defer by the insurer's terms; tell insurers of the delay	Run the remittance as normal
Client enquiries	Use the last daily exported reports (production register, SOA, renewal list)	Not applicable

Recommended: The Daily reports job (05:00 PHT) generates the scheduled daily reports (production register, collections, claims position). Keep the last day's copies, with a premium receivable SOA and the renewal list, outside the system (for example on the broker's file server) so staff can answer clients during an outage.

10. Roles and responsibilities

Role	Who	Responsibilities in a disruption
Incident Manager	iorta TechNXT support manager [name to confirm]	Declares P1, runs the bridge, keeps the timeline, decides with the broker's IT head on DR invocation
Recovery lead	iorta TechNXT DevOps lead [name to confirm]	Carries out restores and DR, records times and recovery points
Application lead	iorta TechNXT L3 engineer [name to confirm]	Checks migrations, data integrity, jobs and the application after restore
Broker IT head	[to confirm]	Approves DR invocation, recovery point and reopening; coordinates the broker's network and devices
Broker Accounting Manager	[to confirm]	Agrees the recovery point; runs the financial checks; approves re-entry and receipt series treatment
Broker System Administrator	[to confirm]	User communication, two-step resets, numbering checks, outbox
Broker DPO	[to confirm]	Decides on NPC and data subject notification when personal data may be affected
Broker sponsor	[to confirm]	Decides on communication to insurers, clients and regulators

11. Communication

When	Who informs	Whom	How
Within 30 minutes of a P1	iorta TechNXT Incident Manager	Broker System Administrator and IT head	Telephone, then e-mail
Every hour during a P1	Incident Manager	Broker IT head and sponsor	E-mail status update
Outage over 1 hour	Broker System Administrator	All users	E-mail or chat; banner on the intranet
Outage affecting receipts or issuance over 1 business day	Broker sponsor	Insurers concerned	E-mail from the broker
Possible personal data breach	iorta TechNXT	Broker DPO	Within [24] hours of discovery, written
Regulator notification, where required	Broker DPO or compliance officer	NPC; IC if the broker's compliance officer decides it is required	As the rules require
Recovery complete	Incident Manager	Broker IT head and System Administrator	E-mail with recovery point, data to re-enter and next steps
After the incident	iorta TechNXT	Broker	RCA draft within 5 business days

Contact list (to be completed for each broker and reviewed every six months):

Role	Name	Mobile	E-mail
iorta TechNXT service desk (P1 line)	[to confirm]	[to confirm]	[to confirm]
iorta TechNXT Incident Manager	[to confirm]	[to confirm]	[to confirm]
iorta TechNXT DevOps lead	[to confirm]	[to confirm]	[to confirm]
Broker IT head	[to confirm]	[to confirm]	[to confirm]
Broker System Administrator and deputy	[to confirm]	[to confirm]	[to confirm]
Broker Accounting Manager	[to confirm]	[to confirm]	[to confirm]
Broker DPO	[to confirm]	[to confirm]	[to confirm]
Hosting provider or partner support	[to confirm]	[to confirm]	[to confirm]

12. DR drills and evidence

12.1 Drill calendar

Test	Frequency	Success criteria
Backup jobs succeeded; latest restorable time within 15 minutes	Daily	Recorded in the daily health check
PITR to a new instance, API started against it in isolation, smoke test	Quarterly and before go-live	Restore completed within 4 hours; smoke test passed
File restore with a sample of documents	Quarterly	Sample opens
Logical dump restore into a clean PostgreSQL 16, row counts compared	Twice a year	Counts equal
Secret escrow check under dual control	Yearly	Escrow key matches the live key (compared by hash, not by reading it out)
Tabletop exercise of a region loss and of ransomware with the broker	Yearly	Roles, contacts and decision points confirmed; actions logged
Full recovery in the recovery region or site	Every two years (where a DR option is in the Order Form)	Achieved RTO and RPO recorded against the objectives

Recommended: Hold the first tabletop before go-live, in the cutover rehearsal week, so the contact list and the decision thresholds are agreed before they are needed.

12.2 Evidence kept

Evidence	Content	Kept by	Retention
Restore test record	Date, operator, backup used, recovery point, start and end times, achieved RTO and RPO, checks run, issues	iorta TechNXT DevOps; copy to the broker	3 years (recommended)
Tabletop minutes	Scenario, participants, decisions, gaps, actions with owners and dates	iorta TechNXT support manager	3 years
DR exercise report	Timeline, achieved objectives, deviations, lessons, plan updates	iorta TechNXT; signed by the broker's IT head	3 years
Escrow register	Holders, envelope or vault reference, dates opened and resealed	Broker and iorta TechNXT jointly	Life of the contract
Monthly service report	Backup status and test results of the month	Both	Life of the contract

A failed test is raised as a P2 incident and fixed before the next scheduled test. Results are available to the broker's auditors and, on request, to regulators.

13. Maintaining this plan

- Reviewed yearly, after each DR exercise, after any P1 that needed a restore, and when the hosting option, topology or contacts change.
- Changes are approved by the broker's IT head and the iorta TechNXT support manager and recorded in the document control table.
- The contact list is checked every six months and at each change of key personnel.

14. Document Sign-Off

Serial Number	Description	Owner	Status
1	Recovery objectives become binding only when accepted in the Order Form; DR environment, partner details and contact lists to be completed per broker	iorta TechNXT	Open

Sign Off Date	Signature	Approved By	Department & Project Role



Insurance technology for the Philippines



10+

COUNTRIES

Global Presence



8

GLOBAL OFFICES

Strategically Located



11+

MARKETS SERVED

Across Continents



100%

COMMITMENT

To Excellence



MALAYSIA



INDIA



PHILIPPINES



THAILAND



VIETNAM



USA



ETHIOPIA



CAMBODIA



HONGKONG



SINGAPORE



Scan More Details