

Normalization By Evaluation of Types in $R\omega\mu$

Alex Hubers

Department of Computer Science

The University of Iowa

Iowa City, Iowa, USA

alexander-hubers@uiowa.edu

Conference'17, Washington, DC, USA

2025. ACM ISBN 978-x-xxxx-xxxx-x/YYYY/MM

<https://doi.org/10.1145/nnnnnnnn.nnnnnnn>

Abstract

Hubers et al. [2024] introduce $R\omega\mu$, a higher-order row calculus, but do not describe any metatheory of its type equivalence relation nor of type reduction. $R\omega\mu$ extends System $F\omega\mu$ with rows, records, variants, row mapping, and a novel *row complement* operator. This paper shows not only that $R\omega\mu$ types enjoy normal forms, but formalizes the normalization-by-evaluation (NbE) of types in the interactive proof assistant Agda. We prove that our normalization algorithm is stable, sound and complete with respect to the type equivalence relation. Consequently, type conversion in $R\omega\mu$ is decidable.

1 Introduction

Hubers and Morris [2023] introduce an expressive higher-order row calculus called $R\omega$, which relies on implicit type reductions according to a directed type equivalence relation. Despite this reliance, the authors only provide a proof of *semantic soundness* that well-typed terms inhabit the denotations of well-kinded types. The authors do not characterize the shape of types in normal form, nor prove that the denoted types are sound and complete with respect to the equivalence relation. Hubers et al. [2024] extends the $R\omega$ language to $R\omega\mu$, which is $R\omega$ with recursive types, term-level recursion, and a novel *row complement* operator. The authors similarly extend the proof of semantic soundness, and fail to describe any metatheory of the equivalence relation.

1.1 The need for type normalization

$R\omega$ and $R\omega\mu$ each have a type conversion rule. The rule below states that the term M can have its type converted from τ to v provided a proof that τ and v are equivalent. (For now, let us split environments into kinding environments Δ , evidence environments Φ , and typing environments Γ .)

$$(\text{T-CONV}) \frac{\Delta; \Phi; \Gamma \vdash M : \tau \quad \Delta \vdash \tau = v : \star}{\Delta; \Phi; \Gamma \vdash M : v}$$

Conversion rules can complicate metatheory in an intrinsic setting. Hubers and Morris [2023]; Hubers et al. [2024] each provide an intrinsic semantics and do not provide a procedure to decide type checking or type equivalence. Proofs of type conversion are thus necessarily embedded into the term language. This has a number of consequences:

1. Users of the surface language are forced to write conversion rules by hand.
2. Decidability of type checking now rests upon the decidability of type conversion.
3. Term-level conversions can block β -reduction if a conversion is in the head position of an application.
4. Term-level conversions can block proofs of progress. Let M have type τ , let pf be a proof that $\tau = v$, and consider the term $\text{conv } M \text{ pf}$; ideally, one would expect this to reduce to M (we've changed nothing semantically about the term). But this breaks type preservation, as $\text{conv } M \text{ pf}$ (at type v) has stepped to a term at type τ .
5. Inversion of the typing judgment $\Delta; \Phi; \Gamma \vdash M : \tau$ —that is, induction over derivations—must consider the possibility that this derivation was constructed via conversion. But conversion from what type? Proofs by induction over derivations often thus get stuck.

All of these complications may be avoided provided a sound and complete normalization algorithm. In such a case, all types are reduced to normal forms, where syntactic comparison is enough to decide equivalence. In effect, the proofs of all conversions have collapsed to just the reflexive case, and so term-level conversions can safely be removed.

1.2 Contributions

This paper offers the following as contributions:

1. A normalization procedure for the directed $R\omega\mu$ type equivalence relation;
2. a semantics of the type-level *row complement* operator;
3. proofs of soundness and completeness of normalization with respect to type equivalence; and
4. a complete mechanization in Agda of $R\omega\mu$ and the claimed metatheoretic results.

Type variables $\alpha \in \mathcal{A}$ Labels $\ell \in \mathcal{L}$

Kinds $\kappa ::= \star \mid \mathbf{L} \mid \mathbf{R}[\kappa] \mid \kappa \rightarrow \kappa$

Predicates $\pi, \psi ::= \rho \lesssim \rho \mid \rho \odot \rho \sim \rho$

Types $\mathcal{T} \ni \phi, \tau, \rho, \xi ::= \alpha \mid T \mid \tau \rightarrow \tau \mid \pi \Rightarrow \tau$
 $\mid \forall \alpha : \kappa. \tau \mid \lambda \alpha : \kappa. \tau \mid \tau \tau$
 $\mid \{\xi_i \triangleright \tau_i\}_{i \in 0 \dots m} \mid \ell \mid \# \tau$
 $\mid \phi \$ \rho \mid \rho \setminus \rho$

Type constants $T ::= \Pi^{(\kappa)} \mid \Sigma^{(\kappa)} \mid \mu$

Figure 1. Syntax

2 The $R\omega\mu$ calculus

Figure 1 describes the syntax of kinds, predicates, and types in $R\omega\mu$.

Labels (i.e., record field and variant constructor names) live at the type level, and are classified by kind \mathbf{L} . Rows of kind κ are classified by $\mathbf{R}[\kappa]$. When possible, we use ϕ for type functions, ρ for row types, and ξ for label types. Singleton types $\# \tau$ are used to cast label-kinded types to types at kind \star . $\phi \$ \rho$ maps the type operator ϕ across a row ρ . In practice, we often leave the map operator implicit, using kind information to infer the presence of maps. We define a families of Π and Σ constructors, describing record and variants at various kinds; in practice, we can determine the kind annotation from context. μ builds isorecursive types. Row literals (or, synonymously, *simple rows*) are sequences of labeled types $\xi_i \triangleright \tau_i$. We write $0 \dots m$ to denote the set of naturals up to (but not including) m . We will frequently use ε to denote the empty row.

The type $\pi \Rightarrow \tau$ denotes a qualified type. In essence, the predicate π restricts the instantiation of the type variables in τ . Our predicates capture relationships among rows: $\rho_1 \lesssim \rho_2$ means that ρ_1 is *contained* in ρ_2 , and $\rho_1 \odot \rho_2 \sim \rho_3$ means that ρ_1 and ρ_2 can be *combined* to give ρ_3 .

Finally, $R\omega\mu$ introduces a novel *row complement* operator $\rho_2 \setminus \rho_1$, analogous to a set complement for rows. The complement $\rho_2 \setminus \rho_1$ intuitively means the row obtained by removing any label-type associations in ρ_1 from ρ_2 . In practice, the type $\rho_2 \setminus \rho_1$ is meaningful only when we know that $\rho_1 \lesssim \rho_2$, however constraining the formation of row complements to just this case introduces an unpleasant dependency between predicate evidence and type well-formedness. In practice, it is easy enough to totally define the complement operator on all rows, even without the containment of one by the other.

2.1 Type computation in $R\omega\mu$

$R\omega$ and $R\omega\mu$ are quite expressive languages, with succinct and readable types. To some extent, this magic relies on implicit type application, implicit maps, and unresolved type reduction. Let us demonstrate with a few examples.

2.1.1 Reifying variants, reflecting records. The following $R\omega$ terms witness the duality of records and variants.

$\text{reify} : \forall z : \mathbf{R}[\star], t : \star.$
 $(\Sigma z \rightarrow t) \rightarrow \Pi (z \rightarrow t)$
 $\text{reflect} : \forall z : \mathbf{R}[\star], t : \star.$
 $\Pi (z \rightarrow t) \rightarrow \Sigma z \rightarrow t$

The term *reify* transforms a variant eliminator into a record of individual eliminators; the term *reflect* transforms a record of individual eliminators into a variant eliminator. The syntax above is precise, but arguably so because it hides some latent computation. In particular, what does $z \rightarrow t$ mean? The variable z is at kind $\mathbf{R}[\star]$ and t at kind \star , so this is an implicit map. Rewriting explicitly yields:

$\text{reify} : \forall z : \mathbf{R}[\star], t : \star.$
 $(\Sigma z \rightarrow t) \rightarrow \Pi ((\lambda s. s \rightarrow t) \$ z)$
 $\text{reflect} : \forall z : \mathbf{R}[\star], t : \star.$
 $\Pi ((\lambda s. s \rightarrow t) \$ z) \rightarrow \Sigma z \rightarrow t$

The writing of the former rather than the latter is permitted because the corresponding types are convertible.

2.1.2 Deriving functoriality. We can simulate the deriving of functor typeclass instances: given a record of *fmap* instances at type $\Pi (\text{Functor } z)$, we can give a *Functor* instance for Σz .

type *Functor* : $(\star \rightarrow \star) \rightarrow \star$
type *Functor* = $\lambda f. \forall a b. (a \rightarrow b) \rightarrow f a \rightarrow f b$
fmapS : $\forall z : \mathbf{R}[\star \rightarrow \star].$
 $\Pi (\text{Functor } z) \rightarrow \text{Functor } (\Sigma z)$

When we consider the kind of *Functor* z it becomes apparent that this is another implicit map. Let us write it explicitly and also expand the *Functor* type synonym:

fmapS : $\forall z : \mathbf{R}[\star \rightarrow \star].$
 $\Pi ((\lambda f. \forall a b.$
 $(a \rightarrow b) \rightarrow f a \rightarrow f b) \$ z) \rightarrow$
 $(\lambda f. \forall a b. (a \rightarrow b) \rightarrow f a \rightarrow f b) (\Sigma z)$

which reduces further to:

fmapS : $\forall z : \mathbf{R}[\star \rightarrow \star].$
 $\Pi ((\lambda f. \forall a b.$
 $(a \rightarrow b) \rightarrow f a \rightarrow f b) \$ z) \rightarrow$
 $\forall a b. (a \rightarrow b) \rightarrow (\Sigma z) a \rightarrow (\Sigma z) b$

Intuitively, we suspect that $(\Sigma z) a$ means "the variant of type constructors z applied to the type variable a ". Let us make this intent obvious. First, define a "left-mapping" helper $_??_$ with kind $\mathbf{R}[\star \rightarrow \star] \rightarrow \star \rightarrow \mathbf{R}[\star]$ as so:

$r ?? t = (\lambda f. f t) \$ r$

Now the type of *fmapS* is:

fmapS : $\forall z : \mathbf{R}[\star \rightarrow \star].$
 $\Pi ((\lambda f. \forall a b.$
 $(a \rightarrow b) \rightarrow f a \rightarrow f b) \$ z) \rightarrow$
 $\forall a b. (a \rightarrow b) \rightarrow \Sigma (z ?? a) \rightarrow \Sigma (z ?? b)$

And we have what appears to be a normal form. Of course, the type is more interesting when applied to a real value for z . Suppose z is a functor for naturals, $\{ 'Z \triangleright \text{const Unit}, 'S \triangleright \lambda x. x \}$. Then a first pass yields:

```
fmapS { 'Z ▷ const Unit, 'S ▷ λx. x } :
  Π ((λf. ∀ a b. (a → b) → f a → f b)
    $ { 'Z ▷ const Unit, 'S ▷ λx. x } →
    ∀ a b. (a → b) →
    Σ ({ 'Z ▷ const Unit, 'S ▷ λx. x } ?? a) →
    Σ ({ 'Z ▷ const Unit, 'S ▷ λx. x } ?? b)
```

How do we reduce from here? Regarding the first input, we suspect we would like a record of `fmap` instances for both the `'Z` and `'S` functors. We further intuit that the sub-term $\{ 'Z \triangleright \text{const Unit}, 'S \triangleright \lambda x. x \} ?? a$ really ought to mean "the row with `'Z` mapped to `Unit` and `'S` mapped to `a`". Performing the remaining reductions yields:

```
fmapS { 'Z ▷ const Unit, 'S ▷ λx. x } :
  Π { 'Z ▷ ∀ a b. (a → b) → Unit → Unit,
    'S ▷ ∀ a b. (a → b) → a → b } →
  ∀ a b. (a → b) →
  Σ { 'Z ▷ Unit, 'S ▷ a } →
  Σ { 'Z ▷ Unit, 'S ▷ b }
```

The point we arrive at is that the precision of some $R\omega$ and $R\omega\mu$ types are supplanted quite effectively by type equivalence. Further, as values are passed to type-operators, the shapes of the types incur forms of reduction beyond simple β -reduction. In this case, we must map type operators over rows; we next consider the reduction of row complements.

2.1.3 Desugaring Booleans. Consider a desugaring of Booleans to Church encodings:

```
type BoolF = { 'T ▷ const Unit,
               'F ▷ const Unit,
               'If ▷ λx. Triple x x x }
type LamF  = { 'Lam ▷ Id,
               'App ▷ λx. Pair x x,
               'Var ▷ const Nat }
desugar : ∀ y. BoolF ≤ y, LamF ≤ y \ BoolF ⇒
  Π (Functor (y \ BoolF)) →
  μ (Σ y) →
  μ (Σ (y \ BoolF))
```

We will ignore the already stated complications that arise from subexpressions such as `Functor (y \ BoolF)` and skip to the step in which we tell `desugar` what particular row y it operates over. Here we know it must have at least the `BoolF` and `LamF` constructors. Let us try something like the following AST, using $\#$ as pseudonotation for row concatenation to save space.

```
type AST = BoolF # LamF #
  { 'Lit ▷ const Int, 'Add ▷ λx. Pair x x }
desugar AST : BoolF ≤ AST, LamF ≤ (AST \ BoolF) ⇒
  Π (Functor (AST \ BoolF)) →
  μ (Σ y) → μ (Σ (AST \ BoolF))
```

When `desugar` is passed AST for z , the inherent computation in the complement operator is made more obvious. What should `AST \ BoolF` reduce to? Intuitively, we suspect the following to hold:

```
AST \ BoolF = { 'Lit ▷ const Int,
                'Add ▷ λx. Pair x x,
                'Lam ▷ Id,
                'App ▷ λx. Pair x x,
                'Var ▷ const Nat }
```

But this computation must be realized, just as (analogously) λ -redexes are realized by β -reduction.

3 Type Equivalence & Reduction

We define reduction on types $\tau \rightarrow_{\mathcal{T}} \tau'$ by directing the type equivalence judgment $\Delta \vdash \tau = \tau' : \kappa$ from left to right, defined in Figure 2. We omit conversion and closure rules.

3.1 Normal forms

The syntax of normal types is given in Figure 3.

Type variables	$\alpha \in \mathcal{A}$	Labels	$\ell \in \mathcal{L}$
Ground Kinds	$\gamma ::= \star \mid L$		
Kinds	$\kappa ::= \gamma \mid \kappa \rightarrow \kappa \mid R[\kappa]$		
Row Literals	$\hat{\rho} \ni \hat{\rho} ::= \{ \ell_i \triangleright \hat{\tau}_i \}_{i \in 0 \dots m}$		
Neutral Types	$n ::= \alpha \mid n \hat{\tau}$		
Normal Types	$\hat{\mathcal{T}} \ni \hat{\tau}, \hat{\phi} ::= n \mid \hat{\phi} \$ n \mid \hat{\rho} \mid \hat{\pi} \Rightarrow \hat{\tau}$		
	$\mid \forall \alpha : \kappa. \hat{\tau} \mid \lambda \alpha : \kappa. \hat{\tau}$		
	$\mid n \triangleright \hat{\tau} \mid \ell \mid \# \hat{\tau} \mid \hat{\tau} \setminus \hat{\tau}$		
	$\mid \Pi(\star) \hat{\tau} \mid \Sigma(\star) \hat{\tau}$		

$$\begin{array}{c}
\boxed{\Delta \vdash_{nf} \hat{\tau} : \kappa} \quad \boxed{\Delta \vdash_{ne} n : \kappa} \\
(K_{nf-NE}) \frac{\Delta \vdash_{ne} n : \gamma}{\Delta \vdash_{nf} n : \gamma} \quad (K_{nf-\setminus}) \frac{\Delta \vdash_{nf} \hat{\tau}_1 : R[\kappa] \quad \hat{\tau}_1 \notin \hat{\rho} \text{ or } \hat{\tau}_2 \notin \hat{\rho}}{\Delta \vdash_{nf} \hat{\tau}_2 \setminus \hat{\tau}_1 : R[\kappa]} \\
(K_{nf-\rightarrow}) \frac{\Delta \vdash_{ne} n : L \quad \Delta \vdash_{nf} \hat{\tau} : \kappa}{\Delta \vdash_{nf} n \triangleright \hat{\tau} : R[\kappa]}
\end{array}$$

Figure 3. Normal type forms

Normalization reduces applications and maps except when a variable blocks computation, which we represent as a *neutral type*. A neutral type is either a variable or a spine of applications with a variable in head position. We distinguish ground kinds γ from functional and row kinds, as neutral types may only be promoted to normal type at ground kind (rule (K_{nf-NE})): neutral types n at functional kind must η -expand to have an outer-most λ -binding (e.g., to $\lambda x. n x$), and neutral types at row kind are expanded to an inert map by the identity function (e.g., to $(\lambda x. x) \$ n$). Likewise, repeated maps are necessarily composed according to rule $(E-MAP_{\circ})$:

$$\begin{array}{c}
\boxed{\Delta \vdash \tau = \tau : \kappa} \\
(E-\beta) \frac{\Delta \vdash (\lambda \alpha : \kappa. \tau) v : \kappa'}{\Delta \vdash (\lambda \alpha : \kappa. \tau) v = \tau[v/\alpha] : \kappa'} \\
(E-LIFT\Xi) \frac{\Delta \vdash \rho : R[\kappa_1 \rightarrow \kappa_2] \quad \Delta \vdash \tau : \kappa}{\Delta \vdash (\Xi^{(\kappa_1 \rightarrow \kappa_2)} \rho) \tau = \Xi^{(\kappa_2)} (\rho ?? \tau) : \kappa_2} (\Xi \in \{\Pi, \Sigma\}) \\
\text{where } \rho ?? \tau = (\lambda f. f \tau) \$ \rho \\
(E-\backslash) \frac{\Delta \vdash \{\xi_i \triangleright \tau_i\}_{i \in 0 \dots n} : R[\kappa] \quad \Delta \vdash \{\xi_j \triangleright \tau_j\}_{j \in 0 \dots m} : R[\kappa]}{\Delta \vdash \{\xi_i \triangleright \tau_i\} \setminus \{\xi_j \triangleright \tau_j\} = \text{subtract } \{\xi_i \triangleright \tau_i\} \{\xi_j \triangleright \tau_j\} : R[\kappa]} \\
(E-MAP) \frac{\Delta \vdash \phi : \kappa_1 \rightarrow \kappa_2 \quad \Delta \vdash \{\xi_i \triangleright \tau_i\}_{i \in 0 \dots n} : R[\kappa_1]}{\Delta \vdash \phi \$ \{\xi_i \triangleright \tau_i\}_{i \in 0 \dots n} = \{\xi_i \triangleright \phi \tau_i\}_{i \in 0 \dots n} : R[\kappa_2]} \\
(E-MAP_{id}) \frac{\Delta \vdash \rho : R[\kappa]}{\Delta \vdash \rho = (\lambda \alpha. \alpha) \$ \rho : R[\kappa]} \\
(E-MAP_{\circ}) \frac{\Delta \vdash \phi_1 : \kappa_2 \rightarrow \kappa_3 \quad \Delta \vdash \phi_2 : \kappa_1 \rightarrow \kappa_2 \quad \Delta \vdash \rho : R[\kappa_1]}{\Delta \vdash \phi_1 \$ (\phi_2 \$ \rho) = (\phi_1 \circ \phi_2) \$ \rho : \kappa_3} \\
\text{where } \phi_1 \circ \phi_2 = \lambda \alpha. \phi_1 (\phi_2 \alpha) \\
(E-MAP_{\setminus}) \frac{\Delta \vdash \phi : \kappa_1 \rightarrow \kappa_2 \quad \Delta \vdash \rho_i : R[\kappa_1]}{\Delta \vdash \phi \$ (\rho_2 \setminus \rho_1) = \phi \$ \rho_2 \setminus \phi \$ \rho_1 : \kappa_2} \\
(E-\Xi) \frac{\Delta \vdash \rho : R[R[\kappa]]}{\Delta \vdash \Xi^{(R[\kappa])} \rho = \Xi^{(\kappa)} \$ \rho : R[\kappa]} (\Xi \in \{\Pi, \Sigma\}) \\
(E-\eta) \frac{\Delta \vdash \phi : \kappa_1 \rightarrow \kappa_2}{\Delta \vdash \phi = \lambda \alpha : \kappa_1. \phi \alpha : \kappa_1 \rightarrow \kappa_2} \\
\boxed{\text{subtract } \rho \rho} \\
\text{subtract } \varepsilon \rho = \varepsilon \\
\text{subtract } \rho \varepsilon = \rho \\
\text{subtract } \{\ell \triangleright \tau, \rho\} \{\ell' \triangleright \tau', \rho'\} = \\
\begin{cases} \text{subtract } \rho \rho' & \text{if } \ell = \ell' \text{ and } \tau = \tau' \\ \{\ell \triangleright \tau, \text{subtract } \rho \{\ell' \triangleright \tau', \rho'\}\} & \text{if } \ell < \ell' \\ \text{subtract } \{\ell \triangleright \tau, \rho\} \rho' & \text{if } \ell > \ell' \end{cases}
\end{array}$$

Figure 2. Type equivalence

For example, $\phi_1 \$ (\phi_2 \$ n)$ normalizes by letting ϕ_1 and ϕ_2 compose into $((\phi_1 \circ \phi_2) \$ n)$. By consequence of η -expansion, records and variants need only be formed at kind \star . This means a type such as $\Pi(\ell \triangleright \lambda x. x)$ must reduce to $\lambda x. \Pi(\ell \triangleright x)$, η -expanding its binder over the Π . Nested applications of Π and Σ are also "pushed in" by rule (E- Ξ). For example, the type $\Pi \Sigma (\ell_1 \triangleright (\ell_2 \triangleright \tau))$ has Σ mapped over the outer row, reducing to $\Pi(\ell_1 \triangleright \Sigma(\ell_2 \triangleright \tau))$.

The syntax $n \triangleright \hat{\tau}$ separates singleton rows with variable labels from row literals $\hat{\rho}$ with literal labels; rule $(\kappa_{nf} \triangleright)$ ensures that n is a well-kinded neutral label. A row is otherwise

an inert map $\phi \$ n$ or the complement of two rows $\hat{\tau}_2 \setminus \hat{\tau}_1$. Observe that the complement of two row literals should compute according to rule (E- \backslash); we thus require in the kinding of normal row complements $(\kappa_{nf} \setminus)$ that one (or both) rows are not literal so that the computation is indeed inert. The remaining normal type syntax does not differ meaningfully from the type syntax; the remaining kinding rules for the judgments $\Delta \vdash_{nf} \hat{\tau} : \kappa$ and $\Delta \vdash_{ne} n : \kappa$ are as expected.

3.2 Metatheory

3.2.1 Canonicity of normal types. The normal type syntax is pleasantly partitioned by kind. Due to η -expansion of functional variables, arrow kinded types are canonically λ -bound. A normal type at kind $R[\kappa]$ is either an inert map $\hat{\phi}^\star n$, a variable-labeled row $(n \triangleright \hat{\tau})$, the complement of two rows $\hat{\tau}_2 \setminus \hat{\tau}_1$, or a row literal $\hat{\rho}$. The first three cases necessarily have neutral types (recall that at least one of the two rows in a complement is not a row literal). Hence rows in empty contexts are canonically literal. Likewise, the only types with label kind in empty contexts are label literals; recall that we disallowed the formation of Π and Σ at kind $R[L] \rightarrow L$, thereby disallowing non-literal labels such as $\Delta \vdash \Pi \varepsilon : L$ or $\Delta \vdash \Pi(\ell_1 \triangleright \ell_2) : L$.

Theorem 3.1 (Canonicity). *Let $\hat{\tau} \in \hat{\mathcal{T}}$.*

- If $\Delta \vdash_{nf} \hat{\tau} : (\kappa_1 \rightarrow \kappa_2)$ then $\hat{\tau} = \lambda \alpha : \kappa_1. \hat{v}$;
- if $\varepsilon \vdash_{nf} \hat{\tau} : R[\kappa]$ then $\hat{\tau} = \{\ell_i \triangleright \hat{\tau}_i\}_{i \in 0 \dots m}$.
- If $\varepsilon \vdash_{nf} \hat{\tau} : L$, then $\hat{\tau} = \ell$.

3.2.2 Normalization.

Theorem 3.2 (Normalization). *There exists a normalization function $\Downarrow : \mathcal{T} \rightarrow \hat{\mathcal{T}}$ that maps well-kinded types to well-kinded normal forms.*

\Downarrow is realized in Agda intrinsically as a function from derivations of $\Delta \vdash \tau : \kappa$ to derivations of $\Delta \vdash_{nf} \hat{\tau} : \kappa$. Conversely, we witness the inclusion $\hat{\mathcal{T}} \subseteq \mathcal{T}$ as an embedding $\Uparrow : \hat{\mathcal{T}} \rightarrow \mathcal{T}$, which casts derivations of $\Delta \vdash_{nf} \hat{\tau} : \kappa$ back to a derivation of $\Delta \vdash \tau : \kappa$; we omit this function and its use in the following claims, as it is effectively the identity function (modulo tags).

The following properties confirm that \Downarrow behaves as a normalization function ought to. The first property, *stability*, asserts that normal forms cannot be further normalized. Stability implies *idempotency* and *surjectivity*.

Theorem 3.3 (Properties of normalization).

- (*Stability*) for all $\hat{\tau} \in \hat{\mathcal{T}}$, $\Downarrow \hat{\tau} = \hat{\tau}$.
- (*Idempotency*) For all $\tau \in \mathcal{T}$, $\Downarrow (\Downarrow \tau) = \Downarrow \tau$.
- (*Surjectivity*) For all $\hat{\tau} \in \hat{\mathcal{T}}$, there exists $v \in \mathcal{T}$ such that $\hat{\tau} = \Downarrow v$.

We now show that \Downarrow indeed reduces faithfully according to the equivalence relation $\Delta \vdash \tau = \tau : \kappa$. Completeness of

normalization states that equivalent types normalize to the same form.

Theorem 3.4 (Completeness). *For well-kinded $\tau, v \in \mathcal{T}$ at kind κ , If $\Delta \vdash \tau = v : \kappa$ then $\Downarrow \tau = \Downarrow v$.*

Soundness of normalization states that every type is equivalent to its normalization.

Theorem 3.5 (Soundness). *For well-kinded $\tau \in \mathcal{T}$ at kind κ , there exists a derivation that $\Delta \vdash \tau = \Downarrow \tau : \kappa$. Equivalently, if $\Downarrow \tau = \Downarrow v$, then $\Delta \vdash \tau = v : \kappa$.*

Soundness and completeness together imply, as desired, that $\tau \longrightarrow_{\mathcal{T}} \tau'$ iff $\Downarrow \tau = \Downarrow \tau'$.

3.2.3 Decidability of type conversion. Equivalence of normal types is syntactically decidable which, in conjunction with soundness and completeness, is sufficient to show that $R\omega\mu$'s equivalence relation is decidable.

Theorem 3.6 (Decidability). *Given well-kinded $\tau, v \in \mathcal{T}$ at kind κ , the judgment $\Delta \vdash \tau = v : \kappa$ either (i) has a derivation or (ii) has no derivation.*

4 Normalization by Evaluation (NbE)

This section describes our results' methodology, which is largely inspired by the *normalization by evaluation* algorithm and metatheory of Chapman et al. [2019], although we have made significant extensions to their approach in order to capture the computation of rows. Our work also differs in some design choices (see (§6)). Our full development is available as part of the anonymous supplementary materials. The code we present here is summarized and tidied for display in print and easier digestion, but otherwise remains faithful to the development in behavior and intent. The claims of this section are annotated with the corresponding points in our full artifact.

Normalization by evaluation comes in a handful of different flavors. In our case, we seek to build a normalization function $\Downarrow : \mathcal{T} \rightarrow \hat{\mathcal{T}}$ by interpreting derivations in $\mathcal{T}_{\Delta}^{\kappa}$ (the set of derivations of the judgment $\Delta \vdash \tau : \kappa$) into a semantic domain capable of performing reductions semantically. We then *reify* objects in the semantic domain back to judgments in $\hat{\mathcal{T}}_{\Delta}^{\kappa}$ (the set of derivations of the judgment $\Delta \vdash_{nf} \tau : \kappa$). The mapping of syntax to a semantic domain is typically written as $\llbracket \cdot \rrbracket$ and called the *residualizing semantics*. For example, a judgment of the form $\Delta \vdash \phi : \star \rightarrow \star$ could be interpreted into a set-theoretic function, allowing applications to be interpreted into set-theoretic applications by that function. In our case, the syntax of the judgments $\Delta \vdash \tau : \kappa$, $\Delta \vdash_{nf} \tau : \kappa$, and $\Delta \vdash_{ne} \tau : \kappa$ are represented as Agda data types (where Env is a list of De Bruijn indexed type variables and Kind is the type of kinds):

```
SemType : Env → Kind → Set
SemType Δ ★ = NormalType Δ ★
SemType Δ L = NormalType Δ L
SemType Δ1 (κ1 '→ κ2) = KripkeFunction Δ1 κ1 κ2
SemType Δ R[ κ ] =
  RowType Δ (λ Δ' → SemType Δ' κ) R[ κ ]
```

Figure 4. Semantic types

```
data Type : Env → Kind → Set
data NormalType : Env → Kind → Set
data NeutralType : Env → Kind → Set
```

4.1 Residualizing semantics

We define our semantic domain in Agda recursively over the syntax of Kinds in Figure 4.

Types at ground kind \star and L are simply interpreted as `NormalTypes`. We interpret arrow-kinded types as *Kripke function spaces*, which permit the application of interpreted function ϕ at any environment Δ_2 provided a renaming from Δ_1 into Δ_2 .

```
Renaming Δ1 Δ2 = TVar Δ1 κ → TVar Δ2 κ
KripkeFunction : Env → Kind → Kind → Set
KripkeFunction Δ1 κ1 κ2 = ∀ {Δ2} →
  Renaming Δ1 Δ2 → SemType Δ2 κ1 → SemType Δ2 κ2
```

The first three equations thus far are standard for this style of Agda mechanization, borrowing from Chapman et al. [2019]. Novel to our development is the interpretation of row-kinded types. First, we define the interpretation of row literals as finitely indexed maps to label-type pairs. (Here the type `Label` is a synonym for `String`, but could be any type with decidable equality and a strict total-order.)

```
Row : Set → Set
Row A = ∃[ n ] (Fin n → Label × A)
```

Next, we define a `RowType` inductively as one of four cases: either a row literal constructed by `row`, a neutral-labeled row singleton constructed by `▷_`, an inert map constructed by `_$`, or an inert row complement constructed by `_` (Figure 5).

Care must be taken to explain some nuances of each constructor. First, the `row` and `_` constructors are each constrained by predicates. The `OrderedRow ρ` predicate asserts that ρ has its string labels totally and ascendingly ordered—guaranteeing that labels in the row are unique and that rows are definitionally equal modulo ordering. The `NotRow ρ` predicate asserts simply that ρ was *not* constructed by `row`. In other words, it is not a row literal. This is important, as the complement of two row literals should reduce to a `Row`, so we must disallow the formation of complements in which at least one of the operands is a literal.

```

551 data RowType (Δ : Env)
552       (T : Env → Set) : Kind → Set where
553   row      : (ρ : Row (T Δ)) →
554               OrderedRow ρ →
555               RowType Δ T R[ κ ]
556   _▷_      : NeutralType Δ L →
557               T Δ →
558               RowType Δ T R[ κ ]
559   _$_      : (∀ {Δ'} →
560               Renaming Δ Δ' →
561               NeutralType Δ' κ1 →
562               T Δ') →
563               NeutralType Δ R[ κ1 ] →
564               RowType Δ T R[ κ2 ]
565   _\_      : (ρ2 ρ1 : RowType Δ T R[ κ ]) →
566               {nor : NotRow ρ2 or notRow ρ1} →
567               RowType Δ T R[ κ ]

```

Figure 5. Semantic row type

The next set of nuances come from dancing around Agda's positivity and termination checking. It would have been preferable for us to have written the `row` and `$_` constructors as follows:

```

576 row      : (ρ : Row (SemType Δ κ)) →
577               OrderedRow ρ →
578               RowType Δ T R[ κ ]
579   _$_      : (∀ {Δ'} →
580               Renaming Δ Δ' →
581               SemType Δ' κ1 →
582               SemType Δ' κ2) →
583               NeutralType Δ R[ κ1 ] →
584               RowType Δ T R[ κ2 ]

```

Such a definition would have necessarily made the types `RowType` and `SemType` mutually inductive-recursive. But this would run afoul of Agda's termination and positivity checkers for the following reasons:

1. in the constructor `row`, the input `Row (SemType Δ κ)` makes a recursive call to `SemType Δ κ`, where it's not clear (to Agda) that this is a strictly smaller recursive call. To get around this, we parameterize the `RowType` type by `T : Env → Set` so that we may enforce this recursive call to be structurally smaller—hence the definition of `SemType` at kind `R[κ]` passes the argument $(\lambda \Delta' \rightarrow \text{SemType } \Delta' \kappa)$, which varies in environment but is at a strictly smaller kind.
2. The `$_` constructor takes a `KripkeFunction` as input, in which `SemType Δ' κ1` occurs negatively, which Agda must outright reject. Here we borrow some clever machinery from Allais et al. [2013] and instead make the `KripkeFunction` accept the input `NeutralType Δ' κ1`, which is already defined. The trick is that, as we will

```

606 reflect : NeutralType Δ κ → SemType Δ κ
607 reify   : SemType Δ κ → NormalType Δ κ
608
609 reflect {κ = ★} τ = ne τ
610 reflect {κ = L} τ = ne τ
611 reflect {κ = κ1 ' → κ2} =
612   λ r v → reflect ((rename r τ) · reify v)
613 reflect {κ = R[ κ ]} ρ = (λ r n → reflect n) $ ρ

```

Figure 6. Reflection

show in the next section, every `NeutralType` may be promoted to a `SemType`. In practice this is sufficient for our needs.

4.2 Reflection & reification

We have now declared three domains: the syntax of types, the syntax of normal and neutral types, and the embedded domain of semantic types. Normalization by evaluation involves producing a *reflection* from neutral types to semantic types, a *reification* from semantic types to normal types, and an *evaluation* from types to semantic types. It follows thereafter that normalization is the reification of evaluation. Because we reason about types modulo η -expansion, reflection and reification are necessarily mutually recursive. (This is not the case however with e.g. Chapman et al. [2019].)

Reflection is defined in Figure 6. Types at kind \star and L can be promoted straightforwardly with the `ne` constructor. Neutral types at arrow kind must be expanded into Kripke functions. Note that the input v has type `SemType Δ κ1` and must be reified; additionally, τ is kinded in environment Δ_1 and so must be renamed to Δ_2 , the environment of v . The syntax \cdot is used to construct an application of a `neutralType` to a `normalType`. Finally, a neutral row (e.g., a row variable) must be expanded into an inert mapping by $(\lambda r n \rightarrow \text{reflect } n)$, which is effectively the identity function.

The definition of reification is a little more involved (Figure 7). The first two equations are expected (τ is already in normal form). Functions are reified effectively by η -expansion; note that we are using intrinsically-scoped De Bruijn variables, so `Z` constructs the zero'th variable and `S` induces a renaming in which each variable is incremented by one. (Recall that ϕ is a Kripke function space and so expects a renaming as argument.) The constructor ``` promotes a type variable to a `neutralType`, which is reflected so that it may be passed to ϕ . The remaining equations describe the reification of the four row cases. When the input is a neutral-labeled row singleton, we need only create a `NeutralType`-labeled singleton with the body τ reified. The case of an inert complement $\rho_2 \setminus \rho_1$ remains an inert complement at type `NormalType`. Finally, we reify the inert map $\phi \$ \tau$ by reifying ϕ analogously

```

661 reify {κ = ★} τ = τ
662 reify {κ = L} τ = τ
663 reify {κ = κ1 '→ κ2} ϕ =
664   `λ (reify (ϕ S (reflect (` Z))))
665 reify {κ = R[ κ ]} (l ▷ τ) = l ▷ (reify τ)
666 reify {κ = R[ κ ]} (ρ2 \ ρ1) = reify ρ2 \ reify ρ1
667 reify {κ = R[ κ ]} (ϕ $ τ) =
668   `λ (reify (ϕ S (` Z))) $ (reify τ)
669 reify {κ = R[ κ ]} (row ρ q) =
670   row (reifyRow ρ) (reifyPreservesOrdering q)
671 where
672   reifyRow : Row (SemType Δ κ) →
673     List (Label × NormalType Δ κ)
674   reifyRow (0 , P) = []
675   reifyRow (suc n , P) with P fzero
676   ... | (l , τ) =
677     (l , reify τ) :: reifyRow (n , P ∘ fsuc)

```

Figure 7. Reification

to the $\kappa_1 \rightarrow \kappa_2$ case and mapping it over the reification of τ .

The equation of interest is in reifying row literals. We pun the row constructor to construct row literals at type `NormalType`, which likewise expects a proof that the row is well-ordered. Such a proof is given by the auxiliary lemma `reifyPreservesOrdering`. We use a helper function `reifyRow` to recursively build a list of `Label-NormalType` pairs (that is, the form of `NormalType` row literals) from a semantic row. The empty case is trivial; the successor case must inspect the head of the list by destructing `P fzero`, i.e., the label-type association of the zero'th finite index. From there we yield a semantic type τ which we reify and append to the result of recursing.

Finally, we have asserted that types are reduced modulo β -reduction and η -expansion. It follows that a given `NeutralType` should, after reflection and reification, end up in an expanded form. This is precisely how we define the promotion of `NeutralTypes` to `NormalTypes`:

```

701 η-norm : NeutralType Δ κ → NormalType Δ κ
702 η-norm = reify ∘ reflect

```

This function is necessary: the `NormalType` constructor `ne` stipulates that we may only promote neutral derivations to normal derivations at *ground kind* (rule $(\kappa_{nf}\text{-NE})$). Hence η -norm is the only means by which we may promote neutral types at row or arrow kind.

4.3 Helping evaluation

We will build our evaluation function incrementally; we find it clearer to incrementally build helpers for sub-computation (e.g., mapping or the complement) on our way up to full evaluation. We describe these helpers next.

```

716 _$'_ : SemType Δ (κ1 '→ κ2) →
717       SemType Δ R[ κ1 ] →
718       SemType Δ R[ κ2 ]
719 ϕ $' (l ▷ τ) = l ▷ (ϕ ·' τ)
720 ϕ $' (row (n , P) q) = row (n , fmap (ϕ id) ∘ P)
721 ϕ $' (ρ2 \ ρ1) = (ϕ $ ρ2) \ (ϕ $ ρ1)
722 ϕ $' (ϕ2 $ n) = (λ r → ϕ1 r ∘ ϕ2 r) $ n

```

Figure 8. Semantic mapping

4.3.1 Semantic application. We define semantic application straightforwardly as Agda application under the identity renaming.

```

729 _·'_ : SemType Δ (κ1 '→ κ2) →
730       SemType Δ κ1 →
731       SemType Δ κ2
732 ϕ ·' v = ϕ id v

```

4.3.2 Semantic mapping. Mapping over rows is a form of computation novel to $R\omega\mu$'s equivalence relation. We define the mapping $\phi \$ \rho$ over the four cases a semantic row may take (Figure 8). When ρ is neutral-labeled, we simply apply ϕ to its contents. The case where ρ is a row literal is interesting in that our choice of representation for row literals as Agda functions comes to pay off: we may express the mapping of ϕ across the row (n , P) by pre-composing P with ϕ (note that we must appropriately `fmap` ϕ over the pair's second component). The mapping of ϕ over a complement is distributive, following rule (E-MAP \backslash). Likewise, we follow rule (E-MAP \circ) in grouping the nested map $\phi \$ (\phi_2 \$ n)$ into a composed map.

4.3.3 Semantic complement. The complement of two row-kinded semantic types is always inert when one (or both) are not row literals, and thus constructed simply by the `_ _` constructor. The interesting case is when we must reduce two row literals to another row literal (Figure 9). Here our implementation differs slightly to the syntactic presentation in Figure 2. We proceed by induction on the length of the left-hand row: The resulting row is the empty row $0 , \lambda ()$ when the left-hand row is empty. (That is to say, an empty row minus any other row is empty.) Otherwise, we check if the label of the head entry in $P , P fzero .fst$, is in the right-hand row. If so, we omit it and proceed with recursion. If not, we retain it.

4.3.4 Semantic flap. The rule (E-LIFT Ξ) describes how Π and Σ reassociate from e.g. $(\Pi \rho) a$ to $\Pi (\rho ?? a)$. We define a semantic version of the flap (flipped map) operator as follows:

```

763 _??'_ : SemType Δ R[ κ1 '→ κ2 ] →
764       SemType Δ κ1 → SemType Δ R[ κ2 ]
765 ϕ ??' a = (λ r f → f ·' (rename r a)) $' ϕ

```

4.3.5 Semantic Π and Σ . The defining equations for the reduction of Π is given in Figure 10. (The logic for Σ is identical and omitted.)

```

771 _In?_ : Label → Row (SemType Δ κ) → Bool
772
773 _\'_ : Row (SemType Δ κ) → Row (SemType Δ κ) →
774       Row (SemType Δ κ)
775 (zero , P) \\' (m , Q) = 0 , λ ()
776 (suc n , P) \\' (m , Q) with P fzero .fst In? Q
777 ... | true = (P ∘ fsuc) \\' Q
778 ... | false = suc n , λ { fzero → P fzero ,
779                          fsuc _ → (P ∘ fsuc) \\' Q }

```

Figure 9. Semantic complement

```

783 Π' : SemType Δ R[ κ ] → SemType Δ κ
784 Π' {κ = ★} ρ = Π (reify ρ)
785 Π' {κ = κ1 → κ2} ϕ = λ r v → Π' (rename r ϕ ??' v)
786 Π' {κ = R[ κ ]} ρ = (λ r v → Π' v) $' ρ
787

```

Figure 10. Semantic Π

The input row to Π' has kind $R[\kappa]$; we proceed by destructing κ . Recall that we may only construct record types in normal form at kind \star , and so for the case that $\kappa = \star$ we simply reify the input and construct the record via the `NormalType` constructor Π . We exclude the case that $\kappa = L$ because it is impossible: in the `Type` syntax, we restrict the formation of the Π constructor by the following predicate:

```

798 NotLabel : Kind → Set
799 NotLabel ★ = ⊤
800 NotLabel L = ⊥
801 NotLabel (κ1 ' → κ2) = NotLabel κ2
802 NotLabel R[ κ ] = NotLabel κ
803

```

This is to say, one may not apply Π to an input that is a row of labels, a label-valued function, or a nested row of labels. Next, when applying Π' to a function, we must expand the semantic λ -binding outwards. Thereafter, we apply rule (E-LIFT Ξ) to explain how Π' operates on a single operand. Finally, we implement rule (E- Ξ) directly in the last equation: the application of Π' to a row-kinded input x is simply the mapping of Π' over x .

4.4 Evaluation

Evaluation warrants an environment that maps type variables to semantic types. The identity environment, which fixes the meaning of variables, is given as the composition of reflection and \sim , the constructor of `NeutralTypes` from `TVars`.

```

818 SemEnv : Env → Env → Set
819 SemEnv Δ1 Δ2 = TVar Δ1 κ → SemType Δ2 κ
820 idEnv : SemEnv Δ Δ
821 idEnv = reflect ∘ ~
822

```

We describe only the interesting cases of evaluation (Figure 11); the rest are purely compositional.

```

826 eval : Type Δ1 → SemEnv Δ1 Δ2 → SemType Δ2 κ
827 eval (~ x) η = η x
828 eval (τ1 · τ2) η = (eval τ1 η) ·' (eval τ2 η)
829 eval (ρ2 \ ρ1) η = eval ρ2 η \' eval ρ1 η
830 eval (~λ τ) η = λ r v →
831   eval τ (extend (rename r ∘ η) v)
832 eval Π η = λ r v → Π' v
833 eval Σ η = λ r v → Σ' v
834 eval (ϕ $ τ) η = eval ϕ η $' eval n τ
835 eval (l > τ) η with eval l η
836 ... | ne n = (n > eval τ η)
837 ... | lab ℓ = row (1 , λ { fzero →
838                  (ℓ , eval τ η )}) tt
839 eval (row ρ q) η = row
840   (evalRow ρ η)
841   (evalPreservesOrdering q)
842 where
843   evalRow : List (Label × (Type Δ1 κ)) →
844             SemEnv Δ1 Δ2 →
845             Row (SemType Δ2 κ)
846   evalRow [] η = 0 , λ ()
847   evalRow ((l , τ) :: ρ) η = λ { fzero → eval τ η ,
848                                     fsuc _ → evalRow ρ η }

```

Figure 11. Evaluation

The first equation states that variables evaluate to their meaning in environment η . The equations for application \cdot , row complement \backslash , record and variant operators Π and Σ , and mapping $_ \$$ defer to the semantic helpers defined in (§4.3). The evaluation of a function $\sim \lambda \tau$ is simply the evaluation of the body in the environment η expanded with semantic object v , being careful to rename appropriately as this is a Kripke function. Evaluation of labeled singletons must check if the label is a neutral variable n or label literal ℓ ; in the former case, we evaluate to an inert singleton using the `RowType` constructor $_ >$; in the latter, we evaluate to a row literal in which $fzero$ points to $(\ell , \text{eval } \tau \eta)$. The term `tt : Unit` is the evidence that this row literal is trivially ordered. Finally, we evaluate row literals by recursion: the empty case evaluates to the empty `Row`, $0 , \lambda ()$; the cons case evaluates to a row in which $fzero$ maps to the evaluation of τ , while $fsuc$ otherwise proceeds recursively. Again, we have an obligation to prove that evaluation preserves the ordering evidence q , which is performed by the auxiliary lemma `evalPreservesOrdering`.

4.5 Normalization

Normalization in the NbE approach is simply the composition of reification after evaluation.

```

874 ↓ : Type Δ κ → NormalType Δ κ
875 ↓ τ = reify (eval τ idEnv)
876

```


It will be helpful in the coming metatheory to define an inverse embedding by induction over the `NormalType` structure. The definition is entirely expected and omitted.

```

 $\Uparrow$  : NormalType  $\Delta \kappa \rightarrow$  Type  $\Delta \kappa$ 
 $\Uparrow$ NE : NeutralType  $\Delta \kappa \rightarrow$  Type  $\Delta \kappa$ 

```

5 Mechanized metatheory

This section describes the Agda formalization of the metatheory summarized in (§3.2), including proofs and proof outlines where space permits.

5.1 Canonicity of normal types

Normal forms are partitioned by kind, which can easily be shown by case splitting on `NormalType` inputs. We first demonstrate that neutrals cannot exist in an empty environment:

```

noNeutrals : NeutralType []  $\kappa \rightarrow \perp$ 
noNeutrals (n ·  $\tau$ ) = noNeutrals n

```

Now, in any context an arrow-kinded type is canonically λ -bound:

```

arrow-canonicity : ( $\phi$  : NormalType  $\Delta (\kappa_1 \rightarrow \kappa_2)$ )  $\rightarrow$ 
   $\exists [\tau] (\phi \equiv \lambda \tau)$ 
arrow-canonicity ( $\lambda \tau$ ) =  $\tau$ , refl

```

A row in an empty context is necessarily a row literal (all omitted cases are eliminated by \perp -elim):

```

row-canonicity : ( $\rho$  : NormalType [] R[  $\kappa$  ])  $\rightarrow$ 
   $\exists [xs, oxs]$ 
  ( $\rho \equiv$  row xs oxs)
row-canonicity (row  $\rho$  q) =  $\rho$ , q, refl

```

And a label-kinded type is necessarily a label literal (where `lab` constructs a label literal):

```

label-canonicity : (l : NormalType [] L)  $\rightarrow$ 
   $\exists [\ell] (l \equiv$  lab  $\ell)$ 
label-canonicity (ne x) =  $\perp$ -elim (noNeutrals x)
label-canonicity (lab s) = s, refl

```

5.2 Stability

Stability follows by simple induction on the input derivation $\Delta \vdash_{nf} \tau : \kappa$. Here it is clearer that we are stating \Downarrow is left-inverse to \Uparrow .

```

stability :  $\forall (\tau : NormalType \Delta \kappa) \rightarrow \Downarrow (\Uparrow \tau) \equiv \tau$ 

```

Stability implies idempotency:

```

idempotency :  $\forall (\tau : Type \Delta \kappa) \rightarrow$ 
  ( $\Uparrow \circ \Downarrow \circ \Uparrow \circ \Downarrow$ )  $\tau \equiv (\Uparrow \circ \Downarrow) \tau$ 
idempotency  $\tau$  rewrite (stability ( $\Downarrow \tau$ )) = refl

```

and surjectivity:

```

surjectivity :  $\forall (\tau : NormalType \Delta \kappa) \rightarrow$ 
   $\exists [v] (\Downarrow v \equiv \tau)$ 
surjectivity  $\tau = (\Uparrow \tau, \text{stability } \tau)$ 

```

Dual to surjectivity, stability also implies that embedding is injective.

```

 $\approx$  : { $\kappa = \star$ }  $\tau_1 \tau_2 = \tau_1 \equiv \tau_2$ 
 $\approx$  : { $\kappa = L$ }  $\tau_1 \tau_2 = \tau_1 \equiv \tau_2$ 
 $\approx$  : { $\kappa = \kappa_1 \rightarrow \kappa_2$ }  $\phi_1 \phi_2 =$ 
  Uniform  $\phi_1 \times$  Uniform  $\phi_2 \times$  PointEqual  $\phi_1 \phi_2$ 
 $\approx$  : { $\kappa = R[\kappa]$ } ( $\ell_1 \triangleright \tau_1$ ) ( $\ell_2 \triangleright \tau_2$ ) =  $\ell_1 \equiv \ell_2 \times \tau_1 \approx \tau_2$ 
 $\approx$  : { $\kappa = R[\kappa]$ } ( $\_ \$ \_ \{ \kappa_1 \} \phi_1 n_1$ ) ( $\_ \$ \_ \{ \kappa_1' \} \phi_2 n_2$ ) =
   $\exists [pf : \kappa_1 \equiv \kappa_1']$ 
  UniformNE  $\phi_1 \times$ 
  UniformNE  $\phi_2 \times$ 
  PointEqualNE (convKripkeNE pf  $\phi_1$ )  $\phi_2 \times$ 
  convNE pf  $n_1 \equiv n_2$ 
 $\approx$  : { $\kappa = R[\kappa]$ } ( $\rho_2 \setminus \rho_1$ ) ( $\rho_4 \setminus \rho_3$ ) =  $\rho_2 \approx \rho_4 \times \rho_1 \approx \rho_3$ 
 $\approx$  : { $\kappa = R[\kappa]$ } (row  $\rho_1$  q) (row  $\rho_2$  g) =  $\rho_1 \approx_R \rho_2$ 
where
  ( $\ell_1, \tau_1$ )  $\approx_2$  ( $\ell_2, \tau_2$ ) =  $\ell_1 \equiv \ell_2 \times \tau_1 \approx \tau_2$ 
  (n, P)  $\approx_R$  (m, Q) =  $\exists [pf : n \equiv m]$ 
  ( $\forall (i : \text{fin } m) \rightarrow$ 
  (subst-Row pf P) i  $\approx_2$  Q i)

```

Figure 12. Completeness relation

```

 $\Uparrow$ -inj :  $\forall (\tau_1 \tau_2 : NormalType \Delta \kappa) \rightarrow$ 
   $\Uparrow \tau_1 \equiv \Uparrow \tau_2 \rightarrow \tau_1 \equiv \tau_2$ 
 $\Uparrow$ -inj  $\tau_1 \tau_2$  eq =
  trans
  (sym (stability  $\tau_1$ ))
  (trans
  (cong  $\Downarrow$  eq)
  (stability  $\tau_2$ ))

```

5.3 A logical relation for completeness

Completeness states that equivalent types reduce to the same normal forms. We define the equivalence relation of Figure 2 as an inductive, intrinsically typed relation in Agda.

```

data  $\approx$  : Type  $\Delta \kappa \rightarrow$  Type  $\Delta \kappa \rightarrow$  set

```

and hence completeness may be stated as follows:

```

completeness :  $\forall \tau_1 \tau_2. \tau_1 \equiv \tau_2 \rightarrow \Downarrow \tau_1 \equiv \Downarrow \tau_2$ 

```

We prove completeness via a logical relation \approx on semantic types that specifies when two semantic objects are equivalent modulo uniformity ([Allais et al. 2013; Chapman et al. 2019]) and pointwise functional extensionality. We define \approx recursively over the kinds of the inputs τ_1 and τ_2 (Figure 12).

The completeness logical relation is defined compositionally in the cases where $\kappa = \star$, $\kappa = L$, or $\kappa = R[\kappa]$ and the equated rows are neutral-labeled or inert complements. In the case that $\kappa = \kappa_1 \rightarrow \kappa_2$, we assert that the Kripke functions ϕ_1 and ϕ_2 are *uniform* and *extensionally equivalent* to one another (Figure 13). Uniformity and states effectively that passing a renaming r_2 to a Kripke function applied to its argument is equivalent to renaming it algorithmically. The uniformity property is attributable to Allais et al.

```

991 Uniform : KripkeFunction  $\Delta \kappa_1 \kappa_2 \rightarrow \text{Set}$ 
992 Uniform  $\phi = \forall (r_1 : \text{Renaming } \Delta_1 \Delta_2)$ 
993    $(r_2 : \text{Renaming } \Delta_2 \Delta_3)$ 
994    $(v_1 v_2 : \text{SemType } \Delta_2 \kappa_1) \rightarrow$ 
995    $v_1 \approx v_2 \rightarrow$ 
996    $\text{rename } r_2 (\phi r_1 v_1) \approx$ 
997    $\phi (r_2 \circ r_1) (\text{rename } r_2 v_2)$ 
998 PointEqual :  $(\phi_1 \phi_2 : \text{KripkeFunction } \Delta \kappa_1 \kappa_2) \rightarrow \text{Set}$ 
999 PointEqual  $\phi_1 \phi_2 = \forall (r : \text{Renaming } \Delta_1 \Delta_2)$ 
1000    $\{v_1 v_2 : \text{SemType } \Delta_2 \kappa_1\} \rightarrow$ 
1001    $v_1 \approx v_2 \rightarrow$ 
1002    $\phi_1 r v_1 \approx \phi_2 r v_2$ 

```

Figure 13. Uniformity and point equality

[2013] but simplified drastically by Chapman et al. [2019]. The PointEqual predicate circumvents any need to postulate functional extensionality; rather, we assert that ϕ_1 and ϕ_2 map equivalent inputs to equivalent outputs (a property to be expected of a logical relation).

The predicates UniformNE and PointEqualNE are entirely analogous to Uniform and PointEqual except that they describe Kripke functions in which the domain is a NeutralType rather than SemType. In the case that we are equating two inert maps, we must additionally assert that the domains of ϕ_1 and ϕ_2 (that is, κ_1 and κ_1' , resp.) are equivalent. The helpers convKripkeNE and convNE convert ϕ_1 and n_1 appropriately so to be indexed by kind κ_1' .

Finally, we equate row literals under the \approx_R relation, which states that (i) the two rows' lengths are equal, and (ii) the two rows have pointwise related contents. Note that we must use an auxiliary helper subst-Row to convert the length n indexing P to be m .

5.3.1 Properties. Propositionally equal neutral types reflect to equivalent semantic objects:

```

1027 reflect- $\approx : \forall \{ \tau_1 \tau_2 : \text{NeutralType } \Delta \kappa \} \rightarrow$ 
1028    $\tau_1 \equiv \tau_2 \rightarrow \text{reflect } \tau_1 \approx \text{reflect } \tau_2$ 

```

Dually, equivalent semantic objects reify to propositionally equal types.

```

1032 reify- $\approx : \lambda \forall \{ v_1 v_2 : \text{SemType } \Delta \kappa \} \rightarrow$ 
1033    $v_1 \approx v_2 \rightarrow$ 
1034    $\text{reify } v_1 \equiv \text{reify } v_2$ 

```

5.3.2 Logical environments. We lift the relation \approx_e to a relation on semantic environments η_1 and η_2 by asserting that the two are pointwise related.

```

1038  $\approx_e : (\eta_1 \eta_2 : \text{SemEnv } \Delta_1 \Delta_2) \rightarrow \text{Set}$ 
1039  $\eta_1 \approx_e \eta_2 = \forall (\alpha : \text{TVar } \Delta_1 \kappa) \rightarrow (\eta_1 \alpha) \approx (\eta_2 \alpha)$ 

```

The identity semantic environment relates to itself under the reflection of propositional equality, as witnessed by idEnv- \approx .

```

1043 idEnv- $\approx : \text{idEnv } \approx_e \text{idEnv}$ 
1044 idEnv- $\approx \alpha = \text{reflect-}\approx \text{refl}$ 

```

5.3.3 The fundamental theorem and completeness.

The fundamental theorem for the completeness relation states that equivalent types evaluate to related semantic objects. The proof of the fundamental theorem is by induction over the type equivalence witness $\tau_1 \equiv \tau_2$.

```

1051 fundC :  $\eta_1 \approx_e \eta_2 \rightarrow \tau_1 \equiv \tau_2 \rightarrow$ 
1052    $\text{eval } \tau_1 \eta_1 \approx \text{eval } \tau_2 \eta_2$ 

```

Completeness follows from the fundamental theorem in the identity semantic environment.

```

1055 completeness :  $\forall \tau_1 \tau_2. \tau_1 \equiv \tau_2 \rightarrow \Downarrow \tau_1 \equiv \Downarrow \tau_2$ 
1056 completeness  $\tau_1 \tau_2 \text{eq} = \text{reify-}\approx (\text{fundC idEnv-}\approx \text{eq})$ 

```

5.4 A logical relation for soundness

Soundness states the converse of completeness: if two types normalize to the same form, then they are equivalent.

```

1061 conv-completeness :  $(\tau_1 \tau_2 : \text{Type } \Delta \kappa) \rightarrow$ 
1062    $\Downarrow \tau_1 \equiv \Downarrow \tau_2 \rightarrow \tau_1 \equiv \tau_2$ 

```

In practice, it is easier to instead prove that each type is equivalent to its embedded normalization:

```

1066 soundness :  $\forall (\tau : \text{Type } \Delta \kappa) \rightarrow \tau \equiv \uparrow (\Downarrow \tau)$ 

```

And it is straightforward to show that the latter implies the former:

```

1069 embed- $\equiv : \forall (\tau_1 : \text{NormalType } \Delta \kappa) (\tau_2 : \text{Type } \Delta \kappa) \rightarrow$ 
1070    $\tau_1 \equiv (\Downarrow \tau_2) \rightarrow \uparrow \tau_1 \equiv \tau_2$ 
1071 embed- $\equiv \text{refl} = \text{sym } (\text{soundness } \tau_2)$ 

```

```

1073 conv-completeness  $\tau_1 \tau_2 \text{eq} =$ 
1074    $\text{trans } (\text{soundness } \tau_1) (\text{embed-}\equiv \text{eq})$ 

```

We define a logical relation for soundness by relating un-normalized types to semantic objects in Figure 14. The first two cases state that τ relates to v at ground kind when τ is equivalent to the embedding of v . Figure 16 describes when syntactic type operators relate to Kripke functions; the definitions are largely the same for semantic and neutral Kripke functions except that, in the neutral case, we require instead that τ is equivalent to the η -expansion of n . The definitions otherwise assert that related inputs map to related outputs.

5.4.1 Properties.

5.4.2 Logical environments.

5.4.3 The fundamental theorem and Soundness.

5.5 Decidability of type conversion

6 Most closely related work

Our technical development owes a huge debt to two papers in particular. We closely follow the formalization patterns and proof techniques of Chapman et al. [2019]; indeed, this paper is in some sense an extension of their work from System $F\omega\mu$ to system $R\omega\mu$. In turn, Chapman et al. [2019] themselves follow closely Allais et al. [2013], from whom we looked to

```

1101  $\llbracket \_ \rrbracket_{\approx} : \text{Type } \Delta \kappa \rightarrow \text{SemType } \Delta \kappa \rightarrow \text{Set}$ 
1102  $\llbracket \_ \rrbracket_{\approx} \{ \kappa = \star \} \tau \quad v = \tau \equiv \uparrow v$ 
1103  $\llbracket \_ \rrbracket_{\approx} \{ \kappa = L \} \tau \quad v = \tau \equiv \uparrow v$ 
1104  $\llbracket \_ \rrbracket_{\approx} \{ \kappa = \kappa_1 \xrightarrow{\sim} \kappa_2 \} \phi \quad F = \text{SoundKripke } \phi \quad F$ 
1105  $\llbracket \_ \rrbracket_{\approx} \{ \kappa = R[ \kappa ] \} \tau \quad (\text{row } (n, P) \text{ } q) =$ 
1106  $\exists [ \text{xs} ]$ 
1107  $\exists [ \text{oxs} ]$ 
1108  $(\tau \equiv \text{row } \text{xs } \text{oxs}) \times$ 
1109  $\llbracket \text{xs} \rrbracket_{R\approx} (n, P)$ 
1110  $\llbracket \_ \rrbracket_{\approx} \{ \kappa = R[ \kappa ] \} \tau \quad (n \triangleright v) =$ 
1111  $\exists [ v ]$ 
1112  $(\tau \equiv \text{t } (\uparrow \text{NE } n \triangleright v)) \times$ 
1113  $\llbracket v \rrbracket_{\approx} v$ 
1114  $\llbracket \_ \rrbracket_{\approx} \{ \kappa = R[ \kappa ] \} \tau \quad (\rho_2 \setminus \rho_1) =$ 
1115  $(\tau \equiv \uparrow (\text{reify } (\rho_2 \setminus \rho_1))) \times$ 
1116  $\llbracket \uparrow (\text{reify } \rho_2) \rrbracket_{\approx} \rho_2 \times$ 
1117  $\llbracket \uparrow (\text{reify } \rho_1) \rrbracket_{\approx} \rho_1$ 
1118  $\llbracket \_ \rrbracket_{\approx} \{ \kappa = R[ \kappa ] \} \tau \quad (F \$ n) =$ 
1119  $\exists [ \phi ]$ 
1120  $(\tau \equiv (\phi \$ \uparrow \text{NE } n)) \times$ 
1121  $(\text{SoundKripkeNE } \phi \quad F)$ 

```

Figure 14. Soundness relation

```

1124  $\llbracket [] \rrbracket_{R\approx} (\text{zero}, P) = \top$ 
1125  $\llbracket [] \rrbracket_{R\approx} (\text{suc } n, P) = \perp$ 
1126  $\llbracket x :: \rho \rrbracket_{R\approx} (\text{zero}, P) = \perp$ 
1127  $\llbracket x :: \rho \rrbracket_{R\approx} (\text{suc } n, P) =$ 
1128  $\llbracket x \rrbracket_{\approx 2} (P \text{ fzero}) \times$ 
1129  $\llbracket \rho \rrbracket_{R\approx} (n, P \circ \text{fsuc})$ 
1130 where
1131  $\llbracket (\ell_1, \tau) \rrbracket_{\approx 2} (\ell_2, v) =$ 
1132  $(\ell_1 \equiv \ell_2) \times \llbracket \tau \rrbracket_{\approx} v$ 

```

Figure 15. Soundness relation (row literals)

```

1136  $\text{SoundKripke} : \text{Type } \Delta_1 (\kappa_1 \xrightarrow{\sim} \kappa_2) \rightarrow$ 
1137  $\text{KripkeFunction } \Delta_1 \kappa_1 \kappa_2 \rightarrow \text{Set}$ 
1138  $\text{SoundKripke } \phi \quad F =$ 
1139  $(r : \text{Renaming } \Delta_1 \Delta_2)$ 
1140  $\{ \tau : \text{Type } \Delta_2 \kappa \} \{ v : \text{SemType } \Delta_2 \kappa \}$ 
1141  $\llbracket \tau \rrbracket_{\approx} v \rightarrow$ 
1142  $\llbracket \text{rename } r \phi \cdot \tau \rrbracket_{\approx} F \quad r \quad v$ 
1143
1144  $\text{SoundKripkeNE} : \text{Type } \Delta_1 (\kappa_1 \xrightarrow{\sim} \kappa_2) \rightarrow$ 
1145  $\text{KripkeFunctionNE } \Delta_1 \kappa_1 \kappa_2 \rightarrow \text{Set}$ 
1146  $\text{SoundKripkeNE } \phi \quad F =$ 
1147  $(r : \text{Renaming } \Delta_1 \Delta_2)$ 
1148  $\{ \tau : \text{Type } \Delta_1 \kappa \} \{ n : \text{NeutralType } \Delta_1 \kappa \}$ 
1149  $\tau \equiv \text{t } (\eta\text{-norm } n) \rightarrow$ 
1150  $\llbracket \text{rename } r \phi \cdot n \rrbracket_{\approx} F \quad r \quad n$ 

```

Figure 16. Soundness of Kripke functions

in finding the correct semantic image of rows (borrowing from their semantic image of lists). Our paper differs in a few key ways. Firstly, we introduce label and row kinds to the syntax, incurring an additional burden to reduce row maps, the row operators Π and Σ , and row complements. We also reason about types modulo η -equivalence of functions and also expansion of rows to inert maps, which made many proof definitions harder to define. (For example, Chapman et al. [2019] do not need a mutually recursive reify and reflect, which in turn made many auxiliary lemmas harder to define.)

References

- Guillaume Allais, Pierre Boutillier, and Conor McBride. New equations for neutral terms: A sound and complete decision procedure, formalized, 2013. URL <https://arxiv.org/abs/1304.0809>.
- James Chapman, Roman Kireev, Chad Nester, and Philip Wadler. System F in agda, for fun and profit. In Graham Hutton, editor, *Mathematics of Program Construction - 13th International Conference, MPC 2019, Porto, Portugal, October 7-9, 2019, Proceedings*, volume 11825 of *Lecture Notes in Computer Science*, pages 255–297. Springer, 2019. ISBN 978-3-030-33635-6. doi: 10.1007/978-3-030-33636-3_10. URL https://doi.org/10.1007/978-3-030-33636-3_10.
- Alex Hubers and J. Garrett Morris. Generic programming with extensible data types: Or, making ad hoc extensible data types less ad hoc. *Proc. ACM Program. Lang.*, 7(ICFP):356–384, 2023. doi: 10.1145/3607843. URL <https://doi.org/10.1145/3607843>.
- Alex Hubers, Apoorv Ingle, Andrew Marmaduke, and J. Garrett Morris. Extensible recursive functions, algebraically, 2024. URL <https://arxiv.org/abs/2410.11742>.