

Recursive Rows in Rome

AH & JGM

ACM Reference Format:

AH & JGM. 2023. Recursive Rows in Rome. 1, 1 (December 2023), 5 pages. <https://doi.org/10.1145/nnnnnnnnn.nnnnnnnn>

1 IX: THE INDEX CALCULUS

1.1 Syntax

Let $0, 1, 2, \dots$ denote object-level natural numbers in the intuitive fashion and let i_n be the finite natural obtained by n applications of FSuc to FZero.

Sorts	$\sigma ::= \star \mid \mathcal{U}$
Terms	$A, B, M, N, T ::= \star \mid x \mid$ $\text{Nat} \mid \text{Zero} \mid \text{Suc } M \mid$ $\text{case}_{\mathbb{N}} M \text{ of } \{\text{Zero} \mapsto N_1; \text{Suc } x \mapsto N_2\} \mid$ $\text{Ix } M \mid \text{FZero} \mid \text{FSuc } M \mid$ $\text{case}_{\text{Fin}} M \text{ of } \{\text{FZero} \mapsto N_1; \text{FSuc } x \mapsto N_2\} \mid$ $\llbracket M_1, \dots, M_n \rrbracket \mid$ $\top \mid \text{tt} \mid$ $\forall \alpha : T. N \mid \lambda x : T. N \mid M N \mid$ $\exists \alpha : T. M \mid (\alpha : T, M) \mid$ $M + N \mid \text{left } M \mid \text{right } M \mid$ $\text{case}_+ M \text{ of } \{\text{left } x \mapsto N_1; \text{right } y \mapsto N_2\} \mid$ $M \equiv N \mid \text{refl } T M N \mid$
Environments	$\Gamma ::= \varepsilon \mid \Gamma, \alpha : T$

Fig. 1. Syntax

Author's address: AH & JGM.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

© 2023 Association for Computing Machinery.

XXXX-XXXX/2023/12-ART \$15.00

<https://doi.org/10.1145/nnnnnnnnn.nnnnnnnn>

1.2 Typing

$$\begin{array}{c}
 \boxed{\vdash \Gamma} \\
 (\text{EMP}) \frac{}{\vdash \varepsilon} \quad (\text{VAR}) \frac{\vdash \Gamma \quad \Gamma \vdash M : \sigma}{\vdash \Gamma, x : M} \\
 \boxed{\Gamma \vdash M : \sigma} \\
 (\star) \frac{}{\Gamma \vdash \star : \mathcal{U}} \quad (\top) \frac{}{\Gamma \vdash \top : \sigma} \quad (\text{NAT}) \frac{}{\Gamma \vdash \text{Nat} : \star} \quad (\text{IX}) \frac{\Gamma \vdash n : \text{Nat}}{\Gamma \vdash \text{Ix } n : \star} \\
 (\forall) \frac{\Gamma \vdash M : \sigma_1 \quad \Gamma, \alpha : M \vdash N : \sigma_2}{\Gamma \vdash \forall \alpha : M. N : \sigma_2} \quad (\exists) \frac{\Gamma \vdash M : \sigma_1 \quad \Gamma, \alpha : M \vdash N : \sigma_2}{\Gamma \vdash \exists \alpha : M. N : \sigma_2} \\
 (+) \frac{\Gamma \vdash M : \sigma \quad \Gamma \vdash N : \sigma}{\Gamma \vdash M + N : \sigma} \quad (\equiv) \frac{\Gamma \vdash M : \sigma \quad \Gamma \vdash N : \sigma}{\Gamma \vdash M \equiv N : \sigma}
 \end{array}$$

Fig. 2. Context and type formation rules

$$\begin{array}{c}
 \boxed{\Gamma \vdash M : N} \\
 (\text{VAR}) \frac{x : M \in \Gamma}{\Gamma \vdash x : M} \quad (\text{tt}) \frac{}{\Gamma \vdash \text{tt} : \top} \\
 (\text{Zero}) \frac{}{\Gamma \vdash \text{Zero} : \text{Nat}} \quad (\text{Suc}) \frac{\Gamma \vdash n : \text{Nat}}{\Gamma \vdash \text{Suc } n : \text{Nat}} \\
 (\text{FZero}) \frac{\Gamma \vdash n : \text{Nat}}{\Gamma \vdash \text{FZero} : \text{Ix} (\text{Suc } n)} \quad (\text{FSuc}) \frac{\Gamma \vdash n : \text{Nat} \quad \Gamma \vdash i : \text{Ix } n}{\Gamma \vdash \text{FSuc } i : \text{Ix} (\text{Suc } n)} \\
 (\forall I) \frac{\Gamma \vdash T : \star \quad \Gamma, x : T \vdash M : N}{\Gamma \vdash \lambda x : T. M : \forall (x : T). N} \quad (\forall E) \frac{\Gamma \vdash M : \forall (x : T_1). T_2 \quad \Gamma \vdash N : T_1}{\Gamma \vdash M N : T_2 [N/x]} \\
 (\exists I) \frac{\Gamma \vdash M : T_1 \quad \Gamma \vdash N : T_2 [M/x]}{\Gamma \vdash (M : T_1, N) : \exists (x : T_1). T_2} \quad (\exists E_1) \frac{\Gamma \vdash M : \Sigma (x : T_1). T_2}{\Gamma \vdash \text{fst } M : T_1} \quad (\exists E_2) \frac{\Gamma \vdash M : \Sigma (x : T_1). T_2}{\Gamma \vdash \text{snd } M : T_1 [\text{fst } M/x]} \\
 (\equiv I) \frac{\Gamma \vdash M : \sigma}{\Gamma \vdash \text{refl} : M \equiv M} \quad (\text{CONV}) \frac{\Gamma \vdash M : T_1 \quad \Gamma \vdash T_1 = T_2 : \sigma \quad \sigma \text{ Safe}}{\Gamma \vdash M : T_2} \\
 \begin{array}{c}
 \Gamma \vdash P : T_1 \equiv T_2 \\
 \Gamma \vdash M : T_1 \\
 \Gamma \vdash N : T_1 \\
 \Gamma, x : T_1, y : T_1, p : x \equiv y \vdash T : \star \\
 \Gamma, z : T_1 \vdash H : T [z/x, z/y, \text{refl}/p]
 \end{array} \\
 (\equiv E) \frac{}{\Gamma \vdash \mathcal{J} H M N P : T [M/x, N/y, P/p]}
 \end{array}$$

Fig. 3. Typing rules

$$\begin{array}{c}
\boxed{\Gamma \vdash M = N : \sigma} \\
\text{(E-REFL)} \frac{\Gamma \vdash M : \sigma}{\Gamma \vdash M = M : \sigma} \quad \text{(E-SYM)} \frac{\Gamma \vdash N = M : \sigma}{\Gamma \vdash M = N : \sigma} \quad \text{(E-TRANS)} \frac{\Gamma \vdash M = P : \sigma \quad \Gamma \vdash P = N : \sigma}{\Gamma \vdash M = N : \sigma} \\
\boxed{\Gamma \vdash M = N : T} \\
\text{(C-REFL)} \frac{\Gamma \vdash M : T}{\Gamma \vdash M = M : T} \quad \text{(C-SYM)} \frac{\Gamma \vdash N = M : T}{\Gamma \vdash M = N : T} \quad \text{(C-TRANS)} \frac{\Gamma \vdash M = P : T \quad \Gamma \vdash P = N : T}{\Gamma \vdash M = N : T}
\end{array}$$

Fig. 4. Definitional equality & computational laws

1.3 A Comparison to $\lambda^{\Pi\mathcal{U}\mathcal{N}}$ [Abel et al. 2018]

2 TRANSLATION FROM $R\omega$

2.1 Untyped Translation

We follow the approach of [Morris and McKinnin 2019] and give both typed and untyped translations of $R\omega$ types. Figure 5 describe the untyped translation, which is used to show translational soundness of the typed translation (Figure 5).

$$\begin{aligned}
& \boxed{(\kappa)^{\bullet}} \\
& (\star)^{\bullet} = \star \\
& (\mathbf{L})^{\bullet} = \top \\
& (\kappa_1 \rightarrow \kappa_2)^{\bullet} = \forall(\alpha : (\kappa_1)^{\bullet}).(\kappa_2)^{\bullet} \\
& (\mathbf{R}^{\kappa})^{\bullet} = \exists(n : \mathbf{Nat}).\forall(j : \mathbf{Ix } n).(\kappa)^{\bullet} \\
\\
& \boxed{(\Gamma \vdash \tau : \kappa)^{\bullet}} \\
& (\alpha)^{\bullet} = \alpha \\
& (\tau_1 \rightarrow \tau_2)^{\bullet} = \forall(\alpha : (\tau_1)^{\bullet}).(\tau_2)^{\bullet} \\
& (\forall \alpha : \kappa. \tau)^{\bullet} = \forall(\alpha : (\kappa)^{\bullet}).(\tau)^{\bullet} \\
& (\lambda \alpha : \kappa. \tau)^{\bullet} = \forall(\alpha : (\kappa)^{\bullet}).(\tau)^{\bullet} \\
& (\pi \Rightarrow \tau)^{\bullet} = \forall(\alpha : (\pi)^{\bullet}).(\tau)^{\bullet} \\
& (\tau v)^{\bullet} = (\tau)^{\bullet} (v)^{\bullet} \\
& (\rho \upharpoonright v)^{\bullet} = (\text{fst } (\rho)^{\bullet} : \mathbf{Nat}, \lambda(j : \mathbf{Ix } (\text{fst } (\rho)^{\bullet})).(\text{snd } (\rho)^{\bullet})(v)^{\bullet}) \\
& (\lceil \tau \rceil \rho)^{\bullet} = (\text{fst } (\rho)^{\bullet} : \mathbf{Nat}, \lambda(j : \mathbf{Ix } (\text{fst } (\rho)^{\bullet})).(\tau)^{\bullet} (\text{snd } (\rho)^{\bullet})) \\
& (\ell)^{\bullet} = \top \\
& (\lfloor \xi \rfloor)^{\bullet} = \top \\
& (\xi \triangleright \tau)^{\bullet} = (1, \lambda(i : \mathbf{Ix } 1).(\tau)^{\bullet}) \\
& (\Pi \rho)^{\bullet} = \forall(i : \mathbf{Ix } (\text{fst } (\rho)^{\bullet})).(\text{snd } (\rho)^{\bullet}) i \\
& (\Sigma \rho)^{\bullet} = \exists(i : \mathbf{Ix } (\text{fst } (\rho)^{\bullet})).(\text{snd } (\rho)^{\bullet}) i \\
\\
& \boxed{(\Gamma \vdash \pi : \kappa)^{\bullet}} \\
& \dots \\
\\
& \boxed{(\Gamma \Vdash \pi)^{\bullet}} \\
& \dots \\
\\
& \boxed{(\Gamma \vdash M : \tau)^{\bullet}} \\
& \dots
\end{aligned}$$

Fig. 5. A compositional translation of $\mathbf{R}\omega$ judgments to (untyped) \mathbf{Ix} terms

2.2 Typed translation

$$\begin{array}{c}
 \boxed{\Gamma \vdash \tau \rightsquigarrow v : \kappa} \\
 \\
 \text{(C-FOO)} \frac{A}{B} \\
 \boxed{\Gamma \vdash M \rightsquigarrow N : \tau} \\
 \\
 \text{(C-FOO)} \frac{A}{B} \\
 \boxed{\Gamma \Vdash \pi \rightsquigarrow N} \\
 \\
 \text{(C-FOO)} \frac{A}{B} \\
 \boxed{\tau \equiv v \rightsquigarrow P} \\
 \\
 \text{(C-FOO)} \frac{A}{B}
 \end{array}$$

Fig. 6. Translation of $R\omega$ derivations to lx derivations

2.3 Properties of Translation

Presume an $R\omega$ instantiation of the simple row theory. A lot of this is likely bullshit.

THEOREM 1 (TRANSLATIONAL SOUNDNESS (TYPES)). *if $\Gamma \vdash \tau : \kappa$ such that $\Gamma \vdash \tau \rightsquigarrow v : \kappa$ then $(\Gamma)^\bullet \vdash v : (\kappa)^\bullet$.*

THEOREM 2 (TRANSLATIONAL SOUNDNESS (TYPE EQUIVALENCE)). *if*

- (1) $\Gamma \vdash \tau_1 \rightsquigarrow v_1 : \kappa_1$;
- (2) $\Gamma \vdash \tau_2 \rightsquigarrow v_2 : \kappa_2$; and
- (3) $\tau_1 \equiv \tau_2 \rightsquigarrow P$,

then $(\Gamma)^\bullet \vdash P : v_1 \equiv v_2$.

THEOREM 3 (TRANSLATIONAL SOUNDNESS (OF PREDICATES)). *if $\Gamma \Vdash \pi$ such that $\Gamma \Vdash \pi \rightsquigarrow N$ then $(\Gamma)^\bullet \vdash N : (\pi)^\bullet$.*

Finally,

THEOREM 4 (TRANSLATIONAL SOUNDNESS). *if $\Gamma \vdash M : \tau$ such that $\Gamma \vdash M \rightsquigarrow N : \tau$ then $(\Gamma)^\bullet \vdash N : (\tau)^\bullet$.*

3 OPERATIONAL SEMANTICS

REFERENCES

- Andreas Abel, Joakim Öhman, and Andrea Vezzosi. 2018. Decidability of conversion for type theory in type theory. *Proc. ACM Program. Lang.* 2, POPL (2018), 23:1–23:29. <https://doi.org/10.1145/3158111>
- Alex Hubers and J. Garrett Morris. 2023. Generic Programming with Extensible Data Types; Or, Making Ad Hoc Extensible Data Types Less Ad Hoc. *CoRR* abs/2307.08759 (2023). <https://doi.org/10.48550/arXiv.2307.08759> arXiv:2307.08759
- J. Garrett Morris and James McKinna. 2019. Abstracting extensible data types: or, rows by any other name. *Proc. ACM Program. Lang.* 3, POPL (2019), 12:1–12:28. <https://doi.org/10.1145/3290325>