HELP - Wmalauncher

This document is based on an excerpt from the README file in the installation folder and also material from the man file (in a terminal: *man wmalauncher*).

Description

Developed by Sébastien Ballet, wmalauncher is an easy -to -use and highly configurable command-line application launcher especially designed for fluxbox, but which also works well under blackbox, openbox and windowmaker. Features:

- Provides support for
 - PNG, SVG, XPM icons
 - desktop files
 - Configuration files
 - Mouse hover event
 - Icon color/grayscale mode
 - Color gradient
- Permits customization of
 - Button appearance
 - o Icon brightness/contrast/gamma
 - Tooltip

It creates one or more icons in the slit, whose location is defined in the *init* file.

Usage

There are three ways to create a launcher for a given application with wmalauncher:

- 1. Pass the command to execute and the icon to display on the command line, as in example below :
 - \$ wmalauncher --command /usr/bin/firefox --icon firefox.png &

In the example above, wmalauncher will use the first icon found in the "icon search paths" that match firefox.png (note: the extension can be omitted).

- 2. Pass the .desktop file of the target application on the command line :
 - \$ wmalauncher --desktop-file mozilla-firefox.desktop:firefox.desktop &

In the example above, wmalauncher will use the first .desktop file found in the "desktop file search path" that match mozilla-firefox.desktop or firefox.desktop (note: the extensions can be omitted).

3. Pass a configuration file containing the settings for the target application on the command line:

In the example above, wmalauncher loads the settings from the configuration file /usr/share/wmalauncher/lighting.conf, then, configures the command, icon and tooltip-text according to the settings dedicated to the application firefox.

MX-Fluxbox uses wmalauncher to create a default menu icon when the toolbar is in legacy mode using this command:

```
wmalauncher --command xfce4-appfinder --icon /usr/local/share/icons/mxfcelogo-rounded.png -w 48 \,\&\,
```

That produces this launcher which, when clicked, opens the menu:



A launcher may be deleted by clicking Menu > Out of sight > Wmalauncher (in a terminal: *killall wmalauncher*).

Configuration files

For more about wmalauncher configuration files, see the section "CONFIGURATION FILE FORMAT" in the man page.

Wmalauncher comes with the following pre-defined configuration files in /usr/share/wmalauncher:

- lighting.conf
- multi-effects.conf
- old-school.conf
- frame-onthefly.conf
- wmaker-style.conf

Each of the predefined configuration files includes a global section for visual settings, along with entries for the following applications :

Development

- emacs
- geany
- gvim

Games

- darkplaces
- dhewm3
- gzdoom
- ioquake3
- iortcw
- quake2
- xboard

Graphics

- geeqie
- gimp
- gwenview
- krita
- libreoffice-draw
- xsane

Internet

- gftp
- google-chrome
- mozilla-firefox
- mozilla-thunderbird
- pan
- pidgin
- seamonkey
- transmission-gtk
- transmission-qt

Multimedia

- amarok
- audacious
- k3b
- kplayer
- mplayer
- pavucontrol
- xine
- xmms

Office

- libreoffice
 - o base
 - o calc
 - o impress
 - o math
 - startcenter

- o writer
- okular
- qpdfview
- scribus
- xpdf

System

- dolphin
- grsync
- htop
- konsole
- ksysguard
- thunar
- uxterm
- virtualbox
- xfce4-terminal
- xfe
- xterm
- xfce4-taskmanager

Utilities

- galculator
- gucharmap
- kate
- kcalc
- kwrite
- leafpad
- xarchiver
- xfce4-screenshooter

v. 20200119