

Default.aspx

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="PVFC._Default" %>
<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
    <title>My WEBSITE</title>
    <style>
        .linkStyle { display: inline-block; margin: 10px 0; }
    </style>
</head>
<body>
    <form id="form1" runat="server">
        <h2>Role Base Access Control</h2>
        <asp:HyperLink ID="lnkTask1Problem" runat="server"
            NavigateUrl="Problem_Statement.txt"
            CssClass="linkStyle">Problem Statement</asp:HyperLink><br />

        <asp:HyperLink ID="lnkTask1Report" runat="server"
            NavigateUrl="Code_Implementation_Report.pdf"
            CssClass="linkStyle">Code Implementation Report</asp:HyperLink><br />

        <asp:HyperLink ID="lnkTask1Output" runat="server"
            NavigateUrl="Sample_Output.pdf"
            CssClass="linkStyle">Sample Output</asp:HyperLink><br />

        <asp:HyperLink ID="lnkTask1Demo" runat="server"
            NavigateUrl="login.aspx"
            CssClass="linkStyle">Demonstration Page</asp:HyperLink><br />
    </form>
</body>
</html>
```

Default.aspx.cs

```
using System;
using System.Web.UI;

namespace PVFC
{
    public partial class _Default : System.Web.UI.Page
    {
        protected void Page_Load(object sender, EventArgs e)
        {

        }
    }
}
```

Login.aspx

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Login.aspx.cs"
Inherits="PVFC.Login" %>

<html>
<body>
<form runat="server">

<h2>User Login</h2>

Username:<br />
<asp:TextBox ID="txtUser" runat="server" /><br /><br />

Password:<br />
<asp:TextBox ID="txtPass" runat="server" TextMode="Password" /><br /><br />

<asp:Button ID="btnLogin" runat="server"
    Text="Login"
    OnClick="btnLogin_Click" />

<br /><br />

<asp:Label ID="lblMsg" runat="server" ForeColor="Red" />

<br /><br />

<asp:HyperLink ID="lnkRegister" runat="server"
    NavigateUrl="CustomerRegistration.aspx">
    Register Now
</asp:HyperLink>

</form>
</body>
</html>
```

Login.aspx.cs

```
using System;
using System.Data.SqlClient;
using System.Configuration;

namespace PVFC
{
    public partial class Login : System.Web.UI.Page
    {
        string connStr =
        ConfigurationManager.ConnectionStrings["PVFCConnectionString"].ConnectionString;

        protected void btnLogin_Click(object sender, EventArgs e)
        {
            using (SqlConnection con = new SqlConnection(connStr))
            {
                con.Open();

                SqlCommand cmd = new SqlCommand(@"
                SELECT UserID
```

```

        FROM Users
        WHERE Username=@u AND Password=@p AND IsActive=1", con);

cmd.Parameters.AddWithValue("@u", txtUser.Text);
cmd.Parameters.AddWithValue("@p", txtPass.Text);

object userId = cmd.ExecuteScalar();

if (userId == null)
{
    lblMsg.Text = "Invalid username or password!";
    return;
}

int uid = Convert.ToInt32(userId);

Session["UserID"] = uid;

SqlCommand cmdRole = new SqlCommand(@"
    SELECT r.RoleName
    FROM UserRoles ur
    JOIN Roles r ON ur.RoleID = r.RoleID
    WHERE ur.UserID=@uid", con);

cmdRole.Parameters.AddWithValue("@uid", uid);

string role = cmdRole.ExecuteScalar()?.ToString();

if (role == null)
{
    lblMsg.Text = "No role assigned!";
    return;
}

Session["Role"] = role;

if (role == "Admin")
{
    Response.Redirect("AdminDashboard.aspx");
}
else if (role == "Manager")
{
    Response.Redirect("ManagerDashboard.aspx");
}
else if (role == "Salesperson")
{
    Response.Redirect("SalesDashboard.aspx");
}
else if (role == "Customer")
{
    Response.Redirect("CustomerDashboard.aspx");
}
else
{
    lblMsg.Text = "Unknown role!";
}
}
}

```

```
}  
}
```

CustomerDashboard.aspx

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="CustomerDashboard.aspx.cs"  
Inherits="PVFC.CustomerDashboard" %>
```

```
<!DOCTYPE html>  
<html xmlns="http://www.w3.org/1999/xhtml">  
<head runat="server">  
<title>Customer Store</title>  
</head>  
  
<body>  
  
<form id="form1" runat="server">  
  
<h2>Available Products</h2>  
  
<ul>  
<li>End Table</li>  
<li>Coffee Table</li>  
<li>Computer Desk</li>  
<li>Entertainment Center</li>  
<li>Writers Desk</li>  
<li>8-Drawer Desk</li>  
<li>Dining Table</li>  
<li>Computer Desk Walnut</li>  
</ul>  
  
<hr />  
  
Search Product:<br />  
  
<asp:TextBox ID="txtSearch" runat="server"></asp:TextBox>  
  
<asp:Button ID="btnSearch"  
runat="server"  
Text="Search"  
OnClick="btnSearch_Click" />  
  
<br /><br />  
  
<asp:GridView ID="gvProducts"  
runat="server"  
AutoGenerateColumns="False"  
DataKeyNames="Product_Id"  
OnRowCommand="gvProducts_RowCommand">  
  
<Columns>
```

```

<asp:BoundField DataField="Product_Id" HeaderText="Product ID" />
<asp:BoundField DataField="Product_Description" HeaderText="Product Name" />
<asp:BoundField DataField="Product_Finish" HeaderText="Finish" />
<asp:BoundField DataField="Standard_Price" HeaderText="Price" />

<asp:ButtonField
Text="Add To Cart"
CommandName="AddProduct"
ButtonType="Button" />

</Columns>

</asp:GridView>

<br />

<asp:Label ID="lblMsg"
runat="server"
ForeColor="Green"></asp:Label>

<asp:Button ID="btnCheckout"
runat="server"
Text="Proceed to Checkout"
OnClick="btnCheckout_Click" />

</form>

</body>
</html>

```

CustomerDashboard.aspx.cs

```

using System;
using System.Configuration;
using System.Data;
using System.Data.SqlClient;
using System.Web.UI.WebControls;

namespace PVFC
{
    public partial class CustomerDashboard : BasePage
    {
        string connStr =
ConfigurationManager.ConnectionStrings["PVFCConnectionString"].ConnectionString;

        protected void Page_Load(object sender, EventArgs e)
        {
            CheckAccess(new string[] { "Customer", "Admin", "Manager", "Salesperson" });
        }

        protected void btnSearch_Click(object sender, EventArgs e)
        {
            string searchText = txtSearch.Text.Trim();

            using (SqlConnection con = new SqlConnection(connStr))

```

```

        {
            string query = @"SELECT Product_Id,
                                Product_Description,
                                Product_Finish,
                                Standard_Price
                                FROM PRODUCT_t
                                WHERE Product_Description LIKE '%' + @search + '%';

            SqlCommand cmd = new SqlCommand(query, con);

            cmd.Parameters.AddWithValue("@search", searchText);

            SqlDataAdapter da = new SqlDataAdapter(cmd);

            DataTable dt = new DataTable();

            da.Fill(dt);

            gvProducts.DataSource = dt;
            gvProducts.DataBind();
        }
    }

    protected void gvProducts_RowCommand(object sender, GridViewCommandEventArgs e)
    {
        if (e.CommandName == "AddProduct")
        {
            int index = Convert.ToInt32(e.CommandArgument);
            int productId = Convert.ToInt32(gvProducts.DataKeys[index].Value);

            Session["SelectedProduct"] = productId;

            lblMsg.Text = "Product added! Now click Checkout.";
        }
    }

    protected void btnCheckout_Click(object sender, EventArgs e)
    {
        if (Session["SelectedProduct"] == null)
        {
            lblMsg.Text = "Please select a product first!";
            return;
        }

        Response.Redirect("ProductSelection.aspx");
    }
}
}

```

AdminDashboard.aspx

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="AdminDashboard.aspx.cs"
Inherits="PVFC.AdminDashboard" %>
<html>

```

```

<body>
  <form runat="server">
<h2>Admin Dashboard</h2>
<asp:HyperLink runat="server" NavigateUrl="ProductCatalogUpdate.aspx">Product Catalog
Update</asp:HyperLink><br /><br />
<asp:HyperLink runat="server" NavigateUrl="ProductSearch.aspx">Product
Search</asp:HyperLink><br /><br />
<asp:HyperLink runat="server" NavigateUrl="CustomerDashboard.aspx">Product
Selection</asp:HyperLink><br /><br />
<asp:HyperLink runat="server" NavigateUrl="PaymentProvision.aspx">Payment
Provision</asp:HyperLink>

</form>
</body>
</html>

```

AdminDashboard.aspx.cs

```

using System;

namespace PVFC
{
    public partial class AdminDashboard : BasePage
    {
        {
            protected void Page_Load(object sender, EventArgs e)
            {
                CheckAccess(new string[] { "Admin" });
            }
        }
    }
}

```

ManagerDashboard.aspx

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="ManagerDashboard.aspx.cs"
Inherits="PVFC.ManagerDashboard" %>

```

```

<html>
<body>
<form runat="server">

<h2>Manager Dashboard</h2>

<asp:HyperLink runat="server" NavigateUrl="ProductSearch.aspx">
    Product Search
</asp:HyperLink>
<br /><br />

<asp:HyperLink runat="server" NavigateUrl="CustomerDashboard.aspx">
    Product Selection
</asp:HyperLink>
<br /><br />

<asp:HyperLink runat="server" NavigateUrl="PaymentProvision.aspx">
    Payment Provision
</asp:HyperLink>

```

```
</form>
</body>
</html>
```

ManagerDashboard.aspx.cs

```
using System;

namespace PVFC
{
    public partial class ManagerDashboard : BasePage
    {
        protected void Page_Load(object sender, EventArgs e)
        {
            CheckAccess(new string[] { "Manager" });
        }
    }
}
```

SalespersonDashboard.aspx

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="SalesDashboard.aspx.cs"
Inherits="PVFC.SalesDashboard" %>
<html>
<body>
<form runat="server">
<h2>Salesperson Dashboard</h2>
<asp:HyperLink runat="server" NavigateUrl="CustomerDashboard.aspx">Product
Selection</asp:HyperLink><br /><br />
<asp:HyperLink runat="server" NavigateUrl="PaymentProvision.aspx">Payment
Provision</asp:HyperLink>

</form>
</body>
</html>
```

SalespersonDashboard.aspx.cs

```
using System;

namespace PVFC
{
    public partial class SalesDashboard : BasePage
    {
        protected void Page_Load(object sender, EventArgs e)
        {
            CheckAccess(new string[] { "Salesperson" });
        }
    }
}
```


CustomerRegistration.aspx

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="CustomerRegistration.aspx.cs"
Inherits="PVFC.CustomerRegistration" %>
```

```
<!DOCTYPE html>
<html>
<head runat="server">
    <title>Customer Registration</title>
</head>
<body>
<form id="form1" runat="server">
    <h2>New Customer Registration</h2>

    Customer ID:<br />
    <asp:TextBox ID="txtId" runat="server" /><br /><br />

    Customer Name:<br />
    <asp:TextBox ID="txtName" runat="server" /><br /><br />

    Address:<br />
    <asp:TextBox ID="txtAddress" runat="server" /><br /><br />

    State:<br />
    <asp:TextBox ID="txtState" runat="server" /><br /><br />

    City:<br />
    <asp:DropDownList ID="ddlCity" runat="server" AutoPostBack="true"
        OnSelectedIndexChanged="ddlCity_SelectedIndexChanged">
        <asp:ListItem Text="Lahore" Value="54000" />
        <asp:ListItem Text="Karachi" Value="74000" />
        <asp:ListItem Text="Islamabad" Value="44000" />
        <asp:ListItem Text="Rawalpindi" Value="46000" />
    </asp:DropDownList><br /><br />

    Postal Code:<br />
    <asp:TextBox ID="txtPostal" runat="server" ReadOnly="true" /><br /><br />

    Username:<br />
    <asp:TextBox ID="txtUsername" runat="server" /><br /><br />

    Password:<br />
    <asp:TextBox ID="txtPassword" runat="server" TextMode="Password" /><br /><br />
    <asp:Button ID="btnRegister" runat="server"
        Text="Register Customer"
        OnClick="btnRegister_Click" />

    <br /><br />
    <asp:Label ID="lblMsg" runat="server" ForeColor="Green" />
</form>
</body>
</html>
```

CustomerRegistration.aspx.cs

```
using System;
using System.Configuration;
using System.Data.SqlClient;
```

```
namespace PVFC
{
```

```

public partial class CustomerRegistration : System.Web.UI.Page
{
    string connStr =
ConfigurationManager.ConnectionStrings["PVFCCConnectionString"].ConnectionString;

    protected void Page_Load(object sender, EventArgs e)
    {
        if (!IsPostBack)
        {
            ddlCity.Items.Insert(0, new System.Web.UI.WebControls.ListItem("Select
City", ""));
        }
    }

    protected void ddlCity_SelectedIndexChanged(object sender, EventArgs e)
    {
        txtPostal.Text = ddlCity.SelectedValue;
    }

    protected void btnRegister_Click(object sender, EventArgs e)
    {
        try
        {
            using (SqlConnection con = new SqlConnection(connStr))
            {
                con.Open();

                string q1 = @"INSERT INTO CUSTOMER_t
(Customer_Id, Customer_Name, Customer_Address, Customer_City,
Customer_State, Postal_Code)
VALUES
(@Id, @Name, @Address, @City, @State, @Postal)";

                SqlCommand cmd1 = new SqlCommand(q1, con);
                cmd1.Parameters.AddWithValue("@Id", txtId.Text);
                cmd1.Parameters.AddWithValue("@Name", txtName.Text);
                cmd1.Parameters.AddWithValue("@Address", txtAddress.Text);
                cmd1.Parameters.AddWithValue("@City", ddlCity.SelectedItem.Text);
                cmd1.Parameters.AddWithValue("@State", txtState.Text);
                cmd1.Parameters.AddWithValue("@Postal", txtPostal.Text);

                cmd1.ExecuteNonQuery();

                string q2 = @"INSERT INTO Users(Uname, Password)
VALUES(@u,@p); SELECT SCOPE_IDENTITY()";

                SqlCommand cmd2 = new SqlCommand(q2, con);
                cmd2.Parameters.AddWithValue("@u", txtUsername.Text);
                cmd2.Parameters.AddWithValue("@p", txtPassword.Text);

                int userId = Convert.ToInt32(cmd2.ExecuteScalar());

                SqlCommand cmd3 = new SqlCommand("INSERT INTO UserRoles
VALUES(@uid,4)", con);
                cmd3.Parameters.AddWithValue("@uid", userId);
                cmd3.ExecuteNonQuery();

                Session["UserID"] = userId;
            }
        }
    }
}

```

```

        Session["CustomerID"] = txtId.Text;

        Response.Redirect("ProductSelection.aspx");
    }
}
catch (Exception ex)
{
    lblMsg.Text = "Error: " + ex.Message;
}
}
}
}
}

```

ProductSelection.aspx

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="ProductSelection.aspx.cs"
Inherits="PVFC.ProductSelection" %>

```

```

<!DOCTYPE html>
<html>
<head runat="server">
<title>Product Selection</title>
</head>

<body>

<form id="form1" runat="server">

<h2>Confirm Your Order</h2>

<asp:Label ID="lblProduct" runat="server"></asp:Label>

<br /><br />

Quantity:<br />
<asp:TextBox ID="txtQuantity" runat="server" Text="1"></asp:TextBox>

<br /><br />

<asp:Button ID="btnConfirm"
runat="server"
Text="Confirm Order"
OnClick="btnConfirm_Click" />

<br /><br />

<asp:Label ID="lblMsg" runat="server"></asp:Label>

</form>

</body>
</html>

```

ProductSelection.aspx.cs

```

using System;
using System.Configuration;
using System.Data.SqlClient;

```

```

namespace PVFC
{
    public partial class ProductSelection : BasePage
    {
        string connStr =
        ConfigurationManager.ConnectionStrings["PVFCCConnectionString"].ConnectionString;

        protected void Page_Load(object sender, EventArgs e)
        {
            if (Session["UserID"] == null)
            {
                Response.Redirect("Login.aspx");
                return;
            }

            if (!IsPostBack)
            {
                if (Session["SelectedProduct"] == null)
                {
                    Response.Redirect("CustomerDashboard.aspx");
                    return;
                }

                lblProduct.Text = "Selected Product ID: " +
                Session["SelectedProduct"].ToString();
            }
        }

        protected void btnConfirm_Click(object sender, EventArgs e)
        {
            try
            {
                if (Session["SelectedProduct"] == null || Session["UserID"] == null)
                {
                    lblMsg.Text = "Invalid session.";
                    return;
                }

                int productId = Convert.ToInt32(Session["SelectedProduct"]);
                int quantity = Convert.ToInt32(txtQuantity.Text);
                int userId = Convert.ToInt32(Session["UserID"]);

                using (SqlConnection con = new SqlConnection(connStr))
                {
                    con.Open();

                    SqlCommand cmdOrder = new SqlCommand(@"
                    INSERT INTO Orders_t (UserID, Order_Date)
                    OUTPUT INSERTED.Order_Id
                    VALUES (@uid, GETDATE())", con);

                    cmdOrder.Parameters.AddWithValue("@uid", userId);

                    int orderId = Convert.ToInt32(cmdOrder.ExecuteScalar());

                    SqlCommand cmdLine = new SqlCommand(@"
                    INSERT INTO Order_line_t (Order_Id, Product_Id,
                    Ordered_Quantity)

```

```

VALUES (@oid, @pid, @qty)", con);

cmdLine.Parameters.AddWithValue("@oid", orderId);
cmdLine.Parameters.AddWithValue("@pid", productId);
cmdLine.Parameters.AddWithValue("@qty", quantity);

cmdLine.ExecuteNonQuery();

Session["OrderID"] = orderId;

lblMsg.Text = "Order placed successfully!";
Response.Redirect("PaymentProvision.aspx");
    }
}
catch (Exception ex)
{
    lblMsg.Text = ex.Message;
}
}
}
}

```

ProductSearch.aspx

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="ProductSearch.aspx.cs"
Inherits="PVFC.ProductSearch" %>

```

```

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Product Search</title>
    <style>
        body {
            font-family: Arial, sans-serif;
            background-color: #f2f2f2;
        }
        form
        {
            width: 800px;
            margin: 40px auto;
            padding: 25px;
            background-color: white;
            border: 1px solid #ccc;
        }
        h2
        {
            text-align: center;
            margin-bottom: 20px;
        }
        input, select
        { width: 200px;
          padding: 5px;
          margin-bottom: 15px;
        }
        .btnSearch

```

```

        {
            padding: 6px 12px;
        }
        #GridView1
        {
            margin-top: 20px;
            width: 100%;
            border-collapse: collapse;

        }
        #GridView1 th, #GridView1 td
        {
            border: 1px solid #ccc;
            padding: 5px;
            text-align: left;
        }
    }
</style>
</head>
<body>
    <form id="form1" runat="server">
        <h2>Product Search</h2>

        <label>Enter Product Name:</label><br />
        <asp:TextBox ID="txtSearch" runat="server"></asp:TextBox><br />

        <asp:Button ID="btnSearch" runat="server" Text="Search Product"
        CssClass="btnSearch"
            OnClick="btnSearch_Click" /><br />

        <asp:GridView ID="GridView1" runat="server"
        AutoGenerateColumns="true"></asp:GridView>
        <asp:Button ID="btnBack" runat="server" Text="Back to Dashboard"
        OnClick="btnBack_Click" />
        <asp:Label ID="lblMsg" runat="server" ForeColor="Red"></asp:Label>
    </form>
</body>
</html>

```

ProductSearch.aspx.cs

```

using System;
using System.Configuration;
using System.Data;
using System.Data.SqlClient;
using System.Web.UI.WebControls;

namespace PVFC
{
    public partial class ProductSearch : BasePage
    {
        string connStr =
        ConfigurationManager.ConnectionStrings["PVFCCConnectionString"].ConnectionString;

        protected void btnBack_Click(object sender, EventArgs e)
        {
            RedirectToDashboard();
        }
        protected void btnSearch_Click(object sender, EventArgs e)
        {

```

```

        string searchText = txtSearch.Text.Trim();

        if (string.IsNullOrEmpty(searchText))
        {
            GridView1.DataSource = null;
            GridView1.DataBind();
            return;
        }

        try
        {
            using (SqlConnection con = new SqlConnection(connStr))
            {
                string query = @"SELECT Product_Id, Product_Description,
Product_Finish, Standard_Price
                                FROM PRODUCT_t
                                WHERE Product_Description LIKE '%' + @search +
                                '%';

                SqlCommand cmd = new SqlCommand(query, con);
                cmd.Parameters.AddWithValue("@search", searchText);

                SqlDataAdapter da = new SqlDataAdapter(cmd);
                DataTable dt = new DataTable();
                da.Fill(dt);

                GridView1.DataSource = dt;
                GridView1.DataBind();
            }
        }
        catch (Exception ex)
        {
            lblMsg.Text = "Error: " + ex.Message;
        }
    }
}
}

```

ProductCatalogUpdate.aspx

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="ProductCatalogUpdate.aspx.cs"
Inherits="PVFC.ProductCatalogUpdate" %>

```

```

<!DOCTYPE html>
<html>
<head runat="server">
    <title>Product Catalog Update</title>
</head>
<body>
<form id="form1" runat="server">
    <h2>Product Catalog Update</h2>

    Product ID:<br />
    <asp:TextBox ID="txtProductId" runat="server" /><br /><br />

    Product Line:<br />

```

```

<asp:DropDownList ID="ddlProductLine" runat="server">
    <asp:ListItem Text="Select Line" Value="" />
    <asp:ListItem Text="Cherry Tree" Value="1" />
    <asp:ListItem Text="Scandinavia" Value="2" />
    <asp:ListItem Text="Country Look" Value="3" />
</asp:DropDownList><br /><br />

Description:<br />
<asp:TextBox ID="txtDescription" runat="server" /><br /><br />

Finish:<br />
<asp:TextBox ID="txtFinish" runat="server" /><br /><br />

Standard Price:<br />
<asp:TextBox ID="txtPrice" runat="server" /><br /><br />

<asp:Button ID="btnUpdate" runat="server"
    Text="Update Product"
    OnClick="btnUpdate_Click" />

<br /><br />
<asp:Label ID="lblMsg" runat="server" ForeColor="Green" />
</form>
</body>
</html>

```

ProductCatalogUpdate.aspx.cs

```

using System;
using System.Configuration;
using System.Data.SqlClient;

namespace PVFC
{
    public partial class ProductCatalogUpdate : BasePage
    {
        protected void Page_Load(object sender, EventArgs e)
        {
            if (Request.QueryString["redirect"] == "1")
            {
                RedirectToDashboard();
            }
        }

        string connStr =
ConfigurationManager.ConnectionStrings["PVFCCConnectionString"].ConnectionString;

        protected void btnUpdate_Click(object sender, EventArgs e)
        {
            try
            {
                using (SqlConnection con = new SqlConnection(connStr))
                {
                    string query = @"UPDATE PRODUCT_t
                        SET Product_Line_Id = @LineId,
                            Product_Description = @Desc,
                            Product_Finish = @Finish,
                            Standard_Price = @Price
                        WHERE Product_Id = @Pid";

                    using (SqlCommand cmd = new SqlCommand(query, con))
                    {

```



```

        cmd.Parameters.AddWithValue("@Pid", txtProductId.Text);
        cmd.Parameters.AddWithValue("@LineId",
ddlProductLine.SelectedValue);
        cmd.Parameters.AddWithValue("@Desc", txtDescription.Text);
        cmd.Parameters.AddWithValue("@Finish", txtFinish.Text);
        cmd.Parameters.AddWithValue("@Price", txtPrice.Text);

        con.Open();
        int rows = cmd.ExecuteNonQuery();

        if (rows > 0)
        {
            lblMsg.Text = "Product Updated Successfully!";

            ClientScript.RegisterStartupScript(this.GetType(),
"redirect",
                                "setTimeout(function(){ window.location =
'ProductCatalogUpdate.aspx?redirect=1'; }, 1500);", true);
        }
        else
        {
            lblMsg.Text = "Product ID Not Found!";
        }
    }
}
catch (Exception ex)
{
    lblMsg.Text = "Error: " + ex.Message;
}
}
}
}

```

PaymentProvision.aspx

```

<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="PaymentProvision.aspx.cs"
Inherits="PVFC.PaymentProvision" %>

```

```

<!DOCTYPE html>
<html>
<head runat="server">
<title>Payment Provision</title>

```

```

<style>

```

```

form{
width:420px;
margin:40px auto;
padding:25px;
border:1px solid #ccc;
background-color:white;
}

```

```

h2{
text-align:center;
}

```

```

input{

```

```
width:200px;
padding:5px;
}

button{
padding:6px 10px;
margin-right:5px;
}

</style>

</head>

<body>

<form id="form1" runat="server">

<h2>Payment Provision</h2>

Order ID:<br />
<asp:TextBox ID="txtOrderId" runat="server"></asp:TextBox>

<br /><br />

Account Number:<br />
<asp:TextBox ID="txtAccount" runat="server"></asp:TextBox>

<br /><br />

Payment Method:<br />

<asp:Button ID="btnCash"
runat="server"
Text="Cash"
OnClick="btnCash_Click" />

<asp:Button ID="btnOnline"
runat="server"
Text="Online"
OnClick="btnOnline_Click" />

<asp:Button ID="btnOthers"
runat="server"
Text="Others"
OnClick="btnOthers_Click" />

<br /><br />

<asp:Button ID="btnSubmit"
runat="server"
Text="Submit Payment"
OnClick="btnSubmit_Click" />

<br /><br />

<asp:Label ID="lblOutput"
runat="server"
ForeColor="Green"></asp:Label>

</form>
```

```
</body>
</html>
```

PaymentProvision.aspx.cs

```
using System;

namespace PVFC
{
    public partial class PaymentProvision : BasePage
    {
        protected void Page_Load(object sender, EventArgs e)
        {
            if (!IsPostBack)
            {
                if (Session["OrderID"] != null)
                {
                    txtOrderId.Text = Session["OrderID"].ToString();
                }
            }
        }

        protected void btnSubmit_Click(object sender, EventArgs e)
        {
            lblOutput.Text = "Payment successful for Order ID: " + txtOrderId.Text;

            Session["OrderID"] = null;
            Session["SelectedProduct"] = null;

            RedirectToDashboard();
        }

        protected void btnCash_Click(object sender, EventArgs e)
        {
            lblOutput.Text = "Cash selected";
        }

        protected void btnOnline_Click(object sender, EventArgs e)
        {
            lblOutput.Text = "Online selected";
        }

        protected void btnOthers_Click(object sender, EventArgs e)
        {
            lblOutput.Text = "Other payment selected";
        }
    }
}
```

BasePage.cs Class

```

using System;
using System.Web.UI;

namespace PVFC
{
    public class BasePage : Page
    {
        protected void CheckAccess(string[] allowedRoles)
        {
            if (Session["Role"] == null)
            {
                Response.Redirect("Login.aspx");
                return;
            }

            string role = Session["Role"].ToString();

            bool allowed = false;

            foreach (string r in allowedRoles)
            {
                if (r == role)
                {
                    allowed = true;
                    break;
                }
            }

            if (!allowed)
            {
                Response.Write("Access Denied!");
                Response.End();
            }
        }

        protected void RedirectToDashboard()
        {
            if (Session["Role"] == null)
            {
                Response.Redirect("Login.aspx");
                return;
            }

            string role = Session["Role"].ToString();

            switch (role)
            {
                case "Admin":
                    Response.Redirect("AdminDashboard.aspx");
                    break;

                case "Manager":
                    Response.Redirect("ManagerDashboard.aspx");
                    break;

                case "Salesperson":
                    Response.Redirect("SalesDashboard.aspx");
                    break;

                case "Customer":
                    Response.Redirect("CustomerDashboard.aspx");
                    break;
            }
        }
    }
}

```

```
        default:
            Response.Redirect("Login.aspx");
            break;
    }
}
}
```