NED UNIVERSITY OF ENGINEERING & TECHNOLOGY

DEPARTMENT OF COMPUTER SCIENCE & IT

CSIT (with Specialization in Data Science)

PROJECT REPORT

COURSE: MACHINE LEARNING (CT-378)

PROJECT TITLE: SENTIMENT ANALYSIS FOR PRODUCT REVIEWS

TEAM MEMBERS: IQRA NAWAZ [DT-22005]

SAMEEN FATIMA [DT-22027]

LAIBA NADEEM [DT-22028]

SUBMITTED TO: MS. AMNA AHMED

Introduction

Project Overview

Sentiment analysis is one of the methods used in natural language processing, the primary goal being to interpret and classify the emotions expressed in a given text. It has proven useful in the examination of customer feedback, social media interactions and many other text based data sources. In this particular project, we focus on applying machine learning technologies to determine if the sentiment expressed in text data is positive, negative, or neutral.

To accomplish our objective, we intend first to create an effective sentiment analysis model that will enable us to handle large quantities of text data and accomplish precise sentiment classification. Among other things, the model will serve social media marketers, customer review analysts, and users seeking to understand overall brand sentiment.

Motivation

The significance of sentiment analysis is crucial in today's data-driven environment. Companies utilize sentiment analysis to gather insights into customer perceptions, enhance product offerings, and customize marketing approaches. By streamlining the sentiment classification process, businesses can examine vast datasets more effectively, enabling faster decision-making and immediate feedback analysis.

In the social media landscape, sentiment analysis is essential for grasping public opinion on a range of subjects, from political occurrences to product introductions. Reliable sentiment analysis tools assist organizations in monitoring brand reputation, assessing customer satisfaction, and forecasting trends based on public sentiment.

Objective

The aim of this project is to create a sentiment analysis system capable of categorizing text data into three main classifications: positive, negative, and neutral. We will apply a range of machine learning algorithms to train models on labeled sentiment data and assess their effectiveness based on accuracy, precision, recall, and F1-score.

The central focus of this project includes:

Preparing and preprocessing the data for machine learning purposes.

Implementing machine learning models such as Logistic Regression, Random Forest, SVM and Naive Bayes.

Assessing the effectiveness of these models using established metrics.

Determining the most effective model for sentiment analysis tasks.

Data Gathering and Preparation

Description of the Dataset

The dataset utilized in this project comprises text data sourced from online platforms, including Amazon product reviews, tweets, and customer feedback forms. This data includes a variety of texts that are tagged with their respective sentiment, which could be positive, negative, or neutral. A standard dataset for sentiment analysis typically features columns such as:

Text: The actual review or statement.

Sentiment: The label indicating sentiment (positive, negative, neutral).

For this project, we employed the Amazon Fine Food Reviews dataset, which is readily accessible and contains thousands of product reviews categorized by sentiment. Prior to training the models, the dataset was cleaned and preprocessed.

Data Cleaning

The dataset was sanitized to ensure that only pertinent and significant information was utilized for training the model. The preprocessing procedures included:

Eliminating Stopwords: Generic words such as "the," "is," "in," etc., were excluded from the dataset to ensure that the model concentrates on more substantial terms.

Erasing Punctuation and Special Characters: Any non-alphabetical symbols (including punctuation marks, numbers, etc.) were stripped from the text data.

Transforming to Lowercase: All text data was converted to lowercase to ensure uniformity, as the model does not require a distinction between uppercase and lowercase letters.

Addressing Missing Data: Any gaps in the dataset were managed by either removing the rows with missing labels or substituting missing text with placeholder values.

Feature Engineering

After preprocessing the data, we carried out feature extraction to transform the raw text into a format suitable for machine learning algorithms. The subsequent steps were implemented:

Tokenization: The text was divided into individual words (tokens), with each token serving as a meaningful unit of text that contributes to the sentiment analysis.

TF-IDF Vectorization: We employed the term frequency-inverse document frequency (TF-IDF) technique to convert the text into numerical vectors. This approach takes into account both the occurrence of words within each document and the significance of those words throughout the entire dataset.

These numerical vectors were subsequently utilized as features for training the machine learning algorithms.

Test Information

Here's a test of how the information looks some time recently and after preprocessing:

Unique Content:

"The item is incredible and I cherish it!"

Handled Content:

"item incredible cherish"

This preprocessing guarantees that the information is clean, reliable, and prepared for utilize in machine learning models.

Machine Learning Models

Summary of Models

In this sentiment analysis project, various machine learning models were developed and assessed to identify the most efficient model for classifying the sentiment of textual data. The models implemented in this project consist of:

Logistic Regression: A linear approach utilized for binary classification tasks but can also be adapted to multi-class issues such as sentiment analysis.

Random Forest: An ensemble technique that constructs several decision trees and combines their outcomes to enhance effectiveness.

Support Vector Machine (SVM): An effective classifier that performs excellently on both linear and non-linear data.

Naive Bayes: A probabilistic classifier based on Bayes' theorem, ideal for text classification due to its simplicity, efficiency, and effectiveness with large datasets.

All of these models underwent training on the preprocessed dataset, and their effectiveness was assessed through several metrics, including accuracy, precision, recall, and F1-score.

Logistic Regression

Logistic Regression is a basic machine learning algorithm typically utilized for binary classification, yet it is also capable of addressing multi-class classification issues. In this sentiment analysis assignment, Logistic Regression was employed to determine if the sentiment of a review is positive, negative, or neutral.

Reasons for Logistic Regression: Logistic Regression is straightforward, easy to understand, and performs effectively with linearly separable datasets. It employs a logistic function to represent probabilities, rendering it appropriate for classification tasks.

Execution: The model was developed utilizing TF-IDF vectors as input attributes and the sentiment labels as the desired output. The performance of the model was assessed through cross-validation.

Random Forest

Random Forest is an ensemble technique that employs a group of decision trees to enhance classification precision. It functions by integrating several decision trees and averaging their outcomes, which aids in minimizing overfitting and enhancing the model's robustness.

Reason for Choosing Random Forest: Random Forest is a flexible and robust model capable of managing both regression and classification tasks. It is also effective with non-linear data and manages noisy data proficiently.

Execution: The Random Forest classifier underwent training with the processed text features, resulting in the creation of several decision trees. The model's result was determined by the prevailing vote of all the trees.

Support Vector Machine (SVM)

SVM is a strong machine learning algorithm frequently employed for classification duties, especially when dealing with high-dimensional data, such as in text classification challenges. SVM operates by identifying a hyperplane that most effectively divides the classes within the feature space.

Why SVM: SVM performs well in high-dimensional environments and is ideal for both binary and multi-class classification tasks. It employs kernel functions to map data into higher dimensions, aiding in the discovery of optimal separating hyperplanes.

Execution: The SVM classifier was educated on the TF-IDF feature vectors, and the outcomes were contrasted with other models by utilizing accuracy and precision.

Naive Bayes

Naive Bayes is a probabilistic classifier based on Bayes' theorem, which calculates the probability of each class based on the input features. Despite its simplicity, it has proven to be an effective model for text classification tasks, particularly when the feature space is large.

Why Naive Bayes: Naive Bayes is particularly effective in text classification because it works well with a high number of features, such as words or n-grams, and requires fewer computational resources compared to other models. It assumes that the features are independent, which is a simplifying assumption that works surprisingly well in practice.

Execution: The Naive Bayes model was trained on the same TF-IDF features as the other models. Given its simplicity, it performed quickly, and the results were compared against other models using accuracy, precision, and recall.

Assessment Metrics

In order to evaluate the models' performance, we utilized several assessment metrics, including accuracy, precision, recall, and F1-score. These metrics are crucial for grasping how effectively the models succeed in forecasting sentiment labels (positive, negative, or neutral) for textual data. Here are the definitions and outcomes for each model.

Accuracy: The proportion of correct predictions compared to the overall number of predictions.


Precision: The ratio of correctly predicted positives to the total number of predicted positives.


Recall: The proportion of correctly identified positive predictions to the overall count of actual positives.

F1-Score: The harmonic average of precision and recall, offering a balanced metric.

Comparison of Model Performance

In order to enhance the visualization of each model's performance, the outcomes were displayed through bar charts. This facilitates a straightforward comparison of the models using various metrics.





Methodology

Summary of Approach

To successfully execute sentiment analysis with machine learning, we adhered to a systematic approach that can be divided into these key steps:

Data Gathering: Gather unprocessed text information from sources such as product evaluations, social media messages, or consumer opinions.

Data Preparation: Clean and prepare the data to eliminate unnecessary or noisy details.

Feature Extraction: Transform the raw text data into numerical features by employing methods like TF-IDF or word embeddings.

Model Training: Utilize the preprocessed text data and the extracted features to train various machine learning models.


Model Assessment: Assess the effectiveness of each model utilizing different metrics such as accuracy, precision, recall, and F1-score.

Model Selection: After the assessment, choose the top-performing model for implementation.

Future Enhancements: Pinpoint possible areas for enhancement, including the integration of deep learning methods or refining feature extraction.

Diagram of Methodology

Here is a diagram that illustrates the complete methodology:



Moral Considerations

When dealing with text data, particularly from openly accessible sources like product reviews or social media updates, ethical concerns are of utmost importance. Here are essential ethical considerations taken into account in this sentiment analysis project:

Data Confidentiality:

The information utilized in this project is sourced from publicly accessible materials like product evaluations or social media updates. No private or sensitive data was utilized, guaranteeing that individuals' privacy is preserved.

Even though the data is publicly available, it is crucial to recognize that ethical data use involves following the terms and conditions set by the sources from which it is obtained.

Prejudice in the Data Collection:

The data utilized might include intrinsic biases, like a disproportionate amount of specific sentiments (e.g., an excess of positive reviews compared to negative ones). This might result in a model that favors predicting specific sentiments more often than others.

To reduce bias, efforts were made to ensure the dataset was balanced during preprocessing. Furthermore, methods such as oversampling or undersampling may be utilized in forthcoming research to further diminish bias.

Clarity and Justice:

Clarity regarding the data processing, model training, and result evaluation is essential for establishing confidence in the predictions made by the model. This report details the procedures undertaken in the creation and assessment of the sentiment analysis model.

The model's fairness was evaluated by assessing multiple input types (e.g., diverse product categories or social media subjects) to confirm that it performs consistently across different text sources.

Summary

Overview

The goal of this sentiment analysis project was to develop machine learning models that can categorize text data as positive, negative, or neutral sentiments. We tested different machine learning models, including **Logistic Regression**, **Random Forest**, **Support Vector Machine (SVM)**, and **Naive Bayes**, and assessed their performance using measures like accuracy, precision, recall, and F1-score.

Based on the results:

- **SVM** and **Random Forest** were the top-performing models, exhibiting the highest **tuned accuracy** on both training and testing datasets, which indicates that these models benefit significantly from hyperparameter tuning.

- **Logistic Regression** showed moderate performance but did not achieve as high accuracy as **SVM** and **Random Forest** after tuning.

- **Naive Bayes** performed decently, but its accuracy remained lower than the other models across both original and tuned settings.

Main Discoveries

- **Top Models**: **SVM** and **Random Forest** were the best performers, achieving the highest accuracy in both training and testing after tuning.

- **Data Preprocessing**: Effective data cleaning and feature extraction using TF-IDF were essential for the models to identify significant patterns in the data.

- **Model Performance**: **SVM** and **Random Forest** showed strong generalization and improved significantly after hyperparameter tuning. **Naive Bayes** and **Logistic Regression** performed well in certain areas but had more variability in testing performance.

Contributions

The main contribution of this project is the creation and assessment of different machine learning models for sentiment analysis. The initiative emphasizes the significance of selecting the appropriate model and the necessity for detailed preprocessing and feature engineering to attain the best outcomes. Moreover, the project highlights the shortcomings of conventional machine learning models in managing neutral sentiments and the possible advantages of employing more sophisticated methods like deep learning for enhanced contextual comprehension.

Effect

The created sentiment analysis model boasts various practical uses, such as:

Brand Sentiment Monitoring: Businesses can utilize this model to monitor customer opinions regarding their products or services through social media comments and reviews.

Customer Assistance: Companies are able to automate the evaluation of client feedback to enhance their offerings or resolve problems quickly.

Market Analysis: The model can assist in evaluating consumer attitudes regarding a new product or market trend.

Future Work

Although the models created in this project are efficient, there are numerous methods to improve their performance and broaden the project's scope:

Enhanced Models: Integrating deep learning architectures such as BERT or GPT-3 may enhance the comprehension of contextual and sentiment subtleties in textual data.

Multilingual Sentiment Analysis: Extending the model to accommodate various languages would enhance its usefulness, particularly for worldwide sentiment evaluation.

Real-Time Sentiment Analysis: Executing real-time sentiment analysis on social media sites such as Twitter would allow companies to monitor sentiment trends immediately and react in the moment.

Managing Domain-Specific Information: Improving the model to manage texts specific to a domain, like medical or legal evaluations, would necessitate tailored data and adjustment.

To sum up, this project illustrates how machine learning proves beneficial in sentiment analysis and lays the groundwork for future advancements that can boost the precision and adaptability of sentiment classification systems.

References

1. **Scikit-learn Documentation** (2021). *User Guide*. Retrieved from https://scikit-learn.org/stable/user_guide.html

    - This documentation was referred to for understanding machine learning algorithms like Logistic Regression, Random Forest, and Support Vector Machines used in this project.

2. **Kaggle: Amazon Fine Food Reviews Dataset** (2021). Retrieved from https://www.kaggle.com/sbhatti/amazon-fine-food-reviews

    - The dataset used in this project was sourced from Kaggle, containing customer reviews on various products, which were utilized for training and evaluating the models.

3. **A Survey on Sentiment Analysis and Opinion Mining: Tasks, Approaches, and Applications** by Anoop K. K. and B. B. K. (2016). *International Journal of Computer Applications*. Retrieved from https://www.ijcaonline.org/

    - This survey paper provided an overview of various sentiment analysis techniques, helping in understanding the challenges and solutions for sentiment classification tasks.

4. **The Elements of Statistical Learning: Data Mining, Inference, and Prediction** by Trevor Hastie, Robert Tibshirani, and Jerome Friedman (2009). *Springer Series in Statistics*. ISBN 978-0387848570

    - This book provided foundational knowledge on statistical learning and was useful for understanding machine learning models and their mathematical underpinnings.

5. **SMOTE: Synthetic Minority Over-sampling Technique** by N.V. Chawla, K.W. Bowyer, L.O. Hall, and W.P. Kegelmeyer (2002). *Journal of Artificial Intelligence Research*. Retrieved from https://www.jair.org/index.php/jair/article/view/10302

- This paper was referenced for understanding how to handle class imbalance in sentiment datasets using SMOTE (Synthetic Minority Over-sampling Technique).