Assignment#5: Perceptron

- Part 1
  - Plot data from data.csv
  - Implement perceptron using the heuristic approach (left box next page)
  - Plot the initial separation line as red, subsequent ones after each iteration in dashed green, and the last one in black (see page 4)
  - Play with the learning rate
  - Analysis the results in a report

- Part 2
  - Plot data from data.csv
  - Implement perceptron using the Gradient Descent approach (right box next page)
  - Play with learning rate, number of epochs.
  - Plot the initial separation line as red, subsequent ones after each iteration in dashed green, and the last one in black
  - Compute log loss (error) and plot the error graph every 10 epoch (see page 5)
  - Analysis the results in a report

Learning by Gradient Descent (Right Side)

1. Start a perceptron with random weights and bias: w_1, w_2, …, w_n, b
2. For **each of** all points (data) with their corresponding labels (answers):
   - 2.1. Classify according to the perceptron
   - 2.2. For a misclassified point $(x_1, x_2, …, x_n)$:
     - 2.2.1. If classification==0:
       - 2.2.1.1. $b + r \rightarrow b$
       - 2.2.1.2. For all w_i: $w_i + rx_i \rightarrow w_i$
     - 2.2.2. If classification==1:
       - 2.2.2.1. $b - r \rightarrow b$
       - 2.2.2.2. For all w_i: $w_i - rx_i \rightarrow w_i$
3. Repeat #2 <u>enough</u> number of times

Earlier heuristic approach with binary classification

1. Start a perceptron with random weights and bias: w_1, w_2, …, w_n, b
2. For **each of** all points (data) with their corresponding labels (answers):
   - 2.1. Compute prediction output (ŷ)
   - 2.2. Compute error function (y - ŷ)
   - 2.3. $b + r$**(y - ŷ)** $\rightarrow b$
   - 2.4. For all w_i: $w_i + r$**(y - ŷ)**$x_i \rightarrow w_i$
3. Repeat #2 until **error is small**

*Note: **ŷ** is no longer 0 or 1 from a step function. See next page*

Perceptron

- Linear Function → Biased Sum of Weighted input

z = WX + b

$$= W \cdot X^t + b$$

$$= \sum_{i=1}^{n} W_i x_i + b$$

- Sigmoid → **Continuous** Classification

$\hat{y} = \sigma (WX + b)$

weights adjustment

x_1 w_1

x_2 w_2

..

..

..

..

w_n

x_n

b

1

$\sigma(z) = \dfrac{1}{1 + e^{-z}}$

where: z = WX + b

$\hat{y}$

error function

# Learning rate (samples, your results may be different)

learning_rate = 0.01

iteration = 65

learning_rate = 0.1

iteration = 65

learning_rate = 1

iteration = 65

For Part 2 (samples, your results may be different)

Submission

- In Canvas Assignments:

  - **Submit as File Uploads**: A PDF report with snippets of your code, all the plots and the analysis of them.

  - **Submit as Web URL**: Link to your Github repo/project/ with folder name Assignment_4, which include all your Jupyter Notebook code and any other associated files.

- Make sure you have invited me to your Github repo/project/folder

Grading Rubric (Total 100% of 10 pts in final grade)

- Data Loading (10%)
  - Dataset is correctly retrieved and plotted.
- Part1 Implementation (40%)
  - Experiments with learning rate and number of epochs
  - Analysis of results
- Part 2 Implementation (40%)
  - Experiments with learning rate and number of epochs
  - Analysis of results
- PDF Report (10%)