





















ECN. REV NO. APPD. **OEM** Α NOTES: 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5-1982 2. THE DIMENSIONS MARKED TO WILL BE CHECKED BY QC AND PROCESS ENGINEERS. ∴ MATERIAL: SWC DIAMETER=ø1.20±0.05mm. THE SPRING PARAMETER SEE THE FOLLOWING TABLE. 4 SURFACE FINISH: SEE TABLE. 5. ALL SHARP EDGES TO BE ROUNDED TO PREVENT INJURY. 6. MATERIAL SHOULD BE IN ACCORDANCE WITH FOXCONN ENVIRONMENTIAL SPEC. EMT-D00-079. В В C **PARAMETERS** MATERIAL SWC MATERIAL DIAMETER ø1.20 D D THREAD OUTER DIAMETER ø7.4 THREAD INNER DIAMETER ø5.0 WINDING DIRECTION **RIGHT** FREE HEIGHT (mm) 17.5 LOAD(b) 18.9±10% LOAD HEIGHT(mm) 11.2 SPRING CONSTANT(b/mm) 3.0±10% **FINISHED** NI-PLATING Ε UNITS NAME(INTENDED USE) FOXCONN X.°± 2° X.± mm HON HAI PRECISION IND. CO.,LTD. MAT'L $.x \pm 0.50$.X°± GX100 TAIPEI, TAIWAN, R.O.C. PART NO.(INTENDED USE) TITLE: $.XX \pm 0.30$.XX°± CUSTOMER DRAWING PHG199GB0012(Z)

DWG NO.:

SCALE | SHEET

12/12

N/A

REV.

Α

Ε

.XXX±

FINISH

Q'TY

APPD:

CHKD:

DR:

12

.XXX°±

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI

PRECISION IND. CO., LTD.