Introduction

Please find two other learning partners,

- form a standing group and
- tell them what you already know about
 - graphs,
 - graph databases and
 - ▶ Neo4j.

Graph Data - Modelling and Querying with Neo4j and Cypher

Iryna Feuerstein

Graph Database - NRW Meetup

6 December 2017



Learning goals

What are graphs?

Definition
Use cases

Starting with Neo4j and Cypher Configuration and start CRUD operations with Cypher

Quering for paths and patterns

Using graph algorithms apoc library algo library

Importing data

Refactoring graph data model

Graph

Definition


Graph is an ordered pair G = (V, E) comprising a set V of vertices, nodes or points together with a set E of edges, arcs or lines, which are 2-element subsets of V.

¹en.wikipedia.org/wiki/Graph_(discrete_mathematics)

Graph

Definition

Graph is an ordered pair G = (V, E) comprising a set V of vertices, nodes or points together with a set E of edges, arcs or lines, which are 2-element subsets of V.



¹en.wikipedia.org/wiki/Graph_(discrete_mathematics)

Networks

- Networks
 - Social networks




Networks


Social networks



Computer networks




- Networks
 - Transport networks




OC = Oxford Circus, LS = Leicester Square HB = Holborn, PC = Piccadilly Circus

TC = Tottenham Court Road


Natural Language Processing



Document management



Biochemistry / Genomics



Practice activity - Graph modeling

- Come up with any use case idea of your choice.
- ► Model it as a graph on a sheet of paper.
- Introduce it to at least one of the attendees.

► Find the right installation file for your OS at neo4j-training-files/neo4j on the flash drive and install the software.

- ► Find the right installation file for your OS at neo4j-training-files/neo4j on the flash drive and install the software.
- ► Linux-Users: Copy both JAR-files from the neo4j-training-files/plugins directory into NEO4J_HOME/plugins directory of your Neo4j installation.

- ► Find the right installation file for your OS at neo4j-training-files/neo4j on the flash drive and install the software.
- ► Linux-Users: Copy both JAR-files from the neo4j-training-files/plugins directory into NEO4J_HOME/plugins directory of your Neo4j installation.
- ► Mac-Users: Copy the plugins directory into your /Application/Neo... and into graph.db/plugins

- ► Find the right installation file for your OS at neo4j-training-files/neo4j on the flash drive and install the software.
- ► Linux-Users: Copy both JAR-files from the neo4j-training-files/plugins directory into NEO4J_HOME/plugins directory of your Neo4j installation.
- ► Mac-Users: Copy the plugins directory into your /Application/Neo... and into graph.db/plugins
- Windows-Users: Follow the installation and start client.

➤ Replace the NEO4J_HOME/conf/neo4j.conf configuration file with the one found on the flash drive at neo4j-training-files/conf/neo4j.conf.

- ► Replace the NEO4J_HOME/conf/neo4j.conf configuration file with the one found on the flash drive at neo4j-training-files/conf/neo4j.conf.
- ► Copy the neo4j-training-files/data/ctdbase.db folder into your NEO4J_HOME/data/databases/ directory

Starting Neo4j

► Start the database with NEO4J_HOME/bin/neo4j start

Starting Neo4j

- ► Start the database with NEO4J_HOME/bin/neo4j start
- ► Go to http://localhost:7474 within you browser

Practice activity

- ▶ Please separate in 4 groups:
 - Chemical
 - Disease
 - Organism
 - ▶ Gene

Practice activity

- ▶ Please separate in 4 groups:
 - Chemical
 - Disease
 - Organism
 - ▶ Gene
- Explore the dashboard in groups
- What can you find out about your node type?
- What questions arise?

Demonstration

Important configuration entries

dbms.active_database=odsc.db

dbms.security.auth_enabled=false

dbms.security.procedures.unrestricted=algo.*,apoc.*

apoc.import.file.enabled=true

```
create node

CREATE (c:Chemical {name: 'Helium'})

RETURN c

update node

MERGE (c:Chemical {name: 'Helium'})

SET c.symbol = 'He' RETURN c
```

```
delete node without relations
MATCH (c:Chemical {name:'Helium'})
     DELETE c
delete node without relations
MATCH (c:Chemical)
     WHERE c.name = 'Helium'
     DELETE c
delete node with existing relations
MATCH (c:Chemical {name:'Helium'})
     DETACH DELETE c
```

```
create relation between new nodes
CREATE (c:Chemical {chemicalName:'Helium'})
     -[:BELONGS_TO]->
     (g:ChemicalGroup {groupName:'Noble gases'})
RETURN c,g
create relation between existing nodes
MATCH (g:ChemicalGroup {groupName:'Noble gases'}),
       (p:ChemicalGroup {groupName:'Gases'})
CREATE (g)-[:HAS_PARENT]->(p)
RETURN g,p
```

```
update relation

MATCH ()-[r:BELONGS_TO]-()

SET r.updateTime = timestamp()

RETURN r

delete relation

MATCH ()-[r:BELONGS_TO]-()

DELETE r
```

Practice activity

- ► Go back to your graph model from the beginning of the training.
- Create about
 - ▶ 10 nodes and
 - ▶ 15 relations
 - with properties.

FINISH: PART ONE

Check your indexes

CALL db.indexes

CREATE INDEX ON :Disease(diseaseId)

CREATE INDEX ON :Gene(geneName, geneSymbol)

```
Example
MATCH (g:Gene)
     WHERE g.geneSymbol = 'CTSD'
     RETURN g
Example
MATCH (g:Gene)<-[:ASSOCIATED_WITH]-(d:Disease)
     WHERE g.geneSymbol = 'CTSD'
     RETURN g, d
Example
MATCH (g:Gene)<-[:ASSOCIATED_WITH]-(d:Disease)
     WHERE g.geneSymbol = 'CTSD'
     RETURN g, count(d)
```

Example

MATCH (g:Gene)<-[:ASSOCIATED_WITH]-(d:Disease)
WITH g, count(d) as diseases
WHERE diseases >50
RETURN g.geneName, g.geneSymbol, diseases
ORDER BY diseases DESC

Example

MATCH (g:Gene)<-[:ASSOCIATED_WITH]-(d:Disease)
-[:ASSOCIATED_WITH]->(otherGene:Gene)
WHERE g.geneSymbol = 'CTSD'
AND d.diseaseName = 'Osteoarthritis'
RETURN otherGene.geneName, otherGene.geneSymbol

Example

MATCH p = (c:Chemical)-[*2]-(d:Disease)
WHERE d.diseaseName STARTS WITH 'Osteo'
RETURN p LIMIT 20

Example

MATCH (c:Chemical)<-[:HAS_PARENT*3..4]-(d:Chemical)
WITH c, count(d) AS descendants,
collect(d.chemicalName) AS names
ORDER BY descendants DESC LIMIT 10
RETURN c.chemicalName, names[1..10], descendants

```
Example
MATCH (c:Chemical)
     WHERE c.chemicalName = 'Zinc Acetate'
MATCH (d:Disease)
     WHERE d.diseaseName = 'Alzheimer Disease'
MATCH p = (c)-[*1..3]-(d)
RETURN p LIMIT 20
Example
MATCH (:InteractionType {typeName:'degradation'})
     <-[:INCREASES|:DECREASES]-
     (i:Interaction)-[:APPLIES_TO]->
     (:Organism {organismName: 'Cricetulus griseus'})
RETURN i.description
```

Practice activity

For each group (Chemical, Disease, Organism, Gene):

- Please check your questions from the first practice activity.
 - Can you answer any of them now?
- Think about new questions as you explore the graph with the querying techniques just learned.
- Present one question, appropriate query and an answer to your classmates.

```
Shortest path example
MATCH (zinc:Chemical {chemicalName:'Zinc Acetate'}),
      (metals:Chemical {chemicalName:'Metals, Heavy'}),
      p = \text{shortestPath}((zinc)-[*..15]-(metals))
RETURN p
Shortest path example
MATCH (zinc:Chemical {chemicalName:'Zinc Acetate'}),
      (metals:Chemical {chemicalName:'Metals, Heavy'}),
      p = \text{shortestPath}((zinc)-[*..15]-(metals))
WHERE NONE(r IN relationships(p)
               WHERE type(r)='CAUSES')
RETURN p
```

Calling procedures

- ► CALL db.schema
- CALL dbms.procedures
- CALL dbms.functions
- CALL apoc.help('dijkstra')

Definition

In a connected graph, the normalized *closeness centrality* of a node is the average length of the shortest path between the node and all other nodes in the graph. Thus the more central a node is, the closer it is to all other nodes.²

Closeness Centrality Example

MATCH (node:Chemical)

WHERE node.chemicalName CONTAINS 'Vitamin' WITH collect(node) AS nodes

CALL apoc.algo.closeness(['HAS_PARENT'],nodes,'BOTH')
YIELD node, score

RETURN node, score
ORDER BY score DESC

²en.wikipedia.org/wiki/Centrality#Closeness_centrality

Definition

Betweenness centrality quantifies the number of times a node acts as a bridge along the shortest path between two other nodes.³

Betweenness Centrality Example

MATCH (node:Disease)

WHERE node.diseaseName CONTAINS 'deficiency'

WITH collect(node) AS nodes

 ${\sf CALL\ apoc.algo.betweenness} (['{\sf HAS_PARENT'}],$

nodes, 'BOTH')

YIELD node, score RETURN node.diseaseName, score

ORDER BY score DESC LIMIT 10

³en.wikipedia.org/wiki/Centrality#Betweenness_centrality

Definition

In graph theory, a *clique* is a subset of vertices of an undirected graph such that every two distinct vertices in the clique are adjacent.

Clique example query

MATCH (startNode:Category

{name: 'Endocrine system disease'})

CALL apoc.algo.cliquesWithNode(startNode, 4)

YIELD clique

RETURN clique

³en.wikipedia.org/wiki/Clique_(graph_theory)

Practice activity

Explore the APOC library:

- read the documentation,
- try out different queries,
- make notes to about your questions and results.

PageRank example CALL algo.pageRank.stream('InteractionType', 'HAS_PARENT', {iterations:20}) YIELD node, score WITH * ORDER BY score DESC LIMIT 5 RETURN node.typeName, node.code, score; Partitioning into connected components CALL algo.unionFind('InteractionType', 'HAS_PARENT', write:true, partitionProperty:"partition") YIELD nodes, setCount, loadMillis, computeMillis, writeMillis

Closeness

CALL algo.closeness('Chemical', 'HAS_PARENT', {write:true, writeProperty:'centrality'})
YIELD nodes, loadMillis, computeMillis, writeMillis

Closeness

MATCH (c:Chemical)
WHERE c.centrality >200
RETURN c.chemicalName, c.centrality
ORDER BY c.centrality DESC LIMIT 10

LOAD CSV

View the data USING PERIODIC COMMIT 500 LOAD CSV WITH HEADERS FROM

 $"file:///.../_Disease-GO_biological_process_associations.csv"$

AS line

RETURN line LIMIT 10

³http://ctdbase.org/

LOAD CSV

```
Import the data
USING PERIODIC COMMIT 500
LOAD CSV WITH HEADERS FROM
"file:///.../Disease-GO_biological_process_associations.csv"
      AS line LIMIT 20
MATCH (d:Disease)
     WHERE last(split(d.diseaseID,':')) = line.DiseaseID
MERGE (b:BiologicalProcess goid:line.GOID)
     SET b.goName = line.GOName
MERGE (b)<-[:AFFECTED_BY
           {inferenceGeneQty:line.InferenceGeneQty,
```

inferenceGeneSymbols:line.InferenceGeneSymbols}]-(d)

³http://ctdbase.org/

apoc.load.csv

```
View the data
CALL apoc.load.csv(
    'file:///.../CTD_chem_go_enriched.csv',
)
YIELD lineNo, map AS line RETURN lineNo, line limit 5
```

Loading big files

```
CALL apoc.periodic.iterate(
      "CALL apoc.load.csv(
                'file:///.../CTD_chem_go_enriched.csv',
      YIELD lineNo, map AS line RETURN lineNo, line",
      "MATCH (c:Chemical {chemicalID : line.ChemicalID})
      MERGE (o:Ontology {name : line.Ontology})
      MERGE (t:Term {termID : line.GOTermID})
                SET t.termName = line.GOTermName
                SET t.level = line.HighestGOLevel
      MERGE (c)<-[r:AFFECTED_BY]-(t)-[:TERM_OF]->(o)
           SET r.pValue = line.PValue
           SET r.correctedPValue = line.CorrectedPValue",
      {batchSize:10000, iterateList:true}
```

Practice activity

- Choose a CSV file from neo4j-training-files/data/CTD.
- Load and show first 15 lines.
- Import some of the columns of the first 15-20 lines and connect it to existing graph nodes.

Refactor your graph

```
Add labels
MATCH (p:Pathway)
     WHERE toLower(p.pathwayName)
      CONTAINS 'reaction'
CALL apoc.create.addLabels(id(p), ['Reaction'])
      YIELD node
RETURN count(node)
Rename relation
MATCH ()-[r:PART_OF]-()
CALL apoc.refactor.setType(r, 'BELONGS_TO')
YIELD input, output
RETURN count(input), count(output)
```

Practice activity

- Rename the relation : INVOLVED_IN in : INVOLVES
- and invert the direction.
- Can you find out how to invert the direction of the relation?
- First rename, then invert? Or first invert and then rename?

References

- ➤ Curated chemical—gene, chemical—disease and gene—disease interactions data were retrieved from the Comparative Toxicogenomics Database (CTD), MDI Biological Laboratory, Salisbury Cove, Maine, and NC State University, Raleigh, North Carolina. URL: http://ctdbase.org/. [October, 2017].
- ➤ Cypher Reference Card https: //neo4j.com/docs/cypher-refcard/current/
- ► APOC User Guide https://neo4j-contrib.github. io/neo4j-apoc-procedures/
- ► Efficient Graph Algorithms in Neo4j https://neo4j. com/blog/efficient-graph-algorithms-neo4j/

Getting Help

Slack

neo4j.com/blog/public-neo4j-users-slack-group/

Getting Help

Slack

neo4j.com/blog/public-neo4j-users-slack-group/

Contact details

- ▶ in www.linkedin.com/in/ifeuerstein/
- ▶ **೧** github.com/IraRe
- iryna.feuerstein@prodyna.com

Home work

Pick an organism from the data base (for example the Chinese Hamster aka *Cricetulus griseus*).



- Find some interesting information about it in the database.
- Tweet to me a piece of information with the hashtag #cricetulus.
- Get a coffe mug for an interesting tweet!