

L^AT_EX Cheatsheet

Ashfaqur Rahman

May 12, 2018

Contents

1	Characters and Commands	2
1.1	Latex special characters	2
1.2	Latex commands	2
2	Writing	2
2.1	Modes in L ^A T _E X	2
2.2	Creating a New Paragraph	2
2.3	Spaces	2
2.3.1	Inserting Spaces	2
2.3.2	Space after a period	2
2.3.3	Space after a latex command	3
2.4	Dashes	3
2.5	Quotations	3
2.5.1	Putting Quotation in a Quotation	3
2.6	Commenting	3
3	L^AT_EX Commands List	3

A latex cheatsheet.

1 Characters and Commands

1.1 Latex special characters

`$ % & # - { } \ ~ ^` are special characters and has special meaning to latex. You can use a leading `\` to use them. To print `$`, write `\$`

1.2 Latex commands

Each latex command starts with a `\` and contains only letters. Example: `\maketitle`, `\tableofcontents` etc. Parameters to a command are specified inside `{}` and optional parameters are specified inside `[]`. For example `\documentclass[10pt]{article}`.

2 Writing

2.1 Modes in L^AT_EX

Paragraph mode Normal mode

Math Mode For mathematical equation. Text inside `\(...\)` or `$...$` or

`$$...$$` or `\begin{equation}...\end{equation}` or `\begin{displaymath}...\end{displaymath}`

Left to right mode Text are displayed from left to right without line breaks. text inside `\mbox{}`

2.2 Creating a New Paragraph

A blank line creates a new paragraph.

2.3 Spaces

2.3.1 Inserting Spaces

`\,` is used for inserting a space.

2.3.2 Space after a period

Latex assumes end of sentence if it found period after small case later. In that case it puts extra space after period. But for the cases like “etc.” a space followed by \ should be used after period like `etc.\` . A space followed by \ means inter word space.

If ending of a sentence contains a uppercase letter to end the sentence use \@ before period.

2.3.3 Space after a latex command

All spaces are ignored after a latex command like `\LaTeX` command. To make a space after `\LaTeX` a space followed by \ should be used like `\LaTeX\` . Another way to do this is to use empty {} after a command like `\LaTeX{}`.

2.4 Dashes

- - A intra-word dash or hyphene. Example: X-ray.
- -- A number range dash. Example: 1–10
- --- A punctuation dash. Example: —

2.5 Quotations

` is used for single quotation start (‘).
' is used for single quotation end (’).
`` is used for double quotation start (“).
" is used for double quotation end (”).

2.5.1 Putting Quotation in a Quotation

```\,`Ah!`\,``` She said produces “ ‘Ah!’ ” She said

## 2.6 Commenting

% is used for commenting. Latex ignore all character after % to the end of the line. Also ignores space in the beginig of the next line.

### 3 $\LaTeX$ Commands List

- `\documentclass[]{} —` To specify document type. Arguments can be book, article, report etc. Options<sup>1</sup> are:
  1. 11pt — 10% larger than 10pt.
  2. 12pt — 20% larger than 10pt.
  3. twoside — to print in both sides.
  4. twocolumn — two column in a single page.
- `\usepackage{}` — To use external packages.
- `\title{}` — To specify document title.
- `\author{}` — To specify document author. Multiple authors can be specified using `\and` command.
- `\begin{}` — To begin any block. like `\begin{document}` to begin any document, `\begin{quote}` begins a long quotation, `\begin{math}` begins a math block etc.
- `\end{}` — ends any block that begins with `\begin{}`
- Argument of `\begin` and `\end` are called environments. They create different display environments. Every declaration or command can be environment like `\emph` can also be written as environment like `\begin{emph} ... \end{emph}` Here is a list of different environments:

**document** Document environment.

**quote** Short quotation environment.

**quotation** Long quotation environment.

**itemize** Unordered list environment.

**enumerate** Ordered list environment.

**description** Description list environment like this one.

**displaymath** Display math equations in separate line but without equation number.

**equation** Display equation in separate line with equation number for further reference.

---

<sup>1</sup>Options are specified inside the square brackets

- `\maketitle` — To create title. It must be inside `\begin{document}`.
- `\part` — Create parts of a document. Doesn't effect document numbering.
- `\chapter` — Create chapters. No applicable for article document class.
- `\section` — Specify a section.
- `\subsection` — Specify a sub-section of a section.
- `\subsubsection` — Specify a sub-section of a sub-section.
- `\appendix` — Specify an appendix.
- `{}` — Curly braces can be used for defining scope. Example — Input: Hello, `{\em aagontuk}` Output: Hello, *aagontuk*
- `\today` — Current date December 19, 2019
- `\TeX` — Shows  $\TeX$
- `\LaTeX` — Shows  $\LaTeX$
- `\ldots` — Produces ...
- `\emph{}` — To emphasize text. Example: I will *emphasize* it.
- `\mbox{TEXT}` — Never breaks TEXT.
- `\footnote{footnote}` — To create a footnote. Example: Footnote<sup>2</sup>
- `\\` — New line.
- `\\*` — New line but prevents a new page.
- `\newline` — New line.
- `\hfill \break` — New line.
- `\newpage` — New Page.
- `\hspace{xmm}` — x mm horizontal space.
- `\vspace{xmm}` — x mm vertical space.

---

<sup>2</sup>Please find the footnote here