



Week3_Course_part4

Principles of Data Layout and Index

Index Structure Review

Database System - Nankai



Principles of Data Layout and Index

How to lay out data on disk?

上周课



关系模式与关系

属性(Attribute) → 字段(Field)

元组(tuple) → 记录(Record)

记录集合 → 存储块 (Block)

块的集合 → 存储关系(Relation)

How to find a record quickly?

本周课



磁盘的结构与访问特征

Conventional indexes

B+Trees

Hashing schemes

Database System - Nankai






磁盘结构



轴(Spindle)

磁头(disk head)

Arm assembly




- Platter (2 surfaces)
- Head
- Cylinder
- Track
- Sector (physical)
- Block (logical)
- Gap

Database System - Nankai



Physical vs. Logical I/O

- Sector: indivisible unit of disk I/O
- Blocks
 - logical (DBMS/OS) units of disk storage
 - transferred btw disk and main memory buffers
 - typically 4... 56 KB, consisting of one or more sectors
- Disk Access Time



Time = Seek Time +
Rotational Delay +
Transfer Time +
Other

Database System - Nankai



磁盘访问特性

- Seek time
 - time to move heads to proper cylinder. (一般7.5 ~ 14ms)
- Rotational latency
 - time for desired block to come under the head.
 - 7200转/每分钟的硬盘，旋转一周时间为8.33毫秒，平均4.17毫秒
- Transfer time
 - time during which block passes under head.
- Miscellaneous
 - including time for disk controller to process data, contention for controller, bus, etc. Neglect this.

Database System - Nankai



磁盘访问效率举例

- 全国有14亿人口，需要构建数据库存储人口的基本信息，每位公民要存储身份证号、姓名、家庭住址、联系方式等信息；
- 如果磁盘块是4K(4096字节,8个扇区)，一个块可以存储100个人的记录，则14亿人口需要存储到1400万个数据块中；
- 如果在此数据库中需要根据身份证号查找人员的姓名及其他信息，就必须依次将块读入内存，逐个匹配身份证号，命中记录的平均读取块数大概有700万个。对7200转的磁盘来说，平均随机访问一个块的时间是14ms左右，读取700万个数据块要花费27个小时，即使数据按柱面存储也要花费近10个小时。

Database System - Nankai



How to find a record quickly, given a key

Next


- 磁盘的结构与访问特征
- Conventional indexes
- B+Trees
- Hashing schemes

Database System - Nankai



索引的直观描述

查找学号20190675
学生的学籍卡片




ikai



Index Structures


- Data structure for locating records with given search key efficiently



Also facilitates a full scan of a relation (or the extent of an object class) if records not stored on physically consecutive blocks




Dense Index (稠密索引)



Database System - Nankai



Sparse Index (稀疏索引)




Database System - Nankai



Sparse 2nd level index

Sequential File



Database System - Nankai



Sparse vs. Dense Tradeoff


Sparse: Less index space per record

-> can keep more of index in memory

Dense: Can tell if any record exists without accessing file


Dense Index

Sequential File



Sparse Index

Sequential File



Database System - Nankai



Terms

- Search key ($\neq$ primary key 搜索键或者查找键)
- Primary index (主索引)
 - index locations determine locations of data blocks
- Secondary index (辅助索引)
- Dense index (contains all search key values 稠密索引)
- Sparse index (稀疏索引)
- Multi-level index (多级索引)

Database System - Nankai



Index Structure - Summary

- The Role of index (深刻理解索引的作用)
- Dense index (contains all search key values 稠密索引)
- Primary index (主索引)
- Sparse index (稀疏索引)
- Multi-level index (多级索引)

请在学堂云上完成相关练习,加深对知识的理解!

Database System - Nankai

单选题 1分



课前预习索引部分--互动交流

某日某趟高铁直达列车有1500人乘坐，每个座位用车厢座位号标识，每个乘坐人用身份证号标识，关系表的模式为：某日乘车（车厢座位号，身份证号、姓名），表中的元组按车厢座位号排序存储的。请问如果需要快速查找某个座位上的乘客信息，应该构建如下哪个索引？

- A 在车厢座位号属性上，构建稀疏索引
- B 在车厢座位号属性上，构建稠密索引
- C 在身份证号属性上，构建稀疏索引
- D 在身份证号属性上，构建稠密索引

提交

Database System - Nankai

单选题 1分



课前预习索引部分--互动交流

某日某趟高铁直达列车有1500人乘坐，每个座位用车厢座位号标识，每个乘坐人用身份证号标识，关系表的模式为：某日乘车（车厢座位号，身份证号、姓名），表中的元组按车厢座位号排序存储的。请问如果需要快速查找某身份证号的乘客坐在哪个位置，应该构建如下哪个索引？

- A 在车厢座位号属性上，构建稀疏索引
- B 在车厢座位号属性上，构建稠密索引
- C 在身份证号属性上，构建稀疏索引
- D 在身份证号属性上，构建稠密索引

提交

Database System - Nankai

单选题 1分



课前预习索引部分--互动交流

某日某趟高铁直达列车有1500人乘坐，每个座位用车厢座位号标识，每个乘坐人用身份证号标识，关系表的模式为：某日乘车（车厢座位号，身份证号、姓名），表中的元组按车厢座位号排序存储的。请问如果需要快速查找某个姓名的乘客坐在哪个位置，应该构建如下哪个索引？

- A 在车厢座位号属性上，构建稀疏索引
- B 在车厢座位号属性上，构建稠密索引
- C 在姓名属性上，构建稀疏索引
- D 在姓名属性上，构建稠密索引

提交

Database System - Nankai



Week3_Course_part5

Principles of Data Layout and Index

Conventional Indexes

Database System - Nankai



Next:


- Duplicate keys
- Deletion/Insertion
- Secondary indexes

Database System - Nankai



Duplicate keys

Dense index, one way to implement?



Database System - Nankai



Duplicate keys

Sparse index, one way?

careful if looking
for 20 or 30!

10	
10	
20	
30	

10	
10	
10	
20	
20	
30	
30	
40	
45	

Database System - Nankai



Duplicate keys

Sparse index, another way?

– first new key from block

should
this be
40?


10	
20	
30	
30	

10	
10	
10	
20	
20	
30	
30	
40	
45	



Duplicate values, primary index

- Index may point to first instance of each value only




Database System - Nankai



Index update operations


Deletion from sparse index





Deletion from sparse index


- delete record 40





Deletion from sparse index


- delete record 30






Deletion from sparse index

- delete records 30 & 40





Deletion from dense index




Database System - Nankai




Deletion from dense index

- delete record 30






Insertion, sparse index case





Insertion, sparse index case

— insert record 34




- our lucky day!
we have free space
where we need it!



Insertion, sparse index case

– insert record 15




- Illustrated: Immediate reorganization
- Variation:
 - insert new block (chained file)
 - update index



Insertion, sparse index case

— insert record 25





Secondary indexes

Sequence
field


30	
50	
20	
70	
80	
40	
100	
10	
90	
60	

Database System - Nankai



Secondary indexes


- Sparse index





Secondary indexes

- Dense index





With secondary indexes:

- Lowest level is dense
- Other levels are sparse

Also: Pointers are record pointers
(not block pointers; not computed)

Database System - Nankai



Duplicate values & secondary indexes

20	
10	
20	
40	
10	
40	
10	
40	
30	
40	

Database System - Nankai




Duplicate values & secondary indexes

one option...

Problem:
excess overhead!


- disk space
- search time



Database System - Nankai



Duplicate values & secondary indexes





Why “bucket” idea is useful

Example:

Indexes

Records

Name: primary

EMP(name,dept,floor,...)


Dept: secondary

Floor: secondary

Database System - Nankai




Query: Get employees in (Toy Dept) AND (2nd floor)



→ Intersect toy bucket and 2nd Floor
bucket to get set of matching EMP's



This idea used in text information retrieval





IR QUERIES

- Find articles with "cat" and "dog"
- Find articles with "cat" or "dog"
- Find articles with "cat" and not "dog"

- **Find articles with "cat" in title**
- **Find articles with "cat" and "dog" within 5 words**

Database System - Nankai



Conventional indexes

Advantage:

- Simple
- Index is sequential file
good for scans

Disadvantage:

- Inserts expensive, and/or
- lose sequentiality & balance



Summary so far

- Conventional index
 - Basic Ideas: sparse, dense, multi-level...
 - Duplicate Keys
 - Deletion/Insertion
 - Secondary indexes
 - Buckets of Postings List/File

Database System - Nankai

单选题 1分




互动交流一

下图索引哪个部分是主索引 (Primary index) ?

Sparse 2nd level index

Sequential File



- A 1
- B 2
- C 3
- D 以上都不是

提交

Database System - Nankai

多选题 1分




互动交流二

下图索引哪个部分是稀疏索引 (sparse index) ?

Sparse 2nd level index

Sequential File



- ☐ A 1
- ☐ B 2
- ☐ C 3
- ☐ D 以上都不是

提交

Database System - Nankai

单选题 1分



互动交流三

判断以下描述是否正确？

A secondary index is one in which keys don't necessarily have to be ordered.

A TRUE

B FALSE

提交

Database System - Nankai



Week3_Course_part6

Principles of Data Layout and Index

B+ Tree Indexes

Database System - Nankai



Principles of Data Layout and Index

How to find a record quickly?

本周课



磁盘的结构与访问特征

Conventional indexes

NEXT ⇒

B+Trees


Hashing schemes

Database System - Nankai



Example

Index (sequential)





Outline:

- Conventional indexes
- B-Trees $\Rightarrow$ NEXT
 - a commonly used index structure that adapts well to insertions and deletions
- Hashing schemes

Database System - Nankai




- B-Trees
 - a commonly used index structure
 - nonsequential, “balanced” (access paths to different records of equal length)
 - adapts well to insertions & deletions
 - consists of blocks holding at most n keys and $n+1$ pointers, and at least half of this
 - (We consider a variation actually called a B+ tree)

Database System - Nankai



B+Tree Example


n=3



Database System - Nankai




Sample non-leaf



Database System - Nankai



Sample leaf node:





Don't want nodes to be too empty

- Number of pointers in use:

- at internal nodes at least $\lceil (n+1)/2 \rceil$
(to child nodes)


- at leaves at least $\lfloor (n+1)/2 \rfloor$
(to data records/blocks)

$$\lceil x \rceil = \min \{n \in \mathbb{Z} \mid n \geq x\}$$

$$\lfloor x \rfloor = \max \{n \in \mathbb{Z} \mid n \leq x\}$$



$n=3$



Database System - Nankai



B+tree rules

- (1) All leaves at the same lowest level (balanced tree)
- (2) Pointers in leaves point to records
except for "sequence pointer"
- (3) Number of pointers/keys for B+tree

	Max ptrs	Max keys	Min ptrs→data	Min keys
Non-leaf (non-root)	n+1	n	$\lceil (n+1)/2 \rceil$	$\lceil (n+1)/2 \rceil - 1$
Leaf (non-root)	n+1	n	$\lfloor (n+1)/2 \rfloor$	$\lfloor (n+1)/2 \rfloor$
Root	n+1	n	$2^{(*)}$	1

(*) 1, if only one record in the file

Database System - Nankai



Insert into B+tree

First lookup the proper leaf

(a) simple case

- leaf not full: just insert (key, pointer-to-record)

(b) leaf overflow

(c) non-leaf overflow


(d) new root

Database System - Nankai



(a) Insert key = 32

n=3




Database System - Nankai



(b) Insert key = 7

n=3




Database System - Nankai



(c) Insert key = 160

n=3




Database System - Nankai



(d) New root, insert 45

n=3



Database System - Nankai



Deletion from B+tree

Again, first lookup the proper leaf;

- (a): Simple case: no underflow; Otherwise ...
- (b): Borrow keys from an adjacent sibling
(if it doesn't become too empty); Else ...
- (c): Coalesce with a sibling node
- (d): Cases (a), (b) or (c) at non-leaf

Database System - Nankai




(b) Borrow keys

– Delete 50

$n=4$

$\Rightarrow$ min # of keys
in a leaf = $\lfloor 5/2 \rfloor = 2$




Database System - Nankai



(c) Coalesce with a sibling

n=4

– Delete 50



Database System - Nankai




(d) Non-leaf coalesce

– Delete 37

$n=4$

=> min # of keys in a non-leaf =

$$\lceil (n+1)/2 \rceil - 1 = 3 - 1 = 2$$





B+tree deletions in practice

- Often, coalescing is not implemented
 - Too hard and not worth it!
 - later insertions may return the node back to its required minimum size
 - Compromise: Try redistributing keys with a sibling; If not possible, leave it there
 - if all accesses to the records go through the B-tree, can place a "tombstone" for the deleted record at the leaf

Database System - Nankai



Why B-trees Are Good?

- B-tree adapts well to insertions and deletions, maintaining balance
 - DBA does not need to care about reorganizing
 - split/merge operations rather rare
(How often would nodes with 200 keys be split?)
- Access times dominated by key-lookup
(i.e., traversal from root to a leaf)

Database System - Nankai



Efficiency of B-trees

- For example, assume 4 KB blocks, 4 byte keys and 8 byte pointers
- How many keys and pointers fit in a node (= index block)?
 - Max n s.t. $(4*n + 8*(n+1)) B \leq 4096 B$?
 - > $n=340$; 340 keys and 341 pointers fit in a node
 - > 171 ... 341 pointers in a non-leaf node

Database System - Nankai



Efficiency of B-trees (cont.)

- Assume an average node has 255 pointer
 - > a three-level B-tree has $255^2 = 65025$ leaves with total of 255^3 or about 16.6 million pointers to records
 - > if root block kept in main memory, each record can be accessed with 2+1 disk I/Os;
 - If all 256 internal nodes are in main memory, record access requires 1+1 disk I/Os
 - (256 x 4 KB = 1 MB; quite feasible!)

Database System - Nankai



B+ Tree Index - Summary

B+树是DBMS在存储层采用的核心索引技术，同学们要深刻体会B+树的动态调整特性，掌握B+树的机理。

Database System - Nankai

填空题 1分



互动交流一

Relation R has 4000 records. Suppose a B+ tree index is built on R's key attribute. A block can hold a B+ tree node (interior or leaf node) with 20 keys and 21 pointers. In this case, at least [填空1] blocks are needed to hold the entire B+ tree index?

提交


Course System - Nankai

主观题 10分



互动交流二

Find any/all violations of a B+ tree structure in the following diagram. Circle each bad node and give a brief explanation of each error. Assume the order of the tree is 4 ($n=4$; 4 keys)



提交

Database System - Nankai



Week3_Course_part6

Principles of Data Layout and Index

B+ Tree Indexes

Database System - Nankai



Principles of Data Layout and Index

How to find a record quickly?

本周课



磁盘的结构与访问特征

Conventional indexes

B+Trees

NEXT ⇒

Hashing schemes

Database System - Nankai



Week3_Course_part7

Principles of Data Layout and Index


Hashing

Database System - Nankai



Hashing?

- Locating the storage block of a record by the hash value $h(k)$ of its key k
- Normally really fast
 - records (often) located by a single disk access




Database System - Nankai



Two alternatives

(1) Hash value determines the storage block directly




- to implement a primary index



Two alternatives

(2) Records located indirectly via index buckets



- for a secondary index

Index



Example hash function

- Key = 'x₁ x₂ ... x_n' *n* byte character string
- Have *b* buckets
- $h = (x_1 + x_2 + \dots + x_n) \bmod b \in \{0, 1, \dots, b-1\}$

Good hash function

Expected number of function:

keys/bucket is the same for all buckets

Database System - Nankai



一个实用的hash函数

J.D.Ullman提出了一个较为实用的Hash函数:

- (1) 把关键字值化为二进制位串;
- (2) 把二进制位串分成等长的几组, 若最后一组位数不足则补0凑齐;
- (3) 将各组二进制位串相加, 得到一个整数;
- (4) 将该整数除以桶的个数, 其余数作为相应记录的桶地址

Database System - Nankai



EXAMPLE 2 records/bucket

INSERT:


$h(a) = 1$

$h(b) = 2$

$h(c) = 1$

$h(d) = 0$

$h(e) = 1$






EXAMPLE: deletion

Delete:

e

f

c





Rule of thumb:


- Try to keep space utilization between 50% and 80%

$$\text{Utilization} = \frac{\text{\# keys used}}{\text{total \# keys that fit}}$$

- If < 50%, wasting space
- If > 80%, overflows significant
 ↖ depends on how good hash
 function is & on # keys/bucket



数据库中Hash方法的使用困难



Database System - Nankai



How do we cope with growth?

- Overflows and reorganizations
- Dynamic hashing: # of buckets may vary

- Extensible
- Linear
- also others ...


Linear hashing: grow # of buckets by one

Two ideas:

(a) Use i low order bits of hash

(b) File grows linearly

→ No bucket directory needed



Linear Hashing: Parameters

- n : number of buckets in use
 - buckets numbered $0 \dots n-1$
- i : number of bits of $h(k)$ used to address buckets
 - $i = \lceil \log(n) \rceil$
- r : number of records in hash table
 - ratio r/n limited to fit an avg bucket in a block
 - next example: $r \leq 1.7n$, and block holds 2 records
 - ⇒ AVG bucket occupancy is $\leq 1.7/2 = 0.85$ of a block

Database System - Nankai



本周课程总结

How to find a record quickly?

本周课



- ◆ 磁盘的结构与访问特征
- ◆ Conventional indexes (sparse, dense, Primary index, Secondary index)
- ◆ B+Trees (B+tree rules, Insertion, Deletion)
- ◆ Hashing schemes

Database System - Nankai