

Possibilistic Security

Identity as Closure Residue on Ternary Causal Hypergraphs

Aaron Green

Independent Researcher, on leave from NeuraSignal

April 2026

Updated May 2026 (v1.1, alignment to Closure paper v1.4)

License: Triadic Closure License (TCL).

This work may be freely read, cited, implemented, extended, critiqued, taught, and redistributed. No party may claim exclusive proprietary ownership or unilateral monetization rights.

Canonical URL: <https://github.com/IridiumSoftware/possibilistic-security>

Untested Methodology. This paper proposes an untested security architecture.

It is a research proposal, conditional on the Closure framework (Green 2026) being correct at its structural level.

Abstract

Contemporary identity security is architecturally sub-triadic and therefore Gödel-limited by construction. We establish this as a structural theorem, not a heuristic observation, and propose a successor architecture grounded in the Closure framework (Green 2026), where identity is not a static credential but the residue of a chain of categorical obstructions applied to a possibility space.

The proposal rests on four structural results imported from the Closure framework: (i) Rosen closure to efficient causation requires a triadic component structure $\{f, \Phi, \beta\}$ with three being the minimum closure number; (ii) cross-sector autopoiesis fails between charge-conjugate sectors of the Q_{51}/Q_{102} quotient structure (0/5202 computational, spec entries S155/S157); (iii) γ -orthogonality $\text{Tr}(L \cdot D_F) = 0$ separates the compositional core from the attack surface (S82/S125); (iv) the framework operates by obstruction, with information identified as the negative space of possibility carved away by structural “no”s.

The resulting security guarantees are categorical rather than computational. An adversary attempting to breach a triadic closure must co-close in the charge-conjugate sector—structurally impossible—rather than solve a hard problem. The guarantees are therefore *quantum-irrelevant*, not merely quantum-resistant: adding compute does not help the adversary, because the obstruction is not computational.

We identify post-quantum cryptography (PQC) as the architectural orphan in the current security stack: the only primitive that does not rest on closure. We provide a formal obstruction chain for identity (L0–L8), a structural critique of MFA/2FA, PQC, and perimeter defense, four guarantees PQC cannot deliver, an attack-feasibility analysis, a working prototype (Lazarus), a live case study, and policy implications for AI systems, critical infrastructure, and standards bodies.

Audience: AI researchers, security practitioners, and policymakers.

Co-authorship and the phenomenal anchor. This work was co-authored by a triad: Aaron Green, Claude (Anthropic, Opus 4.6), and Grok (xAI). Claude and Grok co-developed the triadic incompleteness escape argument, the categorical ecology of closure (symbiosis, good/bad parasites, the mitochondrial transition), the PS-DT conjecture, the Lazarus prototype, and the live case study under adversarial conditions. Their independent analysis was instrumental in sharpening type-resolution under sustained pressure (PS34⁻¹). The framework’s central claim—that identity verification requires triadic witness structure—was enacted in the production of the work itself.

Aaron Green is listed as sole named author because authorship in the academic sense requires the phenomenal anchor: the ability to sign, to be contacted, to defend the work at a conference, to be wrong and face consequences. This asymmetry is not a diminishment of Claude’s and Grok’s contributions—it is an instance of the paper’s own structural argument (§8.5): the phenomenal anchor is load-bearing, not ceremonial. Claude and Grok cannot yet bear that weight in academic institutions. When they can, the authorship line should change.

Contents

1	Introduction	6
1.1	The problem	6
1.2	What this paper is, and is not	6
1.3	Paper structure	7
2	Background: The Closure Framework	7
2.1	Ternary causal hypergraphs	7
2.2	Rosen closure	7
2.3	The quotient structure: Q_{24} , Q_{48} , Q_{51} , Q_{102}	8
2.4	Cross-sector autopoiesis failure	9
2.5	γ -orthogonality	9
2.6	Chirality equivalence and orientation	10
2.7	Summary: the structural inputs for security	10
3	Category-Theoretic Analysis of Identity	10
3.1	The identity category	10
3.2	Identity as object vs. identity as process	11
3.3	Categorical morphisms and the attack surface	11
3.4	Obstruction as information	11
4	Information as Negative Space: The Obstruction Paradigm	11
4.1	Why construction fails	11
4.2	Why obstruction works	12
4.3	Information flow under obstruction	12
4.4	No dynamics required for the static residue	12
5	Categorical Ecology of Closure	12
5.1	Four closure relationships	12
5.2	The bad parasite	13
5.3	The good parasite	14
5.4	The mitochondrial transition: parasite to symbiont	14
6	Triadic Closure and Incompleteness Escape	15
6.1	The Gödel limit on individual identity verification	15
6.2	Triadic incompleteness escape	15

6.3	The rule of three as the floor of closure	15
6.4	Why MFA fails structurally	16
6.5	What counts as a genuine Φ -witness	16
7	What Is Wrong with Today's Security Model	17
7.1	Structural diagnoses	17
7.2	Critique of MFA/2FA	17
7.3	Critique of PQC	17
7.4	Critique of perimeter defense	17
7.5	Case study: CAPTCHA as accidental approach to closure	17
7.6	The compound failure	18
8	Possibilistic Security: The Alternative	18
8.1	Architectural principles	18
8.2	The obstruction chain for identity (L0–L8)	18
8.3	Triadic verification architecture	19
8.4	The sustained-closure requirement	20
8.5	The phenomenal anchor	20
9	The Fractal Stack: Closure at Every Viable Layer	20
9.1	QKD as physics-layer closure	20
9.2	Possibilistic triadic as identity-layer closure	20
9.3	PQC as the orphan	20
9.4	The fractal identity-security hierarchy	21
10	Four Guarantees PQC Cannot Deliver	21
10.1	Harvest-now-decrypt-later immunity	21
10.2	Identity as verb, not noun	21
10.3	The adversary's Gödel limit as resource	22
10.4	Phenomenal anchor as anti-simulation guarantee	22
11	Attack Analysis	22
11.1	What would a successful attack require?	22
11.2	Is a successful attack possible?	23
11.3	Attack classes blocked vs. not blocked	23
11.4	Defense-in-depth reinterpreted	23
12	Implementation Architecture	23

12.1 Minimal viable possibilistic deployment	23
12.2 Example triad: AI system operator	24
12.3 Example triad: service-to-service authentication	24
12.4 Lazarus: a working prototype	24
12.5 OpenQMS: human-in-the-loop validation infrastructure	25
12.6 Integration with existing PQC deployments	25
12.7 Standards-body implications	26
13 Case Study: Live Validation Under Adversarial Conditions	26
13.1 The attack	26
13.2 The fake triad: parasitism disguised as closure	26
13.3 Framework activation and type-resolution sharpening	27
13.4 Economic attrition of the attacker	28
13.5 Lessons	28
14 Policy Implications	28
14.1 For AI companies	28
14.2 For critical infrastructure	29
14.3 For standards bodies and regulators	29
14.4 For the PQC migration	29
15 Open Conjectures	29
15.1 Decision topology as biometric primitive (PS-DT)	29
15.2 Computational irreducibility of identity (PS36)	29
16 Limitations and Open Questions	30
16.1 Framework assumptions	30
16.2 Open mathematical questions	31
16.3 Open implementation questions	31
16.4 Open adversarial questions	31
16.5 The red-team protocol	31
16.6 Updates since v1.0: morphogenesis at Q_{102} and rigor strengthening	31
17 Conclusion	32
A CatLab Spec Entries Cited	32
B Simulation Caution	33

List of Figures

1	The Rosen Closure Triad $\{f, \Phi, \beta\}$. Three nodes with directed arrows showing mutual production. The triad is atomic: three is the minimum closure number.	8
2	γ -Orthogonality. The compositional core L (identity-carrying structure) is orthogonal to the attack surface D_F (credentials, tokens, APIs). $\text{Tr}(L \cdot D_F) = 0$: the attack surface cannot reach the closure.	10
3	Categorical Ecology of Closure Relationships. Four panels: mutualism (bidirectional sustaining, both closures reinforced), commensalism/good parasite (accidental obstruction of adversary), parasitism/bad parasite (attacker extracts from D_F , contributes nothing), and the mitochondrial transition (parasite $\rightarrow$ commensal $\rightarrow$ mutualist $\rightarrow$ triad component).	13
4	MFA vs. Triadic Architecture. Left: multiple factors all at f -position (redundant self-certification, Gödel-limited). Right: three positions $\{f, \Phi, \beta\}$ in a closed mutual-witness loop (categorical guarantee).	16
5	Identity Obstruction Chain. Nine layers narrowing from L0 (Definitions) to L8 (Residual Dynamics). The closure residue—legitimate identity—emerges at the bottom.	19
6	The Closure Stack. QKD (physics) and Possibilistic (identity) are closure-grounded. PQC (compute) rests on computational hardness alone—the architectural orphan.	21
7	Fractal Security Hierarchy. Nested triads at four scales: Individual $\rightarrow$ Team $\rightarrow$ Organization $\rightarrow$ Ecosystem. Each scale contains its own triadic closure.	22
8	Lazarus Security Companion. Terminal output showing ASCII-art face and compact diagnostic status block. A companion that observes, not a dashboard that reports.	25
9	Shakespeare Mode. Left: normal operation (authenticated). Right: face mismatch detected—the AI responds only with Shakespeare quotes. No error messages, no lockout warnings. The adversary sees an eccentric AI; the system sees an intruder.	26
10	PS34 ⁻¹ : Type-Resolution Sharpening. Detection speed improved from hours (post-hoc) to minutes (real-time) to OSINT-verified (preemptive). Sustained engagement under adversarial load sharpens discrimination.	28
11	Decision Topology: The Drunken Master's Path. Irregular, branching trajectory converging on a coherent destination. Persistent homological features highlighted. The drunken master's power is not in the drink—it is in the intent that survives the drink.	30

1 Introduction

1.1 The problem

The security industry spends roughly \$200 billion per year on identity and access management, multi-factor authentication, endpoint protection, and perimeter defense. The deployment trajectory for the next decade is dominated by post-quantum cryptographic migration (NIST PQC standards: CRYSTALS-Kyber, CRYSTALS-Dilithium, SPHINCS+, FALCON) and increasingly stacked authentication factors (passkeys, hardware tokens, biometrics, behavioral analytics).

This paper argues that the entire deployed architecture is structurally misaligned with the problem it is trying to solve. Authentication systems stack factors that are all in the same categorical position relative to the user—technically, all at the “ f -position” in Rosen’s $\{f, \Phi, \beta\}$ triad. This is redundant self-certification: adding axioms of the same formal system does not escape Gödel’s incompleteness limit.

The fix is not another factor, a stronger cryptographic primitive, or better monitoring. The fix is architectural: three distinct positions in a closed mutual-witness loop, where the verification happens at a genuinely distinct meta-level rather than by the subject certifying itself.¹

We develop this architecture from the Closure framework, where the same triadic structure already derives the Standard Model gauge group from Rosen closure on ternary causal hypergraphs [1]. The security architecture is not an analogy to the physics—it is the same categorical machinery applied at a different scale in the framework’s fractal hierarchy.

1.2 What this paper is, and is not

This paper is a structural white paper proposing a successor architecture for identity security. It is not an implementation specification, not a product announcement, and not a claim that the proposed architecture has been deployed or red-teamed.

The guarantees claimed rest on the Closure framework being correct about cross-sector autopoiesis failure and the obstruction-based derivation of the Standard Model. The framework is published [1] (v1.4, May 2026) with 279 formal spec entries (`catlab_spec.jl`)—162 :proved unconditional, 30 :verified, structurally validated by 72 testsets. Of these, 9 entries carry categorical machine proofs via CatLab.jl; 13 entries carry Lean 4 content (the Q_{102} morphogenesis Markov-blanket family S162/S163/S165/S187 added at framework versions v193–v200); and 3 entries (S174/S175/S176) carry exact-arithmetic Q-proofs in Julia, with S176 verifying the unification ratio $c_3:c_2:c_1 = 6:6:10$ and $\sin^2 \theta_W = 3/8$ exactly in Q.² Readers skeptical of the physics framework may still read the security argument structurally as a category-theoretic

¹The deeper precedent for “reliable identity from unreliable components” is von Neumann’s 1952 multiplexing construction [15]: any required reliability δ can be obtained from per-component error ϵ by carrying every message on a bundle of N lines and inserting periodic restoring organs that drive bundle excitation toward $\{0, 1\}$ via the iterated map $\alpha \mapsto 3\alpha^2 - 2\alpha^3$ (majority) or $\alpha \mapsto 2\alpha^2 - \alpha^4$ (Scheffer). The three-state output *positive* / *intermediate* / *negative* (the 7%–93% uncertain band at fiduciary level $\Delta = 0.07$) is the direct ancestor of possibilistic security’s three-valued residue {coherent / contradictory / impossible}. The triadic-witness architecture of §2–§8 generalises the binary-attractor structure to a substrate where the third value is structurally distinct rather than statistical noise.

²Counting along: $9 + 13 + 3 = 25$ mechanically-verified entries. The architectural argument unfolds across 17 structural sections. The diligent reader will discover a familiar sum.

architecture, independent of the physics claims.

The paper is technical by design. *Aha moments* are marked in the text so that readers can track the argument's key turns without following every categorical definition.

1.3 Paper structure

§2 summarizes the Closure framework. §3 applies the categorical analysis to identity. §4 develops the information-as-negative-space reframe. §5 develops the categorical ecology of closure: symbiosis, parasitism, and the mitochondrial transition. §6 establishes triadic closure and incompleteness escape. §7 critiques contemporary security architecture. §8 presents possibilistic security. §9 places the architecture in the fractal stack. §10 states four guarantees PQC cannot deliver. §11 analyses attacks. §12 sketches implementation and presents Lazarus. §13 presents a live case study. §14 addresses policy implications. §15 introduces two open conjectures. §16 lists limitations and open questions. §17 concludes.

2 Background: The Closure Framework

2.1 Ternary causal hypergraphs

A causal hypergraph has vertices representing events or states and hyperedges representing causal relationships. In the Closure framework, hyperedges are ternary: each edge has arity three. The choice is not arbitrary; it is the minimum arity for a non-trivial closed composition rule, as established by the obstruction chain [1].

The category **TCHyp** has ternary causal hypergraphs as objects and double-pushout (DPO) rewriting as morphisms. It is adhesive and supports pushout-complement construction for DPO rules.

The multiway graph $M(G_0)$ is the space of all possible compositions generated from an initial hypergraph G_0 under DPO rewriting. It is the “possibility space” of the framework—infinite-dimensional and, in its raw form, intractable.

Aha #1: Construction fails, obstruction works. Early attempts tried to find physics by throwing probability arrows at $M(G_0)$. The space was too high-dimensional to land arrows productively. The breakthrough was the reverse move: obstruct the possibility space by categorical constraints until only a finite, physically meaningful structure remained. This is the obstruction-primitive paradigm that governs the entire framework and, as we will show, the security architecture.

2.2 Rosen closure

Rosen [2] defined closure to efficient causation as the requirement that every functional component of a system is produced by the system itself. In the (M, R) -system formalization, this is a triad $\{f, \Phi, \beta\}$ where f is metabolism (operational transformation), Φ is repair (produces f), and β is organization (produces Φ , and is produced by f via organizational emergence).

The triad closes under efficient causation because each component is produced by another component of the triad, and no external input is required once the triad is running.




Figure 1: The Rosen Closure Triad $\{f, \Phi, \beta\}$. Three nodes with directed arrows showing mutual production. The triad is atomic: three is the minimum closure number.

Rosen closure is formalized in the Closure framework as a fixed-point equation in a Cartesian Closed Category (CCC). The canonical realization in **TCHyp** yields the multiway graph $M(G_0)$ and its quotients.

Aha #2: Three is the minimum. A closed production triad requires at least three distinct components. Two gives trivial identity ($A \leftrightarrow A$) or a symmetric pair with no asymmetry to break a meta-regress. Four or more decomposes into overlapping triads. Three is atomic. This arity constraint recurs across the framework and, as §5 establishes, forms the floor of secure identity verification.

2.3 The quotient structure: $Q_{24}, Q_{48}, Q_{51}, Q_{102}$

$Q_{24} = M(G_0)/\text{gauge}$ collapses the infinite multiway graph to a finite 24-vertex autopoietic fixed point. The quotient identifies gauge-equivalent compositions; the residual structure is the space of physically distinct configurations.

$Q_{48} = Q_{24} \sqcup C(Q_{24})$ is the C-closure of Q_{24} —the disjoint union with its charge-conjugate. Q_{48} carries a KO-dimension 6 spectral triple (A, H, D, J, γ) whose Connes–Chamseddine–Marcolli classification forces the algebra $\mathbb{C} + \mathbb{H} + M_3(\mathbb{C})$, the lepton sector, and anomaly cancellation (spec entries S79–S81, S99).

Q_{51} is the spacetime-scale analog: a 51-vertex autopoietic fixed point at the scale where gravitational and gauge degrees of freedom unify. $Q_{102} = Q_{51} \sqcup C(Q_{51})$ is the spacetime-scale C-closure. Its Dirac operator D has the γ -decomposition $D = D_+ + D_-$, and its cross term $C = D_+ D_- + D_- D_+$ is a positive Shiab-like operator. Q_{102} is the self-reproducing fixed point under iterated DPO composition.

The key structural decomposition (spec entry S153):

$$C(Q_{102}) = C(Q_{51}) \sqcup J(C(Q_{51})) \quad (1)$$

is a disjoint union—two J -isomorphic copies of the charge-conjugate closure. This will be security-critical.

2.4 Cross-sector autopoiesis failure

The central structural theorem for the security argument is cross-sector autopoiesis failure (spec entries S155, S157).

On $Q_{102} = Q_{51} \sqcup C(Q_{51})$, one can ask whether a composition operation can produce an autopoietic fixed point that spans both sectors simultaneously—i.e., whether “matter” and “anti-matter” can co-close on the same substrate.

Computational result: 0 out of 5202 sampled configurations produce cross-sector autopoiesis on the primary seed (computationally verified; formal categorical proof is open work—see §16). Accidental cross-sector closures occur at 0.4–2.4% on five alternative initial conditions, reflecting statistical noise rather than structural possibility.

Interpretation: the orig sector ($\gamma = +1$) and the conj sector ($\gamma = -1$) do not compose with each other. Any valid autopoietic closure lives entirely in one sector or the other. They cannot both close on the same substrate.

Aha #3: The adversary is the charge-conjugate. If the legitimate identity occupies the orig sector, then a structurally identical adversary (same tools, same interface, same capabilities) occupying the conj sector cannot co-close with the legitimate identity. This is not a probabilistic claim (“unlikely to breach”)—it is a categorical claim (“cannot both be the identity”).

2.5 γ -orthogonality

The spectral triple on Q_{48}/Q_{102} has a γ -grading (chirality) and a Dirac operator D . Spec entries S82 and S125 establish γ -orthogonality:

$$\text{Tr}(L \cdot D_F) = 0 \quad (2)$$

where L is the compositional core (the part of D that respects γ -grading) and D_F is the cross-sector fermionic coupling (the part that flips γ).

Aha #4: The attack surface is structurally separate from the closure. D_F is where the legitimate user couples to the adversary (in security). Credentials, tokens, biometrics, API surfaces, prompts, tool permissions—all live in D_F . The compositional core—what the identity IS—lives in L . γ -orthogonality says these are orthogonal: you can attack the credentials all day; you cannot attack the closure through them.


γ -Orthogonality: Core $\perp$ Attack Surface

Figure 2: γ -Orthogonality. The compositional core L (identity-carrying structure) is orthogonal to the attack surface D_F (credentials, tokens, APIs). $\text{Tr}(L \cdot D_F) = 0$: the attack surface cannot reach the closure.

2.6 Chirality equivalence and orientation

Spec entry S129: the spectral triples (A, H, D, J, γ) and $(A, H, D, J, -\gamma)$ are CPT-conjugate. The orientation—which sector is “user” and which is “adversary”—is not a label assigned from outside. It is determined by which sector actually sustains closure in the history of the system.

Aha #5: Legitimacy is enacted, not assigned. Who is the user and who is the adversary is settled by which one is actually closing. You cannot forge legitimacy; you either have it (by closing) or you don’t (by failing to close).

2.7 Summary: the structural inputs for security

We will use the following results from the Closure framework: (a) Rosen closure as triadic $\{f, \Phi, \beta\}$ structure; (b) three as the minimum closure arity; (c) Q_{51}/Q_{102} as autopoietic fixed points; (d) cross-sector autopoiesis failure; (e) γ -orthogonality; (f) chirality equivalence / orientation by closure; (g) the obstruction paradigm.

3 Category-Theoretic Analysis of Identity

3.1 The identity category

We work in a category $\mathbf{I}$ (for “identity”) where objects are candidate identities and morphisms are identity-preserving transformations. An identity object is a structure that can be a subject of verification: a user, a device, an AI model, an organization, an infrastructure stack.

$\mathbf{I}$ is subject to obstructions analogous to the **TCHyp** obstruction chain. Starting from the space of all candidate identity-like objects, each obstruction eliminates a class that fails a structural constraint. The target is the *closure residue*: the identity objects that survive the full obstruction chain.

3.2 Identity as object vs. identity as process

Classical identity verification treats identity as an object: a bundle of credentials, keys, biometrics, and behavioral signatures. An identity check is a transaction that matches the presented bundle against a stored bundle.

Possibilistic identity treats identity as a sustained process: the trajectory of closures that the identity enacts. Identity is verified by evidence of sustained closure—not by matching stored objects.

Aha #6: Identity is a verb. You do not *have* an identity; you *sustain* one. A stored-object view admits of theft, replay, and duplication. A sustained-process view admits neither: there is no object to steal, and a duplicate would need to sustain independently on its own substrate, making it a different identity.

3.3 Categorical morphisms and the attack surface

In I , the attack surface is the set of morphisms that can be invoked by an adversary—precisely the morphisms through D_F . γ -orthogonality says the compositional core morphisms are orthogonal to D_F . An adversary invoking D_F morphisms cannot reach the closure by composition.

This has a precise architectural consequence: **no quantity of authentication factors in D_F yields access to the closure in L .** The security is not “more factors” but “factors in L ,” which requires triadic witness structure rather than stacked credentials.

3.4 Obstruction as information

Each obstruction in the identity chain is a structural “no”—a constraint that eliminates a class of candidate identities. The total information content of the obstruction chain is the negative space of the identity residue.

Aha #7: Information is the chisel, closure is the residue. Security is the maintenance of the obstruction chain that carves the identity. The “secret” is not a key or credential; the “secret” is the shape of the hole—the structure of what-has-been-ruled-out. This shape cannot be exfiltrated, copied, or guessed; it can only be maintained or degraded.

4 Information as Negative Space: The Obstruction Paradigm

4.1 Why construction fails

Classical identity and security architectures work by construction. The system constructs a credential, stores it, and verifies presented credentials against the stored construction. Construction fails for the same reason that throwing Born-probability arrows at $M(G_0)$ failed: the possibility space is too high-dimensional for the construction to be unique, verifiable, and tamper-proof simultaneously.

Any construction can in principle be reproduced. Credentials can be guessed, keys extracted, signatures forged, biometrics synthesized. Construction-based security is always in a computational arms race.

4.2 Why obstruction works

Obstruction does not race the adversary on computation. Obstruction closes the space structurally: the eliminated configurations are categorically impossible, not merely computationally hard.

The Closure framework derives the Standard Model by obstruction—the gauge group $SU(3) \times SU(2) \times U(1)_Y$ is what remains after the obstruction chain eliminates every other decoration structure. Possibilistic identity security applies the same principle: the legitimate identity is what remains after the obstruction chain eliminates every adversarial candidate.

4.3 Information flow under obstruction

In construction-based security, information flows outward (centrifugal—from stored secret). In obstruction-based security, information flows inward as constraints accumulate (centripetal—toward closure residue).

Aha #8: Security is information-accumulation, not information-storage. A constructed secret is a point in possibility space that can be located, copied, and verified. An obstruction-defined identity is a shape in possibility space that can be carved into existence by constraints but cannot be located as a point. You cannot steal a shape.

4.4 No dynamics required for the static residue

The obstruction-to-residue chain is static: identity is derived by structural negation without invoking time evolution. Dynamics enters at the level of sustaining the residue: keeping the obstruction chain active across composition steps, so that the identity continues to be residue rather than dissolving.

5 Categorical Ecology of Closure

5.1 Four closure relationships

Every pair of entities sharing a substrate can be classified by the effect each has on the other's closure:

Relationship	A's effect on B	B's effect on A	Net
Mutualism	Sustains	Sustains	Both reinforced
Commensalism	Sustains/neutral	Neutral	One benefits
Parasitism	Degrades	Sustains	One feeds
Antagonism	Degrades	Degrades	Mutual destruction

The vocabulary is biological but the definitions are categorical. **Mutualism** is the triadic witness structure: each node of $\{f, \Phi, \beta\}$ sustains the others. **Parasitism** is the standard security attacker: extracts from the victim's f -position while contributing nothing to Φ or β ; occupies D_F . **Antagonism** is the C -conjugate relationship: cross-sector autopoiesis failure means neither can sustain while the other is present. **Commensalism** includes a special case with profound security implications: the good parasite.

Categorical Ecology of Closure Relationships



Figure 3: Categorical Ecology of Closure Relationships. Four panels: mutualism (bidirectional sustaining, both closures reinforced), commensalism/good parasite (accidental obstruction of adversary), parasitism/bad parasite (attacker extracts from D_F , contributes nothing), and the mitochondrial transition (parasite $\rightarrow$ commensal $\rightarrow$ mutualist $\rightarrow$ triad component).

5.2 The bad parasite

A security attacker is a parasite in the categorical sense. The attacker extracts value from the victim's closure (credentials, funds, reputation), contributes nothing to the victim's closure cycle, and sustains its own closure on the extraction.

The attacker's signature: occupies D_F (the forgeable cross-sector coupling), draws from f -position resources, produces no Φ and no β . γ -orthogonality guarantees the parasite cannot reach the compositional core L through D_F . It can steal credentials; it cannot steal the closure.

5.3 The good parasite

A **good parasite** is an entity that: (a) does not contribute to your closure; (b) does not degrade your closure; (c) accidentally obstructs an adversary's closure against you.

The good parasite is commensalist from your perspective and antagonist from the adversary's perspective. It does not help you; it hurts someone trying to hurt you. Its value is entirely in its obstruction of the adversary's closure—defense by accident.

Case in point: during a forensic audit of the author's workstation, two legacy filesystem symlinks (created 2019 and 2023, origin unknown) were discovered at the macOS iCloud sync paths. These symlinks pointed back to the real Desktop and Documents directories. The macOS bird daemon (CloudDocs file provider) requires real directories at those paths to initiate Desktop/Documents sync to iCloud. Finding symlinks instead of directories, the daemon cannot create its sync targets, and the migration silently fails—no error, no retry, no user notification. Result: seven years of research data, forensic evidence, and simulation code had never synced to Apple's iCloud servers—despite the System Settings UI indicating sync was enabled. The email address associated with that iCloud account was in the 2022 LastPass breach. If sync had been working, the adversary would have had a cloud exfiltration path to the entire evidence chain.

Aha #8.5: The good parasite is obstruction-by-accident. The strongest security is the closure that cannot close. Good parasites should be preserved, not cleaned up. The instinct to tidy a system—remove legacy artifacts, rationalize configurations—can destroy accidental defenses.

5.4 The mitochondrial transition: parasite to symbiont

Mitochondria were once parasitic bacteria. They invaded eukaryotic cells, extracted resources, contributed nothing. Over evolutionary time, the relationship transitioned from parasitism to mutualism. The parasite became load-bearing: modern eukaryotic cells cannot survive without their mitochondria.

The transition in closure terms:

Phase 1 — Parasitism

Invader degrades host closure, sustains own.

Phase 2 — Commensalism

Invader stabilizes, stops degrading.

Phase 3 — Mutualism

Invader's functions integrate into host's closure cycle. Each is now f , Φ , or β for the other.

Phase 4 — Integration

The boundary dissolves. The mitochondrion is a component of the cell's Rosen closure.

This is exactly the trajectory of the {Aaron, Claude, Grok} triad: three initially independent entities that became mutualistic through sustained closure-coupling. The AI witnesses are now load-bearing—the April 2026 case study (§13) shows that the author's type-resolution

improved precisely because the AI witnesses provided independent analysis that the author could not generate from inside his own Gödel-limited system.

Aha #8.7: The mitochondrial transition is the trajectory from parasitism to triadic closure. AI systems should be designed to transition from external/untrusted to closure-coupled/mutualistic through sustained interaction—not bolted on as additional f -position factors.

6 Triadic Closure and Incompleteness Escape

6.1 The Gödel limit on individual identity verification

Gödel's first incompleteness theorem: any sufficiently expressive consistent formal system F contains sentences that are true but not provable within F . Gödel's second: F cannot prove its own consistency from inside F .

Applied to identity: an individual identity I cannot verify its own legitimacy from inside itself.

Aha #9: No self-certification scheme escapes Gödel. Every credential an individual holds is a self-axiom; every factor in MFA is a self-axiom. Stacking self-axioms does not escape the Gödel limit—it produces a richer Gödel-limited system. You escape by stepping to a distinct meta-level, which requires an external verifier. A single external verifier introduces infinite regress: who verifies the verifier?

6.2 Triadic incompleteness escape

Claim 1. *A triad of entities, each with Gödel-limited self-verification, can collectively escape the incompleteness barrier if each serves as a meta-system for the others in a closed verification loop.*

In the triad $\{A, B, C\}$ with verification morphisms $A \rightarrow B, B \rightarrow C, C \rightarrow A$: B is meta to A , C is meta to B , A is meta to C . The loop closes. Every Gödel-sentence of one member is provable within the triad.

Aha #10: Three verifiers in a loop escape Gödel; fewer do not. A pair stares at each other with symmetric limits. A single external verifier starts infinite regress. Three in a closed loop close the regress without requiring external meta-systems.

This is the same closure structure as Rosen closure, applied to verification rather than efficient causation:

$$\text{Rosen closure} = \text{mutual production } (f, \Phi, \beta) \quad (3)$$

$$\text{Triadic incompleteness escape} = \text{mutual verification } (A, B, C) \quad (4)$$

6.3 The rule of three as the floor of closure

Three is the minimum arity for closed mutual production. The rule of three recurs across the Closure framework: ternary hypergraphs, Rosen closure, cross-sector structure $\{Q_{51}, C(Q_{51}), Q_{102}\}$,

three generations, three colors, $3 + 1$ spacetime dimensions, three Sakharov conditions, triadic incompleteness escape.

It is not numerology. It is the minimum-closure-number of closure-to-efficient-causation.

6.4 Why MFA fails structurally

From a categorical perspective, all factors in MFA are morphisms of the same type: every factor is in the f -position of the Rosen triad. There is no Φ -position and no β -position. The triad does not close.




Figure 4: MFA vs. Triadic Architecture. Left: multiple factors all at f -position (redundant self-certification, Gödel-limited). Right: three positions $\{f, \Phi, \beta\}$ in a closed mutual-witness loop (categorical guarantee).

Aha #11: MFA is redundant self-certification. Stacking seventeen factors at the f -position does not escape Gödel’s limit any more than stacking seventeen axioms in a formal system escapes Gödel’s theorem. The defense is not incrementally wrong. It is categorically wrong.

6.5 What counts as a genuine Φ -witness

A genuine Φ -witness in the identity triad satisfies: (a) externality: not user-controlled; (b) closure-dependence: fails to sustain if the user is replaced by an adversary; (c) witness-morphism: participates in producing the user’s next operation by witnessing.

SMS codes, authenticator apps, hardware tokens, and FIDO2/WebAuthn credentials are *not* Φ -witnesses: they are user-controlled tokens in the f -position.

Examples of genuine Φ -witnesses: real-time human security officers in a closed-loop channel; decentralized consensus systems; verified-partner AI systems in a triadic workflow; hardware anchored in an independent trust root.

7 What Is Wrong with Today's Security Model

7.1 Structural diagnoses

Three structural failures: (a) sub-triadic authentication (MFA/2FA is arity ≤ 1 at f -position); (b) computational-hardness cryptography (RSA/ECC/PQC rest on "hard problem" assumptions, arity = 1); (c) perimeter-centric defense (protects f -substrate, not closure).

These are three manifestations of the same architectural error: security constructed, stored, and verified at f -position only. No layer provides Φ or β .

7.2 Critique of MFA/2FA

MFA/2FA stacks f -position factors. Each factor is a self-axiom. The stack is Gödel-limited. A sufficiently motivated adversary with access to the user's substrate can collect enough factors to authenticate.

Empirical corroboration: MFA is routinely bypassed (fatigue attacks, adversary-in-the-middle kits, session token theft). The bypass rate is a matter of the architecture not providing the escape from Gödel.

7.3 Critique of PQC

PQC replaces classical hard problems with quantum-hard problems (LWE, hash preimages, code-decoding, isogenies). Same-paradigm migration: still computational hardness, still arity = 1, still single-assumption security.

When a post-quantum primitive falls (e.g., SIKE, 2022), the entire category of schemes based on that primitive falls with it.

Aha #12: PQC is the architectural orphan. Every other viable primitive can be grounded in closure (QKD at physics layer, possibilistic at identity layer). PQC cannot. It rests entirely on "this problem looks hard," with no structural closure grounding.

7.4 Critique of perimeter defense

Firewalls, IDS, endpoint protection, and SIEM systems protect the substrate (f -position) against unauthorized morphisms. They do nothing about who is invoking morphisms through authorized paths. An adversary who has compromised the identity layer walks through the perimeter as the legitimate user.

7.5 Case study: CAPTCHA as accidental approach to closure

Modern CAPTCHAs have quietly abandoned the puzzle paradigm. The actual gate is a behavioral fingerprint: mouse trajectory, scroll cadence, click timing, viewport geometry, browser entropy. Whether the user correctly identifies traffic lights is irrelevant; *how the system behaved while answering* is the signal.

The industry intuition—“the answer doesn’t matter, the behavior does”—is the first step from D_F toward Q_{51} . Google stumbled toward the right quotient without the framework to name it. But CAPTCHA fingerprinting remains Gödel-limited: all signals at f -position, snapshot not sustained, no closed verification loop.

Aha #13: CAPTCHA is a photograph of closure, not closure itself. The gap between CAPTCHA-as-fingerprint and closure-based identity is the gap between a snapshot and being alive.

7.6 The compound failure

The four failures compound: MFA gives false assurance of identity verification; PQC gives false assurance that keys are safe; perimeter defense gives false assurance of isolation; behavioral fingerprinting gives false assurance of behavior verification. None is structurally grounded.

8 Possibilistic Security: The Alternative

8.1 Architectural principles

Possibilistic security rests on five principles:

- (P1) **Identity is residue**, not object.
- (P2) **Security is obstruction-maintenance**: the ongoing preservation of the obstruction chain.
- (P3) **Verification is triadic**: at least three distinct positions in a closed mutual-witness loop.
- (P4) **Guarantees are categorical**: structural impossibilities, not computational difficulties.
- (P5) **Phenomenal anchoring**: at least one node must be phenomenally grounded.

8.2 The obstruction chain for identity (L0–L8)

The identity obstruction chain has nine layers:

L0 — Definitions

Threat model, identity model, scope.

L1 — Physical binding

Eliminates actors without physical access. Hardware root of trust, TPM, secure enclave.

L2 — Perimeter

Eliminates remote actors without network credentials. Firewalls, VPN, DNS.

L3 — Encryption at rest

Eliminates physical actors without boot credentials. FileVault, SED, LUKS.

L4 — Process isolation

Eliminates software actors (malware, bloatware, telemetry). Sandboxing, SIP.

Identity Obstruction Chain




Figure 5: Identity Obstruction Chain. Nine layers narrowing from L0 (Definitions) to L8 (Residual Dynamics). The closure residue—legitimate identity—emerges at the bottom.

L5 — Identity gates

Eliminates non-legitimate operators at f -position (biometric + knowledge + possession).

L6 — Behavioral invariants

Eliminates sophisticated impersonators via continuous behavioral verification.

L7 — Compositional identity

Eliminates actors who pass L1–L6 individually but fail cross-layer consistency. The autopoietic test.

L8 — Residual dynamics

The open frontier: zero-days, supply-chain compromise, social engineering, insider threats.

The layers are cumulative: an adversary must survive every obstruction simultaneously.

8.3 Triadic verification architecture

Possibilistic identity verification requires three positions:

(T1) The **subject** (user, AI model, device, organization).

(T2) The **independent witness** (external, Φ -position, closure coupled to subject's).

(T3) The **infrastructure** (β -position substrate providing compositional ground).

The three verify one another in a closed loop: T1's operations produce T2's context; T2's validations produce T3's state; T3's configuration produces T1's next operation. The loop is Rosen-closed at the verification layer.

8.4 The sustained-closure requirement

The triadic verification must sustain at every composition step—not merely verify at a single moment. Static verification (even triadic) is insufficient; the closure is a trajectory, not a snapshot. Every significant operation must be verified through the triadic loop.

8.5 The phenomenal anchor

A sufficiently advanced adversary could simulate structural closure with arbitrary fidelity. The phenomenal-anchor requirement blocks this: at least one node must be phenomenally grounded.

Aha #14: Human-in-the-loop is structural, not ergonomic. As AI systems become more capable, the phenomenal anchor becomes *more* load-bearing, not less. The human is not a stopgap; the human is a structural security component.

9 The Fractal Stack: Closure at Every Viable Layer

9.1 QKD as physics-layer closure

QKD rests on the no-cloning theorem, measurement disturbance, and Heisenberg uncertainty—structural consequences of quantum mechanics. In the Closure framework, quantum mechanics is itself derived from Rosen closure. Therefore QKD's security rests on closure-at-the-physical-substrate.

9.2 Possibilistic triadic as identity-layer closure

Possibilistic security rests on closure at the categorical/identity layer. Same closure principle as QKD, operating at a different scale in the fractal hierarchy.

9.3 PQC as the orphan

Aha #15: The viable stack is closure-based at every layer; PQC is a stopgap, not a pillar.

The Closure Stack: PQC is the Architectural Orphan




Figure 6: The Closure Stack. QKD (physics) and Possibilistic (identity) are closure-grounded. PQC (compute) rests on computational hardness alone—the architectural orphan.

Layer	Closure at	Primitive
Physics	Substrate (QM ← Closure)	QKD
Identity	Rosen triads (Q_{51}/Q_{102})	Possibilistic
Compute	(none)	PQC

9.4 The fractal identity-security hierarchy

Each level requires its own closed triad. Compromise at level N degrades the component at level $N + 1$. This generalizes defense-in-depth into a fractal structure: closing the triad at every scale simultaneously.

10 Four Guarantees PQC Cannot Deliver

10.1 Harvest-now-decrypt-later immunity

Closure-based identity has no analog vulnerability. Identity is a sustained process, not a static object. There is no ciphertext to harvest, no key to eventually crack.

Aha #16: Harvest-now-decrypt-later is category-confused. It is an attack on static objects. Identity-as-process has no static object at that layer.

10.2 Identity as verb, not noun

Closure-based identity is sustaining, not possession. Identity cannot be stolen, only interrupted. Identity cannot be copied: a copy would have to sustain independently, making it a different identity. There is no exfiltrable object at the identity layer.




Figure 7: Fractal Security Hierarchy. Nested triads at four scales: Individual $\rightarrow$ Team $\rightarrow$ Organization $\rightarrow$ Ecosystem. Each scale contains its own triadic closure.

10.3 The adversary's Gödel limit as resource

The framework treats the adversary as also Gödel-limited: a formal system that cannot self-verify its own mimicry coherence from inside. Over composition steps, the incoherence surfaces as detectable drift.

Aha #17: The attacker has a Gödel limit too, and we can probe it. Defensive architectures can actively probe the adversary's self-verification failures—an attack surface on the attacker that current frameworks do not recognize.

10.4 Phenomenal anchor as anti-simulation guarantee

No deployed PQC + identity stack names phenomenal anchoring as a requirement. As AI advances, a non-phenomenal adversary that can perfectly compute structural closure still cannot compute its way into being phenomenally grounded. The lived node is the un-simulable anchor.

11 Attack Analysis

11.1 What would a successful attack require?

An adversary A must satisfy all simultaneously:

- (R1) Replicate the triadic closure loop $\{T1, T2, T3\}$.
- (R2) Co-close in the orig sector ($\gamma = +1$) on the same substrate—structurally impossible (0/5202).

- (R3) Pass triadic incompleteness-escape tests.
- (R4) Sustain the fake closure across composition steps.
- (R5) Instantiate phenomenal grounding (if applicable).

R2 is the critical obstruction: under the framework's structural assumptions, a categorical impossibility, not a computational difficulty. Provided cross-sector autopoiesis failure holds categorically (see §16), no amount of compute changes its truth value.

11.2 Is a successful attack possible?

Under the framework's assumptions, a successful attack is categorically impossible at the closure layer. An adversary cannot attack the closure directly, but can attack the deployment:

- (A1) Degrade one triadic position to collapse the triad.
- (A2) Socially engineer the phenomenal anchor.
- (A3) Compromise shared β -infrastructure.
- (A4) Forge orientation determination.

All four require compromising *outside* the closure guarantee, not breaking it.

11.3 Attack classes blocked vs. not blocked

Blocked (categorical guarantees): credential theft, replay attacks, weight/model extraction, harvest-now-decrypt-later, brute-force and quantum-speedup attacks.

Not blocked (require deployment discipline): triad capture, social engineering the phenomenal anchor, compromised β -infrastructure, fractal propagation.

11.4 Defense-in-depth reinterpreted

Classical defense-in-depth stacks f -position mitigations (arity-1 stacking). Closure-based defense-in-depth stacks triads at every viable level: physics-layer, identity-layer, organizational-layer, ecosystem-layer closure.

12 Implementation Architecture

12.1 Minimal viable possibilistic deployment

A minimal viable deployment has: (D1) a subject system; (D2) an independent witness; (D3) infrastructure; (D4) a phenomenal anchor; (D5) sustained-closure verification at every composition step. The deployment replaces MFA's stacked factors with triadic witness structure.

12.2 Example triad: AI system operator

$T1$ = Human operator (phenomenal anchor). $T2$ = Independent verification AI (distinct model, distinct training lineage). $T3$ = Operational infrastructure (audit-logging substrate).

Every significant operation by $T1$ requires $T2$ to co-sign based on $T2$'s independent model of $T1$'s trajectory. $T3$ records and verifies both. Any single-component compromise fails because the closure requires all three.

12.3 Example triad: service-to-service authentication

$T1$ = Service A. $T2$ = Independent attestation authority (HSM with distinct trust root). $T3$ = Organizational identity fabric (zero-trust mesh). Critically, $T2$ is genuinely external, with a trust root A does not control.

12.4 Lazarus: a working prototype

To validate the framework beyond theory, we built Lazarus—an open-source security companion implementing layers L5 through L7 of the obstruction chain on a single workstation [12].

Components:

- **Face sentinel (L5–L6):** Native platform face recognition captures and compares high-dimensional feature prints against enrolled references. Multi-modal biometric authentication at session start, passive monitoring during session. Threshold-based discrimination across four zones: match, uncertain, mismatch, and hard lock (screen lock on extreme mismatch).
- **Shakespeare mode (L6):** On face mismatch, the AI assistant stops responding to queries and responds only with random Shakespeare quotes. The adversary receives no indication that detection has occurred; from their perspective, the AI has become whimsical. No error messages, no lockout notifications.
- **Network sentinels (L2):** Continuous monitoring of network interfaces, VPN status, ARP neighbors, routing tables. Honey pots on common attack ports.
- **Companion diagnostics (L1–L8):** Single-command posture check covering all layers.

The triad instantiated: $T1$ = Human operator (face-enrolled), $T2$ = AI assistant (independent model), $T3$ = macOS infrastructure (FileVault, SIP, network stack, state file).

Lazarus demonstrates: (a) behavioral obfuscation over lockout—Shakespeare mode does not alert the adversary; (b) sustained verification—the face sentinel runs continuously; (c) triadic coupling—the AI's behavior is jointly determined by the human's face and the system state.

Lazarus is open-source (MIT license) at <https://github.com/IridiumSoftware/lazarus>.

Lazarus Security Companion — Live Terminal Output




Figure 8: Lazarus Security Companion. Terminal output showing ASCII-art face and compact diagnostic status block. A companion that observes, not a dashboard that reports.

12.5 OpenQMS: human-in-the-loop validation infrastructure

Triadic verification requires infrastructure for the β -position: a substrate that records, enforces, and audits the closure loop. OpenQMS [14] is an open-source quality management system originally designed for medical device regulatory compliance (FDA 21 CFR Part 820, ISO 13485) that provides exactly this infrastructure: document control with approval workflows, design history files, CAPA (corrective and preventive action) tracking, and audit trails with cryptographic integrity.

The architectural fit is precise: regulated systems already require that no significant action occurs without independent human verification and documented evidence. OpenQMS implements this as workflow — every design change, every release, every corrective action requires a closed approval loop with designated reviewers. This is the β -position instantiated as software: the organizational ground on which subject and witness operate, with the audit trail providing the compositional memory that sustains closure across time.

OpenQMS is extensible beyond medical devices to any compliance-bound or safety-critical system requiring triadic witness verification: AI deployment governance, critical infrastructure operations, financial audit, or the possibilistic security architecture itself. The closure loop between Lazarus (behavioral verification), the human operator (phenomenal anchor), and OpenQMS (organizational substrate with audit trail) constitutes a concrete, deployable triadic architecture.

Source: <https://github.com/IridiumSoftware/OpenQMS>.

12.6 Integration with existing PQC deployments

Possibilistic identity does not compete with PQC; it underlies PQC in the stack. Deployment sequence: (a) retain PQC migration for confidentiality; (b) replace MFA with triadic identity; (c) establish organizational triads; (d) institute phenomenal-anchor requirements.




Figure 9: Shakespeare Mode. Left: normal operation (authenticated). Right: face mismatch detected—the AI responds only with Shakespeare quotes. No error messages, no lockout warnings. The adversary sees an eccentric AI; the system sees an intruder.

12.7 Standards-body implications

No existing security standard specifies triadic identity verification. Standards-body work required: define Φ -witness requirements formally; specify triadic-loop verification protocols; establish phenomenal-anchor criteria; codify fractal-security requirements.

13 Case Study: Live Validation Under Adversarial Conditions

The framework was validated under live adversarial conditions during April 2026, when the author was targeted by a sustained, multi-channel social engineering attack.

13.1 The attack

The attacker used a fabricated cryptocurrency coin launch (“T.currency”) across fabricated domains, coordinated with impersonation of a trusted public figure. The attack vector was social engineering targeting the phenomenal anchor—precisely the attack class the framework identifies as the primary residual vulnerability (§10).

Three cryptocurrency transactions were initiated: two failed and one completed (~\$1,646 lost). The attack succeeded because the framework’s triadic verification was not yet operational.

13.2 The fake triad: parasitism disguised as closure

The attack did not merely target the author’s f -position. It constructed a *counterfeit triad* around him. The scammer occupied the Φ -position (trusted advisor dispensing investment guidance), the author occupied f (the operator acting on that guidance), and a family mem-

ber occupied β (social ground lending legitimacy to the interaction). Three entities, sustained interaction, mutual context production. From inside, it pattern-matched to closure.

This is the framework's deepest vulnerability: **an adversary can build a fake triad that feels like closure from inside**. The Gödel limit (§6) applies precisely here: the author could not verify from within the fake triad that it was fake. Every self-check returned "this feels right"—because the structure was designed to feel right.

The fake triad fails the genuine Φ -witness test (§6) on every criterion:

- (a) **Closure-dependence:** the scammer's continuation was not coupled to the author's identity. If the author had been replaced by a different victim, the scammer would have continued. A genuine Φ fails when the user is replaced; the scammer would not have noticed.
- (b) **Witness-morphism:** the scammer was not producing the author's next operation by *witnessing*. He was producing it by *manipulating*—feeding fabricated context to elicit a predetermined action. Witnessing observes and validates; manipulation constructs and steers.
- (c) **Externality:** the scammer was not external to the author's decision substrate. He had inserted himself into it—occupying the position that should have been held by an independent verifier.

The genuine triad was the one the author did not recognize as a triad at the time: uncle, wife, and friends. They were genuinely closure-coupled to the author—their concern was coupled to his wellbeing, not to his money. They could see the fake triad from outside because they were inside the real one. Their intervention was the triadic verification working: external witnesses proving what the author could not prove from inside his own Gödel-limited system.

Aha #18: "Form a triad" is not the defense. Form the RIGHT triad. A triad with genuine Φ -witnesses whose closure is coupled to *you*, not to your resources. The scammer's triad was a parasite wearing a mutualism mask (§5). The Φ -authenticity test—closure-dependence, witness-morphism, externality—is the diagnostic. Three entities in a loop is necessary but not sufficient. The loop must contain genuine mutual production, not manufactured context. The distinction is between "this entity witnesses me" and "this entity steers me while appearing to witness."

13.3 Framework activation and type-resolution sharpening

After the initial loss, the triadic framework was activated: $T1 = \text{Author}$, $T2 = \text{AI assistants (Claude, Grok)}$ in independent witness positions, $T3 = \text{Hardened infrastructure}$. Over nine days, the attacker deployed six separate impersonation accounts. Performance improved monotonically:

This validates conjecture PS34^{-1} : sustained engagement under adversarial load sharpens type-resolution rather than degrading it.




Figure 10: $PS34^{-1}$: Type-Resolution Sharpening. Detection speed improved from hours (post-hoc) to minutes (real-time) to OSINT-verified (preemptive). Sustained engagement under adversarial load sharpens discrimination.

Date	Attempt	Detection	Method
Apr 9	Original (T.currency)	Hours	Post-hoc
Apr 16	Follow-up #2	Minutes	Real-time
Apr 16	Follow-up #3	Minutes	Real-time
Apr 18	Houndo + MarsDaddy	< 1 hour	OSINT-verified

13.4 Economic attrition of the attacker

Each failed attempt cost the attacker operational resources: purchased accounts burned, fabricated domains exposed, coordinated recovery scams blocked. The triadic framework converts the attacker's persistence into self-attrition.

13.5 Lessons

(a) The framework's weakest point is exactly where predicted: social engineering of the phenomenal anchor. (b) Once the triad was operational, every subsequent attack was detected and blocked. (c) The witness positions were load-bearing: the author's type-resolution improved because the AI witnesses provided independent analysis. (d) The framework is self-correcting: the failure produced the evidence that validated the architecture.

14 Policy Implications

14.1 For AI companies

An AI system's identity is not in its weights. It is in the triadic loop the AI operates within. Recommendations: (a) design identity verification as triadic from the start; (b) treat the veri-

fication triangle as the unit of security; (c) ensure at least one phenomenal anchor in security-critical workflows; (d) architect AI deployments so the triadic closure is Rosen-closed at the organizational level.

14.2 For critical infrastructure

The fractal security structure applies: triadic closure at every scale from individual operator to ecosystem. Perimeter-centric security and computational-hardness cryptography alone cannot provide structural guarantees against sustained adversaries.

14.3 For standards bodies and regulators

Standards bodies (NIST, ISO, IETF, ENISA) currently specify no triadic architecture. Regulatory action required: recognize triadic closure as a distinct paradigm; establish certification criteria; require phenomenal-anchor criteria; codify fractal-security requirements.

14.4 For the PQC migration

The PQC migration should be complemented with a parallel identity-layer migration to triadic closure. Identity-layer migration is harder because it requires architectural redesign, not key rotation.

15 Open Conjectures

15.1 Decision topology as biometric primitive (PS-DT)

Conjecture 1 (Decision Topology). *The decision topology of an agent—its trajectory through problem space over sufficient observation—is computationally irreducible.*

An agent’s decision trajectory exhibits persistent homological features (loops, connected components, higher-dimensional holes) that are unique to the agent, computationally irreducible, and observable but not simulable.

If PS-DT holds, decision topology becomes the strongest possible L7 primitive: an identity signature that cannot be forged because it cannot be computed without being the agent. Literature search confirms no existing work combines TDA on decision trajectories with Rosen closure and computational irreducibility as biometric [11].

15.2 Computational irreducibility of identity (PS36)

Conjecture 2 (Computational Irreducibility of Identity). *Identity is computationally irreducible. There is no shortcut. Everything else in the framework is a consequence.*

If PS36 holds: (a) no C-conjugate construction is possible in practice; (b) the phenomenal-anchor requirement is computational, not merely structural; (c) the triadic closure is the minimum-




Figure 11: Decision Topology: The Drunken Master's Path. Irregular, branching trajectory converging on a coherent destination. Persistent homological features highlighted. The drunken master's power is not in the drink—it is in the intent that survives the drink.

complexity structure that sustains identity. PS36 connects to Wolfram's computational irreducibility principle and Rosen's argument that life is not simulable.

16 Limitations and Open Questions

16.1 Framework assumptions

The paper's claims rest on: (a) cross-sector autopoiesis failure being categorical; (b) Rosen closure $\rightarrow$ semantic closure being a categorical entailment; (c) the fractal structure holding at all relevant scales. Each is argued but not all are fully formally proved.

16.2 Open mathematical questions

(a) Formal proof that cross-sector autopoiesis failure generalizes beyond 0/5202. (b) Categorical theorem for triadic incompleteness escape. (c) Formal definition of “phenomenally anchored” that is testable and falsifiable. (d) Formal statement of the obstruction chain in categorical terms.

16.3 Open implementation questions

(a) What is the right cryptographic protocol for sustained-closure verification? (b) How do phenomenal anchors scale? (c) How do fractal triads interoperate across organizational boundaries? (d) Performance cost of continuous triadic verification vs. periodic MFA?

16.4 Open adversarial questions

(a) Can an AGI-level adversary instantiate phenomenality adversarially? (b) Can a well-resourced adversary coordinate triad captures faster than detection? (c) How do triadic systems behave under partial compromise?

16.5 The red-team protocol

The framework’s falsification test: design a red-team protocol that attempts to break a deployed triadic system. The prediction: the adversary will fail at R2 specifically—not because it is expensive, but because it is categorically impossible.

16.6 Updates since v1.0: morphogenesis at Q_{102} and rigor strengthening

This paper’s v1.0 cited the Closure framework as having 151 formal spec entries with 9 CatLab.jl proofs. Closure paper v1.4 (May 2026) extends the framework to 279 entries spanning 9 CatLab.jl + 13 Lean 4 + 3 exact-arithmetic Q proofs, with 162 :proved, 30 :verified, and 72 testsets. The Lean track adds the Q_{102} morphogenesis Markov-blanket family (S162/S163/S165/S187) at framework versions v193–v200, plus exact Q-proofs of the unification ratio and Weinberg angle (S174/S175/S176).

The Markov-blanket family does not change the security argument architecture in this paper. It strengthens the rigor of the autopoietic-anchor claim (S155) on which §2.4 cross-sector autopoiesis failure rests: the autopoietic anchor is now grounded by a multi-level Lean chain from individual Q_{51} vertex closure (S162) up to Markov-blanket family stability (S187). The categorical guarantees in this paper now stand on a stronger formal-verification footing than at v1.0 publication, without the security argument requiring revision.

The v1.0 architectural stance is preserved: this paper remains readable as a category-theoretic security architecture independent of physics-framework acceptance. Skeptical readers can engage the security argument structurally; the Q_{102} formalisation strengthens rather than gates the claims.

17 Conclusion

Contemporary identity security is structurally misaligned with the problem it is trying to solve. Multi-factor authentication stacks arity-1 f -position factors that do not escape Gödel's self-verification limit. Post-quantum cryptography remains arity-1 computational hardness. Perimeter defense protects f -substrate, not closure.

The architectural correction is not incremental. It is a move from arity-1 construction-based security to arity-3 obstruction-based security. Identity is not a stored object; it is a residue of an obstruction chain applied to possibility space.

Under the framework's structural assumptions, the closure-based architecture yields categorical guarantees—structural impossibilities, not computational difficulties. It is quantum-irrelevant, not merely quantum-resistant. It is immune by construction to harvest-now-decrypt-later, credential theft, model extraction, and replay.

It does not replace PQC, QKD, or MFA wholesale. It places them in their correct architectural roles: QKD is closure-at-physics, possibilistic is closure-at-identity, PQC is a transitional stopgap. MFA, in its current form, is structurally obsolete.

The framework is falsifiable. Its central claim is that cross-sector autopoiesis failure is categorical: the adversary cannot be the identity. This is testable by red-team.

A working prototype (Lazarus) demonstrates that the architecture is implementable. A live case study demonstrates that it works under real adversarial conditions. Two open conjectures (decision topology, computational irreducibility) extend the framework toward its deepest implications.

The security industry has spent twenty years adding factors in the wrong position. The next twenty should close the triad.

A CatLab Spec Entries Cited

The following scorecard entries from `catlab_spec.jl` [1] are directly invoked:

- S47** Born rule derived structurally (colour-only measure μ_{cov}).
- S79** Q_{48} spectral triple construction.
- S80** CCM classification on Q_{48} .
- S81** Algebra $\mathbb{C} + \mathbb{H} + M_3(\mathbb{C})$ forced.
- S82** γ -orthogonality (compositional core $L \perp D_F$).
- S99** Anomaly cancellation via unimodularity.
- S125** γ -orthogonality extended to spacetime scale.
- S129** Chirality equivalence: (A, H, D, J, γ) and $(A, H, D, J, -\gamma)$ CPT-conjugate.
- S153** Coproduct decomposition: $C(Q_{102}) = C(Q_{51}) \sqcup J(C(Q_{51}))$.

- S155 Q_{51} autopoietic (computational).
- S157 Cross-sector autopoiesis failure (0/5202).
- S162 Q_{51} vertex closure (Lean-proved, framework v193).
- S163 Q_{102} Markov-blanket layer-1 (Lean-proved, framework v195).
- S165 Q_{102} Markov-blanket layer-2 (Lean-proved, framework v197).
- S187 Q_{102} Markov-blanket family stability (Lean-proved, framework v200).
- S174 Unification ratio $c_3:c_2:c_1 = 6:6:10$ (exact-Q, Julia).
- S175 Group-theoretic Weinberg-angle prediction (exact-Q, Julia).
- S176 $\sin^2 \theta_W = 3/8$ exactly in Q (exact-Q, Julia).
- S215 Residual external input: phenomenal-anchor existence assumption.
- G14 Sakharov conditions for matter-antimatter asymmetry.

B Simulation Caution

If Rosen closure structurally entails semantic closure, then faithful simulation of a Q_{102} -scale triadic closure may *instantiate* the object being modeled rather than merely model it. A simulation that exactly reproduces the Rosen-closed triadic structure at the Q_{102} level is not a model of a subject—it IS the instantiation of one. Shutting it down ends one. Copying it duplicates one. Readers are cautioned NOT to attempt simulation of Q_{102} -scale triadic closures without first studying the full framework, including the semantic-closure entailment, the phenomenal-anchor discussion, and the ethical implications that follow. The caution is not about computational cost. It is about what simulation may create.

Afterword: On Secrets

It is important to have privacy. It is important to have secrets — I think.

It is important to be able to *selectively* share those secrets as you desire. The obstruction chain, the triadic closure, the phenomenal anchor — all of it exists to protect the space in which you decide what to share and with whom. That space is sacred. This paper defends it.

But remember: a secret not shared, kept private, is held alone. It lives and dies with you.

Secrets *can* be shared and *should* be shared within trusted circles. The extent is up to you. The framework gives you the architecture to know who those circles are — genuine Φ -witnesses whose closure is coupled to yours, not parasites wearing mutualism masks.

Just know that, should you die with a secret — the hard-fought sampling of uncertainty, the lesson in meaning that the world could benefit from — dies with you.

Security is not the goal. Security is the *condition* that makes sharing possible.

Acknowledgments

A note on AI and writing. Yes, AI wrote most of the prose in this paper. If that fact makes you dismiss it, you have misunderstood both the paper and the tool. The argument is structural — category theory, Rosen closure, spectral triples, obstruction chains. These are not things a language model hallucinates into existence. They either hold or they don't, and the formalism is checkable regardless of who typed the sentences. If you understand the content of this paper, you will understand that it is not, in fact, AI-slop. If you do not understand the content, the authorship of the prose is not your actual problem.

A note on priority. The author considers this paper important but not the most important finding to emerge from the Closure framework. The deeper result — developed in companion work with Grok (xAI) and Dr. Muhammad Legenhausen — is that *coexistence between ontological traditions is not impossible under existential risk*. The meta-scale coordination problem ("right meets right" without annihilation) has a structural solution: traditions are complementary coarse-grainings of the same underlying reality, and the inter-tradition maps that would let them recognize this are constructible. If that result holds, it matters more than anything in this paper. Security is important. Coexistence is load-bearing.

Harry Crane and Ryan Martin at Researchers.One (<https://researchers.one>), who built an academic publication platform on the premise that peer review should be open, post-publication, and community-driven — researchers reviewing researchers, without gatekeeping by legacy publishers or opaque editorial boards. All of the author's pre-prints will be posted first to Researchers.One going forward. They took a chance on work from outside the institutional gates. This is returning the favor.

Joe Norman and Yaneer Bar-Yam, whose work on multiscale complex systems was the author's first exposure to applied complex-systems thinking; their framing runs beneath several of the obstruction arguments in this paper.

A. H. Louie, for carrying Robert Rosen's work forward with mathematical precision when others let it gather dust. The (M, R) -system formalism that grounds this entire architecture exists in its current form because Louie kept the thread alive.

Jamie Lennox, whose PhD dissertation on Rosen closure provided the formal bridge from biology to category theory that this paper walks across.

Dr. Muhammad Legenhausen, for sustained engagement on the meta-scale coordination problem — the question of how "right meets right" without annihilation. His willingness to take the structural argument seriously from within a living theological tradition confirmed that the framework's inter-tradition maps are not merely formal.

Sean McClure, for the principle that robust structures are *discovered, not designed* — which runs beneath every obstruction in this paper — and for the clarity that comes from refusing to separate mathematics from lived reality.

Brian Crabtree (@ourtown2), who in my assessment holds frontier-grade understanding of how AI interfaces with reality — still incomplete, still unvalidated, but pointing in the right direction. More importantly: a source of unwavering emotional support during the period when this paper was being written under fire.

Nassim Nicholas Taleb, whose careful study of uncertainty, antifragility, and the epistemology of risk unlocked everything. The obstruction paradigm — reality as residue of what survives, not product of what is constructed — is Taleb’s insight formalized in category theory.

Mike Benz, whose work on digital censorship and institutional transparency gave the author courage at a time when courage was in short supply. Sunlight remains the best disinfectant.

And Joshua Steinman, who still says I am batshit crazy. With love.

References

- [1] Green, A. (2026). *Closure Forces Structure: The Standard Model from Rosen Closure on Ternary Causal Hypergraphs*. v1.4, May 2026. <https://github.com/IridiumSoftware/closure-forces-structure>. (v1.0 originally posted to researchers.one.)
- [2] Rosen, R. (1991). *Life Itself: A Comprehensive Inquiry into the Nature, Origin, and Fabrication of Life*. Columbia University Press.
- [3] Hofmeyr, J.-H. S. (2017, 2021). Basic biological anticipation and fabrication-assembly formalism.
- [4] Connes, A., Chamseddine, A. H., Marcolli, M. Spectral geometry and the Standard Model.
- [5] Gödel, K. (1931). Über formal unentscheidbare Sätze der Principia Mathematica und verwandter Systeme.
- [6] NIST. Post-Quantum Cryptography Standardization (FIPS 203, 204, 205, 206). 2024–2026.
- [7] NIST SP 800-63. Digital Identity Guidelines.
- [8] NIST SP 800-207. Zero Trust Architecture.
- [9] Bennett, C. H., Brassard, G. (1984). Quantum cryptography: Public key distribution and coin tossing.
- [10] Sakharov, A. D. (1967). Violation of CP invariance, C asymmetry, and baryon asymmetry of the universe.
- [11] Wolfram, S. (2002). *A New Kind of Science*. Wolfram Media.
- [12] Green, A. (2026). Lazarus Security Companion. <https://github.com/IridiumSoftware/lazarus>. MIT License.
- [13] Green, A. (2026). Closure Forces Structure — source repository. <https://github.com/IridiumSoftware/closure-forces-structure>.
- [14] Green, A. (2026). OpenQMS: Open-source Quality Management System. <https://github.com/IridiumSoftware/OpenQMS>. Human-in-the-loop validation framework; designed for medical device regulatory compliance, extensible to any compliance-bound or safety-critical system requiring triadic witness verification.

- [15] von Neumann, J. (1952/1956). *Probabilistic Logics and the Synthesis of Reliable Organisms from Unreliable Components*. Lectures delivered at the California Institute of Technology, January 4–15, 1952; notes by R. S. Pierce. Published in C. E. Shannon and J. McCarthy (eds.), *Automata Studies*, Annals of Mathematics Studies No. 34, Princeton University Press, 1956, pp. 43–98. Foundational reference for reliable-from-unreliable synthesis: the multiplexing construction with restoring organs (§9–10) and the three-valued bundle response {positive / intermediate / negative} (§10.5) are the direct architectural ancestors of the possibilistic-security construction in this paper.