

Language Specific

Interview Cracker question bank

Generated from the Markdown sources in the Interview Cracker repository. Every code snippet in these pages was executed and checked before publication.

Java Interview Questions

[Easy] Q. What is the difference between JDK, JRE and JVM?

Answer. **JVM** executes bytecode and is the thing that makes Java portable - one `.class` file runs anywhere a JVM exists. **JRE** is the JVM plus the standard class libraries: enough to run Java. **JDK** is the JRE plus development tools (`javac`, `jdb`, `jar`): enough to build Java.

"Write once, run anywhere" is a property of bytecode plus a per-platform JVM, not of the source language.

[Easy] Q. Primitive vs reference types?

Answer. Primitives (`int`, `double`, `boolean`, `char`, ...) hold values directly, live on the stack when local, cannot be null, and have no methods. Reference types hold a pointer to a heap object, can be null, and carry methods.

The consequence that produces bugs:

```
String a = new String("hi");
String b = new String("hi");
a == b           // false - different objects
a.equals(b)      // true  - same characters
```

`==` compares references for objects, values for primitives. **Always use `.equals()` for objects.**

Autoboxing makes this worse:

```
Integer x = 127, y = 127;
x == y;           // true  - cached (-128..127)
Integer p = 128, q = 128;
p == q;           // false - outside the cache
```

Same code, different answer depending on the value. Never compare boxed types with `==`.

[Hard] Q. Explain the equals/hashCode contract.

Answer. If `a.equals(b)` then `a.hashCode() == b.hashCode()`, **always**. The reverse is not required - equal hash codes with unequal objects is just a collision.

Override one and you must override the other. Break it and hash-based collections fail silently:

```
Map<Point, String> map = new HashMap<>();
map.put(new Point(1, 2), "origin-ish");
map.get(new Point(1, 2)); // null, if hashCode() was not overridden
```

The lookup hashes to a different bucket and never finds the entry.

The second half of the contract: **a key's hash must not change while it is in a collection**. Mutating a field used by `hashCode` strands the entry - present but unreachable, and `remove()` will not find it either. Prefer immutable keys; `record` types give you correct `equals/hashCode` for free.

[Medium] Q. Compare the collections.

Answer.

Interface	Implementation	Ordering	Notes
List	ArrayList	insertion	O(1) index, O(n) middle insert. The default.

	LinkedList	insertion	O(1) ends, poor locality - rarely the right choice
Set	HashSet	none	O(1) average
	LinkedHashSet	insertion	O(1), remembers order
	TreeSet	sorted	O(log n), needs Comparable/Comparator
Map	HashMap	none	O(1) average; chains become trees past 8 entries
	LinkedHashMap	insertion or access	access-order mode gives you an LRU cache
	TreeMap	sorted	O(log n), range queries

`ArrayList` unless you need ordering or sorting. `LinkedList` is almost never the answer despite what its Big-O table suggests - cache locality wins.

[Medium] Q. Checked vs unchecked exceptions?

Answer. Checked (extend `Exception`) must be declared or caught - the compiler enforces it. Intended for recoverable conditions: `IOException`, `SQLException`.

Unchecked (extend `RuntimeException`) need no declaration. Intended for programming errors: `NullPointerException`, `IllegalArgumentException`, `IndexOutOfBoundsException`.

`Error` (e.g. `OutOfMemoryError`, `StackOverflowError`) signals a JVM-level problem you should not catch.

The design debate is worth knowing: checked exceptions were meant to force handling, but in practice they encourage `catch (Exception e) {}` and leak implementation details through signatures. Later languages (C#, Kotlin, Scala) deliberately omitted them. Worked example:

`java/exceptions/exception_handling_basics.java`.

[Hard] Q. What is type erasure?

Answer. Generics are a **compile-time** feature. The compiler checks types, then erases them - `List<String>` becomes plain `List` in the bytecode, with casts inserted automatically. This was done for backwards compatibility with pre-generics code.

The consequences you can be asked to explain:

```
List<String> a = new ArrayList<>();
List<Integer> b = new ArrayList<>();
a.getClass() == b.getClass();      // true - both are just ArrayList

// Illegal, because the type is not available at runtime:
// if (obj instanceof List<String>) { }
// T[] array = new T[10];
```

You also cannot overload on `List<String>` vs `List<Integer>` - after erasure both methods have identical signatures. Contrast with C#, where generics are reified and the runtime does know the type argument.

[Medium] Q. How does garbage collection work?

Answer. The JVM reclaims objects no longer **reachable** from GC roots (stack references, statics, JNI references). Note it is reachability, not reference counting - so cycles are collected correctly.

The design rests on the **generational hypothesis**: most objects die young. So the heap is split:

- **Young generation** (Eden + two survivor spaces) - collected frequently with
- **Old generation** - objects that survived several collections; collected

Modern collectors (G1, ZGC, Shenandoah) do most work concurrently to keep pause times low - ZGC targets sub-millisecond pauses on large heaps.

`System.gc()` is a suggestion the JVM may ignore. You cannot force collection, and calling it is almost always a mistake. Memory leaks in Java are real but take a different form: objects still referenced but never used - a static collection that only ever grows, an unremoved listener, an unclosed resource.

[Medium] Q. What does the Stream API give you?

Answer. A declarative pipeline over a sequence, with lazy intermediate operations and one terminal operation that triggers execution.

```
List<String> names = people.stream()
    .filter(p -> p.age() >= 18)           // intermediate, lazy
    .map(Person::name)                   // intermediate, lazy
    .sorted()
    .toList();                          // terminal, runs the pipeline
```

Nothing executes until the terminal operation, which allows fusion and short-circuiting (`findFirst` stops early).

Two cautions worth raising unprompted: a stream is **single-use** - reusing one throws

`IllegalStateException`; and `parallelStream()` is not free speed. It uses the common `ForkJoinPool`, so it helps only for large datasets with CPU-bound, independent, side-effect-free work, and can be slower otherwise. Worked example: `java/streams/group_and_collect_with_streams.java`.

[Medium] Q. `String`, `StringBuilder`, `StringBuffer`?

Answer. `String` is **immutable** - every concatenation allocates a new object, so building in a loop is $O(n^2)$.

`StringBuilder` is a mutable buffer, not thread-safe, and is what you want. `StringBuffer` is the synchronised version: slower, and almost never needed since a builder is normally local to one thread.

Note the compiler rewrites simple + concatenation into builder calls, so `"a" + b + "c"` is fine - it is concatenation **inside a loop** that is the problem. Worked example:

`java/strings/string_immutability_and_stringbuilder.java`.

JavaScript Interview Questions

[Easy] Q. `var`, `let` and `const`?

Answer.

	Scope	Hoisting	Reassign
<code>var</code>	function	hoisted, initialised undefined	yes
<code>let</code>	block	hoisted into the temporal dead zone	yes
<code>const</code>	block	same as <code>let</code>	no

`const` prevents **rebinding the name**, not mutation of the value:

```
const user = { name: "Sara" };
user.name = "Ali";           // fine - the object is mutable
user = {};                   // TypeError - cannot rebound
```

Use `const` by default, `let` when you must reassign, and `var` never.

[Medium] Q. What is a closure?

Answer. A function that retains access to the variables of the scope it was created in, even after that scope has returned.

```
function counter() {
  let count = 0;           // stays alive via the closure
  return {
    increment: () => ++count,
    value: () => count,
  };
}
const c = counter();
c.increment(); c.increment();
c.value();           // 2
```

`count` is genuinely private - unreachable except through the returned functions. This is the basis of the module pattern, memoisation, and every callback that "remembers" something.

The classic interview trap:

```
for (var i = 0; i < 3; i++) setTimeout(() => console.log(i)); // 3, 3, 3
for (let i = 0; i < 3; i++) setTimeout(() => console.log(i)); // 0, 1, 2
```

`var` is function-scoped, so all three callbacks close over **one** variable, which is 3 by the time they run. `let` creates a fresh binding per iteration. Worked example: [javascript/basics/closures.js](#).

[Hard] Q. Explain the event loop.

Answer. JavaScript is single-threaded but non-blocking. The runtime has:

- a **call stack** - what is executing now;
- **Web APIs / host APIs** - timers, network, file I/O, running outside the
- a **macrotask queue** - `setTimeout`, I/O callbacks, UI events;
- a **microtask queue** - promise callbacks, `queueMicrotask`.

The loop: when the stack empties, **drain the entire microtask queue**, then take **one** macrotask, then drain microtasks again. Microtasks always have priority.

```
console.log("1");
setTimeout(() => console.log("2"), 0); // macrotask
Promise.resolve().then(() => console.log("3")); // microtask
console.log("4");
// 1, 4, 3, 2
```

2 comes last despite a 0 ms delay, because the microtask queue is drained first. The follow-up: an infinite chain of microtasks **starves** the macrotask queue and freezes the page - microtask priority is not free. Worked example: `javascript/async/promises_and_event_loop.js`.

[Medium] Q. How does `this` get its value?

Answer. In a normal function `this` is determined by **how it is called**, not where it is defined. Four rules, in precedence order:

- 1 **new** - `this` is the new object.
- 2 **Explicit** - `call`, `apply`, `bind` set it.
- 3 **Implicit** - `obj.method()` sets `this` to `obj`.
- 4 **Default** - `undefined` in strict mode, `globalThis` otherwise.

Arrow functions ignore all four: they have **no** `this` **of their own** and inherit it lexically from the enclosing scope. That is the fix for the classic bug:

```
class Timer {
  constructor() { this.seconds = 0; }
  startBroken() { setInterval(function () { this.seconds++; }, 1000); } // wrong `this`
  start()       { setInterval(() => { this.seconds++; }, 1000); }      // correct
}
```

Worked example: `javascript/basics/this_and_binding.js`.

[Medium] Q. `==` vs `===`?

Answer. `===` compares type and value with no conversion. `==` coerces first, using rules that are genuinely surprising:

```
0 == ""; // true
0 == "0"; // true
"" == "0"; // false <- not transitive!
null == undefined // true
null == 0 // false
NaN == NaN // false
```

Always use `===`. The one accepted exception is `x == null`, which checks for `null` or `undefined` in a single test.

For `NaN`, use `Number.isNaN(x)`. `NaN !== NaN` is required by IEEE 754 and is also why `[NaN].includes(NaN)` is true (it uses `SameValueZero`) while `[NaN].indexOf(NaN)` is `-1` (it uses `===`).

[Medium] Q. What is prototypal inheritance?

Answer. Every object has a hidden link to another object, its **prototype**. A property miss walks up that chain until it is found or the chain ends at `null`.

```
const animal = { speak() { return `${this.name} makes a sound`; } };
const dog = Object.create(animal);
dog.name = "Rex";
dog.speak(); // found on the prototype
```

`class` syntax is sugar over this - there are no classical classes underneath, just constructor functions and prototype objects. That is why you can add a method to every existing instance at runtime by assigning to the prototype, which classical inheritance does not allow.

[Medium] Q. Promise, async/await, and how do you run things in parallel?

Answer. A promise represents a value that is not ready yet, in one of three states: pending, fulfilled, rejected. `async/await` is syntax over promises - an `async` function always returns one, and `await` suspends until it settles.

The mistake that matters:

```
// Sequential - 3 seconds, and usually a bug
const a = await fetchA();
const b = await fetchB();

// Parallel - 1 second
const [a, b] = await Promise.all([fetchA(), fetchB()]);
```

If the calls are independent, awaiting them one at a time wastes the whole latency of each. Know the four combinators:

- `Promise.all` - all succeed, or reject on the **first** failure.
- `Promise.allSettled` - wait for all, never rejects; inspect each result.
- `Promise.race` - first to **settle**, success or failure (used for timeouts).
- `Promise.any` - first to **succeed**.

Worked example: `typescript/async/async_await_parallel_vs_sequential.ts`.

[Medium] Q. Debounce vs throttle?

Answer. Both limit how often a function runs, in opposite ways.

- **Debounce** - wait until the events stop, then run once. Search-as-you-type,
- **Throttle** - run at most once per interval while events continue. Scroll

"Fire after the user stops typing" is debounce; "fire at most every 200 ms while scrolling" is throttle. Worked example: `javascript/utilities/debounce_with_cancellation.js`.

Python Interview Questions

[Easy] Q. Mutable vs immutable - and why does it matter?

Answer. Immutable: int, float, str, tuple, frozenset, bytes. Mutable: list, dict, set, bytearray, most custom classes.

It decides three things: whether a value can be a dict key (hashable, which requires immutable), whether passing it to a function can change the caller's object, and whether it is safe to share between threads.

The classic bug it causes:

```
def append_to(item, target=[]):      # DANGER: evaluated once, at def time
    target.append(item)
    return target

append_to(1)    # [1]
append_to(2)    # [1, 2] <- the same list, still there
```

Default arguments are evaluated **once**, when the function is defined. Use `None` as the sentinel:

```
def append_to(item, target=None):
    if target is None:
        target = []
    target.append(item)
    return target
```

[Easy] Q. is vs ==?

Answer. `==` compares **values** (via `__eq__`); `is` compares **identity** - whether both names point to the same object.

```
a = [1, 2, 3]
b = [1, 2, 3]
a == b    # True - same contents
a is b    # False - two distinct objects
```

Use `is` only for singletons: `is None`, `is True`, `is False`.

The confusing part is small-integer and string caching. `256 is 256` is `True` because CPython interns small integers (-5 to 256); `1000 is 1000` may be `False` depending on context. This is an implementation detail you must never rely on - and a favourite trick question.

[Hard] Q. What is the GIL and what does it mean for you?

Answer. The Global Interpreter Lock is a mutex ensuring only one thread executes Python bytecode at a time, even on a many-core machine. It exists because CPython's reference-counting memory management is not thread-safe, and one coarse lock was far simpler and faster for single-threaded code than locking every object.

The practical consequence:

- **CPU-bound work gets no speedup from threads.** Four threads on four cores
- **I/O-bound work does benefit**, because the GIL is released around blocking

Worth knowing this is changing: PEP 703 adds an optional free-threaded build (3.13+) with no GIL, and 3.12+ supports per-interpreter GILs. Saying "the GIL is being removed as an option, gradually" is more accurate than either "it's gone" or "Python can't do parallelism".

[Medium] Q. What is a generator and why use one?

Answer. A function containing `yield`. Calling it returns a lazy iterator that computes values on demand rather than building a list.

```
def read_large_file(path):
    with open(path) as f:
        for line in f:
            yield line.strip()          # one line in memory, not the whole file
```

Two benefits: **constant memory** regardless of input size, and the ability to represent infinite sequences. The costs: you can only iterate once, and you cannot index or take `len()`.

Use `()` instead of `[]` to get a generator expression: `sum(x*x for x in range(10**8))` never allocates the list. Worked example: `python/generators/log_pipeline_with_generators.py`.

[Medium] Q. What is a decorator?

Answer. A callable that takes a function and returns a replacement, used to add behaviour without editing the original.

```
import functools, time

def timed(func):
    @functools.wraps(func)          # preserve __name__, __doc__, signature
    def wrapper(*args, **kwargs):
        start = time.perf_counter()
        try:
            return func(*args, **kwargs)
        finally:
            print(f"{func.__name__} took {time.perf_counter() - start:.4f}s")
    return wrapper

@timed
def work(): ...

@timed is exactly work = timed(work).
```

`functools.wraps` **is the detail interviewers check for**. Without it the decorated function reports the wrapper's name and loses its docstring, which breaks introspection, documentation tools and debugging. Worked example: `python/decorators/retry_decorator_with_backoff.py`.

[Medium] Q. Shallow vs deep copy?

Answer. A **shallow copy** (`list(x)`, `x[:]`, `copy.copy`) makes a new outer object holding **references to the same inner objects**. A **deep copy** (`copy.deepcopy`) recursively copies everything.

```
import copy
original = [[1, 2], [3, 4]]
shallow = copy.copy(original)
shallow[0].append(99)
original          # [[1, 2, 99], [3, 4]]  <- mutated!

deep = copy.deepcopy(original)
deep[0].append(100)
original          # unchanged
```

Deep copy is slower and fails or loops on some structures - it handles cycles, but not open file handles or sockets. Prefer immutable data over copying.

[Medium] Q. What does a context manager do?

Answer. Guarantees cleanup via `__enter__` / `__exit__`, so a resource is released even if an exception is raised.

```
from contextlib import contextmanager

@contextmanager
def timer(label):
    start = time.perf_counter()
    try:
        yield
    finally:
        # runs on exception too
        print(f"{label}: {time.perf_counter() - start:.3f}s")
```

with open(...) is the everyday example: the file closes on any exit path. Worked example: `python/context-managers/custom_context_managers.py`.

[Medium] Q. `__str__` vs `__repr__`?

Answer. `__repr__` is for **developers** - unambiguous, ideally valid Python that would recreate the object. It is what the REPL and containers show. `__str__` is for **users** - readable.

If you implement only one, implement `__repr__`: `__str__` falls back to it, but not the other way round. Worked example: `python/oop/dunder_methods.py`.

[Medium] Q. What are `*args` and `**kwargs`?

Answer. `*args` collects extra positional arguments into a tuple; `**kwargs` collects extra keyword arguments into a dict. In a call, the same symbols unpack:

```
def f(a, b, c): ...
values = [1, 2, 3]
f(*values)                # unpacks positionally

config = {"a": 1, "b": 2, "c": 3}
f(**config)               # unpacks by keyword
```

This is what lets a decorator wrap any function signature.