v1.0 OAS 3.0.1

NavPro API

Terms of Service

Download OpenAPI Document

Welcome to the NavPro API documentation. NavPro enables fleet operators and integration partners to manage drivers, trips, vehicles, and fleet assets programmatically — including driver invitation, GPS tracking, trip routing, document management, and more. By accessing or using the NavPro API, you are agreeing to the Trucker Path Terms of Service.

Need help? Email us at: integrations@truckerpath.com

Release Note

03/31/2026 NavPro API is now live

API Versioning

Current version: **v1** (stable). The base URL is `https://api.truckerpath.com/navpro`.

Non-breaking additions (new optional fields, new endpoints) are introduced without a version bump. Breaking changes will be released under a new major version (e.g., `/v2/...`) with advance notice.

Rate Limiting

To ensure reliable service across all integration partners, we recommend keeping your request rate below **25 requests per second (QPS)** per client. Exceeding this threshold may result in degraded response times.

If your integration requires higher throughput, please contact us at integrations@truckerpath.com.

Server
https://api.truckerpath.com/navpro

Production

Authentication Authorization

To access the NavPro API, you need a **Client Identifier** and a **JWT token**. **Option 1 — Self Ser...** More

Bearer Token: Token

Client Libraries

Shell Ruby Node.js PHP Python More

```
Shell Curl
```

0. Drivers APIS

The API allows partners to invite drivers to a network of NavPro operators and perform various operational behaviors.

Operations

```
   POST  /api/driver/query
   POST  /api/driver/performance/query
   POST  /api/driver/invite
   POST  /api/driver/edit
 DELETE  /api/driver/delete/{driver_id}
```

Query Drivers

Enable filtering out all drivers owned by the company based on specific criteria.

Body · QueryDriverInfo required application/json

driver_created_after_time string · `^\d{4}-\d{2}-\d{2}$` Example

After the time when the driver was invited to the company. Please enter a date in the yyyy-MM-dd format, otherwise an error will occur.

driver_ids array integer[] Example

The unique IDs of the drivers.

---

driver_status string · enum Example

The driver's state.

values

ACTIVE

INACTIVE

PENDING

---

driver_updated_after_time string · `^\d{4}-\d{2}-\d{2}$` Example

After the time when changes were made to the driver's information. Please enter a date in the yyyy-MM-dd format, otherwise an error will occur.

---

page integer · int32 · min: 0 Example

Current page

---

size integer · int32 · min: 1 · max: 500 Example

Page size

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

POST /api/driver/query Shell Curl

```shell
curl https://api.truckerpath.com/navpro/api/driver/query \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "page": 0,
  "size": 20,
  "driver_ids": [
```

```
    36711,
    87741
  ],
  "driver_status": "ACTIVE",
  "driver_updated_after_time": "2023-05-20",
  "driver_created_after_time": "2023-05-05"
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```
{
  "total": 1000,
  "page": 0,
  "data": [
    {
      "driver_id": 12154,
      "basic_info": {
        "driver_first_name": "John",
        "driver_last_name": "Doe",
        "carrier": "Big Fleet Co.",
        "work_status": "IN_TRANSIT",
        "terminal": "Terminal A",
        "driver_type": "OWNER_OPERATOR_OO",
        "driver_phone_number": "111-222-3333",
        "driver_email": "johndoe@driver.com"
      },
      "driver_location": {
        "last_known_location": "S Martin L King Blvd, Las Vegas, NV",
        "latest_update": 1681440338089,
        "timezone": "PDT"
      },
      "driver_activities": [
        {
          "time": 1681401600000,
          "activities": [
            "John Doe joined Big Fleet Co."
          ]
        }
      ],
      "loads": {
        "driver_assign_loads": [
          {
            "load_id": 9964255,
            "load_show_id": "15",
            "customer": "ATS",
            "revenue": 500,
            "origin": "GA, United States",
            "destination": "Aledo, IL, United States",
```


Query Driver Performance

Query driver performance statistics within a specified time range. Optionally filter by a single driver ID. Returns mileage and time metrics for each driver, with pagination support.

Body · QueryDriverPerformanceInfo required application/json

time_range object · TimeRange required

Time range for the GPS trail query. Must not exceed 30 days. Contains start_time and end_time in ISO 8601 UTC format (e.g. 2026-03-01T00:00:00Z).

+ Show Child Attributes

driver_id integer · int32 Example

The unique ID of the driver to filter by. If not provided, returns performance data for all drivers under the company.

page integer · int32 · min: 0 Example

Current page

page_size integer · int32 · min: 1 · max: 500 Example

Page size

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error


```
      "pickup_date": 1681844400000,
      "delivery_date": 1681862400000
    }
  ],
  "driver_current_load": {
    "load_id": 9964234,
    "load_show_id": "10",
    "origin": "Pueblo, CO",
    "destination": "Los Angeles, CA",
    "pickup_date": 1680310861000,
    "delivery_date": 1681794989000
  }
},
"contact_detail_info": {
  "driver_street_address": "2031 Burroughs Ave",
  "driver_city": "New York",
  "driver_country": "UNITED_STATES",
  "driver_state": "CA",
  "zip_code": "12314",
  "emergency_contact_name": "John Doe",
  "emergency_contact_number": "222-222-4444",
  "emergency_contact_email": "janedoe@example.com"
},
"license_detail_info": {
  "license_expiration": "2027-08-03",
  "license_country": "UNITED_STATES",
  "license_state": "AL",
  "license_type": "A",
  "restrictions": [
    "E"
```


POST /api/driver/performance/query Shell Curl

```shell
curl https://api.truckerpath.com/navpro/api/driver/performance/query \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "page": 0,
  "driver_id": 36711,
  "time_range": {
    "start_time": "2026-03-01T00:00:00Z",
    "end_time": "2026-03-31T23:59:59Z"
  },
  "page_size": 20
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "total": 1000,
  "page": 0,
  "data": [
    {
      "driver_id": 36711,
      "oor_miles": 12.5,
      "schedule_miles": 500,
      "actual_miles": 512.5,
      "schedule_time": 480,
      "actual_time": 495
    }
  ],
  "code": 200,
  "success": true,
  "msg": "success",
  "page_size": 20
}
```


OK

Invite Drivers

Invite drivers to the NavPro carrier network and create a Trucker Path account for them simultaneously.

Body · InviteDriverInfo

required application/json

driver_info array object[] · DriverInfo[] required

Basic information of invited drivers.

Individual driver invitation details.

+ Show Child Attributes

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

POST /api/driver/invite Shell Curl

```shell
curl https://api.truckerpath.com/navpro/api/driver/invite \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "driver_info": [
    {
      "driver_first_name": "John",
      "driver_last_name": "Doe",
      "driver_phone_number": "111-222-3333",
      "driver_password": "password123",
      "driver_email": "johndoe@driver.com",
      "driver_type": "OWNER_OPERATOR_OO"
    }
  ]
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```json
{
  "code": 200,
  "success": true,
  "msg": "success",
  "driver_result": {
    "success_drivers": [
      {
        "driver_id": 12154,
        "driver_email": "johndoe@driver.com"
      }
    ],
    "fail_drivers": [
      {
        "driver_email": "invalid@driver.com",
        "fail_case": "Email already exists"
      }
    ]
```

```
}
```

OK

Edit Driver

This API is used to edit a driver's information within your company.

Body · EditDriverInfo

required application/json

driver_id integer · int32 required Example

The ID of the driver you want to edit. Data can be obtained through /api/driver/query.

driver_phone_number string · `\d{3}-\d{3}-\d{4}` required Example

The driver's phone number. It should follow the format xxx-xxx-xxxx. Failure to adhere to this format may result in system errors. Please ensure the phone number is correctly formatted to avoid any issues.

driver_type string · enum required Example

Type of the invited driver.

Owner Operator (OO):Owner operator who gets paid a percentage of the total weekly revenue.

Company Driver (CM):Company driver who gets paid per mile.

Lease Owner (LO):Lease owner who gets paid the same way as OOs (they don't own the truck, rather, they rent it and take full responsibility for fuel and maintenance).

Company Driver (C):Company driver gets paid a percentage of the total weekly revenue (but less than the OO).

Other:If a driver type was not selected, the default type is Other.

values

- `OWNER_OPERATOR_OO`
- `COMPANY_DRIVER_CM`
- `LEASE_OWNER_LO`
- `COMPANY_DRIVER_C`
- `OTHER`

contact_detail_info object · ContactDetailInfo Example

Additional contact information for the driver.

+ Show Child Attributes

driver_first_name string · max length: 512 Example

The first name of the driver.

driver_last_name string · max length: 512 Example

The last name of the driver.

license_detail_info object · LicenseDetailInfo Example

Additional license information for the driver.

+ Show Child Attributes

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

POST /api/driver/edit Shell Curl

```
curl https://api.truckerpath.com/navpro/api/driver/edit \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "driver_id": 8955563,
  "driver_first_name": "John",
  "driver_last_name": "Doe",
  "driver_phone_number": "111-222-3333",
  "driver_type": "OWNER_OPERATOR_OO",
  "contact_detail_info": {
    "driver_street_address": "2031 Burroughs Ave",
    "driver_city": "New York",
    "driver_country": "UNITED_STATES",
    "driver_state": "CA",
    "zip_code": "12314",
    "emergency_contact_name": "John Doe",
    "emergency_contact_number": "222-222-4444",
    "emergency_contact_email": "janedoe@example.com"
```

```
20    },
```

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

```
30        H
31      ]
32    }
33  }'
```

▶ Test Request

Delete Driver

Removes the driver from your company. The driver's Trucker Path account remains active and they will no longer have access to your company's data or trips.

Path Parameters

driver_id string required Examples

The driver ID to be deleted.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

DELETE /api/driver/delete/{driver_id} Shell Curl

```
1 curl https://api.truckerpath.com/navpro/api/driver/delete/854423 \
2   --request DELETE \
3   --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

1. Vehicles APIS

This API allows the NavPro Company to manage vehicles and their associations with drivers or loads.

Operations

```
   POST /api/vehicle/update/status
   POST /api/vehicle/query
   POST /api/vehicle/edit
   POST /api/vehicle/add
 DELETE /api/vehicle/delete
```

Update Status

Modify the status of the specified vehicle. Required information can be obtained through vehicle/query.

Body · UpdateStatusVehicleInfo required application/json

vehicle_id integer · int32 required Example

ID of the vehicle to update status.

vehicle_status string · enum required Example

Status to change the vehicle to.

values

ACTIVE

INACTIVE

Responses

- 200 OK
- 400 Bad Request
- 401 Not Authorized
- 403 Forbidden
- 404 Not Found
- 500 Server Error

POST /api/vehicle/update/status Shell Curl

```
curl https://api.truckerpath.com/navpro/api/vehicle/update/status \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "vehicle_id": 12345,
  "vehicle_status": "ACTIVE"
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

Query Vehicles

Retrieve all vehicles under the company based on specified conditions.

Body · QueryVehicleInfo

required application/json

owners array integer[] Example

Owners of the vehicle.

page integer · int32 · min: 0 Example

Current page

search_name string Example

Name of the vehicle.

size integer · int32 · min: 1 · max: 500 Example

Page size

status string · enum Example

Status of the vehicle.

values

- ACTIVE
- INACTIVE

vehicle_type string · enum Example

Type of the vehicle.

values

- TRUCK
- TRAILER

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden

> **404** Not Found

> **500** Server Error

POST /api/vehicle/query Shell Curl

```shell
curl https://api.truckerpath.com/navpro/api/vehicle/query \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "page": 0,
  "size": 20,
  "status": "ACTIVE",
  "vehicle_type": "TRUCK",
  "search_name": "My Truck101",
  "owners": [
    111123,
    231312
  ]
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```json
{
  "total": 1000,
  "page": 0,
  "data": [
    {
      "created_date": "Apr 14, 2023",
      "vehicle_id": 840215,
      "owner_id": 49845,
      "owner_name": "Operator A",
      "vehicle_status": "ACTIVE",
      "vehicle_no": "Truck No1",
      "vehicle_type": "TRUCK",
      "vehicle_vin": "1HGCM82633A123456",
      "gross_vehicle_weight": 3500,
      "trailer_type": "VAN",
      "vehicle_make": "CHRYSLER",
      "vehicle_model": "Pacifica",
      "assignments_drivers": {
        "driver_ids": [
          49852
        ],
```

```
        "assign_driver_info": [
          {
            "assign_driver_id": 49852,
            "assign_driver_name": "John Doe"
          }
        ]
      }
    }
  ],
  "code": 200,
  "success": true,
  "msg": "success",
  "page_size": 20
}
```


Edit Vehicle

Modify all information for a specified vehicle.

Body EditVehicleInfo required application/json

vehicle_id integer · int32 required Example

ID of the vehicle to be modified.

OK

vehicle_no string required Example

The vehicle number, e.g., Truck001, Truck002...

assign_drivers array integer[] Example

Bind drivers to the vehicle; multiple drivers can be assigned. This parameter can be obtained from /driver/query.

axles string · enum Example

Specify the number of axles for the vehicle.

values

- AXLES_1
- AXLES_2
- AXLES_3
- AXLES_4
- AXLES_5

+ Show all values

fuel_type string · enum Example

Select the fuel type for the vehicle. When the vehicle type is "trailers", this field is not applicable.

values

- GASOLINE
- DIESEL
- BIO_DIESEL
- ETHANOL

gross_vehicle_weight integer · int32 Example

The total weight of the vehicle under normal use.

status string · enum Example

Status of the vehicle.

values

ACTIVE

INACTIVE

---

trailer_type string · enum Example

When the vehicle type is 'TRAILER', this field can be filled. When the vehicle type is "TRUCK", this field is not applicable.

values

FLATBED

VAN

REEFER

CONTAINER

DRY_BULK

+ Show all values

---

vehicle_details object · VehicleDetails

+ Show Child Attributes

---

vehicle_make string Example

Vehicle manufacturer.

---

vehicle_model string Example

Model of the vehicle.

---

vehicle_vin string Example

The unique identification number of the vehicle.

+ Show additional properties

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

POST /api/vehicle/edit Shell Curl

```
curl https://api.truckerpath.com/navpro/api/vehicle/edit \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "vehicle_id": 12345,
  "vehicle_no": "Truck001",
  "vehicle_vin": "12345",
  "fuel_type": "GASOLINE",
  "trailer_type": "VAN",
  "axles": "AXLES_8",
  "gross_vehicle_weight": 130,
  "vehicle_year": "2022",
  "vehicle_make": "CHRYSLER",
  "vehicle_model": "Pacifica",
  "assign_drivers": [
    11111,
    22222
```

▶ Test Request

```
    "vehicle_height": 123
```

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

```
    "fuel_capacity": 300
  },
  "status": "ACTIVE"
}'
```

Add Vehicle

Add a new vehicle to your company.

Body · VehicleInfo required application/json

vehicle_no string required Example

The vehicle number, e.g., Truck001, Truck002...

---

vehicle_type string · enum required Example

Specify the type of the vehicle.

values

- TRUCK
- TRAILER

---

assign_drivers array integer[] Example

Bind drivers to the vehicle; multiple drivers can be assigned. This parameter can be obtained from /driver/query.

---

axles string · enum Example

Specify the number of axles for the vehicle.

values

- AXLES_1
- AXLES_2
- AXLES_3
- AXLES_4
- AXLES_5

+ Show all values

---

fuel_type string · enum Example

Select the fuel type for the vehicle. When the vehicle type is "trailers", this field is not applicable.

values

- GASOLINE
- DIESEL
- BIO_DIESEL
- ETHANOL

---

gross_vehicle_weight integer · int32 Example

The total weight of the vehicle under normal use.

---

trailer_type string · enum Example

When the vehicle type is 'TRAILER', this field can be filled. When the vehicle type is "TRUCK", this field is not applicable.

values

- FLATBED

VAN

REEFER

CONTAINER

DRY_BULK

+ Show all values

vehicle_details object · VehicleDetails

+ Show Child Attributes

vehicle_make string Example

Vehicle manufacturer.

vehicle_model string Example

Model of the vehicle.

vehicle_vin string Example

The unique identification number of the vehicle.

vehicle_year string · `\b\d{4}\b` Example

Year of vehicle manufacture. Please enter a date in the yyyy format, otherwise an error will occur.

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

POST /api/vehicle/add Shell Curl

```
curl https://api.truckerpath.com/navpro/api/vehicle/add \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "vehicle_type": "TRUCK",
```

```
  "vehicle_no": "Truck001",
  "vehicle_vin": "12345",
  "fuel_type": "GASOLINE",
  "trailer_type": "VAN",
  "axles": "AXLES_8",
  "gross_vehicle_weight": 230,
  "vehicle_year": "2020",
  "vehicle_make": "CHRYSLER",
  "vehicle_model": "Pacifica",
  "assign_drivers": [
    11111,
    22222
  ],
  "vehicle_details": {
```

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "id": 45196
}
```

OK

```
  }
}'
```

▶ Test Request

Delete Vehicle

Delete all specified vehicles. Required information can be obtained through vehicle/query.

Body · DeleteVehicleInfo required application/json

vehicle_ids array integer[] required Example

IDs of the vehicles to be deleted.

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

DELETE /api/vehicle/delete Shell Curl

```
curl https://api.truckerpath.com/navpro/api/vehicle/delete \
  --request DELETE \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "vehicle_ids": [
    12345,
    23456
  ]
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

2. Tracking APIS

Tracks the movement of a driver at a certain time.

Operations

POST /api/tracking/get/driver-dispatch

Query Driver Dispatch

Retrieve GPS trail and active trip ETA for a driver. Returns the trail as a list of location points and, if the driver is currently In_transit, the active trip info including estimated dropoff arrival time (ETA in UTC). If the driver is not In_transit, active_trip will be null.

Body · QueryDriverDispatch

required application/json

driver_id integer · int32 required Example

ID of the driver to query, obtainable through the /api/driver/query interface.

time_range object · TimeRange required

Time range for the GPS trail query. Must not exceed 30 days. Contains start_time and end_time in ISO 8601 UTC format (e.g. 2026-03-01T00:00:00Z).

+ Show Child Attributes

date_source string · enum Example

Source of driver tracking data. Optional, defaults to APP. Note: when using ELD, the driver must first log in to NavPro and complete ELD binding — GPS points will only begin syncing after the binding is established.

values

- APP
- ELD

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

```
POST /api/tracking/get/driver-dispatch
```

Shell Curl

```
curl https://api.truckerpath.com/navpro/api/tracking/get/driver-dispatch \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "driver_id": 8569147,
  "time_range": {
    "start_time": "2026-03-01T00:00:00Z",
    "end_time": "2026-03-31T23:59:59Z"
  },
  "date_source": "APP"
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "data": {
    "trail": [
      {
        "id": 4031402,
        "latitude": 30.4100166,
        "longitude": -75.24951,
        "time": "2023-07-20T10:12:35.557"
      },
      {
        "id": 4031403,
        "latitude": 30.4200166,
        "longitude": -75.25951,
        "time": "2023-07-20T10:22:35.557"
      }
    ],
    "active_trip": {
      "trip_id": "20260320-10",
      "eta": "2026-03-20T15:30:00"
    }
  }
}
```


3. Document APIS

Manage all documents within your company.

Operations

```
   POST  /api/document/query
   POST  /api/document/edit
   POST  /api/document/add
 DELETE  /api/document/delete
```

Query Document

Search for documents based on specified criteria within the company.

Body · QueryDocumentInfo required application/json

`blurry` string Example

Fuzzy search based on the document file name.

`document_types` array string[] · enum Example

Types of documents to search for.

values

- BILL_OF_LADING
- PROOF_OF_DELIVERY
- TRIP_SHEET
- CAT_SCALE
- FUEL_RECEIPT

+ Show all values

`page` integer · int32 · min: 0 Example

Current page

`size` integer · int32 · min: 1 · max: 500 Example

Page size

`upload_by_ids` array integer[] Example

IDs of the uploaders. This parameter can be obtained from /api/users/get/all.

`upload_end_time_stamp` integer · int64 Example

Query documents within a time range, enter the end time. Timestamps are used at the millisecond level.

`upload_start_time_stamp` integer · int64 Example

Query documents within a time range, enter the start time. Timestamps are used at the millisecond level.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

POST /api/document/query Shell Curl

```
curl https://api.truckerpath.com/navpro/api/document/query \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "page": 0,
  "size": 20,
  "upload_by_ids": [
    86554,
    231894
  ],
  "document_types": [
    "BILL_OF_LADING",
    "INVOICE"
  ],
  "blurry": "My Settlement.pdf",
  "upload_start_time_stamp": 1690170393208,
  "upload_end_time_stamp": 1690510393208
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "total": 1000,
  "page": 0,
  "data": [
    {
      "document_id": 185451,
```

```
      "document_name": "John's Settlement.pdf",
      "document_type": "BILL_OF_LADING",
      "document_url": "xxx",
      "upload_by": "Operator A",
      "upload_date": 1680598682984,
      "file_type": "pdf",
      "document_tag": [
        {
          "tag_name": "broker",
          "related_id": 84631,
          "related_name": "Customer A"
        }
      ],
      "is_private": false,
      "size": "248.17KB",
      "scope": "UPLOAD_FILE"
    }
  ],
  "code": 200,
  "success": true,
  "msg": "success",
  "page_size": 20
}
```


Edit Document

Modify document parameters.

Body · EditDocumentInfo

required application/json

document_id integer · int32 required Example

ID of the document. Obtainable through /api/document/query.

scope string · enum required Example

Document scope. Only files with scope UPLOAD_FILE can be edited.Obtainable through /api/document/query.

values

- UPLOAD_FILE
- INVOICE
- PAYMENTT

document_name string · max length: 512 Example

New name for the document.

is_private boolean Example

Update document privacy.

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

POST /api/document/edit Shell Curl

```
curl https://api.truckerpath.com/navpro/api/document/edit \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "document_id": 498456,
  "document_name": "Test Document.pdf",
  "is_private": false,
  "scope": "UPLOAD_FILE"
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

Add Document

Upload a new document to your company and associate it with relevant entities. Tags can also be added to the document.

Query Parameters

file string required

Body

application/json

documentInfo object · DocumentInfo required

+ Show Child Attributes

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

POST /api/document/add Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/document/add?file=' \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "documentInfo": {
    "document_type": "BILL_OF_LADING",
    "is_private": false,
    "link_to_customer": [
      2312315,
      1424341
    ],
    "link_to_load": [
      27987,
      234119
    ],
    "link_to_driver": [
      2347987,
      896876
    ],
    "link_to_vehicle": [
```

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "document_result": {
    "document_id": 52471,
    "scope": "UPLOAD_FILE"
  }
}
```

▶ Test Request

OK

Delete Document

Delete a document from your company.

Body · DeleteDocumentInfo

required application/json

document_id integer · int32 required Example

ID of the document to delete.

scope string · enum required Example

Document scope. Only files with scope UPLOAD_FILE can be deleted.Obtainable through /api/document/query.

values

UPLOAD_FILE

INVOICE

PAYMENTT

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

DELETE /api/document/delete Shell Curl

```shell
curl https://api.truckerpath.com/navpro/api/document/delete \
  --request DELETE \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "document_id": 498456,
  "scope": "UPLOAD_FILE"
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```json
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

4. Terminal APIS

Create and manage different terminals to organize and group drivers.

Operations

```
   POST /api/terminal/edit
   POST /api/terminal/create
   POST /api/terminal/add/member
    GET /api/terminal/get/member/{terminal_id}
    GET /api/terminal/get/list
 DELETE /api/terminal/delete/{terminal_id}
 DELETE /api/terminal/delete/member/{terminal_id}/{member_id}
```

Edit Terminal

Modify the name of a terminal.

Body · EditTerminal

required application/json

terminal_id integer · int32 required Example

ID of the terminal to modify.

terminal_name string required Example

New name for the terminal.

Responses

- 200 OK
- 400 Bad Request
- 401 Not Authorized
- 403 Forbidden
- 404 Not Found
- 500 Server Error

POST /api/terminal/edit Shell Curl

```
curl https://api.truckerpath.com/navpro/api/terminal/edit \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "terminal_name": "Driver Terminal 1",
  "terminal_id": 45614
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
```

```
  "success": true,
  "msg": "success"
}
```

OK

Create Terminal

Create a new terminal.

Body · CreateTerminal required application/json

terminal_name string required Example

Specify the terminal name. Terminal names must be unique within the company.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

POST /api/terminal/create Shell Curl

```
curl https://api.truckerpath.com/navpro/api/terminal/create \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "terminal_name": "Driver Terminal 1"
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "id": 45196
}
```

OK

Add Terminal Member

Add a driver to the specified terminal.

Body · AddMember

required application/json

members array integer[] required Example

IDs of drivers to be added. Obtainable through /api/driver/query.

terminal_id integer · int32 required Example

ID of the terminal.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

POST /api/terminal/add/member Shell Curl

```
curl https://api.truckerpath.com/navpro/api/terminal/add/member \
  --request POST \
```

```
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "terminal_id": 256847,
  "members": [
    68457,
    68243
  ]
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

Get Terminal Member

Retrieve the list of members in a terminal.

Path Parameters

terminal_id string required Examples

ID of the terminal to query.

Query Parameters

page string Examples

Current page

size string Examples

Page size

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

GET /api/terminal/get/member/{terminal_id} Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/terminal/get/member/45647?page=0&s
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```
{
  "total": 1000,
  "page": 0,
  "data": [
    {
      "member_id": 56284,
      "member_email": "johndoe@example.com",
      "member_first_name": "John",
      "member_last_name": "Doe",
      "member_phone_number": "365-9687-4411",
      "member_status": "Active",
      "member_role": "Driver"
    }
  ],
  "code": 200,
  "success": true,
  "msg": "success",
  "page_size": 20
}
```


Get Terminal

Retrieve information about all terminals.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

GET /api/terminal/get/list Shell Curl

```
curl https://api.truckerpath.com/navpro/api/terminal/get/list \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "terminals": [
    {
      "terminal_name": "Driver Terminal 1",
      "terminal_id": 45649,
      "created_by": "Operator 1",
      "member_number": 45649
    }
  ]
}
```

OK

Delete Terminal

Delete a terminal along with all its members. Note that deleting member records in a terminal does not affect their accounts.

Path Parameters

terminal_id string required

ID of the terminal to delete. Obtainable through /api/terminal/query/list.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

DELETE /api/terminal/delete/{terminal_id} Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/terminal/delete/{terminal_id}' \
  --request DELETE \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

Delete Terminal Member

Remove a member from a terminal.

Path Parameters

terminal_id string required

ID of the terminal the driver belongs to. Obtainable through /api/terminal/query/list.

member_id string required

ID of the member to be removed. Obtainable through /api/terminal/query/member.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

DELETE /api/terminal/delete/member/{terminal_id}/{member_id} Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/terminal/delete/member/{terminal_i
  --request DELETE \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

5. Users APIS

Used for managing and retrieving all users under the company and their associated information.

Operations

GET /api/users/get/all

Get Users

This API is used to retrieve all users under the company. Currently, this API only supports fetching basic information.

Query Parameters

page string Examples

Current page

size string Examples

Page size

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

GET /api/users/get/all Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/users/get/all?page=0&size=20' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "user_infos": [
    {
      "user_id": 5412243,
      "user_full_name": "John Doe",
      "user_email": "johndoe@example.com",
      "user_rank": "DRIVER"
    }
  ]
}
```


OK

6. Poi APIS

Manage your company's custom POIs and associated last-mile data through this API.

Operations

```
   POST  /api/poi/query
   POST  /api/poi/edit
   POST  /api/poi/edit/group
   POST  /api/poi/add
   POST  /api/poi/add/group
    GET  /api/poi/get/group
    GET  /api/poi/export
 DELETE  /api/poi/delete/{poi_id}
 DELETE  /api/poi/delete/group/{group_id}
```

Query POI

Pagination query for all POIs within a specific POI group.

Body · QueryPoiInfoVo

required application/json

group_id integer · int32 required Example

The group ID for POIs can be obtained through /api/poi/get/group.

external_ids array string[] Example

External IDs related to the POIs.

page integer · int32 · min: 0 Example

Current page

size integer · int32 · min: 1 · max: 500 Example

Page size

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found

> **500** Server Error

POST /api/poi/query Shell Curl

```shell
curl https://api.truckerpath.com/navpro/api/poi/query \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "page": 0,
  "size": 20,
  "group_id": 754114,
  "external_ids": [
    "Poi00001",
    "Poi00002"
  ]
}'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```json
{
  "code": 200,
  "success": true,
  "msg": "success",
  "total": 1300,
  "poi_infos": [
    {
      "poi_id": 415714,
      "latitude": 33.76837,
      "longitude": -118.20175,
      "poi_detail": {
        "street": "Long Beach, California",
        "city": "Long Beach",
        "state": "CA",
        "zip_code": "90802",
        "country": "US",
        "contact_number": "111-222-3333",
        "site_instruction": "This is a description example."
      },
      "site_detail": {
        "entrance": [
          {
            "site_id": 52411,
            "latitude": 33.768637172618696,
            "longitude": -118.20210121482552,
```

Edit POI

Modify basic information and last mile infos about the poi. Location information such as latitude and longitude cannot be modified.

Body · PoiEditRequestVO

required application/json

name string required Example

POI Name

poi_id integer · int32 required Example

The unique id of the poi that want to modify. The POI ID can be obtained through /api/poi/get.

contact_number string \d{3}-\d{3}-\d{4} Example

The contact phone number for the POI. It followed the format xxx-xxx-xxxx.

external_id string Example

The external id of the POI.

site_detail object · PoiEditSiteManagerVO

Last Mile Information

+ Show Child Attributes

site_instruction string · max length: 100 Example

Site Instruction

Responses

OK

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

```
POST /api/poi/edit                                  Shell Curl
```


```
"path": [
  {
    "latitude": 33.767284073170934,
    "longitude": -118.20188556076194
  },
  {
    "latitude": 33.76726830662819,
    "longitude": -118.20294605499872
  }
],
"path_type": "TRUCK"
}
},
"exit": [
{
"site_i
"latitude": 33.769637,
"longitude": -118.2031,
"path": [
{
"latitude": 33.768284,
"longitude": -118.20288
}
],
"path_type": "TRUCK"
}
]
}
"external_id": "98524818"
}
]
}
```

```
curl https://api.truckerpath.com/navpro/api/poi/edit \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "name": "MCDONALD'\''S",
  "poi_id": 415714,
  "external_id": "98524818",
  "contact_number": "111-222-3333",
  "site_instruction": "This is a description example.",
  "site_detail": {
    "entrance": [
      {
        "site_id": 1452353,
        "latitude": 33.768637172618696,
        "longitude": -118.20210121482552,
        "path": [
          {
            "latitude": 33.767284073170934,
```

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

```
        ],
        "path_type": "ROAD_PATH"
      }
    ],
    "exit": [
      {
        "site_id": 1452353,
        "latitude": 33.768637172618696,
        "longitude": -118.20210121482552,
        "path": [
          {
            "latitude": 33.767284073170934,
            "longitude": -118.20188556076194
          },
          {
            "latitude": 33.76726830662819,
            "longitude": -118.20294605499872
          },
          {
            "latitude": 33.7672529085608,
```

Edit POI Group

Modify basic information about the group.

Body · PoiGroupEditRequestVO required application/json

group_id integer · int32 required Example

The unique id of the poi group that want to modify. The group ID for POIs can be obtained through /api/poi/get/group.

group_name string · min length: 1 · max length: 50 required Example

The name of the POI group.

group_description string · max length: 100 Example

The description of the POI group.

```
            "longitude": -118.20352649304614
            }
        ],
        "path_type": "ROAD_PATH"
    }
  ]
}
}'
```

Test Request

Responses

- 200 OK
- 400 Bad Request
- 401 Not Authorized
- 403 Forbidden
- 404 Not Found
- 500 Server Error

POST /api/poi/edit/group

Shell Curl

```
curl https://api.truckerpath.com/navpro/api/poi/edit/group \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "group_name": "Favorite food group",
  "group_description": "This is a note example",
  "group_id": 13512
}'
```

Test Request

200 400 401 403 404 500

Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

Add POI

Add custom POIs to a specified POI group for the company.

Body · PoiAddRequestVO

required application/json

latitude number · double required Example

The latitude of the POI. lat/lon will be the used to determine geolocation of poi.

longitude number · double required Example

The longitude of the POI. lat/lon will be the used to determine geolocation of poi.

name string required Example

POI Name

poi_detail object · PoiDetail required

Details of the POI, including address, state, and more. POI details including street address, city, state, additional information.

+ Show Child Attributes

poi_group_id integer · int32 required Example

The ID of the POI group to add this POI.

external_id string Example

The external id of the POI.

site_detail object · PoiSiteManagerVO

Last Mile Information

+ Show Child Attributes

Responses

> **200** OK

> **400** Bad Request

> **401** Not Authorized

> **403** Forbidden

> **404** Not Found

> **500** Server Error

POST /api/poi/add Shell Curl

```
curl https://api.truckerpath.com/navpro/api/poi/add \
  --request POST \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "latitude": 33.76837,
  "longitude": -118.20175,
  "poi_detail": {
    "street": "Long Beach, California",
    "city": "Long Beach",
    "state": "CA",
    "country": "US",
    "zip_code": "90802",
    "contact_number": "111-222-3333",
    "site_instruction": "This is a description example."
  },
  "name": "MCDONALD'\''S",
  "external_id": "98524818",
  "poi_group_id": 13512,
  "site_detail": {
```

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "id": 45196
}
```

OK

```
              "latitude": 33.7672830882819,
              "longitude": -118.20294605499872
            },
            {
              "latitude": 33.7672529085608,
              "longitude": -118.20352649304614
            }
          ],
          "path_type": "ROAD_PATH"
        }
      ],
      "exit": [
        {
          "latitude": 33.768637172618696,
          "longitude": -118.20210121482552,
          "path": [
            {
```

Add POI Group

Add POI groups for the company.

Body · PoiGroupInfoVO required application/json

group_name string · min length: 1 · max length: 50 required Example

The name of the POI group.

group_description string · max length: 100 Example

The description of the POI group.

Responses

200 OK

400 Bad Request

401 Not Authorized

403 Forbidden

404 Not Found

500 Server Error

```
48                "latitude": 33.767284073170934,
49                "longitude": -118.20188556076194
50            },
51            {
52                "latitude": 33.76726830662819,
53                "longitude": -118.20294605499872
54            },
55            {
56                "latitude": 33.7672529085608,
57                "longitude": -118.20352649304614
58            }
59        ],
60        "path_type": "ROAD_PATH"
61    }
62    ]
63 }
64 }'
```

▶ Test Request

POST /api/poi/add/group Shell Curl

```
1 curl https://api.truckerpath.com/navpro/api/poi/add/group \
2   --request POST \
3   --header 'Content-Type: application/json' \
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
5   --data '{
6   "group_name": "Favorite food group",
7   "group_description": "This is a note example"
8 }'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "id": 45196
}
```

OK

Get POI Group

Search custom POI group.

Query Parameters

page string Examples

Current page

size string Examples

Page size

fuzzy string Examples

Fuzzy search for group names.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

GET /api/poi/get/group Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/poi/get/group?page=0&size=20&fuzzy
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```
{
  "total": 120,
  "code": 200,
  "success": true,
  "msg": "success",
  "poi_group_infos": [
    {
      "group_id": 8560545,
      "poi_count": 1000,
```

```
      "group_name": "Favorite food group",
      "group_description": "This is a note example"
    }
  ]
}
```

OK

Export POI Infos

Exported POI file will be sent by email. You need to specify the recipient email in request and the export process will take around 3-5 mins.

Query Parameters

email string required Examples

The email is for receiving exported data.

group_ids string Examples

Specify the group IDs of the POI group you want to export. If not specified, all POIs will be exported by default. The group IDs for POIs can be obtained through the /api/poi/get/group endpoint.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

GET /api/poi/export Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/poi/export?email=johndoe%40example
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

Delete POI

Specify the ID of the POI to delete it.

Path Parameters

poi_id string required Examples

The unique id of the poi that want to delete. The POI ID can be obtained through /api/poi/get.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

DELETE /api/poi/delete/{poi_id} Shell Curl

```
curl https://api.truckerpath.com/navpro/api/poi/delete/369411 \
  --request DELETE \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

Delete POI Group

Specify the ID of the POI Group to delete it. Deleting a group deletes all POIs that belong to this group.

Path Parameters

group_id string required Examples

The unique id of the poi group that want to delete. The group ID for POIs can be obtained through /api/poi/get/group.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

DELETE /api/poi/delete/group/{group_id} Shell Curl

```
curl https://api.truckerpath.com/navpro/api/poi/delete/group/12464 \
  --request DELETE \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success"
}
```

OK

7. Trip APIS

Manage customized trip routes for fleet drivers.

Operations

POST /api/trip/create

Create Trip

Generate customized trip routes and send to designated driver.

Headers

Idempotency-Key string Example

Optional. A unique key (e.g. UUID) to ensure idempotency. Max 255 characters. If the same key is sent within 24 hours, the original response will be returned without creating a duplicate trip.

Body · TripInfo

required application/json

driver_id integer · int64 required Example

The unique ID of the driver to assign the trip to. The driver ID can be obtained through /api/driver/query.

scheduled_start_time string · `^\d{4}-\d{2}-\d{2}T\d{2}:\d{2}:\d{2}Z$` required Example

Trip scheduled start time. Must be in ISO 8601 UTC format, e.g. 2026-03-01T16:50:00Z.

stop_points array object[] · TripBasicInfo[] · 2...2147483647 required Example

A collection of trip route points information, can add multiple.

Trip stop point details.

+ Show Child Attributes

routing_profile_id integer · int32 Example

The ID of the routing profile (truck configuration) to use for route calculation. Obtainable through /api/trip/routing-profile/list. If not specified, the default truck configuration will be used.

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

POST /api/trip/create Shell Curl

```
curl https://api.truckerpath.com/navpro/api/trip/create \
  --request POST \
  --header 'Idempotency-Key: 550e8400-e29b-41d4-a716-446655440000' \
  --header 'Content-Type: application/json' \
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
  --data '{
  "scheduled_start_time": "2026-03-01T16:50:00Z",
  "stop_points": [
    {
      "latitude": 43.51351,
      "longitude": -96.74067,
      "address_name": "Sioux Falls, SD",
      "appointment_time": "2026-03-01T18:35:00Z",
```

```
14        "dwell_time": 30,
15        "notes": "Gate code: 1234"
16      },
17      {
18        "latitude": 42.85929,
19        "longitude": -91.23645,
20        "address_name": "Dubuque, IA",
```

200 400 401 403 404 500 Show Schema

```
{
  "code": 200,
  "success": true,
  "msg": "success",
  "trip_id": "20260306-1"
}
```

▶ Test Request

OK

8. Routing Profile APIS

Manage and retrieve truck routing profiles. A routing profile defines truck dimensions and weight constraints used for route calculation.

Operations

GET /api/routing-profile/list

Get Routing Profiles

Retrieve a paginated list of routing profiles (truck configurations) available to the current user. The routing profile ID can be used in the Create Trip API to apply specific truck parameters for route calculation.

Query Parameters

page string Examples

Current page

size string Examples

Page size

Responses

- **200** OK
- **400** Bad Request
- **401** Not Authorized
- **403** Forbidden
- **404** Not Found
- **500** Server Error

GET /api/routing-profile/list Shell Curl

```
curl 'https://api.truckerpath.com/navpro/api/routing-profile/list?page=0&size=2
  --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 404 500 Show Schema


```
{
  "total": 1000,
  "page": 0,
  "data": [
    {
      "id": 6831,
      "name": "My Truck Profile",
      "truck_ft_length": 53,
      "truck_in_length": 0,
      "truck_ft_width": 8,
      "truck_in_width": 6,
      "truck_ft_height": 13,
      "truck_in_height": 6,
      "weight_limit": 80000,
      "weight_per_axle": 2000,
      "axles": 5,
      "trailers": 1,
      "avoid_areas": [
```

```
        {
          "area_name": "Downtown",
          "type": "rectangle",
          "coordinates": [
            [
              {
                "lat": 33.25,
                "lng": -111.84
              },
              {
                "lat": 33.26,
                "lng": -111.84
              },
              {
                "lat": 33.26,
                "lng": -111.83
              },
              {
                "lat": 33.25,
                "lng": -111.83
              }
            ]
          ]
        }
      ],
      "avoid_bridges": [
        {
          "state": "FL",
          "rules": [
            "TTT1",
            "CRN2"
          ]
        }
      ]
    }
  ],
  "code": 200,
  "success": true,
  "msg": "success",
  "page_size": 20
}
```


OK