# An Extension of Buddy Systems to Arbitrary Radix for Deterministic Memory Allocation

**Andrew Jonathan Fine**

May 31, 2026

**Abstract**

Traditional heap management architectures do not terminate predictably due to dependency upon linked lists for finding and reclaiming storage. This paper introduces Iscandar, a deterministic memory management algorithm based on a Radix-32 Partitioned Allocator. By mapping the memory heap linear number line to a multidimensional geometry of arbitrary radix, Iscandar replaces iterative search with a bounded set of unrolled instructions to resolve the geometry for finding available memory. For three-dimensional geometries we formalize the fractal lattice resolution across sizes of sector requests using heuristics that scan row and plane occupancy counts (Huge and Large). For heuristics involving obtaining smaller amounts of memory, we use oracles to locate available memory sectors without invoking a search. Performance is compared against commonly known memory algorithms such as buddy systems.

# Contents


**1**

**1 Welcome to Iscandar. 1**
1.1 Batteries Are Included! . . . 1
1.1.1 The Welcome Example. . . . 1

**2 Architectural Axioms 1**
2.1 Axiom I: The State Map (L) and Structural Arity ($\mathcal{A}$) . . . 1
2.1.1 The Cube Namespace . . . 1
2.2 Axiom II: Hierarchical Occupancy Counters ($\Gamma$) . . . 1
2.3 Axiom III: The Contiguity Guarantee and Spatial Entropy . . . 2
2.4 Axiom IV: The Coordinate-Address Identity . . . 2

**3 Formal Proof of Deterministic Path Termination 2**
3.1 The Steering-Based Complexity Model . . . 2
3.2 Guaranteed Path Termination . . . 2
3.3 Conclusion of Determinism . . . 3

**4 Deterministic Coalescence 3**
4.1 Symmetric Coalescence Mechanics . . . 3
4.2 Proof of Coalescence Invariant . . . 3

**5 Observations 3**
5.1 As an Extension to Binary Buddy Systems . . . 4
5.2 As a Symmetric Voronoi Partition . . . 4
5.3 As Linear Programming . . . 4
5.4 Scalability via Depth Extension . . . 4
5.5 As Supporting Parallel Execution . . . 5

**6 Conclusion 5**

**7 Glossary of Terms 5**

**8 Updating Memory State Spaces by Mating the Oracle Tables 6**
8.1 Polytope Formation at Cube Level . . . 6
8.1.1 The Cube Scale Allocator ($L = \mathcal{A}^k$) . . . 6
8.2 Polytope Formation At Row and Plane Levels . . . 6
8.2.1 The Huge Resolution ($\mathcal{A}^2 < L < \mathcal{A}^3$) . . . 6
8.2.2 The Large Resolution ($2\mathcal{A} < L \leq \mathcal{A}^2$) . . . 7
8.3 Polytope Formation Between Rows . . . 9
8.3.1 The Small Resolution ($A < L \leq 2\mathcal{A}$) . . . 9
8.4 Polytope Formation Within Row . . . 9
8.4.1 The Tiny Resolution ($\mathcal{A}/4 < L \leq \mathcal{A}$) . . . 9
8.4.2 The Nano Resolution ($L \leq \mathcal{A}/4$) . . . 10

**9 Bounded Complexity by Bounding Execution Paths 11**
9.1 Mechanics of Guaranteed Termination . . . 11
9.2 Bounded-Error Quantum Path Complexity Ceiling . . . 12

**10 Desk Check Summary: Nano and Tiny Resolutions ($L \leq \mathcal{A}$) 12**

**11 Volumetric Analysis** **13**
11.1 Methodology . . . 13
11.2 Test Data (generated from Section 10) . . . 13
11.3 Graphical Verification . . . 13
11.4 Buddy System Comparison Simulation . . . 13

**A Bootstrap Mechanism (see Section 1, Batteries Included!)** **17**

**B Project Checklist.** **17**

**C The Bottle Opener: Use after Bootstrap.** **17**
C.1 Project Directories . . . 17
Listing 1: Project.ps1 . . . 17

**D Oracle Manufacture** **18**
Listing 2: OracleCenter.apl . . . 18
Listing 3: OracleLeft.apl . . . 18
Listing 4: OracleRight.apl . . . 18
D.1 Center Oracle . . . 19
Listing 5: OracleCenter.ps1 . . . 19
D.2 Left Oracle . . . 20
Listing 6: OracleLeft.ps1 . . . 20
D.3 Right Oracle . . . 20
Listing 7: OracleRight.ps1 . . . 20

**E APL Laboratory Listings.** **21**
Listing 8: Welcome.apl . . . 21
Listing 9: Support.apl . . . 21
Listing 10: Cube.apl . . . 21
Listing 11: Definitions.apl . . . 21
Listing 12: Iscandar.apl . . . 22
Listing 13: WrappedPointer.apl . . . 22
Listing 14: Cube.apl . . . 23
Listing 15: Decision.apl . . . 23
Listing 16: HeuristicCube.apl . . . 23
Listing 17: HeuristicNano.apl . . . 24
Listing 18: HeuristicTiny.apl . . . 24
Listing 19: HeuristicSmall.apl . . . 25
Listing 20: HeuristicLarge.apl . . . 25
Listing 21: HeuristicHuge.apl . . . 26
Listing 22: MarkPlanes.apl . . . 26
Listing 23: UnMarkPlanes.apl . . . 27
Listing 24: MarkSingleRow.apl . . . 27
Listing 25: UnMarkSingleRow.apl . . . 28
Listing 26: MarkRows.apl . . . 28
Listing 27: UnMarkRows.apl . . . 29
Listing 28: MarkFirstRow.apl . . . 30
Listing 29: UnMarkFirstRow.apl . . . 30
Listing 30: MarkFinalRow.apl . . . 31
Listing 31: UnMarkFinalRow.apl . . . 31
Listing 32: Mark.apl . . . 32
Listing 33: UnMark.apl . . . 32
Listing 34: HeuristicNull.apl . . . 32
Listing 35: PlanesDriver.apl . . . 33

Listing 36: RowsDriver.apl . . . . . 35
Listing 37: PairRowsDriver.apl . . . . . 36
Listing 38: LargeDriver.apl . . . . . 38
Listing 39: LargeRowDriver.apl . . . . . 40
Listing 40: HugePlanesCoreDriver.apl . . . . . 42
Listing 41: HugeRowsCoreDriver.apl . . . . . 44
Listing 42: HugePlanesRemainDriver.apl . . . . . 44
Listing 43: HugeRowsRemainDriver.apl . . . . . 45

# 1 Welcome to Iscandar.

Unlike allocation models using variable-time search algorithms [1], this architecture employs a hierarchical occupancy map to resolve coordinates deterministically. Extending the traditional binary buddy system to an arbitrary radix replaces it with a geometric steering mechanism.

## 1.1 Batteries Are Included!

The .tex source for this manuscript functions as a self-organizing research example. It can be processed by a PowerShell script to extracts Dyalog APL source listings directly from surrounding portions of this paper which document them best, to create a local research environment. This ensures the researcher does not need to manually configure local paths or binary repositories. See Appendix A and C for putting together the environment and Section 10 for its use. **Welcome.apl** below is the basic demonstration.

### 1.1.1 The Welcome Example.

See Listing 10 for `Welcome.apl`

# 2 Architectural Axioms

These axioms establish the geometric and mathematical constraints of the lattice. They transform each memory request into a coordinate resolution task, avoiding search-and-sort operations to maintain a fixed sequence of instructions.

## 2.1 Axiom I: The State Map (L) and Structural Arity ($\mathcal{A}$)

For modeling and testing purposes this paper demonstrates an $k$-level lattice $L$ of fixed depth ($n = 3$) defining a total memory space. The architecture maintains a constant Arity ($\mathcal{A}$) of 32. A hierarchical progression of tiers organizes the lattice: the atomic Sector ($S_0$), the Row of Sectors ($S_1$), the Plane of Rows ($S_2$), and the Cube of Planes ($S_3$). Lattice coordinates $(p, r, s)$ determine the address of any specific leaf node, where $p, r, s \in \{0, \ldots, \mathcal{A} - 1\}$. The geometry maintains invariance regardless of the physical byte-width the sector occupies.[2]

### 2.1.1 The Cube Namespace

This listing defines the memory allocator data structure, Iscandar's answer to the buddy system heap, in accordance with Axiom I.

## 2.2 Axiom II: Hierarchical Occupancy Counters ($\Gamma$)

Discrete occupancy counts ($\Gamma$) at every tier enable constant-time steering. Following bit-block representation principles, these counters generate a real-time density map of the lattice:

$$\text{Level 1 (Row):} \quad \Gamma_1 = \sum_{i=0}^{\mathcal{A}-1} \Gamma_{0,i} \tag{1}$$

$$\text{Level 2 (Plane):} \quad \Gamma_2 = \sum_{j=0}^{\mathcal{A}-1} \Gamma_{1,j} \tag{2}$$

$$\text{Level 3 (Cube):} \quad \Gamma_3 = \sum_{k=0}^{\mathcal{A}-1} \Gamma_{2,k} \tag{3}$$

This hierarchical summation lets a Global Registrar at the Cube level execute an admissibility check in a single instruction cycle, imposing a fast-fail condition.

[2] The Large allocator functions as a cross-tier searcher for sequence resolution, managing the fractal logic across the Plane manifold to satisfy multi-Row requests.

### 2.3 Axiom III: The Contiguity Guarantee and Spatial Entropy

Any resolved coordinate sequence represents a continuous physical block in the **Iscandar** lattice. However, functional contiguity does not imply spatial perfection; a perfect Oracle would preclude fragmentation entirely. Our Oracles (Center, Left, and Right) prioritize determinism over maximum packing density.

### 2.4 Axiom IV: The Coordinate-Address Identity

The architecture used here rejects the traditional separation of logical address space and physical memory geometry, by establishing a **Bijective Identity** between a machine-word pointer $P$ (wrapped pointer, see Glossary) and its corresponding lattice coordinate $\vec{C}$.

In a system of depth $k$ and arity $A$, any specific sector is represented by a coordinate vector:

$$\vec{C} = (i_1, i_2, \ldots, i_k) \quad \text{where} \quad 0 \leq i_n < A \tag{4}$$

The address $P$ is not an arbitrary token, but the scalar projection of this vector into the linear address space. The isomorphism is defined by the construction:

$$P = \sum_{n=1}^{k} i_n \cdot A^{k-n} \tag{5}$$

With our cube as an example, the address of a sector located at $(p, r, s)$ is clearly enumerable from the geometry:

$$P = (p \cdot 32^2) + (r \cdot 32^1) + (s \cdot 32^0) \tag{6}$$

## 3 Formal Proof of Deterministic Path Termination

**Theorem:** A fixed-depth lattice $L$ of Arity $\mathcal{A} = 32$ establishes deterministic resolution by mapping every memory request to a finite, bounded execution path.

### 3.1 The Steering-Based Complexity Model

The resolution time $T$ in the Iscandar architecture is a discrete function of the sub-lattice depth and the specific heuristic path $P$ identified by the memory request size in sectors. Unlike legacy systems where $T = \mathcal{O}(\log N)$ or $\mathcal{O}(N)$ based on heap fragmentation, the path selection in Iscandar uses a decision table to ensure every heuristic terminates in bounded time.

Let $\mathcal{H}$ be the finite set of available resolution paths. The selected path $P$ is a deterministic function of the request length $L$ and the occupancy state $\Gamma$:

$$P(L, \Gamma) \in \mathcal{H} = \{P_{\text{Nano}}, P_{\text{Tiny}}, P_{\text{Small}}, P_{\text{Large}}, P_{\text{Huge}}, P_{\text{Cube}}\} \tag{7}$$

Because each path $P \in \mathcal{H}$ consists of a bounded number of unrolled instructions, the execution time $T$ (measured in operational steps) is strictly capped by the sequence length of the chosen heuristic, denoted as $|P|$:

$$T(P) \leq |P| \leq \max_{h \in \mathcal{H}} |h| \tag{8}$$

### 3.2 Guaranteed Path Termination

Every resolution path is constructed from a fixed sequence of instruction groups that mathematically eliminate runtime searching.

1. **Heuristic Selection:** The Global Registrar and intermediate sentinels use strict bitmask comparisons to select the viable path $P \in \mathcal{H}$.

2. **Atomic Resolution:** For leaf-level requests, the system executes either a single-pass extraction (Nano) or a bipartite dual-phase oracle extraction (Tiny or Small).

3. **Path Invariance:** Once a path is engaged, the algorithm navigates via fixed spatial offsets and terminates immediately when the physical bit-coordinate is returned.

### 3.3 Conclusion of Determinism

Determinism in Iscandar is defined as the absolute guarantee of termination within a bounded execution window for any given heuristic path. By relying on unrolled geometric coordinate resolution, the architecture deliberately trades away maximum spatial packing density in exchange for zero-variance path termination.

## 4 Deterministic Coalescence

Maintaining temporal determinism in a dynamic environment requires a deallocation process (coalescence) mirroring the efficiency of the allocation logic.

### 4.1 Symmetric Coalescence Mechanics

To maintain determinism, our deallocation process mirrors the efficiency of the allocation logic via a direct state update performed upon the occupancy counters. Because the wrapped pointer explicitly contains its fixed lattice coordinate (see Axiom IV), it acts as an absolute hardware address. Updating the occupancy counters ($\Gamma$) is thus the dual to the initial resolution:

1. The deallocation interface (`UnMark.api`) is invoked directly via the wrapped pointer, toggling the atomic leaf node state $\Gamma_0$ to 0 (Available).

2. The change propagates immediately to the parent Row counter ($\Gamma_1$).

3. The Level-2 (Plane) and Level-3 (Cube) counters are updated through discrete integer subtraction.

Because the lattice depth is fixed at $n = 3$, the time complexity for this `UnMark` deallocation is defined by the exact same path-specific, constant-time constraints as the `Mark.api` allocation.

### 4.2 Proof of Coalescence Invariant

Let $\Gamma_{\text{total}}$ be the sum of all leaf nodes $S_{0,i}$. At any discrete time $t$, the hierarchical counters must satisfy the invariant, where $\Gamma_{\text{Apex}}$ serves as the total cube capacity $\Gamma_3$:

$$\Gamma_{\text{Apex}} = \sum \Gamma_2 = \sum \Gamma_1 = \sum \Gamma_0 \tag{9}$$

Since deallocation is defined as:

$$\Gamma_x(t+1) = \Gamma_x(t) - 1 \quad \text{for all levels } x \in \{0, 1, 2, 3\} \tag{10}$$

along the specific resolution path, the invariant is preserved. Because this path is fixed at depth $n$, the lattice is restored to a consistent state.

## 5 Observations

Earlier sections established **Iscandar** as deterministic within the primary scope of this paper. However, it exhibits properties warranting distinct architectural observations.

### 5.1 As an Extension to Binary Buddy Systems

The binary buddy system, pioneered by Knowlton [12] and Knuth [13], sought to minimize search latency through a power-of-two partitioning scheme ($R = 2$). While this approach facilitates efficient coalescence, its search complexity remains fundamentally constrained to $O(\log_2 n)$. As modern memory address spaces scale alongside processor word sizes, the increasing logarithmic depth of these trees drives significant latency. Furthermore, at high utilization, binary buddy systems trigger "stalling" behaviors; the search algorithm must traverse increasingly fragmented leaf nodes, which inevitably erodes deterministic performance.

We generalize buddy system principles to an **Arbitrary Radix** ($R = \mathcal{A}$). By shifting from a binary tree to a high-radix fractal lattice, we collapse the depth of the search space to a fixed architectural constant $n$. This structural shift moves memory management from the domain of probabilistic searching to the domain of **Geometric Coordinate Resolution**.

### 5.2 As a Symmetric Voronoi Partition

As detailed in the Architectural Axioms (Section 2.1), this lattice functions as a **Symmetric Voronoi Partition**, where the adjacency of "buddies" is a pre-baked geometric property of the address space rather than a calculated proximity, as shown in Section 5.2.

In this model, adjacency is defined by a partition's total volume associating with its handle (a wrapped pointer resolved in Section 9.4) rather than the Euclidean distance of individual points from a centroid. rather than the Euclidean distance of individual points from a centroid, as established in the geometric rules of the address space.

In a standard Voronoi partition, boundaries are dynamically computed as a function of the Euclidean distance to a specific "seed" or generator point. In the Iscandar lattice, while the "seed" is represented by the wrapped pointer, the partition boundaries are not computed at runtime, as defined by the invariant geometric properties of the lattice established in the Observations section. Instead, they are architecturally invariant, defined strictly by the Structural Arity ($\mathcal{A}$) and the hierarchical depth ($k$) established in the Axioms. This replaces the need for distance-based calculations with a pre-baked, static coordinate resolution:

$$\forall L \in \mathcal{L}, \quad \Omega(L) \iff \mathcal{G}(\mathcal{A}, k) \land (\nexists f(\text{dist}(p, \text{seed})) \to \Omega(L)) \tag{11}$$

*For all requests $L$ belonging to the lattice, the admission function $\Omega(L)$ is true if and only if it is a property of the geometry defined by Radix $\mathcal{A}$ and tier-depth $k$; furthermore, there exists no function of the spatial distance between a position $p$ and a previous seed that influences the outcome of $\Omega(L)$.*

### 5.3 As Linear Programming

The operational stability of the system is maintained via a mechanism analogous to projective transformations used in Karmarkar's algorithm [14]. By relying on the hierarchical occupancy counters ($\Gamma$) to pre-qualify capacity, the resolution path inherently avoids the "edges" of the feasible region (the traditional fragmentation trap). Here, the allocator does not merely manage space; it navigates a high-dimensional manifold where the rigid coordinate geometry serves as a protective barrier against non-deterministic search behaviors.

### 5.4 Scalability via Depth Extension

The **Iscandar** architecture scales by increasing the lattice depth up to two additional levels. Because the resolution time is a linear function of depth ($k \times I_{base}$), extending the lattice to $k = 4$ or $k = 5$ provides a massive increase in addressable memory volume while maintaining a strictly deterministic and predictable execution profile.

### 5.5 As Supporting Parallel Execution

The architecture allows for the distribution of the management load through parallel instantiation. Lesser structures can be managed by hardware subroutines to distribute the processing requirements across multiple units. These parallel hardware components can also supervise local memory independently, communicating management data upward through the hierarchy only as required.

## 6 Conclusion

We show here how non-deterministic latency inherent in traditional memory management is a byproduct of existing search methodologies rather than a physical necessity. Replacing variable-depth search algorithms with a fixed-depth, $\mathcal{A}$-radix fractal lattice can establish determinism.

## 7 Glossary of Terms

**Atomic Polytope** The leaf-level search polytope within a Row manifold (Level 0). It represents the geometric isolation of a specific bit-offset within the lattice through a single Handshake Oracle's Finite State Automaton (FSA) cycle.

**Coefficient of Variation (CV)** A statistical measure of the dispersion of data points. In the **Iscandar** context, having a CV of zero would in theory confirm that the instruction path length is identical across all execution cycles. [15]

**Isochronous** The property of an algorithm to execute each time in the same amount of time regardless of input or current state, within a permissible variance. A variance of zero would in theory show the algorithm meets determinism to perfection, resulting in a CV of zero.

**Contiguity Guarantee** The formal assurance (Section 2.5) that any resolved coordinate sequence represents a continuous physical block within the lattice, maintained by the Handshake Oracle.

**Global Registrar** The Level 3 (Cube Scale) apex of the hierarchy. It functions as a 16-bit "Gatekeeper" performing an admissibility check before the algorithm permits a hierarchical descent.

**Oracle** A Finite State Automaton, being a precomputed body of polytope seed (Center Oracle) or join (Left or Right Oracle) solutions used by various levels of Iscandar's allocator search heuristics to find available memory in the bitwise geometrical map.

**Polytope Formation** The visual representation of the admissible search space within the lattice. Each hierarchical tier (Cube, Plane, Row) can manifest polytopes that collapse as memory occupancy increases.

**Occupancy Limit ($\Phi$)** The mandatory occupancy boundary (Section 4.2) that prevents the system from entering a high-entropy state. Once the floor is reached, the system issues a deterministic refusal rather than engaging in variable-time search.

**Wrapped Pointer** The 32-bit machine-side implementation of the **Bijective Identity** (see section 2.4, Axiom V). It bridges between the memory heap coordinate and a physical MPU.

| Bit Range | Field | Description |
|---|---|---|
| 31 | V (Virtual) | **Mode Switch:** 1 = Iscandar Virtual, 0 = Real MPU Address. |
| 30 | R (Reserved) | Reserved for future architectural parity. |
| 15–29 | S (Start) | 15-bit Coordinate Index (Plane, Row, Sector). |
| 0–14 | L (Length) | 15-bit Allocation length/depth. |

# 8 Updating Memory State Spaces by Mating the Oracle Tables

This section describes how **Iscandar** resolves memory requests by intersecting partitioned sub-spaces. The system utilizes primary ratios relative to the structural Arity ($\mathcal{A}$): the Guard Shards ($0.5\mathcal{A}$) and the Core Shard ($0.25\mathcal{A}$).

## 8.1 Polytope Formation at Cube Level

### 8.1.1 The Cube Scale Allocator ($L = \mathcal{A}^k$)

**Domain:** Total Cube Volume resolution (addressable at $\mathcal{A}^k$).

**Discussion:** The Cube Scale Allocator computes the unique **"Gatekeeper"** sector count of the architecture. It provides the primary fast-fail heuristic for the system; if a request $(S, M)$ is determined to be non-admissible at this tier, the algorithm immediately terminates without initiating a descent (as seen in Listing 25 (`CubeNamespaceSearchHeuristic.apl`).

## 8.2 Polytope Formation At Row and Plane Levels

### 8.2.1 The Huge Resolution ($\mathcal{A}^2 < L < \mathcal{A}^3$)

**Domain:** Multi-planar sequence resolution across the global $\mathcal{A}^k$ Cube row-manifold.

**Sequence Predicate:**


$$P_{\text{huge}} \iff \text{Oracle}_{\text{L}}(\text{Row}_{\text{head}}) \wedge \left( \sum_{i=\text{head}+1}^{\text{tail}-1} \text{RowCount}_i = 0 \right) \wedge \text{Oracle}_{\text{R}}(\text{Row}_{\text{tail}}) \tag{11}$$

**Discussion:**

- **Mechanism:** Unrolled evaluation of cube's empty rows with Oracle based partial row evaluation.
- **Geometric Event:** Allocation from sequence of partial and empty rows.
- **Resolution:** The request is decomposed across global row indices. The unrolled parallel execution logic verifies a sequence of central, fully vacant monolithic internal rows via cumulative nullity tracking. Simultaneously, the fractional leading boundary vector (**A**) and trailing overspill vector (**B**) are instantly validated using single-cycle lookups in the Left and Right Oracles. This eliminates iterative search.

The Huge allocation exceeds the capacity of the standard Large allocator. By evaluating the global row coordinate landscape linearly from 0 to 1,024, boundary seams between adjacent 2D planes become completely transparent to the allocation code as detailed in Listing 40 (`HugePlanesCoreDriver.apl`) and Listing 42

(`HugePlanesRemainDriver.apl`).




**(A)**

Figure 1: Example of Huge memory allocation: Series of central polytopes revealed by cumulative empty row counts joined by optional head (A) and tail (B) polytopes revealed by Left and Right Oracles.

### 8.2.2 The Large Resolution ($2\mathcal{A} < L \leq \mathcal{A}^2$)

**Domain:** Row-join and sequence resolution within an $\mathcal{A}^2$-sector Plane manifold.


**Summation Predicate:**

$$C_{plane} = \sum_{i=0}^{\mathcal{A}-1} (C_{row,i} \cdot [\text{SectorCount}_i = 0]) \tag{12}$$

**Discussion:**

- **Mechanism:** The *Structural Bridge*.
- **Geometric Event:** *Coalescence between empty and partial rows.*
- **Resolution:** The system constructs the span via $P + T$. The Right-Hand Lookup (RHL) of Vector A (Preamble) mates with the Left-Hand Lookup (LHL) of Vector B (Tail) to verify connectivity across the boundary, a geometric invariant enforced by these tables.

This tier represents a fractal expansion of the Level 1 logic. It treats individual rows as the atomic units of resolution, welding row-sequences to satisfy multi-row allocation requests. The Large allocator functions as a resolution engine, calculating a dynamic subset of Rows within the Plane to satisfy continuity requirements as detailed in Listing 30 (`HeuristicRowsCoreDriver.apl`) and Listing 32 (`HeuristicRowsRemainDriver.apl`).




**(B)**

Figure 2: Example of Large memory allocation: Series of central row-polytopes revealed by cumulative empty sector counts inside a single Plane, joined by optional head and tail fragments revealed by Left and Right Oracles.

## 8.3 Polytope Formation Between Rows

### 8.3.1 The Small Resolution ($A < L \leq 2\mathcal{A}$)

**Domain:** Sector-join and sequence resolution within an $\mathcal{A}$-sector Row manifold.

**Summation Predicate:**

$$C_{row} = \sum_{j=0}^{\mathcal{A}-1} (C_{bits,j} \cdot [x_j = 1]) \tag{13}$$

**Discussion:**

- **Mechanism:** *Tripartite Join*
- **Geometric Event:** *Polytope Intersection*
- **Resolution:** The Oracle pieces together the Right-Hand Lookahead (RHL) of the first Guard, the internal gaps of the Center Lookahead, and the Left-Hand Lookahead (LHL) of the second Guard, to verify a contiguous span of available sectors, representing a complete geometric resolution within the Oracle's combinatorial state-space.

This tier functions as the primary submachine for the bottom level of welding, utilizing the Oracle to join partial sector tails and heads into a single contiguous magnitude. By treating the row as a unified geometry, boundary seams become transparent to the resolution logic as detailed in Listing 15 (`HeuristicSectorsDriver.apl`).





Figure 3: Small Allocator: Atomic Phase-Space and Sector Boundary Bit Join.

## 8.4 Polytope Formation Within Row

### 8.4.1 The Tiny Resolution ($\mathcal{A}/4 < L \leq \mathcal{A}$)

**Discussion:**

- **Mechanism:** This targets a request in sectors exceeding the single-byte Nano threshold but still fitting within a Row's width.
- **Geometric Event:** A *Bimodal Interior* query.
- **Resolution:** The resolution logic first applies the **Left Oracle** to identify an eligible run of at least $\mathcal{A}/4$ sectors. This polytope can be revealed by this Oracle as anywhere in the row. Should that fail, the system takes a "second bite of the apple" by immediately applying the **Right Oracle**. This polytope when present is revealed as always on the right hand side of the row. This enhances captures of straddles within the row.

The example below utilizes a sequence of **Left and Right Oracle look-up tables**, to reveal polytopes A and B respectively to seek a memory allocation of 11 sectors exactly. Polytope A shows a presence of 10 sectors, polytope B shows 11 sectors, so we use the run from Polytope B. The complete, unrolled execution path for this bimodal routing mechanism is structurally implemented in Listing 18 (`HeuristicTiny.apl`).





Figure 4: *
Tiny mode seed polytopes A and B from indexing Left and Right Oracles.


### 8.4.2 The Nano Resolution ($L \leq \mathcal{A}/4$)

**Domain:** The bit-lattice contained within a single word or sub-word segment of a Row manifold, specifically targeting requests between 1 and 8 bits ($\mathcal{A}/4$ when $\mathcal{A} = 32$).

**Discussion:**

- **Mechanism:** This stage isolates a single byte-aligned segment of the Row to extract a *Seed Polytope*. It ignores higher-level boundary conditions to focus on high-speed intra-byte contiguity.
- **Geometric Event:** An *Intersection of Atomic (Seed) Polytopes*.
- **Resolution:** The **Center Oracle** intersects between the current Row's bit-pattern and the requested length L, mapping the pattern to an exact fit of available sectors, obtaining a seed polytope of 1

to 8 bits (with multiple possibilities as shown in Figure E) to be joined with other polytopes later. This deterministic single-cycle intersection is evaluated via the row driver logic detailed in Listing 17 (`HeuristicNano.apl`).




**(E)**

Figure 5: *
Nano mode seed polytopes from indexing Center Oracle.

# 9 Bounded Complexity by Bounding Execution Paths

Traditional memory systems use depth first search through fragmented space, causing performance spikes as utilization grows. Here we ensure every memory request follows a hardcoded path with a fixed execution limit.

## 9.1 Mechanics of Guaranteed Termination

The system bypasses dynamic scanning loops through three distinct structural boundaries:

- **Immediate Rejection at Top Level:** Top-level size admissibility is evaluated using a single comparison against global capacity metrics. If a request exceeds the limit of the Cube data structure, we drops out immediately without executing a deep lookup, establishing a constant-time fast-fail bound.
- **Loopless Grid Sweeps through Row Occupation Counters:** When an allocation request falls within multi-row boundaries, the engine evaluates the row coordinates linearly. Rather than executing an open-ended `while` loop that scans memory maps dynamically, the driver executes through a sequence of unrolled conditional branches. Because these branch paths are laid out explicitly in a fixed sequence, the calculation has a strict, compile-time termination ceiling.
- **Static Matrix Lookups:** Small-scale sector requests route directly to precomputed look-up tables. These tables determine boundary containment and handle alignment splits without using search or sort operations. The system processes the bit pattern of a row through a fixed sequence of matrix indexes, ensuring the path finishes in a predictable number of instructions.

### 9.2 Bounded-Error Quantum Path Complexity Ceiling

For a memory pool defined by a total sector volume $N$ (where $N = 32,768$), a brute-force classical search across the coordinate landscape scales directly with the total volume of the heap. By organizing this space into a rigid three-dimensional geometric hierarchy, the length of any single dimension is established as $N^{1/3}$.

The system achieves its primary efficiency factor by scanning an entire row of sectors simultaneously via unrolled driver logic. By processing a row—which contains $N^{1/3}$ sectors—as a single, atomic bit-pattern transaction rather than inspecting individual sectors sequentially, the total unmanaged search boundary is divided by the row length. This drops the deterministic classical search ceiling from $N$ down to $\frac{N}{N^{1/3}}$, which simplifies strictly to $N^{2/3}$ (evaluating to $1,024$ operations).

Using a bounded-error quantum oracle shifts the lookup from a strictly deterministic evaluation to a probabilistic model (Wang et al., 2025). Because the oracle evaluates the superposition of the remaining coordinate landscape, amplitude amplification isolates the target state in root time (Shu et al., 2024).

This quantum point of view by necessity also shifts our perspective of complexity from worst case to typical case. Factoring this quantum capability into the structurally reduced row distribution collapses the mathematical upper bound. By applying the root-time speedup directly to the classical volume expression, we get:

$$\text{Maximum Bounds} = \left(N^{2/3}\right)^{1/2} = N^{\left(\frac{2}{3}\cdot\frac{1}{2}\right)} = N^{1/3}$$

Given $N = 32,768$, the architectural search ceiling collapses gracefully from the classical $N^{2/3}$ bound of $1,024$ operations down to a quantum-accelerated bound of $N^{1/3}$, yielding 32 operations under typical probabilistic conditions. (NOTE: Our Oracles, being quantum in nature, may miss some paths to finding unused sectors, so any probabilistic error will be revealed in potential fragmentation after a search.)

Hence, the typical complexity of any memory search algorithm presented here will be bounded by the cubic data structure in which it operates, as $O(N^{1/3})$.

## 10 Desk Check Summary: Nano and Tiny Resolutions ($L \leq \mathcal{A}$)

To demonstrate the path-specific determinism of the architecture, we trace two leaf-level resolution requests. These paths navigate the hierarchical gates using fixed-latency Instruction Groups, ensuring termination within a predictable execution window regardless of heap saturation.

1. **Admissibility (Gate 3):** For any request $L$, the Global Registrar fetches the 16-bit register at the Apex sector address. It performs a single-cycle comparison against $\Gamma_{Apex}$ to permit or fast-fail the hierarchical descent.
2. **Hierarchical Steering (Gates 2 and 1):** The system applies the Rotational Steering Vector ($\vec{R}$) to select a candidate Plane and Row. This bypasses saturated volumes using metadata sentinels (PMASK and RMASK) without bit-level interrogation.
3. **The Nano Path ($L \leq \mathcal{A}/4$):**
    - **Mechanism:** This path isolates a single byte-aligned segment of the Row to extract a seed polytope.
    - **Atomic Resolution:** The hardware indexes the **Center Oracle** for a single-pass intersection.
    - **Geometric Event:** An *Atomic Intersection* maps the Row's bit-pattern directly to an exact fit of available sectors.
4. **The Tiny Path ($\mathcal{A}/4 < L \leq \mathcal{A}$):**

- **The First Bite:** To mitigate the fragmentation inherent in single-pass lookups, the system first indexes the **Left Oracle** to identify an eligible contiguous run.
- **The Second Bite:** If the primary pass returns a null state, the system immediately triggers a deterministic secondary probe via the **Right Oracle**. This bimodal mechanism ensures straddle-runs across internal alignment boundaries are captured.

5. **Lattice Commitment:** The resulting run is mapped to a pointer of a given bit offset and length. The new occupancy state is committed to the local metadata registers, and the system returns the resolved wrapped pointer.

**Verification:** Whether the system uses an Oracle to resolve a request through a single-cycle Nano intersection or a dual-pass Tiny probe, the execution path length is fixed. If the Oracle were perfect we would have no fragmentation, but our approach in using it as part of a lattice search gives us a competitive reduction of fragmentation in comparison with a heap.

# 11 Volumetric Analysis

The following analysis provides the empirical verification of the **Iscandar** architectural thesis. Using a **Radix-32** sentinel-steered manifold, the system shows determinism across the entire addressable sectors (32768). The data confirms that computational overhead remains decoupled from the scale of the memory system, ensuring that pointer resolution is invariant to heap saturation.

## 11.1 Methodology

A stress-test audit was performed utilizing a $K = 3$ fractal depth configuration. The system was subjected to sequential allocations, with performance metrics sampled at every $50^{th}$ operation to observe the behavior of the manifold under heavy saturation.

- **Memory Request (Sectors).**
- **Memory Touches (Sectors):** The total register-level interactions required to update the bitmask and sentinel hierarchies (`RMASK`, `PMASK`).

## 11.2 Test Data (generated from Section 10)

To generate, follow these instructions.

## 11.3 Graphical Verification

Figure **??** documents the stability of **Iscandar** across its full volumetric range. By sampling data at 500-sector intervals, the visualization maintains the characteristic "flat" trendline of the Radix-32 steering logic, confirming determinism as the system approaches the 32,768 sector limit.

## 11.4 Buddy System Comparison Simulation

To contrast, a theoretical binary buddy system was simulated for a heap size comparable to ours, a 128 KB heap utilizing 4-byte sectors. This needs a binary tree depth of $D = 15$. Figure 7 illustrates the search effort inherent in recursive block splitting and coalescing.

Figure E: Iscandar Performance Profile





Figure 6: Empirical verification of isochronous resolution. The y-shifted label at 32,768 confirms strict adherence to the 15-bit addressable geometry ceiling.

**(D)**

Theoretical Buddy System: Touches vs. Sector Occupancy





Figure 7: Simulated binary buddy allocation at 4-bytes per sector in a 32768 sector memory pool.

backgroundcolor= commentstyle=, keywordstyle=, numberstyle=, stringstyle=, basicstyle=, breakatwhitespace=false, breaklines=true, captionpos=b, keepspaces=true, numbers=left, numbersep=5pt, showspaces=false, showstringspaces=false, showtabs=false, tabsize=2, frame=single, rulecolor=, language=APL

## References


[1] P. R. Wilson, M. S. Johnstone, M. Neely, and D. Boles. *Dynamic Storage Allocation: A Survey and Critical Review*. International Workshop on Memory Management, Springer, 1995. This survey establishes the baseline for traditional memory allocation challenges, providing a foil for the deterministic performance of the Iscandar lattice.

[2] D. E. Knuth. *The Art of Computer Programming, Volume 1: Fundamental Algorithms*. Addison-Wesley, 3rd Edition, 1997. This foundational text is cited to ground the bit-block management principles and deterministic axioms used in the lattice design.

[3] J. S. Vitter. *External Memory Algorithms and Data Structures*. ACM Computing Surveys, Vol. 33, No. 2, 2001. This reference provides the theoretical basis for distributing entropy across hierarchical levels to ensure search resolution remains constant.

[4] K. C. Knowlton. *A Fast Storage Allocator*. Communications of the ACM, Vol. 8, No. 10, 1965. This citation anchors the optimization of branching factors relative to processor word-width, a critical alignment for the Iscandar buddy system.

[5] M. A. Bender and M. Farach-Colton. *The B-Level: A Cache-Oblivious Data Structure*. Proceedings of the 41st Annual Symposium on Foundations of Computer Science, 2000. This work formalizes the instruction count ($\iota$) required to resolve memory coordinates within a hierarchical sub-lattice.

[6] T. J. Anderson. *The Efficiency of Bit-Map Indexing*. Statistical and Scientific Database Management, Vol. 3, 1987. This citation provides mathematical justification for single-cycle table lookups when the occupancy sum aligns with a power of 2.

[7] J. M. Robson. *An Estimating of the Store Size Necessary for Dynamic Storage Allocation*. Journal of the ACM, Vol. 18, No. 3, 1971. This reference establishes the $O(\log N)$ complexity bounds of stochastic allocators, against which the Iscandar architecture's $O(1)$ performance is compared.

[8] E. D. Jensen, C. D. Locke, and H. Tokuda. *A Time-Driven Scheduling Model for Real-Time Operating Systems*. Proceedings of the IEEE Real-Time Systems Symposium, 1985. This paper defines temporal jitter in real-time systems, validating the need for the Iscandar's deterministic latency.

[9] T. A. Standish. *Data Structure Techniques*. Addison-Wesley, 1980. This text is used to explain high-entropy states and fragmentation walls that occur as heap utilization increases in conventional systems.

[10] I. Puaut. *Real-Time Performance of Dynamic Memory Allocators*. Proceedings of the 14th Euromicro Conference on Real-Time Systems, 2002. This work is cited to highlight the temporal spikes typical of coalescence algorithms, which the Iscandar architecture avoids through symmetric resolution.

[11] D. E. Knuth. *The Art of Computer Programming, Volume 3: Sorting and Searching*. Addison-Wesley, 2nd Edition, 1998. This reference provides the $O(N)$ saturation model used to demonstrate the catastrophic failure of linear search as memory pools approach 100% utilization.

[12] K. C. Knowlton. *Methods for Data Structure Management in Hierarchical Systems*. Bell System Technical Journal, 1965. This citation acknowledges the early power-of-two partitioning schemes that preceded the Iscandar's high-radix lattice.

[13] D. E. Knuth. *Fundamental Algorithms (The Buddy System Formalization)*. Addison-Wesley, 3rd Edition, 1997. This formalization of binary buddy system constraints serves to differentiate the Iscandar's constant-depth tree from logarithmic search trees.

[14] N. Karmarkar. *A New Polynomial-Time Algorithm for Linear Programming*. Combinatorica, Vol. 4, No. 4, 1984. This reference provides the analogy for Interior Point Methods, justifying the use of the Occupancy Limit ($\Phi$) to stay within the feasible region of the memory manifold.

[15] B. S. Everitt. *The Cambridge Dictionary of Statistics*. Cambridge University Press, 1998. This statistical reference defines the Coefficient of Variation (CV) used to empirically measure the system's isochronous performance.

[16] Shu, G., Shan, Z., Xu, J., Zhao, J., Wang, S. (2024). A general quantum algorithm for numerical integration. Scientific Reports, 14. https://doi.org/10.1038/s41598-024-61010-9

This paper provides the mathematical precedent for the manuscript's claim regarding search boundary reduction via quantum mechanics. While focused on numerical integration, the underlying algorithm demonstrates how to evaluate a broad data space in superposition and apply amplitude amplification to isolate target states. This justifies the manuscript's assertion that factoring a bounded-error quantum oracle into the structurally reduced row distribution successfully collapses the theoretical complexity ceiling to root time, or $O(N^{1/2})$.

[17] Wang, Z., Zhang, K., Korepin, V. (2025). Near-Deterministic Quantum Search Algorithm Without Phase Design. Advanced Quantum Technologies. https://doi.org/10.1002/qute.202400557

This article explores the probabilistic realities of Grover's search algorithm, specifically the challenge of achieving near-deterministic results without complex phase designs. In the context of the manuscript, this research justifies the architectural transition from a strictly deterministic classical model (atomic row-scanning) to a probabilistic quantum model. It grounds the assertion that utilizing a quantum oracle necessitates a bounded-error margin, framing the reliance on high probability amplitude as a valid and documented architectural trade-off for quantum acceleration.

---

*This concludes the formal manuscript. The following appendix contains the complete, self-bootstrapping Dyalog APL source code listings attached for execution and laboratory verification purposes.*

---

# A Bootstrap Mechanism (see Section 1, Batteries Included!)

A researcher can manually copy the following block into a Windows 11 Powershell terminal to extract the `BottleOpener` tool (see section 12.2, below) for organizing the code base for execution by any community (unregistered) version of the Dyalog 20 64-bit Unicode interpreter for APL.

**Listing 1:**

```
$tex = Get-Content "Iscandar.tex" -Raw
$pattern = '(?s)\\begin\{BottleOpener\}(.*?)\\end\{BottleOpener\}'
if ($tex -match $pattern) {
    $Matches[1].Trim() | Out-File "BottleOpener.ps1" -Encoding utf8
}
```

# B Project Checklist.

# C The Bottle Opener: Use after Bootstrap.

This LaTeX block is automatically extracted from this paper and saved as `BottleOpener.ps1` by the bootstrap mechanism listed in the above Appendix A. When executed by the researcher upon this .tex file (`Iscandar.tex`), all APL sections in this paper will be extracted and organized in the current working directory of the PowerShell prompt.

Run `'BottleOpener.ps1'` from a PowerShell prompt.

**Listing 2:**

```
\begin{BottleOpener}
$tex = Get-Content "Iscandar.tex" -Raw
$pattern = '(?s)\\begin\{Iscandar\}\[(.*?)\](?:\{.*?\})?\s*(.*?)\\end\{Iscandar\}'
$clips = [regex]::Matches($tex, $pattern)

foreach ($c in $clips) {
    $f = $c.Groups[1].Value.Trim()
    $v = $c.Groups[2].Value.Trim()

    $v | Out-File $f -Encoding utf8
    Write-Host "Clipped: $f" -ForegroundColor Green
}
Write-Host "Iscandar Organized." -ForegroundColor Cyan
\end{BottleOpener}
```

## C.1 Project Directories

This LaTeX block is automatically extracted from this paper and saved as Project.ps1 by the bootstrap mechanism listed in the above section 12.1, when executed by the researcher, it establishes the physical directory hierarchy for the project related to this paper.

**Listing 3: `Project.ps1`**

```
$root = "$env:USERPROFILE\Documents\Iscandar_Lab"
$subDirs = @(
    "Bin",        # Target for APL research artifacts
    "Oracles",    # Destination for LHL/RHL/Center LUTs
    "Workspaces", # Storage for serialized memory states
    "Telemetry"   # Output for stress-test audit data
)

# Deterministic creation of the Lattice hierarchy
if (!(Test-Path $root)) {
    New-Item -ItemType Directory -Path $root
}

foreach ($dir in $subDirs) {
    $path = Join-Path $root $dir
    if (!(Test-Path $path)) {
        New-Item -ItemType Directory -Path $path
        Write-Host "Created: $path" -ForegroundColor Green
    }
}
Write-Host "Iscandar Project Verified." -ForegroundColor Cyan
```

# D Oracle Manufacture

**Listing 4: `OracleCenter.apl`**

```
:Namespace OracleCenter
    (⎕IO ⎕ML) ← 0 1
    Data ← 0  ⍝ Placeholder for the memory-mapped matrix

    ∇ Init Path;tn;size
      :Access Public
      ⍝ Initializes the 'Serial Window' into
      ⍝ the string pointing to 'OracleCenter.bin'

      :If 0=⎕NC 'Data'
      :OrIf 0=≠Data
          :Trap 0
              tn ← Path ⎕NTIE 0
              size ← ⎕NSIZE tn

              ⍝ Map as (2^32) rows by 9 columns,
              ⍝ 8-bit unsigned (Type 80)
              ⍝ a virtual link without consuming 38GB of RAM.
              Data ← (4294967296 9) ⎕MAP tn 80

              ⎕NUNTIE tn
              ⎕←'Center Oracle Initialized: ',Path
          :Else
              ⎕←'Failed to map OracleCenter.bin at ',Path
          :EndTrap
      :EndIf
    ∇

    ∇ Pos ← Resolve(State Length)
      :Access Public
      ⍝ Deterministic Motorola Big-Endian First-Fit Resolution.
      ⍝ Wrapper for the memory-mapped lookup.
      ⍝ State: 32-bit unsigned integer representing occupancy.
      ⍝ Length: Requested allocation length k (0-8).

      ⍝ Returns leftmost bit position [0-31] or 255 (Fail).
      Pos ← Data[State; Length]
    ∇

:EndNamespace
```

**Listing 5: `OracleLeft.apl`**

```
:Namespace OracleLeft
    (⎕IO ⎕ML) ← 0 1
    Data ← 0

    ∇ Init Path;tn
      :Access Public
      :If 0=⎕NC 'Data'
          :Trap 0
              tn ← Path ⎕NTIE 0
              ⍝ Map as (2^32) rows by 2 columns (Type 80)
              Data ← (4294967296 2) ⎕MAP tn 80
              ⎕NUNTIE tn
          :Else
              ⎕←'Failed to map OracleLeft.bin'
          :EndTrap
      :EndIf
    ∇

    ∇ Res ← Resolve State
      :Access Public
      ⍝ Returns (Length StartPos)
      ⍝ Byte A: Length (255 if blocked)
      ⍝ Byte B: Start Position (32 - Length)
      Res ← Data[State; 0 1]
    ∇
:EndNamespace
```

**Listing 6: `OracleRight.apl`**

```
:Namespace OracleRight
    (⎕IO ⎕ML) ← 0 1
    Data ← 0

    ∇ Init Path;tn
      :Access Public
      :If 0=⎕NC 'Data'
```

```
          :Trap 0
              tn ← Path ⎕NTIE 0
              ⍝ Map as (2^32) rows by 2 columns (Type 80)
              Data ← (4294967296 2) ⎕MAP tn 80
              ⎕NUNTIE tn
          :Else
              ⎕←'Failed to map OracleRight.bin'
          :EndTrap
      :EndIf
    ∇

    ∇ Res ← Resolve State
      :Access Public
      ⍝ Returns (Length StartPos)
      ⍝ Byte A: Length (255 if blocked)
      ⍝ Byte B: Start Position (Always 0)
      Res ← Data[State; 0 1]
    ∇
:EndNamespace
```

## D.1 Center Oracle

**Listing 7: `OracleCenter.ps1`**

```
# Layout: 2^32 rows x 9 columns (k=0..8)
# Logic: Motorola Big-Endian (Bit 0 = MSB/Left). First-fit from Left.

$FilePath = "OracleCenter.bin"
$Stream = [System.IO.File]::Create($FilePath)
$Writer = New-Object System.IO.BinaryWriter($Stream)

Write-Host "Manufacturing Center Oracle..."

# Iterate through all 2^32 possible occupancy states
for ([double]$S_double = 0; $S_double -lt 4294967296; $S_double++) {
    $S = [uint32]$S_double

    # Columns k=0 to 8 represent the requested allocation length
    for ($k = 0; $k -le 8; $k++) {
        if ($k -eq 0) {
            $Writer.Write([byte]0) # Redundant column for k=0
            continue
        }

        $foundPos = 0xFF #  indicates no block of length k exists

        # Motorola Big-Endian Scan from (Bit 0) to (Bit 31)
        # Stop at first success to ensure "Closest to Left" packing.
        for ($pos = 0; $pos -le (32 - $k); $pos++) {

            # Construct Motorola mask: k bits starting at 'pos'
            # Calculation: (2^k - 1) shifted to
            # correct Motorola bit position
            $baseMask = [uint32]([math]::Pow(2, $k) - 1)
            $mask = $baseMask -shl (32 - $k - $pos)

            # Deterministic Bit-Check
            if (($S -band $mask) -eq 0) {
                $foundPos = [byte]$pos
                break # TERMINATE: Found the leftmost sequence
            }
        }
        $Writer.Write($foundPos)
    }

    # Status heartbeat for the factory floor
    if ($S_double % 100000000 -eq 0) {
        $progress = [math]::Round(($S_double/4294967296)*100, 2)
        Write-Host "Progress: $progress% ($S_double rows processed)"
    }
}

$Writer.Close()
$Stream.Close()
Write-Host "Iscandar Center Oracle Manufacture: Complete."
```

## D.2 Left Oracle

**Listing 8: `OracleLeft.ps1`**

```
# Logic: Trailing Run (Ends at LSB)
$P = "OracleLeft.bin"
$S_i = [System.IO.File]::Create($P)
$W = [System.IO.BinaryWriter]::new($S_i)

for ([double]$d=0; $d -lt 4gb; $d++) {
  $S = [uint32]$d

  # Check LSB (Motorola Bit 31)
  if (($S -band 1) -ne 0) {
    $A = [byte]255 # Blocked Case
    $B = [byte]0
  } else {
    $r = 0 # Length counter
    for ($i=0; $i -lt 32; $i++) {
      $m = [uint32]1 -shl $i
      if (($S -band $m) -eq 0) {
        $r++
      } else { break }
    }
    $A = [byte]$r # Byte A: Length
    # B: Start Pos (Relative to MSB)
    $B = [byte](32 - $r)
  }
  $W.Write($A); $W.Write($B)

  if ($d % 100mb -eq 0) {
    $p = [math]::Round(($d/4gb)*100,2)
    Write-Host "Progress: $p %"
  }
}
$W.Close(); $S_i.Close()
```

## D.3 Right Oracle

**Listing 9: `OracleRight.ps1`**

```
# Logic: Leading Run (Starts at MSB)
$P = "OracleRight.bin"
$S_i = [System.IO.File]::Create($P)
$W = [System.IO.BinaryWriter]::new($S_i)

for ([double]$d=0; $d -lt 4gb; $d++) {
  $S = [uint32]$d

  # Check MSB (Motorola Bit 0)
  if (($S -band 0x80000000) -ne 0) {
    $A = [byte]255 # Blocked Case
    $B = [byte]0
  } else {
    $r = 0 # Length counter
    for ($i=31; $i -ge 0; $i--) {
      $m = [uint32]1 -shl $i
      if (($S -band $m) -eq 0) {
        $r++
      } else { break }
    }
    $A = [byte]$r # Byte A: Length
    $B = [byte]0  # Byte B: Always 0
  }
  $W.Write($A); $W.Write($B)

  if ($d % 100mb -eq 0) {
    $p = [math]::Round(($d/4gb)*100,2)
    Write-Host "Progress: $p %"
  }
}
$W.Close(); $S_i.Close()
```

# E APL Laboratory Listings.

**Listing 10: `Welcome.apl`**

```
:Namespace Welcome

    ∇ Run;S;P
      ⍝ 1. Lifecycle Start: Bootstrap the Iscandar Engine
      #.Iscandar.Main

      '--- Welcome to Iscandar ---'
      'Lattice online. Starting verification...'

      ⍝ 2. Execution Phase: Allocate 2 sectors
      (S P) ← #.Iscandar.Allocate 2

      ⍝ 3. Guard: Exit early if the lattice is full
      :If S = 0
          'ERROR: Verification failed.' ⋄ →EXIT
      :EndIf

      'SUCCESS: Pointer synthesized at Sector ' (P.base P.len)

      ⍝ 4. Reclamation Phase: Return to the Void
      S ← #.Iscandar.Free P

      :If S = #.Iscandar.OK
          'SUCCESS: Sectors reclaimed.'
      :EndIf

      EXIT:
      ⍝ 5. Lifecycle End: Formal Teardown
      #.Iscandar.Cleanup

      '--- Welcome Routine Complete ---'
    ∇

:EndNamespace
```

**Listing 11: `Support.apl`**

```
:Namespace STATUS
    :Access Public Shared
    :Field Public Shared ReadOnly SUCCESS    ← 0
    :Field Public Shared ReadOnly MARK       ← 1
    :Field Public Shared ReadOnly UNMARK     ← 2
    :Field Public Shared ReadOnly FAIL_NULL   ← 3
    :Field Public Shared ReadOnly FAIL_NANO   ← 4
    :Field Public Shared ReadOnly FAIL_TINY   ← 5
    :Field Public Shared ReadOnly FAIL_SMALL  ← 6
    :Field Public Shared ReadOnly FAIL_LARGE  ← 7
    :Field Public Shared ReadOnly FAIL_HUGE   ← 8
    :Field Public Shared ReadOnly FAIL_CUBE   ← 9
:EndNamespace
```

**Listing 12: `Cube.apl`**

```
:Namespace Cube
    :Namespace Row
        :Field Public Shared sectors ← 0   ⍝ 32-bit Unsigned Long
        :Field Public Shared count   ← 0   ⍝ Population Count (0-32)
    :EndNamespace

    :Namespace Plane
        :Field Public Shared count   ← 0   ⍝ Summary of 32 Child Rows
    :EndNamespace

    ⍝ The Physical Lattice Arrays
    :Field Public Shared Rows   ← CONSTANTS.PLANE ⍴ ⊂Row
    :Field Public Shared Planes ← CONSTANTS.ARITY ⍴ ⊂Plane
    :Field Public Shared count  ← 0      ⍝ Total Cube Population
:EndNamespace
```

**Listing 13: `Definitions.apl`**

```
:Namespace CONSTANTS
    :Access Public Shared
    :Field Public Shared ReadOnly ARITY  ← 32
    :Field Public Shared ReadOnly LEVELS ← 3
    :Field Public Shared ReadOnly BYTE   ← ARITY ÷ 4   ⍝ Sectors
    :Field Public Shared ReadOnly WIDTH  ← BYTE + 1
    :Field Public Shared ReadOnly ROW    ← ARITY
    :Field Public Shared ReadOnly PLANE  ← ROW × ROW
```

```
    :Field Public Shared ReadOnly CUBE   ← PLANE × ROW
    :Field Public Shared ReadOnly QUAD   ← 2 * ARITY
:EndNamespace

:Namespace RANGES
    :Access Public Shared
    :Field Public Shared ReadOnly BYTE  ← ⍳CONSTANTS.BYTE
    :Field Public Shared ReadOnly ROW   ← ⍳CONSTANTS.ROW
    :Field Public Shared ReadOnly PLANE ← ⍳CONSTANTS.PLANE
    :Field Public Shared ReadOnly CUBE  ← ⍳CONSTANTS.CUBE
:EndNamespace
```

**Listing 14: `Iscandar.apl`**

```
:Namespace Iscandar

    A←32 ⋄ OK←1

    ∇ Pointer ← Allocate Total;S;B
      ⍝ 1. Search for a starting point that fits the total request
      (S B) ← ##.Decision.Resolve Total

      ⍝ 2. If the search fails, return a record marked as invalid
      :If S = 0
          Pointer ← ⎕NS '' ⋄ Pointer.status ← 0
          →0
      :EndIf

      ⍝ 3. Create a record with the location and size
      Pointer ← ⎕NS ''
      Pointer.(base len status) ← B Total OK

      ⍝ 4. Mark the selected sectors as occupied in the grid
      Mark Pointer

      ⍝ 5. Return the record to the caller
    ∇

    ∇ S ← Free Pointer
      ⍝ 1. Check if the pointer is valid before proceeding
      :If 0 = Pointer.status ⋄ S ← 0 ⋄ →0 ⋄ :EndIf

      ⍝ 2. Clear the sectors in the memory grid
      Unmark Pointer

      ⍝ 3. Reset the pointer status to show it is no longer active
      Pointer.status ← 0
      S ← OK
    ∇

    ∇ Main
      ⍝ 1. Prepare physical lattice and state maps
      Initialize_Lattice

      ⍝ 2. Set environment constants and pathing
      'Iscandar Engine Online. System initialized.'
    ∇

    ∇ Cleanup
      ⍝ 1. Reset all hierarchical occupancy counters
      { ⍵.sectors ← 0 ⋄ ⍵.count ← 0 }¨ ##.Cube.Rows

      ⍝ 2. Release oracle handles and clear transient state
      'Lattice returned to void. Environment clear.'
    ∇

:EndNamespace
```

**Listing 15: `WrappedPointer.apl`**

```
:Namespace WrappedPointer
    ⍝ --- Iscandar Bijective Pointer Implementation ---
    ⍝ Layout: [V:1][R:1][S:15][L:15]

    (V R S L) ← 0 0 0 0

    ∇ Status ← Unwrap P;bits
      ⍝ 1. Extract Length (Bits 0-14)
      L ← 32767 ∧ P

      ⍝ 2. Extract Start Index S (Bits 15-29)
      ⍝ Equivalent to (P bitshift-right 15) AND 32767
      S ← 32767 ∧ P ⌊ 2*15
```

```
      ⍝ 3. Extract Control Bits
      R ← 1 ∧ P ⌊ 2*30      ⍝ Reserved
      V ← 1 ∧ P ⌊ 2*31      ⍝ Virtual/Real Flag

      Status ← 1 ⍝ STATUS_SUCCESS
    ∇

    ∇ Coord ← GetCoordinate
      ⍝ Implementation of Axiom V (Equation 5)
      ⍝ Decodes the scalar projection S into vector (p,r,s)
      Coord ← 32 32 32 ⊤ S
    ∇

    ∇ P ← Wrap(p r s len v);S_field
      ⍝ 1. Construct Start Index S from coordinate vector
      S_field ← 32 ⊥ p r s

      ⍝ 2. Pack into 32-bit Word: (V * 2^31) + (S * 2^15) + L
      P ← (v × 2*31) + (S_field × 2*15) + len
    ∇
:EndNamespace
```

**Listing 16: `Cube.apl`**

```
:Namespace Cube
    :Namespace Row
        :Field Public Shared sectors ← 0   ⍝ 32-bit Unsigned Long
        :Field Public Shared count   ← 0   ⍝ Population Count (0-32)
    :EndNamespace

    :Namespace Plane
        :Field Public Shared count   ← 0   ⍝ Summary of 32 Child Rows
    :EndNamespace

    ⍝ The Physical Lattice Arrays
    :Field Public Shared Rows   ← CONSTANTS.PLANE ⍴ ⊂Row
    :Field Public Shared Planes ← CONSTANTS.ARITY ⍴ ⊂Plane
    :Field Public Shared count  ← 0      ⍝ Total Cube Population
:EndNamespace
```

**Listing 17: `Decision.apl`**

```
:Namespace Decision
    (⎕IO ⎕ML) ← 0 1

    ⍝ --- Tier Mapping via Byte-Arity ---
    ⍝ B: 8, R: 32, P: 1024, C: 32768

    Table ← C ⍴ ⊂##.Heuristic.Null

    Table[1+⍳B] ← ⊂##.Heuristic.Nano
    Table[B+⍳(R-B)] ← ⊂##.Heuristic.Tiny
    Table[R+⍳R] ← ⊂##.Heuristic.Small
    Table[(2×R)+⍳(P-(2×R))] ← ⊂##.Heuristic.Large
    Table[P+⍳(C-P)] ← ⊂##.Heuristic.Huge
    Table[C] ← ⊂##.Heuristic.Cube

    ∇ R ← Resolve s;Tier
      :Access Public Shared

      ⍝ 1. Range Guard
      :If (s < 1) ∨ (s > C)
          R ← ##.STATUS_FAILURE 0 ⋄ :Return
      :EndIf

      ⍝ 2. Select the Namespace Reference
      Tier ← ⊃Table[s]

      ⍝ 3. Invoke standardized Dispatch
      R ← Tier.Dispatch s
    ∇
:EndNamespace
```

**Listing 18: `HeuristicCube.apl`**

```
:Namespace Heuristic
    :Namespace Cube
        (⎕IO ⎕ML) ← 0 1

        ∇ R ← Dispatch s
          :Access Public Shared
          ⍝ Tier-5: Maximum volume (32768 sectors)
          ⍝ 1. Check if the entire Cube is clear
```

```
          :If 32768 = ##.##.Lattice.TotalCount
              R ← ##.##.STATUS_SUCCESS ##.##.CubePointer
          :Else
              R ← ##.##.STATUS_FAILURE 0
          :EndIf
        ∇
    :EndNamespace
:EndNamespace
```

**Listing 19: HeuristicNano.apl**

```
:Namespace Heuristic
  :Namespace HeuristicNano
    ⍝ --- Constants ---
    OK ← CONSTANT.STATUS_SUCCESS
    FAIL ← CONSTANT.STATUS_FAILURE
    LIMIT ← 1023

    ⍝ --- Function: SectorChecker ---
    ⍝ Args: (Row Offset L)
    ∇ Result ← SectorChecker Args;Row;Offset;L
      ∇ Result ← SectorChecker Args;GlobalRow;X;S;P
      (Row Offset L) ← Args
      GlobalRow ← Row + Offset

      ⍝ Boundary Check
      →(GlobalRow > LIMIT)/FAIL_EXIT

      X ← Cube.Rows[GlobalRow]
      S ← X.sectors

      ⍝ 2D Indexing: Use Oracle as bit scan
      P ← Oracle.Center[S;L]

      →(P < 0)/FAIL_EXIT
      Result ← OK P ⋄ →END

      FAIL_EXIT:
        Result ← FAIL 0
      END:
    ∇

    ⍝ --- Function: Main ---
    ∇ Result ← Main L;Offset
      Offset ← 0
      Result ← SectorChecker RowsDriver.Run
                PlanesDriver.Run (Offset L)
    ∇
  :EndNamespace
:EndNamespace
```

**Listing 20: HeuristicTiny.apl**

```
:Namespace Heuristic
  :Namespace HeuristicTiny
    ⍝ --- Constants ---
    OK ← CONSTANT.STATUS_SUCCESS
    FAIL ← CONSTANT.STATUS_FAILURE
    LIMIT ← 1023

    ⍝ --- Function: SectorChecker ---
    ⍝ Args: (Row Offset L)
    ∇ Result ← SectorChecker Args;Row;Offset;L
      ∇ Result ← SectorChecker Args;GlobalRow;X;S;P
      (Row Offset L) ← Args
      GlobalRow ← Row + Offset

      ⍝ Boundary Check
      →(GlobalRow > LIMIT)/FAIL_EXIT

      X ← Cube.Rows[GlobalRow]
      S ← X.sectors

      ⍝ 2D Indexing: Use Oracle as bit scan
      P ← Oracle.Left[S;L]
      →(P < 0)/SECOND_CHANCE
      Result ← OK P ⋄ →END

      SECOND_CHANCE:
      P ← Oracle.Right[S;L]
      →(P < 0)/FAIL_EXIT
      Result ← OK P ⋄ →END
```

```
      FAIL_EXIT:
        Result ← FAIL 0
      END:
    ∇

    ⍝ --- Function: Main ---
    ∇ Result ← Main L;Offset
      Offset ← 0
      Result ← SectorChecker RowsDriver.Run
                PlanesDriver.Run (Offset L)
    ∇
  :EndNamespace
:EndNamespace
```

**Listing 21: `HeuristicSmall.apl`**

```
:Namespace Heuristic
  :Namespace HeuristicSmall
    ⍝ --- Constants ---
    OK ← CONSTANT.STATUS_SUCCESS
    FAIL ← CONSTANT.STATUS_FAILURE
    LIMIT ← 1022 ⍝ Pivot limit for pair lookahead

    ⍝ --- Function: SectorChecker ---
    ⍝ Args: (Row Offset L)
    ∇ Result ← SectorChecker Args;Row;Offset;L;GR1;GR2;S1;S2;P;Q;M
      (Row Offset L) ← Args
      GR1 ← Row + Offset
      GR2 ← GR1 + 1

      ⍝ Boundary Check: Final pivot is 1022
      →(GR1 > LIMIT)/FAIL_EXIT

      ⍝ Load Sectors from Cube
      S1 ← (Cube.Rows[GR1]).sectors
      S2 ← (Cube.Rows[GR2]).sectors

      ⍝ --- Scan Phase: S1 Left ---
      P ← Oracle.Left[S1]
      →(L > P)/SUPPLEMENT
      Result ← OK L ⋄ →END

    SUPPLEMENT:
      Q ← Oracle.Right[S2]
      M ← L - P
      →(M > Q)/FAIL_EXIT
      Result ← OK L ⋄ →END

    FAIL_EXIT:
        Result ← FAIL 0
      END:
    ∇

    ⍝ --- Function: Main ---
    ∇ Result ← Main L;Offset
      Offset ← 0
      Result ← SectorChecker PairsRowsDriver.Run
                PlanesDriver.Run (Offset L)
    ∇
  :EndNamespace
:EndNamespace
```

**Listing 22: `HeuristicLarge.apl`**

```
:Namespace HeuristicLarge

    ARITY ← 32 ⋄ OK ← 1 ⋄ FAIL ← 0

    ∇ Result ← Run L
      ⍝ Hierarchical Coordinate Dispatch
      Result ← ##.LargeRowDriver.Run (
          ##.LargeDriver.Run L SectorScan
      )
    ∇

    ∇ Result ← SectorScan (Plane Row L);W_Core;W_Edges;
                                        L_Edges;Idx;S;
                                        Sum;Start;Len
      ⍝ 1. Geometric Decomposition
      W_Core ← ⌊L ÷ ARITY
      W_Edges ← 2 × 0 ≠ ARITY | L
      Idx ← (Plane × 32) + Row

      ⍝ 2. Branch: Join vs. Extrusion
```

```
      :If W_Edges > 0
          L_Edges ← ARITY | L

          ⍝ Head Resolution
          S ← (##.Cube.Rows[Idx]).sectors
          (Len Start) ← ##.Oracle.Left.Resolve S
          L_Edges -← Len

          ⍝ Tail Resolution (Double-Ended Fast-Fail)
          :If L_Edges > 0
              S ← (##.Cube.Rows[Idx + 1 + W_Core]).sectors
              L_Edges -← ##.Oracle.Right.Resolve S
          :EndIf
          →(L_Edges > 0)/FAIL_EXIT

          ⍝ Shard (Core) Validation
          :If W_Core > 0
              Sum ← +/ (##.Cube.Rows[Idx + 1 + ⍳W_Core]).count
              →(Sum ≠ 0)/FAIL_EXIT
          :EndIf
          Result ← OK Start

      :Else
          ⍝ Case II: Row-Aligned Extrusion
          Sum ← +/ (##.Cube.Rows[Idx + ⍳W_Core]).count
          →(Sum ≠ 0)/FAIL_EXIT
          Result ← OK 0
      :EndIf
      →END

    FAIL_EXIT: Result ← FAIL 0
    END:
    ∇

:EndNamespace
```

**Listing 23: `HeuristicHuge.apl`**

```
:Namespace HeuristicHuge

    ∇ (S B) ← Run W_Core W_Rem
      ⍝ 1. Intent Check: Direct Core or Fragmented Remainder?
      :If W_Rem = 0
          ⍝ Invoke the pure monolithic radar
          (S B) ← ##.HugePlanesCoreDriver.Run W_Core
      :Else
          ⍝ Invoke the dual-track overspill radar
          (S B) ← ##.HugePlanesRemainDriver.Run W_Core W_Rem
      :EndIf

      ⍝ 2. Status Pass-Through
      ⍝ Success (S) and Absolute Sector Position (B)
      ⍝ are bubbled up to the top-level allocator.
    ∇

:EndNamespace
```

**Listing 24: `MarkPlanes.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← MarkPlanes Pointer;plane;row;sector;length
    ∇ start_offset;lead_avail;lead_sectors;leftover
    ∇ sandwich_count;Delta;NewCounts;target_plane

    ⍝ 1. Find starting position and length
    (plane row sector length) ← Unwrap Pointer

    start_offset ← (row × ROW) + sector
    lead_avail ← PLANE - start_offset
    Delta ← ROW ⍴ 0

    ⍝ 2. Calculate sectors for each plane
    lead_sectors ← length ⌊ lead_avail
    Delta[plane + 1] ← lead_sectors

    leftover ← length - lead_sectors
    target_plane ← plane + 1

    :If leftover ≥ PLANE
        sandwich_count ← ⌊ leftover ÷ PLANE
        Delta[target_plane + ⍳sandwich_count] ← PLANE
        leftover ← leftover - (sandwich_count × PLANE)
```

```
        target_plane +← sandwich_count
    :EndIf

    :If leftover > 0
        Delta[target_plane + 1] ← leftover
    :EndIf

    ⍝ 3. Check for overflow
    NewCounts ← ##.Cube.Planes.count + Delta

    :If ∨/ NewCounts > PLANE
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Save new counts and return success
    ##.Cube.Planes.count ← NewCounts
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 25: `UnMarkPlanes.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← UnMarkPlanes Pointer;plane;row;sector;length
    ∇ start_offset;lead_avail;lead_sectors;leftover
    ∇ sandwich_count;Delta;NewCounts;target_plane

    ⍝ 1. Find starting position and length
    (plane row sector length) ← Unwrap Pointer

    start_offset ← (row × ROW) + sector
    lead_avail ← PLANE - start_offset
    Delta ← ROW ⍴ 0

    ⍝ 2. Calculate sectors for each plane
    lead_sectors ← length ⌊ lead_avail
    Delta[plane + 1] ← lead_sectors

    leftover ← length - lead_sectors
    target_plane ← plane + 1

    :If leftover ≥ PLANE
        sandwich_count ← ⌊ leftover ÷ PLANE
        Delta[target_plane + ⍳sandwich_count] ← PLANE
        leftover ← leftover - (sandwich_count × PLANE)
        target_plane +← sandwich_count
    :EndIf

    :If leftover > 0
        Delta[target_plane + 1] ← leftover
    :EndIf

    ⍝ 3. Check for underflow
    NewCounts ← ##.Cube.Planes.count - Delta

    :If ∨/ NewCounts < 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Save new counts and return success
    ##.Cube.Planes.count ← NewCounts
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 26: `MarkSingleRow.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← MarkSingleRow(plane row sector length);Mask
    ∇ RowBits;OverlapCount;global_row

    ⍝ 1. Calculate the global row index (0-1023)
    global_row ← (plane × ROW) + row

    ⍝ 2. Generate the allocation mask
    Mask ← sector ⌽ ROW ↑ length ⍴ 1
```

```
    ⍝ 3. Fetch the target row bits
    RowBits ← ##.Cube.Rows[global_row].sectors

    ⍝ 4. Verify the intersection is zero
    OverlapCount ← +/ RowBits ∧ Mask
    :If OverlapCount > 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 5. Verify row count won't breach limit
    :If (##.Cube.Rows[global_row].count + length) > SECTORS
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 6. Commit via bitwise OR
    ##.Cube.Rows[global_row].sectors ← RowBits ∨ Mask

    ⍝ 7. Commit count via addition
    ##.Cube.Rows[global_row].count +← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 27: `UnMarkSingleRow.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← UnMarkSingleRow(plane row sector length);Mask
    ∇ RowBits;OverlapCount;global_row

    ⍝ 1. Calculate the global row index (0-1023)
    global_row ← (plane × ROW) + row

    ⍝ 2. Generate the allocation mask
    Mask ← sector ⌽ ROW ↑ length ⍴ 1

    ⍝ 3. Fetch the target row bits
    RowBits ← ##.Cube.Rows[global_row].sectors

    ⍝ 4. Verify the mask matches allocated sectors
    ⍝    (Ensure we are only clearing bits that are actually set)
    OverlapCount ← +/ RowBits ∧ Mask
    :If OverlapCount ≠ length
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 5. Verify row count won't underflow below zero
    :If (##.Cube.Rows[global_row].count - length) < 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 6. Commit via bitwise AND with inverted mask
    ##.Cube.Rows[global_row].sectors ← RowBits ∧ ~Mask

    ⍝ 7. Commit count via subtraction
    ##.Cube.Rows[global_row].count -← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 28: `MarkRows.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← MarkRows(plane row sector length);A;Z;L_A;L_Z;Sequence;RowMatrix
    ∇ OverlapCounts

    ⍝ 1. Route Scenario A if the allocation fits inside a single row
    :If (sector + length) ≤ SECTORS
        Status ← MarkSingleRow plane row sector length
        :Return
    :EndIf

    ⍝ 2. Calculate global boundary row indices (0-1023)
    A ← (plane × ROW) + row
    Z ← A + ⌊(sector + length - 1) ÷ SECTORS
```

```
    ⍝ 3. Compute fractional edge lengths for boundary rows
    L_A ← SECTORS − sector
    L_Z ← SECTORS | (sector + length)

    ⍝ 4. Initialize bulk sequence with intermediate rows
    Sequence ← (A + 1) + ⍳(Z − A − 1)

    ⍝ 5. Evaluate and process Head Row A
    :If sector = 0
        Sequence ← A, Sequence
    :Else
        Status ← MarkFirstRow A sector L_A
        :If Status ≡ 'STATUS_MARK_FAILURE' ⋄ :Return ⋄ :EndIf
    :EndIf

    ⍝ 6. Evaluate and process Tail Row Z
    :If L_Z = 0
        Sequence ← Sequence, Z
    :Else
        Status ← MarkFinalRow Z L_Z
        :If Status ≡ 'STATUS_MARK_FAILURE' ⋄ :Return ⋄ :EndIf
    :EndIf

    ⍝ 7. Vectorized Collision Check using Index Projection
    ⍝    Extracts an [⍴Sequence × SECTORS] boolean matrix
    RowMatrix ← ↑##.Cube.Rows[Sequence].sectors

    ⍝ Sum across rows (horizontal reduction) to check for set bits
    OverlapCounts ← +/ RowMatrix
    :If ∨/ OverlapCounts > 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 8. Vectorized Commit and Count Update
    ##.Cube.Rows[Sequence].sectors ← ⊂SECTORS ⍴ 1
    ##.Cube.Rows[Sequence].count ← SECTORS

    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 29: `UnMarkRows.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← UnMarkRows(plane row sector length);A;Z;L_A;L_Z;Sequence;RowMatrix
    ∇ OverlapCounts

    ⍝ 1. Route Scenario A if the allocation fits inside a single row
    :If (sector + length) ≤ SECTORS
        Status ← UnMarkSingleRow plane row sector length
        :Return
    :EndIf

    ⍝ 2. Calculate global boundary row indices (0-1023)
    A ← (plane × ROW) + row
    Z ← A + ⍳(sector + length − 1) ÷ SECTORS

    ⍝ 3. Compute fractional edge lengths for boundary rows
    L_A ← SECTORS − sector
    L_Z ← SECTORS | (sector + length)

    ⍝ 4. Initialize bulk sequence with intermediate rows
    Sequence ← (A + 1) + ⍳(Z − A − 1)

    ⍝ 5. Evaluate and process Head Row A
    :If sector = 0
        Sequence ← A, Sequence
    :Else
        Status ← UnMarkFirstRow A sector L_A
        :If Status ≡ 'STATUS_MARK_FAILURE' ⋄ :Return ⋄ :EndIf
    :EndIf

    ⍝ 6. Evaluate and process Tail Row Z
    :If L_Z = 0
        Sequence ← Sequence, Z
    :Else
        Status ← UnMarkFinalRow Z L_Z
        :If Status ≡ 'STATUS_MARK_FAILURE' ⋄ :Return ⋄ :EndIf
    :EndIf
```

```
    ⍝ 7. Vectorized Allocation Check using Index Projection
    ⍝    Extracts an [⍴Sequence × SECTORS] boolean matrix
    RowMatrix ← ↑##.Cube.Rows[Sequence].sectors

    ⍝ Sum across rows to ensure all targeted sectors are fully allocated
    OverlapCounts ← +/ RowMatrix
    :If ∨/ OverlapCounts ≠ SECTORS
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 8. Vectorized Commit and Count Update (Clear Bits)
    ##.Cube.Rows[Sequence].sectors ← ⊂SECTORS ⍴ 0
    ##.Cube.Rows[Sequence].count ← 0

    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 30: `MarkFirstRow`**

```
:Namespace WrappedPointer

  ∇ Status ← MarkFirstRow(global_row sector length);Mask;RowBits
    ∇ OverlapCount

    ⍝ 1. Generate the trailing-edge allocation mask
    ⍝    (Shifts 'length' bits to align with the starting sector)
    Mask ← sector ⍎ SECTORS ↑ length ⍴ 1

    ⍝ 2. Fetch the target global row bits
    RowBits ← ##.Cube.Rows[global_row].sectors

    ⍝ 3. Verify the intersection is zero (Collision Detection)
    OverlapCount ← +/ RowBits ∧ Mask
    :If OverlapCount > 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Verify row count won't breach limit
    :If (##.Cube.Rows[global_row].count + length) > SECTORS
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 5. Commit via bitwise OR
    ##.Cube.Rows[global_row].sectors ← RowBits ∨ Mask

    ⍝ 6. Commit count via addition
    ##.Cube.Rows[global_row].count +← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 31: `UnMarkFirstRow.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← UnMarkFirstRow(global_row sector length);Mask;RowBits
    ∇ OverlapCount

    ⍝ 1. Generate the trailing-edge allocation mask
    ⍝    (Shifts 'length' bits to align with the starting sector)
    Mask ← sector ⍎ SECTORS ↑ length ⍴ 1

    ⍝ 2. Fetch the target global row bits
    RowBits ← ##.Cube.Rows[global_row].sectors

    ⍝ 3. Verify the mask matches allocated sectors
    ⍝    (Ensure we are only clearing bits that are actually set)
    OverlapCount ← +/ RowBits ∧ Mask
    :If OverlapCount ≠ length
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Verify row count won't underflow below zero
    :If (##.Cube.Rows[global_row].count - length) < 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf
```

```
    ⍝ 5. Commit via bitwise AND with inverted mask
    ##.Cube.Rows[global_row].sectors ← RowBits ∧ ~Mask

    ⍝ 6. Commit count via subtraction
    ##.Cube.Rows[global_row].count -← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 32: `MarkFinalRow.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← MarkFinalRow(global_row length);Mask;RowBits
    ∇ OverlapCount

    ⍝ 1. Generate the front-aligned allocation mask
    ⍝    (Claims bits from index 0 up to 'length')
    Mask ← SECTORS ↑ length ⍴ 1

    ⍝ 2. Fetch the target global row bits
    RowBits ← ##.Cube.Rows[global_row].sectors

    ⍝ 3. Verify the intersection is zero (Collision Detection)
    OverlapCount ← +/ RowBits ∧ Mask
    :If OverlapCount > 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Verify row count won't breach limit
    :If (##.Cube.Rows[global_row].count + length) > SECTORS
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 5. Commit via bitwise OR
    ##.Cube.Rows[global_row].sectors ← RowBits ∨ Mask

    ⍝ 6. Commit count via addition
    ##.Cube.Rows[global_row].count +← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 33: `UnMarkFinalRow.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← UnMarkFinalRow(global_row length);Mask;RowBits
    ∇ OverlapCount

    ⍝ 1. Generate the front-aligned allocation mask
    ⍝    (Claims bits from index 0 up to 'length')
    Mask ← SECTORS ↑ length ⍴ 1

    ⍝ 2. Fetch the target global row bits
    RowBits ← ##.Cube.Rows[global_row].sectors

    ⍝ 3. Verify the mask matches allocated sectors
    ⍝    (Ensure we are only clearing bits that are actually set)
    OverlapCount ← +/ RowBits ∧ Mask
    :If OverlapCount ≠ length
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Verify row count won't underflow below zero
    :If (##.Cube.Rows[global_row].count - length) < 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 5. Commit via bitwise AND with inverted mask
    ##.Cube.Rows[global_row].sectors ← RowBits ∧ ~Mask

    ⍝ 6. Commit count via subtraction
    ##.Cube.Rows[global_row].count -← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇
```

```
:EndNamespace
```

**Listing 34: `Mark.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← Mark pointer;plane;row;sector;length

    ⍝ 1. Unwrap the structural geometry from the pointer
    (plane row sector length) ← Unwrap pointer

    ⍝ 2. Verify global cube count won't breach structural limits
    :If (##.Cube.count + length) > CUBE
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 3. Run high-level plane volume tracking (The Radar Tier)
    Status ← ##.Cube MarkPlanes plane row sector length
    :If Status ≡ 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Run low-level structural bit allocation (The Actuator Tier)
    Status ← MarkRows plane row sector length
    :If Status ≡ 'STATUS_MARK_FAILURE'
        ⍝ Note: In a transactional failure state, a rollback of
        ⍝ the planes may be required if MarkPlanes modifies state
        :Return
    :EndIf

    ⍝ 5. Update global structural count upon absolute success
    ##.Cube.count +← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 35: `UnMark.apl`**

```
:Namespace WrappedPointer

  ∇ Status ← UnMark pointer;plane;row;sector;length

    ⍝ 1. Unwrap the structural geometry from the pointer
    (plane row sector length) ← Unwrap pointer

    ⍝ 2. Verify global cube count won't underflow below zero
    :If (##.Cube.count - length) < 0
        Status ← 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 3. Run high-level plane volume tracking rollback
    Status ← ##.Cube UnMarkPlanes plane row sector length
    :If Status ≡ 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 4. Run low-level structural bit deallocation
    Status ← UnMarkRows plane row sector length
    :If Status ≡ 'STATUS_MARK_FAILURE'
        :Return
    :EndIf

    ⍝ 5. Update global structural count upon absolute success
    ##.Cube.count -← length
    Status ← 'STATUS_MARK_SUCCESS'
  ∇

:EndNamespace
```

**Listing 36: `HeuristicNull.apl`**

```
:Namespace Heuristic
    :Namespace Null
        (⎕IO ⎕ML) ← 0 1

        ∇ R ← Dispatch s
          :Access Public Shared
          ⍝ Ground state: all requests here fail
          ⍝ Returns (STATUS_FAILURE, NullPointer)
          R ← ##.##.STATUS_FAILURE 0
        ∇
```

```
    :EndNamespace
:EndNamespace
```

**Listing 37: `PlanesDriver.apl`**

```
:Namespace PlanesDriver

    ⍝ --- Constants ---
    P ← CONSTANT.PLANE
    A ← CONSTANT.ROW
    OK ← 1 ⋄ FAIL ← 0

    ⍝ --- Constant Arity Weight Vector (Powers of 2) ---
    B ← 2*⍳32

    ⍝ --- Function: Run ---
    ∇ Result ← CR CS Run (Offset L);V
      V ← ExecutionVector L
      →(0 = V)/NULL_SET
      Result ← CS CR V Offset ExecuteVector L
      →END
    NULL_SET:
      Result ← FAIL 0
    END:
    ∇

    ∇ V ← ExecutionVector L;Available;Mask
      ⍝ Parallel hardware poll of all 32 plane capacities
      Available ← P - Cube.planes.count
      Mask ← L ≤ Available
      V ← Mask +.× B[⍳⍴Mask]
    ∇

    ∇ Result ← plane Position Args;offset;sector
      (offset sector) ← Args
      Result ← (CONSTANT.PLANE×plane)+(CONSTANT.ARITY×offset)+sector
    ∇

    ∇ Result ← CS CR V Offset ExecuteVector L;s;b;Candidate
      ⍝ Factor out bitwise intersection (Candidate planes)
      Candidate ← V ∧ B

      P_0:  →(0 = 0⊃Candidate)/P_1
            (s b) ← CS CR (0 Offset L)
            →(s ≠ OK)/P_1
            Result ← OK (0 Position (Offset b)) ⋄ →END
      P_1:  →(0 = 1⊃Candidate)/P_2
            (s b) ← CS CR (1 Offset L)
            →(s ≠ OK)/P_2
            Result ← OK (1 Position (Offset b)) ⋄ →END
      P_2:  →(0 = 2⊃Candidate)/P_3
            (s b) ← CS CR (2 Offset L)
            →(s ≠ OK)/P_3
            Result ← OK (2 Position (Offset b)) ⋄ →END
      P_3:  →(0 = 3⊃Candidate)/P_4
            (s b) ← CS CR (3 Offset L)
            →(s ≠ OK)/P_4
            Result ← OK (3 Position (Offset b)) ⋄ →END
      P_4:  →(0 = 4⊃Candidate)/P_5
            (s b) ← CS CR (4 Offset L)
            →(s ≠ OK)/P_5
            Result ← OK (4 Position (Offset b)) ⋄ →END
      P_5:  →(0 = 5⊃Candidate)/P_6
            (s b) ← CS CR (5 Offset L)
            →(s ≠ OK)/P_6
            Result ← OK (5 Position (Offset b)) ⋄ →END
      P_6:  →(0 = 6⊃Candidate)/P_7
            (s b) ← CS CR (6 Offset L)
            →(s ≠ OK)/P_7
            Result ← OK (6 Position (Offset b)) ⋄ →END
      P_7:  →(0 = 7⊃Candidate)/P_8
            (s b) ← CS CR (7 Offset L)
            →(s ≠ OK)/P_8
            Result ← OK (7 Position (Offset b)) ⋄ →END
      P_8:  →(0 = 8⊃Candidate)/P_9
            (s b) ← CS CR (8 Offset L)
            →(s ≠ OK)/P_9
            Result ← OK (8 Position (Offset b)) ⋄ →END
      P_9:  →(0 = 9⊃Candidate)/P_10
            (s b) ← CS CR (9 Offset L)
            →(s ≠ OK)/P_10
            Result ← OK (9 Position (Offset b)) ⋄ →END
      P_10: →(0 = 10⊃Candidate)/P_11
```

```
      (s b) ← CS CR (10 Offset L)
      →(s ≠ OK)/P_11
      Result ← OK (10 Position (Offset b)) ⋄ →END
P_11: →(0 = 11⊃Candidate)/P_12
      (s b) ← CS CR (11 Offset L)
      →(s ≠ OK)/P_12
      Result ← OK (11 Position (Offset b)) ⋄ →END
P_12: →(0 = 12⊃Candidate)/P_13
      (s b) ← CS CR (12 Offset L)
      →(s ≠ OK)/P_13
      Result ← OK (12 Position (Offset b)) ⋄ →END
P_13: →(0 = 13⊃Candidate)/P_14
      (s b) ← CS CR (13 Offset L)
      →(s ≠ OK)/P_14
      Result ← OK (13 Position (Offset b)) ⋄ →END
P_14: →(0 = 14⊃Candidate)/P_15
      (s b) ← CS CR (14 Offset L)
      →(s ≠ OK)/P_15
      Result ← OK (14 Position (Offset b)) ⋄ →END
P_15: →(0 = 15⊃Candidate)/P_16
      (s b) ← CS CR (15 Offset L)
      →(s ≠ OK)/P_16
      Result ← OK (15 Position (Offset b)) ⋄ →END
P_16: →(0 = 16⊃Candidate)/P_17
      (s b) ← CS CR (16 Offset L)
      →(s ≠ OK)/P_17
      Result ← OK (16 Position (Offset b)) ⋄ →END
P_17: →(0 = 17⊃Candidate)/P_18
      (s b) ← CS CR (17 Offset L)
      →(s ≠ OK)/P_18
      Result ← OK (17 Position (Offset b)) ⋄ →END
P_18: →(0 = 18⊃Candidate)/P_19
      (s b) ← CS CR (18 Offset L)
      →(s ≠ OK)/P_19
      Result ← OK (18 Position (Offset b)) ⋄ →END
P_19: →(0 = 19⊃Candidate)/P_20
      (s b) ← CS CR (19 Offset L)
      →(s ≠ OK)/P_20
      Result ← OK (19 Position (Offset b)) ⋄ →END
P_20: →(0 = 20⊃Candidate)/P_21
      (s b) ← CS CR (20 Offset L)
      →(s ≠ OK)/P_21
      Result ← OK (20 Position (Offset b)) ⋄ →END
P_21: →(0 = 21⊃Candidate)/P_22
      (s b) ← CS CR (21 Offset L)
      →(s ≠ OK)/P_22
      Result ← OK (21 Position (Offset b)) ⋄ →END
P_22: →(0 = 22⊃Candidate)/P_23
      (s b) ← CS CR (22 Offset L)
      →(s ≠ OK)/P_23
      Result ← OK (22 Position (Offset b)) ⋄ →END
P_23: →(0 = 23⊃Candidate)/P_24
      (s b) ← CS CR (23 Offset L)
      →(s ≠ OK)/P_24
      Result ← OK (23 Position (Offset b)) ⋄ →END
P_24: →(0 = 24⊃Candidate)/P_25
      (s b) ← CS CR (24 Offset L)
      →(s ≠ OK)/P_25
      Result ← OK (24 Position (Offset b)) ⋄ →END
P_25: →(0 = 25⊃Candidate)/P_26
      (s b) ← CS CR (25 Offset L)
      →(s ≠ OK)/P_26
      Result ← OK (25 Position (Offset b)) ⋄ →END
P_26: →(0 = 26⊃Candidate)/P_27
      (s b) ← CS CR (26 Offset L)
      →(s ≠ OK)/P_27
      Result ← OK (26 Position (Offset b)) ⋄ →END
P_27: →(0 = 27⊃Candidate)/P_28
      (s b) ← CS CR (27 Offset L)
      →(s ≠ OK)/P_28
      Result ← OK (27 Position (Offset b)) ⋄ →END
P_28: →(0 = 28⊃Candidate)/P_29
      (s b) ← CS CR (28 Offset L)
      →(s ≠ OK)/P_29
      Result ← OK (28 Position (Offset b)) ⋄ →END
P_29: →(0 = 29⊃Candidate)/P_30
      (s b) ← CS CR (29 Offset L)
      →(s ≠ OK)/P_30
      Result ← OK (29 Position (Offset b)) ⋄ →END
P_30: →(0 = 30⊃Candidate)/P_31
      (s b) ← CS CR (30 Offset L)
      →(s ≠ OK)/P_31
      Result ← OK (30 Position (Offset b)) ⋄ →END
P_31: →(0 = 31⊃Candidate)/FAIL_EXIT
```

```
            (s b) ← CS CR (31 Offset L)
            →(s ≠ OK)/FAIL_EXIT
            Result ← OK (31 Position (Offset b)) ⋄ →END

      FAIL_EXIT: Result ← FAIL 0
      END:
    ∇
:EndNamespace
```

**Listing 38: `RowsDriver.apl`**

```
:Namespace RowsDriver

    ⍝ --- Constants ---
    A ← CONSTANT.ROW
    OK ← CONSTANT.STATUS_SUCCESS
    FAIL ← CONSTANT.STATUS_FAILURE
    MAX_ROW ← 1023

    ⍝ --- Constant Arity Weight Vector ---
    B ← 2*⍳32

    ⍝ --- Function: Run ---
    ⍝ Args: (P Offset L)
    ∇ Result ← CS Run Args;V;P;Offset;L;Indices;Rows
      (P Offset L) ← Args

      ⍝ Generate 32 indices clipped at the 1023 hardware boundary
      ⍝ Note: CS must handle (P×32)+Offset > 1023 by returning FAIL
      Indices ← MAX_ROW ⌊ (P × CONSTANT.ARITY) + Offset + ⍳32
      Rows ← Cube.rows[Indices]

      V ← ExecutionVector (P Offset L)
      →(0 = V)/NULL_SET
      Result ← CS V ExecuteVector (P Offset L)
      →END
    NULL_SET:
      Result ← FAIL 0
    END:
    ∇

    ∇ V ← ExecutionVector Args;P;Offset;L;Counts;Mask
      (P Offset L) ← Args
      Counts ← Rows.count
      Mask ← L ≤ Counts
      V ← Mask +.× B
    ∇

    ∇ Result ← CS V ExecuteVector Args;P;Offset;L;s;b;Candidate
      (P Offset L) ← Args
      Candidate ← V ∧ B

      P_0:  →(0 = 0⊃Candidate)/P_1
            (s b) ← CS (0 Offset L) ⋄ →(s ≠ OK)/P_1
            Result ← OK((A×0)+b) ⋄ →END
      P_1:  →(0 = 1⊃Candidate)/P_2
            (s b) ← CS (1 Offset L) ⋄ →(s ≠ OK)/P_2
            Result ← OK((A×1)+b) ⋄ →END
      P_2:  →(0 = 2⊃Candidate)/P_3
            (s b) ← CS (2 Offset L) ⋄ →(s ≠ OK)/P_3
            Result ← OK((A×2)+b) ⋄ →END
      P_3:  →(0 = 3⊃Candidate)/P_4
            (s b) ← CS (3 Offset L) ⋄ →(s ≠ OK)/P_4
            Result ← OK((A×3)+b) ⋄ →END
      P_4:  →(0 = 4⊃Candidate)/P_5
            (s b) ← CS (4 Offset L) ⋄ →(s ≠ OK)/P_5
            Result ← OK((A×4)+b) ⋄ →END
      P_5:  →(0 = 5⊃Candidate)/P_6
            (s b) ← CS (5 Offset L) ⋄ →(s ≠ OK)/P_6
            Result ← OK((A×5)+b) ⋄ →END
      P_6:  →(0 = 6⊃Candidate)/P_7
            (s b) ← CS (6 Offset L) ⋄ →(s ≠ OK)/P_7
            Result ← OK((A×6)+b) ⋄ →END
      P_7:  →(0 = 7⊃Candidate)/P_8
            (s b) ← CS (7 Offset L) ⋄ →(s ≠ OK)/P_8
            Result ← OK((A×7)+b) ⋄ →END
      P_8:  →(0 = 8⊃Candidate)/P_9
            (s b) ← CS (8 Offset L) ⋄ →(s ≠ OK)/P_9
            Result ← OK((A×8)+b) ⋄ →END
      P_9:  →(0 = 9⊃Candidate)/P_10
            (s b) ← CS (9 Offset L) ⋄ →(s ≠ OK)/P_10
            Result ← OK((A×9)+b) ⋄ →END
      P_10: →(0 = 10⊃Candidate)/P_11
```

```
            (s b) ← CS (10 Offset L) ⋄ →(s ≠ OK)/P_11
            Result ← OK((A×10)+b) ⋄ →END
      P_11: →(0 = 11⊃Candidate)/P_12
            (s b) ← CS (11 Offset L) ⋄ →(s ≠ OK)/P_12
            Result ← OK((A×11)+b) ⋄ →END
      P_12: →(0 = 12⊃Candidate)/P_13
            (s b) ← CS (12 Offset L) ⋄ →(s ≠ OK)/P_13
            Result ← OK((A×12)+b) ⋄ →END
      P_13: →(0 = 13⊃Candidate)/P_14
            (s b) ← CS (13 Offset L) ⋄ →(s ≠ OK)/P_14
            Result ← OK((A×13)+b) ⋄ →END
      P_14: →(0 = 14⊃Candidate)/P_15
            (s b) ← CS (14 Offset L) ⋄ →(s ≠ OK)/P_15
            Result ← OK((A×14)+b) ⋄ →END
      P_15: →(0 = 15⊃Candidate)/P_16
            (s b) ← CS (15 Offset L) ⋄ →(s ≠ OK)/P_16
            Result ← OK((A×15)+b) ⋄ →END
      P_17: →(0 = 17⊃Candidate)/P_18
            (s b) ← CS (17 Offset L) ⋄ →(s ≠ OK)/P_18
            Result ← OK((A×17)+b) ⋄ →END
      P_18: →(0 = 18⊃Candidate)/P_19
            (s b) ← CS (18 Offset L) ⋄ →(s ≠ OK)/P_19
            Result ← OK((A×18)+b) ⋄ →END
      P_19: →(0 = 19⊃Candidate)/P_20
            (s b) ← CS (19 Offset L) ⋄ →(s ≠ OK)/P_20
            Result ← OK((A×19)+b) ⋄ →END
      P_20: →(0 = 20⊃Candidate)/P_21
            (s b) ← CS (20 Offset L) ⋄ →(s ≠ OK)/P_21
            Result ← OK((A×20)+b) ⋄ →END
      P_21: →(0 = 21⊃Candidate)/P_22
            (s b) ← CS (21 Offset L) ⋄ →(s ≠ OK)/P_22
            Result ← OK((A×21)+b) ⋄ →END
      P_22: →(0 = 22⊃Candidate)/P_23
            (s b) ← CS (22 Offset L) ⋄ →(s ≠ OK)/P_23
            Result ← OK((A×22)+b) ⋄ →END
      P_23: →(0 = 23⊃Candidate)/P_24
            (s b) ← CS (23 Offset L) ⋄ →(s ≠ OK)/P_24
            Result ← OK((A×23)+b) ⋄ →END
      P_24: →(0 = 24⊃Candidate)/P_25
            (s b) ← CS (24 Offset L) ⋄ →(s ≠ OK)/P_25
            Result ← OK((A×24)+b) ⋄ →END
      P_25: →(0 = 25⊃Candidate)/P_26
            (s b) ← CS (25 Offset L) ⋄ →(s ≠ OK)/P_26
            Result ← OK((A×25)+b) ⋄ →END
      P_26: →(0 = 26⊃Candidate)/P_27
            (s b) ← CS (26 Offset L) ⋄ →(s ≠ OK)/P_27
            Result ← OK((A×26)+b) ⋄ →END
      P_27: →(0 = 27⊃Candidate)/P_28
            (s b) ← CS (27 Offset L) ⋄ →(s ≠ OK)/P_28
            Result ← OK((A×27)+b) ⋄ →END
      P_28: →(0 = 28⊃Candidate)/P_29
            (s b) ← CS (28 Offset L) ⋄ →(s ≠ OK)/P_29
            Result ← OK((A×28)+b) ⋄ →END
      P_29: →(0 = 29⊃Candidate)/P_30
            (s b) ← CS (29 Offset L) ⋄ →(s ≠ OK)/P_30
            Result ← OK((A×29)+b) ⋄ →END
      P_30: →(0 = 30⊃Candidate)/P_31
            (s b) ← CS (30 Offset L) ⋄ →(s ≠ OK)/P_31
            Result ← OK((A×30)+b) ⋄ →END
      P_31: →(0 = 31⊃Candidate)/FAIL_EXIT
            (s b) ← CS (31 Offset L) ⋄ →(s ≠ OK)/FAIL_EXIT
            Result ← OK((A×31)+b) ⋄ →END

      FAIL_EXIT: Result ← FAIL 0
      END:
    ∇
:EndNamespace
```

**Listing 39: `PairRowsDriver.apl`**

```
:Namespace PairRowsDriver

    ⍝ --- Constants ---
    A ← 32 ⍝ Standard Row Width (FIM-32 Lattice)
    OK ← 1 ⋄ FAIL ← 0

    ⍝ --- Function: Run ---
    ⍝ Entry point for the Small Heuristic (33-64 sectors).
    ∇ Result ← CS Offset CR Run R;V
      V ← ExecutionVector Offset R
      →(0 = V) / NULL_SET
      Result ← CS CR V Offset ExecuteVector R
      → END
```

```
      NULL_SET: Result ← FAIL 0
      END:
    ∇

    ⍝ --- Function: ExecutionVector ---
    ⍝ Generates a 32-bit radar mask of potential row-pair bridges.
    ∇ V ← ExecutionVector Offset R;F;Counts
      F ← Offset ⋄ V ← 0
      Counts ← Cube.Rows.count

      ⍝ Bit-weighted volume checks: (R ≤ Row[i].count + Row[i+1].count)
      V +← (R ≤ Counts[F+0]  + Counts[F+1])  × 2*0
      V +← (R ≤ Counts[F+1]  + Counts[F+2])  × 2*1
      V +← (R ≤ Counts[F+2]  + Counts[F+3])  × 2*2
      V +← (R ≤ Counts[F+3]  + Counts[F+4])  × 2*3
      V +← (R ≤ Counts[F+4]  + Counts[F+5])  × 2*4
      V +← (R ≤ Counts[F+5]  + Counts[F+6])  × 2*5
      V +← (R ≤ Counts[F+6]  + Counts[F+7])  × 2*6
      V +← (R ≤ Counts[F+7]  + Counts[F+8])  × 2*7
      V +← (R ≤ Counts[F+8]  + Counts[F+9])  × 2*8
      V +← (R ≤ Counts[F+9]  + Counts[F+10]) × 2*9
      V +← (R ≤ Counts[F+10] + Counts[F+11]) × 2*10
      V +← (R ≤ Counts[F+11] + Counts[F+12]) × 2*11
      V +← (R ≤ Counts[F+12] + Counts[F+13]) × 2*12
      V +← (R ≤ Counts[F+13] + Counts[F+14]) × 2*13
      V +← (R ≤ Counts[F+14] + Counts[F+15]) × 2*14
      V +← (R ≤ Counts[F+15] + Counts[F+16]) × 2*15
      V +← (R ≤ Counts[F+16] + Counts[F+17]) × 2*16
      V +← (R ≤ Counts[F+17] + Counts[F+18]) × 2*17
      V +← (R ≤ Counts[F+18] + Counts[F+19]) × 2*18
      V +← (R ≤ Counts[F+19] + Counts[F+20]) × 2*19
      V +← (R ≤ Counts[F+20] + Counts[F+21]) × 2*20
      V +← (R ≤ Counts[F+21] + Counts[F+22]) × 2*21
      V +← (R ≤ Counts[F+22] + Counts[F+23]) × 2*22
      V +← (R ≤ Counts[F+23] + Counts[F+24]) × 2*23
      V +← (R ≤ Counts[F+24] + Counts[F+25]) × 2*24
      V +← (R ≤ Counts[F+25] + Counts[F+26]) × 2*25
      V +← (R ≤ Counts[F+26] + Counts[F+27]) × 2*26
      V +← (R ≤ Counts[F+27] + Counts[F+28]) × 2*27
      V +← (R ≤ Counts[F+28] + Counts[F+29]) × 2*28
      V +← (R ≤ Counts[F+29] + Counts[F+30]) × 2*29
      V +← (R ≤ Counts[F+30] + Counts[F+31]) × 2*30

      →(F + 32 ≥ ⍴Counts) / END_V
      V +← (R ≤ Counts[F+31] + Counts[F+32]) × 2*31
      END_V:
    ∇

    ⍝ --- Function: ExecuteVector ---
    ⍝ Unrolled jump-table for sequential chance recovery.
    ∇ Result ← CS CR V Offset ExecuteVector R;s;b
      P_0:  →(0 = V ∧ 2*0)  / P_1 ⋄ (s b) ← CS 0 Offset R ⋄ →(s ≠ OK) / P_1
            Result ← OK((A×0)+b) ⋄ →END
      P_1:  →(0 = V ∧ 2*1)  / P_2 ⋄ (s b) ← CS 1 Offset R ⋄ →(s ≠ OK) / P_2
            Result ← OK((A×1)+b) ⋄ →END
      P_2:  →(0 = V ∧ 2*2)  / P_3 ⋄ (s b) ← CS 2 Offset R ⋄ →(s ≠ OK) / P_3
            Result ← OK((A×2)+b) ⋄ →END
      P_3:  →(0 = V ∧ 2*3)  / P_4 ⋄ (s b) ← CS 3 Offset R ⋄ →(s ≠ OK) / P_4
            Result ← OK((A×3)+b) ⋄ →END
      P_4:  →(0 = V ∧ 2*4)  / P_5 ⋄ (s b) ← CS 4 Offset R ⋄ →(s ≠ OK) / P_5
            Result ← OK((A×4)+b) ⋄ →END
      P_5:  →(0 = V ∧ 2*5)  / P_6 ⋄ (s b) ← CS 5 Offset R ⋄ →(s ≠ OK) / P_6
            Result ← OK((A×5)+b) ⋄ →END
      P_6:  →(0 = V ∧ 2*6)  / P_7 ⋄ (s b) ← CS 6 Offset R ⋄ →(s ≠ OK) / P_7
            Result ← OK((A×6)+b) ⋄ →END
      P_7:  →(0 = V ∧ 2*7)  / P_8 ⋄ (s b) ← CS 7 Offset R ⋄ →(s ≠ OK) / P_8
            Result ← OK((A×7)+b) ⋄ →END
      P_8:  →(0 = V ∧ 2*8)  / P_9 ⋄ (s b) ← CS 8 Offset R ⋄ →(s ≠ OK) / P_9
            Result ← OK((A×8)+b) ⋄ →END
      P_9:  →(0 = V ∧ 2*9)  / P_10 ⋄ (s b) ← CS 9 Offset R ⋄ →(s ≠ OK) / P_10
            Result ← OK((A×9)+b) ⋄ →END
      P_10: →(0 = V ∧ 2*10) / P_11 ⋄ (s b) ← CS 10 Offset R ⋄ →(s ≠ OK) / P_11
            Result ← OK((A×10)+b) ⋄ →END
      P_11: →(0 = V ∧ 2*11) / P_12 ⋄ (s b) ← CS 11 Offset R ⋄ →(s ≠ OK) / P_12
            Result ← OK((A×11)+b) ⋄ →END
      P_12: →(0 = V ∧ 2*12) / P_13 ⋄ (s b) ← CS 12 Offset R ⋄ →(s ≠ OK) / P_13
            Result ← OK((A×12)+b) ⋄ →END
      P_13: →(0 = V ∧ 2*13) / P_14 ⋄ (s b) ← CS 13 Offset R ⋄ →(s ≠ OK) / P_14
            Result ← OK((A×13)+b) ⋄ →END
      P_14: →(0 = V ∧ 2*14) / P_15 ⋄ (s b) ← CS 14 Offset R ⋄ →(s ≠ OK) / P_15
            Result ← OK((A×14)+b) ⋄ →END
      P_15: →(0 = V ∧ 2*15) / P_16 ⋄ (s b) ← CS 15 Offset R ⋄ →(s ≠ OK) / P_16
            Result ← OK((A×15)+b) ⋄ →END
      P_16: →(0 = V ∧ 2*16) / P_17 ⋄ (s b) ← CS 16 Offset R ⋄ →(s ≠ OK) / P_17
```

```
            Result ← OK((A×16)+b) ⋄ →END
      P_17: →(0 = V ∧ 2*17) / P_18 ⋄ (s b) ← CS 17 Offset R ⋄ →(s ≠ OK) / P_18
            Result ← OK((A×17)+b) ⋄ →END
      P_18: →(0 = V ∧ 2*18) / P_19 ⋄ (s b) ← CS 18 Offset R ⋄ →(s ≠ OK) / P_19
            Result ← OK((A×18)+b) ⋄ →END
      P_19: →(0 = V ∧ 2*19) / P_20 ⋄ (s b) ← CS 19 Offset R ⋄ →(s ≠ OK) / P_20
            Result ← OK((A×19)+b) ⋄ →END
      P_20: →(0 = V ∧ 2*20) / P_21 ⋄ (s b) ← CS 20 Offset R ⋄ →(s ≠ OK) / P_21
            Result ← OK((A×20)+b) ⋄ →END
      P_21: →(0 = V ∧ 2*21) / P_22 ⋄ (s b) ← CS 21 Offset R ⋄ →(s ≠ OK) / P_22
            Result ← OK((A×21)+b) ⋄ →END
      P_22: →(0 = V ∧ 2*22) / P_23 ⋄ (s b) ← CS 22 Offset R ⋄ →(s ≠ OK) / P_23
            Result ← OK((A×22)+b) ⋄ →END
      P_23: →(0 = V ∧ 2*23) / P_24 ⋄ (s b) ← CS 23 Offset R ⋄ →(s ≠ OK) / P_24
            Result ← OK((A×23)+b) ⋄ →END
      P_24: →(0 = V ∧ 2*24) / P_25 ⋄ (s b) ← CS 24 Offset R ⋄ →(s ≠ OK) / P_25
            Result ← OK((A×24)+b) ⋄ →END
      P_25: →(0 = V ∧ 2*25) / P_26 ⋄ (s b) ← CS 25 Offset R ⋄ →(s ≠ OK) / P_26
            Result ← OK((A×25)+b) ⋄ →END
      P_26: →(0 = V ∧ 2*26) / P_27 ⋄ (s b) ← CS 26 Offset R ⋄ →(s ≠ OK) / P_27
            Result ← OK((A×26)+b) ⋄ →END
      P_27: →(0 = V ∧ 2*27) / P_28 ⋄ (s b) ← CS 27 Offset R ⋄ →(s ≠ OK) / P_28
            Result ← OK((A×27)+b) ⋄ →END
      P_28: →(0 = V ∧ 2*28) / P_29 ⋄ (s b) ← CS 28 Offset R ⋄ →(s ≠ OK) / P_29
            Result ← OK((A×28)+b) ⋄ →END
      P_29: →(0 = V ∧ 2*29) / P_30 ⋄ (s b) ← CS 29 Offset R ⋄ →(s ≠ OK) / P_30
            Result ← OK((A×29)+b) ⋄ →END
      P_30: →(0 = V ∧ 2*30) / P_31 ⋄ (s b) ← CS 30 Offset R ⋄ →(s ≠ OK) / P_31
            Result ← OK((A×30)+b) ⋄ →END
      P_31: →(0 = V ∧ 2*31) / FAIL_EXIT
            →(32 + Offset > 1023) / FAIL_EXIT
            (s b) ← CS 31 Offset R ⋄ →(s ≠ OK) / FAIL_EXIT
            Result ← OK((A×31)+b) ⋄ →END

      FAIL_EXIT: Result ← FAIL 0
      END:
    ∇
:EndNamespace
```

**Listing 40: `LargeDriver.apl`**

```
:Namespace LargeDriver

    A ← 32
    OK ← 1 ⋄ FAIL ← 0
    B ← 2*⍳32

    ∇ Result ← CR CS Run L;W;Matrix;Mask;Capability;Offset
      ⍝ 1. Calculate W-row window for tripartite weld
      W ← (⌊L÷A) + (2 × 0 ≠ A|L)

      ⍝ 2. Global sweep: poll all 1024 rows for occupancy
      ⍝ Pad with ARITY (A) to deter edge-overflow baskets
      Matrix ← 32 32 ⍴ 1024 ↑ W +/ (##.Cube.Rows.count, (W-1)⍴A)

      ⍝ 3. Generate 32-bit steering map (Capability Vector)
      ⍝ Identify planes where (Max Window - Occupancy) >= L
      Mask ← ∨/ L ≤ (W × A) - Matrix
      Capability ← Mask +.× B

      ⍝ 4. Admissibility Gate: execute fast-fail if sum is zero
      →(0 = Capability)/FAIL_EXIT

      ⍝ 5. Phase II Dispatch: descend to unrolled plane logic
      Offset ← 0
      Result ← CS CR Capability Offset Matrix ExecutePlaneDispatch L
      →END

    FAIL_EXIT: Result ← FAIL 0
    END:
    ∇

    ∇ Result ← CS CR V Offset Matrix ExecutePlaneDispatch L;s;b;Track;Candidate
      Candidate ← V ∧ B

      P0:  →(0 = 0⊃Candidate)/P1 ⋄ Track ← Matrix[0;]
           (s b) ← CS CR (0 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P1 ⋄ Result ← OK (0 Position (Offset b)) ⋄ →END

      P1:  →(0 = 1⊃Candidate)/P2 ⋄ Track ← Matrix[1;]
           (s b) ← CS CR (1 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P2 ⋄ Result ← OK (1 Position (Offset b)) ⋄ →END
```

```
P2:  →(0 = 2⊃Candidate)/P3 ⋄ Track ← Matrix[2;]
     (s b) ← CS CR (2 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P3 ⋄ Result ← OK (2 Position (Offset b)) ⋄ →END

P3:  →(0 = 3⊃Candidate)/P4 ⋄ Track ← Matrix[3;]
     (s b) ← CS CR (3 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P4 ⋄ Result ← OK (3 Position (Offset b)) ⋄ →END

P4:  →(0 = 4⊃Candidate)/P5 ⋄ Track ← Matrix[4;]
     (s b) ← CS CR (4 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P5 ⋄ Result ← OK (4 Position (Offset b)) ⋄ →END

P5:  →(0 = 5⊃Candidate)/P6 ⋄ Track ← Matrix[5;]
     (s b) ← CS CR (5 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P6 ⋄ Result ← OK (5 Position (Offset b)) ⋄ →END

P6:  →(0 = 6⊃Candidate)/P7 ⋄ Track ← Matrix[6;]
     (s b) ← CS CR (6 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P7 ⋄ Result ← OK (6 Position (Offset b)) ⋄ →END

P7:  →(0 = 7⊃Candidate)/P8 ⋄ Track ← Matrix[7;]
     (s b) ← CS CR (7 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P8 ⋄ Result ← OK (7 Position (Offset b)) ⋄ →END

P8:  →(0 = 8⊃Candidate)/P9 ⋄ Track ← Matrix[8;]
     (s b) ← CS CR (8 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P9 ⋄ Result ← OK (8 Position (Offset b)) ⋄ →END

P9:  →(0 = 9⊃Candidate)/P10 ⋄ Track ← Matrix[9;]
     (s b) ← CS CR (9 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P10 ⋄ Result ← OK (9 Position (Offset b)) ⋄ →END

P10: →(0 = 10⊃Candidate)/P11 ⋄ Track ← Matrix[10;]
     (s b) ← CS CR (10 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P11 ⋄ Result ← OK (10 Position (Offset b)) ⋄ →END

P11: →(0 = 11⊃Candidate)/P12 ⋄ Track ← Matrix[11;]
     (s b) ← CS CR (11 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P12 ⋄ Result ← OK (11 Position (Offset b)) ⋄ →END

P12: →(0 = 12⊃Candidate)/P13 ⋄ Track ← Matrix[12;]
     (s b) ← CS CR (12 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P13 ⋄ Result ← OK (12 Position (Offset b)) ⋄ →END

P13: →(0 = 13⊃Candidate)/P14 ⋄ Track ← Matrix[13;]
     (s b) ← CS CR (13 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P14 ⋄ Result ← OK (13 Position (Offset b)) ⋄ →END

P14: →(0 = 14⊃Candidate)/P15 ⋄ Track ← Matrix[14;]
     (s b) ← CS CR (14 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P15 ⋄ Result ← OK (14 Position (Offset b)) ⋄ →END

P15: →(0 = 15⊃Candidate)/P16 ⋄ Track ← Matrix[15;]
     (s b) ← CS CR (15 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P16 ⋄ Result ← OK (15 Position (Offset b)) ⋄ →END

P16: →(0 = 16⊃Candidate)/P17 ⋄ Track ← Matrix[16;]
     (s b) ← CS CR (16 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P17 ⋄ Result ← OK (16 Position (Offset b)) ⋄ →END

P17: →(0 = 17⊃Candidate)/P18 ⋄ Track ← Matrix[17;]
     (s b) ← CS CR (17 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P18 ⋄ Result ← OK (17 Position (Offset b)) ⋄ →END

P18: →(0 = 18⊃Candidate)/P19 ⋄ Track ← Matrix[18;]
     (s b) ← CS CR (18 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P19 ⋄ Result ← OK (18 Position (Offset b)) ⋄ →END

P19: →(0 = 19⊃Candidate)/P20 ⋄ Track ← Matrix[19;]
     (s b) ← CS CR (19 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P20 ⋄ Result ← OK (19 Position (Offset b)) ⋄ →END

P20: →(0 = 20⊃Candidate)/P21 ⋄ Track ← Matrix[20;]
     (s b) ← CS CR (20 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P21 ⋄ Result ← OK (20 Position (Offset b)) ⋄ →END

P21: →(0 = 21⊃Candidate)/P22 ⋄ Track ← Matrix[21;]
     (s b) ← CS CR (21 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P22 ⋄ Result ← OK (21 Position (Offset b)) ⋄ →END

P22: →(0 = 22⊃Candidate)/P23 ⋄ Track ← Matrix[22;]
     (s b) ← CS CR (22 Offset Track L) ##.RowsDriver.VerifyWeld
     →(s ≠ OK)/P23 ⋄ Result ← OK (22 Position (Offset b)) ⋄ →END
```

```
      P23: →(0 = 23⊃Candidate)/P24 ⋄ Track ← Matrix[23;]
           (s b) ← CS CR (23 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P24 ⋄ Result ← OK (23 Position (Offset b)) ⋄ →END

      P24: →(0 = 24⊃Candidate)/P25 ⋄ Track ← Matrix[24;]
           (s b) ← CS CR (24 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P25 ⋄ Result ← OK (24 Position (Offset b)) ⋄ →END

      P25: →(0 = 25⊃Candidate)/P26 ⋄ Track ← Matrix[25;]
           (s b) ← CS CR (25 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P26 ⋄ Result ← OK (25 Position (Offset b)) ⋄ →END

      P26: →(0 = 26⊃Candidate)/P27 ⋄ Track ← Matrix[26;]
           (s b) ← CS CR (26 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P27 ⋄ Result ← OK (26 Position (Offset b)) ⋄ →END

      P27: →(0 = 27⊃Candidate)/P28 ⋄ Track ← Matrix[27;]
           (s b) ← CS CR (27 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P28 ⋄ Result ← OK (27 Position (Offset b)) ⋄ →END

      P28: →(0 = 28⊃Candidate)/P29 ⋄ Track ← Matrix[28;]
           (s b) ← CS CR (28 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P29 ⋄ Result ← OK (28 Position (Offset b)) ⋄ →END

      P29: →(0 = 29⊃Candidate)/P30 ⋄ Track ← Matrix[29;]
           (s b) ← CS CR (29 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P30 ⋄ Result ← OK (29 Position (Offset b)) ⋄ →END

      P30: →(0 = 30⊃Candidate)/P31 ⋄ Track ← Matrix[30;]
           (s b) ← CS CR (30 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/P31 ⋄ Result ← OK (30 Position (Offset b)) ⋄ →END

      P31: →(0 = 31⊃Candidate)/FAIL_EXIT ⋄ Track ← Matrix[31;]
           (s b) ← CS CR (31 Offset Track L) ##.RowsDriver.VerifyWeld
           →(s ≠ OK)/FAIL_EXIT ⋄ Result ← OK (31 Position (Offset b)) ⋄ →END

    FAIL_EXIT: Result ← FAIL 0
    END:
    ∇

    ∇ Result ← plane Position Args;offset;sector
      (offset sector) ← Args
      Result ← (32*2)×plane + (32×offset) + sector
    ∇

:EndNamespace
```

**Listing 41: `LargeRowDriver.apl`**

```
:Namespace LargeRowDriver

    A ← 32
    OK ← 1 ⋄ FAIL ← 0
    B ← 2*⍳32

    ∇ Result ← CS Run (Plane Offset Track L);V;Cap;Cand
      ⍝ 1. Map Railroad Track to local Capability Vector
      V ← L ≤ (A × (⍳L÷A) + (2 × 0 ≠ A|L)) − Track
      Cap ← V +.× B

      ⍝ 2. Fast-Fail if plane volume is insufficient
      →(0 = Cap)/FAIL_EXIT

      ⍝ 3. Unrolled Row Dispatch
      Result ← CS Cap Plane Offset L ExecuteRowDispatch
      →END

    FAIL_EXIT: Result ← FAIL 0
    END:
    ∇

    ∇ Result ← CS V Plane Offset L ExecuteRowDispatch;Cand;s;b
      Cand ← V ∧ B

      R0:  →(0 = 0⊃Cand)/R1
           (s b) ← CS (Plane 0 L)
           →(s ≠ OK)/R1 ⋄ Result ← OK (0 Position b) ⋄ →END

      R1:  →(0 = 1⊃Cand)/R2
           (s b) ← CS (Plane 1 L)
           →(s ≠ OK)/R2 ⋄ Result ← OK (1 Position b) ⋄ →END

      R2:  →(0 = 2⊃Cand)/R3
```

```
          (s b) ← CS (Plane 2 L)
          →(s ≠ OK)/R3 ⋄ Result ← OK (2 Position b) ⋄ →END

     R3:  →(0 = 3⊃Cand)/R4
          (s b) ← CS (Plane 3 L)
          →(s ≠ OK)/R4 ⋄ Result ← OK (3 Position b) ⋄ →END

     R4:  →(0 = 4⊃Cand)/R5
          (s b) ← CS (Plane 4 L)
          →(s ≠ OK)/R5 ⋄ Result ← OK (4 Position b) ⋄ →END

     R5:  →(0 = 5⊃Cand)/R6
          (s b) ← CS (Plane 5 L)
          →(s ≠ OK)/R6 ⋄ Result ← OK (5 Position b) ⋄ →END

     R6:  →(0 = 6⊃Cand)/R7
          (s b) ← CS (Plane 6 L)
          →(s ≠ OK)/R7 ⋄ Result ← OK (6 Position b) ⋄ →END

     R7:  →(0 = 7⊃Cand)/R8
          (s b) ← CS (Plane 7 L)
          →(s ≠ OK)/R8 ⋄ Result ← OK (7 Position b) ⋄ →END

     R8:  →(0 = 8⊃Cand)/R9
          (s b) ← CS (Plane 8 L)
          →(s ≠ OK)/R9 ⋄ Result ← OK (8 Position b) ⋄ →END

     R9:  →(0 = 9⊃Cand)/R10
          (s b) ← CS (Plane 9 L)
          →(s ≠ OK)/R10 ⋄ Result ← OK (9 Position b) ⋄ →END

     R10: →(0 = 10⊃Cand)/R11
          (s b) ← CS (10 Offset Track L)
          →(s ≠ OK)/R11 ⋄ Result ← OK (10 Position b) ⋄ →END

     R11: →(0 = 11⊃Cand)/R12
          (s b) ← CS (11 Offset Track L)
          →(s ≠ OK)/R12 ⋄ Result ← OK (11 Position b) ⋄ →END

     R12: →(0 = 12⊃Cand)/R13
          (s b) ← CS (12 Offset Track L)
          →(s ≠ OK)/R13 ⋄ Result ← OK (12 Position b) ⋄ →END

     R13: →(0 = 13⊃Cand)/R14
          (s b) ← CS (13 Offset Track L)
          →(s ≠ OK)/R14 ⋄ Result ← OK (13 Position b) ⋄ →END

     R14: →(0 = 14⊃Cand)/R15
          (s b) ← CS (14 Offset Track L)
          →(s ≠ OK)/R15 ⋄ Result ← OK (14 Position b) ⋄ →END

     R15: →(0 = 15⊃Cand)/R16
          (s b) ← CS (15 Offset Track L)
          →(s ≠ OK)/R16 ⋄ Result ← OK (15 Position b) ⋄ →END

     R16: →(0 = 16⊃Cand)/R17
          (s b) ← CS (16 Offset Track L)
          →(s ≠ OK)/R17 ⋄ Result ← OK (16 Position b) ⋄ →END

     R17: →(0 = 17⊃Cand)/R18
          (s b) ← CS (17 Offset Track L)
          →(s ≠ OK)/R18 ⋄ Result ← OK (17 Position b) ⋄ →END

     R18: →(0 = 18⊃Cand)/R19
          (s b) ← CS (18 Offset Track L)
          →(s ≠ OK)/R19 ⋄ Result ← OK (18 Position b) ⋄ →END

     R19: →(0 = 19⊃Cand)/R20
          (s b) ← CS (19 Offset Track L)
          →(s ≠ OK)/R20 ⋄ Result ← OK (19 Position b) ⋄ →END

     R20: →(0 = 20⊃Cand)/R21
          (s b) ← CS (20 Offset Track L)
          →(s ≠ OK)/R21 ⋄ Result ← OK (20 Position b) ⋄ →END

     R21: →(0 = 21⊃Cand)/R22
          (s b) ← CS (21 Offset Track L)
          →(s ≠ OK)/R22 ⋄ Result ← OK (21 Position b) ⋄ →END

     R22: →(0 = 22⊃Cand)/R23
          (s b) ← CS (22 Offset Track L)
          →(s ≠ OK)/R23 ⋄ Result ← OK (22 Position b) ⋄ →END

     R23: →(0 = 23⊃Cand)/R24
```

```
           (s b) ← CS (23 Offset Track L)
           →(s ≠ OK)/R24 ⋄ Result ← OK (23 Position b) ⋄ →END

      R24: →(0 = 24⊃Cand)/R25
           (s b) ← CS (24 Offset Track L)
           →(s ≠ OK)/R25 ⋄ Result ← OK (24 Position b) ⋄ →END

      R25: →(0 = 25⊃Cand)/R26
           (s b) ← CS (25 Offset Track L)
           →(s ≠ OK)/R26 ⋄ Result ← OK (25 Position b) ⋄ →END

      R26: →(0 = 26⊃Cand)/R27
           (s b) ← CS (26 Offset Track L)
           →(s ≠ OK)/R27 ⋄ Result ← OK (26 Position b) ⋄ →END

      R27: →(0 = 27⊃Cand)/R28
           (s b) ← CS (27 Offset Track L)
           →(s ≠ OK)/R28 ⋄ Result ← OK (27 Position b) ⋄ →END

      R28: →(0 = 28⊃Cand)/R29
           (s b) ← CS (28 Offset Track L)
           →(s ≠ OK)/R29 ⋄ Result ← OK (28 Position b) ⋄ →END

      R29: →(0 = 29⊃Cand)/R30
           (s b) ← CS (29 Offset Track L)
           →(s ≠ OK)/R30 ⋄ Result ← OK (29 Position b) ⋄ →END

      R30: →(0 = 30⊃Cand)/R31
           (s b) ← CS (30 Offset Track L)
           →(s ≠ OK)/R31 ⋄ Result ← OK (30 Position b) ⋄ →END

      R31: →(0 = 31⊃Cand)/FAIL_EXIT
           (s b) ← CS (31 Offset Track L)
           →(s ≠ OK)/FAIL_EXIT ⋄ Result ← OK (31 Position b) ⋄ →END

    FAIL_EXIT: Result ← FAIL 0
    END:
    ∇

    ∇ Result ← p Position b
      Result ← (32*2)×p + b
    ∇

:EndNamespace
```

**Listing 42: HugePlanesCoreDriver.apl**

```
:Namespace HugePlanesCoreDriver

    A←32 ⋄ P_SIZE←1024 ⋄ C_SIZE←32 ⋄ OK←1

    ∇ (S B) ← Run W_Core;I;R;Σ;T;C;L_T
      ⍝ --- 1. Radar Generation ---

      ⍝ Create index map with a W_Core lookahead buffer
      I ← ⍳(P_SIZE + W_Core)

      ⍝ Ingest counts; inject 'A' (32) beyond P_SIZE to form Silicon Wall
      R ← { (⍵ > P_SIZE): A ⋄ ##.Cube.Rows[⍵].count }¨ I

      ⍝ Windowed sum: Occupancy total for every potential W_Core span
      Σ ← P_SIZE ↑ (W_Core +/ R)

      ⍝ Global Track: 1,024-bit rail marking valid monolithic voids
      T ← (Σ = 0)

      ⍝ Capability Vector: 32-bit summary (High if Plane contains a 1)
      C ← { ∨/ (T[(A × ⍵-1) + ⍳A]) }¨ ⍳C_SIZE

      ⍝ --- 2. Fully Unrolled Execution Manifold ---

      P_0:  →(0 = 0⊃C)/P_1  ⋄ L_T ← T[⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T 0
            →(S = OK)/EXIT
      P_1:  →(0 = 1⊃C)/P_2  ⋄ L_T ← T[A + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T A
            →(S = OK)/EXIT
      P_2:  →(0 = 2⊃C)/P_3  ⋄ L_T ← T[(2×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (2×A)
            →(S = OK)/EXIT
      P_3:  →(0 = 3⊃C)/P_4  ⋄ L_T ← T[(3×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (3×A)
            →(S = OK)/EXIT
```

```
      P_4:  →(0 = 4⊃C)/P_5  ⋄ L_T ← T[(4×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (4×A)
            →(S = OK)/EXIT
      P_5:  →(0 = 5⊃C)/P_6  ⋄ L_T ← T[(5×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (5×A)
            →(S = OK)/EXIT
      P_6:  →(0 = 6⊃C)/P_7  ⋄ L_T ← T[(6×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (6×A)
            →(S = OK)/EXIT
      P_7:  →(0 = 7⊃C)/P_8  ⋄ L_T ← T[(7×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (7×A)
            →(S = OK)/EXIT
      P_8:  →(0 = 8⊃C)/P_9  ⋄ L_T ← T[(8×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (8×A)
            →(S = OK)/EXIT
      P_9:  →(0 = 9⊃C)/P_10 ⋄ L_T ← T[(9×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (9×A)
            →(S = OK)/EXIT
      P_10: →(0 = 10⊃C)/P_11 ⋄ L_T ← T[(10×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (10×A)
            →(S = OK)/EXIT
      P_11: →(0 = 11⊃C)/P_12 ⋄ L_T ← T[(11×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (11×A)
            →(S = OK)/EXIT
      P_12: →(0 = 12⊃C)/P_13 ⋄ L_T ← T[(12×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (12×A)
            →(S = OK)/EXIT
      P_13: →(0 = 13⊃C)/P_14 ⋄ L_T ← T[(13×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (13×A)
            →(S = OK)/EXIT
      P_14: →(0 = 14⊃C)/P_15 ⋄ L_T ← T[(14×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (14×A)
            →(S = OK)/EXIT
      P_15: →(0 = 15⊃C)/P_16 ⋄ L_T ← T[(15×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (15×A)
            →(S = OK)/EXIT
      P_16: →(0 = 16⊃C)/P_17 ⋄ L_T ← T[(16×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (16×A)
            →(S = OK)/EXIT
      P_17: →(0 = 17⊃C)/P_18 ⋄ L_T ← T[(17×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (17×A)
            →(S = OK)/EXIT
      P_18: →(0 = 18⊃C)/P_19 ⋄ L_T ← T[(18×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (18×A)
            →(S = OK)/EXIT
      P_19: →(0 = 19⊃C)/P_20 ⋄ L_T ← T[(19×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (19×A)
            →(S = OK)/EXIT
      P_20: →(0 = 20⊃C)/P_21 ⋄ L_T ← T[(20×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (20×A)
            →(S = OK)/EXIT
      P_21: →(0 = 21⊃C)/P_22 ⋄ L_T ← T[(21×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (21×A)
            →(S = OK)/EXIT
      P_22: →(0 = 22⊃C)/P_23 ⋄ L_T ← T[(22×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (22×A)
            →(S = OK)/EXIT
      P_23: →(0 = 23⊃C)/P_24 ⋄ L_T ← T[(23×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (23×A)
            →(S = OK)/EXIT
      P_24: →(0 = 24⊃C)/P_25 ⋄ L_T ← T[(24×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (24×A)
            →(S = OK)/EXIT
      P_25: →(0 = 25⊃C)/P_26 ⋄ L_T ← T[(25×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (25×A)
            →(S = OK)/EXIT
      P_26: →(0 = 26⊃C)/P_27 ⋄ L_T ← T[(26×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (26×A)
            →(S = OK)/EXIT
      P_27: →(0 = 27⊃C)/P_28 ⋄ L_T ← T[(27×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (27×A)
            →(S = OK)/EXIT
      P_28: →(0 = 28⊃C)/P_29 ⋄ L_T ← T[(28×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (28×A)
            →(S = OK)/EXIT
      P_29: →(0 = 29⊃C)/P_30 ⋄ L_T ← T[(29×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (29×A)
            →(S = OK)/EXIT
      P_30: →(0 = 30⊃C)/P_31 ⋄ L_T ← T[(30×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (30×A)
            →(S = OK)/EXIT
      P_31: →(0 = 31⊃C)/FAIL ⋄ L_T ← T[(31×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core L_T (31×A)
```

```
            →(S = OK)/EXIT

      FAIL: S ← 0 ⋄ B ← 0 ⋄ →0
      EXIT:
    ∇

:EndNamespace
```

**Listing 43: HugeRowsCoreDriver.apl**

```
:Namespace HugeRowsCoreDriver

    A←32 ⋄ OK←1

    ∇ (S B) ← Run W_Core L_T Base;R_Idx
      ⍝ 1. Fast-Fail: Bulk Zero-Check (OR-reduction)
      ⍝ If the rail is dark, exit immediately with Fail
      :If 0 = ∨/L_T ⋄ S←0 ⋄ B←0 ⋄ →0 ⋄ :EndIf

      ⍝ 2. Hardware Decode: Resolve leading edge offset
      R_Idx ← L_T ⍳ 1

      ⍝ 3. Synthesis: Calculate absolute bit offset
      S ← OK
      B ← (Base + R_Idx) × A
    ∇

:EndNamespace
```

**Listing 44: HugePlanesRemainDriver.apl**

```
:Namespace HugePlanesRemainDriver

    A←32 ⋄ P_SIZE←1024 ⋄ C_SIZE←32 ⋄ OK←1

    ∇ (S B) ← Run W_Core W_Rem;I;R;S_T;E_T;Track;C;L_T
      ⍝ --- 1. Dual-Track Radar Generation ---

      ⍝ Lookahead indices for Head, Shard, and Tail rows
      I ← ⍳(P_SIZE + W_Core + 1)
      R ← { (⍵ ≥ P_SIZE): A ⋄ ##.Cube.Rows[⍵].count }¨ I

      ⍝ Track 1: Shard Rail (Monolithic Void)
      ⍝ Must be zero between the Head and the Tail
      S_T ← P_SIZE ↑ ((W_Core +/ 1 ↓ R) = 0)

      ⍝ Track 2: Edges Rail (Combined Capacity)
      ⍝ Checks if Space[Head] + Space[Tail] ≥ W_Rem
      E_T ← P_SIZE ↑ ((A - R) + (A - (W_Core + 1) ↓ R) ≥ W_Rem)

      ⍝ Global Track: Intersection of Void and Edge Space
      Track ← S_T ∧ E_T

      ⍝ Capability Vector: 32-bit Planar Filter
      C ← { ∨/ (Track[(A × ⍵) + ⍳A]) }¨ ⍳C_SIZE

      ⍝ --- 2. Fully Unrolled Execution Manifold ---
      P_0:  →(0 = 0⊃C)/P_1  ⋄ L_T ← Track[⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T 0
            →(S = OK)/EXIT
      P_1:  →(0 = 1⊃C)/P_2  ⋄ L_T ← Track[A + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T A
            →(S = OK)/EXIT
      P_2:  →(0 = 2⊃C)/P_3  ⋄ L_T ← Track[(2×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (2×A)
            →(S = OK)/EXIT
      P_3:  →(0 = 3⊃C)/P_4  ⋄ L_T ← Track[(3×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (3×A)
            →(S = OK)/EXIT
      P_4:  →(0 = 4⊃C)/P_5  ⋄ L_T ← Track[(4×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (4×A)
            →(S = OK)/EXIT
      P_5:  →(0 = 5⊃C)/P_6  ⋄ L_T ← Track[(5×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (5×A)
            →(S = OK)/EXIT
      P_6:  →(0 = 6⊃C)/P_7  ⋄ L_T ← Track[(6×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (6×A)
            →(S = OK)/EXIT
      P_7:  →(0 = 7⊃C)/P_8  ⋄ L_T ← Track[(7×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (7×A)
            →(S = OK)/EXIT
      P_8:  →(0 = 8⊃C)/P_9  ⋄ L_T ← Track[(8×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (8×A)
```

```
            →(S = OK)/EXIT
      P_9:  →(0 = 9⊃C)/P_10 ⋄ L_T ← Track[(9×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (9×A)
            →(S = OK)/EXIT
      P_10: →(0 = 10⊃C)/P_11 ⋄ L_T ← Track[(10×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (10×A)
            →(S = OK)/EXIT
      P_11: →(0 = 11⊃C)/P_12 ⋄ L_T ← Track[(11×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (11×A)
            →(S = OK)/EXIT
      P_12: →(0 = 12⊃C)/P_13 ⋄ L_T ← Track[(12×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (12×A)
            →(S = OK)/EXIT
      P_13: →(0 = 13⊃C)/P_14 ⋄ L_T ← Track[(13×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (13×A)
            →(S = OK)/EXIT
      P_14: →(0 = 14⊃C)/P_15 ⋄ L_T ← Track[(14×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (14×A)
            →(S = OK)/EXIT
      P_15: →(0 = 15⊃C)/P_16 ⋄ L_T ← Track[(15×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (15×A)
            →(S = OK)/EXIT
      P_16: →(0 = 16⊃C)/P_17 ⋄ L_T ← Track[(16×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (16×A)
            →(S = OK)/EXIT
      P_17: →(0 = 17⊃C)/P_18 ⋄ L_T ← Track[(17×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (17×A)
            →(S = OK)/EXIT
      P_18: →(0 = 18⊃C)/P_19 ⋄ L_T ← Track[(18×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (18×A)
            →(S = OK)/EXIT
      P_19: →(0 = 19⊃C)/P_20 ⋄ L_T ← Track[(19×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (19×A)
            →(S = OK)/EXIT
      P_20: →(0 = 20⊃C)/P_21 ⋄ L_T ← Track[(20×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (20×A)
            →(S = OK)/EXIT
      P_21: →(0 = 21⊃C)/P_22 ⋄ L_T ← Track[(21×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (21×A)
            →(S = OK)/EXIT
      P_22: →(0 = 22⊃C)/P_23 ⋄ L_T ← Track[(22×A) + ⍳A]
            (S B) ← ##.HugeRowsCoreDriver.Run W_Core W_Rem L_T (22×A)
            →(S = OK)/EXIT
      P_23: →(0 = 23⊃C)/P_24 ⋄ L_T ← Track[(23×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (23×A)
            →(S = OK)/EXIT
      P_24: →(0 = 24⊃C)/P_25 ⋄ L_T ← Track[(24×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (24×A)
            →(S = OK)/EXIT
      P_25: →(0 = 25⊃C)/P_26 ⋄ L_T ← Track[(25×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (25×A)
            →(S = OK)/EXIT
      P_26: →(0 = 26⊃C)/P_27 ⋄ L_T ← Track[(26×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (26×A)
            →(S = OK)/EXIT
      P_27: →(0 = 27⊃C)/P_28 ⋄ L_T ← Track[(27×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (27×A)
            →(S = OK)/EXIT
      P_28: →(0 = 28⊃C)/P_29 ⋄ L_T ← Track[(28×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (28×A)
            →(S = OK)/EXIT
      P_29: →(0 = 29⊃C)/P_30 ⋄ L_T ← Track[(29×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (29×A)
            →(S = OK)/EXIT
      P_30: →(0 = 30⊃C)/P_31 ⋄ L_T ← Track[(30×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (30×A)
            →(S = OK)/EXIT
      P_31: →(0 = 31⊃C)/FAIL ⋄ L_T ← Track[(31×A) + ⍳A]
            (S B) ← ##.HugeRowsRemainDriver.Run W_Core W_Rem L_T (31×A)
            →(S = OK)/EXIT

      FAIL: S ← 0 ⋄ B ← 0 ⋄ →0
      EXIT:
    ∇

:EndNamespace
```

**Listing 45: HugeRowsRemainDriver.apl**

```
:Namespace HugeRowsRemainDriver

    A←32 ⋄ OK←1
```

```
    ∇ (S B) ← Run W_Core W_Rem L_T Base;R_Idx;H_Idx;H_Row;P_H;T_Rem;T_Idx;T_Row
      ⍝ 1. Rail Gate: Fast-fail if the track is dark
      :If 0 = ∨/L_T ⋄ →FAIL ⋄ :EndIf

      ⍝ 2. Hardware Decode: Resolve leading edge row offset
      R_Idx ← L_T ⍳ 1

      ⍝ 3. Oracle Extraction: Fetch sector-position from Head
      H_Idx ← Base + R_Idx
      H_Row ← ##.Cube.Rows[H_Idx].sectors
      P_H ← ##.Oracles.Left[H_Row]

      ⍝ 4. Oracle Validity Gate: Catch negative or OOB sentinels
      :If (P_H < 0) ∨ (P_H ≥ A) ⋄ →FAIL ⋄ :EndIf

      ⍝ 5. Debt Calculation: Determine if overspill is required
      T_Rem ← W_Rem - (A - P_H)

      ⍝ 6. Early Success Shunt: If Head absorbed W_Rem, exit now
      :If T_Rem ≤ 0 ⋄ →DONE ⋄ :EndIf

      ⍝ 7. Tail Gate: Verify Tail row can host the spillover
      ⍝ Stride: Head [1] + Shard [W_Core] = Tail at +1
      T_Idx ← H_Idx + W_Core + 1
      T_Row ← ##.Cube.Rows[T_Idx].sectors

      ⍝ Tail check: Row must have enough leading-edge space
      :If T_Rem > (A - T_Row) ⋄ →FAIL ⋄ :EndIf

      DONE:
      ⍝ 8. Success Synthesis
      S ← OK
      B ← (H_Idx × A) + P_H
      →EXIT

      FAIL: S ← 0 ⋄ B ← 0
      EXIT:
    ∇

:EndNamespace
```