

Terminal Commands

All the following commands are to be run in a terminal, the keywords **git** must be prefixed to each of them.

<code>clone url</code>	Clone a repository from <code>url</code> into a new directory.
<code>status</code>	Display the state of the working directory.
<code>log</code>	Show all commit logs of the current repository.
<code>add file</code>	Add <code>file</code> to the staging area.
<code>add -A</code>	Add all changes to the staging area.
<code>commit -m "msg"</code>	Commit the staged changes with message <code>msg</code> .
<code>commit -am "msg"</code>	Add all changes and commit with message <code>msg</code> .
<code>commit --amend -m "msg"</code>	change the last commit message to <code>msg</code> .
<code>reset</code>	delete all local changes.
<code>push origin branch</code>	Push the commits to remote <code>origin</code> on <code>branch</code> .
<code>push</code>	Push the commits to the default remote and branch.
<code>pull</code>	Fetch changes to the local repository.
<code>pull --rebase</code>	Fetch changes and rebase the local commits.
<code>rm fileName</code>	remove a file from the repo.
<code>checkout branch</code>	switch to <code>branch</code> .
<code>checkout -- fileName</code>	discard local changes to <code>fileName</code> .

Git Config

<code>config --list</code>	output config.
<code>config --global --list</code>	output global config.
<code>config --local --list</code>	output local config.
<code>config --system --list</code>	output system config.
<code>config user.name "b"</code>	set the user name to <code>b</code> . to change other settings simply use the same command and replace "user.name" with the desired value.
<code>config user.name</code>	Output the user name. to output other settings simply use the same command and replace "user.name" with the desired value.

GitHub

USEFUL TIP: On the git hub page of the repository, press "." button to launch a online vscode.

CLI

To use the GitHub Cli start the command with `gh`.

<code>create myRepoName</code>	Create a new repository on GitHub. -source=repoPATH -private
<code>view user/repo</code>	View the repository on GitHub.
<code>pr</code>	
<code>create</code>	Create a pull request.
<code>status</code>	View the status of pull requests.
<code>merge</code>	Merge a pull request.
<code>issue</code>	
<code>create</code>	Create a new issue.
<code>view</code>	View an issue.
<code>list</code>	List all issues.

Open-Source Licenses

Copyleft Strength	Determines how strongly the license requires derivative works to use the same license.
Commercial Use	Whether the code can be used in commercial products or services.
Attribution	Requirements for giving credit to original authors and maintaining notices.
Patent Protection	Whether the license includes explicit protection against patent claims.
Work Flexibility	Conditions and restrictions on how the code can be modified and redistributed.
Typical Use Cases	Common projects and applications where the license is frequently used.

License	Copyleft Strength	Commercial Use Allowed	Attribution Required	Patent Protection	Derivative Work Flexibility	Typical Use Cases / Examples
MIT	None (Permissive)	Yes	Yes (license & copyright)	No explicit	Unlimited (incl. proprietary)	Libraries, web frameworks, commercial reuse (React, jQuery, Rails).
Apache 2.0	None (Permissive)	Yes	Yes (NOTICE & license)	Explicit patent grant	Unlimited (incl. proprietary)	Enterprise/cloud, ML frameworks (Android, TensorFlow, Apache Spark).
GNU GPL v3	Strong (Copyleft)	Yes (derivatives must be GPL when distributed)	Yes (license & source terms)	Explicit contributor patent license	Must remain GPL (project-wide)	GNU/Linux ecosystem, dev tools (GCC, Bash, GIMP).
GNU LGPL v3	Weak (Library)	Yes (derivatives must be LGPL when distributed)	Yes (license & source terms)	Explicit contributor patent license	Library-only copyleft	Libraries/frameworks that can be used in proprietary software (GLib, FFmpeg).
Mozilla Public License 2.0	Weak (File-based)	Yes	Yes (license/NOTICE)	Explicit patent grant	File-based copyleft	Mixed open/proprietary codebases (Firefox, Thunderbird).
BSD License	None (Permissive)	Yes	Yes (license & copyright)	No explicit	Unlimited (incl. proprietary)	OS components, academic projects (FreeBSD, OpenBSD).