©Maximilien Notz 2026

Terminal Commands

All the following commands are to be run in a terminal, the keywords `git` must be prefixed to each of them.

`clone url`	Clone a repository from `url` into a new directory.
`status`	Display the state of the working directory.
`log`	Show all commit logs of the current repository.
`add file`	Add `file` to the staging area.
`add -A`	Add all changes to the staging area.
`commit -m "msg"`	Commit the staged changes with message `msgg`.
`commit -am "msg"`	Add all changes and commit with message `msgg`.
`commit --amend -m "msg"`	change the last commit message to `msgg`.
`reset`	delete all local changes.
`push origin branch`	Push the commits to remote `origin` on `branch`.
`push`	Push the commits to the default remote and branch.
`pull`	Fetch changes to the local repository.
`pull --rebase`	Fetch changes and rebase the local commits.
`rm fileName`	remove a file from the repo.
`checkout branch`	switch to `branch`.
`checkout -- fileName`	discard local changes to `fileName`.

Git Stash

`stash`	stash all the local changes.
`stash pop`	Apply the most recent stash and remove it from the stash list.
`stash drop`	Delete the most recent stash from the stash list.
`stash list`	List all stashes.
`stash clear`	Delete all stashes.

Git Config

`config --list`	output config.
`config --global --list`	output global config.
`config --local --list`	output local config.
`config --system --list`	output system config.
`config user.name "b"`	set the user name to `b`. to change other settings simply use the same command and replace "user.name" with the desired value.
`config user.name`	Output the user name. to output other settings simply use the same command and replace "user.name" with the desired value.

GitHub

USEFUL TIP: On the git hub page of the repository, press "." button to launch a online vscode.

CLI

To use the GitHub Cli start the command with `gh`.

`repo`		
	`create myRepoName`	Create a new repository on GitHub. –source=repoPATH –private
	`view user/repo`	View the repository on GitHub.
`pr`		
	`create`	Create a pull request.
	`status`	View the status of pull requests.
	`merge`	Merge a pull request.
`issue`		
	`create`	Create a new issue.
	`view`	View an issue.
	`list`	List all issues.

Open-Source Licenses

`Copyleft Strength`	Determines how strongly the license requires derivative works to use the same license.
`Commercial Use`	Whether the code can be used in commercial products or services.
`Attribution`	Requirements for giving credit to original authors and maintaining notices.
`Patent Protection`	Whether the license includes explicit protection against patent claims.
`Work Flexibility`	Conditions and restrictions on how the code can be modified and redistributed.
`Typical Use Cases`	Common projects and applications where the license is frequently used.

License	Copyleft Strength	Commercial Use Allowed	Attribution Required	Patent Protection	Derivative Work Flexibility	Typical Use Cases / Examples
MIT	None (Permissive)	Yes	Yes (license & copyright)	No explicit	Unlimited (incl. proprietary)	Libraries, web frameworks, commercial reuse (React, jQuery, Rails).
Apache 2.0	None (Permissive)	Yes	Yes (NOTICE & license)	Explicit patent grant	Unlimited (incl. proprietary)	Enterprise/cloud, ML frameworks (Android, TensorFlow, Apache Spark).
GNU GPL v3	Strong (Copyleft)	Yes (derivatives must be GPL when distributed)	Yes (license & source terms)	Explicit contributor patent license	Must remain GPL (project-wide)	GNU/Linux ecosystem, dev tools (GCC, Bash, GIMP).
GNU LGPL v3	Weak (Library)	Yes (derivatives must be LGPL when distributed)	Yes (license & source terms)	Explicit contributor patent license	Library-only copyleft	Libraries/frameworks that can be used in proprietary software (GLib, FFmpeg).
Mozilla Public License 2.0	Weak (File-based)	Yes	Yes (license/NOTICE)	Explicit patent grant	File-based copyleft	Mixed open/proprietary codebases (Firefox, Thunderbird).
BSD License	None (Permissive)	Yes	Yes (license & copyright)	No explicit	Unlimited (incl. proprietary)	OS components, academic projects (FreeBSD, OpenBSD).