

# Formalisation of Ground Resolution and CDCL in Isabelle/HOL

Mathias Fleury and Jasmin Blanchette

March 16, 2016

## Contents

<b>1</b>	<b>Transitions</b>	<b>5</b>
1.1	More theorems about Closures . . . . .	5
1.2	Full Transitions . . . . .	6
1.3	Well-Foundedness and Full Transitions . . . . .	8
1.4	More Well-Foundedness . . . . .	9
<b>2</b>	<b>Various Lemmas</b>	<b>11</b>
<b>3</b>	<b>More List</b>	<b>12</b>
3.1	<i>upt</i> . . . . .	12
3.2	Lexicographic Ordering . . . . .	15
3.3	Remove and Multiset equality . . . . .	15
<b>4</b>	<b>Logics</b>	<b>16</b>
4.1	Definition and abstraction . . . . .	16
4.2	properties of the abstraction . . . . .	18
4.3	Subformulas and properties . . . . .	20
4.4	Positions . . . . .	23
<b>5</b>	<b>Semantics over the syntax</b>	<b>26</b>
<b>6</b>	<b>Rewrite systems and properties</b>	<b>27</b>
6.1	Lifting of rewrite rules . . . . .	27
6.2	Consistency preservation . . . . .	30
6.3	Full Lifting . . . . .	31
<b>7</b>	<b>Transformation testing</b>	<b>31</b>
7.1	Definition and first properties . . . . .	31
7.2	Invariant conservation . . . . .	34
7.2.1	Invariant while lifting of the rewriting relation . . . . .	34
7.2.2	Invariant after all rewriting . . . . .	35
<b>8</b>	<b>Rewrite Rules</b>	<b>37</b>
8.1	Elimination of the equivalences . . . . .	37
8.2	Eliminate Implication . . . . .	39
8.3	Eliminate all the True and False in the formula . . . . .	40
8.4	PushNeg . . . . .	46
8.5	Push inside . . . . .	51

8.5.1	Only one type of connective in the formula (+ not)	61
8.5.2	Push Conjunction	64
8.5.3	Push Disjunction	65
<b>9</b>	<b>The full transformations</b>	<b>65</b>
9.1	Abstract Property characterizing that only some connective are inside the others	65
9.1.1	Definition	65
9.2	Conjunctive Normal Form	68
9.2.1	Full CNF transformation	68
9.3	Disjunctive Normal Form	69
9.3.1	Full DNF transform	69
<b>10</b>	<b>More aggressive simplifications: Removing true and false at the beginning</b>	<b>70</b>
10.1	Transformation	70
10.2	More invariants	71
10.3	The new CNF and DNF transformation	76
<b>11</b>	<b>Partial Clausal Logic</b>	<b>77</b>
11.1	Clauses	77
11.2	Partial Interpretations	77
11.2.1	Consistency	77
11.2.2	Atoms	77
11.2.3	Totality	79
11.2.4	Interpretations	82
11.2.5	Satisfiability	83
11.2.6	Entailment for Multisets of Clauses	84
11.2.7	Tautologies	86
11.2.8	Entailment for clauses and propositions	88
11.3	Subsumptions	93
11.4	Removing Duplicates	94
11.5	Set of all Simple Clauses	94
11.6	Experiment: Expressing the Entailments as Locales	97
11.7	Entailment to be extended	98
<b>12</b>	<b>Link with Multiset Version</b>	<b>99</b>
12.1	Transformation to Multiset	99
12.2	Equisatisfiability of the two Version	99
<b>13</b>	<b>Resolution</b>	<b>102</b>
13.1	Simplification Rules	102
13.2	Unconstrained Resolution	104
13.2.1	Subsumption	104
13.3	Inference Rule	104
13.4	Lemma about the simplified state	120
13.5	Resolution and Invariants	122
13.5.1	Invariants	122
13.5.2	well-foundedness if the relation	128

<b>14 Partial Clausal Logic</b>	<b>143</b>
14.1 Marked Literals . . . . .	143
14.1.1 Definition . . . . .	143
14.1.2 Entailment . . . . .	144
14.1.3 Defined and undefined literals . . . . .	146
14.2 Backtracking . . . . .	147
14.3 Decomposition with respect to the marked literals . . . . .	148
14.4 Negation of Clauses . . . . .	155
14.5 Other . . . . .	158
14.6 Abstract Clause Representation . . . . .	160
<b>15 Measure</b>	<b>162</b>
<b>16 NOT's CDCL</b>	<b>166</b>
16.1 Auxiliary Lemmas and Measure . . . . .	166
16.2 Initial definitions . . . . .	166
16.2.1 The state . . . . .	166
16.2.2 Definition of the operation . . . . .	170
16.3 DPLL with backjumping . . . . .	171
16.3.1 Definition . . . . .	172
16.3.2 Basic properties . . . . .	173
16.3.3 Termination . . . . .	175
16.3.4 Normal Forms . . . . .	180
16.4 CDCL . . . . .	187
16.4.1 Learn and Forget . . . . .	187
16.4.2 Definition of CDCL . . . . .	189
16.5 CDCL with invariant . . . . .	193
16.6 Termination . . . . .	199
16.6.1 Restricting learn and forget . . . . .	199
16.7 CDCL with restarts . . . . .	210
16.7.1 Definition . . . . .	210
16.7.2 Increasing restarts . . . . .	211
16.8 Merging backjump and learning . . . . .	219
16.8.1 Instantiations . . . . .	231
<b>17 DPLL as an instance of NOT</b>	<b>246</b>
17.1 DPLL with simple backtrack . . . . .	246
17.2 Adding restarts . . . . .	252
<b>18 DPLL</b>	<b>253</b>
18.1 Rules . . . . .	253
18.2 Invariants . . . . .	253
18.3 Termination . . . . .	261
18.4 Final States . . . . .	264
18.5 Link with NOT's DPLL . . . . .	265
18.5.1 Level of literals and clauses . . . . .	266
18.5.2 Properties about the levels . . . . .	270

<b>19 Weidenbach's CDCL</b>	<b>273</b>
19.1 The State . . . . .	273
19.2 CDCL Rules . . . . .	282
19.3 Invariants . . . . .	289
19.3.1 Properties of the trail . . . . .	289
19.3.2 Better-Suited Induction Principle . . . . .	293
19.3.3 Compatibility with $op \sim$ . . . . .	297
19.3.4 Conservation of some Properties . . . . .	302
19.3.5 Learned Clause . . . . .	303
19.3.6 No alien atom in the state . . . . .	305
19.3.7 No duplicates all around . . . . .	308
19.3.8 Conflicts and co . . . . .	309
19.3.9 Putting all the invariants together . . . . .	317
19.3.10 No tautology is learned . . . . .	320
19.4 CDCL Strong Completeness . . . . .	321
19.5 Higher level strategy . . . . .	323
19.5.1 Definition . . . . .	323
19.5.2 Invariants . . . . .	325
19.5.3 Literal of highest level in conflicting clauses . . . . .	331
19.5.4 Literal of highest level in marked literals . . . . .	335
19.5.5 Strong completeness . . . . .	345
19.5.6 No conflict with only variables of level less than backtrack level . . . . .	351
19.5.7 Final States are Conclusive . . . . .	362
19.6 Termination . . . . .	369
19.7 No Relearning of a clause . . . . .	369
19.8 Decrease of a measure . . . . .	385
<b>20 Simple Implementation of the DPLL and CDCL</b>	<b>392</b>
20.1 Common Rules . . . . .	392
20.1.1 Propagation . . . . .	392
20.1.2 Unit propagation for all clauses . . . . .	393
20.1.3 Decide . . . . .	394
20.2 Simple Implementation of DPLL . . . . .	395
20.2.1 Combining the propagate and decide: a DPLL step . . . . .	395
20.2.2 Adding invariants . . . . .	397
20.2.3 Code export . . . . .	404
20.3 CDCL Implementation . . . . .	408
20.3.1 Definition of the rules . . . . .	408
20.3.2 The Transitions . . . . .	410
20.3.3 Code generation . . . . .	421
<b>21 Link between Weidenbach's and NOT's CDCL</b>	<b>436</b>
21.1 Inclusion of the states . . . . .	436
21.2 More lemmas conflict-propagate and backjumping . . . . .	438
21.2.1 Termination . . . . .	438
21.2.2 More backjumping . . . . .	439
21.3 CDCL FW . . . . .	452
21.4 FW with strategy . . . . .	457
21.4.1 The intermediate step . . . . .	457

21.5 Adding Restarts . . . . .	491
<b>22 Link between Weidenbach's and NOT's CDCL</b>	<b>503</b>
22.1 Inclusion of the states . . . . .	503
22.2 Additional Lemmas between NOT and W states . . . . .	507
22.3 More lemmas conflict-propagate and backjumping . . . . .	508
22.4 CDCL FW . . . . .	508
<b>23 Incremental SAT solving</b>	<b>516</b>
<b>24 2-Watched-Literal</b>	<b>526</b>
24.1 Datastructure and Access Functions . . . . .	526
24.2 Invariants . . . . .	528
24.3 Abstract 2-WL . . . . .	536
24.4 Instantiation of the previous locale . . . . .	538
<b>25 Invariants for 2 Watched-Literals</b>	<b>547</b>
25.1 Interpretation for <i>conflict-driven-clause-learning<sub>W</sub>.cdcl<sub>W</sub></i> . . . . .	547
25.1.1 Direct Interpretation . . . . .	547
25.1.2 Opaque Type with Invariant . . . . .	548
<b>26 Superposition</b>	<b>555</b>
26.1 We can now define the rules of the calculus . . . . .	561
theory <i>Wellfounded-More</i>	
imports <i>Main</i>	

begin

## 1 Transitions

This theory contains more facts about closure, the definition of full transformations, and well-foundedness.

### 1.1 More theorems about Closures

This is the equivalent of  $?r \leq ?s \implies ?r^{**} \leq ?s^{**}$  for *trancpl*

**lemma** *trancpl-mono-explicit*:

$r^{++} \ a \ b \implies r \leq s \implies s^{++} \ a \ b$

**using** *rtrancpl-mono* **by** (*auto dest!*: *trancplD intro: rtrancpl-into-trancpl2*)

**lemma** *trancpl-mono*:

**assumes** *mono*:  $r \leq s$

**shows**  $r^{++} \leq s^{++}$

**using** *rtrancpl-mono[OF mono]* *mono* **by** (*auto dest!*: *trancplD intro: rtrancpl-into-trancpl2*)

**lemma** *trancpl-idemp-rel*:

$R^{++++} \ a \ b \longleftrightarrow R^{++} \ a \ b$

**apply** (*rule iffI*)

**prefer** 2 **apply** *blast*

**by** (*induction rule: trancpl-induct*) *auto*

Equivalent of  $?r^{****} = ?r^{**}$

**lemma** *tranc1-idemp*:  $(r^+)^+ = r^+$   
**by** *simp*

**lemmas** *tranc1-idemp*[*simp*] = *tranc1-idemp*[*to-pred*]

This theorem already exists as  $?r^{**} ?a ?b \equiv ?a = ?b \vee ?r^{++} ?a ?b$  (and sledgehammer uses it), but it makes sense to duplicate it, because it is unclear how stable the lemmas in Nitpick are.

**lemma** *rtranc1-unfold*:  $rtranc1\ r\ a\ b \longleftrightarrow (a = b \vee tranc1\ r\ a\ b)$   
**by** (*meson* *rtranc1.simps* *rtranc1D* *tranc1-into-rtranc1*)

**lemma** *tranc1-unfold-end*:  $tranc1\ r\ a\ b \longleftrightarrow (\exists a'. rtranc1\ r\ a\ a' \wedge r\ a'\ b)$   
**by** (*metis* *rtranc1.rtranc1-refl* *rtranc1-into-tranc11* *tranc1.cases* *tranc1-into-rtranc1*)

**lemma** *tranc1-unfold-begin*:  $tranc1\ r\ a\ b \longleftrightarrow (\exists a'. r\ a\ a' \wedge rtranc1\ r\ a'\ b)$   
**by** (*meson* *rtranc1-into-tranc12* *tranc1D*)

**lemma** *tranc1-set-tranc1*:  $(a, b) \in \{(b, a). P\ a\ b\}^+ \longleftrightarrow P^{++}\ b\ a$   
**apply** (*rule* *iffI*)  
**apply** (*induction* *rule*: *tranc1-induct*; *simp*)  
**apply** (*induction* *rule*: *tranc1-induct*; *auto* *simp*: *tranc1-into-tranc12*)  
**done**

**lemma** *tranc1-rtranc1-rtranc1-rel*:  $R^{+++}\ a\ b \longleftrightarrow R^{**}\ a\ b$   
**by** (*simp* *add*: *rtranc1-unfold*)

**lemma** *tranc1-rtranc1-rtranc1*[*simp*]:  $R^{+++} = R^{**}$   
**by** (*fastforce* *simp*: *rtranc1-unfold*)

**lemma** *rtranc1-exists-last-with-prop*:  
**assumes**  $R\ x\ z$   
**and**  $R^{**}\ z\ z'$  **and**  $P\ x\ z$   
**shows**  $\exists y\ y'. R^{**}\ x\ y \wedge R\ y\ y' \wedge P\ y\ y' \wedge (\lambda a\ b. R\ a\ b \wedge \neg P\ a\ b)^{**}\ y'\ z'$   
**using** *assms*(2,1,3)  
**proof** (*induction* *arbitrary*: )  
**case** *base*  
**then show** *?case* **by** *auto*  
**next**  
**case** (*step*  $z'\ z''$ ) **note**  $z = \text{this}(2)$  **and**  $IH = \text{this}(3)[OF\ \text{this}(4-5)]$   
**show** *?case*  
**apply** (*cases*  $P\ z'\ z''$ )  
**apply** (*rule* *exI*[*of* - *z'*], *rule* *exI*[*of* - *z''*])  
**using** *z* *assms*(1) *step.hyps*(1) *step.premis*(2) **apply** *auto*[1]  
**using** *IH* *z* *rtranc1.rtranc1-into-rtranc1* **by** *fastforce*  
**qed**

**lemma** *rtranc1-and-rtranc1-left*:  $(\lambda a\ b. P\ a\ b \wedge Q\ a\ b)^{**}\ S\ T \Longrightarrow P^{**}\ S\ T$   
**by** (*induction* *rule*: *rtranc1-induct*) *auto*

## 1.2 Full Transitions

We define here properties to define properties after all possible transitions.

**abbreviation** *no-step* *step*  $S \equiv (\forall S'. \neg \text{step}\ S\ S')$

**definition** *full1* ::  $('a \Rightarrow 'a \Rightarrow \text{bool}) \Rightarrow 'a \Rightarrow 'a \Rightarrow \text{bool}$  **where**

$full1\ transf = (\lambda S\ S'.\ tranclp\ transf\ S\ S' \wedge (\forall S''.\ \neg\ transf\ S'\ S''))$

**definition**  $full:: ('a \Rightarrow 'a \Rightarrow bool) \Rightarrow 'a \Rightarrow 'a \Rightarrow bool$  **where**  
 $full\ transf = (\lambda S\ S'.\ rtranclp\ transf\ S\ S' \wedge (\forall S''.\ \neg\ transf\ S'\ S''))$

**lemma**  $rtranclp-full1I$ :

$R^{**}\ a\ b \Longrightarrow full1\ R\ b\ c \Longrightarrow full1\ R\ a\ c$

**unfolding**  $full1-def$  **by**  $auto$

**lemma**  $tranclp-full1I$ :

$R^{++}\ a\ b \Longrightarrow full1\ R\ b\ c \Longrightarrow full1\ R\ a\ c$

**unfolding**  $full1-def$  **by**  $auto$

**lemma**  $rtranclp-fullI$ :

$R^{**}\ a\ b \Longrightarrow full\ R\ b\ c \Longrightarrow full\ R\ a\ c$

**unfolding**  $full-def$  **by**  $auto$

**lemma**  $tranclp-full-full1I$ :

$R^{++}\ a\ b \Longrightarrow full\ R\ b\ c \Longrightarrow full1\ R\ a\ c$

**unfolding**  $full-def\ full1-def$  **by**  $auto$

**lemma**  $full-fullI$ :

$R\ a\ b \Longrightarrow full\ R\ b\ c \Longrightarrow full1\ R\ a\ c$

**unfolding**  $full-def\ full1-def$  **by**  $auto$

**lemma**  $full-unfold$ :

$full\ r\ S\ S' \longleftrightarrow ((S = S' \wedge no-step\ r\ S') \vee full1\ r\ S\ S')$

**unfolding**  $full-def\ full1-def$  **by**  $(auto\ simp\ add:\ rtranclp-unfold)$

**lemma**  $full1-is-full[intro]$ :  $full1\ R\ S\ T \Longrightarrow full\ R\ S\ T$

**by**  $(simp\ add:\ full-unfold)$

**lemma**  $not-full1-rtranclp-relation$ :  $\neg full1\ R^{**}\ a\ b$

**by**  $(meson\ full1-def\ rtranclp.rtrancl-refl)$

**lemma**  $not-full-rtranclp-relation$ :  $\neg full\ R^{**}\ a\ b$

**by**  $(meson\ full-fullI\ not-full1-rtranclp-relation\ rtranclp.rtrancl-refl)$

**lemma**  $full1-tranclp-relation-full$ :

$full1\ R^{++}\ a\ b \longleftrightarrow full1\ R\ a\ b$

**by**  $(metis\ converse-tranclpE\ full1-def\ reflclp-tranclp\ rtranclpD\ rtranclp-idemp\ rtranclp-reflclp\ tranclp.r-into-trancl\ tranclp-into-rtranclp)$

**lemma**  $full-tranclp-relation-full$ :

$full\ R^{++}\ a\ b \longleftrightarrow full\ R\ a\ b$

**by**  $(metis\ full-unfold\ full1-tranclp-relation-full\ tranclp.r-into-trancl\ tranclpD)$

**lemma**  $rtranclp-full1-eq-or-full1$ :

$(full1\ R)^{**}\ a\ b \longleftrightarrow (a = b \vee full1\ R\ a\ b)$

**proof** –

**have**  $\forall p\ a\ aa.\ \neg p^{**}\ (a::'a)\ aa \vee a = aa \vee (\exists ab.\ p^{**}\ a\ ab \wedge p\ ab\ aa)$

**by**  $(metis\ rtranclp.cases)$

**then obtain**  $aa:: ('a \Rightarrow 'a \Rightarrow bool) \Rightarrow 'a \Rightarrow 'a \Rightarrow 'a$  **where**

$f1:: \forall p\ a\ ab.\ \neg p^{**}\ a\ ab \vee a = ab \vee p^{**}\ a\ (aa\ p\ a\ ab) \wedge p\ (aa\ p\ a\ ab)\ ab$

**by**  $moura$

```

{ assume  $a \neq b$ 
  { assume  $\neg \text{full1 } R \ a \ b \wedge a \neq b$ 
    then have  $a \neq b \wedge a \neq b \wedge \neg \text{full1 } R \ (aa \ (\text{full1 } R) \ a \ b) \ b \vee \neg (\text{full1 } R)^{**} \ a \ b \wedge a \neq b$ 
      using  $f1$  by (metis (no-types) full1-def full1-tranclp-relation-full)
    then have ?thesis
      using  $f1$  by blast }
  then have ?thesis
    by auto }
then show ?thesis
  by fastforce
qed

```

```

lemma tranclp-full1-full1:
   $(\text{full1 } R)^{++} \ a \ b \longleftrightarrow \text{full1 } R \ a \ b$ 
  by (metis full1-def rtranclp-full1-eq-or-full1 tranclp-unfold-begin)

```

### 1.3 Well-Foundedness and Full Transitions

```

lemma wf-exists-normal-form:
  assumes  $wf:wf \ \{(x, y). \ R \ y \ x\}$ 
  shows  $\exists b. R^{**} \ a \ b \wedge \text{no-step } R \ b$ 
proof (rule ccontr)
  assume  $\neg ?thesis$ 
  then have  $H: \bigwedge b. \neg R^{**} \ a \ b \vee \neg \text{no-step } R \ b$ 
    by blast
  def  $F \equiv \text{rec-nat } a \ (\lambda i \ b. \ \text{SOME } c. \ R \ b \ c)$ 
  have [simp]:  $F \ 0 = a$ 
    unfolding  $F$ -def by auto
  have [simp]:  $\bigwedge i. F \ (\text{Suc } i) = (\text{SOME } b. \ R \ (F \ i) \ b)$ 
    using  $F$ -def by simp
  { fix  $i$ 
    have  $\forall j < i. \ R \ (F \ j) \ (F \ (\text{Suc } j))$ 
      proof (induction  $i$ )
        case 0
        then show ?case by auto
      next
        case  $(\text{Suc } i)$ 
        then have  $R^{**} \ a \ (F \ i)$ 
          by (induction  $i$ ) auto
        then have  $R \ (F \ i) \ (\text{SOME } b. \ R \ (F \ i) \ b)$ 
          using  $H$  by (simp add: someI-ex)
        then have  $\forall j < \text{Suc } i. \ R \ (F \ j) \ (F \ (\text{Suc } j))$ 
          using  $H \ \text{Suc}$  by (simp add: less-Suc-eq)
        then show ?case by fast
      qed
    }
  then have  $\forall j. \ R \ (F \ j) \ (F \ (\text{Suc } j))$  by blast
  then show False
    using  $wf$  unfolding  $wfP$ -def  $wf$ -iff-no-infinite-down-chain by blast
qed

```

```

lemma wf-exists-normal-form-full:
  assumes  $wf:wf \ \{(x, y). \ R \ y \ x\}$ 
  shows  $\exists b. \text{full } R \ a \ b$ 
  using wf-exists-normal-form[OF assms] unfolding full-def by blast

```



## 1.4 More Well-Foundedness

A little list of theorems that could be useful, but are hidden:

- link between  $wf$  and infinite chains:  $wf \text{ ?}r = (\nexists f. \forall i. (f (Suc\ i), f\ i) \in \text{?}r), \llbracket wf \text{ ?}r; \bigwedge k. (\text{?}f (Suc\ k), \text{?}f\ k) \notin \text{?}r \implies \text{?thesis} \rrbracket \implies \text{?thesis}$

**lemma** *wf-if-measure-in-wf*:

$wf\ R \implies (\bigwedge a\ b. (a, b) \in S \implies (\nu\ a, \nu\ b) \in R) \implies wf\ S$   
**by** (*metis in-inv-image wfE-min wfI-min wf-inv-image*)

**lemma** *wfP-if-measure*: **fixes**  $f :: 'a \Rightarrow nat$

**shows**  $(\bigwedge x\ y. P\ x \implies g\ x\ y \implies f\ y < f\ x) \implies wf\ \{(y, x). P\ x \wedge g\ x\ y\}$   
**apply**(*insert wf-measure[of f]*)  
**apply**(*simp only: measure-def inv-image-def less-than-def less-eq*)  
**apply**(*erule wf-subset*)  
**apply** *auto*  
**done**

**lemma** *wf-if-measure-f*:

**assumes**  $wf\ r$   
**shows**  $wf\ \{(b, a). (f\ b, f\ a) \in r\}$   
**using** *assms* **by** (*metis inv-image-def wf-inv-image*)

**lemma** *wf-wf-if-measure'*:

**assumes**  $wf\ r$  **and**  $H: (\bigwedge x\ y. P\ x \implies g\ x\ y \implies (f\ y, f\ x) \in r)$   
**shows**  $wf\ \{(y, x). P\ x \wedge g\ x\ y\}$

**proof** –

**have**  $wf\ \{(b, a). (f\ b, f\ a) \in r\}$  **using** *assms(1) wf-if-measure-f* **by** *auto*  
**then have**  $wf\ \{(b, a). P\ a \wedge g\ a\ b \wedge (f\ b, f\ a) \in r\}$   
**using** *wf-subset[of - {(b, a). P a ∧ g a b ∧ (f b, f a) ∈ r}]* **by** *auto*  
**moreover have**  $\{(b, a). P\ a \wedge g\ a\ b \wedge (f\ b, f\ a) \in r\} \subseteq \{(b, a). (f\ b, f\ a) \in r\}$  **by** *auto*  
**moreover have**  $\{(b, a). P\ a \wedge g\ a\ b \wedge (f\ b, f\ a) \in r\} = \{(b, a). P\ a \wedge g\ a\ b\}$  **using** *H* **by** *auto*  
**ultimately show** *?thesis* **using** *wf-subset* **by** *simp*

**qed**

**lemma** *wf-lex-less*:  $wf\ (\text{lex}\ \{(a, b). (a::nat) < b\})$

**proof** –

**have**  $m: \{(a, b). a < b\} = \text{measure}\ id$  **by** *auto*  
**show** *?thesis* **apply** (*rule wf-lex*) **unfolding** *m* **by** *auto*

**qed**

**lemma** *wfP-if-measure2*: **fixes**  $f :: 'a \Rightarrow nat$

**shows**  $(\bigwedge x\ y. P\ x\ y \implies g\ x\ y \implies f\ x < f\ y) \implies wf\ \{(x, y). P\ x\ y \wedge g\ x\ y\}$   
**apply**(*insert wf-measure[of f]*)  
**apply**(*simp only: measure-def inv-image-def less-than-def less-eq*)  
**apply**(*erule wf-subset*)  
**apply** *auto*  
**done**

**lemma** *lexord-on-finite-set-is-wf*:

**assumes**

*P-finite*:  $\bigwedge U. P\ U \longrightarrow U \in A$  **and**

*finite*: *finite* *A* **and**

*wf*:  $wf\ R$  **and**

```

  trans: trans R
  shows wf  $\{(T, S). (P S \wedge P T) \wedge (T, S) \in \text{lexord } R\}$ 
proof (rule wfP-if-measure2)
  fix T S
  assume P:  $P S \wedge P T$  and
  s-le-t:  $(T, S) \in \text{lexord } R$ 
  let ?f =  $\lambda S. \{U. (U, S) \in \text{lexord } R \wedge P U \wedge P S\}$ 
  have ?f T  $\subseteq$  ?f S
    using s-le-t P lexord-trans trans by auto
  moreover have  $T \in ?f S$ 
    using s-le-t P by auto
  moreover have  $T \notin ?f T$ 
    using s-le-t by (auto simp add: lexord-irreflexive local.wf)
  ultimately have  $\{U. (U, T) \in \text{lexord } R \wedge P U \wedge P T\} \subset \{U. (U, S) \in \text{lexord } R \wedge P U \wedge P S\}$ 
    by auto
  moreover have finite  $\{U. (U, S) \in \text{lexord } R \wedge P U \wedge P S\}$ 
    using finite by (metis (no-types, lifting) P-finite finite-subset mem-Collect-eq subsetI)
  ultimately show  $\text{card } (?f T) < \text{card } (?f S)$  by (simp add: psubset-card-mono)
qed

```

```

lemma wf-fst-wf-pair:
  assumes wf  $\{(M', M). R M' M\}$ 
  shows wf  $\{((M', N'), (M, N)). R M' M\}$ 
proof -
  have wf  $\{(M', M). R M' M\} < *lex* > \{\}$ 
    using assms by auto
  then show ?thesis
    by (rule wf-subset) auto
qed

```

```

lemma wf-snd-wf-pair:
  assumes wf  $\{(M', M). R M' M\}$ 
  shows wf  $\{((M', N'), (M, N)). R N' N\}$ 
proof -
  have wf: wf  $\{((M', N'), (M, N)). R M' M\}$ 
    using assms wf-fst-wf-pair by auto
  then have wf:  $\bigwedge P. (\forall x. (\forall y. (y, x) \in \{((M', N'), M, N). R M' M\} \longrightarrow P y) \longrightarrow P x) \implies \text{All } P$ 
    unfolding wf-def by auto
  show ?thesis
    unfolding wf-def
  proof (intro allI impI)
    fix P ::  $'c \times 'a \Rightarrow \text{bool}$  and x ::  $'c \times 'a$ 
    assume H:  $\forall x. (\forall y. (y, x) \in \{((M', N'), M, N). R N' y\} \longrightarrow P y) \longrightarrow P x$ 
    obtain a b where  $x = (a, b)$  by (cases x)
    have P:  $P x = (P \circ (\lambda(a, b). (b, a))) (b, a)$ 
      unfolding x by auto
    show P x
      using wf[of P o  $(\lambda(a, b). (b, a))$ ] apply rule
      using H apply simp
      unfolding P by blast
  qed
qed

```

```

lemma wf-if-measure-f-notation2:

```

```

assumes wf r
shows wf  $\{(b, h\ a)|b\ a.\ (f\ b, f\ (h\ a)) \in r\}$ 
apply (rule wf-subset)
using wf-if-measure-f[OF assms, of f] by auto

lemma wf-wf-if-measure'-notation2:
assumes wf r and H:  $(\bigwedge x\ y.\ P\ x \implies g\ x\ y \implies (f\ y, f\ (h\ x)) \in r)$ 
shows wf  $\{(y, h\ x)|\ y\ x.\ P\ x \wedge g\ x\ y\}$ 
proof -
  have wf  $\{(b, h\ a)|b\ a.\ (f\ b, f\ (h\ a)) \in r\}$  using assms(1) wf-if-measure-f-notation2 by auto
  then have wf  $\{(b, h\ a)|b\ a.\ P\ a \wedge g\ a\ b \wedge (f\ b, f\ (h\ a)) \in r\}$ 
    using wf-subset[of -  $\{(b, h\ a)|b\ a.\ P\ a \wedge g\ a\ b \wedge (f\ b, f\ (h\ a)) \in r\}$ ] by auto
  moreover have  $\{(b, h\ a)|b\ a.\ P\ a \wedge g\ a\ b \wedge (f\ b, f\ (h\ a)) \in r\}$ 
     $\subseteq \{(b, h\ a)|b\ a.\ (f\ b, f\ (h\ a)) \in r\}$  by auto
  moreover have  $\{(b, h\ a)|b\ a.\ P\ a \wedge g\ a\ b \wedge (f\ b, f\ (h\ a)) \in r\} = \{(b, h\ a)|b\ a.\ P\ a \wedge g\ a\ b\}$ 
    using H by auto
  ultimately show ?thesis using wf-subset by simp
qed

end
theory List-More
imports Main ../lib/Multiset-More
begin

```

Sledgehammer parameters

sledgehammer-params[debug]

## 2 Various Lemmas

Close to  $(\bigwedge n.\ \forall m < n.\ ?P\ m \implies ?P\ n) \implies ?P\ ?n$ , but with a separation between zero and non-zero, and case names.

**thm** nat-less-induct

**lemma** nat-less-induct-case[case-names 0 Suc]:

```

assumes
  P 0 and
   $\bigwedge n.\ (\forall m < Suc\ n.\ P\ m) \implies P\ (Suc\ n)$ 
shows P n
apply (induction rule: nat-less-induct)
by (rename-tac n, case-tac n) (auto intro: assms)

```

This is only proved in simple cases by auto. In assumptions, nothing happens, and  $?P$  (if  $?Q$  then  $?x$  else  $?y$ ) =  $(\neg (?Q \wedge \neg ?P\ ?x \vee \neg ?Q \wedge \neg ?P\ ?y))$  can blow up goals (because of other if expression).

**lemma** if-0-1-ge-0[simp]:

```

  0 < (if P then a else (0::nat))  $\longleftrightarrow$  P  $\wedge$  0 < a
by auto

```

Bounded function have not been defined in Isabelle.

**definition** bounded **where**

$bounded\ f \longleftrightarrow (\exists b.\ \forall n.\ f\ n \leq b)$

**abbreviation** unbounded ::  $('a \Rightarrow 'b::ord) \Rightarrow bool$  **where**

$unbounded\ f \equiv \neg bounded\ f$

```

lemma not-bounded-nat-exists-larger:
  fixes  $f :: \text{nat} \Rightarrow \text{nat}$ 
  assumes unbound: unbounded  $f$ 
  shows  $\exists n. f\ n > m \wedge n > n_0$ 
proof (rule ccontr)
  assume  $H: \neg ?thesis$ 
  have finite  $\{f\ n \mid n. n \leq n_0\}$ 
    by auto
  have  $\bigwedge n. f\ n \leq \text{Max} (\{f\ n \mid n. n \leq n_0\} \cup \{m\})$ 
    apply (case-tac  $n \leq n_0$ )
    apply (metis (mono-tags, lifting) Max-ge Un-insert-right  $\langle \text{finite } \{f\ n \mid n. n \leq n_0\} \rangle$ 
      finite-insert insertCI mem-Collect-eq sup-bot.right-neutral)
    by (metis (no-types, lifting)  $H$  Max-less-iff Un-insert-right  $\langle \text{finite } \{f\ n \mid n. n \leq n_0\} \rangle$ 
      finite-insert insertI1 insert-not-empty leI sup-bot.right-neutral)
  then show False
    using unbound unfolding bounded-def by auto
qed

```

```

lemma bounded-const-product:
  fixes  $k :: \text{nat}$  and  $f :: \text{nat} \Rightarrow \text{nat}$ 
  assumes  $k > 0$ 
  shows  $\text{bounded } f \longleftrightarrow \text{bounded } (\lambda i. k * f\ i)$ 
  unfolding bounded-def apply (rule iffI)
  using mult-le-mono2 apply blast
  by (meson assms le-less-trans less-or-eq-imp-le nat-mult-less-cancel-disj split-div-lemma)

```

This lemma is not used, but here to show that a property that can be expected from *bounded* holds.

```

lemma bounded-finite-linorder:
  fixes  $f :: 'a \Rightarrow 'a :: \{\text{finite}, \text{linorder}\}$ 
  shows bounded  $f$ 
proof –
  have  $\bigwedge x. f\ x \leq \text{Max } \{f\ x \mid x. \text{True}\}$ 
    by (metis (mono-tags) Max-ge finite mem-Collect-eq)
  then show ?thesis
    unfolding bounded-def by blast
qed

```

## 3 More List

### 3.1 *upt*

The simplification rules are not very handy, because  $[?i..<\text{Suc } ?j] = (\text{if } ?i \leq ?j \text{ then } [?i..<?j] @ [?j] \text{ else } [])$  leads to a case distinction, that we do not want if the condition is not in the context.

```

lemma upt-Suc-le-append:  $\neg i \leq j \implies [i..<\text{Suc } j] = []$ 
  by auto

```

```

lemmas upt-simps[simp] = upt-Suc-append upt-Suc-le-append

```

```

declare upt.simps(2)[simp del]

```

**lemma**

**assumes**  $i \leq n - m$

**shows**  $\text{take } i \ [m..<n] = [m..<m+i]$

**by** (*metis Nat.le-diff-conv2 add.commute assms diff-is-0-eq' linear take-upt upt-conv-Nil*)

The counterpart for this lemma when  $n - m < i$  is  $\text{length } ?xs \leq ?n \implies \text{take } ?n \ ?xs = ?xs$ . It is close to  $?i + ?m \leq ?n \implies \text{take } ?m \ [?i..<?n] = [?i..<?i + ?m]$ , but seems more general.

**lemma** *take-upt-bound-minus[simp]*:

**assumes**  $i \leq n - m$

**shows**  $\text{take } i \ [m..<n] = [m..<m+i]$

**using** *assms* **by** (*induction i*) *auto*

**lemma** *append-cons-eq-upt*:

**assumes**  $A @ B = [m..<n]$

**shows**  $A = [m..<m+\text{length } A]$  **and**  $B = [m + \text{length } A..<n]$

**proof** –

**have**  $\text{take } (\text{length } A) \ (A @ B) = A$  **by** *auto*

**moreover**

**have**  $\text{length } A \leq n - m$  **using** *assms* *linear calculation* **by** *fastforce*

**then have**  $\text{take } (\text{length } A) \ [m..<n] = [m..<m+\text{length } A]$  **by** *auto*

**ultimately show**  $A = [m..<m+\text{length } A]$  **using** *assms* **by** *auto*

**show**  $B = [m + \text{length } A..<n]$  **using** *assms* **by** (*metis append-eq-conv-conj drop-upt*)

**qed**

**lemma** *length-list-Suc-0*:

$\text{length } W = \text{Suc } 0 \longleftrightarrow (\exists L. W = [L])$

**apply** (*cases W*)

**apply** *simp*

**apply** (*rename-tac a W', case-tac W'*)

**apply** *auto*

**done**

**lemma** *length-list-2*:  $\text{length } S = 2 \longleftrightarrow (\exists a \ b. S = [a, b])$

**apply** (*cases S*)

**apply** *simp*

**apply** (*rename-tac a S'*)

**apply** (*case-tac S'*)

**by** *simp-all*

The converse of  $?A @ ?B = [?m..<?n] \implies ?A = [?m..<?m + \text{length } ?A]$

$?A @ ?B = [?m..<?n] \implies ?B = [?m + \text{length } ?A..<?n]$  does not hold, for example if  $B$  is empty and  $A$  is  $[0::'a]$ :

**lemma**  $A @ B = [m..<n] \longleftrightarrow A = [m..<m+\text{length } A] \wedge B = [m + \text{length } A..<n]$

**oops**

A more restrictive version holds:

**lemma**  $B \neq [] \implies A @ B = [m..<n] \longleftrightarrow A = [m..<m+\text{length } A] \wedge B = [m + \text{length } A..<n]$

(**is**  $?P \implies ?A = ?B$ )

**proof**

**assume**  $?A$  **then show**  $?B$  **by** (*auto simp add: append-cons-eq-upt*)

**next**

**assume**  $?P$  **and**  $?B$

**then show**  $?A$  **using** *append-eq-conv-conj* **by** *fastforce*

qed

**lemma** *append-cons-eq-upt-length-i:*

**assumes**  $A @ i \# B = [m..<n]$

**shows**  $A = [m..<i]$

**proof** –

**have**  $A = [m..<m + \text{length } A]$  **using** *assms append-cons-eq-upt* **by** *auto*

**have**  $(A @ i \# B) ! (\text{length } A) = i$  **by** *auto*

**moreover have**  $n - m = \text{length } (A @ i \# B)$

**using** *assms length-upt* **by** *presburger*

**then have**  $[m..<n] ! (\text{length } A) = m + \text{length } A$  **by** *simp*

**ultimately have**  $i = m + \text{length } A$  **using** *assms* **by** *auto*

**then show** *?thesis* **using**  $\langle A = [m..<m + \text{length } A] \rangle$  **by** *auto*

qed

**lemma** *append-cons-eq-upt-length:*

**assumes**  $A @ i \# B = [m..<n]$

**shows**  $\text{length } A = i - m$

**using** *assms*

**proof** (*induction A arbitrary: m*)

**case** *Nil*

**then show** *?case* **by** (*metis append-Nil diff-is-0-eq list.size(3) order-refl upt-eq-Cons-conv*)

**next**

**case** (*Cons a A*)

**then have**  $A @ i \# B = [m + 1..<n]$  **by** (*metis append-Cons upt-eq-Cons-conv*)

**then have**  $m < i$  **by** (*metis Cons.premis append-cons-eq-upt-length-i upt-eq-Cons-conv*)

**with** *Cons.IH[OF A]* **show** *?case* **by** *auto*

qed

**lemma** *append-cons-eq-upt-length-i-end:*

**assumes**  $A @ i \# B = [m..<n]$

**shows**  $B = [\text{Suc } i..<n]$

**proof** –

**have**  $B = [\text{Suc } m + \text{length } A..<n]$  **using** *assms append-cons-eq-upt[of A @ [i] B m n]* **by** *auto*

**have**  $(A @ i \# B) ! (\text{length } A) = i$  **by** *auto*

**moreover have**  $n - m = \text{length } (A @ i \# B)$

**using** *assms length-upt* **by** *auto*

**then have**  $[m..<n] ! (\text{length } A) = m + \text{length } A$  **by** *simp*

**ultimately have**  $i = m + \text{length } A$  **using** *assms* **by** *auto*

**then show** *?thesis* **using**  $\langle B = [\text{Suc } m + \text{length } A..<n] \rangle$  **by** *auto*

qed

**lemma** *Max-n-upt: Max (insert 0 {Suc 0..<n}) = n - Suc 0*

**proof** (*induct n*)

**case** *0*

**then show** *?case* **by** *simp*

**next**

**case** (*Suc n*) **note** *IH = this*

**have**  $i: \text{insert } 0 \{ \text{Suc } 0..<\text{Suc } n \} = \text{insert } 0 \{ \text{Suc } 0..<n \} \cup \{n\}$  **by** *auto*

**show** *?case* **using** *IH* **unfolding** *i* **by** *auto*

qed

**lemma** *upt-decomp-lt:*

**assumes**  $H: xs @ i \# ys @ j \# zs = [m..<n]$

**shows**  $i < j$

**proof** –

**have**  $xs$ :  $xs = [m \dots i]$  **and**  $ys$ :  $ys = [Suc\ i \dots j]$  **and**  $zs$ :  $zs = [Suc\ j \dots n]$   
**using**  $H$  **by** (*auto dest: append-cons-eq-upt-length-i append-cons-eq-upt-length-i-end*)  
**show** *?thesis*  
**by** (*metis append-cons-eq-upt-length-i-end assms lessI less-trans self-append-conv2*  
*upt-eq-Cons-conv upt-rec ys*)

**qed**

### 3.2 Lexicographic Ordering

**lemma** *lexn-Suc*:

$(x \# xs, y \# ys) \in \text{lexn } r \ (Suc\ n) \longleftrightarrow$   
 $(length\ xs = n \wedge length\ ys = n) \wedge ((x, y) \in r \vee (x = y \wedge (xs, ys) \in \text{lexn } r\ n))$   
**by** (*auto simp: map-prod-def image-iff lex-prod-def*)

**lemma** *lexn-n*:

$n > 0 \implies (x \# xs, y \# ys) \in \text{lexn } r\ n \longleftrightarrow$   
 $(length\ xs = n-1 \wedge length\ ys = n-1) \wedge ((x, y) \in r \vee (x = y \wedge (xs, ys) \in \text{lexn } r\ (n-1)))$   
**apply** (*cases n*)  
**apply** *simp*  
**by** (*auto simp: map-prod-def image-iff lex-prod-def*)

There is some subtle point in the proof here.  $1$  is converted to  $Suc\ 0$ , but  $2$  is not: meaning that  $1$  is automatically simplified by default using the default simplification rule  $\text{lexn } ?r\ 0 = \{\}$

$\text{lexn } ?r\ (Suc\ ?n) = \text{map-prod } (\lambda(x, xs). x \# xs) (\lambda(x, xs). x \# xs) \text{ ' } (?r <*\text{lex}*> \text{lexn } ?r\ ?n) \cap \{(xs, ys). length\ xs = Suc\ ?n \wedge length\ ys = Suc\ ?n\}$ . However, the latter needs additional simplification rule.

**lemma** *lexn2-conv*:

$([a, b], [c, d]) \in \text{lexn } r\ 2 \longleftrightarrow (a, c) \in r \vee (a = c \wedge (b, d) \in r)$   
**by** (*auto simp: lexn-n simp del: lexn.simps(2)*)

**lemma** *lexn3-conv*:

$([a, b, c], [a', b', c']) \in \text{lexn } r\ 3 \longleftrightarrow$   
 $(a, a') \in r \vee (a = a' \wedge (b, b') \in r) \vee (a = a' \wedge b = b' \wedge (c, c') \in r)$   
**by** (*auto simp: lexn-n simp del: lexn.simps(2)*)

### 3.3 Remove and Multiset equality

**lemma** *remove1-mset-single-add*:

$a \neq b \implies \text{remove1-mset } a\ (\{\#b\# \} + C) = \{\#b\# \} + \text{remove1-mset } a\ C$   
 $\text{remove1-mset } a\ (\{\#a\# \} + C) = C$   
**by** (*auto simp: multiset-eq-iff*)

This is the same as *remove1* under the assumptions of non-duplication inside a clause.

**fun** *remove1-cond* **where**

*remove1-cond*  $f\ [] = []$  |  
*remove1-cond*  $f\ (C' \# L) = (\text{if } f\ C' \text{ then } L \text{ else } C' \# \text{remove1-cond } f\ L)$

**lemma** *mset-map-mset-remove1-cond*:

$\text{mset } (\text{map } \text{mset } (\text{remove1-cond } (\lambda L. \text{mset } L = \text{mset } a)\ C)) =$   
 $\text{remove1-mset } (\text{mset } a)\ (\text{mset } (\text{map } \text{mset } C))$   
**by** (*induction C*) (*auto simp: ac-simps remove1-mset-single-add*)

**fun** *removeAll-cond* **where**

```

removeAll-cond f [] = [] |
removeAll-cond f (C' # L) =
  (if f C' then removeAll-cond f L else C' # removeAll-cond f L)

```

**lemma** *mset-map-mset-removeAll-cond*:  

$$\text{mset } (\text{map mset } (\text{removeAll-cond } (\lambda b. \text{mset } b = \text{mset } a) C))$$

$$= \text{removeAll-mset } (\text{mset } a) (\text{mset } (\text{map mset } C))$$
**by** (*induction C*) (*auto simp: ac-simps mset-less-eqI multiset-diff-union-assoc*)

Take from `../lib/Multiset_More.thy`, but named:

**abbreviation** *union-mset-list* **where**  

$$\text{union-mset-list } xs \ ys \equiv \text{case-prod append } (\text{fold } (\lambda x \ (ys, zs). (\text{remove1 } x \ ys, x \# \ zs)) \ xs \ (ys, []))$$

**lemma** *union-mset-list*:  

$$\text{mset } xs \# \cup \text{mset } ys = \text{mset } (\text{union-mset-list } xs \ ys)$$
**proof** –  
**have**  $\bigwedge zs. \text{mset } (\text{case-prod append } (\text{fold } (\lambda x \ (ys, zs). (\text{remove1 } x \ ys, x \# \ zs)) \ xs \ (ys, zs))) =$   

$$(\text{mset } xs \# \cup \text{mset } ys) + \text{mset } zs$$
**by** (*induct xs arbitrary: ys*) (*simp-all add: multiset-eq-iff*)  
**then show** *?thesis* **by** *simp*  
**qed**

**end**  
**theory** *Prop-Logic*

**imports** *Main*

**begin**

## 4 Logics

In this section we define the syntax of the formula and an abstraction over it to have simpler proofs. After that we define some properties like subformula and rewriting.

### 4.1 Definition and abstraction

The propositional logic is defined inductively. The type parameter is the type of the variables.

**datatype** *'v propo* =  

$$FT \mid FF \mid FVar \ 'v \mid FNot \ 'v \ propo \mid FAnd \ 'v \ propo \ 'v \ propo \mid FOr \ 'v \ propo \ 'v \ propo$$

$$\mid FImp \ 'v \ propo \ 'v \ propo \mid FEq \ 'v \ propo \ 'v \ propo$$

We do not define any notation for the formula, to distinguish properly between the formulas and Isabelle's logic.

To ease the proofs, we will write the the formula on a homogeneous manner, namely a connecting argument and a list of arguments.

**datatype** *'v connective* = *CT* | *CF* | *CVar 'v* | *CNot* | *CAnd* | *COr* | *CImp* | *CEq*

**abbreviation** *nullary-connective*  $\equiv \{CF\} \cup \{CT\} \cup \{CVar \ x \mid x. \text{True}\}$

**definition** *binary-connectives*  $\equiv \{CAnd, COr, CImp, CEq\}$

We define our own induction principal: instead of distinguishing every constructor, we group them by arity.



```

lemma propo-induct-arity[case-names nullary unary binary]:
  fixes  $\varphi \psi :: 'v \text{ propo}$ 
  assumes nullary:  $(\bigwedge \varphi x. \varphi = FF \vee \varphi = FT \vee \varphi = FVar\ x \implies P\ \varphi)$ 
  and unary:  $(\bigwedge \psi. P\ \psi \implies P\ (FNot\ \psi))$ 
  and binary:  $(\bigwedge \varphi \psi1\ \psi2. P\ \psi1 \implies P\ \psi2 \implies \varphi = FAnd\ \psi1\ \psi2 \vee \varphi = FOr\ \psi1\ \psi2 \vee \varphi = FImp\ \psi1\ \psi2 \vee \varphi = FEq\ \psi1\ \psi2 \implies P\ \varphi)$ 
  shows  $P\ \psi$ 
  apply (induct rule: propo.induct)
  using assms by metis+

```

The function *conn* is the interpretation of our representation (connective and list of arguments). We define any thing that has no sense to be false

```

fun conn :: 'v connective  $\Rightarrow$  'v propo list  $\Rightarrow$  'v propo where
  conn CT [] = FT |
  conn CF [] = FF |
  conn (CVar v) [] = FVar v |
  conn CNot [ $\varphi$ ] = FNot  $\varphi$  |
  conn CAnd ( $\varphi \# [\psi]$ ) = FAnd  $\varphi \psi$  |
  conn COr ( $\varphi \# [\psi]$ ) = FOr  $\varphi \psi$  |
  conn CImp ( $\varphi \# [\psi]$ ) = FImp  $\varphi \psi$  |
  conn CEq ( $\varphi \# [\psi]$ ) = FEq  $\varphi \psi$  |
  conn - - = FF

```

We will often use case distinction, based on the arity of the 'v connective, thus we define our own splitting principle.

```

lemma connective-cases-arity[case-names nullary binary unary]:
  assumes nullary:  $\bigwedge x. c = CT \vee c = CF \vee c = CVar\ x \implies P$ 
  and binary:  $c \in \text{binary-connectives} \implies P$ 
  and unary:  $c = CNot \implies P$ 
  shows  $P$ 
  using assms by (cases c) (auto simp: binary-connectives-def)

```

```

lemma connective-cases-arity-2[case-names nullary unary binary]:
  assumes nullary:  $c \in \text{nullary-connective} \implies P$ 
  and unary:  $c = CNot \implies P$ 
  and binary:  $c \in \text{binary-connectives} \implies P$ 
  shows  $P$ 
  using assms by (cases c, auto simp add: binary-connectives-def)

```

Our previous definition is not necessary correct (connective and list of arguments) , so we define an inductive predicate.

```

inductive wf-conn :: 'v connective  $\Rightarrow$  'v propo list  $\Rightarrow$  bool for c :: 'v connective where
  wf-conn-nullary[simp]:  $(c = CT \vee c = CF \vee c = CVar\ v) \implies \text{wf-conn}\ c\ []$  |
  wf-conn-unary[simp]:  $c = CNot \implies \text{wf-conn}\ c\ [\psi]$  |
  wf-conn-binary[simp]:  $c \in \text{binary-connectives} \implies \text{wf-conn}\ c\ (\psi \# \psi' \# [])$ 
thm wf-conn.induct

```

```

lemma wf-conn-induct[consumes 1, case-names CT CF CVar CNot COr CAnd CImp CEq]:
  assumes wf-conn c x and
     $(\bigwedge v. c = CT \implies P\ [])$  and
     $(\bigwedge v. c = CF \implies P\ [])$  and
     $(\bigwedge v. c = CVar\ v \implies P\ [])$  and
     $(\bigwedge \psi. c = CNot \implies P\ [\psi])$  and
     $(\bigwedge \psi\ \psi'. c = COr \implies P\ [\psi, \psi'])$  and

```

```

( $\wedge \psi \ \psi'. \ c = CAnd \implies P \ [\psi, \ \psi']$ ) and
( $\wedge \psi \ \psi'. \ c = CImp \implies P \ [\psi, \ \psi']$ ) and
( $\wedge \psi \ \psi'. \ c = CEq \implies P \ [\psi, \ \psi']$ )
shows  $P \ x$ 
using assms by induction (auto simp: binary-connectives-def)

```

## 4.2 properties of the abstraction

First we can define simplification rules.

```

lemma wf-conn-conn[simp]:
  wf-conn CT l  $\implies$  conn CT l = FT
  wf-conn CF l  $\implies$  conn CF l = FF
  wf-conn (CVar x) l  $\implies$  conn (CVar x) l = FVar x
apply (simp-all add: wf-conn.simps)
unfolding binary-connectives-def by simp-all

```

```

lemma wf-conn-list-decomp[simp]:
  wf-conn CT l  $\longleftrightarrow$  l = []
  wf-conn CF l  $\longleftrightarrow$  l = []
  wf-conn (CVar x) l  $\longleftrightarrow$  l = []
  wf-conn CNot ( $\xi \ @ \ \varphi \ \# \ \xi'$ )  $\longleftrightarrow$   $\xi = [] \wedge \xi' = []$ 
apply (simp-all add: wf-conn.simps)
unfolding binary-connectives-def apply simp-all
by (metis append-Nil append-is-Nil-conv list.distinct(1) list.sel(3) tl-append2)

```

```

lemma wf-conn-list:
  wf-conn c l  $\implies$  conn c l = FT  $\longleftrightarrow$  ( $c = CT \wedge l = []$ )
  wf-conn c l  $\implies$  conn c l = FF  $\longleftrightarrow$  ( $c = CF \wedge l = []$ )
  wf-conn c l  $\implies$  conn c l = FVar x  $\longleftrightarrow$  ( $c = CVar \ x \wedge l = []$ )
  wf-conn c l  $\implies$  conn c l = FAnd a b  $\longleftrightarrow$  ( $c = CAnd \wedge l = a \ \# \ b \ \# \ []$ )
  wf-conn c l  $\implies$  conn c l = FOr a b  $\longleftrightarrow$  ( $c = COr \wedge l = a \ \# \ b \ \# \ []$ )
  wf-conn c l  $\implies$  conn c l = FEq a b  $\longleftrightarrow$  ( $c = CEq \wedge l = a \ \# \ b \ \# \ []$ )
  wf-conn c l  $\implies$  conn c l = FImp a b  $\longleftrightarrow$  ( $c = CImp \wedge l = a \ \# \ b \ \# \ []$ )
  wf-conn c l  $\implies$  conn c l = FNot a  $\longleftrightarrow$  ( $c = CNot \wedge l = a \ \# \ []$ )
apply (induct l rule: wf-conn.induct)
unfolding binary-connectives-def by auto

```

In the binary connective cases, we will often decompose the list of arguments (of length 2) into two elements.

```

lemma list-length2-decomp:  $length \ l = 2 \implies (\exists \ a \ b. \ l = a \ \# \ b \ \# \ [])$ 
apply (induct l, auto)
by (rename-tac l, case-tac l, auto)

```

*wf-conn* for binary operators means that there are two arguments.

```

lemma wf-conn-bin-list-length:
  fixes  $l :: 'v \ \text{propo} \ \text{list}$ 
  assumes conn:  $c \in \text{binary-connectives}$ 
  shows  $length \ l = 2 \longleftrightarrow wf-conn \ c \ l$ 
proof
  assume  $length \ l = 2$ 
  then show  $wf-conn \ c \ l$  using wf-conn-binary list-length2-decomp using conn by metis
next

```

```

assume wf-conn c l
then show length l = 2 (is ?P l)
  proof (cases rule: wf-conn.induct)
    case wf-conn-nullary
    then show ?P [] using conn binary-connectives-def
      using connective.distinct(11) connective.distinct(13) connective.distinct(9) by blast
    next
    fix ψ :: 'v propo
    case wf-conn-unary
    then show ?P [ψ] using conn binary-connectives-def
      using connective.distinct by blast
    next
    fix ψ ψ' :: 'v propo
    show ?P [ψ, ψ'] by auto
  qed
qed

lemma wf-conn-not-list-length[iff]:
  fixes l :: 'v propo list
  shows wf-conn CNot l  $\longleftrightarrow$  length l = 1
  apply auto
  apply (metis append-Nil connective.distinct(5,17,27) length-Cons list.size(3) wf-conn.simps
    wf-conn-list-decomp(4))
  by (simp add: length-Suc-conv wf-conn.simps)

```

Decomposing the Not into an element is moreover very useful.

```

lemma wf-conn-Not-decomp:
  fixes l :: 'v propo list and a :: 'v
  assumes corr: wf-conn CNot l
  shows  $\exists$  a. l = [a]
  by (metis (no-types, lifting) One-nat-def Suc-length-conv corr length-0-conv
    wf-conn-not-list-length)

```

The *wf-conn* remains correct if the length of list does not change. This lemma is very useful when we do one rewriting step

```

lemma wf-conn-no-arity-change:
  length l = length l'  $\implies$  wf-conn c l  $\longleftrightarrow$  wf-conn c l'
proof -
  {
    fix l l'
    have length l = length l'  $\implies$  wf-conn c l  $\implies$  wf-conn c l'
    apply (cases c l rule: wf-conn.induct, auto)
    by (metis wf-conn-bin-list-length)
  }
  then show length l = length l'  $\implies$  wf-conn c l = wf-conn c l' by metis
qed

```

```

lemma wf-conn-no-arity-change-helper:
  length (ξ @ φ # ξ') = length (ξ @ φ' # ξ')
  by auto

```

The injectivity of *conn* is useful to prove equality of the connectives and the lists.

```

lemma conn-inj-not:
  assumes correct: wf-conn c l
  and conn: conn c l = FNot ψ

```

```

shows  $c = CNot$  and  $l = [\psi]$ 
apply (cases c l rule: wf-conn.cases)
using correct conn unfolding binary-connectives-def apply auto
apply (cases c l rule: wf-conn.cases)
using correct conn unfolding binary-connectives-def by auto

lemma conn-inj:
  fixes c ca :: 'v connective and l  $\psi$ s :: 'v propo list
  assumes corr: wf-conn ca l
  and corr': wf-conn c  $\psi$ s
  and eq: conn ca l = conn c  $\psi$ s
  shows  $ca = c \wedge \psi s = l$ 
  using corr
proof (cases ca l rule: wf-conn.cases)
  case (wf-conn-nullary v)
  then show  $ca = c \wedge \psi s = l$  using assms
    by (metis conn.simps(1) conn.simps(2) conn.simps(3) wf-conn-list(1-3))
next
  case (wf-conn-unary  $\psi'$ )
  then have *: FNot  $\psi' = conn\ c\ \psi s$  using conn-inj-not eq assms by auto
  then have  $c = ca$  by (metis conn-inj-not(1) corr' wf-conn-unary(2))
  moreover have  $\psi s = l$  using * conn-inj-not(2) corr' wf-conn-unary(1) by force
  ultimately show  $ca = c \wedge \psi s = l$  by auto
next
  case (wf-conn-binary  $\psi' \psi''$ )
  then show  $ca = c \wedge \psi s = l$ 
    using eq corr' unfolding binary-connectives-def apply (cases ca, auto simp add: wf-conn-list)
    using wf-conn-list(4-7) corr' by metis+
qed

```

### 4.3 Subformulas and properties

A characterization using sub-formulas is interesting for rewriting: we will define our relation on the sub-term level, and then lift the rewriting on the term-level. So the rewriting takes place on a subformula.

**inductive** subformula :: 'v propo  $\Rightarrow$  'v propo  $\Rightarrow$  bool (infix  $\preceq$  45) for  $\varphi$  where  
 subformula-refl[simp]:  $\varphi \preceq \varphi$  |  
 subformula-into-subformula:  $\psi \in set\ l \implies wf\text{-}conn\ c\ l \implies \varphi \preceq \psi \implies \varphi \preceq conn\ c\ l$

On the *subformula-into-subformula*, we can see why we use our *conn* representation: one case is enough to express the subformulas property instead of listing all the cases.

This is an example of a property related to subformulas.

```

lemma subformula-in-subformula-not:
shows b: FNot  $\varphi \preceq \psi \implies \varphi \preceq \psi$ 
  apply (induct rule: subformula.induct)
  using subformula-into-subformula wf-conn-unary subformula-refl list.set-intros(1) subformula-refl
  by (fastforce intro: subformula-into-subformula)+

```

```

lemma subformula-in-binary-conn:
  assumes conn:  $c \in binary\text{-}connectives$ 
  shows  $f \preceq conn\ c\ [f, g]$ 
  and  $g \preceq conn\ c\ [f, g]$ 
proof -

```

```

have a: wf-conn c (f# [g]) using conn wf-conn-binary binary-connectives-def by auto
moreover have b: f  $\preceq$  f using subformula-refl by auto
ultimately show f  $\preceq$  conn c [f, g]
  by (metis append-Nil in-set-conv-decomp subformula-into-subformula)
next
have a: wf-conn c ([f] @ [g]) using conn wf-conn-binary binary-connectives-def by auto
moreover have b: g  $\preceq$  g using subformula-refl by auto
ultimately show g  $\preceq$  conn c [f, g] using subformula-into-subformula by force
qed

```

```

lemma subformula-trans:
 $\psi \preceq \psi' \implies \varphi \preceq \psi \implies \varphi \preceq \psi'$ 
  apply (induct  $\psi'$  rule: subformula.inducts)
  by (auto simp: subformula-into-subformula)

```

```

lemma subformula-leaf:
  fixes  $\varphi \psi :: 'v \text{ propo}$ 
  assumes incl:  $\varphi \preceq \psi$ 
  and simple:  $\psi = FT \vee \psi = FF \vee \psi = FVar x$ 
  shows  $\varphi = \psi$ 
  using incl simple
  by (induct rule: subformula.induct, auto simp: wf-conn-list)

```

```

lemma subformula-not-incl-eq:
  assumes  $\varphi \preceq \text{conn } c \ l$ 
  and wf-conn c l
  and  $\forall \psi. \psi \in \text{set } l \longrightarrow \neg \varphi \preceq \psi$ 
  shows  $\varphi = \text{conn } c \ l$ 
  using assms apply (induction conn c l rule: subformula.induct, auto)
  using conn-inj by blast

```

```

lemma wf-subformula-conn-cases:
 $\text{wf-conn } c \ l \implies \varphi \preceq \text{conn } c \ l \longleftrightarrow (\varphi = \text{conn } c \ l \vee (\exists \psi. \psi \in \text{set } l \wedge \varphi \preceq \psi))$ 
  apply standard
  using subformula-not-incl-eq apply metis
  by (auto simp add: subformula-into-subformula)

```

```

lemma subformula-decomp-explicit[simp]:
 $\varphi \preceq FAnd \ \psi \ \psi' \longleftrightarrow (\varphi = FAnd \ \psi \ \psi' \vee \varphi \preceq \psi \vee \varphi \preceq \psi')$  (is ?P FAnd)
 $\varphi \preceq FOr \ \psi \ \psi' \longleftrightarrow (\varphi = FOr \ \psi \ \psi' \vee \varphi \preceq \psi \vee \varphi \preceq \psi')$ 
 $\varphi \preceq FEq \ \psi \ \psi' \longleftrightarrow (\varphi = FEq \ \psi \ \psi' \vee \varphi \preceq \psi \vee \varphi \preceq \psi')$ 
 $\varphi \preceq FImp \ \psi \ \psi' \longleftrightarrow (\varphi = FImp \ \psi \ \psi' \vee \varphi \preceq \psi \vee \varphi \preceq \psi')$ 

```

```

proof -
  have wf-conn CAnd [ψ, ψ'] by (simp add: binary-connectives-def)
  then have  $\varphi \preceq \text{conn } CAnd \ [\psi, \psi'] \longleftrightarrow$ 
    ( $\varphi = \text{conn } CAnd \ [\psi, \psi'] \vee (\exists \psi''. \psi'' \in \text{set } [\psi, \psi'] \wedge \varphi \preceq \psi'')$ )
    using wf-subformula-conn-cases by metis
  then show ?P FAnd by auto
next
  have wf-conn COr [ψ, ψ'] by (simp add: binary-connectives-def)
  then have  $\varphi \preceq \text{conn } COr \ [\psi, \psi'] \longleftrightarrow$ 
    ( $\varphi = \text{conn } COr \ [\psi, \psi'] \vee (\exists \psi''. \psi'' \in \text{set } [\psi, \psi'] \wedge \varphi \preceq \psi'')$ )
    using wf-subformula-conn-cases by metis
  then show ?P FOr by auto
next

```

```

have wf-conn CEq [ $\psi$ ,  $\psi'$ ] by (simp add: binary-connectives-def)
then have  $\varphi \preceq \text{conn CEq } [\psi, \psi'] \longleftrightarrow$ 
  ( $\varphi = \text{conn CEq } [\psi, \psi'] \vee (\exists \psi''. \psi'' \in \text{set } [\psi, \psi'] \wedge \varphi \preceq \psi'')$ )
  using wf-subformula-conn-cases by metis
then show ?P FEq by auto
next
have wf-conn CImp [ $\psi$ ,  $\psi'$ ] by (simp add: binary-connectives-def)
then have  $\varphi \preceq \text{conn CImp } [\psi, \psi'] \longleftrightarrow$ 
  ( $\varphi = \text{conn CImp } [\psi, \psi'] \vee (\exists \psi''. \psi'' \in \text{set } [\psi, \psi'] \wedge \varphi \preceq \psi'')$ )
  using wf-subformula-conn-cases by metis
then show ?P FImp by auto
qed

```

```

lemma wf-conn-helper-facts[iff]:
  wf-conn CNot [ $\varphi$ ]
  wf-conn CT []
  wf-conn CF []
  wf-conn (CVar  $x$ ) []
  wf-conn CAnd [ $\varphi$ ,  $\psi$ ]
  wf-conn COr [ $\varphi$ ,  $\psi$ ]
  wf-conn CImp [ $\varphi$ ,  $\psi$ ]
  wf-conn CEq [ $\varphi$ ,  $\psi$ ]
  using wf-conn.intros unfolding binary-connectives-def by fastforce+

```

```

lemma exists-c-conn:  $\exists c l. \varphi = \text{conn } c l \wedge \text{wf-conn } c l$ 
by (cases  $\varphi$ ) force+

```

```

lemma subformula-conn-decomp[simp]:
  assumes wf: wf-conn  $c l$ 
  shows  $\varphi \preceq \text{conn } c l \longleftrightarrow (\varphi = \text{conn } c l \vee (\exists \psi \in \text{set } l. \varphi \preceq \psi))$  (is ?A  $\longleftrightarrow$  ?B)
proof (rule iffI)
  {
    fix  $\xi$ 
    have  $\varphi \preceq \xi \implies \xi = \text{conn } c l \implies \text{wf-conn } c l \implies \forall x::'a \text{ propo} \in \text{set } l. \neg \varphi \preceq x \implies \varphi = \text{conn } c l$ 
    apply (induct rule: subformula.induct)
    apply simp
    using conn-inj by blast
  }
  moreover assume ?A
  ultimately show ?B using wf by metis
next
  assume ?B
  then show  $\varphi \preceq \text{conn } c l$  using wf wf-subformula-conn-cases by blast
qed

```

```

lemma subformula-leaf-explicit[simp]:
   $\varphi \preceq FT \longleftrightarrow \varphi = FT$ 
   $\varphi \preceq FF \longleftrightarrow \varphi = FF$ 
   $\varphi \preceq FVar x \longleftrightarrow \varphi = FVar x$ 
  apply auto
  using subformula-leaf by metis +

```

The variables inside the formula gives precisely the variables that are needed for the formula.

```

primrec vars-of-prop:: ' $v$  propo  $\Rightarrow$  ' $v$  set where
vars-of-prop FT = {} |

```

$\text{vars-of-prop } FF = \{\}$  |  
 $\text{vars-of-prop } (FVar\ x) = \{x\}$  |  
 $\text{vars-of-prop } (FNot\ \varphi) = \text{vars-of-prop } \varphi$  |  
 $\text{vars-of-prop } (FAnd\ \varphi\ \psi) = \text{vars-of-prop } \varphi \cup \text{vars-of-prop } \psi$  |  
 $\text{vars-of-prop } (FOr\ \varphi\ \psi) = \text{vars-of-prop } \varphi \cup \text{vars-of-prop } \psi$  |  
 $\text{vars-of-prop } (FImp\ \varphi\ \psi) = \text{vars-of-prop } \varphi \cup \text{vars-of-prop } \psi$  |  
 $\text{vars-of-prop } (FEq\ \varphi\ \psi) = \text{vars-of-prop } \varphi \cup \text{vars-of-prop } \psi$

**lemma** *vars-of-prop-incl-conn*:

**fixes**  $\xi\ \xi' :: 'v\ \text{propo list and } \psi :: 'v\ \text{propo and } c :: 'v\ \text{connective}$   
**assumes** *corr*:  $\text{wf-conn } c\ l$  **and** *incl*:  $\psi \in \text{set } l$   
**shows**  $\text{vars-of-prop } \psi \subseteq \text{vars-of-prop } (\text{conn } c\ l)$

**proof** (*cases c rule: connective-cases-arity-2*)

**case** *nullary*

**then have** *False* **using** *corr incl* **by** *auto*

**then show**  $\text{vars-of-prop } \psi \subseteq \text{vars-of-prop } (\text{conn } c\ l)$  **by** *blast*

**next**

**case** *binary note c = this*

**then obtain** *a b* **where**  $ab: l = [a, b]$

**using** *wf-conn-bin-list-length list-length2-decomp corr* **by** *metis*

**then have**  $\psi = a \vee \psi = b$  **using** *incl* **by** *auto*

**then show**  $\text{vars-of-prop } \psi \subseteq \text{vars-of-prop } (\text{conn } c\ l)$

**using** *ab c unfolding binary-connectives-def* **by** *auto*

**next**

**case** *unary note c = this*

**fix**  $\varphi :: 'v\ \text{propo}$

**have**  $l = [\psi]$  **using** *corr c incl split-list* **by** *force*

**then show**  $\text{vars-of-prop } \psi \subseteq \text{vars-of-prop } (\text{conn } c\ l)$  **using** *c* **by** *auto*

**qed**

The set of variables is compatible with the subformula order.

**lemma** *subformula-vars-of-prop*:

$\varphi \preceq \psi \implies \text{vars-of-prop } \varphi \subseteq \text{vars-of-prop } \psi$

**apply** (*induct rule: subformula.induct*)

**apply** *simp*

**using** *vars-of-prop-incl-conn* **by** *blast*

## 4.4 Positions

Instead of 1 or 2 we use *L* or *R*

**datatype** *sign* = *L* | *R*

We use *nil* instead of  $\varepsilon$ .

**fun** *pos* ::  $'v\ \text{propo} \Rightarrow \text{sign list set}$  **where**

*pos* *FF* =  $\{\{\}\}$  |

*pos* *FT* =  $\{\{\}\}$  |

*pos* (*FVar* *x*) =  $\{\{\}\}$  |

*pos* (*FAnd*  $\varphi\ \psi$ ) =  $\{\{\}\} \cup \{L \# p \mid p. p \in \text{pos } \varphi\} \cup \{R \# p \mid p. p \in \text{pos } \psi\}$  |

*pos* (*FOr*  $\varphi\ \psi$ ) =  $\{\{\}\} \cup \{L \# p \mid p. p \in \text{pos } \varphi\} \cup \{R \# p \mid p. p \in \text{pos } \psi\}$  |

*pos* (*FEq*  $\varphi\ \psi$ ) =  $\{\{\}\} \cup \{L \# p \mid p. p \in \text{pos } \varphi\} \cup \{R \# p \mid p. p \in \text{pos } \psi\}$  |

*pos* (*FImp*  $\varphi\ \psi$ ) =  $\{\{\}\} \cup \{L \# p \mid p. p \in \text{pos } \varphi\} \cup \{R \# p \mid p. p \in \text{pos } \psi\}$  |

*pos* (*FNot*  $\varphi$ ) =  $\{\{\}\} \cup \{L \# p \mid p. p \in \text{pos } \varphi\}$

**lemma** *finite-pos*: *finite* (*pos*  $\varphi$ )

**by** (*induct*  $\varphi$ , *auto*)

```

lemma finite-inj-comp-set:
  fixes  $s :: 'v \text{ set}$ 
  assumes finite: finite  $s$ 
  and inj: inj  $f$ 
  shows  $\text{card } (\{f \ p \mid p. p \in s\}) = \text{card } s$ 
  using finite
proof (induct  $s$  rule: finite-induct)
  show  $\text{card } \{f \ p \mid p. p \in \{\}\} = \text{card } \{\}$  by auto
next
  fix  $x :: 'v$  and  $s :: 'v \text{ set}$ 
  assume f: finite  $s$  and notin:  $x \notin s$ 
  and IH:  $\text{card } \{f \ p \mid p. p \in s\} = \text{card } s$ 
  have f': finite  $\{f \ p \mid p. p \in \text{insert } x \ s\}$  using f by auto
  have notin':  $f \ x \notin \{f \ p \mid p. p \in s\}$  using notin inj injD by fastforce
  have  $\{f \ p \mid p. p \in \text{insert } x \ s\} = \text{insert } (f \ x) \ \{f \ p \mid p. p \in s\}$  by auto
  then have  $\text{card } \{f \ p \mid p. p \in \text{insert } x \ s\} = 1 + \text{card } \{f \ p \mid p. p \in s\}$ 
    using finite card-insert-disjoint f' notin' by auto
  moreover have  $\dots = \text{card } (\text{insert } x \ s)$  using notin f IH by auto
  finally show  $\text{card } \{f \ p \mid p. p \in \text{insert } x \ s\} = \text{card } (\text{insert } x \ s)$  .
qed

```

```

lemma cons-inject:
  inj (op  $\#$   $s$ )
  by (meson injI list.inject)

```

```

lemma finite-insert-nil-cons:
  finite  $s \implies \text{card } (\text{insert } [] \ \{L \ \# \ p \mid p. p \in s\}) = 1 + \text{card } \{L \ \# \ p \mid p. p \in s\}$ 
  using card-insert-disjoint by auto

```

```

lemma cord-not[simp]:
   $\text{card } (\text{pos } (FNot \ \varphi)) = 1 + \text{card } (\text{pos } \varphi)$ 
by (simp add: cons-inject finite-inj-comp-set finite-pos)

```

```

lemma card-seperate:
  assumes finite  $s1$  and finite  $s2$ 
  shows  $\text{card } (\{L \ \# \ p \mid p. p \in s1\} \cup \{R \ \# \ p \mid p. p \in s2\}) = \text{card } (\{L \ \# \ p \mid p. p \in s1\})$ 
     $+ \text{card } (\{R \ \# \ p \mid p. p \in s2\})$  (is  $\text{card } (?L \cup ?R) = \text{card } ?L + \text{card } ?R$ )
proof –
  have finite  $?L$  using assms by auto
  moreover have finite  $?R$  using assms by auto
  moreover have  $?L \cap ?R = \{\}$  by blast
  ultimately show thesis using assms card-Un-disjoint by blast
qed

```

```

definition prop-size where prop-size  $\varphi = \text{card } (\text{pos } \varphi)$ 

```

```

lemma prop-size-vars-of-prop:
  fixes  $\varphi :: 'v \text{ propo}$ 
  shows  $\text{card } (\text{vars-of-prop } \varphi) \leq \text{prop-size } \varphi$ 

  unfolding prop-size-def apply (induct  $\varphi$ , auto simp add: cons-inject finite-inj-comp-set finite-pos)
proof –
  fix  $\varphi1 \ \varphi2 :: 'v \text{ propo}$ 

```



```

assume IH1:  $\text{card } (\text{vars-of-prop } \varphi 1) \leq \text{card } (\text{pos } \varphi 1)$ 
and IH2:  $\text{card } (\text{vars-of-prop } \varphi 2) \leq \text{card } (\text{pos } \varphi 2)$ 
let ?L = {L # p | p. p ∈ pos  $\varphi 1$ }
let ?R = {R # p | p. p ∈ pos  $\varphi 2$ }
have  $\text{card } (?L \cup ?R) = \text{card } ?L + \text{card } ?R$ 
  using card-seperate finite-pos by blast
moreover have ... =  $\text{card } (\text{pos } \varphi 1) + \text{card } (\text{pos } \varphi 2)$ 
  by (simp add: cons-inject finite-inj-comp-set finite-pos)
moreover have ... ≥  $\text{card } (\text{vars-of-prop } \varphi 1) + \text{card } (\text{vars-of-prop } \varphi 2)$  using IH1 IH2 by arith
then have ... ≥  $\text{card } (\text{vars-of-prop } \varphi 1 \cup \text{vars-of-prop } \varphi 2)$  using card-Un-le le-trans by blast
ultimately
  show  $\text{card } (\text{vars-of-prop } \varphi 1 \cup \text{vars-of-prop } \varphi 2) \leq \text{Suc } (\text{card } (?L \cup ?R))$ 
     $\text{card } (\text{vars-of-prop } \varphi 1 \cup \text{vars-of-prop } \varphi 2) \leq \text{Suc } (\text{card } (?L \cup ?R))$ 
     $\text{card } (\text{vars-of-prop } \varphi 1 \cup \text{vars-of-prop } \varphi 2) \leq \text{Suc } (\text{card } (?L \cup ?R))$ 
     $\text{card } (\text{vars-of-prop } \varphi 1 \cup \text{vars-of-prop } \varphi 2) \leq \text{Suc } (\text{card } (?L \cup ?R))$ 
  by auto
qed

```

```

value pos (FImp (FAnd (FVar P) (FVar Q)) (FOr (FVar P) (FVar Q)))

```

```

inductive path-to :: sign list ⇒ 'v propo ⇒ 'v propo ⇒ bool where
  path-to-refl[intro]: path-to []  $\varphi$   $\varphi$  |
  path-to-l:  $c \in \text{binary-connectives} \vee c = \text{CNot} \implies \text{wf-conn } c (\varphi \# l) \implies \text{path-to } p \varphi \varphi' \implies$ 
    path-to (L # p) (conn c ( $\varphi \# l$ ))  $\varphi'$  |
  path-to-r:  $c \in \text{binary-connectives} \implies \text{wf-conn } c (\psi \# \varphi \# []) \implies \text{path-to } p \varphi \varphi' \implies$ 
    path-to (R # p) (conn c ( $\psi \# \varphi \# []$ ))  $\varphi'$ 

```

There is a deep link between subformulas and pathes: a (correct) path leads to a subformula and a subformula is associated to a given path.

**lemma** path-to-subformula:

```

  path-to p  $\varphi$   $\varphi' \implies \varphi' \preceq \varphi$ 
apply (induct rule: path-to.induct)
apply simp
apply (metis list.set-intros(1) subformula-into-subformula)
using subformula-trans subformula-in-binary-conn(2) by metis

```

**lemma** subformula-path-exists:

```

  fixes  $\varphi$   $\varphi'$ :: 'v propo
  shows  $\varphi' \preceq \varphi \implies \exists p. \text{path-to } p \varphi \varphi'$ 
proof (induct rule: subformula.induct)
case subformula-refl
  have path-to []  $\varphi' \varphi'$  by auto
  then show  $\exists p. \text{path-to } p \varphi' \varphi'$  by metis
next
case (subformula-into-subformula  $\psi$  l c)
note wf = this(2) and IH = this(4) and  $\psi = \text{this}(1)$ 
then obtain p where p: path-to p  $\psi \varphi'$  by metis
{
  fix x :: 'v
  assume  $c = \text{CT} \vee c = \text{CF} \vee c = \text{CVar } x$ 
  then have False using subformula-into-subformula by auto
  then have  $\exists p. \text{path-to } p (\text{conn } c \ l) \varphi'$  by blast
}
moreover {
  assume  $c = \text{CNot}$ 

```

```

    then have  $l = [\psi]$  using wf  $\psi$  wf-conn-Not-decomp by fastforce
    then have path-to ( $L \# p$ ) (conn  $c \ l$ )  $\varphi'$  by (metis c wf-conn-unary p path-to-l)
    then have  $\exists p. \text{path-to } p \ (\text{conn } c \ l) \ \varphi'$  by blast
  }
  moreover {
    assume c: c  $\in$  binary-connectives
    obtain  $a \ b$  where  $ab: [a, b] = l$  using subformula-into-subformula c wf-conn-bin-list-length
      list-length2-decomp by metis
    then have  $a = \psi \vee b = \psi$  using  $\psi$  by auto
    then have path-to ( $L \# p$ ) (conn  $c \ l$ )  $\varphi' \vee \text{path-to } (R \# p) \ (\text{conn } c \ l) \ \varphi'$  using c path-to-l
      path-to-r p ab by (metis wf-conn-binary)
    then have  $\exists p. \text{path-to } p \ (\text{conn } c \ l) \ \varphi'$  by blast
  }
  ultimately show  $\exists p. \text{path-to } p \ (\text{conn } c \ l) \ \varphi'$  using connective-cases-arity by metis
qed

```

```

fun replace-at :: sign list  $\Rightarrow$   $'v \text{ propo} \Rightarrow 'v \text{ propo} \Rightarrow 'v \text{ propo}$  where
replace-at [] -  $\psi = \psi$  |
replace-at ( $L \# l$ ) (FAnd  $\varphi \ \varphi'$ )  $\psi = \text{FAnd } (\text{replace-at } l \ \varphi \ \psi) \ \varphi'$  |
replace-at ( $R \# l$ ) (FAnd  $\varphi \ \varphi'$ )  $\psi = \text{FAnd } \varphi \ (\text{replace-at } l \ \varphi' \ \psi)$  |
replace-at ( $L \# l$ ) (FOr  $\varphi \ \varphi'$ )  $\psi = \text{FOr } (\text{replace-at } l \ \varphi \ \psi) \ \varphi'$  |
replace-at ( $R \# l$ ) (FOr  $\varphi \ \varphi'$ )  $\psi = \text{FOr } \varphi \ (\text{replace-at } l \ \varphi' \ \psi)$  |
replace-at ( $L \# l$ ) (FEq  $\varphi \ \varphi'$ )  $\psi = \text{FEq } (\text{replace-at } l \ \varphi \ \psi) \ \varphi'$  |
replace-at ( $R \# l$ ) (FEq  $\varphi \ \varphi'$ )  $\psi = \text{FEq } \varphi \ (\text{replace-at } l \ \varphi' \ \psi)$  |
replace-at ( $L \# l$ ) (FImp  $\varphi \ \varphi'$ )  $\psi = \text{FImp } (\text{replace-at } l \ \varphi \ \psi) \ \varphi'$  |
replace-at ( $R \# l$ ) (FImp  $\varphi \ \varphi'$ )  $\psi = \text{FImp } \varphi \ (\text{replace-at } l \ \varphi' \ \psi)$  |
replace-at ( $L \# l$ ) (FNot  $\varphi$ )  $\psi = \text{FNot } (\text{replace-at } l \ \varphi \ \psi)$ 

```

## 5 Semantics over the syntax

Given the syntax defined above, we define a semantics, by defining an evaluation function *eval*. This function is the bridge between the logic as we define it here and the built-in logic of Isabelle.

```

fun eval :: ( $'v \Rightarrow \text{bool}$ )  $\Rightarrow 'v \text{ propo} \Rightarrow \text{bool}$  (infix  $\models$  50) where
 $\mathcal{A} \models \text{FT} = \text{True}$  |
 $\mathcal{A} \models \text{FF} = \text{False}$  |
 $\mathcal{A} \models \text{FVar } v = (\mathcal{A} \ v)$  |
 $\mathcal{A} \models \text{FNot } \varphi = (\neg(\mathcal{A} \models \varphi))$  |
 $\mathcal{A} \models \text{FAnd } \varphi_1 \ \varphi_2 = (\mathcal{A} \models \varphi_1 \wedge \mathcal{A} \models \varphi_2)$  |
 $\mathcal{A} \models \text{FOr } \varphi_1 \ \varphi_2 = (\mathcal{A} \models \varphi_1 \vee \mathcal{A} \models \varphi_2)$  |
 $\mathcal{A} \models \text{FImp } \varphi_1 \ \varphi_2 = (\mathcal{A} \models \varphi_1 \longrightarrow \mathcal{A} \models \varphi_2)$  |
 $\mathcal{A} \models \text{FEq } \varphi_1 \ \varphi_2 = (\mathcal{A} \models \varphi_1 \longleftrightarrow \mathcal{A} \models \varphi_2)$ 

```

**definition** *evalf* (**infix**  $\models_f$  50) **where**  
*evalf*  $\varphi \ \psi = (\forall A. A \models \varphi \longrightarrow A \models \psi)$

The deduction rule is in the book. And the proof looks like to the one of the book.

**theorem** *deduction-theorem*:

$$(\varphi \models_f \psi) \longleftrightarrow (\forall A. (A \models \text{FImp } \varphi \ \psi))$$

**proof**

```

  assume  $H: \varphi \models_f \psi$ 
  {
    fix  $A$ 
    have  $A \models \text{FImp } \varphi \ \psi$ 
    proof (cases  $A \models \varphi$ )

```

```

    case True
    then have  $A \models \psi$  using  $H$  unfolding evalf-def by metis
    then show  $A \models FImp\ \varphi\ \psi$  by auto
next
    case False
    then show  $A \models FImp\ \varphi\ \psi$  by auto
qed
}
then show  $\forall A. A \models FImp\ \varphi\ \psi$  by blast
next
assume  $A: \forall A. A \models FImp\ \varphi\ \psi$ 
show  $\varphi \models_f \psi$ 
proof (rule ccontr)
  assume  $\neg \varphi \models_f \psi$ 
  then obtain  $A$  where  $A \models \varphi$  and  $\neg A \models \psi$  using evalf-def by metis
  then have  $\neg A \models FImp\ \varphi\ \psi$  by auto
  then show False using  $A$  by blast
qed
qed

```

A shorter proof:

**lemma**  $\varphi \models_f \psi \longleftrightarrow (\forall A. A \models FImp\ \varphi\ \psi)$   
 by (*simp add: evalf-def*)

**definition** *same-over-set*::  $('v \Rightarrow bool) \Rightarrow ('v \Rightarrow bool) \Rightarrow 'v\ set \Rightarrow bool$  **where**  
*same-over-set*  $A\ B\ S = (\forall c \in S. A\ c = B\ c)$

If two mapping  $A$  and  $B$  have the same value over the variables, then the same formula are satisfiable.

**lemma** *same-over-set-eval*:  
 assumes *same-over-set*  $A\ B\ (vars\text{-of-prop}\ \varphi)$   
 shows  $A \models \varphi \longleftrightarrow B \models \varphi$   
 using *assms* unfolding *same-over-set-def* by (*induct*  $\varphi$ , *auto*)

**end**  
**theory** *Prop-Abstract-Transformation*  
**imports** *Main Prop-Logic Wellfounded-More*

**begin**

This file is devoted to abstract properties of the transformations, like consistency preservation and lifting from terms to proposition.

## 6 Rewrite systems and properties

### 6.1 Lifting of rewrite rules

We can lift a rewrite relation  $r$  over a full formula: the relation  $r$  works on terms, while *propo-rew-step* works on formulas.

**inductive** *propo-rew-step* ::  $('v\ propo \Rightarrow 'v\ propo \Rightarrow bool) \Rightarrow 'v\ propo \Rightarrow 'v\ propo \Rightarrow bool$   
 for  $r :: 'v\ propo \Rightarrow 'v\ propo \Rightarrow bool$  **where**  
*global-rel*:  $r\ \varphi\ \psi \implies propo\text{-rew-step}\ r\ \varphi\ \psi$  |  
*propo-rew-one-step-lift*:  $propo\text{-rew-step}\ r\ \varphi\ \varphi' \implies wf\text{-conn}\ c\ (\psi s\ @\ \varphi\ \# \psi s')$

$\implies \text{propo-rew-step } r \text{ (conn } c \text{ (}\psi s \text{ @ } \varphi \text{ \# } \psi s')) \text{ (conn } c \text{ (}\psi s \text{ @ } \varphi' \text{ \# } \psi s'))$

Here is a more precise link between the lifting and the subformulas: if a rewriting takes place between  $\varphi$  and  $\varphi'$ , then there are two subformulas  $\psi$  in  $\varphi$  and  $\psi'$  in  $\varphi'$ ,  $\psi'$  is the result of the rewriting of  $r$  on  $\psi$ .

This lemma is only a health condition:

**lemma** *propo-rew-step-subformula-imp*:

**shows**  $\text{propo-rew-step } r \text{ } \varphi \text{ } \varphi' \implies \exists \psi \psi'. \psi \preceq \varphi \wedge \psi' \preceq \varphi' \wedge r \psi \psi'$

**apply** (*induct rule: propo-rew-step.induct*)

**using** *subformula.simps subformula-into-subformula* **apply** *blast*

**using** *wf-conn-no-arity-change subformula-into-subformula wf-conn-no-arity-change-helper in-set-conv-decomp* **by** *metis*

The converse is moreover true: if there is a  $\psi$  and  $\psi'$ , then every formula  $\varphi$  containing  $\psi$ , can be rewritten into a formula  $\varphi'$ , such that it contains  $\psi'$ .

**lemma** *propo-rew-step-subformula-rec*:

**fixes**  $\psi \psi' \varphi :: 'v \text{ propo}$

**shows**  $\psi \preceq \varphi \implies r \psi \psi' \implies (\exists \varphi'. \psi' \preceq \varphi' \wedge \text{propo-rew-step } r \text{ } \varphi \text{ } \varphi')$

**proof** (*induct*  $\varphi$  *rule: subformula.induct*)

**case** *subformula-refl*

**hence**  $\text{propo-rew-step } r \text{ } \psi \text{ } \psi'$  **using** *propo-rew-step.intros* **by** *auto*

**moreover** **have**  $\psi' \preceq \psi'$  **using** *Prop-Logic.subformula-refl* **by** *auto*

**ultimately** **show**  $\exists \varphi'. \psi' \preceq \varphi' \wedge \text{propo-rew-step } r \text{ } \psi \text{ } \varphi'$  **by** *fastforce*

**next**

**case** (*subformula-into-subformula*  $\psi'' \text{ l } c$ *)*

**note**  $IH = \text{this}(4)$  **and**  $r = \text{this}(5)$  **and**  $\psi'' = \text{this}(1)$  **and**  $wf = \text{this}(2)$  **and**  $incl = \text{this}(3)$

**then** **obtain**  $\varphi'$  **where**  $\psi' \preceq \varphi' \wedge \text{propo-rew-step } r \text{ } \psi'' \text{ } \varphi'$  **by** *metis*

**moreover** **obtain**  $\xi \xi' :: 'v \text{ propo list}$  **where**

$l: l = \xi @ \psi'' \# \xi'$  **using** *List.split-list*  $\psi''$  *by metis*

**ultimately** **have**  $\text{propo-rew-step } r \text{ (conn } c \text{ l) (conn } c \text{ (}\xi @ \varphi' \text{ \# } \xi'))$

**using** *propo-rew-step.intros(2) wf* **by** *metis*

**moreover** **have**  $\psi' \preceq \text{conn } c \text{ (}\xi @ \varphi' \text{ \# } \xi')$

**using**  $wf * wf\text{-conn-no-arity-change}$  *Prop-Logic.subformula-into-subformula*

**by** (*metis (no-types) in-set-conv-decomp l wf-conn-no-arity-change-helper*)

**ultimately** **show**  $\exists \varphi'. \psi' \preceq \varphi' \wedge \text{propo-rew-step } r \text{ (conn } c \text{ l) } \varphi'$  **by** *metis*

**qed**

**lemma** *propo-rew-step-subformula*:

$(\exists \psi \psi'. \psi \preceq \varphi \wedge r \psi \psi') \longleftrightarrow (\exists \varphi'. \text{propo-rew-step } r \text{ } \varphi \text{ } \varphi')$

**using** *propo-rew-step-subformula-imp propo-rew-step-subformula-rec* **by** *metis+*

**lemma** *consistency-decompose-into-list*:

**assumes**  $wf: wf\text{-conn } c \text{ l}$  **and**  $wf': wf\text{-conn } c \text{ l'}$

**and**  $\text{same}: \forall n. (A \models l ! n \longleftrightarrow (A \models l' ! n))$

**shows**  $(A \models \text{conn } c \text{ l}) = (A \models \text{conn } c \text{ l'})$

**proof** (*cases*  $c$  *rule: connective-cases-arity-2*)

**case** *nullary*

**thus**  $(A \models \text{conn } c \text{ l}) \longleftrightarrow (A \models \text{conn } c \text{ l'})$  **using**  $wf \text{ } wf'$  **by** *auto*

**next**

**case** *unary* **note**  $c = \text{this}$

**then** **obtain**  $a$  **where**  $l: l = [a]$  **using** *wf-conn-Not-decomp wf* **by** *metis*

**obtain**  $a'$  **where**  $l': l' = [a']$  **using** *wf-conn-Not-decomp wf' c* **by** *metis*

**have**  $A \models a \longleftrightarrow A \models a'$  **using**  $l \text{ } l'$  **by** (*metis nth-Cons-0 same*)

**thus**  $A \models \text{conn } c \text{ l} \longleftrightarrow A \models \text{conn } c \text{ l'}$  **using**  $l \text{ } l' \text{ } c$  **by** *auto*

```

next
case binary note  $c = \text{this}$ 
then obtain  $a\ b$  where  $l: l = [a, b]$ 
  using wf-conn-bin-list-length list-length2-decomp wf by metis
obtain  $a'\ b'$  where  $l': l' = [a', b']$ 
  using wf-conn-bin-list-length list-length2-decomp wf'  $c$  by metis

have  $p: A \models a \longleftrightarrow A \models a' \wedge A \models b \longleftrightarrow A \models b'$ 
  using  $l\ l'$  same by (metis diff-Suc-1 nth-Cons' nat.distinct(2)) +
show  $A \models \text{conn } c\ l \longleftrightarrow A \models \text{conn } c\ l'$ 
  using wf c p unfolding binary-connectives-def l l' by auto
qed

```

Relation between *propo-rew-step* and the rewriting we have seen before: *propo-rew-step*  $r\ \varphi\ \varphi'$  means that we rewrite  $\psi$  inside  $\varphi$  (ie at a path  $p$ ) into  $\psi'$ .

**lemma** *propo-rew-step-rewrite*:

```

fixes  $\varphi\ \varphi' :: 'v\ \text{propo}$  and  $r :: 'v\ \text{propo} \Rightarrow 'v\ \text{propo} \Rightarrow \text{bool}$ 
assumes propo-rew-step  $r\ \varphi\ \varphi'$ 
shows  $\exists \psi\ \psi' p. r\ \psi\ \psi' \wedge \text{path-to } p\ \varphi\ \psi \wedge \text{replace-at } p\ \varphi\ \psi' = \varphi'$ 
using assms
proof (induct rule: propo-rew-step.induct)
case (global-rel  $\varphi\ \psi$ )
  moreover have path-to  $\square\ \varphi\ \varphi$  by auto
  moreover have replace-at  $\square\ \varphi\ \psi = \psi$  by auto
  ultimately show ?case by metis

```

next

```

case (propo-rew-one-step-lift  $\varphi\ \varphi'\ c\ \xi\ \xi'$ ) note rel = this(1) and IH0 = this(2) and corr = this(3)
obtain  $\psi\ \psi' p$  where IH:  $r\ \psi\ \psi' \wedge \text{path-to } p\ \varphi\ \psi \wedge \text{replace-at } p\ \varphi\ \psi' = \varphi'$  using IH0 by metis

```

```

{
  fix  $x :: 'v$ 
  assume  $c = CT \vee c = CF \vee c = CVar\ x$ 
  hence False using corr by auto
  hence  $\exists \psi\ \psi' p. r\ \psi\ \psi' \wedge \text{path-to } p\ (\xi @ (\varphi \# \xi'))\ \psi$ 
     $\wedge \text{replace-at } p\ (\xi @ (\varphi \# \xi'))\ \psi' = \text{conn } c\ (\xi @ (\varphi' \# \xi'))$ 
    by fast
}
moreover {
  assume  $c: c = CNot$ 
  hence empty:  $\xi = []\ \xi' = []$  using corr by auto
  have path-to  $(L \# p)\ (\text{conn } c\ (\xi @ (\varphi \# \xi')))\ \psi$ 
    using c empty IH wf-conn-unary path-to-l by fastforce
  moreover have replace-at  $(L \# p)\ (\text{conn } c\ (\xi @ (\varphi \# \xi')))\ \psi' = \text{conn } c\ (\xi @ (\varphi' \# \xi'))$ 
    using c empty IH by auto
  ultimately have  $\exists \psi\ \psi' p. r\ \psi\ \psi' \wedge \text{path-to } p\ (\xi @ (\varphi \# \xi'))\ \psi$ 
     $\wedge \text{replace-at } p\ (\text{conn } c\ (\xi @ (\varphi \# \xi')))\ \psi' = \text{conn } c\ (\xi @ (\varphi' \# \xi'))$ 
    using IH by metis
}
moreover {
  assume  $c: c \in \text{binary-connectives}$ 
  have length  $(\xi @ \varphi \# \xi') = 2$  using wf-conn-bin-list-length corr c by metis
  hence length  $\xi + \text{length } \xi' = 1$  by auto
  hence ld:  $(\text{length } \xi = 1 \wedge \text{length } \xi' = 0) \vee (\text{length } \xi = 0 \wedge \text{length } \xi' = 1)$  by arith
  obtain  $a\ b$  where ab:  $(\xi = [] \wedge \xi' = [b]) \vee (\xi = [a] \wedge \xi' = [])$ 
    using ld by (case-tac  $\xi$ , case-tac  $\xi'$ , auto)
}

```

```

{
  assume  $\varphi: \xi = [] \wedge \xi' = [b]$ 
  have path-to ( $L \# p$ ) ( $\text{conn } c (\xi @ (\varphi \# \xi'))$ )  $\psi$ 
    using  $\varphi \ c \ IH \ ab \ corr$  by (simp add: path-to-l)
  moreover have replace-at ( $L \# p$ ) ( $\text{conn } c (\xi @ (\varphi \# \xi'))$ )  $\psi' = \text{conn } c (\xi @ (\varphi' \# \xi'))$ 
    using  $c \ IH \ ab \ \varphi$  unfolding binary-connectives-def by auto
  ultimately have  $\exists \psi \ \psi' \ p. \ r \ \psi \ \psi' \wedge \text{path-to } p (\text{conn } c (\xi @ (\varphi \# \xi'))) \ \psi$ 
     $\wedge \text{replace-at } p (\text{conn } c (\xi @ (\varphi \# \xi'))) \ \psi' = \text{conn } c (\xi @ (\varphi' \# \xi'))$ 
    using  $IH$  by metis
}
moreover {
  assume  $\varphi: \xi = [a] \ \xi' = []$ 
  hence path-to ( $R \# p$ ) ( $\text{conn } c (\xi @ (\varphi \# \xi'))$ )  $\psi$ 
    using  $c \ IH \ corr \ \text{path-to-r} \ corr \ \varphi$  by (simp add: path-to-r)
  moreover have replace-at ( $R \# p$ ) ( $\text{conn } c (\xi @ (\varphi \# \xi'))$ )  $\psi' = \text{conn } c (\xi @ (\varphi' \# \xi'))$ 
    using  $c \ IH \ ab \ \varphi$  unfolding binary-connectives-def by auto
  ultimately have ?case using  $IH$  by metis
}
ultimately have ?case using  $ab$  by blast
}
ultimately show ?case using connective-cases-arity by blast
qed

```

## 6.2 Consistency preservation

We define *preserves-un-sat*: it means that a relation preserves consistency.

**definition** *preserves-un-sat* where

*preserves-un-sat*  $r \longleftrightarrow (\forall \varphi \ \psi. \ r \ \varphi \ \psi \longrightarrow (\forall A. \ A \models \varphi \longleftrightarrow A \models \psi))$

**lemma** *propo-rew-step-preservers-val-explicit*:

*propo-rew-step*  $r \ \varphi \ \psi \implies \text{preserves-un-sat } r \implies \text{propo-rew-step } r \ \varphi \ \psi \implies (\forall A. \ A \models \varphi \longleftrightarrow A \models \psi)$

unfolding *preserves-un-sat-def*

**proof** (induction rule: *propo-rew-step.induct*)

case *global-rel*

thus ?case by *simp*

next

case (*propo-rew-one-step-lift*  $\varphi \ \varphi' \ c \ \xi \ \xi'$ ) note  $rel = \text{this}(1)$  and  $wf = \text{this}(2)$

and  $IH = \text{this}(3)[OF \ \text{this}(4) \ \text{this}(1)]$  and  $\text{consistent} = \text{this}(4)$

{

fix  $A$

from  $IH$  have  $\forall n. (A \models (\xi @ \varphi \# \xi') ! n) = (A \models (\xi @ \varphi' \# \xi') ! n)$

by (*metis* (*mono-tags*, *hide-lams*) *list-update-length* *nth-Cons-0* *nth-append-length-plus* *nth-list-update-neq*)

hence  $(A \models \text{conn } c (\xi @ \varphi \# \xi')) = (A \models \text{conn } c (\xi @ \varphi' \# \xi'))$

by (*meson* *consistency-decompose-into-list* *wf* *wf-conn-no-arity-change-helper* *wf-conn-no-arity-change*)

}

thus  $\forall A. \ A \models \text{conn } c (\xi @ \varphi \# \xi') \longleftrightarrow A \models \text{conn } c (\xi @ \varphi' \# \xi')$  by *auto*

qed

**lemma** *propo-rew-step-preservers-val'*:

assumes *preserves-un-sat*  $r$

shows *preserves-un-sat* (*propo-rew-step*  $r$ )

**using** *assms* **by** (*simp add: preserves-un-sat-def propo-rew-step-preservers-val-explicit*)

**lemma** *preserves-un-sat-OO[intro]*:

*preserves-un-sat f  $\implies$  preserves-un-sat g  $\implies$  preserves-un-sat (f OO g)*

**unfolding** *preserves-un-sat-def* **by** *auto*

**lemma** *star-consistency-preservation-explicit*:

**assumes** (*propo-rew-step r*)<sup>\*\*</sup>  $\varphi \psi$  **and** *preserves-un-sat r*

**shows**  $\forall A. A \models \varphi \longleftrightarrow A \models \psi$

**using** *assms* **by** (*induct rule: rtranclp-induct*)

(*auto simp add: propo-rew-step-preservers-val-explicit*)

**lemma** *star-consistency-preservation*:

*preserves-un-sat r  $\implies$  preserves-un-sat (propo-rew-step r)<sup>\*\*</sup>*

**by** (*simp add: star-consistency-preservation-explicit preserves-un-sat-def*)

### 6.3 Full Lifting

In the previous a relation was lifted to a formula, now we define the relation such it is applied as long as possible. The definition is thus simply: it can be derived and nothing more can be derived.

**lemma** *full-ropo-rew-step-preservers-val[simp]*:

*preserves-un-sat r  $\implies$  preserves-un-sat (full (propo-rew-step r))*

**by** (*metis full-def preserves-un-sat-def star-consistency-preservation*)

**lemma** *full-propo-rew-step-subformula*:

*full (propo-rew-step r)  $\varphi' \varphi \implies \neg(\exists \psi \psi'. \psi \preceq \varphi \wedge r \psi \psi')$*

**unfolding** *full-def* **using** *propo-rew-step-subformula-rec* **by** *metis*

## 7 Transformation testing

### 7.1 Definition and first properties

To prove correctness of our transformation, we create a *all-subformula-st* predicate. It tests recursively all subformulas. At each step, the actual formula is tested. The aim of this *test-symb* function is to test locally some properties of the formulas (i.e. at the level of the connective or at first level). This allows a clause description between the rewrite relation and the *test-symb*

**definition** *all-subformula-st* :: (*'a propo  $\Rightarrow$  bool*)  $\Rightarrow$  *'a propo  $\Rightarrow$  bool* **where**

*all-subformula-st test-symb  $\varphi \equiv \forall \psi. \psi \preceq \varphi \longrightarrow test-symb \psi$*

**lemma** *test-symb-imp-all-subformula-st[simp]*:

*test-symb FT  $\implies$  all-subformula-st test-symb FT*

*test-symb FF  $\implies$  all-subformula-st test-symb FF*

*test-symb (FVar x)  $\implies$  all-subformula-st test-symb (FVar x)*

**unfolding** *all-subformula-st-def* **using** *subformula-leaf* **by** *metis+*

**lemma** *all-subformula-st-test-symb-true-phi*:

*all-subformula-st test-symb  $\varphi \implies test-symb \varphi$*

**unfolding** *all-subformula-st-def* **by** *auto*

**lemma** *all-subformula-st-decomp-imp*:  
 $wf\text{-}conn\ c\ l \implies (test\text{-}symb\ (conn\ c\ l) \wedge (\forall \varphi \in set\ l.\ all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi))$   
 $\implies all\text{-}subformula\text{-}st\ test\text{-}symb\ (conn\ c\ l)$   
**unfolding** *all-subformula-st-def* **by** *auto*

To ease the finding of proofs, we give some explicit theorem about the decomposition.

**lemma** *all-subformula-st-decomp-rec*:  
 $all\text{-}subformula\text{-}st\ test\text{-}symb\ (conn\ c\ l) \implies wf\text{-}conn\ c\ l$   
 $\implies (test\text{-}symb\ (conn\ c\ l) \wedge (\forall \varphi \in set\ l.\ all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi))$   
**unfolding** *all-subformula-st-def* **by** *auto*

**lemma** *all-subformula-st-decomp*:  
**fixes**  $c :: 'v\ connective$  **and**  $l :: 'v\ propo\ list$   
**assumes**  $wf\text{-}conn\ c\ l$   
**shows**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (conn\ c\ l)$   
 $\longleftrightarrow (test\text{-}symb\ (conn\ c\ l) \wedge (\forall \varphi \in set\ l.\ all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi))$   
**using** *assms all-subformula-st-decomp-rec all-subformula-st-decomp-imp* **by** *metis*

**lemma** *helper-fact*:  $c \in binary\text{-}connectives \longleftrightarrow (c = COr \vee c = CAnd \vee c = CEq \vee c = CImp)$   
**unfolding** *binary-connectives-def* **by** *auto*

**lemma** *all-subformula-st-decomp-explicit[simp]*:  
**fixes**  $\varphi\ \psi :: 'v\ propo$   
**shows**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FAnd\ \varphi\ \psi)$   
 $\longleftrightarrow (test\text{-}symb\ (FAnd\ \varphi\ \psi) \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \psi)$   
**and**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FOr\ \varphi\ \psi)$   
 $\longleftrightarrow (test\text{-}symb\ (FOr\ \varphi\ \psi) \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \psi)$   
**and**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FNot\ \varphi)$   
 $\longleftrightarrow (test\text{-}symb\ (FNot\ \varphi) \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi)$   
**and**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FEq\ \varphi\ \psi)$   
 $\longleftrightarrow (test\text{-}symb\ (FEq\ \varphi\ \psi) \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \psi)$   
**and**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FImp\ \varphi\ \psi)$   
 $\longleftrightarrow (test\text{-}symb\ (FImp\ \varphi\ \psi) \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \psi)$

**proof** –

**have**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FAnd\ \varphi\ \psi) \longleftrightarrow all\text{-}subformula\text{-}st\ test\text{-}symb\ (conn\ CAnd\ [\varphi, \psi])$   
**by** *auto*  
**moreover have**  $\dots \longleftrightarrow test\text{-}symb\ (conn\ CAnd\ [\varphi, \psi]) \wedge (\forall \xi \in set\ [\varphi, \psi].\ all\text{-}subformula\text{-}st\ test\text{-}symb\ \xi)$   
**using** *all-subformula-st-decomp wf-conn-helper-facts(5)* **by** *metis*  
**finally show**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FAnd\ \varphi\ \psi)$   
 $\longleftrightarrow (test\text{-}symb\ (FAnd\ \varphi\ \psi) \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \psi)$   
**by** *simp*

**have**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FOr\ \varphi\ \psi) \longleftrightarrow all\text{-}subformula\text{-}st\ test\text{-}symb\ (conn\ COr\ [\varphi, \psi])$   
**by** *auto*

**moreover have**  $\dots \longleftrightarrow$   
 $(test\text{-}symb\ (conn\ COr\ [\varphi, \psi]) \wedge (\forall \xi \in set\ [\varphi, \psi].\ all\text{-}subformula\text{-}st\ test\text{-}symb\ \xi))$   
**using** *all-subformula-st-decomp wf-conn-helper-facts(6)* **by** *metis*

**finally show**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FOr\ \varphi\ \psi)$   
 $\longleftrightarrow (test\text{-}symb\ (FOr\ \varphi\ \psi) \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \varphi \wedge all\text{-}subformula\text{-}st\ test\text{-}symb\ \psi)$   
**by** *simp*

**have**  $all\text{-}subformula\text{-}st\ test\text{-}symb\ (FEq\ \varphi\ \psi) \longleftrightarrow all\text{-}subformula\text{-}st\ test\text{-}symb\ (conn\ CEq\ [\varphi, \psi])$   
**by** *auto*

**moreover have**  $\dots$



```

   $\longleftrightarrow$  (test-symb (conn CEq  $[\varphi, \psi]$ )  $\wedge$  ( $\forall \xi \in \text{set } [\varphi, \psi]. \text{all-subformula-st test-symb } \xi$ ))
  using all-subformula-st-decomp wf-conn-helper-facts(8) by metis
finally show all-subformula-st test-symb (FEq  $\varphi \psi$ )
   $\longleftrightarrow$  (test-symb (FEq  $\varphi \psi$ )  $\wedge$  all-subformula-st test-symb  $\varphi \wedge$  all-subformula-st test-symb  $\psi$ )
  by simp

have all-subformula-st test-symb (FImp  $\varphi \psi$ )  $\longleftrightarrow$  all-subformula-st test-symb (conn CImp  $[\varphi, \psi]$ )
  by auto
moreover have ...
   $\longleftrightarrow$  (test-symb (conn CImp  $[\varphi, \psi]$ )  $\wedge$  ( $\forall \xi \in \text{set } [\varphi, \psi]. \text{all-subformula-st test-symb } \xi$ ))
  using all-subformula-st-decomp wf-conn-helper-facts(7) by metis
finally show all-subformula-st test-symb (FImp  $\varphi \psi$ )
   $\longleftrightarrow$  (test-symb (FImp  $\varphi \psi$ )  $\wedge$  all-subformula-st test-symb  $\varphi \wedge$  all-subformula-st test-symb  $\psi$ )
  by simp

have all-subformula-st test-symb (FNot  $\varphi$ )  $\longleftrightarrow$  all-subformula-st test-symb (conn CNot  $[\varphi]$ )
  by auto
moreover have ... = (test-symb (conn CNot  $[\varphi]$ )  $\wedge$  ( $\forall \xi \in \text{set } [\varphi]. \text{all-subformula-st test-symb } \xi$ ))
  using all-subformula-st-decomp wf-conn-helper-facts(1) by metis
finally show all-subformula-st test-symb (FNot  $\varphi$ )
   $\longleftrightarrow$  (test-symb (FNot  $\varphi$ )  $\wedge$  all-subformula-st test-symb  $\varphi$ ) by simp
qed

```

As *all-subformula-st* tests recursively, the function is true on every subformula.

**lemma** *subformula-all-subformula-st*:

```

 $\psi \preceq \varphi \implies \text{all-subformula-st test-symb } \varphi \implies \text{all-subformula-st test-symb } \psi$ 
by (induct rule: subformula.induct, auto simp add: all-subformula-st-decomp)

```

The following theorem *no-test-symb-step-exists* shows the link between the *test-symb* function and the corresponding rewrite relation *r*: if we assume that if every time *test-symb* is true, then a *r* can be applied, finally as long as  $\neg \text{all-subformula-st test-symb } \varphi$ , then something can be rewritten in  $\varphi$ .

**lemma** *no-test-symb-step-exists*:

```

fixes r:: 'v propo  $\Rightarrow$  'v propo  $\Rightarrow$  bool and test-symb:: 'v propo  $\Rightarrow$  bool and x:: 'v
and  $\varphi$ :: 'v propo
assumes test-symb-false-nullary:  $\forall x. \text{test-symb } FF \wedge \text{test-symb } FT \wedge \text{test-symb } (FVar\ x)$ 
and  $\forall \varphi'. \varphi' \preceq \varphi \longrightarrow (\neg \text{test-symb } \varphi') \longrightarrow (\exists \psi. r\ \varphi'\ \psi)$  and
 $\neg \text{all-subformula-st test-symb } \varphi$ 
shows  $(\exists \psi\ \psi'. \psi \preceq \varphi \wedge r\ \psi\ \psi')$ 
using assms
proof (induct  $\varphi$  rule: propo-induct-arity)
case (nullary  $\varphi\ x$ )
thus  $\exists \psi\ \psi'. \psi \preceq \varphi \wedge r\ \psi\ \psi'$ 
  using wf-conn-nullary test-symb-false-nullary by fastforce
next
case (unary  $\varphi$ ) note IH = this(1)[OF this(2)] and r = this(2) and nst = this(3) and subf =
this(4)
from r IH nst have H:  $\neg \text{all-subformula-st test-symb } \varphi \implies \exists \psi. \psi \preceq \varphi \wedge (\exists \psi'. r\ \psi\ \psi')$ 
  by (metis subformula-in-subformula-not subformula-refl subformula-trans)
{
  assume n:  $\neg \text{test-symb } (FNot\ \varphi)$ 
  obtain  $\psi$  where  $r\ (FNot\ \varphi)\ \psi$  using subformula-refl r n nst by blast
  moreover have  $FNot\ \varphi \preceq FNot\ \varphi$  using subformula-refl by auto
  ultimately have  $\exists \psi\ \psi'. \psi \preceq FNot\ \varphi \wedge r\ \psi\ \psi'$  by metis
}

```

```

moreover {
  assume  $n$ : test-symb ( $FNot\ \varphi$ )
  hence  $\neg$  all-subformula-st test-symb  $\varphi$ 
    using all-subformula-st-decomp-explicit(3) nst subf by blast
  hence  $\exists \psi\ \psi'.\ \psi \preceq FNot\ \varphi \wedge r\ \psi\ \psi'$ 
    using H subformula-in-subformula-not subformula-refl subformula-trans by blast
}
ultimately show  $\exists \psi\ \psi'.\ \psi \preceq FNot\ \varphi \wedge r\ \psi\ \psi'$  by blast
next
case (binary  $\varphi\ \varphi1\ \varphi2$ )
note  $IH\varphi1-0 = this(1)[OF\ this(4)]$  and  $IH\varphi2-0 = this(2)[OF\ this(4)]$  and  $r = this(4)$ 
and  $\varphi = this(3)$  and  $le = this(5)$  and  $nst = this(6)$ 

obtain  $c :: 'v\ connective$  where
   $c: (c = CAnd \vee c = COr \vee c = CImp \vee c = CEq) \wedge conn\ c\ [\varphi1, \varphi2] = \varphi$ 
  using  $\varphi$  by fastforce

hence corr: wf-conn  $c\ [\varphi1, \varphi2]$  using wf-conn.simps unfolding binary-connectives-def by auto
have inc:  $\varphi1 \preceq \varphi\ \varphi2 \preceq \varphi$  using binary-connectives-def c subformula-in-binary-conn by blast+
from  $r\ IH\varphi1-0$  have  $IH\varphi1: \neg$  all-subformula-st test-symb  $\varphi1 \implies \exists \psi\ \psi'.\ \psi \preceq \varphi1 \wedge r\ \psi\ \psi'$ 
  using inc(1) subformula-trans le by blast
from  $r\ IH\varphi2-0$  have  $IH\varphi2: \neg$  all-subformula-st test-symb  $\varphi2 \implies \exists \psi. \psi \preceq \varphi2 \wedge (\exists \psi'. r\ \psi\ \psi')$ 
  using inc(2) subformula-trans le by blast
have cases:  $\neg$ test-symb  $\varphi \vee \neg$ all-subformula-st test-symb  $\varphi1 \vee \neg$ all-subformula-st test-symb  $\varphi2$ 
  using  $c\ nst$  by auto
show  $\exists \psi\ \psi'.\ \psi \preceq \varphi \wedge r\ \psi\ \psi'$ 
  using  $IH\varphi1\ IH\varphi2\ subformula-trans\ inc\ subformula-refl\ cases\ le$  by blast
qed

```

## 7.2 Invariant conservation

If two rewrite relation are independant (or at least independant enough), then the property characterizing the first relation *all-subformula-st test-symb* remains true. The next show the same property, with changes in the assumptions.

The assumption  $\forall \varphi' \psi. \varphi' \preceq \Phi \longrightarrow r\ \varphi' \psi \longrightarrow$  *all-subformula-st test-symb*  $\varphi' \longrightarrow$  *all-subformula-st test-symb*  $\psi$  means that rewriting with  $r$  does not mess up the property we want to preserve locally.

The previous assumption is not enough to go from  $r$  to *propo-rew-step*  $r$ : we have to add the assumption that rewriting inside does not mess up the term:  $\forall c\ \xi\ \varphi\ \xi'\ \varphi'. \varphi \preceq \Phi \longrightarrow$  *propo-rew-step*  $r\ \varphi\ \varphi' \longrightarrow$  *wf-conn*  $c\ (\xi\ @\ \varphi\ \# \xi') \longrightarrow$  *test-symb* (*conn*  $c\ (\xi\ @\ \varphi\ \# \xi')$ )  $\longrightarrow$  *test-symb*  $\varphi' \longrightarrow$  *test-symb* (*conn*  $c\ (\xi\ @\ \varphi'\ \# \xi')$ )

### 7.2.1 Invariant while lifting of the rewriting relation

The condition  $\varphi \preceq \Phi$  (that will be used with  $\Phi = \varphi$  most of the time) is here to ensure that the recursive conditions on  $\Phi$  will moreover hold for the subterm we are rewriting. For example if there is no equivalence symbol in  $\Phi$ , we do not have to care about equivalence symbols in the two previous assumptions.

**lemma** *propo-rew-step-inv-stay'*:

**fixes**  $r :: 'v\ propo \Rightarrow 'v\ propo \Rightarrow bool$  **and** *test-symb*:  $'v\ propo \Rightarrow bool$  **and**  $x :: 'v$   
**and**  $\varphi\ \psi\ \Phi :: 'v\ propo$

```

assumes  $H: \forall \varphi' \psi. \varphi' \preceq \Phi \longrightarrow r \varphi' \psi \longrightarrow \text{all-subformula-st test-symb } \varphi'$ 
 $\longrightarrow \text{all-subformula-st test-symb } \psi$ 
and  $H': \forall (c:: 'v \text{ connective}) \xi \varphi \xi' \varphi'. \varphi \preceq \Phi \longrightarrow \text{propo-rew-step } r \varphi \varphi'$ 
 $\longrightarrow \text{wf-conn } c (\xi @ \varphi \# \xi') \longrightarrow \text{test-symb } (\text{conn } c (\xi @ \varphi \# \xi')) \longrightarrow \text{test-symb } \varphi'$ 
 $\longrightarrow \text{test-symb } (\text{conn } c (\xi @ \varphi' \# \xi'))$  and
 $\text{propo-rew-step } r \varphi \psi$  and
 $\varphi \preceq \Phi$  and
 $\text{all-subformula-st test-symb } \varphi$ 
shows  $\text{all-subformula-st test-symb } \psi$ 
using  $\text{assms}(3-5)$ 
proof (induct rule: propo-rew-step.induct)
case global-rel
thus ?case using  $H$  by simp
next
case (propo-rew-one-step-lift  $\varphi \varphi' c \xi \xi'$ )
note  $\text{rel} = \text{this}(1)$  and  $\varphi = \text{this}(2)$  and  $\text{corr} = \text{this}(3)$  and  $\Phi = \text{this}(4)$  and  $\text{nst} = \text{this}(5)$ 
have  $\text{sq}: \varphi \preceq \Phi$ 
using  $\Phi \text{ corr subformula-into-subformula subformula-refl subformula-trans}$ 
by (metis in-set-conv-decomp)
from  $\text{corr}$  have  $\forall \psi. \psi \in \text{set } (\xi @ \varphi \# \xi') \longrightarrow \text{all-subformula-st test-symb } \psi$ 
using  $\text{all-subformula-st-decomp nst}$  by blast
hence  $*$ :  $\forall \psi. \psi \in \text{set } (\xi @ \varphi' \# \xi') \longrightarrow \text{all-subformula-st test-symb } \psi$  using  $\varphi \text{ sq}$  by fastforce
hence  $\text{test-symb } \varphi'$  using  $\text{all-subformula-st-test-symb-true-phi}$  by auto
moreover from  $\text{corr nst}$  have  $\text{test-symb } (\text{conn } c (\xi @ \varphi \# \xi'))$ 
using  $\text{all-subformula-st-decomp}$  by blast
ultimately have  $\text{test-symb: test-symb } (\text{conn } c (\xi @ \varphi' \# \xi'))$  using  $H' \text{ sq corr rel}$  by blast

have  $\text{wf-conn } c (\xi @ \varphi' \# \xi')$ 
by (metis wf-conn-no-arity-change-helper corr wf-conn-no-arity-change)
thus  $\text{all-subformula-st test-symb } (\text{conn } c (\xi @ \varphi' \# \xi'))$ 
using  $*$   $\text{test-symb}$  by (metis all-subformula-st-decomp)
qed

```

The need for  $\varphi \preceq \Phi$  is not always necessary, hence we moreover have a version without inclusion.

**lemma** *propo-rew-step-inv-stay*:

```

fixes  $r:: 'v \text{ propo} \Rightarrow 'v \text{ propo} \Rightarrow \text{bool}$  and  $\text{test-symb}:: 'v \text{ propo} \Rightarrow \text{bool}$  and  $x:: 'v$ 
and  $\varphi \psi:: 'v \text{ propo}$ 
assumes
 $H: \forall \varphi' \psi. r \varphi' \psi \longrightarrow \text{all-subformula-st test-symb } \varphi' \longrightarrow \text{all-subformula-st test-symb } \psi$  and
 $H': \forall (c:: 'v \text{ connective}) \xi \varphi \xi' \varphi'. \text{wf-conn } c (\xi @ \varphi \# \xi') \longrightarrow \text{test-symb } (\text{conn } c (\xi @ \varphi \# \xi'))$ 
 $\longrightarrow \text{test-symb } \varphi' \longrightarrow \text{test-symb } (\text{conn } c (\xi @ \varphi' \# \xi'))$  and
 $\text{propo-rew-step } r \varphi \psi$  and
 $\text{all-subformula-st test-symb } \varphi$ 
shows  $\text{all-subformula-st test-symb } \psi$ 
using  $\text{propo-rew-step-inv-stay'}$  [of  $\varphi \text{ r test-symb } \varphi \psi$ ]  $\text{assms subformula-refl}$  by metis

```

The lemmas can be lifted to *full* (*propo-rew-step*  $r$ ) instead of *propo-rew-step*

### 7.2.2 Invariant after all rewriting

**lemma** *full-propo-rew-step-inv-stay-with-inc*:

```

fixes  $r:: 'v \text{ propo} \Rightarrow 'v \text{ propo} \Rightarrow \text{bool}$  and  $\text{test-symb}:: 'v \text{ propo} \Rightarrow \text{bool}$  and  $x:: 'v$ 
and  $\varphi \psi:: 'v \text{ propo}$ 
assumes
 $H: \forall \varphi \psi. \text{propo-rew-step } r \varphi \psi \longrightarrow \text{all-subformula-st test-symb } \varphi$ 

```

```

    → all-subformula-st test-symb  $\psi$  and
  H':  $\forall (c:: 'v \text{ connective}) \xi \varphi \xi' \varphi'. \varphi \preceq \Phi \longrightarrow \text{propo-rew-step } r \varphi \varphi'$ 
    → wf-conn  $c (\xi @ \varphi \# \xi')$  → test-symb (conn  $c (\xi @ \varphi \# \xi')$ ) → test-symb  $\varphi'$ 
    → test-symb (conn  $c (\xi @ \varphi' \# \xi')$ ) and
     $\varphi \preceq \Phi$  and
  full: full (propo-rew-step  $r$ )  $\varphi \psi$  and
  init: all-subformula-st test-symb  $\varphi$ 
shows all-subformula-st test-symb  $\psi$ 
using assms unfolding full-def
proof -
  have rel: (propo-rew-step  $r$ )**  $\varphi \psi$ 
    using full unfolding full-def by auto
  thus all-subformula-st test-symb  $\psi$ 
    using init
  proof (induct rule: rtrancpl-induct)
    case base
    then show all-subformula-st test-symb  $\varphi$  by blast
  next
    case (step  $b \ c$ ) note star = this(1) and IH = this(3) and one = this(2) and all = this(4)
    then have all-subformula-st test-symb  $b$  by metis
    then show all-subformula-st test-symb  $c$  using propo-rew-step-inv-stay'  $H \ H'$  rel one by auto
  qed
qed

lemma full-propo-rew-step-inv-stay':
  fixes  $r:: 'v \text{ propo} \Rightarrow 'v \text{ propo} \Rightarrow \text{bool}$  and test-symb::  $'v \text{ propo} \Rightarrow \text{bool}$  and  $x:: 'v$ 
  and  $\varphi \psi:: 'v \text{ propo}$ 
  assumes
     $H: \forall \varphi \psi. \text{propo-rew-step } r \varphi \psi \longrightarrow \text{all-subformula-st test-symb } \varphi$ 
    → all-subformula-st test-symb  $\psi$  and
     $H': \forall (c:: 'v \text{ connective}) \xi \varphi \xi' \varphi'. \text{propo-rew-step } r \varphi \varphi' \longrightarrow \text{wf-conn } c (\xi @ \varphi \# \xi')$ 
    → test-symb (conn  $c (\xi @ \varphi \# \xi')$ ) → test-symb  $\varphi'$  → test-symb (conn  $c (\xi @ \varphi' \# \xi')$ ) and
    full: full (propo-rew-step  $r$ )  $\varphi \psi$  and
    init: all-subformula-st test-symb  $\varphi$ 
  shows all-subformula-st test-symb  $\psi$ 
  using full-propo-rew-step-inv-stay-with-inc[of  $r$  test-symb  $\varphi$ ] assms subformula-refl by metis

lemma full-propo-rew-step-inv-stay:
  fixes  $r:: 'v \text{ propo} \Rightarrow 'v \text{ propo} \Rightarrow \text{bool}$  and test-symb::  $'v \text{ propo} \Rightarrow \text{bool}$  and  $x:: 'v$ 
  and  $\varphi \psi:: 'v \text{ propo}$ 
  assumes
     $H: \forall \varphi \psi. r \varphi \psi \longrightarrow \text{all-subformula-st test-symb } \varphi \longrightarrow \text{all-subformula-st test-symb } \psi$  and
     $H': \forall (c:: 'v \text{ connective}) \xi \varphi \xi' \varphi'. \text{wf-conn } c (\xi @ \varphi \# \xi') \longrightarrow \text{test-symb (conn } c (\xi @ \varphi \# \xi'))$ 
    → test-symb  $\varphi' \longrightarrow \text{test-symb (conn } c (\xi @ \varphi' \# \xi'))$  and
    full: full (propo-rew-step  $r$ )  $\varphi \psi$  and
    init: all-subformula-st test-symb  $\varphi$ 
  shows all-subformula-st test-symb  $\psi$ 
  unfolding full-def
proof -
  have rel: (propo-rew-step  $r$ )^**  $\varphi \psi$ 
    using full unfolding full-def by auto
  thus all-subformula-st test-symb  $\psi$ 
    using init
  proof (induct rule: rtrancpl-induct)
    case base

```

```

    thus all-subformula-st test-symb  $\varphi$  by blast
  next
  case (step b c)
  note star = this(1) and IH = this(3) and one = this(2) and all = this(4)
  hence all-subformula-st test-symb b by metis
  thus all-subformula-st test-symb c
    using propo-rew-step-inv-stay subformula-refl H H' rel one by auto
qed
qed

lemma full-propo-rew-step-inv-stay-conn:
  fixes r:: 'v propo  $\Rightarrow$  'v propo  $\Rightarrow$  bool and test-symb:: 'v propo  $\Rightarrow$  bool and x :: 'v
  and  $\varphi \psi$  :: 'v propo
  assumes
    H:  $\forall \varphi \psi. r \varphi \psi \longrightarrow \text{all-subformula-st test-symb } \varphi \longrightarrow \text{all-subformula-st test-symb } \psi$  and
    H':  $\forall (c:: 'v \text{ connective}) l l'. \text{wf-conn } c l \longrightarrow \text{wf-conn } c l' \longrightarrow (\text{test-symb } (\text{conn } c l) \longleftrightarrow \text{test-symb } (\text{conn } c l'))$  and
  full: full (propo-rew-step r)  $\varphi \psi$  and
  init: all-subformula-st test-symb  $\varphi$ 
  shows all-subformula-st test-symb  $\psi$ 
proof -
  have  $\bigwedge (c:: 'v \text{ connective}) \xi \varphi \xi' \varphi'. \text{wf-conn } c (\xi @ \varphi \# \xi') \Longrightarrow \text{test-symb } (\text{conn } c (\xi @ \varphi \# \xi')) \Longrightarrow \text{test-symb } \varphi' \Longrightarrow \text{test-symb } (\text{conn } c (\xi @ \varphi' \# \xi'))$ 
    using H' by (metis wf-conn-no-arity-change-helper wf-conn-no-arity-change)
  thus all-subformula-st test-symb  $\psi$ 
    using H full init full-propo-rew-step-inv-stay by blast
qed

end
theory Prop-Normalisation
imports Main Prop-Logic Prop-Abstract-Transformation ../lib/Multiset-More
begin

```

Given the previous definition about abstract rewriting and theorem about them, we now have the detailed rule making the transformation into CNF/DNF.

## 8 Rewrite Rules

The idea of Christoph Weidenbach's book is to remove gradually the operators: first equivalencies, then implication, after that the unused true/false and finally the reorganizing the or/and. We will prove each transformation seperately.

### 8.1 Elimination of the equivalences

The first transformation consists in removing every equivalence symbol.

```

inductive elim-equiv :: 'v propo  $\Rightarrow$  'v propo  $\Rightarrow$  bool where
  elim-equiv[simp]: elim-equiv (FEq  $\varphi \psi$ ) (FAnd (FImp  $\varphi \psi$ ) (FImp  $\psi \varphi$ ))

```

```

lemma elim-equiv-transformation-consistent:
  A  $\models$  FEq  $\varphi \psi \longleftrightarrow A \models$  FAnd (FImp  $\varphi \psi$ ) (FImp  $\psi \varphi$ )
  by auto

```

**lemma** *elim-equiv-explicit*:  $\text{elim-equiv } \varphi \psi \implies \forall A. A \models \varphi \iff A \models \psi$   
**by** (*induct rule*: *elim-equiv.induct*, *auto*)

**lemma** *elim-equiv-consistent*: *preserves-un-sat elim-equiv*  
**unfolding** *preserves-un-sat-def* **by** (*simp add*: *elim-equiv-explicit*)

**lemma** *elimEquiv-lifted-consistant*:  
*preserves-un-sat (full (propo-rew-step elim-equiv))*  
**by** (*simp add*: *elim-equiv-consistent*)

This function ensures that there is no equivalencies left in the formula tested by *no-equiv-symb*.

**fun** *no-equiv-symb* :: '*v* propo  $\Rightarrow$  bool **where**  
*no-equiv-symb* (*FEq* -) = *False* |  
*no-equiv-symb* - = *True*

Given the definition of *no-equiv-symb*, it does not depend on the formula, but only on the connective used.

**lemma** *no-equiv-symb-conn-characterization*[*simp*]:  
**fixes** *c* :: '*v* connective **and** *l* :: '*v* propo list  
**assumes** *wf*: *wf-conn c l*  
**shows** *no-equiv-symb (conn c l)  $\iff c \neq \text{CEq}$*   
**by** (*metis connective.distinct*(13,25,35,43) *wf no-equiv-symb.elims*(3) *no-equiv-symb.simps*(1)  
*wf-conn.cases wf-conn-list*(6))

**definition** *no-equiv* **where** *no-equiv* = *all-subformula-st no-equiv-symb*

**lemma** *no-equiv-eq*[*simp*]:  
**fixes**  $\varphi \psi$  :: '*v* propo  
**shows**  
 $\neg \text{no-equiv } (\text{FEq } \varphi \psi)$   
 $\text{no-equiv } \text{FT}$   
 $\text{no-equiv } \text{FF}$   
**using** *no-equiv-symb.simps*(1) *all-subformula-st-test-symb-true-phi* **unfolding** *no-equiv-def* **by** *auto*

The following lemma helps to reconstruct *no-equiv* expressions: this representation is easier to use than the set definition.

**lemma** *all-subformula-st-decomp-explicit-no-equiv*[*iff*]:  
**fixes**  $\varphi \psi$  :: '*v* propo  
**shows**  
 $\text{no-equiv } (\text{FNot } \varphi) \iff \text{no-equiv } \varphi$   
 $\text{no-equiv } (\text{FAnd } \varphi \psi) \iff (\text{no-equiv } \varphi \wedge \text{no-equiv } \psi)$   
 $\text{no-equiv } (\text{FOr } \varphi \psi) \iff (\text{no-equiv } \varphi \wedge \text{no-equiv } \psi)$   
 $\text{no-equiv } (\text{FImp } \varphi \psi) \iff (\text{no-equiv } \varphi \wedge \text{no-equiv } \psi)$   
**by** (*auto simp*: *no-equiv-def*)

A theorem to show the link between the rewrite relation *elim-equiv* and the function *no-equiv-symb*. This theorem is one of the assumption we need to characterize the transformation.

**lemma** *no-equiv-elim-equiv-step*:  
**fixes**  $\varphi$  :: '*v* propo  
**assumes** *no-equiv*:  $\neg \text{no-equiv } \varphi$   
**shows**  $\exists \psi \psi'. \psi \preceq \varphi \wedge \text{elim-equiv } \psi \psi'$   
**proof** –  
**have** *test-symb-false-nullary*:  
 $\forall x. :v. \text{no-equiv-symb } \text{FF} \wedge \text{no-equiv-symb } \text{FT} \wedge \text{no-equiv-symb } (\text{FVar } x)$

```

  unfolding no-equiv-def by auto
moreover {
  fix c:: 'v connective and l :: 'v propo list and  $\psi :: 'v propo$ 
  assume a1: elim-equiv (conn c l)  $\psi$ 
  have  $\bigwedge p pa. \neg \text{elim-equiv } (p::'v propo) pa \vee \neg \text{no-equiv-symb } p$ 
  using elim-equiv.cases no-equiv-symb.simps(1) by blast
  then have elim-equiv (conn c l)  $\psi \implies \neg \text{no-equiv-symb } (conn c l)$  using a1 by metis
}
moreover have  $H': \forall \psi. \neg \text{elim-equiv } FT \ \psi \ \forall \psi. \neg \text{elim-equiv } FF \ \psi \ \forall \psi \ x. \neg \text{elim-equiv } (FVar \ x) \ \psi$ 
  using elim-equiv.cases by auto
moreover have  $\bigwedge \varphi. \neg \text{no-equiv-symb } \varphi \implies \exists \psi. \text{elim-equiv } \varphi \ \psi$ 
  by (case-tac  $\varphi$ , auto simp: elim-equiv.simps)
then have  $\bigwedge \varphi'. \varphi' \preceq \varphi \implies \neg \text{no-equiv-symb } \varphi' \implies \exists \psi. \text{elim-equiv } \varphi' \ \psi$  by force
ultimately show ?thesis
  using no-test-symb-step-exists no-equiv test-symb-false-nullary unfolding no-equiv-def by blast
qed

```

Given all the previous theorem and the characterization, once we have rewritten everything, there is no equivalence symbol any more.

**lemma** *no-equiv-full-propo-rew-step-elim-equiv*:  
 full (propo-rew-step elim-equiv)  $\varphi \ \psi \implies \text{no-equiv } \psi$   
 using full-propo-rew-step-subformula no-equiv-elim-equiv-step by blast

## 8.2 Eliminate Implication

After that, we can eliminate the implication symbols.

**inductive** *elim-imp* :: 'v propo  $\Rightarrow$  'v propo  $\Rightarrow$  bool **where**  
 [simp]: *elim-imp* (FImp  $\varphi \ \psi$ ) (FOr (FNot  $\varphi$ )  $\psi$ )

**lemma** *elim-imp-transformation-consistent*:  
 $A \models FImp \ \varphi \ \psi \longleftrightarrow A \models FOr \ (FNot \ \varphi) \ \psi$   
 by auto

**lemma** *elim-imp-explicit*: *elim-imp*  $\varphi \ \psi \implies \forall A. A \models \varphi \longleftrightarrow A \models \psi$   
 by (induct  $\varphi \ \psi$  rule: elim-imp.induct, auto)

**lemma** *elim-imp-consistent*: preserves-un-sat *elim-imp*  
 unfolding preserves-un-sat-def by (simp add: elim-imp-explicit)

**lemma** *elim-imp-lifted-consistent*:  
 preserves-un-sat (full (propo-rew-step elim-imp))  
 by (simp add: elim-imp-consistent)

**fun** *no-imp-symb* **where**  
*no-imp-symb* (FImp -) = False |  
*no-imp-symb* - = True

**lemma** *no-imp-symb-conn-characterization*:  
 $wf\text{-}conn \ c \ l \implies \text{no-imp-symb } (conn \ c \ l) \longleftrightarrow c \neq CImp$   
 by (induction rule: wf-conn-induct) auto

**definition** *no-imp* **where** *no-imp*  $\equiv$  all-subformula-st *no-imp-symb*  
**declare** *no-imp-def*[simp]

**lemma** *no-imp-Imp*[simp]:

$\neg \text{no-imp } (F\text{Imp } \varphi \ \psi)$   
 $\text{no-imp } FT$   
 $\text{no-imp } FF$   
**unfolding**  $\text{no-imp-def}$  **by**  $\text{auto}$

**lemma**  $\text{all-subformula-st-decomp-explicit-imp}[simp]$ :  
**fixes**  $\varphi \ \psi :: 'v \text{ propo}$   
**shows**  
 $\text{no-imp } (F\text{Not } \varphi) \longleftrightarrow \text{no-imp } \varphi$   
 $\text{no-imp } (F\text{And } \varphi \ \psi) \longleftrightarrow (\text{no-imp } \varphi \wedge \text{no-imp } \psi)$   
 $\text{no-imp } (F\text{Or } \varphi \ \psi) \longleftrightarrow (\text{no-imp } \varphi \wedge \text{no-imp } \psi)$   
**by**  $\text{auto}$

Invariant of the  $\text{elim-imp}$  transformation

**lemma**  $\text{elim-imp-no-equiv}$ :  
 $\text{elim-imp } \varphi \ \psi \implies \text{no-equiv } \varphi \implies \text{no-equiv } \psi$   
**by** ( $\text{induct } \varphi \ \psi$   $\text{rule: elim-imp.induct, auto}$ )

**lemma**  $\text{elim-imp-inv}$ :  
**fixes**  $\varphi \ \psi :: 'v \text{ propo}$   
**assumes**  $\text{full } (\text{propo-rew-step } \text{elim-imp}) \ \varphi \ \psi$  **and**  $\text{no-equiv } \varphi$   
**shows**  $\text{no-equiv } \psi$   
**using**  $\text{full-propo-rew-step-inv-stay-conn}[of \ \text{elim-imp } \text{no-equiv-symb } \varphi \ \psi]$   $\text{assms elim-imp-no-equiv}$   
 $\text{no-equiv-symb-conn-characterization}$  **unfolding**  $\text{no-equiv-def}$  **by**  $\text{metis}$

**lemma**  $\text{no-no-imp-elim-imp-step-exists}$ :

**fixes**  $\varphi :: 'v \text{ propo}$   
**assumes**  $\text{no-equiv: } \neg \text{no-imp } \varphi$   
**shows**  $\exists \psi \ \psi'. \ \psi \preceq \varphi \wedge \text{elim-imp } \psi \ \psi'$

**proof** –

**have**  $\text{test-symb-false-nullary: } \forall x. \text{no-imp-symb } FF \wedge \text{no-imp-symb } FT \wedge \text{no-imp-symb } (F\text{Var } (x:: 'v))$   
**by**  $\text{auto}$

**moreover** {

**fix**  $c:: 'v \text{ connective}$  **and**  $l :: 'v \text{ propo list}$  **and**  $\psi :: 'v \text{ propo}$   
**have**  $H: \text{elim-imp } (\text{conn } c \ l) \ \psi \implies \neg \text{no-imp-symb } (\text{conn } c \ l)$   
**by** ( $\text{auto elim: elim-imp.cases}$ )

}

**moreover**

**have**  $H': \forall \psi. \neg \text{elim-imp } FT \ \psi \ \forall \psi. \neg \text{elim-imp } FF \ \psi \ \forall \psi \ x. \neg \text{elim-imp } (F\text{Var } x) \ \psi$   
**by** ( $\text{auto elim: elim-imp.cases}$ ) $+$

**moreover**

**have**  $\bigwedge \varphi. \neg \text{no-imp-symb } \varphi \implies \exists \psi. \text{elim-imp } \varphi \ \psi$   
**by** ( $\text{case-tac } \varphi$ ) ( $\text{force simp: elim-imp.simps}$ ) $+$   
**then have**  $(\bigwedge \varphi'. \varphi' \preceq \varphi \implies \neg \text{no-imp-symb } \varphi' \implies \exists \psi. \text{elim-imp } \varphi' \ \psi)$  **by**  $\text{force}$

**ultimately show**  $?thesis$

**using**  $\text{no-test-symb-step-exists no-equiv test-symb-false-nullary}$  **unfolding**  $\text{no-imp-def}$  **by**  $\text{blast}$

**qed**

**lemma**  $\text{no-imp-full-propo-rew-step-elim-imp}$ :  $\text{full } (\text{propo-rew-step } \text{elim-imp}) \ \varphi \ \psi \implies \text{no-imp } \psi$   
**using**  $\text{full-propo-rew-step-subformula no-no-imp-elim-imp-step-exists}$  **by**  $\text{blast}$

### 8.3 Eliminate all the True and False in the formula

Contrary to the book, we have to give the transformation and the “commutative” transformation. The latter is implicit in the book.



**inductive** *elimTB* **where**

*ElimTB1*: *elimTB* (*FAnd*  $\varphi$  *FT*)  $\varphi$  |  
*ElimTB1'*: *elimTB* (*FAnd* *FT*  $\varphi$ )  $\varphi$  |

*ElimTB2*: *elimTB* (*FAnd*  $\varphi$  *FF*) *FF* |  
*ElimTB2'*: *elimTB* (*FAnd* *FF*  $\varphi$ ) *FF* |

*ElimTB3*: *elimTB* (*FOr*  $\varphi$  *FT*) *FT* |  
*ElimTB3'*: *elimTB* (*FOr* *FT*  $\varphi$ ) *FT* |

*ElimTB4*: *elimTB* (*FOr*  $\varphi$  *FF*)  $\varphi$  |  
*ElimTB4'*: *elimTB* (*FOr* *FF*  $\varphi$ )  $\varphi$  |

*ElimTB5*: *elimTB* (*FNot* *FT*) *FF* |  
*ElimTB6*: *elimTB* (*FNot* *FF*) *FT*

**lemma** *elimTB-consistent: preserves-un-sat elimTB*

**proof** –

```
{
  fix  $\varphi \psi$ :: 'b propo
  have elimTB  $\varphi \psi \implies \forall A. A \models \varphi \longleftrightarrow A \models \psi$  by (induction rule: elimTB.inducts) auto
}
then show ?thesis using preserves-un-sat-def by auto
qed
```

**inductive** *no-T-F-symb* :: 'v propo  $\Rightarrow$  bool **where**

*no-T-F-symb-comp*:  $c \neq CF \implies c \neq CT \implies \text{wf-conn } c \ l \implies (\forall \varphi \in \text{set } l. \varphi \neq FT \wedge \varphi \neq FF)$   
 $\implies \text{no-T-F-symb } (\text{conn } c \ l)$

**lemma** *wf-conn-no-T-F-symb-iff[simp]*:

```
wf-conn  $c \ \psi s \implies$ 
  no-T-F-symb (conn  $c \ \psi s$ )  $\longleftrightarrow (c \neq CF \wedge c \neq CT \wedge (\forall \psi \in \text{set } \psi s. \psi \neq FF \wedge \psi \neq FT))$ 
unfolding no-T-F-symb.simps apply (cases c)
  using wf-conn-list(1) apply fastforce
  using wf-conn-list(2) apply fastforce
  using wf-conn-list(3) apply fastforce
  apply (metis (no-types, hide-lams) conn-inj connective.distinct(5,17))
  using conn-inj apply blast+
done
```

**lemma** *wf-conn-no-T-F-symb-iff-explicit[simp]*:

```
no-T-F-symb (FAnd  $\varphi \ \psi$ )  $\longleftrightarrow (\forall \chi \in \text{set } [\varphi, \psi]. \chi \neq FF \wedge \chi \neq FT)$ 
no-T-F-symb (FOr  $\varphi \ \psi$ )  $\longleftrightarrow (\forall \chi \in \text{set } [\varphi, \psi]. \chi \neq FF \wedge \chi \neq FT)$ 
no-T-F-symb (FEq  $\varphi \ \psi$ )  $\longleftrightarrow (\forall \chi \in \text{set } [\varphi, \psi]. \chi \neq FF \wedge \chi \neq FT)$ 
no-T-F-symb (FImp  $\varphi \ \psi$ )  $\longleftrightarrow (\forall \chi \in \text{set } [\varphi, \psi]. \chi \neq FF \wedge \chi \neq FT)$ 
apply (metis conn.simps(36) conn.simps(37) conn.simps(5) propo.distinct(19)
  wf-conn-helper-facts(5) wf-conn-no-T-F-symb-iff)
apply (metis conn.simps(36) conn.simps(37) conn.simps(6) propo.distinct(22)
  wf-conn-helper-facts(6) wf-conn-no-T-F-symb-iff)
using wf-conn-no-T-F-symb-iff apply fastforce
by (metis conn.simps(36) conn.simps(37) conn.simps(7) propo.distinct(23) wf-conn-helper-facts(7)
  wf-conn-no-T-F-symb-iff)
```

```

lemma no-T-F-symb-false[simp]:
  fixes c :: 'v connective
  shows
    ¬no-T-F-symb (FT :: 'v propo)
    ¬no-T-F-symb (FF :: 'v propo)
  by (metis (no-types) conn.simps(1,2) wf-conn-no-T-F-symb-iff wf-conn-nullary)+

lemma no-T-F-symb-bool[simp]:
  fixes x :: 'v
  shows no-T-F-symb (FVar x)
  using no-T-F-symb-comp wf-conn-nullary by (metis connective.distinct(3, 15) conn.simps(3)
    empty-iff list.set(1))

```

```

lemma no-T-F-symb-fnot-imp:
  ¬no-T-F-symb (FNot φ) ⇒ φ = FT ∨ φ = FF
proof (rule ccontr)
  assume n: ¬no-T-F-symb (FNot φ)
  assume ¬(φ = FT ∨ φ = FF)
  then have ∀φ' ∈ set [φ]. φ' ≠ FT ∧ φ' ≠ FF by auto
  moreover have wf-conn CNot [φ] by simp
  ultimately have no-T-F-symb (FNot φ)
    using no-T-F-symb.intros by (metis conn.simps(4) connective.distinct(5,17))
  then show False using n by blast
qed

```

```

lemma no-T-F-symb-fnot[simp]:
  no-T-F-symb (FNot φ) ⇔ ¬(φ = FT ∨ φ = FF)
  using no-T-F-symb.simps no-T-F-symb-fnot-imp by (metis conn-inj-not(2) list.set-intros(1))

```

Actually it is not possible to remove every *FT* and *FF*: if the formula is equal to true or false, we can not remove it.

```

inductive no-T-F-symb-except-toplevel where
  no-T-F-symb-except-toplevel-true[simp]: no-T-F-symb-except-toplevel FT |
  no-T-F-symb-except-toplevel-false[simp]: no-T-F-symb-except-toplevel FF |
  noTrue-no-T-F-symb-except-toplevel[simp]: no-T-F-symb φ ⇒ no-T-F-symb-except-toplevel φ

```

```

lemma no-T-F-symb-except-toplevel-bool:
  fixes x :: 'v
  shows no-T-F-symb-except-toplevel (FVar x)
  by simp

```

```

lemma no-T-F-symb-except-toplevel-not-decom:
  φ ≠ FT ⇒ φ ≠ FF ⇒ no-T-F-symb-except-toplevel (FNot φ)
  by simp

```

```

lemma no-T-F-symb-except-toplevel-bin-decom:
  fixes φ ψ :: 'v propo
  assumes φ ≠ FT and φ ≠ FF and ψ ≠ FT and ψ ≠ FF
  and c: c ∈ binary-connectives
  shows no-T-F-symb-except-toplevel (conn c [φ, ψ])
  by (metis (no-types, lifting) assms c conn.simps(4) list.discI noTrue-no-T-F-symb-except-toplevel
    wf-conn-no-T-F-symb-iff no-T-F-symb-fnot set-ConsD wf-conn-binary wf-conn-helper-facts(1)
    wf-conn-list-decomp(1,2))

```

**lemma** *no-T-F-symb-except-toplevel-if-is-a-true-false*:  
**fixes**  $l :: 'v \text{ propo list}$  **and**  $c :: 'v \text{ connective}$   
**assumes** *corr*:  $\text{wf-conn } c \ l$   
**and**  $FT \in \text{set } l \vee FF \in \text{set } l$   
**shows**  $\neg \text{no-T-F-symb-except-toplevel } (\text{conn } c \ l)$   
**by** (*metis* *assms empty-iff no-T-F-symb-except-toplevel.simps wf-conn-no-T-F-symb-iff set-empty wf-conn-list*(1,2))

**lemma** *no-T-F-symb-except-top-level-false-example[simp]*:  
**fixes**  $\varphi \ \psi :: 'v \text{ propo}$   
**assumes**  $\varphi = FT \vee \psi = FT \vee \varphi = FF \vee \psi = FF$   
**shows**  
 $\neg \text{no-T-F-symb-except-toplevel } (F\text{And } \varphi \ \psi)$   
 $\neg \text{no-T-F-symb-except-toplevel } (F\text{Or } \varphi \ \psi)$   
 $\neg \text{no-T-F-symb-except-toplevel } (F\text{Imp } \varphi \ \psi)$   
 $\neg \text{no-T-F-symb-except-toplevel } (F\text{Eq } \varphi \ \psi)$   
**using** *assms no-T-F-symb-except-toplevel-if-is-a-true-false* **unfolding** *binary-connectives-def*  
**by** (*metis* (*no-types*) *conn.simps*(5–8) *insert-iff list.simps*(14–15) *wf-conn-helper-facts*(5–8))+

**lemma** *no-T-F-symb-except-top-level-false-not[simp]*:  
**fixes**  $\varphi \ \psi :: 'v \text{ propo}$   
**assumes**  $\varphi = FT \vee \varphi = FF$   
**shows**  
 $\neg \text{no-T-F-symb-except-toplevel } (F\text{Not } \varphi)$   
**by** (*simp* *add*: *assms no-T-F-symb-except-toplevel.simps*)

This is the local extension of *no-T-F-symb-except-toplevel*.

**definition** *no-T-F-except-top-level* **where**  
 $\text{no-T-F-except-top-level} \equiv \text{all-subformula-st no-T-F-symb-except-toplevel}$

This is another property we will use. While this version might seem to be the one we want to prove, it is not since *FT* can not be reduced.

**definition** *no-T-F* **where**  
 $\text{no-T-F} \equiv \text{all-subformula-st no-T-F-symb}$

**lemma** *no-T-F-except-top-level-false*:  
**fixes**  $l :: 'v \text{ propo list}$  **and**  $c :: 'v \text{ connective}$   
**assumes**  $\text{wf-conn } c \ l$   
**and**  $FT \in \text{set } l \vee FF \in \text{set } l$   
**shows**  $\neg \text{no-T-F-except-top-level } (\text{conn } c \ l)$   
**by** (*simp* *add*: *all-subformula-st-decomp assms no-T-F-except-top-level-def no-T-F-symb-except-toplevel-if-is-a-true-false*)

**lemma** *no-T-F-except-top-level-false-example[simp]*:  
**fixes**  $\varphi \ \psi :: 'v \text{ propo}$   
**assumes**  $\varphi = FT \vee \psi = FT \vee \varphi = FF \vee \psi = FF$   
**shows**  
 $\neg \text{no-T-F-except-top-level } (F\text{And } \varphi \ \psi)$   
 $\neg \text{no-T-F-except-top-level } (F\text{Or } \varphi \ \psi)$   
 $\neg \text{no-T-F-except-top-level } (F\text{Eq } \varphi \ \psi)$   
 $\neg \text{no-T-F-except-top-level } (F\text{Imp } \varphi \ \psi)$   
**by** (*metis* *all-subformula-st-test-symb-true-phi assms no-T-F-except-top-level-def no-T-F-symb-except-top-level-false-example*)+

**lemma** *no-T-F-symb-except-toplevel-no-T-F-symb*:  
*no-T-F-symb-except-toplevel*  $\varphi \implies \varphi \neq FF \implies \varphi \neq FT \implies \text{no-T-F-symb } \varphi$   
**by** (*induct rule*: *no-T-F-symb-except-toplevel.induct*, *auto*)

The two following lemmas give the precise link between the two definitions.

**lemma** *no-T-F-symb-except-toplevel-all-subformula-st-no-T-F-symb*:  
*no-T-F-except-top-level*  $\varphi \implies \varphi \neq FF \implies \varphi \neq FT \implies \text{no-T-F } \varphi$   
**unfolding** *no-T-F-except-top-level-def* *no-T-F-def* **apply** (*induct*  $\varphi$ )  
**using** *no-T-F-symb-fnot* **by** *fastforce*+

**lemma** *no-T-F-no-T-F-except-top-level*:  
*no-T-F*  $\varphi \implies \text{no-T-F-except-top-level } \varphi$   
**unfolding** *no-T-F-except-top-level-def* *no-T-F-def*  
**unfolding** *all-subformula-st-def* **by** *auto*

**lemma** *no-T-F-except-top-level-simp[simp]*: *no-T-F-except-top-level*  $FF$  *no-T-F-except-top-level*  $FT$   
**unfolding** *no-T-F-except-top-level-def* **by** *auto*

**lemma** *no-T-F-no-T-F-except-top-level'[simp]*:  
*no-T-F-except-top-level*  $\varphi \longleftrightarrow (\varphi = FF \vee \varphi = FT \vee \text{no-T-F } \varphi)$   
**using** *no-T-F-symb-except-toplevel-all-subformula-st-no-T-F-symb* *no-T-F-no-T-F-except-top-level*  
**by** *auto*

**lemma** *no-T-F-bin-decomp[simp]*:  
**assumes** *c*:  $c \in \text{binary-connectives}$   
**shows** *no-T-F* (*conn* *c*  $[\varphi, \psi]$ )  $\longleftrightarrow (\text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$

**proof** –

**have** *wf*: *wf-conn* *c*  $[\varphi, \psi]$  **using** *c* **by** *auto*  
**then have** *no-T-F* (*conn* *c*  $[\varphi, \psi]$ )  $\longleftrightarrow (\text{no-T-F-symb } (\text{conn } c [\varphi, \psi]) \wedge \text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$   
**by** (*simp add*: *all-subformula-st-decomp no-T-F-def*)  
**then show** *no-T-F* (*conn* *c*  $[\varphi, \psi]$ )  $\longleftrightarrow (\text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$   
**using** *c* *wf* *all-subformula-st-decomp list.discI no-T-F-def no-T-F-symb-except-toplevel-bin-decom*  
*no-T-F-symb-except-toplevel-no-T-F-symb no-T-F-symb-false(1,2) wf-conn-helper-facts(2,3)*  
*wf-conn-list(1,2)* **by** *metis*

**qed**

**lemma** *no-T-F-bin-decomp-expanded[simp]*:  
**assumes** *c*:  $c = CAnd \vee c = COr \vee c = CEq \vee c = CImp$   
**shows** *no-T-F* (*conn* *c*  $[\varphi, \psi]$ )  $\longleftrightarrow (\text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$   
**using** *no-T-F-bin-decomp assms unfolding binary-connectives-def* **by** *blast*

**lemma** *no-T-F-comp-expanded-explicit[simp]*:  
**fixes**  $\varphi \psi :: 'v \text{ propo}$   
**shows**  
*no-T-F* (*FAnd*  $\varphi \psi$ )  $\longleftrightarrow (\text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$   
*no-T-F* (*FOr*  $\varphi \psi$ )  $\longleftrightarrow (\text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$   
*no-T-F* (*FEq*  $\varphi \psi$ )  $\longleftrightarrow (\text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$   
*no-T-F* (*FImp*  $\varphi \psi$ )  $\longleftrightarrow (\text{no-T-F } \varphi \wedge \text{no-T-F } \psi)$   
**using** *assms conn.simps(5–8) no-T-F-bin-decomp-expanded* **by** (*metis (no-types)*)+

**lemma** *no-T-F-comp-not[simp]*:  
**fixes**  $\varphi \psi :: 'v \text{ propo}$   
**shows** *no-T-F* (*FNot*  $\varphi$ )  $\longleftrightarrow \text{no-T-F } \varphi$

by (metis all-subformula-st-decomp-explicit(3) all-subformula-st-test-symb-true-phi no-T-F-def  
no-T-F-symb-false(1,2) no-T-F-symb-fnot-imp)

**lemma** no-T-F-decomp:

fixes  $\varphi \psi :: 'v \text{ propo}$

assumes  $\varphi$ : no-T-F (FAnd  $\varphi \psi$ )  $\vee$  no-T-F (FOr  $\varphi \psi$ )  $\vee$  no-T-F (FEq  $\varphi \psi$ )  $\vee$  no-T-F (FImp  $\varphi \psi$ )

shows no-T-F  $\psi$  and no-T-F  $\varphi$

using assms by auto

**lemma** no-T-F-decomp-not:

fixes  $\varphi :: 'v \text{ propo}$

assumes  $\varphi$ : no-T-F (FNot  $\varphi$ )

shows no-T-F  $\varphi$

using assms by auto

**lemma** no-T-F-symb-except-toplevel-step-exists:

fixes  $\varphi \psi :: 'v \text{ propo}$

assumes no-equiv  $\varphi$  and no-imp  $\varphi$

shows  $\psi \preceq \varphi \implies \neg \text{no-T-F-symb-except-toplevel } \psi \implies \exists \psi'. \text{elimTB } \psi \psi'$

**proof** (induct  $\psi$  rule: propo-induct-arity)

case (nullary  $\varphi' x$ )

then have False using no-T-F-symb-except-toplevel-true no-T-F-symb-except-toplevel-false by auto

then show ?case by blast

next

case (unary  $\psi$ )

then have  $\psi = FF \vee \psi = FT$  using no-T-F-symb-except-toplevel-not-decom by blast

then show ?case using ElimTB5 ElimTB6 by blast

next

case (binary  $\varphi' \psi1 \psi2$ )

note IH1 = this(1) and IH2 = this(2) and  $\varphi' = \text{this}(3)$  and  $F\varphi = \text{this}(4)$  and  $n = \text{this}(5)$

{

assume  $\varphi' = FImp \psi1 \psi2 \vee \varphi' = FEq \psi1 \psi2$

then have False using  $n F\varphi$  subformula-all-subformula-st assms

by (metis (no-types) no-equiv-eq(1) no-equiv-def no-imp-Imp(1) no-imp-def)

then have ?case by blast

}

moreover {

assume  $\varphi'$ :  $\varphi' = FAnd \psi1 \psi2 \vee \varphi' = FOr \psi1 \psi2$

then have  $\psi1 = FT \vee \psi2 = FT \vee \psi1 = FF \vee \psi2 = FF$

using no-T-F-symb-except-toplevel-bin-decom conn.simps(5,6)  $n$  unfolding binary-connectives-def

by fastforce+

then have ?case using elimTB.intros  $\varphi'$  by blast

}

ultimately show ?case using  $\varphi'$  by blast

qed

**lemma** no-T-F-except-top-level-rew:

fixes  $\varphi :: 'v \text{ propo}$

assumes noTB:  $\neg \text{no-T-F-except-top-level } \varphi$  and no-equiv: no-equiv  $\varphi$  and no-imp: no-imp  $\varphi$

shows  $\exists \psi \psi'. \psi \preceq \varphi \wedge \text{elimTB } \psi \psi'$

**proof** –

have test-symb-false-nullary:  $\forall x. \text{no-T-F-symb-except-toplevel } (FF:: 'v \text{ propo})$

$\wedge \text{no-T-F-symb-except-toplevel } FT \wedge \text{no-T-F-symb-except-toplevel } (FVar (x:: 'v))$  by auto

moreover {

fix  $c:: 'v \text{ connective}$  and  $l:: 'v \text{ propo list}$  and  $\psi:: 'v \text{ propo}$

```

  have H: elimTB (conn c l)  $\psi \implies \neg \text{no-T-F-symb-except-toplevel} (\text{conn c l})$ 
    by (cases (conn c l) rule: elimTB.cases, auto)
}
moreover {
  fix x :: 'v
  have H': no-T-F-except-top-level FT no-T-F-except-top-level FF
    no-T-F-except-top-level (FVar x)
    by (auto simp: no-T-F-except-top-level-def test-symb-false-nullary)
}
moreover {
  fix  $\psi$ 
  have  $\psi \preceq \varphi \implies \neg \text{no-T-F-symb-except-toplevel} \psi \implies \exists \psi'. \text{elimTB } \psi \psi'$ 
    using no-T-F-symb-except-toplevel-step-exists no-equiv no-imp by auto
}
ultimately show ?thesis
  using no-test-symb-step-exists noTB unfolding no-T-F-except-top-level-def by blast
qed

```

**lemma** *elimTB-inv*:

```

  fixes  $\varphi \psi :: 'v \text{ propo}$ 
  assumes full (propo-rew-step elimTB)  $\varphi \psi$ 
  and no-equiv  $\varphi$  and no-imp  $\varphi$ 
  shows no-equiv  $\psi$  and no-imp  $\psi$ 
proof -
  {
    fix  $\varphi \psi :: 'v \text{ propo}$ 
    have H: elimTB  $\varphi \psi \implies \text{no-equiv } \varphi \implies \text{no-equiv } \psi$ 
      by (induct  $\varphi \psi$  rule: elimTB.induct, auto)
  }
  then show no-equiv  $\psi$ 
    using full-propo-rew-step-inv-stay-conn[of elimTB no-equiv-symb  $\varphi \psi$ ]
      no-equiv-symb-conn-characterization assms unfolding no-equiv-def by metis
next
  {
    fix  $\varphi \psi :: 'v \text{ propo}$ 
    have H: elimTB  $\varphi \psi \implies \text{no-imp } \varphi \implies \text{no-imp } \psi$ 
      by (induct  $\varphi \psi$  rule: elimTB.induct, auto)
  }
  then show no-imp  $\psi$ 
    using full-propo-rew-step-inv-stay-conn[of elimTB no-imp-symb  $\varphi \psi$ ] assms
      no-imp-symb-conn-characterization unfolding no-imp-def by metis
qed

```

**lemma** *elimTB-full-propo-rew-step*:

```

  fixes  $\varphi \psi :: 'v \text{ propo}$ 
  assumes no-equiv  $\varphi$  and no-imp  $\varphi$  and full (propo-rew-step elimTB)  $\varphi \psi$ 
  shows no-T-F-except-top-level  $\psi$ 
  using full-propo-rew-step-subformula no-T-F-except-top-level-rew assms elimTB-inv by fastforce

```

## 8.4 PushNeg

Push the negation inside the formula, until the litteral.

**inductive** *pushNeg* **where**

```

PushNeg1[simp]: pushNeg (FNot (FAnd  $\varphi \psi$ )) (FOr (FNot  $\varphi$ ) (FNot  $\psi$ )) |
PushNeg2[simp]: pushNeg (FNot (FOr  $\varphi \psi$ )) (FAnd (FNot  $\varphi$ ) (FNot  $\psi$ )) |

```

*PushNeg3[simp]: pushNeg (FNot (FNot  $\varphi$ ))  $\varphi$*

**lemma** *pushNeg-transformation-consistent:*

$A \models \text{FNot } (\text{FAnd } \varphi \ \psi) \longleftrightarrow A \models (\text{FOr } (\text{FNot } \varphi) \ (\text{FNot } \psi))$

$A \models \text{FNot } (\text{FOr } \varphi \ \psi) \longleftrightarrow A \models (\text{FAnd } (\text{FNot } \varphi) \ (\text{FNot } \psi))$

$A \models \text{FNot } (\text{FNot } \varphi) \longleftrightarrow A \models \varphi$

**by** *auto*

**lemma** *pushNeg-explicit: pushNeg  $\varphi \ \psi \implies \forall A. A \models \varphi \longleftrightarrow A \models \psi$*

**by** (*induct  $\varphi \ \psi$  rule: pushNeg.induct, auto*)

**lemma** *pushNeg-consistent: preserves-un-sat pushNeg*

**unfolding** *preserves-un-sat-def* **by** (*simp add: pushNeg-explicit*)

**lemma** *pushNeg-lifted-consistant:*

*preserves-un-sat (full (propo-rew-step pushNeg))*

**by** (*simp add: pushNeg-consistent*)

**fun** *simple where*

*simple FT = True |*

*simple FF = True |*

*simple (FVar  $-$ ) = True |*

*simple - = False*

**lemma** *simple-decomp:*

*simple  $\varphi \longleftrightarrow (\varphi = \text{FT} \vee \varphi = \text{FF} \vee (\exists x. \varphi = \text{FVar } x))$*

**by** (*cases  $\varphi$  auto*)

**lemma** *subformula-conn-decomp-simple:*

**fixes**  $\varphi \ \psi :: 'v \text{ propo}$

**assumes** *s: simple  $\psi$*

**shows**  $\varphi \preceq \text{FNot } \psi \longleftrightarrow (\varphi = \text{FNot } \psi \vee \varphi = \psi)$

**proof**  $-$

**have**  $\varphi \preceq \text{conn } \text{CNot } [\psi] \longleftrightarrow (\varphi = \text{conn } \text{CNot } [\psi] \vee (\exists \psi \in \text{set } [\psi]. \varphi \preceq \psi))$

**using** *subformula-conn-decomp wf-conn-helper-facts(1)* **by** *metis*

**then show**  $\varphi \preceq \text{FNot } \psi \longleftrightarrow (\varphi = \text{FNot } \psi \vee \varphi = \psi)$  **using** *s* **by** (*auto simp: simple-decomp*)

**qed**

**lemma** *subformula-conn-decomp-explicit[simp]:*

**fixes**  $\varphi :: 'v \text{ propo}$  **and**  $x :: 'v$

**shows**

$\varphi \preceq \text{FNot } \text{FT} \longleftrightarrow (\varphi = \text{FNot } \text{FT} \vee \varphi = \text{FT})$

$\varphi \preceq \text{FNot } \text{FF} \longleftrightarrow (\varphi = \text{FNot } \text{FF} \vee \varphi = \text{FF})$

$\varphi \preceq \text{FNot } (\text{FVar } x) \longleftrightarrow (\varphi = \text{FNot } (\text{FVar } x) \vee \varphi = \text{FVar } x)$

**by** (*auto simp: subformula-conn-decomp-simple*)

**fun** *simple-not-symb where*

*simple-not-symb (FNot  $\varphi$ ) = (simple  $\varphi$ ) |*

*simple-not-symb - = True*

**definition** *simple-not where*

*simple-not* = *all-subformula-st simple-not-symb*

**declare** *simple-not-def*[*simp*]

**lemma** *simple-not-Not*[*simp*]:

¬ *simple-not* (*FNot* (*FAnd*  $\varphi$   $\psi$ ))

¬ *simple-not* (*FNot* (*FOr*  $\varphi$   $\psi$ ))

**by** *auto*

**lemma** *simple-not-step-exists*:

**fixes**  $\varphi \psi :: 'v \text{ propo}$

**assumes** *no-equiv*  $\varphi$  **and** *no-imp*  $\varphi$

**shows**  $\psi \preceq \varphi \implies \neg \text{simple-not-symb } \psi \implies \exists \psi'. \text{pushNeg } \psi \psi'$

**apply** (*induct*  $\psi$ , *auto*)

**apply** (*rename-tac*  $\psi$ , *case-tac*  $\psi$ , *auto intro: pushNeg.intros*)

**by** (*metis* *assms*(1,2) *no-imp-Imp*(1) *no-equiv-eq*(1) *no-imp-def* *no-equiv-def* *subformula-in-subformula-not* *subformula-all-subformula-st*)+

**lemma** *simple-not-rew*:

**fixes**  $\varphi :: 'v \text{ propo}$

**assumes** *noTB*: ¬ *simple-not*  $\varphi$  **and** *no-equiv*: *no-equiv*  $\varphi$  **and** *no-imp*: *no-imp*  $\varphi$

**shows**  $\exists \psi \psi'. \psi \preceq \varphi \wedge \text{pushNeg } \psi \psi'$

**proof** –

**have**  $\forall x. \text{simple-not-symb } (FF :: 'v \text{ propo}) \wedge \text{simple-not-symb } FT \wedge \text{simple-not-symb } (FVar (x :: 'v))$

**by** *auto*

**moreover** {

**fix**  $c :: 'v \text{ connective}$  **and**  $l :: 'v \text{ propo list}$  **and**  $\psi :: 'v \text{ propo}$

**have**  $H: \text{pushNeg } (\text{conn } c \ l) \ \psi \implies \neg \text{simple-not-symb } (\text{conn } c \ l)$

**by** (*cases* (*conn*  $c \ l$ ) *rule: pushNeg.cases*) *auto*

}

**moreover** {

**fix**  $x :: 'v$

**have**  $H': \text{simple-not } FT \ \text{simple-not } FF \ \text{simple-not } (FVar \ x)$

**by** *simp-all*

}

**moreover** {

**fix**  $\psi :: 'v \text{ propo}$

**have**  $\psi \preceq \varphi \implies \neg \text{simple-not-symb } \psi \implies \exists \psi'. \text{pushNeg } \psi \psi'$

**using** *simple-not-step-exists* *no-equiv* *no-imp* **by** *blast*

}

**ultimately show** *?thesis* **using** *no-test-symb-step-exists* *noTB* **unfolding** *simple-not-def* **by** *blast*

**qed**

**lemma** *no-T-F-except-top-level-pushNeg1*:

*no-T-F-except-top-level* (*FNot* (*FAnd*  $\varphi$   $\psi$ ))  $\implies$  *no-T-F-except-top-level* (*FOr* (*FNot*  $\varphi$ ) (*FNot*  $\psi$ ))

**using** *no-T-F-symb-except-toplevel-all-subformula-st-no-T-F-symb* *no-T-F-comp-not* *no-T-F-decomp*(1)

*no-T-F-decomp*(2) *no-T-F-no-T-F-except-top-level* **by** (*metis* *no-T-F-comp-expanded-explicit*(2)

*propo.distinct*(5,17))

**lemma** *no-T-F-except-top-level-pushNeg2*:

*no-T-F-except-top-level* (*FNot* (*FOr*  $\varphi$   $\psi$ ))  $\implies$  *no-T-F-except-top-level* (*FAnd* (*FNot*  $\varphi$ ) (*FNot*  $\psi$ ))

**by** *auto*

**lemma** *no-T-F-symb-pushNeg*:

*no-T-F-symb* (*FOr* (*FNot*  $\varphi'$ ) (*FNot*  $\psi'$ ))

*no-T-F-symb* (*FAnd* (*FNot*  $\varphi'$ ) (*FNot*  $\psi'$ ))



*no-T-F-symb* (*FNot* (*FNot*  $\varphi'$ ))  
 by *auto*

**lemma** *propo-rew-step-pushNeg-no-T-F-symb*:

*propo-rew-step pushNeg*  $\varphi \psi \implies \text{no-T-F-except-top-level } \varphi \implies \text{no-T-F-symb } \varphi \implies \text{no-T-F-symb } \psi$   
**apply** (*induct rule*: *propo-rew-step.induct*)  
**apply** (*cases rule*: *pushNeg.cases*)  
**apply** *simp-all*  
**apply** (*metis no-T-F-symb-pushNeg*(1))  
**apply** (*metis no-T-F-symb-pushNeg*(2))  
**apply** (*simp, metis all-subformula-st-test-symb-true-phi no-T-F-def*)

**proof** –

**fix**  $\varphi \varphi'$ : 'a *propo* **and**  $c$ :: 'a *connective* **and**  $\xi \xi'$ :: 'a *propo list*  
**assume** *rel*: *propo-rew-step pushNeg*  $\varphi \varphi'$   
**and** *IH*: *no-T-F*  $\varphi \implies \text{no-T-F-symb } \varphi \implies \text{no-T-F-symb } \varphi'$   
**and** *wf*: *wf-conn*  $c (\xi @ \varphi \# \xi')$   
**and**  $n$ : *conn*  $c (\xi @ \varphi \# \xi') = FF \vee \text{conn } c (\xi @ \varphi \# \xi') = FT \vee \text{no-T-F } (\text{conn } c (\xi @ \varphi \# \xi'))$   
**and**  $x$ :  $c \neq CF \wedge c \neq CT \wedge \varphi \neq FF \wedge \varphi \neq FT \wedge (\forall \psi \in \text{set } \xi \cup \text{set } \xi'. \psi \neq FF \wedge \psi \neq FT)$   
**then have**  $c \neq CF \wedge c \neq CT \wedge \text{wf-conn } c (\xi @ \varphi' \# \xi')$   
**using** *wf-conn-no-arity-change-helper wf-conn-no-arity-change* **by** *metis*  
**moreover have**  $n'$ : *no-T-F* (*conn*  $c (\xi @ \varphi \# \xi')$ ) **using**  $n$  **by** (*simp add*: *wf wf-conn-list*(1,2))  
**moreover**  
 {  
**have** *no-T-F*  $\varphi$   
**by** (*metis Un-iff all-subformula-st-decomp list.set-intros*(1)  $n'$  *wf no-T-F-def set-append*)  
**moreover then have** *no-T-F-symb*  $\varphi$   
**by** (*simp add*: *all-subformula-st-test-symb-true-phi no-T-F-def*)  
**ultimately have**  $\varphi' \neq FF \wedge \varphi' \neq FT$   
**using** *IH no-T-F-symb-false*(1) *no-T-F-symb-false*(2) **by** *blast*  
**then have**  $\forall \psi \in \text{set } (\xi @ \varphi' \# \xi'). \psi \neq FF \wedge \psi \neq FT$  **using**  $x$  **by** *auto*  
 }  
**ultimately show** *no-T-F-symb* (*conn*  $c (\xi @ \varphi' \# \xi')$ ) **by** (*simp add*:  $x$ )

**qed**

**lemma** *propo-rew-step-pushNeg-no-T-F*:

*propo-rew-step pushNeg*  $\varphi \psi \implies \text{no-T-F } \varphi \implies \text{no-T-F } \psi$

**proof** (*induct rule*: *propo-rew-step.induct*)

**case** *global-rel*

**then show** ?*case*

**by** (*metis* (*no-types, lifting*) *no-T-F-symb-except-toplevel-all-subformula-st-no-T-F-symb*  
*no-T-F-def no-T-F-except-top-level-pushNeg1 no-T-F-except-top-level-pushNeg2*  
*no-T-F-no-T-F-except-top-level all-subformula-st-decomp-explicit*(3) *pushNeg.simps*  
*simple.simps*(1,2,5,6))

**next**

**case** (*propo-rew-one-step-lift*  $\varphi \varphi' c \xi \xi'$ )  
**note** *rel* = *this*(1) **and** *IH* = *this*(2) **and** *wf* = *this*(3) **and** *no-T-F* = *this*(4)  
**moreover have**  $wf'$ : *wf-conn*  $c (\xi @ \varphi' \# \xi')$   
**using** *wf-conn-no-arity-change wf-conn-no-arity-change-helper wf* **by** *metis*  
**ultimately show** *no-T-F* (*conn*  $c (\xi @ \varphi' \# \xi')$ )  
**using** *all-subformula-st-test-symb-true-phi*  
**by** (*fastforce simp*: *no-T-F-def all-subformula-st-decomp wf wf'*)

**qed**

**lemma** *pushNeg-inv*:

```

fixes  $\varphi \psi :: 'v \text{ propo}$ 
assumes full (propo-rew-step pushNeg)  $\varphi \psi$ 
and no-equiv  $\varphi$  and no-imp  $\varphi$  and no-T-F-except-top-level  $\varphi$ 
shows no-equiv  $\psi$  and no-imp  $\psi$  and no-T-F-except-top-level  $\psi$ 
proof -
{
  fix  $\varphi \psi :: 'v \text{ propo}$ 
  assume rel: propo-rew-step pushNeg  $\varphi \psi$ 
  and no: no-T-F-except-top-level  $\varphi$ 
  then have no-T-F-except-top-level  $\psi$ 
  proof -
    {
      assume  $\varphi = FT \vee \varphi = FF$ 
      from rel this have False
      apply (induct rule: propo-rew-step.induct)
      using pushNeg.cases apply blast
      using wf-conn-list(1) wf-conn-list(2) by auto
      then have no-T-F-except-top-level  $\psi$  by blast
    }
    moreover {
      assume  $\varphi \neq FT \wedge \varphi \neq FF$ 
      then have no-T-F  $\varphi$ 
      by (metis no no-T-F-symb-except-toplevel-all-subformula-st-no-T-F-symb)
      then have no-T-F  $\psi$ 
      using propo-rew-step-pushNeg-no-T-F rel by auto
      then have no-T-F-except-top-level  $\psi$  by (simp add: no-T-F-no-T-F-except-top-level)
    }
    ultimately show no-T-F-except-top-level  $\psi$  by metis
  qed
}
moreover {
  fix  $c :: 'v \text{ connective}$  and  $\xi \xi' :: 'v \text{ propo list}$  and  $\zeta \zeta' :: 'v \text{ propo}$ 
  assume rel: propo-rew-step pushNeg  $\zeta \zeta'$ 
  and incl:  $\zeta \preceq \varphi$ 
  and corr: wf-conn  $c (\xi @ \zeta \# \xi')$ 
  and no-T-F: no-T-F-symb-except-toplevel (conn  $c (\xi @ \zeta \# \xi')$ )
  and n: no-T-F-symb-except-toplevel  $\zeta'$ 
  have no-T-F-symb-except-toplevel (conn  $c (\xi @ \zeta' \# \xi')$ )
  proof
    have p: no-T-F-symb (conn  $c (\xi @ \zeta \# \xi')$ )
    using corr wf-conn-list(1) wf-conn-list(2) no-T-F-symb-except-toplevel-no-T-F-symb no-T-F
    by blast
    have l:  $\forall \varphi \in \text{set } (\xi @ \zeta \# \xi'). \varphi \neq FT \wedge \varphi \neq FF$ 
    using corr wf-conn-no-T-F-symb-iff p by blast
    from rel incl have  $\zeta' \neq FT \wedge \zeta' \neq FF$ 
    apply (induction  $\zeta \zeta'$  rule: propo-rew-step.induct)
    apply (cases rule: pushNeg.cases, auto)
    by (metis assms(4) no-T-F-symb-except-top-level-false-not no-T-F-except-top-level-def
      all-subformula-st-test-symb-true-phi subformula-in-subformula-not
      subformula-all-subformula-st append-is-Nil-conv list.distinct(1)
      wf-conn-no-arity-change-helper wf-conn-list(1,2) wf-conn-no-arity-change)
    then have  $\forall \varphi \in \text{set } (\xi @ \zeta' \# \xi'). \varphi \neq FT \wedge \varphi \neq FF$  using l by auto
    moreover have  $c \neq CT \wedge c \neq CF$  using corr by auto
    ultimately show no-T-F-symb (conn  $c (\xi @ \zeta' \# \xi')$ )
    by (metis corr no-T-F-symb-comp wf-conn-no-arity-change wf-conn-no-arity-change-helper)
  qed
}

```

```

    qed
  }
ultimately show no-T-F-except-top-level  $\psi$ 
  using full-propo-rew-step-inv-stay-with-inc[of pushNeg no-T-F-symb-except-toplevel  $\varphi$ ] assms
  subformula-refl unfolding no-T-F-except-top-level-def full-unfold by metis
next
{
  fix  $\varphi \psi :: 'v \text{ propo}$ 
  have  $H: \text{pushNeg } \varphi \psi \implies \text{no-equiv } \varphi \implies \text{no-equiv } \psi$ 
    by (induct  $\varphi \psi$  rule: pushNeg.induct, auto)
}
then show no-equiv  $\psi$ 
  using full-propo-rew-step-inv-stay-conn[of pushNeg no-equiv-symb  $\varphi \psi$ ]
  no-equiv-symb-conn-characterization assms unfolding no-equiv-def full-unfold by metis
next
{
  fix  $\varphi \psi :: 'v \text{ propo}$ 
  have  $H: \text{pushNeg } \varphi \psi \implies \text{no-imp } \varphi \implies \text{no-imp } \psi$ 
    by (induct  $\varphi \psi$  rule: pushNeg.induct, auto)
}
then show no-imp  $\psi$ 
  using full-propo-rew-step-inv-stay-conn[of pushNeg no-imp-symb  $\varphi \psi$ ] assms
  no-imp-symb-conn-characterization unfolding no-imp-def full-unfold by metis
qed

```

**lemma** *pushNeg-full-propo-rew-step*:  
**fixes**  $\varphi \psi :: 'v \text{ propo}$   
**assumes**  
 no-equiv  $\varphi$  **and**  
 no-imp  $\varphi$  **and**  
 full (propo-rew-step pushNeg)  $\varphi \psi$  **and**  
 no-T-F-except-top-level  $\varphi$   
**shows** simple-not  $\psi$   
**using** assms full-propo-rew-step-subformula pushNeg-inv(1,2) simple-not-rew **by** blast

## 8.5 Push inside

**inductive** *push-conn-inside* ::  $'v \text{ connective} \Rightarrow 'v \text{ connective} \Rightarrow 'v \text{ propo} \Rightarrow 'v \text{ propo} \Rightarrow \text{bool}$   
**for**  $c c' :: 'v \text{ connective}$  **where**  
*push-conn-inside-l[simp]*:  $c = CAnd \vee c = COr \implies c' = CAnd \vee c' = COr$   
 $\implies \text{push-conn-inside } c c' (\text{conn } c [\text{conn } c' [\varphi 1, \varphi 2], \psi])$   
 $(\text{conn } c' [\text{conn } c [\varphi 1, \psi], \text{conn } c [\varphi 2, \psi]]) \mid$   
*push-conn-inside-r[simp]*:  $c = CAnd \vee c = COr \implies c' = CAnd \vee c' = COr$   
 $\implies \text{push-conn-inside } c c' (\text{conn } c [\psi, \text{conn } c' [\varphi 1, \varphi 2]])$   
 $(\text{conn } c' [\text{conn } c [\psi, \varphi 1], \text{conn } c [\psi, \varphi 2]])$

**lemma** *push-conn-inside-explicit*:  $\text{push-conn-inside } c c' \varphi \psi \implies \forall A. A \models \varphi \longleftrightarrow A \models \psi$   
**by** (induct  $\varphi \psi$  rule: push-conn-inside.induct, auto)

**lemma** *push-conn-inside-consistent*: preserves-un-sat (push-conn-inside  $c c'$ )  
**unfolding** preserves-un-sat-def **by** (simp add: push-conn-inside-explicit)

**lemma** *propo-rew-step-push-conn-inside[simp]*:  
 $\neg \text{propo-rew-step } (\text{push-conn-inside } c c') \text{ FT } \psi \neg \text{propo-rew-step } (\text{push-conn-inside } c c') \text{ FF } \psi$

```

proof –
{
  {
    fix  $\varphi \psi$ 
    have push-conn-inside  $c \ c' \ \varphi \ \psi \implies \varphi = FT \vee \varphi = FF \implies False$ 
      by (induct rule: push-conn-inside.induct, auto)
    } note  $H = this$ 
  } fix  $\varphi$ 
  have propo-rew-step (push-conn-inside  $c \ c'$ )  $\varphi \ \psi \implies \varphi = FT \vee \varphi = FF \implies False$ 
    apply (induct rule: propo-rew-step.induct, auto simp: wf-conn-list(1) wf-conn-list(2))
    using  $H$  by blast+
  }
then show
   $\neg$ propo-rew-step (push-conn-inside  $c \ c'$ )  $FT \ \psi$ 
   $\neg$ propo-rew-step (push-conn-inside  $c \ c'$ )  $FF \ \psi$  by blast+
qed

```

**inductive** *not-c-in-c'-symb*:: '*v* *connective*  $\Rightarrow$  '*v* *connective*  $\Rightarrow$  '*v* *propo*  $\Rightarrow$  *bool* **for**  $c \ c'$  **where**  
*not-c-in-c'-symb-l*[*simp*]: *wf-conn*  $c \ [conn \ c' \ [\varphi, \varphi'], \psi] \implies wf-conn \ c' \ [\varphi, \varphi']$   
 $\implies not-c-in-c'-symb \ c \ c' \ (conn \ c \ [conn \ c' \ [\varphi, \varphi'], \psi]) \mid$   
*not-c-in-c'-symb-r*[*simp*]: *wf-conn*  $c \ [\psi, conn \ c' \ [\varphi, \varphi']] \implies wf-conn \ c' \ [\varphi, \varphi']$   
 $\implies not-c-in-c'-symb \ c \ c' \ (conn \ c \ [\psi, conn \ c' \ [\varphi, \varphi']])$

**abbreviation** *c-in-c'-symb*  $c \ c' \ \varphi \equiv \neg not-c-in-c'-symb \ c \ c' \ \varphi$

**lemma** *c-in-c'-symb-simp*:  
 $not-c-in-c'-symb \ c \ c' \ \xi \implies \xi = FF \vee \xi = FT \vee \xi = FVar \ x \vee \xi = FNot \ FF \vee \xi = FNot \ FT$   
 $\vee \xi = FNot \ (FVar \ x) \implies False$   
**apply** (*induct rule*: *not-c-in-c'-symb.induct*, *auto simp*: *wf-conn.simps* *wf-conn-list*(1–3))  
**using** *conn-inj-not*(2) *wf-conn-binary* **unfolding** *binary-connectives-def* **by** *fastforce*+

**lemma** *c-in-c'-symb-simp'*[*simp*]:  
 $\neg not-c-in-c'-symb \ c \ c' \ FF$   
 $\neg not-c-in-c'-symb \ c \ c' \ FT$   
 $\neg not-c-in-c'-symb \ c \ c' \ (FVar \ x)$   
 $\neg not-c-in-c'-symb \ c \ c' \ (FNot \ FF)$   
 $\neg not-c-in-c'-symb \ c \ c' \ (FNot \ FT)$   
 $\neg not-c-in-c'-symb \ c \ c' \ (FNot \ (FVar \ x))$   
**using** *c-in-c'-symb-simp* **by** *metis*+

**definition** *c-in-c'-only* **where**  
*c-in-c'-only*  $c \ c' \equiv all-subformula-st \ (c-in-c'-symb \ c \ c')$

**lemma** *c-in-c'-only-simp*[*simp*]:  
 $c-in-c'-only \ c \ c' \ FF$   
 $c-in-c'-only \ c \ c' \ FT$   
 $c-in-c'-only \ c \ c' \ (FVar \ x)$   
 $c-in-c'-only \ c \ c' \ (FNot \ FF)$   
 $c-in-c'-only \ c \ c' \ (FNot \ FT)$   
 $c-in-c'-only \ c \ c' \ (FNot \ (FVar \ x))$   
**unfolding** *c-in-c'-only-def* **by** *auto*

**lemma** *not-c-in-c'-symb-commute*:

$\text{not-c-in-c'-symb } c \ c' \ \xi \implies \text{wf-conn } c \ [\varphi, \psi] \implies \xi = \text{conn } c \ [\varphi, \psi]$   
 $\implies \text{not-c-in-c'-symb } c \ c' \ (\text{conn } c \ [\psi, \varphi])$

**proof** (*induct rule: not-c-in-c'-symb.induct*)

**case** (*not-c-in-c'-symb-r*  $\varphi' \ \varphi'' \ \psi'$ ) **note**  $H = \text{this}$

**then have**  $\psi: \psi = \text{conn } c' \ [\varphi'', \psi']$  **using** *conn-inj* **by** *auto*

**have**  $\text{wf-conn } c \ [\text{conn } c' \ [\varphi'', \psi'], \varphi]$

**using**  $H(1)$  *wf-conn-no-arity-change length-Cons* **by** *metis*

**then show**  $\text{not-c-in-c'-symb } c \ c' \ (\text{conn } c \ [\psi, \varphi])$

**unfolding**  $\psi$  **using** *not-c-in-c'-symb.intros(1)*  $H$  **by** *auto*

**next**

**case** (*not-c-in-c'-symb-l*  $\varphi' \ \varphi'' \ \psi'$ ) **note**  $H = \text{this}$

**then have**  $\varphi = \text{conn } c' \ [\varphi', \varphi']$  **using** *conn-inj* **by** *auto*

**moreover have**  $\text{wf-conn } c \ [\psi', \text{conn } c' \ [\varphi', \varphi']]$

**using**  $H(1)$  *wf-conn-no-arity-change length-Cons* **by** *metis*

**ultimately show**  $\text{not-c-in-c'-symb } c \ c' \ (\text{conn } c \ [\psi, \varphi])$

**using** *not-c-in-c'-symb.intros(2)* *conn-inj not-c-in-c'-symb-l.hyps*

*not-c-in-c'-symb-l.prem(1,2)* **by** *blast*

**qed**

**lemma** *not-c-in-c'-symb-commute'*:

$\text{wf-conn } c \ [\varphi, \psi] \implies \text{c-in-c'-symb } c \ c' \ (\text{conn } c \ [\varphi, \psi]) \longleftrightarrow \text{c-in-c'-symb } c \ c' \ (\text{conn } c \ [\psi, \varphi])$

**using** *not-c-in-c'-symb-commute wf-conn-no-arity-change* **by** (*metis length-Cons*)

**lemma** *not-c-in-c'-comm*:

**assumes** *wf*:  $\text{wf-conn } c \ [\varphi, \psi]$

**shows**  $\text{c-in-c'-only } c \ c' \ (\text{conn } c \ [\varphi, \psi]) \longleftrightarrow \text{c-in-c'-only } c \ c' \ (\text{conn } c \ [\psi, \varphi])$  (**is**  $?A \longleftrightarrow ?B$ )

**proof** –

**have**  $?A \longleftrightarrow (\text{c-in-c'-symb } c \ c' \ (\text{conn } c \ [\varphi, \psi])$

$\wedge (\forall \xi \in \text{set } [\varphi, \psi]. \text{all-subformula-st } (\text{c-in-c'-symb } c \ c') \ \xi))$

**using** *all-subformula-st-decomp wf* **unfolding** *c-in-c'-only-def* **by** *fastforce*

**also have**  $\dots \longleftrightarrow (\text{c-in-c'-symb } c \ c' \ (\text{conn } c \ [\psi, \varphi])$

$\wedge (\forall \xi \in \text{set } [\psi, \varphi]. \text{all-subformula-st } (\text{c-in-c'-symb } c \ c') \ \xi))$

**using** *not-c-in-c'-symb-commute' wf* **by** *auto*

**also**

**have**  $\text{wf-conn } c \ [\psi, \varphi]$  **using** *wf-conn-no-arity-change wf* **by** (*metis length-Cons*)

**then have**  $(\text{c-in-c'-symb } c \ c' \ (\text{conn } c \ [\psi, \varphi])$

$\wedge (\forall \xi \in \text{set } [\psi, \varphi]. \text{all-subformula-st } (\text{c-in-c'-symb } c \ c') \ \xi))$

$\longleftrightarrow ?B$

**using** *all-subformula-st-decomp* **unfolding** *c-in-c'-only-def* **by** *fastforce*

**finally show** *?thesis* .

**qed**

**lemma** *not-c-in-c'-simp[simp]*:

**fixes**  $\varphi1 \ \varphi2 \ \psi :: 'v \ \text{propo}$  **and**  $x :: 'v$

**shows**

$\text{c-in-c'-symb } c \ c' \ FT$

$\text{c-in-c'-symb } c \ c' \ FF$

$\text{c-in-c'-symb } c \ c' \ (FVar \ x)$

$\text{wf-conn } c \ [\text{conn } c' \ [\varphi1, \varphi2], \psi] \implies \text{wf-conn } c' \ [\varphi1, \varphi2]$

$\implies \neg \text{c-in-c'-only } c \ c' \ (\text{conn } c \ [\text{conn } c' \ [\varphi1, \varphi2], \psi])$

**apply** (*simp-all add: c-in-c'-only-def*)

**using** *all-subformula-st-test-symb-true-phi not-c-in-c'-symb-l* **by** *blast*

**lemma** *c-in-c'-symb-not[simp]*:

fixes  $c\ c' :: 'v\ connective$  and  $\psi :: 'v\ propo$   
 shows  $c\text{-in-}c'\text{-symb}\ c\ c' (FNot\ \psi)$

proof –

```
{
  fix  $\xi :: 'v\ propo$ 
  have  $not\text{-}c\text{-in-}c'\text{-symb}\ c\ c' (FNot\ \psi) \implies False$ 
    apply (induct  $FNot\ \psi$  rule:  $not\text{-}c\text{-in-}c'\text{-symb}.\text{induct}$ )
    using  $conn\text{-}inj\text{-}not(2)$  by blast+
}
```

then show *?thesis* by auto

qed

lemma  $c\text{-in-}c'\text{-symb}\text{-step}\text{-exists}$ :

fixes  $\varphi :: 'v\ propo$   
 assumes  $c: c = CAnd \vee c = COr$  and  $c': c' = CAnd \vee c' = COr$   
 shows  $\psi \preceq \varphi \implies \neg c\text{-in-}c'\text{-symb}\ c\ c' \psi \implies \exists \psi'. \text{push-conn-inside}\ c\ c' \psi \psi'$   
 apply (induct  $\psi$  rule:  $propo\text{-induct-arity}$ )  
 apply auto[2]

proof –

```
fix  $\psi1\ \psi2\ \varphi' :: 'v\ propo$ 
assume  $IH\psi1: \psi1 \preceq \varphi \implies \neg c\text{-in-}c'\text{-symb}\ c\ c' \psi1 \implies \text{Ex}(\text{push-conn-inside}\ c\ c' \psi1)$ 
and  $IH\psi2: \psi2 \preceq \varphi \implies \neg c\text{-in-}c'\text{-symb}\ c\ c' \psi2 \implies \text{Ex}(\text{push-conn-inside}\ c\ c' \psi2)$ 
and  $\varphi': \varphi' = FAnd\ \psi1\ \psi2 \vee \varphi' = FOr\ \psi1\ \psi2 \vee \varphi' = FImp\ \psi1\ \psi2 \vee \varphi' = FEq\ \psi1\ \psi2$ 
and  $in\varphi: \varphi' \preceq \varphi$  and  $n0: \neg c\text{-in-}c'\text{-symb}\ c\ c' \varphi'$ 
then have  $n: not\text{-}c\text{-in-}c'\text{-symb}\ c\ c' \varphi'$  by auto
```

```
{
  assume  $\varphi': \varphi' = \text{conn}\ c\ [\psi1, \psi2]$ 
  obtain  $a\ b$  where  $\psi1 = \text{conn}\ c'\ [a, b] \vee \psi2 = \text{conn}\ c'\ [a, b]$ 
    using  $n\ \varphi'$  apply (induct rule:  $not\text{-}c\text{-in-}c'\text{-symb}.\text{induct}$ )
    using  $c$  by force+
  then have  $\text{Ex}(\text{push-conn-inside}\ c\ c' \varphi')$ 
    unfolding  $\varphi'$  apply auto
    using  $\text{push-conn-inside.intros}(1)\ c\ c'$  apply blast
    using  $\text{push-conn-inside.intros}(2)\ c\ c'$  by blast
}
```

```
moreover {
  assume  $\varphi': \varphi' \neq \text{conn}\ c\ [\psi1, \psi2]$ 
  have  $\forall \varphi\ c\ ca. \exists \varphi1\ \psi1\ \psi2\ \psi1'\ \psi2'\ \varphi2'. \text{conn}\ (c::'v\ connective)\ [\varphi1, \text{conn}\ ca\ [\psi1, \psi2]] = \varphi$ 
     $\vee \text{conn}\ c\ [\text{conn}\ ca\ [\psi1', \psi2'], \varphi2'] = \varphi \vee c\text{-in-}c'\text{-symb}\ c\ ca\ \varphi$ 
    by (metis  $not\text{-}c\text{-in-}c'\text{-symb}.\text{cases}$ )
  then have  $\text{Ex}(\text{push-conn-inside}\ c\ c' \varphi')$ 
    by (metis (no-types)  $c\ c'\ n\ \text{push-conn-inside-l}\ \text{push-conn-inside-r}$ )
}
```

ultimately show  $\text{Ex}(\text{push-conn-inside}\ c\ c' \varphi')$  by blast

qed

lemma  $c\text{-in-}c'\text{-symb}\text{-rew}$ :

fixes  $\varphi :: 'v\ propo$   
 assumes  $noTB: \neg c\text{-in-}c'\text{-only}\ c\ c' \varphi$   
 and  $c: c = CAnd \vee c = COr$  and  $c': c' = CAnd \vee c' = COr$   
 shows  $\exists \psi\ \psi'. \psi \preceq \varphi \wedge \text{push-conn-inside}\ c\ c' \psi \psi'$

proof –

```
have  $test\text{-symb-false-nullary}$ :
   $\forall x. c\text{-in-}c'\text{-symb}\ c\ c' (FF:: 'v\ propo) \wedge c\text{-in-}c'\text{-symb}\ c\ c' FT$ 
```

```

     $\wedge c\text{-in-}c'\text{-symb } c \ c' \ (FVar \ (x:: 'v))$ 
  by auto
moreover {
  fix x :: 'v
  have  $H': c\text{-in-}c'\text{-symb } c \ c' \ FT \ c\text{-in-}c'\text{-symb } c \ c' \ FF \ c\text{-in-}c'\text{-symb } c \ c' \ (FVar \ x)$ 
    by simp+
}
moreover {
  fix  $\psi :: 'v \ propo$ 
  have  $\psi \preceq \varphi \implies \neg c\text{-in-}c'\text{-symb } c \ c' \ \psi \implies \exists \psi'. \text{push-conn-inside } c \ c' \ \psi \ \psi'$ 
    by (auto simp: assms(2) c' c-in-c'-symb-step-exists)
}
ultimately show ?thesis using noTB no-test-symb-step-exists[of c-in-c'-symb c c']
  unfolding c-in-c'-only-def by metis
qed

```

**lemma** *push-conn-insidec-in-c'-symb-no-T-F*:

```

  fixes  $\varphi \ \psi :: 'v \ propo$ 
  shows  $\text{propo-rew-step } (\text{push-conn-inside } c \ c') \ \varphi \ \psi \implies \text{no-T-F } \varphi \implies \text{no-T-F } \psi$ 
proof (induct rule: propo-rew-step.induct)
  case (global-rel  $\varphi \ \psi$ )
  then show  $\text{no-T-F } \psi$ 
    by (cases rule: push-conn-inside.cases, auto)

```

**next**

```

  case (propo-rew-one-step-lift  $\varphi \ \varphi' \ c \ \xi \ \xi'$ )
  note rel = this(1) and IH = this(2) and wf = this(3) and no-T-F = this(4)
  have  $\text{no-T-F } \varphi$ 
    using wf no-T-F no-T-F-def subformula-into-subformula subformula-all-subformula-st
    subformula-refl by (metis (no-types) in-set-conv-decomp)
  then have  $\varphi': \text{no-T-F } \varphi'$  using IH by blast

```

```

  have  $\forall \zeta \in \text{set } (\xi @ \varphi \ \# \ \xi'). \text{no-T-F } \zeta$  by (metis wf no-T-F no-T-F-def all-subformula-st-decomp)
  then have  $n: \forall \zeta \in \text{set } (\xi @ \varphi' \ \# \ \xi'). \text{no-T-F } \zeta$  using  $\varphi'$  by auto
  then have  $n': \forall \zeta \in \text{set } (\xi @ \varphi' \ \# \ \xi'). \zeta \neq FF \wedge \zeta \neq FT$ 
    using  $\varphi'$  by (metis no-T-F-symb-false(1) no-T-F-symb-false(2) no-T-F-def
    all-subformula-st-test-symb-true-phi)

```

```

  have  $\text{wf}': \text{wf-conn } c \ (\xi @ \varphi' \ \# \ \xi')$ 
    using wf wf-conn-no-arity-change by (metis wf-conn-no-arity-change-helper)

```

```

  {
    fix x :: 'v
    assume  $c = CT \vee c = CF \vee c = CVar \ x$ 
    then have False using wf by auto
    then have  $\text{no-T-F } (\text{conn } c \ (\xi @ \varphi' \ \# \ \xi'))$  by blast
  }

```

```

moreover {
  assume  $c: c = CNot$ 
  then have  $\xi = [] \ \xi' = []$  using wf by auto
  then have  $\text{no-T-F } (\text{conn } c \ (\xi @ \varphi' \ \# \ \xi'))$ 
    using c by (metis  $\varphi'$  conn.simps(4) no-T-F-symb-false(1,2) no-T-F-symb-fnot no-T-F-def
    all-subformula-st-decomp-explicit(3) all-subformula-st-test-symb-true-phi self-append-conv2)
}

```

```

moreover {
  assume  $c: c \in \text{binary-connectives}$ 
  then have  $\text{no-T-F-symb } (\text{conn } c \ (\xi @ \varphi' \ \# \ \xi'))$  using  $\text{wf}' \ n' \ \text{no-T-F-symb.simps}$  by fastforce

```

```

    then have no-T-F (conn c (ξ @ φ' # ξ'))
      by (metis all-subformula-st-decomp-imp wf' n no-T-F-def)
  }
  ultimately show no-T-F (conn c (ξ @ φ' # ξ')) using connective-cases-arity by auto
qed

```

**lemma** *simple-propo-rew-step-push-conn-inside-inv*:

```

propo-rew-step (push-conn-inside c c') φ ψ ⇒ simple φ ⇒ simple ψ
  apply (induct rule: propo-rew-step.induct)
  apply (rename-tac φ, case-tac φ, auto simp: push-conn-inside.simps)[]
  by (metis append-is-Nil-conv list.distinct(1) simple.elims(2) wf-conn-list(1-3))

```

**lemma** *simple-propo-rew-step-inv-push-conn-inside-simple-not*:

```

fixes c c' :: 'v connective and φ ψ :: 'v propo
shows propo-rew-step (push-conn-inside c c') φ ψ ⇒ simple-not φ ⇒ simple-not ψ
proof (induct rule: propo-rew-step.induct)
  case (global-rel φ ψ)
  then show ?case by (cases φ, auto simp: push-conn-inside.simps)
next
  case (propo-rew-one-step-lift φ φ' ca ξ ξ') note rew = this(1) and IH = this(2) and wf = this(3)
  and simple = this(4)
  show ?case
    proof (cases ca rule: connective-cases-arity)
      case nullary
      then show ?thesis using propo-rew-one-step-lift by auto
    next
      case binary note ca = this
      obtain a b where ab: ξ @ φ' # ξ' = [a, b]
      using wf ca list-length2-decomp wf-conn-bin-list-length
      by (metis (no-types) wf-conn-no-arity-change-helper)
      have ∀ ζ ∈ set (ξ @ φ # ξ'). simple-not ζ
      by (metis wf all-subformula-st-decomp simple simple-not-def)
      then have ∀ ζ ∈ set (ξ @ φ' # ξ'). simple-not ζ using IH by simp
      moreover have simple-not-symb (conn ca (ξ @ φ' # ξ')) using ca
      by (metis ab conn.simps(5-8) helper-fact simple-not-symb.simps(5) simple-not-symb.simps(6)
        simple-not-symb.simps(7) simple-not-symb.simps(8))
      ultimately show ?thesis
      by (simp add: ab all-subformula-st-decomp ca)
    next
      case unary
      then show ?thesis
        using rew simple-propo-rew-step-push-conn-inside-inv[OF rew] IH local.wf simple by auto
  qed
qed

```

**lemma** *propo-rew-step-push-conn-inside-simple-not*:

```

fixes φ φ' :: 'v propo and ξ ξ' :: 'v propo list and c :: 'v connective
assumes
  propo-rew-step (push-conn-inside c c') φ φ' and
  wf-conn c (ξ @ φ # ξ') and
  simple-not-symb (conn c (ξ @ φ # ξ')) and
  simple-not-symb φ'
shows simple-not-symb (conn c (ξ @ φ' # ξ'))

```



```

using assms
proof (induction rule: propo-rew-step.induct)
print-cases
case (global-rel)
then show ?case
by (metis conn.simps(12,17) list.discI push-conn-inside.cases simple-not-symb.elims(3)
wf-conn-helper-facts(5) wf-conn-list(2) wf-conn-list(8) wf-conn-no-arity-change
wf-conn-no-arity-change-helper)
next
case (propo-rew-one-step-lift  $\varphi$   $\varphi'$   $c'$   $\chi s$   $\chi s'$ ) note tel = this(1) and wf = this(2) and
IH = this(3) and wf' = this(4) and simple' = this(5) and simple = this(6)
then show ?case
proof (cases  $c'$  rule: connective-cases-arity)
case nullary
then show ?thesis using wf simple simple' by auto
next
case binary note  $c = \text{this}(1)$ 
have corr': wf-conn  $c$  ( $\xi @ \text{conn } c' (\chi s @ \varphi' \# \chi s') \# \xi'$ )
using wf wf-conn-no-arity-change
by (metis wf' wf-conn-no-arity-change-helper)
then show ?thesis
using  $c$  propo-rew-one-step-lift wf
by (metis conn.simps(17) connective.distinct(37) propo-rew-step-subformula-imp
push-conn-inside.cases simple-not-symb.elims(3) wf-conn.simps wf-conn-list(2,8))
next
case unary
then have empty:  $\chi s = []$   $\chi s' = []$  using wf by auto
then show ?thesis using simple unary simple' wf wf'
by (metis connective.distinct(37) connective.distinct(39) propo-rew-step-subformula-imp
push-conn-inside.cases simple-not-symb.elims(3) tel wf-conn-list(8)
wf-conn-no-arity-change wf-conn-no-arity-change-helper)
qed
qed

```

**lemma** *push-conn-inside-not-true-false:*  
 $\text{push-conn-inside } c \ c' \ \varphi \ \psi \implies \psi \neq FT \wedge \psi \neq FF$   
by (induct rule: push-conn-inside.induct, auto)

**lemma** *push-conn-inside-inv:*  
fixes  $\varphi \ \psi :: 'v \text{ propo}$   
assumes full (propo-rew-step (push-conn-inside  $c \ c'$ ))  $\varphi \ \psi$   
and no-equiv  $\varphi$  and no-imp  $\varphi$  and no-T-F-except-top-level  $\varphi$  and simple-not  $\varphi$   
shows no-equiv  $\psi$  and no-imp  $\psi$  and no-T-F-except-top-level  $\psi$  and simple-not  $\psi$   
**proof** –  
{  
{  
fix  $\varphi \ \psi :: 'v \text{ propo}$   
have  $H: \text{push-conn-inside } c \ c' \ \varphi \ \psi \implies \text{all-subformula-st simple-not-symb } \varphi$   
 $\implies \text{all-subformula-st simple-not-symb } \psi$   
by (induct  $\varphi \ \psi$  rule: push-conn-inside.induct, auto)  
} **note**  $H = \text{this}$   
  
fix  $\varphi \ \psi :: 'v \text{ propo}$   
have  $H: \text{propo-rew-step } (\text{push-conn-inside } c \ c') \ \varphi \ \psi \implies \text{all-subformula-st simple-not-symb } \varphi$   
 $\implies \text{all-subformula-st simple-not-symb } \psi$

```

apply (induct  $\varphi$   $\psi$  rule: propo-rew-step.induct)
using H apply simp
proof (rename-tac  $\varphi$   $\varphi'$  ca  $\psi$   $\psi'$ , case-tac ca rule: connective-cases-arity)
  fix  $\varphi$   $\varphi' :: 'v$  propo and c ::  $'v$  connective and  $\xi$   $\xi' :: 'v$  propo list
  and x ::  $'v$ 
  assume wf-conn c ( $\xi @ \varphi \# \xi'$ )
  and  $c = CT \vee c = CF \vee c = CVar$  x
  then have  $\xi @ \varphi \# \xi' = []$  by auto
  then have False by auto
  then show all-subformula-st simple-not-symb (conn c ( $\xi @ \varphi' \# \xi'$ )) by blast
next
  fix  $\varphi$   $\varphi' :: 'v$  propo and ca ::  $'v$  connective and  $\xi$   $\xi' :: 'v$  propo list
  and x ::  $'v$ 
  assume rel: propo-rew-step (push-conn-inside c  $c'$ )  $\varphi$   $\varphi'$ 
  and  $\varphi$ - $\varphi'$ : all-subformula-st simple-not-symb  $\varphi \implies$  all-subformula-st simple-not-symb  $\varphi'$ 
  and corr: wf-conn ca ( $\xi @ \varphi \# \xi'$ )
  and n: all-subformula-st simple-not-symb (conn ca ( $\xi @ \varphi \# \xi'$ ))
  and c: ca = CNot

  have empty:  $\xi = [] \wedge \xi' = []$  using c corr by auto
  then have simple-not:all-subformula-st simple-not-symb (FNot  $\varphi$ ) using corr c n by auto
  then have simple  $\varphi$ 
    using all-subformula-st-test-symb-true-phi simple-not-symb.simps(1) by blast
  then have simple  $\varphi'$ 
    using rel simple-propo-rew-step-push-conn-inside-inv by blast
  then show all-subformula-st simple-not-symb (conn ca ( $\xi @ \varphi' \# \xi'$ )) using c empty
    by (metis simple-not  $\varphi$ - $\varphi'$  append-Nil conn.simps(4) all-subformula-st-decomp-explicit(3)
      simple-not-symb.simps(1))
next
  fix  $\varphi$   $\varphi' :: 'v$  propo and ca ::  $'v$  connective and  $\xi$   $\xi' :: 'v$  propo list
  and x ::  $'v$ 
  assume rel: propo-rew-step (push-conn-inside c  $c'$ )  $\varphi$   $\varphi'$ 
  and n $\varphi$ : all-subformula-st simple-not-symb  $\varphi \implies$  all-subformula-st simple-not-symb  $\varphi'$ 
  and corr: wf-conn ca ( $\xi @ \varphi \# \xi'$ )
  and n: all-subformula-st simple-not-symb (conn ca ( $\xi @ \varphi \# \xi'$ ))
  and c: ca  $\in$  binary-connectives

  have all-subformula-st simple-not-symb  $\varphi$ 
    using n c corr all-subformula-st-decomp by fastforce
  then have  $\varphi'$ : all-subformula-st simple-not-symb  $\varphi'$  using n $\varphi$  by blast
  obtain a b where ab:  $[a, b] = (\xi @ \varphi \# \xi')$ 
    using corr c list-length2-decomp wf-conn-bin-list-length by metis
  then have  $\xi @ \varphi' \# \xi' = [a, \varphi'] \vee (\xi @ \varphi' \# \xi') = [\varphi', b]$ 
    using ab by (metis (no-types, hide-lams) append-Cons append-Nil append-Nil2
      append-is-Nil-conv butlast.simps(2) butlast-append list.sel(3) tl-append2)
  moreover
  {
    fix  $\chi :: 'v$  propo
    have wf': wf-conn ca  $[a, b]$ 
      using ab corr by presburger
    have all-subformula-st simple-not-symb (conn ca  $[a, b]$ )
      using ab n by presburger
    then have all-subformula-st simple-not-symb  $\chi \vee \chi \notin$  set ( $\xi @ \varphi' \# \xi'$ )
      using wf' by (metis (no-types)  $\varphi'$  all-subformula-st-decomp calculation insert-iff
        list.set(2))
  }

```

```

}
then have  $\forall \varphi. \varphi \in \text{set } (\xi @ \varphi' \# \xi') \longrightarrow \text{all-subformula-st simple-not-symb } \varphi$ 
  by (metis (no-types))

moreover have simple-not-symb (conn ca ( $\xi @ \varphi' \# \xi'$ ))
  using ab conn-inj-not(1) corr wf-conn-list-decomp(4) wf-conn-no-arity-change
    not-Cons-self2 self-append-conv2 simple-not-symb.elims(3) by (metis (no-types) c
      calculation(1) wf-conn-binary)
moreover have wf-conn ca ( $\xi @ \varphi' \# \xi'$ ) using c calculation(1) by auto
ultimately show all-subformula-st simple-not-symb (conn ca ( $\xi @ \varphi' \# \xi'$ ))
  by (metis all-subformula-st-decomp-imp)
qed
}
moreover {
  fix ca :: 'v connective and  $\xi \xi' :: 'v \text{ propo list}$  and  $\varphi \varphi' :: 'v \text{ propo}$ 
  have propo-rew-step (push-conn-inside c c')  $\varphi \varphi' \Longrightarrow \text{wf-conn ca } (\xi @ \varphi \# \xi')$ 
     $\Longrightarrow \text{simple-not-symb (conn ca } (\xi @ \varphi \# \xi')) \Longrightarrow \text{simple-not-symb } \varphi'$ 
     $\Longrightarrow \text{simple-not-symb (conn ca } (\xi @ \varphi' \# \xi'))$ 
  by (metis append-self-conv2 conn.simps(4) conn-inj-not(1) simple-not-symb.elims(3)
    simple-not-symb.simps(1) simple-propo-rew-step-push-conn-inside-inv
    wf-conn-no-arity-change-helper wf-conn-list-decomp(4) wf-conn-no-arity-change)
}
ultimately show simple-not  $\psi$ 
  using full-propo-rew-step-inv-stay'[of push-conn-inside c c' simple-not-symb] assms
  unfolding no-T-F-except-top-level-def simple-not-def full-unfold by metis
next
{
  fix  $\varphi \psi :: 'v \text{ propo}$ 
  have H: propo-rew-step (push-conn-inside c c')  $\varphi \psi \Longrightarrow \text{no-T-F-except-top-level } \varphi$ 
     $\Longrightarrow \text{no-T-F-except-top-level } \psi$ 
  proof –
    assume rel: propo-rew-step (push-conn-inside c c')  $\varphi \psi$ 
    and no-T-F-except-top-level  $\varphi$ 
    then have no-T-F  $\varphi \vee \varphi = FF \vee \varphi = FT$ 
      by (metis no-T-F-symb-except-toplevel-all-subformula-st-no-T-F-symb)
    moreover {
      assume  $\varphi = FF \vee \varphi = FT$ 
      then have False using rel propo-rew-step-push-conn-inside by blast
      then have no-T-F-except-top-level  $\psi$  by blast
    }
    moreover {
      assume no-T-F  $\varphi \wedge \varphi \neq FF \wedge \varphi \neq FT$ 
      then have no-T-F  $\psi$  using rel push-conn-inside-in-c'-symb-no-T-F by blast
      then have no-T-F-except-top-level  $\psi$  using no-T-F-no-T-F-except-top-level by blast
    }
    ultimately show no-T-F-except-top-level  $\psi$  by blast
  qed
}
moreover {
  fix ca :: 'v connective and  $\xi \xi' :: 'v \text{ propo list}$  and  $\varphi \varphi' :: 'v \text{ propo}$ 
  assume rel: propo-rew-step (push-conn-inside c c')  $\varphi \varphi'$ 
  assume corr: wf-conn ca ( $\xi @ \varphi \# \xi'$ )
  then have c: ca  $\neq CT \wedge$  ca  $\neq CF$  by auto
  assume no-T-F: no-T-F-symb-except-toplevel (conn ca ( $\xi @ \varphi \# \xi'$ ))
  have no-T-F-symb-except-toplevel (conn ca ( $\xi @ \varphi' \# \xi'$ ))

```

```

proof
  have  $c: ca \neq CT \wedge ca \neq CF$  using corr by auto
  have  $\zeta: \forall \zeta \in \text{set } (\xi @ \varphi \# \xi'). \zeta \neq FT \wedge \zeta \neq FF$ 
    using corr no-T-F no-T-F-symb-except-toplevel-if-is-a-true-false by blast
  then have  $\varphi \neq FT \wedge \varphi \neq FF$  by auto
  from rel this have  $\varphi' \neq FT \wedge \varphi' \neq FF$ 
    apply (induct rule: propo-rew-step.induct)
    by (metis append-is-Nil-conv conn.simps(2) conn-inj list.distinct(1)
      wf-conn-helper-facts(3) wf-conn-list(1) wf-conn-no-arity-change
      wf-conn-no-arity-change-helper push-conn-inside-not-true-false)
  then have  $\forall \zeta \in \text{set } (\xi @ \varphi' \# \xi'). \zeta \neq FT \wedge \zeta \neq FF$  using  $\zeta$  by auto
  moreover have wf-conn  $ca (\xi @ \varphi' \# \xi')$ 
    using corr wf-conn-no-arity-change by (metis wf-conn-no-arity-change-helper)
  ultimately show no-T-F-symb (conn  $ca (\xi @ \varphi' \# \xi')$ ) using no-T-F-symb.intros c by metis
qed
}
ultimately show no-T-F-except-top-level  $\psi$ 
  using full-propo-rew-step-inv-stay'[of push-conn-inside c c' no-T-F-symb-except-toplevel] assms
  unfolding no-T-F-except-top-level-def full-unfold by metis

next
{
  fix  $\varphi \psi :: 'v \text{ propo}$ 
  have  $H: \text{push-conn-inside } c \ c' \ \varphi \ \psi \implies \text{no-equiv } \varphi \implies \text{no-equiv } \psi$ 
    by (induct  $\varphi \ \psi$  rule: push-conn-inside.induct, auto)
}
then show no-equiv  $\psi$ 
  using full-propo-rew-step-inv-stay-conn[of push-conn-inside c c' no-equiv-symb] assms
  no-equiv-symb-conn-characterization unfolding no-equiv-def by metis

next
{
  fix  $\varphi \psi :: 'v \text{ propo}$ 
  have  $H: \text{push-conn-inside } c \ c' \ \varphi \ \psi \implies \text{no-imp } \varphi \implies \text{no-imp } \psi$ 
    by (induct  $\varphi \ \psi$  rule: push-conn-inside.induct, auto)
}
then show no-imp  $\psi$ 
  using full-propo-rew-step-inv-stay-conn[of push-conn-inside c c' no-imp-symb] assms
  no-imp-symb-conn-characterization unfolding no-imp-def by metis
qed

lemma push-conn-inside-full-propo-rew-step:
  fixes  $\varphi \psi :: 'v \text{ propo}$ 
  assumes
    no-equiv  $\varphi$  and
    no-imp  $\varphi$  and
    full (propo-rew-step (push-conn-inside  $c \ c'$ ))  $\varphi \ \psi$  and
    no-T-F-except-top-level  $\varphi$  and
    simple-not  $\varphi$  and
     $c = CAnd \vee c = COr$  and
     $c' = CAnd \vee c' = COr$ 
  shows c-in-c'-only  $c \ c' \ \psi$ 
  using c-in-c'-symb-rew assms full-propo-rew-step-subformula by blast

```

### 8.5.1 Only one type of connective in the formula (+ not)

**inductive** *only-c-inside-symb* :: 'v connective  $\Rightarrow$  'v propo  $\Rightarrow$  bool **for** *c* :: 'v connective **where**  
*simple-only-c-inside*[simp]: *simple*  $\varphi \Longrightarrow$  *only-c-inside-symb* *c*  $\varphi$  |  
*simple-cnot-only-c-inside*[simp]: *simple*  $\varphi \Longrightarrow$  *only-c-inside-symb* *c* (FNot  $\varphi$ ) |  
*only-c-inside-into-only-c-inside*: wf-conn *c* *l*  $\Longrightarrow$  *only-c-inside-symb* *c* (conn *c* *l*)

**lemma** *only-c-inside-symb-simp*[simp]:  
*only-c-inside-symb* *c* FF *only-c-inside-symb* *c* FT *only-c-inside-symb* *c* (FVar *x*) **by** *auto*

**definition** *only-c-inside* **where** *only-c-inside* *c* = *all-subformula-st* (*only-c-inside-symb* *c*)

**lemma** *only-c-inside-symb-decomp*:  
*only-c-inside-symb* *c*  $\psi \longleftrightarrow$  (*simple*  $\psi$   
 $\vee (\exists \varphi'. \psi = \text{FNot } \varphi' \wedge \text{simple } \varphi')$   
 $\vee (\exists l. \psi = \text{conn } c \ l \wedge \text{wf-conn } c \ l)$ )  
**by** (*auto simp: only-c-inside-symb.intros*(3)) (*induct rule: only-c-inside-symb.induct, auto*)

**lemma** *only-c-inside-symb-decomp-not*[simp]:  
**fixes** *c* :: 'v connective  
**assumes** *c*: *c*  $\neq$  CNot  
**shows** *only-c-inside-symb* *c* (FNot  $\psi$ )  $\longleftrightarrow$  *simple*  $\psi$   
**apply** (*auto simp: only-c-inside-symb.intros*(3))  
**by** (*induct FNot*  $\psi$  *rule: only-c-inside-symb.induct, auto simp: wf-conn-list*(8) *c*)

**lemma** *only-c-inside-decomp-not*[simp]:  
**assumes** *c*: *c*  $\neq$  CNot  
**shows** *only-c-inside* *c* (FNot  $\psi$ )  $\longleftrightarrow$  *simple*  $\psi$   
**by** (*metis* (*no-types, hide-lams*) *all-subformula-st-def all-subformula-st-test-symb-true-phi c*  
*only-c-inside-def only-c-inside-symb-decomp-not simple-only-c-inside*  
*subformula-conn-decomp-simple*)

**lemma** *only-c-inside-decomp*:  
*only-c-inside* *c*  $\varphi \longleftrightarrow$   
 $(\forall \psi. \psi \preceq \varphi \longrightarrow (\text{simple } \psi \vee (\exists \varphi'. \psi = \text{FNot } \varphi' \wedge \text{simple } \varphi') \vee (\exists l. \psi = \text{conn } c \ l \wedge \text{wf-conn } c \ l)))$   
**unfolding** *only-c-inside-def* **by** (*auto simp: all-subformula-st-def only-c-inside-symb-decomp*)

**lemma** *only-c-inside-c-c'-false*:  
**fixes** *c* *c'* :: 'v connective **and** *l* :: 'v propo list **and**  $\varphi$  :: 'v propo  
**assumes** *cc'*: *c*  $\neq$  *c'* **and** *c*: *c* = CAnd  $\vee$  *c* = COr **and** *c'*: *c'* = CAnd  $\vee$  *c'* = COr  
**and** *only*: *only-c-inside* *c*  $\varphi$  **and** *incl*: conn *c'* *l*  $\preceq$   $\varphi$  **and** *wf*: wf-conn *c'* *l*  
**shows** False  
**proof** –  
**let**  $? \psi = \text{conn } c' \ l$   
**have** *simple*  $? \psi \vee (\exists \varphi'. ? \psi = \text{FNot } \varphi' \wedge \text{simple } \varphi') \vee (\exists l. ? \psi = \text{conn } c \ l \wedge \text{wf-conn } c \ l)$   
**using** *only-c-inside-decomp only incl* **by** *blast*  
**moreover** **have**  $\neg \text{simple } ? \psi$   
**using** *wf simple-decomp* **by** (*metis* *c'* *connective.distinct*(19) *connective.distinct*(7,9,21,29,31)  
*wf-conn-list*(1–3))  
**moreover**  
**{**  
**fix**  $\varphi'$

```

    have ?ψ ≠ FNot φ' using c' conn-inj-not(1) wf by blast
  }
ultimately obtain l :: 'v propo list where ?ψ = conn c l ∧ wf-conn c l by metis
then have c = c' using conn-inj wf by metis
then show False using cc' by auto
qed

```

```

lemma only-c-inside-implies-c-in-c'-symb:
  assumes δ: c ≠ c' and c: c = CAnd ∨ c = COr and c': c' = CAnd ∨ c' = COr
  shows only-c-inside c φ ⇒ c-in-c'-symb c c' φ
  apply (rule ccontr)
  apply (cases rule: not-c-in-c'-symb.cases, auto)
  by (metis δ c c' connective.distinct(37,39) list.distinct(1) only-c-inside-c-c'-false
      subformula-in-binary-conn(1,2) wf-conn.simps)+

```

```

lemma c-in-c'-symb-decomp-level1:
  fixes l :: 'v propo list and c c' ca :: 'v connective
  shows wf-conn ca l ⇒ ca ≠ c ⇒ c-in-c'-symb c c' (conn ca l)
proof -
  have not-c-in-c'-symb c c' (conn ca l) ⇒ wf-conn ca l ⇒ ca = c
    by (induct conn ca l rule: not-c-in-c'-symb.induct, auto simp: conn-inj)
  then show wf-conn ca l ⇒ ca ≠ c ⇒ c-in-c'-symb c c' (conn ca l) by blast
qed

```

```

lemma only-c-inside-implies-c-in-c'-only:
  assumes δ: c ≠ c' and c: c = CAnd ∨ c = COr and c': c' = CAnd ∨ c' = COr
  shows only-c-inside c φ ⇒ c-in-c'-only c c' φ
  unfolding c-in-c'-only-def all-subformula-st-def
  using only-c-inside-implies-c-in-c'-symb
  by (metis all-subformula-st-def assms(1) c c' only-c-inside-def subformula-trans)

```

```

lemma c-in-c'-symb-c-implies-only-c-inside:
  assumes δ: c = CAnd ∨ c = COr c' = CAnd ∨ c' = COr c ≠ c' and wf: wf-conn c [φ, ψ]
  and inv: no-equiv (conn c l) no-imp (conn c l) simple-not (conn c l)
  shows wf-conn c l ⇒ c-in-c'-only c c' (conn c l) ⇒ (∀ ψ ∈ set l. only-c-inside c ψ)
using inv
proof (induct conn c l arbitrary: l rule: propo-induct-arity)
  case (nullary x)
  then show ?case by (auto simp: wf-conn-list assms)
next
  case (unary φ la)
  then have c = CNot ∧ la = [φ] by (metis (no-types) wf-conn-list(8))
  then show ?case using assms(2) assms(1) by blast
next
  case (binary φ1 φ2)
  note IHφ1 = this(1) and IHφ2 = this(2) and φ = this(3) and only = this(5) and wf = this(4)
  and no-equiv = this(6) and no-imp = this(7) and simple-not = this(8)
  then have l: l = [φ1, φ2] by (meson wf-conn-list(4-7))
  let ?φ = conn c l

```

```

  obtain c1 l1 c2 l2 where φ1: φ1 = conn c1 l1 and wfφ1: wf-conn c1 l1
    and φ2: φ2 = conn c2 l2 and wfφ2: wf-conn c2 l2 using exists-c-conn by metis
  then have c-in-onlyφ1: c-in-c'-only c c' (conn c1 l1) and c-in-c'-only c c' (conn c2 l2)

```

```

    using only l unfolding c-in-c'-only-def using assms(1) by auto
  have incφ1: φ1 ≼ ?φ and incφ2: φ2 ≼ ?φ
    using φ1 φ2 φ local.wf by (metis conn.simps(5-8) helper-fact subformula-in-binary-conn(1,2))+

  have c1-eq: c1 ≠ CEq and c2-eq: c2 ≠ CEq
    unfolding no-equiv-def using incφ1 incφ2 by (metis φ1 φ2 wfφ1 wfφ2 assms(1) no-equiv
      no-equiv-eq(1) no-equiv-symb.elims(3) no-equiv-symb-conn-characterization wf-conn-list(4,5)
      no-equiv-def subformula-all-subformula-st)+
  have c1-imp: c1 ≠ CImp and c2-imp: c2 ≠ CImp
    using no-imp by (metis φ1 φ2 all-subformula-st-decomp-explicit-imp(2,3) assms(1)
      conn.simps(5,6) l no-imp-imp(1) no-imp-symb.elims(3) no-imp-symb-conn-characterization
      wfφ1 wfφ2 all-subformula-st-decomp no-imp-symb-conn-characterization)+
  have c1c: c1 ≠ c'
  proof
    assume c1c: c1 = c'
    then obtain ξ1 ξ2 where l1: l1 = [ξ1, ξ2]
      by (metis assms(2) connective.distinct(37,39) helper-fact wfφ1 wf-conn.simps
        wf-conn-list-decomp(1-3))
    have c-in-c'-only c c' (conn c [conn c' l1, φ2]) using c1c l only φ1 by auto
    moreover have not-c-in-c'-symb c c' (conn c [conn c' l1, φ2])
      using l1 φ1 c1c l local.wf not-c-in-c'-symb-l wfφ1 by blast
    ultimately show False using φ1 c1c l l1 local.wf not-c-in-c'-simp(4) wfφ1 by blast
  qed
  then have (φ1 = conn c l1 ∧ wf-conn c l1) ∨ (∃ψ1. φ1 = FNot ψ1) ∨ simple φ1
    by (metis φ1 assms(1-3) c1-eq c1-imp simple.elims(3) wfφ1 wf-conn-list(4) wf-conn-list(5-7))
  moreover {
    assume φ1 = conn c l1 ∧ wf-conn c l1
    then have only-c-inside c φ1
      by (metis IHφ1 φ1 all-subformula-st-decomp-imp incφ1 no-equiv no-equiv-def no-imp no-imp-def
        c-in-onlyφ1 only-c-inside-def only-c-inside-into-only-c-inside simple-not simple-not-def
        subformula-all-subformula-st)
  }
  moreover {
    assume ∃ψ1. φ1 = FNot ψ1
    then obtain ψ1 where φ1 = FNot ψ1 by metis
    then have only-c-inside c φ1
      by (metis all-subformula-st-def assms(1) connective.distinct(37,39) incφ1
        only-c-inside-decomp-not simple-not simple-not-def simple-not-symb.simps(1))
  }
  moreover {
    assume simple φ1
    then have only-c-inside c φ1
      by (metis all-subformula-st-decomp-explicit(3) assms(1) connective.distinct(37,39)
        only-c-inside-decomp-not only-c-inside-def)
  }
  ultimately have only-c-insideφ1: only-c-inside c φ1 by metis

  have c-in-onlyφ2: c-in-c'-only c c' (conn c2 l2)
    using only l φ2 wfφ2 assms unfolding c-in-c'-only-def by auto
  have c2c: c2 ≠ c'
  proof
    assume c2c: c2 = c'
    then obtain ξ1 ξ2 where l2: l2 = [ξ1, ξ2]
      by (metis assms(2) wfφ2 wf-conn.simps connective.distinct(7,9,19,21,29,31,37,39))
    then have c-in-c'-symb c c' (conn c [φ1, conn c' l2])

```

```

    using c2c l only  $\varphi 2$  all-subformula-st-test-symb-true-phi unfolding c-in-c'-only-def by auto
  moreover have not-c-in-c'-symb c c' (conn c [ $\varphi 1$ , conn c' l2])
    using assms(1) c2c l2 not-c-in-c'-symb-r wf $\varphi 2$  wf-conn-helper-facts(5,6) by metis
  ultimately show False by auto
qed
then have ( $\varphi 2 = \text{conn } c \text{ l2} \wedge \text{wf-conn } c \text{ l2}$ )  $\vee$  ( $\exists \psi 2. \varphi 2 = \text{FNot } \psi 2$ )  $\vee$  simple  $\varphi 2$ 
  using c2-eq by (metis  $\varphi 2$  assms(1-3) c2-eq c2-imp simple.elims(3) wf $\varphi 2$  wf-conn-list(4-7))
moreover {
  assume  $\varphi 2 = \text{conn } c \text{ l2} \wedge \text{wf-conn } c \text{ l2}$ 
  then have only-c-inside c  $\varphi 2$ 
    by (metis IH $\varphi 2$   $\varphi 2$  all-subformula-st-decomp inc $\varphi 2$  no-equiv no-equiv-def no-imp no-imp-def
      c-in-only $\varphi 2$  only-c-inside-def only-c-inside-into-only-c-inside simple-not simple-not-def
      subformula-all-subformula-st)
}
moreover {
  assume  $\exists \psi 2. \varphi 2 = \text{FNot } \psi 2$ 
  then obtain  $\psi 2$  where  $\varphi 2 = \text{FNot } \psi 2$  by metis
  then have only-c-inside c  $\varphi 2$ 
    by (metis all-subformula-st-def assms(1-3) connective.distinct(38,40) inc $\varphi 2$ 
      only-c-inside-decomp-not simple-not simple-not-def simple-not-symb.simps(1))
}
moreover {
  assume simple  $\varphi 2$ 
  then have only-c-inside c  $\varphi 2$ 
    by (metis all-subformula-st-decomp-explicit(3) assms(1) connective.distinct(37,39)
      only-c-inside-decomp-not only-c-inside-def)
}
ultimately have only-c-inside $\varphi 2$ : only-c-inside c  $\varphi 2$  by metis
show ?case using l only-c-inside $\varphi 1$  only-c-inside $\varphi 2$  by auto
qed

```

## 8.5.2 Push Conjunction

**definition** *pushConj* where *pushConj* = *push-conn-inside CAnd COr*

**lemma** *pushConj-consistent: preserves-un-sat pushConj*  
 unfolding *pushConj-def* by (*simp add: push-conn-inside-consistent*)

**definition** *and-in-or-symb* where *and-in-or-symb* = *c-in-c'-symb CAnd COr*

**definition** *and-in-or-only* where  
*and-in-or-only* = *all-subformula-st (c-in-c'-symb CAnd COr)*

**lemma** *pushConj-inv*:  
 fixes  $\varphi \psi :: 'v \text{ propo}$   
 assumes full (propo-rew-step *pushConj*)  $\varphi \psi$   
 and no-equiv  $\varphi$  and no-imp  $\varphi$  and no-T-F-except-top-level  $\varphi$  and simple-not  $\varphi$   
 shows no-equiv  $\psi$  and no-imp  $\psi$  and no-T-F-except-top-level  $\psi$  and simple-not  $\psi$   
 using *push-conn-inside-inv assms* unfolding *pushConj-def* by metis+

**lemma** *pushConj-full-propo-rew-step*:

fixes  $\varphi \psi :: 'v \text{ propo}$   
 assumes  
 no-equiv  $\varphi$  and  
 no-imp  $\varphi$  and



*full (propo-rew-step pushConj)  $\varphi$   $\psi$  and*  
*no-T-F-except-top-level  $\varphi$  and*  
*simple-not  $\varphi$*   
**shows** *and-in-or-only  $\psi$*   
**using** *assms push-conn-inside-full-propo-rew-step*  
**unfolding** *pushConj-def and-in-or-only-def c-in-c'-only-def* **by** *(metis (no-types))*

### 8.5.3 Push Disjunction

**definition** *pushDisj* **where** *pushDisj = push-conn-inside COr CAnd*

**lemma** *pushDisj-consistent: preserves-un-sat pushDisj*  
**unfolding** *pushDisj-def* **by** *(simp add: push-conn-inside-consistent)*

**definition** *or-in-and-symb* **where** *or-in-and-symb = c-in-c'-symb COr CAnd*

**definition** *or-in-and-only* **where**  
*or-in-and-only = all-subformula-st (c-in-c'-symb COr CAnd)*

**lemma** *not-or-in-and-only-or-and[simp]:*  
 $\sim$  *or-in-and-only (FOr (FAnd  $\psi_1$   $\psi_2$ )  $\varphi'$ )*  
**unfolding** *or-in-and-only-def*  
**by** *(metis all-subformula-st-test-symb-true-phi conn.simps(5-6) not-c-in-c'-symb-l wf-conn-helper-facts(5) wf-conn-helper-facts(6))*

**lemma** *pushDisj-inv:*  
**fixes**  $\varphi \psi :: 'v$  *propo*  
**assumes** *full (propo-rew-step pushDisj)  $\varphi \psi$*   
**and** *no-equiv  $\varphi$  and no-imp  $\varphi$  and no-T-F-except-top-level  $\varphi$  and simple-not  $\varphi$*   
**shows** *no-equiv  $\psi$  and no-imp  $\psi$  and no-T-F-except-top-level  $\psi$  and simple-not  $\psi$*   
**using** *push-conn-inside-inv assms* **unfolding** *pushDisj-def* **by** *metis+*

**lemma** *pushDisj-full-propo-rew-step:*  
**fixes**  $\varphi \psi :: 'v$  *propo*  
**assumes**  
*no-equiv  $\varphi$  and*  
*no-imp  $\varphi$  and*  
*full (propo-rew-step pushDisj)  $\varphi \psi$  and*  
*no-T-F-except-top-level  $\varphi$  and*  
*simple-not  $\varphi$*   
**shows** *or-in-and-only  $\psi$*   
**using** *assms push-conn-inside-full-propo-rew-step*  
**unfolding** *pushDisj-def or-in-and-only-def c-in-c'-only-def* **by** *(metis (no-types))*

## 9 The full transformations

### 9.1 Abstract Property characterizing that only some connective are inside the others

#### 9.1.1 Definition

The normal is a super group of groups

**inductive** *grouped-by*  $:: 'a$  *connective*  $\Rightarrow 'a$  *propo*  $\Rightarrow bool$  **for**  $c$  **where**  
*simple-is-grouped[simp]: simple  $\varphi \Longrightarrow grouped-by\ c\ \varphi$  |*

*simple-not-is-grouped*[simp]:  $\text{simple } \varphi \implies \text{grouped-by } c \text{ (FNot } \varphi) \mid$   
*connected-is-group*[simp]:  $\text{grouped-by } c \varphi \implies \text{grouped-by } c \psi \implies \text{wf-conn } c [\varphi, \psi]$   
 $\implies \text{grouped-by } c (\text{conn } c [\varphi, \psi])$

**lemma** *simple-clause*[simp]:

*grouped-by*  $c$   $FT$   
*grouped-by*  $c$   $FF$   
*grouped-by*  $c$   $(FVar\ x)$   
*grouped-by*  $c$   $(FNot\ FT)$   
*grouped-by*  $c$   $(FNot\ FF)$   
*grouped-by*  $c$   $(FNot\ (FVar\ x))$   
**by** *simp+*

**lemma** *only-c-inside-symb-c-eq-c'*:

*only-c-inside-symb*  $c$   $(\text{conn } c' [\varphi 1, \varphi 2]) \implies c' = CAnd \vee c' = COr \implies \text{wf-conn } c' [\varphi 1, \varphi 2]$   
 $\implies c' = c$   
**by** (*induct*  $\text{conn } c' [\varphi 1, \varphi 2]$  *rule: only-c-inside-symb.induct, auto simp: conn-inj*)

**lemma** *only-c-inside-c-eq-c'*:

*only-c-inside*  $c$   $(\text{conn } c' [\varphi 1, \varphi 2]) \implies c' = CAnd \vee c' = COr \implies \text{wf-conn } c' [\varphi 1, \varphi 2] \implies c = c'$   
**unfolding** *only-c-inside-def all-subformula-st-def* **using** *only-c-inside-symb-c-eq-c'* *subformula-refl*  
**by** *blast*

**lemma** *only-c-inside-imp-grouped-by*:

**assumes**  $c: c \neq CNot$  **and**  $c': c' = CAnd \vee c' = COr$   
**shows** *only-c-inside*  $c \varphi \implies \text{grouped-by } c \varphi$  (**is**  $?O \varphi \implies ?G \varphi$ )

**proof** (*induct*  $\varphi$  *rule: propo-induct-arity*)

**case** (*nullary*  $\varphi\ x$ )  
**then show**  $?G \varphi$  **by** *auto*

**next**

**case** (*unary*  $\psi$ )  
**then show**  $?G (FNot\ \psi)$  **by** (*auto simp: c*)

**next**

**case** (*binary*  $\varphi\ \varphi 1\ \varphi 2$ )  
**note**  $IH\varphi 1 = \text{this}(1)$  **and**  $IH\varphi 2 = \text{this}(2)$  **and**  $\varphi = \text{this}(3)$  **and**  $\text{only} = \text{this}(4)$   
**have**  $\varphi\text{-conn}: \varphi = \text{conn } c [\varphi 1, \varphi 2]$  **and**  $\text{wf}: \text{wf-conn } c [\varphi 1, \varphi 2]$

**proof** –

**obtain**  $c''\ l''$  **where**  $\varphi\text{-c}'': \varphi = \text{conn } c''\ l''$  **and**  $\text{wf}: \text{wf-conn } c''\ l''$

**using** *exists-c-conn* **by** *metis*

**then have**  $l'': l'' = [\varphi 1, \varphi 2]$  **using**  $\varphi$  **by** (*metis wf-conn-list(4–7)*)

**have** *only-c-inside-symb*  $c$   $(\text{conn } c'' [\varphi 1, \varphi 2])$

**using** *only all-subformula-st-test-symb-true-phi*

**unfolding** *only-c-inside-def*  $\varphi\text{-c}''\ l''$  **by** *metis*

**then have**  $c = c''$

**by** (*metis*  $\varphi\ \varphi\text{-c}''\ \text{conn-inj}\ \text{conn-inj-not}(2)\ l''\ \text{list.distinct}(1)\ \text{list.inject}\ \text{wf}$   
*only-c-inside-symb.cases simple.simps(5–8)*)

**then show**  $\varphi = \text{conn } c [\varphi 1, \varphi 2]$  **and**  $\text{wf-conn } c [\varphi 1, \varphi 2]$  **using**  $\varphi\text{-c}''\ \text{wf}\ l''$  **by** *auto*

**qed**

**have** *grouped-by*  $c\ \varphi 1$  **using**  $\text{wf}\ IH\varphi 1\ IH\varphi 2\ \varphi\text{-conn}\ \text{only}\ \varphi$  **unfolding** *only-c-inside-def* **by** *auto*  
**moreover have** *grouped-by*  $c\ \varphi 2$

**using**  $\text{wf}\ \varphi\ IH\varphi 1\ IH\varphi 2\ \varphi\text{-conn}\ \text{only}$  **unfolding** *only-c-inside-def* **by** *auto*

**ultimately show**  $?G \varphi$  **using**  $\varphi\text{-conn}\ \text{connected-is-group}\ \text{local.wf}$  **by** *blast*

**qed**

**lemma** *grouped-by-false*:

```

grouped-by c (conn c' [φ, ψ]) ⇒ c ≠ c' ⇒ wf-conn c' [φ, ψ] ⇒ False
apply (induct conn c' [φ, ψ] rule: grouped-by.induct)
apply (auto simp: simple-decomp wf-conn-list, auto simp: conn-inj)
by (metis list.distinct(1) list.sel(3) wf-conn-list(8))+

```

Then the CNF form is a conjunction of clauses: every clause is in CNF form and two formulas in CNF form can be related by an and.

**inductive** *super-grouped-by*:: 'a connective ⇒ 'a connective ⇒ 'a propo ⇒ bool **for** c c' **where**  
*grouped-is-super-grouped*[simp]: grouped-by c φ ⇒ super-grouped-by c c' φ |  
*connected-is-super-group*: super-grouped-by c c' φ ⇒ super-grouped-by c c' ψ ⇒ wf-conn c [φ, ψ]  
⇒ super-grouped-by c c' (conn c' [φ, ψ])

**lemma** *simple-cnf*[simp]:

```

super-grouped-by c c' FT
super-grouped-by c c' FF
super-grouped-by c c' (FVar x)
super-grouped-by c c' (FNot FT)
super-grouped-by c c' (FNot FF)
super-grouped-by c c' (FNot (FVar x))
by auto

```

**lemma** *c-in-c'-only-super-grouped-by*:

```

assumes c: c = CAnd ∨ c = COr and c': c' = CAnd ∨ c' = COr and cc': c ≠ c'
shows no-equiv φ ⇒ no-imp φ ⇒ simple-not φ ⇒ c-in-c'-only c c' φ
⇒ super-grouped-by c c' φ
(is ?NE φ ⇒ ?NI φ ⇒ ?SN φ ⇒ ?C φ ⇒ ?S φ)

```

**proof** (induct φ rule: propo-induct-arity)

**case** (nullary φ x)

**then show** ?S φ **by** auto

**next**

**case** (unary φ)

**then have** simple-not-symb (FNot φ)

**using** all-subformula-st-test-symb-true-phi **unfolding** simple-not-def **by** blast

**then have** φ = FT ∨ φ = FF ∨ (∃ x. φ = FVar x) **by** (cases φ, auto)

**then show** ?S (FNot φ) **by** auto

**next**

**case** (binary φ φ1 φ2)

**note** IHφ1 = this(1) **and** IHφ2 = this(2) **and** no-equiv = this(4) **and** no-imp = this(5)

**and** simpleN = this(6) **and** c-in-c'-only = this(7) **and** φ' = this(3)

{

**assume** φ = FImp φ1 φ2 ∨ φ = FEq φ1 φ2

**then have** False **using** no-equiv no-imp **by** auto

**then have** ?S φ **by** auto

}

**moreover** {

**assume** φ: φ = conn c' [φ1, φ2] ∧ wf-conn c' [φ1, φ2]

**have** c-in-c'-only: c-in-c'-only c c' φ1 ∧ c-in-c'-only c c' φ2 ∧ c-in-c'-symb c c' φ

**using** c-in-c'-only φ' **unfolding** c-in-c'-only-def **by** auto

**have** super-grouped-by c c' φ1 **using** φ c' no-equiv no-imp simpleN IHφ1 c-in-c'-only **by** auto

**moreover have** super-grouped-by c c' φ2

**using** φ c' no-equiv no-imp simpleN IHφ2 c-in-c'-only **by** auto

**ultimately have** ?S φ

**using** super-grouped-by.intros(2) φ **by** (metis c wf-conn-helper-facts(5,6))

```

}
moreover {
  assume  $\varphi: \varphi = \text{conn } c [\varphi 1, \varphi 2] \wedge \text{wf-conn } c [\varphi 1, \varphi 2]$ 
  then have  $\text{only-c-inside } c \varphi 1 \wedge \text{only-c-inside } c \varphi 2$ 
  using  $c\text{-in-}c'\text{-symb-}c\text{-implies-only-c-inside } c \ c' \ c\text{-in-}c'\text{-only } \text{list.set-intros}(1)$ 
   $\text{wf-conn-helper-facts}(5,6) \ \text{no-equiv} \ \text{no-imp} \ \text{simpleN} \ \text{last-ConsL} \ \text{last-ConsR} \ \text{last-in-set}$ 
   $\text{list.distinct}(1) \ \text{by} \ (\text{metis} \ (\text{no-types}, \text{hide-lams}) \ cc')$ 
  then have  $\text{only-c-inside } c (\text{conn } c [\varphi 1, \varphi 2])$ 
  unfolding  $\text{only-c-inside-def}$  using  $\varphi$ 
  by  $(\text{simp add: only-c-inside-into-only-c-inside all-subformula-st-decomp})$ 
  then have  $\text{grouped-by } c \ \varphi$  using  $\varphi$   $\text{only-c-inside-imp-grouped-by } c$  by  $\text{blast}$ 
  then have  $?S \ \varphi$  using  $\text{super-grouped-by.intros}(1)$  by  $\text{metis}$ 
}
ultimately show  $?S \ \varphi$  by  $(\text{metis } \varphi' \ c \ c' \ cc' \ \text{conn.simps}(5,6) \ \text{wf-conn-helper-facts}(5,6))$ 
qed

```

## 9.2 Conjunctive Normal Form

**definition**  $\text{is-conj-with-TF}$  **where**  $\text{is-conj-with-TF} == \text{super-grouped-by } COr \ CAnd$

**lemma**  $\text{or-in-and-only-conjunction-in-disj}$ :

**shows**  $\text{no-equiv } \varphi \implies \text{no-imp } \varphi \implies \text{simple-not } \varphi \implies \text{or-in-and-only } \varphi \implies \text{is-conj-with-TF } \varphi$   
**using**  $c\text{-in-}c'\text{-only-super-grouped-by}$   
**unfolding**  $\text{is-conj-with-TF-def}$   $\text{or-in-and-only-def}$   $c\text{-in-}c'\text{-only-def}$   
**by**  $(\text{simp add: } c\text{-in-}c'\text{-only-def } c\text{-in-}c'\text{-only-super-grouped-by})$

**definition**  $\text{is-cnf}$  **where**

$\text{is-cnf } \varphi \equiv \text{is-conj-with-TF } \varphi \wedge \text{no-T-F-except-top-level } \varphi$

### 9.2.1 Full CNF transformation

The full CNF transformation consists simply in chaining all the transformation defined before.

**definition**  $\text{cnf-rew}$  **where**  $\text{cnf-rew} =$   
 $(\text{full } (\text{propo-rew-step elim-equiv})) \ OO$   
 $(\text{full } (\text{propo-rew-step elim-imp})) \ OO$   
 $(\text{full } (\text{propo-rew-step elimTB})) \ OO$   
 $(\text{full } (\text{propo-rew-step pushNeg})) \ OO$   
 $(\text{full } (\text{propo-rew-step pushDisj}))$

**lemma**  $\text{cnf-rew-consistent: preserves-un-sat cnf-rew}$

**by**  $(\text{simp add: cnf-rew-def elimEquiv-lifted-consistant elim-imp-lifted-consistant elimTB-consistent}$   
 $\text{preserves-un-sat-OO pushDisj-consistent pushNeg-lifted-consistant})$

**lemma**  $\text{cnf-rew-is-cnf: cnf-rew } \varphi \ \varphi' \implies \text{is-cnf } \varphi'$

**apply**  $(\text{unfold cnf-rew-def OO-def})$   
**apply**  $\text{auto}$

**proof** –

**fix**  $\varphi \ \varphi Eq \ \varphi Imp \ \varphi TB \ \varphi Neg \ \varphi Disj :: 'v \ \text{propo}$

**assume**  $Eq: \text{full } (\text{propo-rew-step elim-equiv}) \ \varphi \ \varphi Eq$

**then have**  $\text{no-equiv: no-equiv } \varphi Eq$  **using**  $\text{no-equiv-full-propo-rew-step-elim-equiv}$  **by**  $\text{blast}$

**assume**  $Imp: \text{full } (\text{propo-rew-step elim-imp}) \ \varphi Eq \ \varphi Imp$

**then have**  $\text{no-imp: no-imp } \varphi Imp$  **using**  $\text{no-imp-full-propo-rew-step-elim-imp}$  **by**  $\text{blast}$

**have**  $\text{no-imp-inv: no-equiv } \varphi Imp$  **using**  $\text{no-equiv Imp elim-imp-inv}$  **by**  $\text{blast}$

**assume** *TB*: full (propo-rew-step elim*TB*)  $\varphi$ *Imp*  $\varphi$ *TB*  
**then have** *noTB*: no-*T-F-except-top-level*  $\varphi$ *TB*  
**using** *no-imp-inv no-imp elimTB-full-propo-rew-step* **by** *blast*  
**have** *noTB-inv*: no-equiv  $\varphi$ *TB* no-imp  $\varphi$ *TB* **using** *elimTB-inv TB no-imp no-imp-inv* **by** *blast+*  
  
**assume** *Neg*: full (propo-rew-step push*Neg*)  $\varphi$ *TB*  $\varphi$ *Neg*  
**then have** *noNeg*: simple-not  $\varphi$ *Neg*  
**using** *noTB-inv noTB pushNeg-full-propo-rew-step* **by** *blast*  
**have** *noNeg-inv*: no-equiv  $\varphi$ *Neg* no-imp  $\varphi$ *Neg* no-*T-F-except-top-level*  $\varphi$ *Neg*  
**using** *pushNeg-inv Neg noTB noTB-inv* **by** *blast+*  
  
**assume** *Disj*: full (propo-rew-step push*Disj*)  $\varphi$ *Neg*  $\varphi$ *Disj*  
**then have** *noDisj*: or-in-and-only  $\varphi$ *Disj*  
**using** *noNeg-inv noNeg pushDisj-full-propo-rew-step* **by** *blast*  
**have** *noDisj-inv*: no-equiv  $\varphi$ *Disj* no-imp  $\varphi$ *Disj* no-*T-F-except-top-level*  $\varphi$ *Disj*  
simple-not  $\varphi$ *Disj*  
**using** *pushDisj-inv Disj noNeg noNeg-inv* **by** *blast+*  
  
**moreover have** *is-conj-with-TF*  $\varphi$ *Disj*  
**using** *or-in-and-only-conjunction-in-disj noDisj-inv noDisj* **by** *blast*  
**ultimately show** *is-cnf*  $\varphi$ *Disj* **unfolding** *is-cnf-def* **by** *blast*  
**qed**

### 9.3 Disjunctive Normal Form

**definition** *is-disj-with-TF* **where** *is-disj-with-TF*  $\equiv$  *super-grouped-by CAnd COr*

**lemma** *and-in-or-only-conjunction-in-disj*:

**shows** no-equiv  $\varphi \implies$  no-imp  $\varphi \implies$  simple-not  $\varphi \implies$  and-in-or-only  $\varphi \implies$  *is-disj-with-TF*  $\varphi$   
**using** *c-in-c'-only-super-grouped-by*  
**unfolding** *is-disj-with-TF-def and-in-or-only-def c-in-c'-only-def*  
**by** (*simp add: c-in-c'-only-def c-in-c'-only-super-grouped-by*)

**definition** *is-dnf*  $:: 'a \text{ propo} \Rightarrow \text{bool}$  **where**  
*is-dnf*  $\varphi \longleftrightarrow$  *is-disj-with-TF*  $\varphi \wedge$  no-*T-F-except-top-level*  $\varphi$

#### 9.3.1 Full DNF transform

The full DNF transformation consists simply in chaining all the transformation defined before.

**definition** *dnf-rew* **where** *dnf-rew*  $\equiv$   
(*full (propo-rew-step elim-equiv)*) *OO*  
(*full (propo-rew-step elim-imp)*) *OO*  
(*full (propo-rew-step elimTB)*) *OO*  
(*full (propo-rew-step pushNeg)*) *OO*  
(*full (propo-rew-step pushConj)*)

**lemma** *dnf-rew-consistent: preserves-un-sat dnf-rew*

**by** (*simp add: dnf-rew-def elimEquiv-lifted-consistant elim-imp-lifted-consistant elimTB-consistent preserves-un-sat-OO pushConj-consistent pushNeg-lifted-consistant*)

**theorem** *dnf-transformation-correction*:

$\text{dnf-rew } \varphi \varphi' \implies \text{is-dnf } \varphi'$   
**apply** (*unfold dnf-rew-def OO-def*)  
**by** (*meson and-in-or-only-conjunction-in-disj elimTB-full-propo-rew-step elimTB-inv(1,2)*)

*elim-imp-inv is-dnf-def no-equiv-full-propo-rew-step-elim-equiv*  
*no-imp-full-propo-rew-step-elim-imp pushConj-full-propo-rew-step pushConj-inv(1-4)*  
*pushNeg-full-propo-rew-step pushNeg-inv(1-3))*

## 10 More aggressive simplifications: Removing true and false at the beginning

### 10.1 Transformation

We should remove *FT* and *FF* at the beginning and not in the middle of the algorithm. To do this, we have to use more rules (one for each connective):

**inductive** *elimTBFull* **where**

*ElimTBFull1[simp]: elimTBFull (FAnd  $\varphi$  FT)  $\varphi$  |*  
*ElimTBFull1'[simp]: elimTBFull (FAnd FT  $\varphi$ )  $\varphi$  |*

*ElimTBFull2[simp]: elimTBFull (FAnd  $\varphi$  FF) FF |*  
*ElimTBFull2'[simp]: elimTBFull (FAnd FF  $\varphi$ ) FF |*

*ElimTBFull3[simp]: elimTBFull (FOr  $\varphi$  FT) FT |*  
*ElimTBFull3'[simp]: elimTBFull (FOr FT  $\varphi$ ) FT |*

*ElimTBFull4[simp]: elimTBFull (FOr  $\varphi$  FF)  $\varphi$  |*  
*ElimTBFull4'[simp]: elimTBFull (FOr FF  $\varphi$ )  $\varphi$  |*

*ElimTBFull5[simp]: elimTBFull (FNot FT) FF |*  
*ElimTBFull5'[simp]: elimTBFull (FNot FF) FT |*

*ElimTBFull6-l[simp]: elimTBFull (FImp FT  $\varphi$ )  $\varphi$  |*  
*ElimTBFull6-l'[simp]: elimTBFull (FImp FF  $\varphi$ ) FT |*  
*ElimTBFull6-r[simp]: elimTBFull (FImp  $\varphi$  FT) FT |*  
*ElimTBFull6-r'[simp]: elimTBFull (FImp  $\varphi$  FF) (FNot  $\varphi$ ) |*

*ElimTBFull7-l[simp]: elimTBFull (FEq FT  $\varphi$ )  $\varphi$  |*  
*ElimTBFull7-l'[simp]: elimTBFull (FEq FF  $\varphi$ ) (FNot  $\varphi$ ) |*  
*ElimTBFull7-r[simp]: elimTBFull (FEq  $\varphi$  FT)  $\varphi$  |*  
*ElimTBFull7-r'[simp]: elimTBFull (FEq  $\varphi$  FF) (FNot  $\varphi$ ) |*

The transformation is still consistent.

**lemma** *elimTBFull-consistent: preserves-un-sat elimTBFull*

**proof** –

```
{
  fix  $\varphi \psi :: 'b \text{ propo}$ 
  have  $\text{elimTBFull } \varphi \psi \implies \forall A. A \models \varphi \longleftrightarrow A \models \psi$ 
    by (induct-tac rule: elimTBFull.inducts, auto)
}
then show ?thesis using preserves-un-sat-def by auto
qed
```

Contrary to the theorem  $\llbracket \text{no-equiv } ?\varphi; \text{no-imp } ?\varphi; ?\psi \preceq ?\varphi; \neg \text{no-T-F-symb-except-toplevel } ?\psi \rrbracket \implies \exists \psi'. \text{elimTB } ?\psi \psi'$ , we do not need the assumption *no-equiv*  $\varphi$  and *no-imp*  $\varphi$ , since our transformation is more general.

**lemma** *no-T-F-symb-except-toplevel-step-exists'*:

**fixes**  $\varphi :: 'v \text{ propo}$

```

shows  $\psi \preceq \varphi \implies \neg \text{no-}T\text{-}F\text{-symb-except-toplevel } \psi \implies \exists \psi'. \text{elimTBFull } \psi \psi'$ 
proof (induct  $\psi$  rule: propo-induct-arity)
  case (nullary  $\varphi'$ )
  then have False using no- $T$ - $F$ -symb-except-toplevel-true no- $T$ - $F$ -symb-except-toplevel-false by auto
  then show  $\text{Ex } (\text{elimTBFull } \varphi')$  by blast
next
  case (unary  $\psi$ )
  then have  $\psi = FF \vee \psi = FT$  using no- $T$ - $F$ -symb-except-toplevel-not-decom by blast
  then show  $\text{Ex } (\text{elimTBFull } (F\text{Not } \psi))$  using ElimTBFull5 ElimTBFull5' by blast
next
  case (binary  $\varphi' \psi_1 \psi_2$ )
  then have  $\psi_1 = FT \vee \psi_2 = FT \vee \psi_1 = FF \vee \psi_2 = FF$ 
  by (metis binary-connectives-def conn.simps(5-8) insertI1 insert-commute
    no- $T$ - $F$ -symb-except-toplevel-bin-decom binary.hyps(3))
  then show  $\text{Ex } (\text{elimTBFull } \varphi')$  using elimTBFull.intros binary.hyps(3) by blast
qed

```

The same applies here. We do not need the assumption, but the deep link between  $\neg \text{no-}T\text{-}F\text{-except-top-level } \varphi$  and the existence of a rewriting step, still exists.

```

lemma no- $T$ - $F$ -except-top-level-rew':
  fixes  $\varphi :: 'v \text{ propo}$ 
  assumes noTB:  $\neg \text{no-}T\text{-}F\text{-except-top-level } \varphi$ 
  shows  $\exists \psi \psi'. \psi \preceq \varphi \wedge \text{elimTBFull } \psi \psi'$ 
proof -
  have test-symb-false-nullary:
     $\forall x. \text{no-}T\text{-}F\text{-symb-except-toplevel } (FF :: 'v \text{ propo}) \wedge \text{no-}T\text{-}F\text{-symb-except-toplevel } F' T$ 
     $\wedge \text{no-}T\text{-}F\text{-symb-except-toplevel } (F\text{Var } (x :: 'v))$ 
  by auto
  moreover {
    fix  $c :: 'v \text{ connective}$  and  $l :: 'v \text{ propo list}$  and  $\psi :: 'v \text{ propo}$ 
    have  $H: \text{elimTBFull } (\text{conn } c \ l) \ \psi \implies \neg \text{no-}T\text{-}F\text{-symb-except-toplevel } (\text{conn } c \ l)$ 
    by (cases (conn c l) rule: elimTBFull.cases) auto
  }
  ultimately show ?thesis
  using no-test-symb-step-exists[of no- $T$ - $F$ -symb-except-toplevel  $\varphi$  elimTBFull] noTB
  no- $T$ - $F$ -symb-except-toplevel-step-exists' unfolding no- $T$ - $F$ -except-top-level-def by metis
qed

```

```

lemma elimTBFull-full-propo-rew-step:
  fixes  $\varphi \psi :: 'v \text{ propo}$ 
  assumes full (propo-rew-step elimTBFull)  $\varphi \psi$ 
  shows no- $T$ - $F$ -except-top-level  $\psi$ 
  using full-propo-rew-step-subformula no- $T$ - $F$ -except-top-level-rew' assms by fastforce

```

## 10.2 More invariants

As the aim is to use the transformation as the first transformation, we have to show some more invariants for *elim-equiv* and *elim-imp*. For the other transformation, we have already proven it.

```

lemma propo-rew-step-ElimEquiv-no- $T$ - $F$ : propo-rew-step elim-equiv  $\varphi \psi \implies \text{no-}T\text{-}F \ \varphi \implies \text{no-}T\text{-}F \ \psi$ 
proof (induct rule: propo-rew-step.induct)
  fix  $\varphi' :: 'v \text{ propo}$  and  $\psi' :: 'v \text{ propo}$ 

```

```

assume a1: no-T-F  $\varphi'$ 
assume a2: elim-equiv  $\varphi' \psi'$ 
have  $\forall x0\ x1. (\neg \text{elim-equiv } (x1 :: 'v\ \text{propo})\ x0 \vee (\exists v2\ v3\ v4\ v5\ v6\ v7. x1 = \text{FEq } v2\ v3$ 
   $\wedge x0 = \text{FAnd } (\text{FImp } v4\ v5)\ (\text{FImp } v6\ v7) \wedge v2 = v4 \wedge v4 = v7 \wedge v3 = v5 \wedge v3 = v6))$ 
   $= (\neg \text{elim-equiv } x1\ x0 \vee (\exists v2\ v3\ v4\ v5\ v6\ v7. x1 = \text{FEq } v2\ v3$ 
   $\wedge x0 = \text{FAnd } (\text{FImp } v4\ v5)\ (\text{FImp } v6\ v7) \wedge v2 = v4 \wedge v4 = v7 \wedge v3 = v5 \wedge v3 = v6))$ 
  by meson
then have  $\forall p\ pa. \neg \text{elim-equiv } (p :: 'v\ \text{propo})\ pa \vee (\exists pb\ pc\ pd\ pe\ pf\ pg. p = \text{FEq } pb\ pc$ 
   $\wedge pa = \text{FAnd } (\text{FImp } pd\ pe)\ (\text{FImp } pf\ pg) \wedge pb = pd \wedge pd = pg \wedge pc = pe \wedge pc = pf)$ 
  using elim-equiv.cases by force
then show no-T-F  $\psi'$  using a1 a2 by fastforce
next
fix  $\varphi\ \varphi' :: 'v\ \text{propo}$  and  $\xi\ \xi' :: 'v\ \text{propo list}$  and  $c :: 'v\ \text{connective}$ 
assume rel: propo-rew-step elim-equiv  $\varphi\ \varphi'$ 
and IH: no-T-F  $\varphi \implies \text{no-T-F } \varphi'$ 
and corr: wf-conn  $c\ (\xi @ \varphi \# \xi')$ 
and no-T-F: no-T-F  $(\text{conn } c\ (\xi @ \varphi \# \xi'))$ 
{
  assume  $c: c = \text{CNot}$ 
  then have empty:  $\xi = []\ \xi' = []$  using corr by auto
  then have no-T-F  $\varphi$  using no-T-F  $c$  no-T-F-decomp-not by auto
  then have no-T-F  $(\text{conn } c\ (\xi @ \varphi' \# \xi'))$  using  $c$  empty no-T-F-comp-not IH by auto
}
moreover {
  assume  $c: c \in \text{binary-connectives}$ 
  obtain  $a\ b$  where  $ab: \xi @ \varphi \# \xi' = [a, b]$ 
  using corr  $c$  list-length2-decomp wf-conn-bin-list-length by metis
  then have  $\varphi: \varphi = a \vee \varphi = b$ 
  by  $(\text{metis } \text{append.simps}(1)\ \text{append-is-Nil-conv } \text{list.distinct}(1)\ \text{list.sel}(3)\ \text{nth-Cons-0}\ \text{tl-append2})$ 
  have  $\zeta: \forall \zeta \in \text{set } (\xi @ \varphi \# \xi'). \text{no-T-F } \zeta$ 
  using no-T-F unfolding no-T-F-def using corr all-subformula-st-decomp by blast

  then have  $\varphi': \text{no-T-F } \varphi'$  using  $ab$  IH  $\varphi$  by auto
  have  $l': \xi @ \varphi' \# \xi' = [\varphi', b] \vee \xi @ \varphi' \# \xi' = [a, \varphi']$ 
  by  $(\text{metis } (\text{no-types, hide-lams})\ ab\ \text{append-Cons } \text{append-Nil } \text{append-Nil2}\ \text{butlast.simps}(2)\ \text{butlast-append } \text{list.distinct}(1)\ \text{list.sel}(3))$ 
  then have  $\forall \zeta \in \text{set } (\xi @ \varphi' \# \xi'). \text{no-T-F } \zeta$  using  $\zeta\ \varphi'\ ab$  by fastforce
  moreover
  have  $\forall \zeta \in \text{set } (\xi @ \varphi \# \xi'). \zeta \neq \text{FT} \wedge \zeta \neq \text{FF}$ 
  using  $\zeta$  corr no-T-F no-T-F-except-top-level-false no-T-F-no-T-F-except-top-level by blast
  then have no-T-F-symb  $(\text{conn } c\ (\xi @ \varphi' \# \xi'))$ 
  by  $(\text{metis } \varphi'\ l'\ ab\ \text{all-subformula-st-test-symb-true-phi } c\ \text{list.distinct}(1)\ \text{list.set-intros}(1,2)\ \text{no-T-F-symb-except-toplevel-bin-decom}\ \text{no-T-F-symb-except-toplevel-no-T-F-symb}\ \text{no-T-F-symb-false}(1,2)\ \text{no-T-F-def wf-conn-binary}\ \text{wf-conn-list}(1,2))$ 
  ultimately have no-T-F  $(\text{conn } c\ (\xi @ \varphi' \# \xi'))$ 
  by  $(\text{metis } l'\ \text{all-subformula-st-decomp-imp } c\ \text{no-T-F-def wf-conn-binary})$ 
}
moreover {
  fix  $x$ 
  assume  $c = \text{CVar } x \vee c = \text{CF} \vee c = \text{CT}$ 
  then have False using corr by auto
  then have no-T-F  $(\text{conn } c\ (\xi @ \varphi' \# \xi'))$  by auto
}

```



ultimately show  $\text{no-}T\text{-}F \text{ (conn } c \text{ (}\xi @ \varphi' \# \xi')\text{))}$  using  $\text{corr wf-conn.cases}$  by *metis*  
qed

lemma *elim-equiv-inv'*:

fixes  $\varphi \psi :: 'v \text{ propo}$

assumes *full* (*propo-rew-step elim-equiv*)  $\varphi \psi$  and *no-}T\text{-}F\text{-except-top-level } \varphi*

shows *no-}T\text{-}F\text{-except-top-level } \psi*

proof –

{

fix  $\varphi \psi :: 'v \text{ propo}$

have *propo-rew-step elim-equiv*  $\varphi \psi \implies \text{no-}T\text{-}F\text{-except-top-level } \varphi$

$\implies \text{no-}T\text{-}F\text{-except-top-level } \psi$

proof –

assume *rel: propo-rew-step elim-equiv*  $\varphi \psi$

and *no: no-}T\text{-}F\text{-except-top-level } \varphi*

{

assume  $\varphi = FT \vee \varphi = FF$

from *rel this* have *False*

apply (*induct rule: propo-rew-step.induct*, *auto simp: wf-conn-list(1,2)*)

using *elim-equiv.simps* by *blast+*

then have *no-}T\text{-}F\text{-except-top-level } \psi* by *blast*

}

moreover {

assume  $\varphi \neq FT \wedge \varphi \neq FF$

then have *no-}T\text{-}F*  $\varphi$

by (*metis no no-}T\text{-}F\text{-symb-except-toplevel-all-subformula-st-no-}T\text{-}F\text{-symb}*)

then have *no-}T\text{-}F*  $\psi$  using *propo-rew-step-ElimEquiv-no-}T\text{-}F* *rel* by *blast*

then have *no-}T\text{-}F\text{-except-top-level } \psi* by (*simp add: no-}T\text{-}F\text{-no-}T\text{-}F\text{-except-top-level}*)

}

ultimately show *no-}T\text{-}F\text{-except-top-level } \psi* by *metis*

qed

}

moreover {

fix  $c :: 'v \text{ connective}$  and  $\xi \xi' :: 'v \text{ propo list}$  and  $\zeta \zeta' :: 'v \text{ propo}$

assume *rel: propo-rew-step elim-equiv*  $\zeta \zeta'$

and *incl: } \zeta \preceq \varphi*

and *corr: wf-conn*  $c \text{ (}\xi @ \zeta \# \xi')\text{)}$

and *no-}T\text{-}F*: *no-}T\text{-}F\text{-symb-except-toplevel* (*conn*  $c \text{ (}\xi @ \zeta \# \xi')\text{)}$

and *n: no-}T\text{-}F\text{-symb-except-toplevel } \zeta'*

have *no-}T\text{-}F\text{-symb-except-toplevel* (*conn*  $c \text{ (}\xi @ \zeta' \# \xi')\text{)}$

proof

have *p: no-}T\text{-}F\text{-symb* (*conn*  $c \text{ (}\xi @ \zeta \# \xi')\text{)}$

using *corr wf-conn-list(1) wf-conn-list(2) no-}T\text{-}F\text{-symb-except-toplevel-no-}T\text{-}F\text{-symb no-}T\text{-}F*  
by *blast*

have *l: } \forall \varphi \in \text{set } (\xi @ \zeta \# \xi'). \varphi \neq FT \wedge \varphi \neq FF*

using *corr wf-conn-no-}T\text{-}F\text{-symb-iff* *p* by *blast*

from *rel incl* have  $\zeta' \neq FT \wedge \zeta' \neq FF$

apply (*induction } \zeta \zeta'* *rule: propo-rew-step.induct*)

apply (*cases rule: elim-equiv.cases*, *auto simp: elim-equiv.simps*)

by (*metis append-is-Nil-conv list.distinct wf-conn-list(1,2) wf-conn-no-arity-change*  
*wf-conn-no-arity-change-helper*) +

then have  $\forall \varphi \in \text{set } (\xi @ \zeta' \# \xi'). \varphi \neq FT \wedge \varphi \neq FF$  using *l* by *auto*

moreover have  $c \neq CT \wedge c \neq CF$  using *corr* by *auto*

ultimately show *no-}T\text{-}F\text{-symb* (*conn*  $c \text{ (}\xi @ \zeta' \# \xi')\text{)}$

by (*metis corr wf-conn-no-arity-change wf-conn-no-arity-change-helper no-}T\text{-}F\text{-symb-comp*)

```

    qed
  }
  ultimately show no-T-F-except-top-level  $\psi$ 
    using full-propo-rew-step-inv-stay-with-inc[of elim-equiv no-T-F-symb-except-toplevel  $\varphi$ ]
    assms subformula-refl unfolding no-T-F-except-top-level-def by metis
qed

lemma propo-rew-step-ElimImp-no-T-F: propo-rew-step elim-imp  $\varphi \psi \implies \text{no-T-F } \varphi \implies \text{no-T-F } \psi$ 
proof (induct rule: propo-rew-step.induct)
  case (global-rel  $\varphi' \psi'$ )
  then show no-T-F  $\psi'$ 
    using elim-imp.cases no-T-F-comp-not no-T-F-decomp(1,2)
    by (metis no-T-F-comp-expanded-explicit(2))
next
  case (propo-rew-one-step-lift  $\varphi \varphi' c \xi \xi'$ )
  note rel = this(1) and IH = this(2) and corr = this(3) and no-T-F = this(4)
  {
    assume c:  $c = CNot$ 
    then have empty:  $\xi = [] \ \xi' = []$  using corr by auto
    then have no-T-F  $\varphi$  using no-T-F c no-T-F-decomp-not by auto
    then have no-T-F (conn c ( $\xi @ \varphi' \# \xi'$ )) using c empty no-T-F-comp-not IH by auto
  }
  moreover {
    assume c:  $c \in \text{binary-connectives}$ 
    then obtain a b where ab:  $\xi @ \varphi \# \xi' = [a, b]$ 
      using corr list-length2-decomp wf-conn-bin-list-length by metis
    then have  $\varphi: \varphi = a \vee \varphi = b$ 
      by (metis append-self-conv2 wf-conn-list-decomp(4) wf-conn-unary list.discI list.sel(3)
        nth-Cons-0 tl-append2)
    have  $\zeta: \forall \zeta \in \text{set } (\xi @ \varphi \# \xi'). \text{no-T-F } \zeta$  using ab c propo-rew-one-step-lift.prems by auto

    then have  $\varphi': \text{no-T-F } \varphi'$ 
      using ab IH  $\varphi$  corr no-T-F no-T-F-def all-subformula-st-decomp-explicit by auto
    have  $\chi: \xi @ \varphi' \# \xi' = [\varphi', b] \vee \xi @ \varphi' \# \xi' = [a, \varphi']$ 
      by (metis (no-types, hide-lams) ab append-Cons append-Nil append-Nil2 butlast.simps(2)
        butlast-append list.distinct(1) list.sel(3))
    then have  $\forall \zeta \in \text{set } (\xi @ \varphi' \# \xi'). \text{no-T-F } \zeta$  using  $\zeta \varphi' ab$  by fastforce
    moreover
      have no-T-F (last ( $\xi @ \varphi' \# \xi'$ )) by (simp add: calculation)
      then have no-T-F-symb (conn c ( $\xi @ \varphi' \# \xi'$ ))
        by (metis  $\chi \varphi' \zeta ab$  all-subformula-st-test-symb-true-phi c last.simps list.distinct(1)
          list.set-intros(1) no-T-F-bin-decomp no-T-F-def)
      ultimately have no-T-F (conn c ( $\xi @ \varphi' \# \xi'$ )) using c  $\chi$  by fastforce
  }
  moreover {
    fix x
    assume  $c = CVar\ x \vee c = CF \vee c = CT$ 
    then have False using corr by auto
    then have no-T-F (conn c ( $\xi @ \varphi' \# \xi'$ )) by auto
  }
  ultimately show no-T-F (conn c ( $\xi @ \varphi' \# \xi'$ )) using corr wf-conn.cases by blast
qed

```

```

lemma elim-imp-inv':
  fixes  $\varphi \psi :: 'v \text{ propo}$ 
  assumes full (propo-rew-step elim-imp)  $\varphi \psi$  and no-T-F-except-top-level  $\varphi$ 
  shows no-T-F-except-top-level  $\psi$ 
proof -
  {
    {
      fix  $\varphi \psi :: 'v \text{ propo}$ 
      have  $H: \text{elim-imp } \varphi \psi \implies \text{no-T-F-except-top-level } \varphi \implies \text{no-T-F-except-top-level } \psi$ 
        by (induct  $\varphi \psi$  rule: elim-imp.induct, auto)
      } note H = this
      fix  $\varphi \psi :: 'v \text{ propo}$ 
      have propo-rew-step elim-imp  $\varphi \psi \implies \text{no-T-F-except-top-level } \varphi \implies \text{no-T-F-except-top-level } \psi$ 
      proof -
        assume rel: propo-rew-step elim-imp  $\varphi \psi$ 
        and no: no-T-F-except-top-level  $\varphi$ 
        {
          assume  $\varphi = FT \vee \varphi = FF$ 
          from rel this have False
          apply (induct rule: propo-rew-step.induct)
          by (cases rule: elim-imp.cases, auto simp: wf-conn-list(1,2))
          then have no-T-F-except-top-level  $\psi$  by blast
        }
        moreover {
          assume  $\varphi \neq FT \wedge \varphi \neq FF$ 
          then have no-T-F  $\varphi$ 
            by (metis no no-T-F-symb-except-toplevel-all-subformula-st-no-T-F-symb)
          then have no-T-F  $\psi$ 
            using rel propo-rew-step-ElimImp-no-T-F by blast
          then have no-T-F-except-top-level  $\psi$  by (simp add: no-T-F-no-T-F-except-top-level)
        }
        ultimately show no-T-F-except-top-level  $\psi$  by metis
      qed
    }
  }
  moreover {
    fix  $c :: 'v \text{ connective}$  and  $\xi \xi' :: 'v \text{ propo list}$  and  $\zeta \zeta' :: 'v \text{ propo}$ 
    assume rel: propo-rew-step elim-imp  $\zeta \zeta'$ 
    and incl:  $\zeta \preceq \varphi$ 
    and corr: wf-conn  $c (\xi @ \zeta \# \xi')$ 
    and no-T-F: no-T-F-symb-except-toplevel (conn  $c (\xi @ \zeta \# \xi')$ )
    and n: no-T-F-symb-except-toplevel  $\zeta'$ 
    have no-T-F-symb-except-toplevel (conn  $c (\xi @ \zeta' \# \xi')$ )
    proof
      have  $p: \text{no-T-F-symb } (\text{conn } c (\xi @ \zeta \# \xi'))$ 
        by (simp add: corr no-T-F no-T-F-symb-except-toplevel-no-T-F-symb wf-conn-list(1,2))

      have  $l: \forall \varphi \in \text{set } (\xi @ \zeta \# \xi'). \varphi \neq FT \wedge \varphi \neq FF$ 
        using corr wf-conn-no-T-F-symb-iff  $p$  by blast
      from rel incl have  $\zeta' \neq FT \wedge \zeta' \neq FF$ 
      apply (induction  $\zeta \zeta'$  rule: propo-rew-step.induct)
      apply (cases rule: elim-imp.cases, auto)
      using wf-conn-list(1,2) wf-conn-no-arity-change wf-conn-no-arity-change-helper
      by (metis append-is-Nil-conv list.distinct(1))+
      then have  $\forall \varphi \in \text{set } (\xi @ \zeta' \# \xi'). \varphi \neq FT \wedge \varphi \neq FF$  using  $l$  by auto
      moreover have  $c \neq CT \wedge c \neq CF$  using corr by auto
    qed
  }

```

```

    ultimately show no-T-F-symb (conn c (ξ @ ζ' # ξ'))
    using corr wf-conn-no-arity-change no-T-F-symb-comp
    by (metis wf-conn-no-arity-change-helper)
  qed
}
ultimately show no-T-F-except-top-level ψ
  using full-propo-rew-step-inv-stay-with-inc[of elim-imp no-T-F-symb-except-toplevel φ]
  assms subformula-refl unfolding no-T-F-except-top-level-def by metis
qed

```

### 10.3 The new CNF and DNF transformation

The transformation is the same as before, but the order is not the same.

**definition** *dnf-rew'* :: 'a propo ⇒ 'a propo ⇒ bool **where**

```

dnf-rew' =
  (full (propo-rew-step elimTBFull)) OO
  (full (propo-rew-step elim-equiv)) OO
  (full (propo-rew-step elim-imp)) OO
  (full (propo-rew-step pushNeg)) OO
  (full (propo-rew-step pushConj))

```

**lemma** *dnf-rew'-consistent: preserves-un-sat dnf-rew'*

**by** (simp add: dnf-rew'-def elimEquiv-lifted-consistant elim-imp-lifted-consistant  
elimTBFull-consistent preserves-un-sat-OO pushConj-consistent pushNeg-lifted-consistant)

**theorem** *cnf-transformation-correction:*

*dnf-rew' φ φ' ⇒ is-dnf φ'*

**unfolding** *dnf-rew'-def OO-def*

**by** (meson and-in-or-only-conjunction-in-disj elimTBFull-full-propo-rew-step elim-equiv-inv'  
elim-imp-inv elim-imp-inv' is-dnf-def no-equiv-full-propo-rew-step-elim-equiv  
no-imp-full-propo-rew-step-elim-imp pushConj-full-propo-rew-step pushConj-inv(1-4)  
pushNeg-full-propo-rew-step pushNeg-inv(1-3))

Given all the lemmas before the CNF transformation is easy to prove:

**definition** *cnf-rew'* :: 'a propo ⇒ 'a propo ⇒ bool **where**

```

cnf-rew' =
  (full (propo-rew-step elimTBFull)) OO
  (full (propo-rew-step elim-equiv)) OO
  (full (propo-rew-step elim-imp)) OO
  (full (propo-rew-step pushNeg)) OO
  (full (propo-rew-step pushDisj))

```

**lemma** *cnf-rew'-consistent: preserves-un-sat cnf-rew'*

**by** (simp add: cnf-rew'-def elimEquiv-lifted-consistant elim-imp-lifted-consistant  
elimTBFull-consistent preserves-un-sat-OO pushDisj-consistent pushNeg-lifted-consistant)

**theorem** *cnf'-transformation-correction:*

*cnf-rew' φ φ' ⇒ is-cnf φ'*

**unfolding** *cnf-rew'-def OO-def*

**by** (meson elimTBFull-full-propo-rew-step elim-equiv-inv' elim-imp-inv elim-imp-inv' is-cnf-def  
no-equiv-full-propo-rew-step-elim-equiv no-imp-full-propo-rew-step-elim-imp  
or-in-and-only-conjunction-in-disj pushDisj-full-propo-rew-step pushDisj-inv(1-4)  
pushNeg-full-propo-rew-step pushNeg-inv(1) pushNeg-inv(2) pushNeg-inv(3))

**end**

## 11 Partial Clausal Logic

```
theory Partial-Clausal-Logic
imports ../lib/Clausal-Logic List-More
begin
```

### 11.1 Clauses

Clauses are (finite) multisets of literals.

```
type-synonym 'a clause = 'a literal multiset
type-synonym 'v clauses = 'v clause set
```

### 11.2 Partial Interpretations

```
type-synonym 'a interp = 'a literal set
```

```
definition true-lit :: 'a interp  $\Rightarrow$  'a literal  $\Rightarrow$  bool (infix  $\models_l$  50) where
  I  $\models_l$  L  $\longleftrightarrow$  L  $\in$  I
```

```
declare true-lit-def[simp]
```

#### 11.2.1 Consistency

```
definition consistent-interp :: 'a literal set  $\Rightarrow$  bool where
  consistent-interp I = ( $\forall$  L.  $\neg$ (L  $\in$  I  $\wedge$   $\neg$  L  $\in$  I))
```

```
lemma consistent-interp-empty[simp]:
  consistent-interp {} unfolding consistent-interp-def by auto
```

```
lemma consistent-interp-single[simp]:
  consistent-interp {L} unfolding consistent-interp-def by auto
```

```
lemma consistent-interp-subset:
  assumes
    A  $\subseteq$  B and
    consistent-interp B
  shows consistent-interp A
  using assms unfolding consistent-interp-def by auto
```

```
lemma consistent-interp-change-insert:
  a  $\notin$  A  $\Longrightarrow$   $\neg$ a  $\notin$  A  $\Longrightarrow$  consistent-interp (insert ( $\neg$ a) A)  $\longleftrightarrow$  consistent-interp (insert a A)
  unfolding consistent-interp-def by fastforce
```

```
lemma consistent-interp-insert-pos[simp]:
  a  $\notin$  A  $\Longrightarrow$  consistent-interp (insert a A)  $\longleftrightarrow$  consistent-interp A  $\wedge$   $\neg$ a  $\notin$  A
  unfolding consistent-interp-def by auto
```

```
lemma consistent-interp-insert-not-in:
  consistent-interp A  $\Longrightarrow$  a  $\notin$  A  $\Longrightarrow$   $\neg$ a  $\notin$  A  $\Longrightarrow$  consistent-interp (insert a A)
  unfolding consistent-interp-def by auto
```

#### 11.2.2 Atoms

```
definition atms-of-ms :: 'a literal multiset set  $\Rightarrow$  'a set where
  atms-of-ms  $\psi$ s =  $\bigcup$  (atms-of '  $\psi$ s)
```

**lemma** *atms-of-mmltiset[simp]*:  
 $atms-of (mset\ a) = atm-of\ 'set\ a$   
**by** (*induct a*) *auto*

**lemma** *atms-of-ms-mset-unfold*:  
 $atms-of-ms (mset\ 'b) = (\bigcup_{x \in b}. atm-of\ 'set\ x)$   
**unfolding** *atms-of-ms-def* **by** *simp*

**definition** *atms-of-s* :: '*a* literal set  $\Rightarrow$  '*a* set **where**  
 $atms-of-s\ C = atm-of\ 'C$

**lemma** *atms-of-ms-empty-set[simp]*:  
 $atms-of-ms\ \{\} = \{\}$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-ms-mempty[simp]*:  
 $atms-of-ms\ \{\{\#\}\} = \{\}$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-ms-mono*:  
 $A \subseteq B \implies atms-of-ms\ A \subseteq atms-of-ms\ B$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-ms-finite[simp]*:  
 $finite\ \psi \implies finite\ (atms-of-ms\ \psi)$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-ms-union[simp]*:  
 $atms-of-ms\ (\psi \cup \chi) = atms-of-ms\ \psi \cup atms-of-ms\ \chi$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-ms-insert[simp]*:  
 $atms-of-ms\ (insert\ \psi\ \chi) = atms-of\ \psi \cup atms-of-ms\ \chi$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-ms-singleton[simp]*:  $atms-of-ms\ \{L\} = atms-of\ L$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-atms-of-ms-mono[simp]*:  
 $A \in \psi \implies atms-of\ A \subseteq atms-of-ms\ \psi$   
**unfolding** *atms-of-ms-def* **by** *fastforce*

**lemma** *atms-of-ms-single-set-mset-atms-of[simp]*:  
 $atms-of-ms\ (single\ 'set-mset\ B) = atms-of\ B$   
**unfolding** *atms-of-ms-def* *atms-of-def* **by** *auto*

**lemma** *atms-of-ms-remove-incl*:  
**shows**  $atms-of-ms\ (Set.remove\ a\ \psi) \subseteq atms-of-ms\ \psi$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *atms-of-ms-remove-subset*:  
 $atms-of-ms\ (\varphi - \psi) \subseteq atms-of-ms\ \varphi$   
**unfolding** *atms-of-ms-def* **by** *auto*

**lemma** *finite-atms-of-ms-remove-subset[simp]*:

*finite* (*atms-of-ms* *A*)  $\implies$  *finite* (*atms-of-ms* (*A* - *C*))  
**using** *atms-of-ms-remove-subset*[*of* *A* *C*] *finite-subset* **by** *blast*

**lemma** *atms-of-ms-empty-iff*:  
*atms-of-ms* *A* = {}  $\longleftrightarrow$  *A* = {{#}}  $\vee$  *A* = {}  
**apply** (*rule iffI*)  
**apply** (*metis* (*no-types*, *lifting*) *atms-empty-iff-empty* *atms-of-atms-of-ms-mono* *insert-absorb*  
*singleton-iff* *singleton-insert-inj-eq'* *subsetI* *subset-empty*)  
**apply** *auto*[]  
**done**

**lemma** *in-implies-atm-of-on-atms-of-ms*:  
**assumes** *L*  $\in$  # *C* **and** *C*  $\in$  *N*  
**shows** *atm-of* *L*  $\in$  *atms-of-ms* *N*  
**using** *atms-of-atms-of-ms-mono*[*of* *C* *N*] *assms* **by** (*simp* *add*: *atm-of-lit-in-atms-of* *subset-iff*)

**lemma** *in-plus-implies-atm-of-on-atms-of-ms*:  
**assumes** *C* + {#*L*#}  $\in$  *N*  
**shows** *atm-of* *L*  $\in$  *atms-of-ms* *N*  
**using** *in-implies-atm-of-on-atms-of-ms*[*of* - *C* + {#*L*#}] *assms* **by** *auto*

**lemma** *in-m-in-literals*:  
**assumes** {#*A*#} + *D*  $\in$   $\psi$ *s*  
**shows** *atm-of* *A*  $\in$  *atms-of-ms*  $\psi$ *s*  
**using** *assms* **by** (*auto* *dest*: *atms-of-atms-of-ms-mono*)

**lemma** *atms-of-s-union*[*simp*]:  
*atms-of-s* (*Ia*  $\cup$  *Ib*) = *atms-of-s* *Ia*  $\cup$  *atms-of-s* *Ib*  
**unfolding** *atms-of-s-def* **by** *auto*

**lemma** *atms-of-s-single*[*simp*]:  
*atms-of-s* {*L*} = {*atm-of* *L*}  
**unfolding** *atms-of-s-def* **by** *auto*

**lemma** *atms-of-s-insert*[*simp*]:  
*atms-of-s* (*insert* *L* *Ib*) = {*atm-of* *L*}  $\cup$  *atms-of-s* *Ib*  
**unfolding** *atms-of-s-def* **by** *auto*

**lemma** *in-atms-of-s-decomp*[*iff*]:  
*P*  $\in$  *atms-of-s* *I*  $\longleftrightarrow$  (*Pos* *P*  $\in$  *I*  $\vee$  *Neg* *P*  $\in$  *I*) (**is** ?*P*  $\longleftrightarrow$  ?*Q*)

**proof**  
**assume** ?*P*  
**then show** ?*Q* **unfolding** *atms-of-s-def* **by** (*metis* *image-iff* *literal.exhaust-sel*)  
**next**  
**assume** ?*Q*  
**then show** ?*P* **unfolding** *atms-of-s-def* **by** *force*  
**qed**

**lemma** *atm-of-in-atm-of-set-in-uminus*:  
*atm-of* *L'*  $\in$  *atm-of* ' *B*  $\implies$  *L'*  $\in$  *B*  $\vee$  - *L'*  $\in$  *B*  
**using** *atms-of-s-def* **by** (*cases* *L'*) *fastforce* +

### 11.2.3 Totality

**definition** *total-over-set* :: 'a *interp*  $\Rightarrow$  'a *set*  $\Rightarrow$  *bool* **where**  
*total-over-set* *I* *S* = ( $\forall$  *l*  $\in$  *S*. *Pos* *l*  $\in$  *I*  $\vee$  *Neg* *l*  $\in$  *I*)

**definition** *total-over-m* :: 'a literal set  $\Rightarrow$  'a clause set  $\Rightarrow$  bool **where**  
*total-over-m* *I*  $\psi$ s = *total-over-set* *I* (atms-of-ms  $\psi$ s)

**lemma** *total-over-set-empty*[simp]:  
*total-over-set* *I* {}  
**unfolding** *total-over-set-def* **by** *auto*

**lemma** *total-over-m-empty*[simp]:  
*total-over-m* *I* {}  
**unfolding** *total-over-m-def* **by** *auto*

**lemma** *total-over-set-single*[iff]:  
*total-over-set* *I* {*L*}  $\longleftrightarrow$  (*Pos* *L*  $\in$  *I*  $\vee$  *Neg* *L*  $\in$  *I*)  
**unfolding** *total-over-set-def* **by** *auto*

**lemma** *total-over-set-insert*[iff]:  
*total-over-set* *I* (insert *L* *Ls*)  $\longleftrightarrow$  ((*Pos* *L*  $\in$  *I*  $\vee$  *Neg* *L*  $\in$  *I*)  $\wedge$  *total-over-set* *I* *Ls*)  
**unfolding** *total-over-set-def* **by** *auto*

**lemma** *total-over-set-union*[iff]:  
*total-over-set* *I* (*Ls*  $\cup$  *Ls'*)  $\longleftrightarrow$  (*total-over-set* *I* *Ls*  $\wedge$  *total-over-set* *I* *Ls'*)  
**unfolding** *total-over-set-def* **by** *auto*

**lemma** *total-over-m-subset*:  
 $A \subseteq B \implies \text{total-over-m } I \ B \implies \text{total-over-m } I \ A$   
**using** *atms-of-ms-mono*[of *A*] **unfolding** *total-over-m-def* *total-over-set-def* **by** *auto*

**lemma** *total-over-m-sum*[iff]:  
**shows** *total-over-m* *I* {*C* + *D*}  $\longleftrightarrow$  (*total-over-m* *I* {*C*}  $\wedge$  *total-over-m* *I* {*D*})  
**using** *assms* **unfolding** *total-over-m-def* *total-over-set-def* **by** *auto*

**lemma** *total-over-m-union*[iff]:  
*total-over-m* *I* (*A*  $\cup$  *B*)  $\longleftrightarrow$  (*total-over-m* *I* *A*  $\wedge$  *total-over-m* *I* *B*)  
**unfolding** *total-over-m-def* *total-over-set-def* **by** *auto*

**lemma** *total-over-m-insert*[iff]:  
*total-over-m* *I* (insert *a* *A*)  $\longleftrightarrow$  (*total-over-set* *I* (atms-of *a*)  $\wedge$  *total-over-m* *I* *A*)  
**unfolding** *total-over-m-def* *total-over-set-def* **by** *fastforce*

**lemma** *total-over-m-extension*:  
**fixes** *I* :: 'v literal set **and** *A* :: 'v clauses  
**assumes** *total*: *total-over-m* *I* *A*  
**shows**  $\exists I'. \text{total-over-m } (I \cup I') \ (A \cup B)$   
 $\wedge (\forall x \in I'. \text{atm-of } x \in \text{atms-of-ms } B \wedge \text{atm-of } x \notin \text{atms-of-ms } A)$

**proof** –  
**let**  $?I' = \{\text{Pos } v \mid v. v \in \text{atms-of-ms } B \wedge v \notin \text{atms-of-ms } A\}$   
**have**  $(\forall x \in ?I'. \text{atm-of } x \in \text{atms-of-ms } B \wedge \text{atm-of } x \notin \text{atms-of-ms } A)$  **by** *auto*  
**moreover have** *total-over-m* (*I*  $\cup$   $?I'$ ) (*A*  $\cup$  *B*)  
**using** *total* **unfolding** *total-over-m-def* *total-over-set-def* **by** *auto*  
**ultimately show** *?thesis* **by** *blast*  
**qed**

**lemma** *total-over-m-consistent-extension*:  
**fixes** *I* :: 'v literal set **and** *A* :: 'v clauses



**assumes** *total*: *total-over-m I A*  
**and** *cons*: *consistent-interp I*  
**shows**  $\exists I'. \text{total-over-m } (I \cup I') (A \cup B)$   
 $\wedge (\forall x \in I'. \text{atm-of } x \in \text{atms-of-ms } B \wedge \text{atm-of } x \notin \text{atms-of-ms } A) \wedge \text{consistent-interp } (I \cup I')$   
**proof** –  
**let**  $?I' = \{ \text{Pos } v \mid v. v \in \text{atms-of-ms } B \wedge v \notin \text{atms-of-ms } A \wedge \text{Pos } v \notin I \wedge \text{Neg } v \notin I \}$   
**have**  $(\forall x \in ?I'. \text{atm-of } x \in \text{atms-of-ms } B \wedge \text{atm-of } x \notin \text{atms-of-ms } A)$  **by** *auto*  
**moreover have** *total-over-m*  $(I \cup ?I') (A \cup B)$   
**using** *total unfolding total-over-m-def total-over-set-def* **by** *auto*  
**moreover have** *consistent-interp*  $(I \cup ?I')$   
**using** *cons unfolding consistent-interp-def* **by**  $(\text{intro allI}) (\text{rename-tac } L, \text{case-tac } L, \text{auto})$   
**ultimately show** *?thesis* **by** *blast*  
**qed**

**lemma** *total-over-set-atms-of-m[simp]*:  
*total-over-set Ia (atms-of-s Ia)*  
**unfolding** *total-over-set-def atms-of-s-def* **by**  $(\text{metis image-iff literal.exhaust-sel})$

**lemma** *total-over-set-literal-defined*:  
**assumes**  $\{ \#A\# \} + D \in \psi_s$   
**and** *total-over-set I (atms-of-ms  $\psi_s$ )*  
**shows**  $A \in I \vee -A \in I$   
**using** *assms unfolding total-over-set-def* **by**  $(\text{metis (no-types) Neg-atm-of-iff in-m-in-literals literal.collapse(1) uminus-Neg uminus-Pos})$

**lemma** *tot-over-m-remove*:  
**assumes** *total-over-m*  $(I \cup \{L\}) \{ \psi \}$   
**and**  $L: \neg L \in \# \psi \neg L \notin \# \psi$   
**shows** *total-over-m I*  $\{ \psi \}$   
**unfolding** *total-over-m-def total-over-set-def*  
**proof**  
**fix** *l*  
**assume**  $l: l \in \text{atms-of-ms } \{ \psi \}$   
**then have**  $\text{Pos } l \in I \vee \text{Neg } l \in I \vee l = \text{atm-of } L$   
**using** *assms unfolding total-over-m-def total-over-set-def* **by** *auto*  
**moreover have**  $\text{atm-of } L \notin \text{atms-of-ms } \{ \psi \}$   
**proof**  $(\text{rule ccontr})$   
**assume**  $\neg ?thesis$   
**then have**  $\text{atm-of } L \in \text{atms-of } \psi$  **by** *auto*  
**then have**  $\text{Pos } (\text{atm-of } L) \in \# \psi \vee \text{Neg } (\text{atm-of } L) \in \# \psi$   
**using** *atm-imp-pos-or-neg-lit* **by** *metis*  
**then have**  $L \in \# \psi \vee -L \in \# \psi$  **by**  $(\text{cases } L) \text{ auto}$   
**then show** *False* **using** *L* **by** *auto*  
**qed**  
**ultimately show**  $\text{Pos } l \in I \vee \text{Neg } l \in I$  **using** *l* **by** *metis*  
**qed**

**lemma** *total-union*:  
**assumes** *total-over-m I  $\psi$*   
**shows** *total-over-m*  $(I \cup I') \psi$   
**using** *assms unfolding total-over-m-def total-over-set-def* **by** *auto*

**lemma** *total-union-2*:  
**assumes** *total-over-m I  $\psi$*   
**and** *total-over-m I'  $\psi'$*

**shows** *total-over-m* ( $I \cup I'$ ) ( $\psi \cup \psi'$ )  
**using** *assms unfolding total-over-m-def total-over-set-def* **by** *auto*

#### 11.2.4 Interpretations

**definition** *true-cls* :: 'a interp  $\Rightarrow$  'a clause  $\Rightarrow$  bool (**infix**  $\models$  50) **where**  
 $I \models C \longleftrightarrow (\exists L \in \# C. I \models_l L)$

**lemma** *true-cls-empty*[*iff*]:  $\neg I \models \{\#\}$   
**unfolding** *true-cls-def* **by** *auto*

**lemma** *true-cls-singleton*[*iff*]:  $I \models \{\#L\# \} \longleftrightarrow I \models_l L$   
**unfolding** *true-cls-def* **by** (*auto split:if-split-asm*)

**lemma** *true-cls-union*[*iff*]:  $I \models C + D \longleftrightarrow I \models C \vee I \models D$   
**unfolding** *true-cls-def* **by** *auto*

**lemma** *true-cls-mono-set-mset*:  $\text{set-mset } C \subseteq \text{set-mset } D \Longrightarrow I \models C \Longrightarrow I \models D$   
**unfolding** *true-cls-def subset-eq Bex-def* **by** *metis*

**lemma** *true-cls-mono-leD*[*dest*]:  $A \subseteq \# B \Longrightarrow I \models A \Longrightarrow I \models B$   
**unfolding** *true-cls-def* **by** *auto*

**lemma**  
**assumes**  $I \models \psi$   
**shows** *true-cls-union-increase*[*simp*]:  $I \cup I' \models \psi$   
**and** *true-cls-union-increase'*[*simp*]:  $I' \cup I \models \psi$   
**using** *assms unfolding true-cls-def* **by** *auto*

**lemma** *true-cls-mono-set-mset-l*:  
**assumes**  $A \models \psi$   
**and**  $A \subseteq B$   
**shows**  $B \models \psi$   
**using** *assms unfolding true-cls-def* **by** *auto*

**lemma** *true-cls-replicate-mset*[*iff*]:  $I \models \text{replicate-mset } n L \longleftrightarrow n \neq 0 \wedge I \models_l L$   
**by** (*induct n*) *auto*

**lemma** *true-cls-empty-entails*[*iff*]:  $\neg \{\} \models N$   
**by** (*auto simp add: true-cls-def*)

**lemma** *true-cls-not-in-remove*:  
**assumes**  $L \notin \# \chi$   
**and**  $I \cup \{L\} \models \chi$   
**shows**  $I \models \chi$   
**using** *assms unfolding true-cls-def* **by** *auto*

**definition** *true-clss* :: 'a interp  $\Rightarrow$  'a clauses  $\Rightarrow$  bool (**infix**  $\models_s$  50) **where**  
 $I \models_s CC \longleftrightarrow (\forall C \in CC. I \models C)$

**lemma** *true-clss-empty*[*simp*]:  $I \models_s \{\}$   
**unfolding** *true-clss-def* **by** *blast*

**lemma** *true-clss-singleton*[*iff*]:  $I \models_s \{C\} \longleftrightarrow I \models C$   
**unfolding** *true-clss-def* **by** *blast*

**lemma** *true-clss-empty-entails-empty*[iff]:  $\{\} \models_s N \longleftrightarrow N = \{\}$   
**unfolding** *true-clss-def* **by** (*auto simp add: true-clss-def*)

**lemma** *true-clss-insert-l* [simp]:  
 $M \models A \implies \text{insert } L \ M \models A$   
**unfolding** *true-clss-def* **by** *auto*

**lemma** *true-clss-union*[iff]:  $I \models_s CC \cup DD \longleftrightarrow I \models_s CC \wedge I \models_s DD$   
**unfolding** *true-clss-def* **by** *blast*

**lemma** *true-clss-insert*[iff]:  $I \models_s \text{insert } C \ DD \longleftrightarrow I \models C \wedge I \models_s DD$   
**unfolding** *true-clss-def* **by** *blast*

**lemma** *true-clss-mono*:  $DD \subseteq CC \implies I \models_s CC \implies I \models_s DD$   
**unfolding** *true-clss-def* **by** *blast*

**lemma** *true-clss-union-increase*[simp]:  
**assumes**  $I \models_s \psi$   
**shows**  $I \cup I' \models_s \psi$   
**using** *assms* **unfolding** *true-clss-def* **by** *auto*

**lemma** *true-clss-union-increase'*[simp]:  
**assumes**  $I' \models_s \psi$   
**shows**  $I \cup I' \models_s \psi$   
**using** *assms* **by** (*auto simp add: true-clss-def*)

**lemma** *true-clss-commute-l*:  
 $(I \cup I' \models_s \psi) \longleftrightarrow (I' \cup I \models_s \psi)$   
**by** (*simp add: Un-commute*)

**lemma** *model-remove*[simp]:  $I \models_s N \implies I \models_s \text{Set.remove } a \ N$   
**by** (*simp add: true-clss-def*)

**lemma** *model-remove-minus*[simp]:  $I \models_s N \implies I \models_s N - A$   
**by** (*simp add: true-clss-def*)

**lemma** *notin-vars-union-true-clss-true-clss*:  
**assumes**  $\forall x \in I'. \text{atm-of } x \notin \text{atms-of-ms } A$   
**and**  $\text{atms-of } L \subseteq \text{atms-of-ms } A$   
**and**  $I \cup I' \models L$   
**shows**  $I \models L$   
**using** *assms* **unfolding** *true-clss-def true-lit-def Bex-def*  
**by** (*metis Un-iff atm-of-lit-in-atms-of contra-subsetD*)

**lemma** *notin-vars-union-true-clss-true-clss*:  
**assumes**  $\forall x \in I'. \text{atm-of } x \notin \text{atms-of-ms } A$   
**and**  $\text{atms-of-ms } L \subseteq \text{atms-of-ms } A$   
**and**  $I \cup I' \models_s L$   
**shows**  $I \models_s L$   
**using** *assms* **unfolding** *true-clss-def true-lit-def Ball-def*  
**by** (*meson atms-of-atms-of-ms-mono notin-vars-union-true-clss-true-clss subset-trans*)

### 11.2.5 Satisfiability

**definition** *satisfiable* :: 'a clause set  $\Rightarrow$  bool **where**  
*satisfiable*  $CC \equiv \exists I. (I \models_s CC \wedge \text{consistent-interp } I \wedge \text{total-over-m } I \ CC)$

**lemma** *satisfiable-single*[simp]:  
*satisfiable*  $\{\{\#L\#\}\}$   
**unfolding** *satisfiable-def* **by** *fastforce*

**abbreviation** *unsatisfiable* :: 'a clause set  $\Rightarrow$  bool **where**  
*unsatisfiable*  $CC \equiv \neg$  *satisfiable*  $CC$

**lemma** *satisfiable-decreasing*:  
**assumes** *satisfiable*  $(\psi \cup \psi')$   
**shows** *satisfiable*  $\psi$   
**using** *assms total-over-m-union* **unfolding** *satisfiable-def* **by** *blast*

**lemma** *satisfiable-def-min*:  
*satisfiable*  $CC$   
 $\longleftrightarrow (\exists I. I \models_s CC \wedge \text{consistent-interp } I \wedge \text{total-over-m } I \ CC \wedge \text{atm-of } I = \text{atms-of-ms } CC)$   
(is *?sat*  $\longleftrightarrow ?B$ )

**proof**  
**assume** *?B* **then show** *?sat* **by** (auto simp add: *satisfiable-def*)

**next**  
**assume** *?sat*  
**then obtain**  $I$  **where**  
 $I \models_s CC$  **and**  
*cons*: *consistent-interp*  $I$  **and**  
*tot*: *total-over-m*  $I \ CC$   
**unfolding** *satisfiable-def* **by** *auto*  
**let**  $?I = \{P. P \in I \wedge \text{atm-of } P \in \text{atms-of-ms } CC\}$

**have**  $I \models_s CC$   
**using** *I-CC in-implies-atm-of-on-atms-of-ms* **unfolding** *true-clss-def Ball-def true-cls-def Bex-def true-lit-def*  
**by** *blast*

**moreover have** *cons*: *consistent-interp*  $?I$   
**using** *cons* **unfolding** *consistent-interp-def* **by** *auto*

**moreover have** *total-over-m*  $?I \ CC$   
**using** *tot* **unfolding** *total-over-m-def total-over-set-def* **by** *auto*

**moreover**  
**have** *atms-CC-incl*: *atms-of-ms*  $CC \subseteq \text{atm-of } I$   
**using** *tot* **unfolding** *total-over-m-def total-over-set-def atms-of-ms-def*  
**by** (auto simp add: *atms-of-def atms-of-s-def*[*symmetric*])  
**have** *atm-of* '  $?I = \text{atms-of-ms } CC$   
**using** *atms-CC-incl* **unfolding** *atms-of-ms-def* **by** *force*

**ultimately show** *?B* **by** *auto*

**qed**

## 11.2.6 Entailment for Multisets of Clauses

**definition** *true-cls-mset* :: 'a interp  $\Rightarrow$  'a clause multiset  $\Rightarrow$  bool (infix  $\models_m$  50) **where**  
 $I \models_m CC \longleftrightarrow (\forall C \in \# \ CC. I \models C)$

**lemma** *true-cls-mset-empty*[simp]:  $I \models_m \{\#\}$   
**unfolding** *true-cls-mset-def* **by** *auto*

**lemma** *true-cls-mset-singleton*[iff]:  $I \models_m \{\#C\# \} \longleftrightarrow I \models C$   
**unfolding** *true-cls-mset-def* **by** (auto split: *if-split-asm*)

**lemma** *true-cls-mset-union*[iff]:  $I \models_m CC + DD \longleftrightarrow I \models_m CC \wedge I \models_m DD$   
**unfolding** *true-cls-mset-def* **by** *fastforce*

**lemma** *true-cls-mset-image-mset*[iff]:  $I \models_m \text{image-mset } f A \longleftrightarrow (\forall x \in \# A. I \models f x)$   
**unfolding** *true-cls-mset-def* **by** *fastforce*

**lemma** *true-cls-mset-mono*:  $\text{set-mset } DD \subseteq \text{set-mset } CC \implies I \models_m CC \implies I \models_m DD$   
**unfolding** *true-cls-mset-def* *subset-iff* **by** *auto*

**lemma** *true-clss-set-mset*[iff]:  $I \models_s \text{set-mset } CC \longleftrightarrow I \models_m CC$   
**unfolding** *true-clss-def* *true-cls-mset-def* **by** *auto*

**lemma** *true-cls-mset-increasing-r*[simp]:  
 $I \models_m CC \implies I \cup J \models_m CC$   
**unfolding** *true-cls-mset-def* **by** *auto*

**theorem** *true-cls-remove-unused*:  
**assumes**  $I \models \psi$   
**shows**  $\{v \in I. \text{atm-of } v \in \text{atms-of } \psi\} \models \psi$   
**using** *assms* **unfolding** *true-cls-def* *atms-of-def* **by** *auto*

**theorem** *true-clss-remove-unused*:  
**assumes**  $I \models_s \psi$   
**shows**  $\{v \in I. \text{atm-of } v \in \text{atms-of-ms } \psi\} \models_s \psi$   
**unfolding** *true-clss-def* *atms-of-def* *Ball-def*

**proof** (*intro allI impI*)  
**fix**  $x$   
**assume**  $x \in \psi$   
**then have**  $I \models x$   
**using** *assms* **unfolding** *true-clss-def* *atms-of-def* *Ball-def* **by** *auto*

**then have**  $\{v \in I. \text{atm-of } v \in \text{atms-of } x\} \models x$   
**by** (*simp only: true-cls-remove-unused*[of  $I$ ])  
**moreover have**  $\{v \in I. \text{atm-of } v \in \text{atms-of } x\} \subseteq \{v \in I. \text{atm-of } v \in \text{atms-of-ms } \psi\}$   
**using**  $\langle x \in \psi \rangle$  **by** (*auto simp add: atms-of-ms-def*)  
**ultimately show**  $\{v \in I. \text{atm-of } v \in \text{atms-of-ms } \psi\} \models x$   
**using** *true-cls-mono-set-mset-l* **by** *blast*

**qed**

A simple application of the previous theorem:

**lemma** *true-clss-union-decrease*:  
**assumes**  $II': I \cup I' \models \psi$   
**and**  $H: \forall v \in I'. \text{atm-of } v \notin \text{atms-of } \psi$   
**shows**  $I \models \psi$

**proof** –  
**let**  $?I = \{v \in I \cup I'. \text{atm-of } v \in \text{atms-of } \psi\}$   
**have**  $?I \models \psi$  **using** *true-cls-remove-unused*  $II'$  **by** *blast*  
**moreover have**  $?I \subseteq I$  **using**  $H$  **by** *auto*  
**ultimately show** *?thesis* **using** *true-cls-mono-set-mset-l* **by** *blast*

**qed**

**lemma** *multiset-not-empty*:  
**assumes**  $M \neq \{\#\}$   
**and**  $x \in \# M$

**shows**  $\exists A. x = \text{Pos } A \vee x = \text{Neg } A$   
**using** *assms literal.exhaust-sel* **by** *blast*

**lemma** *atms-of-ms-empty*:  
**fixes**  $\psi :: 'v \text{ clauses}$   
**assumes** *atms-of-ms*  $\psi = \{\}$   
**shows**  $\psi = \{\} \vee \psi = \{\{\#\}\}$   
**using** *assms* **by** (*auto simp add: atms-of-ms-def*)

**lemma** *consistent-interp-disjoint*:  
**assumes** *consI*: *consistent-interp*  $I$   
**and** *disj*: *atms-of-s*  $A \cap \text{atms-of-s } I = \{\}$   
**and** *consA*: *consistent-interp*  $A$   
**shows** *consistent-interp*  $(A \cup I)$   
**proof** (*rule ccontr*)  
**assume**  $\neg ?thesis$   
**moreover have**  $\bigwedge L. \neg (L \in A \wedge \neg L \in I)$   
**using** *disj unfolding atms-of-s-def* **by** (*auto simp add: rev-image-eqI*)  
**ultimately show** *False*  
**using** *consA consI unfolding consistent-interp-def* **by** (*metis (full-types) Un-iff literal.exhaust-sel uminus-Neg uminus-Pos*)  
**qed**

**lemma** *total-remove-unused*:  
**assumes** *total-over-m*  $I \psi$   
**shows** *total-over-m*  $\{v \in I. \text{atm-of } v \in \text{atms-of-ms } \psi\} \psi$   
**using** *assms unfolding total-over-m-def total-over-set-def*  
**by** (*metis (lifting) literal.sel(1,2) mem-Collect-eq*)

**lemma** *true-cls-remove-hd-if-notin-vars*:  
**assumes** *insert*  $a \ M' \models D$   
**and** *atm-of*  $a \notin \text{atms-of } D$   
**shows**  $M' \models D$   
**using** *assms* **by** (*auto simp add: atm-of-lit-in-atms-of true-cls-def*)

**lemma** *total-over-set-atm-of*:  
**fixes**  $I :: 'v \text{ interp}$  **and**  $K :: 'v \text{ set}$   
**shows** *total-over-set*  $I \ K \longleftrightarrow (\forall l \in K. l \in (\text{atm-of } I))$   
**unfolding** *total-over-set-def* **by** (*metis atms-of-s-def in-atms-of-s-decomp*)

### 11.2.7 Tautologies

**definition** *tautology*  $(\psi :: 'v \text{ clause}) \equiv \forall I. \text{total-over-set } I (\text{atms-of } \psi) \longrightarrow I \models \psi$

**lemma** *tautology-Pos-Neg[intro]*:  
**assumes** *Pos*  $p \in \# A$  **and** *Neg*  $p \in \# A$   
**shows** *tautology*  $A$   
**using** *assms unfolding tautology-def total-over-set-def true-cls-def Bex-def*  
**by** (*meson atm-iff-pos-or-neg-lit true-lit-def*)

**lemma** *tautology-minus[simp]*:  
**assumes**  $L \in \# A$  **and**  $\neg L \in \# A$   
**shows** *tautology*  $A$   
**by** (*metis assms literal.exhaust tautology-Pos-Neg uminus-Neg uminus-Pos*)

**lemma** *tautology-exists-Pos-Neg*:

**assumes** *tautology*  $\psi$   
**shows**  $\exists p. \text{Pos } p \in \# \psi \wedge \text{Neg } p \in \# \psi$   
**proof** (*rule ccontr*)  
**assume**  $p: \neg (\exists p. \text{Pos } p \in \# \psi \wedge \text{Neg } p \in \# \psi)$   
**let**  $?I = \{-L \mid L. L \in \# \psi\}$   
**have** *total-over-set*  $?I$  (*atms-of*  $\psi$ )  
**unfolding** *total-over-set-def* **using** *atm-imp-pos-or-neg-lit* **by** *force*  
**moreover** **have**  $\neg ?I \models \psi$   
**unfolding** *true-cls-def* *true-lit-def* *Bex-def* **apply** *clarify*  
**using**  $p$  **by** (*rename-tac*  $x$   $L$ , *case-tac*  $L$ ) *fastforce+*  
**ultimately** **show** *False* **using** *assms* **unfolding** *tautology-def* **by** *auto*  
**qed**

**lemma** *tautology-decomp*:  
 $\text{tautology } \psi \longleftrightarrow (\exists p. \text{Pos } p \in \# \psi \wedge \text{Neg } p \in \# \psi)$   
**using** *tautology-exists-Pos-Neg* **by** *auto*

**lemma** *tautology-false[simp]*:  $\neg \text{tautology } \{\#\}$   
**unfolding** *tautology-def* **by** *auto*

**lemma** *tautology-add-single*:  
 $\text{tautology } (\{\#a\# \} + L) \longleftrightarrow \text{tautology } L \vee -a \in \# L$   
**unfolding** *tautology-decomp* **by** (*cases*  $a$ ) *auto*

**lemma** *minus-interp-tautology*:  
**assumes**  $\{-L \mid L. L \in \# \chi\} \models \chi$   
**shows** *tautology*  $\chi$   
**proof** –  
**obtain**  $L$  **where**  $L \in \# \chi \wedge -L \in \# \chi$   
**using** *assms* **unfolding** *true-cls-def* **by** *auto*  
**then** **show** *?thesis* **using** *tautology-decomp literal.exhaust uminus-Neg uminus-Pos* **by** *metis*  
**qed**

**lemma** *remove-literal-in-model-tautology*:  
**assumes**  $I \cup \{\text{Pos } P\} \models \varphi$   
**and**  $I \cup \{\text{Neg } P\} \models \varphi$   
**shows**  $I \models \varphi \vee \text{tautology } \varphi$   
**using** *assms* **unfolding** *true-cls-def* **by** *auto*

**lemma** *tautology-imp-tautology*:  
**fixes**  $\chi \chi' :: 'v \text{ clause}$   
**assumes**  $\forall I. \text{total-over-m } I \{\chi\} \longrightarrow I \models \chi \longrightarrow I \models \chi'$  **and** *tautology*  $\chi$   
**shows** *tautology*  $\chi'$  **unfolding** *tautology-def*  
**proof** (*intro allI HOL.impI*)  
**fix**  $I :: 'v \text{ literal set}$   
**assume** *totI*: *total-over-set*  $I$  (*atms-of*  $\chi'$ )  
**let**  $?I' = \{\text{Pos } v \mid v. v \in \text{atms-of } \chi \wedge v \notin \text{atms-of-s } I\}$   
**have** *totI'*: *total-over-m*  $(I \cup ?I') \{\chi\}$  **unfolding** *total-over-m-def* *total-over-set-def* **by** *auto*  
**then** **have**  $\chi: I \cup ?I' \models \chi$  **using** *assms*(2) **unfolding** *total-over-m-def* *tautology-def* **by** *simp*  
**then** **have**  $I \cup (?I' - I) \models \chi'$  **using** *assms*(1) *totI'* **by** *auto*  
**moreover** **have**  $\bigwedge L. L \in \# \chi' \implies L \notin ?I'$   
**using** *totI* **unfolding** *total-over-set-def* **by** (*auto dest: pos-lit-in-atms-of*)  
**ultimately** **show**  $I \models \chi'$  **unfolding** *true-cls-def* **by** *auto*  
**qed**

### 11.2.8 Entailment for clauses and propositions

**definition** *true-cls-cls* :: 'a clause  $\Rightarrow$  'a clause  $\Rightarrow$  bool (**infix**  $\models_f$  49) **where**  
 $\psi \models_f \chi \longleftrightarrow (\forall I. \text{total-over-m } I (\{\psi\} \cup \{\chi\}) \longrightarrow \text{consistent-interp } I \longrightarrow I \models \psi \longrightarrow I \models \chi)$

**definition** *true-cls-clss* :: 'a clause  $\Rightarrow$  'a clauses  $\Rightarrow$  bool (**infix**  $\models_{fs}$  49) **where**  
 $\psi \models_{fs} \chi \longleftrightarrow (\forall I. \text{total-over-m } I (\{\psi\} \cup \chi) \longrightarrow \text{consistent-interp } I \longrightarrow I \models \psi \longrightarrow I \models_s \chi)$

**definition** *true-clss-cls* :: 'a clauses  $\Rightarrow$  'a clause  $\Rightarrow$  bool (**infix**  $\models_p$  49) **where**  
 $N \models_p \chi \longleftrightarrow (\forall I. \text{total-over-m } I (N \cup \{\chi\}) \longrightarrow \text{consistent-interp } I \longrightarrow I \models_s N \longrightarrow I \models \chi)$

**definition** *true-clss-clss* :: 'a clauses  $\Rightarrow$  'a clauses  $\Rightarrow$  bool (**infix**  $\models_{ps}$  49) **where**  
 $N \models_{ps} N' \longleftrightarrow (\forall I. \text{total-over-m } I (N \cup N') \longrightarrow \text{consistent-interp } I \longrightarrow I \models_s N \longrightarrow I \models_s N')$

**lemma** *true-cls-cls-refl[simp]*:  
 $A \models_f A$   
**unfolding** *true-cls-cls-def* **by** *auto*

**lemma** *true-cls-cls-insert-l[simp]*:  
 $a \models_f C \implies \text{insert } a \ A \models_p C$   
**unfolding** *true-cls-cls-def* *true-clss-cls-def* *true-clss-def* **by** *fastforce*

**lemma** *true-cls-clss-empty[iff]*:  
 $N \models_{fs} \{\}$   
**unfolding** *true-cls-clss-def* **by** *auto*

**lemma** *true-prop-true-clause[iff]*:  
 $\{\varphi\} \models_p \psi \longleftrightarrow \varphi \models_f \psi$   
**unfolding** *true-cls-cls-def* *true-clss-cls-def* **by** *auto*

**lemma** *true-clss-clss-true-clss-cls[iff]*:  
 $N \models_{ps} \{\psi\} \longleftrightarrow N \models_p \psi$   
**unfolding** *true-clss-clss-def* *true-clss-cls-def* **by** *auto*

**lemma** *true-clss-clss-true-cls-clss[iff]*:  
 $\{\chi\} \models_{ps} \psi \longleftrightarrow \chi \models_{fs} \psi$   
**unfolding** *true-clss-clss-def* *true-cls-clss-def* **by** *auto*

**lemma** *true-clss-clss-empty[simp]*:  
 $N \models_{ps} \{\}$   
**unfolding** *true-clss-clss-def* **by** *auto*

**lemma** *true-clss-cls-subset*:  
 $A \subseteq B \implies A \models_p CC \implies B \models_p CC$   
**unfolding** *true-clss-cls-def* *total-over-m-union* **by** (*simp add: total-over-m-subset true-clss-mono*)

**lemma** *true-clss-clss-mono-l[simp]*:  
 $A \models_p CC \implies A \cup B \models_p CC$   
**by** (*auto intro: true-clss-cls-subset*)

**lemma** *true-clss-clss-mono-l2[simp]*:  
 $B \models_p CC \implies A \cup B \models_p CC$   
**by** (*auto intro: true-clss-cls-subset*)

**lemma** *true-clss-cls-mono-r[simp]*:  
 $A \models_p CC \implies A \models_p CC + CC'$



```

unfolding true-clss-cls-def total-over-m-union total-over-m-sum by blast

lemma true-clss-cls-mono-r'[simp]:
   $A \models_p CC' \implies A \models_p CC + CC'$ 
unfolding true-clss-cls-def total-over-m-union total-over-m-sum by blast

lemma true-clss-clss-union-l[simp]:
   $A \models_{ps} CC \implies A \cup B \models_{ps} CC$ 
unfolding true-clss-clss-def total-over-m-union by fastforce

lemma true-clss-clss-union-l-r[simp]:
   $B \models_{ps} CC \implies A \cup B \models_{ps} CC$ 
unfolding true-clss-clss-def total-over-m-union by fastforce

lemma true-clss-cls-in[simp]:
   $CC \in A \implies A \models_p CC$ 
unfolding true-clss-cls-def true-clss-def total-over-m-union by fastforce

lemma true-clss-cls-insert-l[simp]:
   $A \models_p C \implies \text{insert } a \ A \models_p C$ 
unfolding true-clss-cls-def true-clss-def using total-over-m-union
by (metis Un-iff insert-is-Un sup commute)

lemma true-clss-clss-insert-l[simp]:
   $A \models_{ps} C \implies \text{insert } a \ A \models_{ps} C$ 
unfolding true-clss-cls-def true-clss-clss-def true-clss-def by blast

lemma true-clss-clss-union-and[iff]:
   $A \models_{ps} C \cup D \iff (A \models_{ps} C \wedge A \models_{ps} D)$ 
proof
{
  fix A C D :: 'a clauses
  assume A:  $A \models_{ps} C \cup D$ 
  have A  $A \models_{ps} C$ 
    unfolding true-clss-clss-def true-clss-cls-def insert-def total-over-m-insert
  proof (intro allI impI)
    fix I
    assume
      totAC: total-over-m I (A  $\cup$  C) and
      cons: consistent-interp I and
      I: I  $\models_s$  A
    then have tot: total-over-m I A and tot': total-over-m I C by auto
    obtain I' where
      tot': total-over-m (I  $\cup$  I') (A  $\cup$  C  $\cup$  D) and
      cons': consistent-interp (I  $\cup$  I') and
      H:  $\forall x \in I'. \text{atm-of } x \in \text{atms-of-ms } D \wedge \text{atm-of } x \notin \text{atms-of-ms } (A \cup C)$ 
    using total-over-m-consistent-extension[OF - cons, of A  $\cup$  C] tot tot' by blast
    moreover have I  $\cup$  I'  $\models_s$  A using I by simp
    ultimately have I  $\cup$  I'  $\models_s$  C  $\cup$  D using A unfolding true-clss-clss-def by auto
    then have I  $\cup$  I'  $\models_s$  C  $\cup$  D by auto
    then show I  $\models_s$  C using notin-vars-union-true-clss-true-clss[of I'] H by auto
  qed
} note H = this
assume A  $A \models_{ps} C \cup D$ 
then show A  $A \models_{ps} C \wedge A \models_{ps} D$  using H[of A] Un-commute[of C D] by metis

```

**next**  
**assume**  $A \models_{ps} C \wedge A \models_{ps} D$   
**then show**  $A \models_{ps} C \cup D$   
**unfolding** *true-clss-clss-def* **by** *auto*  
**qed**

**lemma** *true-clss-clss-insert[iff]*:  
 $A \models_{ps} \text{insert } L \text{ } Ls \longleftrightarrow (A \models_p L \wedge A \models_{ps} Ls)$   
**using** *true-clss-clss-union-and*[*of*  $A \{L\} Ls$ ] **by** *auto*

**lemma** *true-clss-clss-subset*:  
 $A \subseteq B \implies A \models_{ps} CC \implies B \models_{ps} CC$   
**by** (*metis subset-Un-eq true-clss-clss-union-l*)

**lemma** *union-trus-clss-clss[simp]*:  $A \cup B \models_{ps} B$   
**unfolding** *true-clss-clss-def* **by** *auto*

**lemma** *true-clss-clss-remove[simp]*:  
 $A \models_{ps} B \implies A \models_{ps} B - C$   
**by** (*metis Un-Diff-Int true-clss-clss-union-and*)

**lemma** *true-clss-clss-subsetE*:  
 $N \models_{ps} B \implies A \subseteq B \implies N \models_{ps} A$   
**by** (*metis sup.orderE true-clss-clss-union-and*)

**lemma** *true-clss-clss-in-imp-true-clss-clss*:  
**assumes**  $N \models_{ps} U$   
**and**  $A \in U$   
**shows**  $N \models_p A$   
**using** *assms mk-disjoint-insert* **by** *fastforce*

**lemma** *all-in-true-clss-clss*:  $\forall x \in B. x \in A \implies A \models_{ps} B$   
**unfolding** *true-clss-clss-def true-clss-def* **by** *auto*

**lemma** *true-clss-clss-left-right*:  
**assumes**  $A \models_{ps} B$   
**and**  $A \cup B \models_{ps} M$   
**shows**  $A \models_{ps} M \cup B$   
**using** *assms* **unfolding** *true-clss-clss-def* **by** *auto*

**lemma** *true-clss-clss-generalise-true-clss-clss*:  
 $A \cup C \models_{ps} D \implies B \models_{ps} C \implies A \cup B \models_{ps} D$   
**proof** –  
**assume**  $a1: A \cup C \models_{ps} D$   
**assume**  $B \models_{ps} C$   
**then have**  $f2: \bigwedge M. M \cup B \models_{ps} C$   
**by** (*meson true-clss-clss-union-l-r*)  
**have**  $\bigwedge M. C \cup (M \cup A) \models_{ps} D$   
**using**  $a1$  **by** (*simp add: Un-commute sup-left-commute*)  
**then show** *?thesis*  
**using**  $f2$  **by** (*metis (no-types) Un-commute true-clss-clss-left-right true-clss-clss-union-and*)  
**qed**

**lemma** *true-clss-clss-or-true-clss-clss-or-not-true-clss-clss-or*:  
**assumes**  $D: N \models_p D + \{\# - L\# \}$

```

and  $C: N \models_p C + \{\#L\# \}$ 
shows  $N \models_p D + C$ 
unfolding true-clss-clss-def
proof (intro allI impI)
fix  $I$ 
assume
  tot: total-over-m  $I (N \cup \{D + C\})$  and
  consistent-interp  $I$  and
 $I \models_s N$ 
{
  assume  $L: L \in I \vee -L \in I$ 
  then have total-over-m  $I \{D + \{\#- L\#\}\}$ 
    using tot by (cases  $L$ ) auto
  then have  $I \models D + \{\#- L\#\}$  using  $D \langle I \models_s N \rangle$  tot  $\langle$ consistent-interp  $I \rangle$ 
    unfolding true-clss-clss-def by auto
  moreover
    have total-over-m  $I \{C + \{\#L\#\}\}$ 
      using  $L$  tot by (cases  $L$ ) auto
    then have  $I \models C + \{\#L\#\}$ 
      using  $C \langle I \models_s N \rangle$  tot  $\langle$ consistent-interp  $I \rangle$  unfolding true-clss-clss-def by auto
    ultimately have  $I \models D + C$  using  $\langle$ consistent-interp  $I \rangle$  consistent-interp-def by fastforce
  }
moreover {
  assume  $L: L \notin I \wedge -L \notin I$ 
  let  $?I' = I \cup \{L\}$ 
  have consistent-interp  $?I'$  using  $L \langle$ consistent-interp  $I \rangle$  by auto
  moreover have total-over-m  $?I' \{D + \{\#- L\#\}\}$ 
    using tot unfolding total-over-m-def total-over-set-def by (auto simp add: atms-of-def)
  moreover have total-over-m  $?I' N$  using tot using total-union by blast
  moreover have  $?I' \models_s N$  using  $\langle I \models_s N \rangle$  using true-clss-union-increase by blast
  ultimately have  $?I' \models D + \{\#- L\#\}$ 
    using  $D$  unfolding true-clss-clss-def by blast
  then have  $?I' \models D$  using  $L$  by auto
  moreover
    have total-over-set  $I (\text{atms-of } (D + C))$  using tot by auto
    then have  $L \notin \# D \wedge -L \notin \# D$ 
      using  $L$  unfolding total-over-set-def atms-of-def by (cases  $L$ ) force+
    ultimately have  $I \models D + C$  unfolding true-clss-clss-def by auto
  }
ultimately show  $I \models D + C$  by blast
qed

```

```

lemma true-clss-union-mset[iff]:  $I \models C \# \cup D \longleftrightarrow I \models C \vee I \models D$ 
  unfolding true-clss-clss-def by force

```

```

lemma true-clss-clss-union-mset-true-clss-clss-or-not-true-clss-clss-or:
  assumes
     $D: N \models_p D + \{\#- L\#\}$  and
     $C: N \models_p C + \{\#L\#\}$ 
  shows  $N \models_p D \# \cup C$ 
  unfolding true-clss-clss-def
proof (intro allI impI)
fix  $I$ 
assume
  tot: total-over-m  $I (N \cup \{D \# \cup C\})$  and

```

```

consistent-interp I and
I  $\models_s$  N
{
  assume L: L  $\in$  I  $\vee$   $\neg$ L  $\in$  I
  then have total-over-m I {D + {#- L#}}
    using tot by (cases L) auto
  then have I  $\models$  D + {#- L#}
    using D  $\langle$  I  $\models_s$  N  $\rangle$  tot  $\langle$  consistent-interp I  $\rangle$  unfolding true-clss-cls-def by auto
  moreover
    have total-over-m I {C + {#L#}}
      using L tot by (cases L) auto
    then have I  $\models$  C + {#L#}
      using C  $\langle$  I  $\models_s$  N  $\rangle$  tot  $\langle$  consistent-interp I  $\rangle$  unfolding true-clss-cls-def by auto
  ultimately have I  $\models$  D  $\#_{\cup}$  C using  $\langle$  consistent-interp I  $\rangle$  unfolding consistent-interp-def
  by auto
}
moreover {
  assume L: L  $\notin$  I  $\wedge$   $\neg$ L  $\notin$  I
  let ?I' = I  $\cup$  {L}
  have consistent-interp ?I' using L  $\langle$  consistent-interp I  $\rangle$  by auto
  moreover have total-over-m ?I' {D + {#- L#}}
    using tot unfolding total-over-m-def total-over-set-def by (auto simp add: atms-of-def)
  moreover have total-over-m ?I' N using tot using total-union by blast
  moreover have ?I'  $\models_s$  N using  $\langle$  I  $\models_s$  N  $\rangle$  using true-clss-union-increase by blast
  ultimately have ?I'  $\models$  D + {#- L#}
    using D unfolding true-clss-cls-def by blast
  then have ?I'  $\models$  D using L by auto
  moreover
    have total-over-set I (atms-of (D + C)) using tot by auto
    then have L  $\notin$  # D  $\wedge$   $\neg$ L  $\notin$  # D
      using L unfolding total-over-set-def atms-of-def by (cases L) force+
    ultimately have I  $\models$  D  $\#_{\cup}$  C unfolding true-clss-def by auto
  }
ultimately show I  $\models$  D  $\#_{\cup}$  C by blast
qed

```

**lemma** *satisfiable-carac*[*iff*]:

$(\exists I. \text{consistent-interp } I \wedge I \models_s \varphi) \longleftrightarrow \text{satisfiable } \varphi$  (**is**  $(\exists I. ?Q \ I) \longleftrightarrow ?S$ )

**proof**

assume ?S

then show  $\exists I. ?Q \ I$  unfolding *satisfiable-def* by auto

**next**

assume  $\exists I. ?Q \ I$

then obtain I where cons: *consistent-interp* I and I: I  $\models_s \varphi$  by *metis*

let ?I' = {Pos v | v. v  $\notin$  atms-of-s I  $\wedge$  v  $\in$  atms-of-ms  $\varphi$ }

have *consistent-interp* (I  $\cup$  ?I')

using cons unfolding *consistent-interp-def* by (intro allI) (rename-tac L, case-tac L, auto)

moreover have total-over-m (I  $\cup$  ?I')  $\varphi$

unfolding total-over-m-def total-over-set-def by auto

moreover have I  $\cup$  ?I'  $\models_s \varphi$

using I unfolding *Ball-def* *true-clss-def* *true-clss-def* by auto

ultimately show ?S unfolding *satisfiable-def* by blast

**qed**

**lemma** *satisfiable-carac'*[*simp*]: *consistent-interp* I  $\implies$  I  $\models_s \varphi \implies$  *satisfiable*  $\varphi$

using *satisfiable-carac* by *metis*

### 11.3 Subsumptions

**lemma** *subsumption-total-over-m*:

**assumes**  $A \subseteq\# B$

**shows**  $\text{total-over-m } I \{B\} \implies \text{total-over-m } I \{A\}$

**using** *assms unfolding subset-mset-def total-over-m-def total-over-set-def*

**by** (*auto simp add: mset-le-exists-conv*)

**lemma** *atms-of-replicate-mset-replicate-mset-uminus[simp]*:

$\text{atms-of } (D - \text{replicate-mset } (\text{count } D \ L) \ L - \text{replicate-mset } (\text{count } D \ (-L)) \ (-L))$   
 $= \text{atms-of } D - \{\text{atm-of } L\}$

**by** (*fastforce simp: atm-of-eq-atm-of atms-of-def*)

**lemma** *subsumption-chained*:

**assumes**

$\forall I. \text{total-over-m } I \{D\} \longrightarrow I \models D \longrightarrow I \models \varphi$  **and**

$C \subseteq\# D$

**shows**  $(\forall I. \text{total-over-m } I \{C\} \longrightarrow I \models C \longrightarrow I \models \varphi) \vee \text{tautology } \varphi$

**using** *assms*

**proof** (*induct card \{Pos v \mid v. v \in \text{atms-of } D \wedge v \notin \text{atms-of } C\} \text{ arbitrary: } D*  
*rule: nat-less-induct-case*)

**case** 0 **note**  $n = \text{this}(1)$  **and**  $H = \text{this}(2)$  **and**  $\text{incl} = \text{this}(3)$

**then have**  $\text{atms-of } D \subseteq \text{atms-of } C$  **by** *auto*

**then have**  $\forall I. \text{total-over-m } I \{C\} \longrightarrow \text{total-over-m } I \{D\}$

**unfolding** *total-over-m-def total-over-set-def* **by** *auto*

**moreover have**  $\forall I. I \models C \longrightarrow I \models D$  **using** *incl true-cls-mono-leD* **by** *blast*

**ultimately show** *?case* **using**  $H$  **by** *auto*

**next**

**case** (*Suc n D*) **note**  $IH = \text{this}(1)$  **and**  $\text{card} = \text{this}(2)$  **and**  $H = \text{this}(3)$  **and**  $\text{incl} = \text{this}(4)$

**let**  $\text{?atms} = \{\text{Pos } v \mid v. v \in \text{atms-of } D \wedge v \notin \text{atms-of } C\}$

**have** *finite ?atms* **by** *auto*

**then obtain**  $L$  **where**  $L: L \in \text{?atms}$

**using** *card* **by** (*metis (no-types, lifting) Collect-empty-eq card-0-eq mem-Collect-eq*  
*nat.simps(3)*)

**let**  $\text{?D}' = D - \text{replicate-mset } (\text{count } D \ L) \ L - \text{replicate-mset } (\text{count } D \ (-L)) \ (-L)$

**have**  $\text{atms-of-}D: \text{atms-of-ms } \{D\} \subseteq \text{atms-of-ms } \{\text{?D}'\} \cup \{\text{atm-of } L\}$  **by** *auto*

{

**fix**  $I$

**assume**  $\text{total-over-m } I \{\text{?D}'\}$

**then have**  $\text{tot: total-over-m } (I \cup \{L\}) \{D\}$

**unfolding** *total-over-m-def total-over-set-def* **using** *atms-of-D* **by** *auto*

**assume**  $IDL: I \models \text{?D}'$

**then have**  $I \cup \{L\} \models D$  **unfolding** *true-cls-def* **by** *force*

**then have**  $I \cup \{L\} \models \varphi$  **using**  $H \text{ tot}$  **by** *auto*

**moreover**

**have**  $\text{tot': total-over-m } (I \cup \{-L\}) \{D\}$

**using** *tot* **unfolding** *total-over-m-def total-over-set-def* **by** *auto*

**have**  $I \cup \{-L\} \models D$  **using**  $IDL$  **unfolding** *true-cls-def* **by** *force*

**then have**  $I \cup \{-L\} \models \varphi$  **using**  $H \text{ tot'}$  **by** *auto*

**ultimately have**  $I \models \varphi \vee \text{tautology } \varphi$

**using** *L remove-literal-in-model-tautology* **by** *force*

```

} note  $H' = this$ 

have  $L \notin \# C$  and  $\neg L \notin \# C$  using  $L \text{ atm-iff-pos-or-neg-lit}$  by force+
then have  $C \text{-in-} D'$ :  $C \subseteq \# ?D'$  using  $\langle C \subseteq \# D \rangle$  by (auto simp: subseteq-mset-def not-in-iff)
have card  $\{Pos\ v \mid v. v \in \text{atms-of } ?D' \wedge v \notin \text{atms-of } C\} <$ 
  card  $\{Pos\ v \mid v. v \in \text{atms-of } D \wedge v \notin \text{atms-of } C\}$ 
  using  $L$  by (auto intro!: psubset-card-mono)
then show ?case
  using IH  $C \text{-in-} D'$   $H'$  unfolding card[symmetric] by blast
qed

```

## 11.4 Removing Duplicates

```

lemma tautology-remdups-mset[iff]:
  tautology (remdups-mset  $C$ )  $\longleftrightarrow$  tautology  $C$ 
  unfolding tautology-decomp by auto

```

```

lemma atms-of-remdups-mset[simp]: atms-of (remdups-mset  $C$ ) = atms-of  $C$ 
  unfolding atms-of-def by auto

```

```

lemma true-clss-remdups-mset[iff]:  $I \models \text{remdups-mset } C \longleftrightarrow I \models C$ 
  unfolding true-clss-def by auto

```

```

lemma true-clss-clss-remdups-mset[iff]:  $A \models_p \text{remdups-mset } C \longleftrightarrow A \models_p C$ 
  unfolding true-clss-clss-def total-over-m-def by auto

```

## 11.5 Set of all Simple Clauses

```

definition simple-clss :: ' $v$  set  $\Rightarrow$  ' $v$  clause set where
  simple-clss atms =  $\{C. \text{atms-of } C \subseteq \text{atms} \wedge \neg \text{tautology } C \wedge \text{distinct-mset } C\}$ 

```

```

lemma simple-clss-empty[simp]:
  simple-clss  $\{\}$  =  $\{\{\#\}\}$ 
  unfolding simple-clss-def by auto

```

```

lemma simple-clss-insert:
  assumes  $l \notin \text{atms}$ 
  shows simple-clss (insert  $l$  atms) =
    (op +  $\{\#Pos\ l\#\}$ ) ' (simple-clss atms)
     $\cup$  (op +  $\{\#Neg\ l\#\}$ ) ' (simple-clss atms)
     $\cup$  simple-clss atms(is ? $I$  = ? $U$ )

```

```

proof (standard; standard)
  fix  $C$ 
  assume  $C \in ?I$ 
  then have
    atms: atms-of  $C \subseteq \text{insert } l \text{ atms}$  and
    taut:  $\neg \text{tautology } C$  and
    dist: distinct-mset  $C$ 
  unfolding simple-clss-def by auto
  have  $H$ :  $\bigwedge x. x \in \# C \implies \text{atm-of } x \in \text{insert } l \text{ atms}$ 
    using atm-of-lit-in-atms-of atms by blast
  consider
    (Add)  $L$  where  $L \in \# C$  and  $L = Neg\ l \vee L = Pos\ l$ 
    | (No)  $Pos\ l \notin \# C$   $Neg\ l \notin \# C$ 
  by auto
  then show  $C \in ?U$ 

```

```

proof cases
  case Add
    then have  $L \notin \# C - \{\#L\}$ 
      using dist unfolding distinct-mset-def by (auto simp: not-in-iff)
    moreover have  $-L \notin \# C$ 
      using taut Add by auto
    ultimately have  $\text{atms-of } (C - \{\#L\}) \subseteq \text{atms}$ 
      using atms Add by (smt H atms-of-def imageE in-diffD insertE literal.exhaust-sel
        subset-iff uminus-Neg uminus-Pos)

    moreover have  $\neg \text{tautology } (C - \{\#L\})$ 
      using taut by (metis Add(1) insert-DiffM tautology-add-single)
    moreover have distinct-mset  $(C - \{\#L\})$ 
      using dist by auto
    ultimately have  $(C - \{\#L\}) \in \text{simple-clss atms}$ 
      using Add unfolding simple-clss-def by auto
    moreover have  $C = \{\#L\} + (C - \{\#L\})$ 
      using Add by (auto simp: multiset-eq-iff)
    ultimately show ?thesis using Add by auto

  next
    case No
    then have  $C \in \text{simple-clss atms}$ 
      using taut atms dist unfolding simple-clss-def
      by (auto simp: atm-iff-pos-or-neg-lit split: if-split-asm dest!: H)
    then show ?thesis by blast

  qed

next
fix  $C$ 
assume  $C \in ?U$ 
then consider
  (Add)  $L \ C'$  where  $C = \{\#L\} + C'$  and  $C' \in \text{simple-clss atms}$  and
   $L = \text{Pos } l \vee L = \text{Neg } l$ 
  | (No)  $C \in \text{simple-clss atms}$ 
by auto
then show  $C \in ?I$ 
proof cases
  case No
  then show ?thesis unfolding simple-clss-def by auto
next
  case (Add  $L \ C'$ ) note  $C' = \text{this}(1)$  and  $C = \text{this}(2)$  and  $L = \text{this}(3)$ 
  then have
    atms:  $\text{atms-of } C' \subseteq \text{atms}$  and
    taut:  $\neg \text{tautology } C'$  and
    dist: distinct-mset  $C'$ 
    unfolding simple-clss-def by auto
  have  $\text{atms-of } C \subseteq \text{insert } l \text{ atms}$ 
    using atms  $C' \ L$  by auto
  moreover have  $\neg \text{tautology } C$ 
    using taut  $C' \ L$  by (metis assms atm-of-lit-in-atms-of atms literal.sel(1,2) subset-eq
      tautology-add-single uminus-Neg uminus-Pos)
  moreover have distinct-mset  $C$ 
    using dist  $C' \ L$ 
    by (metis assms atm-of-lit-in-atms-of atms contra-subsetD distinct-mset-add-single
      literal.sel(1,2))
  ultimately show ?thesis unfolding simple-clss-def by blast

```

qed  
qed

lemma *simple-clss-finite*:

fixes *atms* :: 'v set  
assumes *finite atms*  
shows *finite (simple-clss atms)*  
using *assms* by (induction rule: *finite-induct*) (auto simp: *simple-clss-insert*)

lemma *simple-clssE*:

assumes  
 $x \in \text{simple-clss } \textit{atms}$   
shows  $\textit{atms-of } x \subseteq \textit{atms} \wedge \neg \text{tautology } x \wedge \text{distinct-mset } x$   
using *assms* unfolding *simple-clss-def* by auto

lemma *cls-in-simple-clss*:

shows  $\{\#\} \in \text{simple-clss } s$   
unfolding *simple-clss-def* by auto

lemma *simple-clss-card*:

fixes *atms* :: 'v set  
assumes *finite atms*  
shows  $\text{card } (\text{simple-clss } \textit{atms}) \leq (3::\text{nat}) \wedge (\text{card } \textit{atms})$   
using *assms*

proof (induct *atms* rule: *finite-induct*)

case *empty*  
then show ?case by auto

next

case (insert *l C*) note *fin = this(1)* and *l = this(2)* and *IH = this(3)*

have *notin*:

$\bigwedge C'. \{\#\text{Pos } l\# \} + C' \notin \text{simple-clss } C$   
 $\bigwedge C'. \{\#\text{Neg } l\# \} + C' \notin \text{simple-clss } C$   
using *l* unfolding *simple-clss-def* by auto

have *H*:  $\bigwedge C' D. \{\#\text{Pos } l\# \} + C' = \{\#\text{Neg } l\# \} + D \implies D \in \text{simple-clss } C \implies \text{False}$

proof -

fix *C' D*

assume *C'D*:  $\{\#\text{Pos } l\# \} + C' = \{\#\text{Neg } l\# \} + D$  and *D*:  $D \in \text{simple-clss } C$

then have  $\text{Pos } l \in \# D$  by (metis *insert-noteq-member literal.distinct(1) union-commute*)

then have  $l \in \text{atms-of } D$

by (simp add: *atm-iff-pos-or-neg-lit*)

then show *False* using *D l* unfolding *simple-clss-def* by auto

qed

let *?P* =  $(\text{op} + \{\#\text{Pos } l\# \}) \text{ ' } (\text{simple-clss } C)$

let *?N* =  $(\text{op} + \{\#\text{Neg } l\# \}) \text{ ' } (\text{simple-clss } C)$

let *?O* = *simple-clss C*

have  $\text{card } (?P \cup ?N \cup ?O) = \text{card } (?P \cup ?N) + \text{card } ?O$

apply (subst *card-Un-disjoint*)

using *l fin* by (auto simp: *simple-clss-finite notin*)

moreover have  $\text{card } (?P \cup ?N) = \text{card } ?P + \text{card } ?N$

apply (subst *card-Un-disjoint*)

using *l fin H* by (auto simp: *simple-clss-finite notin*)

moreover

have  $\text{card } ?P = \text{card } ?O$

using *inj-on-iff-eq-card[of ?O op + {\#Pos l\#}]*

by (auto simp: *fin simple-clss-finite inj-on-def*)



```

moreover have  $\text{card } ?N = \text{card } ?O$ 
  using inj-on-iff-eq-card[of ?O op + {#Neg l#}]
  by (auto simp: fin simple-clss-finite inj-on-def)
moreover have  $(3::\text{nat}) \wedge \text{card } (\text{insert } l \ C) = 3 \wedge (\text{card } C) + 3 \wedge (\text{card } C) + 3 \wedge (\text{card } C)$ 
  using l by (simp add: fin mult-2-right numeral-3-eq-3)
ultimately show ?case using IH l by (auto simp: simple-clss-insert)
qed

```

```

lemma simple-clss-mono:
  assumes incl: atms  $\subseteq$  atms'
  shows simple-clss atms  $\subseteq$  simple-clss atms'
  using assms unfolding simple-clss-def by auto

```

```

lemma distinct-mset-not-tautology-implies-in-simple-clss:
  assumes distinct-mset  $\chi$  and  $\neg \text{tautology } \chi$ 
  shows  $\chi \in \text{simple-clss } (\text{atms-of } \chi)$ 
  using assms unfolding simple-clss-def by auto

```

```

lemma simplified-in-simple-clss:
  assumes distinct-mset-set  $\psi$  and  $\forall \chi \in \psi. \neg \text{tautology } \chi$ 
  shows  $\psi \subseteq \text{simple-clss } (\text{atms-of-ms } \psi)$ 
  using assms unfolding simple-clss-def
  by (auto simp: distinct-mset-set-def atms-of-ms-def)

```

## 11.6 Experiment: Expressing the Entailments as Locales

```

locale entail =
  fixes entail :: 'a set  $\Rightarrow$  'b  $\Rightarrow$  bool (infix  $\models_e$  50)
  assumes entail-insert[simp]:  $I \neq \{\} \Rightarrow \text{insert } L \ I \models_e x \longleftrightarrow \{L\} \models_e x \vee I \models_e x$ 
  assumes entail-union[simp]:  $I \models_e A \Rightarrow I \cup I' \models_e A$ 
begin

```

```

definition entails :: 'a set  $\Rightarrow$  'b set  $\Rightarrow$  bool (infix  $\models_{es}$  50) where
   $I \models_{es} A \longleftrightarrow (\forall a \in A. I \models_e a)$ 

```

```

lemma entails-empty[simp]:
   $I \models_{es} \{\}$ 
  unfolding entails-def by auto

```

```

lemma entails-single[iff]:
   $I \models_{es} \{a\} \longleftrightarrow I \models_e a$ 
  unfolding entails-def by auto

```

```

lemma entails-insert-l[simp]:
   $M \models_{es} A \Rightarrow \text{insert } L \ M \models_{es} A$ 
  unfolding entails-def by (metis Un-commute entail-union insert-is-Un)

```

```

lemma entails-union[iff]:  $I \models_{es} CC \cup DD \longleftrightarrow I \models_{es} CC \wedge I \models_{es} DD$ 
  unfolding entails-def by blast

```

```

lemma entails-insert[iff]:  $I \models_{es} \text{insert } C \ DD \longleftrightarrow I \models_e C \wedge I \models_{es} DD$ 
  unfolding entails-def by blast

```

```

lemma entails-insert-mono:  $DD \subseteq CC \Rightarrow I \models_{es} CC \Rightarrow I \models_{es} DD$ 
  unfolding entails-def by blast

```

```

lemma entails-union-increase[simp]:
  assumes  $I \models_{es} \psi$ 
  shows  $I \cup I' \models_{es} \psi$ 
  using assms unfolding entails-def by auto

lemma true-clss-commute-l:
   $(I \cup I' \models_{es} \psi) \longleftrightarrow (I' \cup I \models_{es} \psi)$ 
  by (simp add: Un-commute)

lemma entails-remove[simp]:  $I \models_{es} N \implies I \models_{es} \text{Set.remove } a \ N$ 
  by (simp add: entails-def)

lemma entails-remove-minus[simp]:  $I \models_{es} N \implies I \models_{es} N - A$ 
  by (simp add: entails-def)

end

interpretation true-cls: entail true-cls
  by standard (auto simp add: true-cls-def)

```

## 11.7 Entailment to be extended

**definition** true-clss-ext :: 'a literal set  $\Rightarrow$  'a literal multiset set  $\Rightarrow$  bool (**infix**  $\models_{sext}$  49)  
**where**  
 $I \models_{sext} N \longleftrightarrow (\forall J. I \subseteq J \longrightarrow \text{consistent-interp } J \longrightarrow \text{total-over-m } J \ N \longrightarrow J \models_s N)$

```

lemma true-clss-imp-true-cls-ext:
   $I \models_s N \implies I \models_{sext} N$ 
  unfolding true-clss-ext-def by (metis sup.orderE true-clss-union-increase')

```

```

lemma true-clss-ext-decrease-right-remove-r:
  assumes  $I \models_{sext} N$ 
  shows  $I \models_{sext} N - \{C\}$ 
  unfolding true-clss-ext-def
proof (intro allI impI)
  fix J
  assume
     $I \subseteq J$  and
    cons: consistent-interp J and
    tot: total-over-m J (N - {C})
  let ?J = J  $\cup \{ \text{Pos } (\text{atm-of } P) \mid P. P \in \# \ C \wedge \text{atm-of } P \notin \text{atm-of } 'J \}$ 
  have  $I \subseteq ?J$  using  $\langle I \subseteq J \rangle$  by auto
  moreover have consistent-interp ?J
    using cons unfolding consistent-interp-def apply (intro allI)
    by (rename-tac L, case-tac L) (fastforce simp add: image-iff)+
  moreover have total-over-m ?J N
    using tot unfolding total-over-m-def total-over-set-def atms-of-ms-def
    apply clarify
    apply (rename-tac l a, case-tac a  $\in N - \{C\}$ )
    apply auto[]
    using atms-of-s-def atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set
    by (fastforce simp: atms-of-def)
  ultimately have ?J  $\models_s N$ 
    using assms unfolding true-clss-ext-def by blast
  then have ?J  $\models_s N - \{C\}$  by auto
  have  $\{v \in ?J. \text{atm-of } v \in \text{atms-of-ms } (N - \{C\})\} \subseteq J$ 

```

```

    using tot unfolding total-over-m-def total-over-set-def
    by (auto intro!: rev-image-eqI)
  then show  $J \models_s N - \{C\}$ 
    using true-clss-remove-unused[OF  $\langle ?J \models_s N - \{C\} \rangle$ ] unfolding true-clss-def
    by (meson true-clss-mono-set-mset-l)
qed

```

```

lemma consistent-true-clss-ext-satisfiable:
  assumes consistent-interp I and  $I \models_{\text{set}} A$ 
  shows satisfiable A
  by (metis Un-empty-left assms satisfiable-carac subset-Un-eq sup.left-idem
    total-over-m-consistent-extension total-over-m-empty true-clss-ext-def)

```

```

lemma not-consistent-true-clss-ext:
  assumes  $\neg \text{consistent-interp } I$ 
  shows  $I \models_{\text{set}} A$ 
  by (meson assms consistent-interp-subset true-clss-ext-def)
end

```

```

theory Prop-Logic-Multiset
imports ../lib/Multiset-More Prop-Normalisation Partial-Clausal-Logic
begin

```

## 12 Link with Multiset Version

### 12.1 Transformation to Multiset

```

fun mset-of-conj :: 'a propo  $\Rightarrow$  'a literal multiset where
  mset-of-conj (FOr  $\varphi \psi$ ) = mset-of-conj  $\varphi$  + mset-of-conj  $\psi$  |
  mset-of-conj (FVar  $v$ ) =  $\{\# \text{ Pos } v \#\}$  |
  mset-of-conj (FNot (FVar  $v$ )) =  $\{\# \text{ Neg } v \#\}$  |
  mset-of-conj FF =  $\{\#\}$ 

```

```

fun mset-of-formula :: 'a propo  $\Rightarrow$  'a literal multiset set where
  mset-of-formula (FAnd  $\varphi \psi$ ) = mset-of-formula  $\varphi \cup$  mset-of-formula  $\psi$  |
  mset-of-formula (FOr  $\varphi \psi$ ) =  $\{\text{mset-of-conj (FOr } \varphi \psi)\}$  |
  mset-of-formula (FVar  $\psi$ ) =  $\{\text{mset-of-conj (FVar } \psi)\}$  |
  mset-of-formula (FNot  $\psi$ ) =  $\{\text{mset-of-conj (FNot } \psi)\}$  |
  mset-of-formula FF =  $\{\{\#\}\}$  |
  mset-of-formula FT =  $\{\}$ 

```

### 12.2 Equisatisfiability of the two Version

```

lemma is-conj-with-TF-FNot:
  is-conj-with-TF (FNot  $\varphi$ )  $\longleftrightarrow (\exists v. \varphi = \text{FVar } v \vee \varphi = \text{FF} \vee \varphi = \text{FT})$ 
  unfolding is-conj-with-TF-def apply (rule iffI)
  apply (induction FNot  $\varphi$  rule: super-grouped-by.induct)
  apply (induction FNot  $\varphi$  rule: grouped-by.induct)
    apply simp
    apply (cases  $\varphi$ ; simp)
  apply auto
done

```

```

lemma grouped-by-COr-FNot:
  grouped-by COr (FNot  $\varphi$ )  $\longleftrightarrow (\exists v. \varphi = \text{FVar } v \vee \varphi = \text{FF} \vee \varphi = \text{FT})$ 
  unfolding is-conj-with-TF-def apply (rule iffI)

```

```

apply (induction FNot  $\varphi$  rule: grouped-by.induct)
  apply simp
  apply (cases  $\varphi$ ; simp)
apply auto
done

```

```

lemma
shows no-T-F-FF[simp]:  $\neg$ no-T-F FF and
  no-T-F-FT[simp]:  $\neg$ no-T-F FT
unfolding no-T-F-def all-subformula-st-def by auto

```

```

lemma grouped-by-CAnd-FAnd:
  grouped-by CAnd (FAnd  $\varphi1$   $\varphi2$ )  $\longleftrightarrow$  grouped-by CAnd  $\varphi1$   $\wedge$  grouped-by CAnd  $\varphi2$ 
apply (rule iffI)
apply (induction FAnd  $\varphi1$   $\varphi2$  rule: grouped-by.induct)
using connected-is-group[of CAnd  $\varphi1$   $\varphi2$ ] by auto

```

```

lemma grouped-by-COr-FOr:
  grouped-by COr (FOr  $\varphi1$   $\varphi2$ )  $\longleftrightarrow$  grouped-by COr  $\varphi1$   $\wedge$  grouped-by COr  $\varphi2$ 
apply (rule iffI)
apply (induction FOr  $\varphi1$   $\varphi2$  rule: grouped-by.induct)
using connected-is-group[of COr  $\varphi1$   $\varphi2$ ] by auto

```

```

lemma grouped-by-COr-FAnd[simp]:  $\neg$  grouped-by COr (FAnd  $\varphi1$   $\varphi2$ )
apply clarify
apply (induction FAnd  $\varphi1$   $\varphi2$  rule: grouped-by.induct)
apply auto
done

```

```

lemma grouped-by-COr-FEq[simp]:  $\neg$  grouped-by COr (FEq  $\varphi1$   $\varphi2$ )
apply clarify
apply (induction FEq  $\varphi1$   $\varphi2$  rule: grouped-by.induct)
apply auto
done

```

```

lemma [simp]:  $\neg$ grouped-by COr (FImp  $\varphi$   $\psi$ )
apply clarify
by (induction FImp  $\varphi$   $\psi$  rule: grouped-by.induct) simp-all

```

```

lemma [simp]:  $\neg$  is-conj-with-TF (FImp  $\varphi$   $\psi$ )
unfolding is-conj-with-TF-def apply clarify
by (induction FImp  $\varphi$   $\psi$  rule: super-grouped-by.induct) simp-all

```

```

lemma [simp]:  $\neg$ grouped-by COr (FEq  $\varphi$   $\psi$ )
apply clarify
by (induction FEq  $\varphi$   $\psi$  rule: grouped-by.induct) simp-all

```

```

lemma [simp]:  $\neg$  is-conj-with-TF (FEq  $\varphi$   $\psi$ )
unfolding is-conj-with-TF-def apply clarify
by (induction FEq  $\varphi$   $\psi$  rule: super-grouped-by.induct) simp-all

```

```

lemma is-conj-with-TF-Fand:
  is-conj-with-TF (FAnd  $\varphi1$   $\varphi2$ )  $\implies$  is-conj-with-TF  $\varphi1$   $\wedge$  is-conj-with-TF  $\varphi2$ 
unfolding is-conj-with-TF-def

```

```

apply (induction FAnd  $\varphi 1$   $\varphi 2$  rule: super-grouped-by.induct)
apply (auto simp: grouped-by-CAnd-FAnd intro: grouped-is-super-grouped)[]
apply auto[]
done

```

**lemma** *is-conj-with-TF-FOr*:

```

is-conj-with-TF (FOr  $\varphi 1$   $\varphi 2$ )  $\implies$  grouped-by COr  $\varphi 1 \wedge$  grouped-by COr  $\varphi 2$ 
unfolding is-conj-with-TF-def
apply (induction FOr  $\varphi 1$   $\varphi 2$  rule: super-grouped-by.induct)
apply (auto simp: grouped-by-COr-FOr)[]
apply auto[]
done

```

**lemma** *grouped-by-COr-mset-of-formula*:

```

grouped-by COr  $\varphi \implies$  mset-of-formula  $\varphi =$  (if  $\varphi = FT$  then  $\{\}$  else  $\{\text{mset-of-conj } \varphi\}$ )
by (induction  $\varphi$ ) (auto simp add: grouped-by-COr-FNot)

```

When a formula is in CNF form, then there is equisatisfiability. Remark that the definition for the entailment are slightly different:  $op \models$  uses a function assigning *True* or *False*, while  $op \models s$  uses a set where being in the list means entailment of a literal.

**theorem**

```

fixes  $\varphi :: 'v \text{ propo}$ 
assumes is-cnf  $\varphi$ 
shows  $\text{eval } A \varphi \longleftrightarrow \text{Partial-Clausal-Logic.true-clss } (\{\text{Pos } v | v. A \ v\} \cup \{\text{Neg } v | v. \neg A \ v\})$ 
  (mset-of-formula  $\varphi$ )
using assms
proof (induction  $\varphi$ )
  case FF
    then show ?case by auto
  next
    case FT
      then show ?case by auto
  next
    case (FVar  $v$ )
      then show ?case by auto
  next
    case (FAnd  $\varphi \ \psi$ )
      then show ?case
      unfolding is-cnf-def by (auto simp: is-conj-with-TF-FNot dest: is-conj-with-TF-Fand
        dest!: is-conj-with-TF-FOr)
  next
    case (FOr  $\varphi \ \psi$ )
      then have [simp]: mset-of-formula  $\varphi = \{\text{mset-of-conj } \varphi\}$  mset-of-formula  $\psi = \{\text{mset-of-conj } \psi\}$ 
        unfolding is-cnf-def by (auto dest!: is-conj-with-TF-FOr simp: grouped-by-COr-mset-of-formula
          split: if-splits)
      have is-conj-with-TF  $\varphi$  is-conj-with-TF  $\psi$ 
        using FOr(3) unfolding is-cnf-def no-T-F-def
        by (metis grouped-is-super-grouped is-conj-with-TF-FOr is-conj-with-TF-def) +
      then show ?case using FOr
        unfolding is-cnf-def by simp
  next
    case (FImp  $\varphi \ \psi$ )
      then show ?case
        unfolding is-cnf-def by auto
  next

```

```

case (FEq  $\varphi$   $\psi$ )
then show ?case
  unfolding is-cnf-def by auto
next
case (FNot  $\varphi$ )
then show ?case
  unfolding is-cnf-def by (auto simp: is-conj-with-TF-FNot)
qed

end
theory Prop-Resolution
imports Partial-Clausal-Logic List-More Wellfounded-More

begin

```

## 13 Resolution

### 13.1 Simplification Rules

**inductive** *simplify* :: '*v* clauses  $\Rightarrow$  '*v* clauses  $\Rightarrow$  bool **for** *N* :: '*v* clause set **where**

*tautology-deletion*:

$(A + \{\#Pos\ P\# \} + \{\#Neg\ P\# \}) \in N \Longrightarrow simplify\ N\ (N - \{A + \{\#Pos\ P\# \} + \{\#Neg\ P\# \}\})$

*condensation*:

$(A + \{\#L\# \} + \{\#L\# \}) \in N \Longrightarrow simplify\ N\ (N - \{A + \{\#L\# \} + \{\#L\# \}\} \cup \{A + \{\#L\# \}\})$

*subsumption*:

$A \in N \Longrightarrow A \subset\# B \Longrightarrow B \in N \Longrightarrow simplify\ N\ (N - \{B\})$

**lemma** *simplify-preserves-un-sat'*:

**fixes** *N N'* :: '*v* clauses

**assumes** *simplify N N'*

**and** *total-over-m I N*

**shows**  $I \models_s N' \longrightarrow I \models_s N$

**using** *assms*

**proof** (*induct rule: simplify.induct*)

**case** (*tautology-deletion A P*)

**then have**  $I \models A + \{\#Pos\ P\# \} + \{\#Neg\ P\# \}$

**by** (*metis total-over-m-def total-over-set-literal-defined true-clss-singleton true-clss-union true-lit-def uminus-Neg union-commute*)

**then show** ?case **by** (*metis Un-Diff-cancel2 true-clss-singleton true-clss-union*)

**next**

**case** (*condensation A P*)

**then show** ?case **by** (*metis Diff-insert-absorb Set.set-insert insertE true-clss-union true-clss-def true-clss-singleton true-clss-union*)

**next**

**case** (*subsumption A B*)

**have**  $A \neq B$  **using** *subsumption.hyps(2)* **by** *auto*

**then have**  $I \models_s N - \{B\} \Longrightarrow I \models A$  **using**  $\langle A \in N \rangle$  **by** (*simp add: true-clss-def*)

**moreover have**  $I \models A \Longrightarrow I \models B$  **using**  $\langle A \subset\# B \rangle$  **by** *auto*

**ultimately show** ?case **by** (*metis insert-Diff-single true-clss-insert*)

**qed**

**lemma** *simplify-preserves-un-sat*:

**fixes** *N N'* :: '*v* clauses

**assumes** *simplify N N'*

**and** *total-over-m I N*

```

shows  $I \models_s N \longrightarrow I \models_s N'$ 
using assms apply (induct rule: simplify.induct)
using true-clss-def by fastforce+
```

**lemma** *simplify-preserves-un-sat''*:

```

fixes  $N N' :: 'v \text{ clauses}$ 
assumes simplify  $N N'$ 
and total-over-m  $I N'$ 
shows  $I \models_s N \longrightarrow I \models_s N'$ 
using assms apply (induct rule: simplify.induct)
using true-clss-def by fastforce+
```

**lemma** *simplify-preserves-un-sat-eq*:

```

fixes  $N N' :: 'v \text{ clauses}$ 
assumes simplify  $N N'$ 
and total-over-m  $I N$ 
shows  $I \models_s N \longleftrightarrow I \models_s N'$ 
using simplify-preserves-un-sat simplify-preserves-un-sat' assms by blast
```

**lemma** *simplify-preserves-finite*:

```

assumes simplify  $\psi \psi'$ 
shows finite  $\psi \longleftrightarrow \text{finite } \psi'$ 
using assms by (induct rule: simplify.induct, auto simp add: remove-def)
```

**lemma** *rtranclp-simplify-preserves-finite*:

```

assumes rtranclp simplify  $\psi \psi'$ 
shows finite  $\psi \longleftrightarrow \text{finite } \psi'$ 
using assms by (induct rule: rtranclp-induct) (auto simp add: simplify-preserves-finite)
```

**lemma** *simplify-atms-of-ms*:

```

assumes simplify  $\psi \psi'$ 
shows atms-of-ms  $\psi' \subseteq \text{atms-of-ms } \psi$ 
using assms unfolding atms-of-ms-def
proof (induct rule: simplify.induct)
  case (tautology-deletion  $A P$ )
  then show ?case by auto
next
  case (condensation  $A P$ )
  moreover have  $A + \{\#P\# \} + \{\#P\# \} \in \psi \implies \exists x \in \psi. \text{atm-of } P \in \text{atm-of } ' \text{ set-mset } x$ 
    by (metis Un-iff atms-of-def atms-of-plus atms-of-singleton insert-iff)
  ultimately show ?case by (auto simp add: atms-of-def)
next
  case (subsumption  $A P$ )
  then show ?case by auto
qed
```

**lemma** *rtranclp-simplify-atms-of-ms*:

```

assumes rtranclp simplify  $\psi \psi'$ 
shows atms-of-ms  $\psi' \subseteq \text{atms-of-ms } \psi$ 
using assms apply (induct rule: rtranclp-induct)
  apply (fastforce intro: simplify-atms-of-ms)
using simplify-atms-of-ms by blast
```

**lemma** *factoring-imp-simplify*:

```

assumes  $\{\#L\# \} + \{\#L\# \} + C \in N$ 
```

shows  $\exists N'. \text{ simplify } N \ N'$   
**proof** –  
 have  $C + \{\#L\# \} + \{\#L\# \} \in N$  **using** *assms* **by** (*simp add: add.commute union-lcomm*)  
 from *condensation[OF this]* **show** *?thesis* **by** *blast*  
**qed**

## 13.2 Unconstrained Resolution

**type-synonym** *'v uncon-state* = *'v clauses*  
**inductive** *uncon-res* :: *'v uncon-state*  $\Rightarrow$  *'v uncon-state*  $\Rightarrow$  *bool* **where**  
*resolution*:  
 $\{\#Pos \ p\# \} + C \in N \implies \{\#Neg \ p\# \} + D \in N \implies (\{\#Pos \ p\# \} + C, \{\#Neg \ p\# \} + D) \notin$   
*already-used*  
 $\implies \text{uncon-res } (N) (N \cup \{C + D\}) \mid$   
*factoring*:  $\{\#L\# \} + \{\#L\# \} + C \in N \implies \text{uncon-res } N (N \cup \{C + \{\#L\# \}\})$

**lemma** *uncon-res-increasing*:  
**assumes** *uncon-res*  $S \ S'$  **and**  $\psi \in S$   
**shows**  $\psi \in S'$   
**using** *assms* **by** (*induct rule: uncon-res.induct*) *auto*

**lemma** *rtranclp-uncon-inference-increasing*:  
**assumes** *rtranclp uncon-res*  $S \ S'$  **and**  $\psi \in S$   
**shows**  $\psi \in S'$   
**using** *assms* **by** (*induct rule: rtranclp-induct*) (*auto simp add: uncon-res-increasing*)

### 13.2.1 Subsumption

**definition** *subsumes* :: *'a literal multiset*  $\Rightarrow$  *'a literal multiset*  $\Rightarrow$  *bool* **where**  
*subsumes*  $\chi \ \chi' \iff$   
 $(\forall I. \text{total-over-}m \ I \ \{\chi'\} \longrightarrow \text{total-over-}m \ I \ \{\chi\})$   
 $\wedge (\forall I. \text{total-over-}m \ I \ \{\chi\} \longrightarrow I \models \chi \longrightarrow I \models \chi')$

**lemma** *subsumes-refl[simp]*:  
*subsumes*  $\chi \ \chi$   
**unfolding** *subsumes-def* **by** *auto*

**lemma** *subsumes-subsumption*:  
**assumes** *subsumes*  $D \ \chi$   
**and**  $C \subset\# D$  **and**  $\neg \text{tautology } \chi$   
**shows** *subsumes*  $C \ \chi$  **unfolding** *subsumes-def*  
**using** *assms* *subsumption-total-over-m* *subsumption-chained* **unfolding** *subsumes-def*  
**by** (*blast intro!: subset-mset.less-imp-le*)

**lemma** *subsumes-tautology*:  
**assumes** *subsumes*  $(C + \{\#Pos \ P\# \} + \{\#Neg \ P\# \}) \ \chi$   
**shows** *tautology*  $\chi$   
**using** *assms* **unfolding** *subsumes-def* **by** (*simp add: tautology-def*)

## 13.3 Inference Rule

**type-synonym** *'v state* = *'v clauses*  $\times$  (*'v clause*  $\times$  *'v clause*) *set*  
**inductive** *inference-clause* :: *'v state*  $\Rightarrow$  *'v clause*  $\times$  (*'v clause*  $\times$  *'v clause*) *set*  $\Rightarrow$  *bool*  
 (*infix*  $\Rightarrow_{\text{Res}}$  100) **where**  
*resolution*:



$\{\#Pos\ p\# \} + C \in N \implies \{\#Neg\ p\# \} + D \in N \implies (\{\#Pos\ p\# \} + C, \{\#Neg\ p\# \} + D) \notin$   
*already-used*  
 $\implies \text{inference-clause } (N, \text{already-used}) (C + D, \text{already-used} \cup \{(\{\#Pos\ p\# \} + C, \{\#Neg\ p\# \} + D)\}) \mid$   
*factoring*:  $\{\#L\# \} + \{\#L\# \} + C \in N \implies \text{inference-clause } (N, \text{already-used}) (C + \{\#L\# \}, \text{already-used})$

**inductive inference** :: '*v* state  $\Rightarrow$  '*v* state  $\Rightarrow$  bool **where**  
*inference-step*: *inference-clause* *S* (*clause*, *already-used*)  
 $\implies \text{inference } S (\text{fst } S \cup \{\text{clause}\}, \text{already-used})$

**abbreviation** *already-used-inv*

:: '*a* literal multiset set  $\times$  ('*a* literal multiset  $\times$  '*a* literal multiset) set  $\Rightarrow$  bool **where**  
*already-used-inv* state  $\equiv$   
 $(\forall (A, B) \in \text{snd state}. \exists p. \text{Pos } p \in\# A \wedge \text{Neg } p \in\# B \wedge$   
 $((\exists \chi \in \text{fst state}. \text{subsumes } \chi ((A - \{\#Pos\ p\# \}) + (B - \{\#Neg\ p\# \})))$   
 $\vee \text{tautology } ((A - \{\#Pos\ p\# \}) + (B - \{\#Neg\ p\# \}))))$

**lemma** *inference-clause-preserves-already-used-inv*:  
**assumes** *inference-clause* *S* *S'*  
**and** *already-used-inv* *S*  
**shows** *already-used-inv* (*fst* *S*  $\cup$  {*fst* *S'*}, *snd* *S'*)  
**using** *assms* **apply** (*induct* rule: *inference-clause.induct*)  
**by** *fastforce* +

**lemma** *inference-preserves-already-used-inv*:  
**assumes** *inference* *S* *S'*  
**and** *already-used-inv* *S*  
**shows** *already-used-inv* *S'*  
**using** *assms*  
**proof** (*induct* rule: *inference.induct*)  
**case** (*inference-step* *S* *clause* *already-used*)  
**then show** ?*case*  
**using** *inference-clause-preserves-already-used-inv*[of *S* (*clause*, *already-used*)] **by** *simp*  
**qed**

**lemma** *rtranclp-inference-preserves-already-used-inv*:  
**assumes** *rtranclp inference* *S* *S'*  
**and** *already-used-inv* *S*  
**shows** *already-used-inv* *S'*  
**using** *assms* **apply** (*induct* rule: *rtranclp-induct*, *simp*)  
**using** *inference-preserves-already-used-inv* **unfolding** *tautology-def* **by** *fast*

**lemma** *subsumes-condensation*:  
**assumes** *subsumes* (*C* + {*#L#*} + {*#L#*}) *D*  
**shows** *subsumes* (*C* + {*#L#*}) *D*  
**using** *assms* **unfolding** *subsumes-def* **by** *simp*

**lemma** *simplify-preserves-already-used-inv*:  
**assumes** *simplify* *N* *N'*  
**and** *already-used-inv* (*N*, *already-used*)  
**shows** *already-used-inv* (*N'*, *already-used*)  
**using** *assms*  
**proof** (*induct* rule: *simplify.induct*)  
**case** (*condensation* *C* *L*)

```

then show ?case
  using subsumes-condensation by simp fast
next
{
  fix a:: 'a and A :: 'a set and P
  have  $(\exists x \in \text{Set.remove } a \ A. P \ x) \longleftrightarrow (\exists x \in A. x \neq a \wedge P \ x)$  by auto
} note ex-member-remove = this
{
  fix a a0 :: 'v clause and A :: 'v clauses and y
  assume  $a \in A$  and  $a0 \subset\# a$ 
  then have  $(\exists x \in A. \text{subsumes } x \ y) \longleftrightarrow (\text{subsumes } a \ y \ \vee (\exists x \in A. x \neq a \wedge \text{subsumes } x \ y))$ 
    by auto
} note tt2 = this
case (subsumption A B) note A = this(1) and AB = this(2) and B = this(3) and inv = this(4)
show ?case
proof (standard, standard)
  fix x a b
  assume  $x: x \in \text{snd } (N - \{B\}, \text{already-used})$  and [simp]:  $x = (a, b)$ 
  obtain p where  $p: \text{Pos } p \in\# a \wedge \text{Neg } p \in\# b$  and
     $q: (\exists \chi \in N. \text{subsumes } \chi (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\})))$ 
     $\vee \text{tautology } (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\}))$ 
  using inv x by fastforce
  consider (taut)  $\text{tautology } (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\})) \mid$ 
     $(\chi) \chi$  where  $\chi \in N$   $\text{subsumes } \chi (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\}))$ 
     $\neg \text{tautology } (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\}))$ 
  using q by auto
  then show
     $\exists p. \text{Pos } p \in\# a \wedge \text{Neg } p \in\# b$ 
     $\wedge ((\exists \chi \in \text{fst } (N - \{B\}, \text{already-used}). \text{subsumes } \chi (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\})))$ 
     $\vee \text{tautology } (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\})))$ 
  proof cases
    case taut
      then show ?thesis using p by auto
  next
    case  $\chi$  note H = this
      show ?thesis using p A AB B subsumes-subsumption[OF - AB H(3)] H(1,2) by auto
  qed
qed
next
case (tautology-deletion C P)
then show ?case apply clarify
proof -
  fix a b
  assume  $C + \{\# \text{Pos } P\} + \{\# \text{Neg } P\} \in N$ 
  assume already-used-inv (N, already-used)
  and  $(a, b) \in \text{snd } (N - \{C + \{\# \text{Pos } P\} + \{\# \text{Neg } P\}\}, \text{already-used})$ 
  then obtain p where
     $\text{Pos } p \in\# a \wedge \text{Neg } p \in\# b \wedge$ 
     $((\exists \chi \in \text{fst } (N \cup \{C + \{\# \text{Pos } P\} + \{\# \text{Neg } P\}\}, \text{already-used}).$ 
     $\text{subsumes } \chi (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\})))$ 
     $\vee \text{tautology } (a - \{\# \text{Pos } p\} + (b - \{\# \text{Neg } p\})))$ 
  by fastforce
  moreover have  $\text{tautology } (C + \{\# \text{Pos } P\} + \{\# \text{Neg } P\})$  by auto
  ultimately show
     $\exists p. \text{Pos } p \in\# a \wedge \text{Neg } p \in\# b$ 

```

$\wedge ((\exists \chi \in \text{fst } (N - \{C + \{\#Pos\ P\# \} + \{\#Neg\ P\# \}), \text{already-used}).$   
 $\text{subsumes } \chi (a - \{\#Pos\ p\# \} + (b - \{\#Neg\ p\# \})))$   
 $\vee \text{tautology } (a - \{\#Pos\ p\# \} + (b - \{\#Neg\ p\# \})))$   
**by** (*metis* (*no-types*) *Diff-iff* *Un-insert-right* *empty-iff* *fst-conv* *insertE* *subsumes-tautology* *sup-bot.right-neutral*)  
**qed**  
**qed**

**lemma**

*factoring-satisfiable*:  $I \models \{\#L\# \} + \{\#L\# \} + C \longleftrightarrow I \models \{\#L\# \} + C$  **and**  
*resolution-satisfiable*:  
*consistent-interp*  $I \implies I \models \{\#Pos\ p\# \} + C \implies I \models \{\#Neg\ p\# \} + D \implies I \models C + D$  **and**  
*factoring-same-vars*:  $\text{atms-of } (\{\#L\# \} + \{\#L\# \} + C) = \text{atms-of } (\{\#L\# \} + C)$   
**unfolding** *true-cls-def* *consistent-interp-def* **by** (*fastforce* *split*: *if-split-asm*)**+**

**lemma** *inference-increasing*:

**assumes** *inference*  $S\ S'$  **and**  $\psi \in \text{fst } S$   
**shows**  $\psi \in \text{fst } S'$   
**using** *assms* **by** (*induct* *rule*: *inference.induct*, *auto*)

**lemma** *rtranclp-inference-increasing*:

**assumes** *rtranclp* *inference*  $S\ S'$  **and**  $\psi \in \text{fst } S$   
**shows**  $\psi \in \text{fst } S'$   
**using** *assms* **by** (*induct* *rule*: *rtranclp-induct*, *auto* *simp* *add*: *inference-increasing*)

**lemma** *inference-clause-already-used-increasing*:

**assumes** *inference-clause*  $S\ S'$   
**shows**  $\text{snd } S \subseteq \text{snd } S'$   
**using** *assms* **by** (*induct* *rule*: *inference-clause.induct*, *auto*)

**lemma** *inference-already-used-increasing*:

**assumes** *inference*  $S\ S'$   
**shows**  $\text{snd } S \subseteq \text{snd } S'$   
**using** *assms* **apply** (*induct* *rule*: *inference.induct*)  
**using** *inference-clause-already-used-increasing* **by** *fastforce*

**lemma** *inference-clause-preserves-un-sat*:

**fixes**  $N\ N' :: 'v \text{ clauses}$   
**assumes** *inference-clause*  $T\ T'$   
**and** *total-over-m*  $I\ (\text{fst } T)$   
**and** *consistent*: *consistent-interp*  $I$   
**shows**  $I \models_s \text{fst } T \longleftrightarrow I \models_s \text{fst } T \cup \{\text{fst } T'\}$   
**using** *assms* **apply** (*induct* *rule*: *inference-clause.induct*)  
**unfolding** *consistent-interp-def* *true-clss-def* **by** *auto* *force***+**

**lemma** *inference-preserves-un-sat*:

**fixes**  $N\ N' :: 'v \text{ clauses}$   
**assumes** *inference*  $T\ T'$   
**and** *total-over-m*  $I\ (\text{fst } T)$   
**and** *consistent*: *consistent-interp*  $I$   
**shows**  $I \models_s \text{fst } T \longleftrightarrow I \models_s \text{fst } T'$   
**using** *assms* **apply** (*induct* *rule*: *inference.induct*)

**using** *inference-clause-preserves-un-sat* **by** *fastforce*

**lemma** *inference-clause-preserves-atms-of-ms*:

**assumes** *inference-clause*  $S S'$

**shows**  $\text{atms-of-ms } (\text{fst } (\text{fst } S \cup \{\text{fst } S'\}, \text{snd } S')) \subseteq \text{atms-of-ms } (\text{fst } S)$

**using** *assms* **apply** (*induct rule: inference-clause.induct*)

**apply** *auto*

**apply** (*metis* *Set.set-insert* *UnCI* *atms-of-ms-insert* *atms-of-plus*)

**apply** (*metis* *Set.set-insert* *UnCI* *atms-of-ms-insert* *atms-of-plus*)

**apply** (*simp add: in-m-in-literals union-assoc*)

**unfolding** *atms-of-ms-def* **using** *assms* **by** *fastforce*

**lemma** *inference-preserves-atms-of-ms*:

**fixes**  $N N' :: 'v \text{ clauses}$

**assumes** *inference*  $T T'$

**shows**  $\text{atms-of-ms } (\text{fst } T') \subseteq \text{atms-of-ms } (\text{fst } T)$

**using** *assms* **apply** (*induct rule: inference.induct*)

**using** *inference-clause-preserves-atms-of-ms* **by** *fastforce*

**lemma** *inference-preserves-total*:

**fixes**  $N N' :: 'v \text{ clauses}$

**assumes** *inference*  $(N, \text{already-used}) (N', \text{already-used}')$

**shows**  $\text{total-over-m } I N \implies \text{total-over-m } I N'$

**using** *assms* *inference-preserves-atms-of-ms* **unfolding** *total-over-m-def* *total-over-set-def* **by** *fastforce*

**lemma** *rtranclp-inference-preserves-total*:

**assumes** *rtranclp inference*  $T T'$

**shows**  $\text{total-over-m } I (\text{fst } T) \implies \text{total-over-m } I (\text{fst } T')$

**using** *assms* **by** (*induct rule: rtranclp-induct, auto simp add: inference-preserves-total*)

**lemma** *rtranclp-inference-preserves-un-sat*:

**assumes** *rtranclp inference*  $N N'$

**and**  $\text{total-over-m } I (\text{fst } N)$

**and** *consistent: consistent-interp*  $I$

**shows**  $I \models_s \text{fst } N \longleftrightarrow I \models_s \text{fst } N'$

**using** *assms* **apply** (*induct rule: rtranclp-induct*)

**apply** (*simp add: inference-preserves-un-sat*)

**using** *inference-preserves-un-sat rtranclp-inference-preserves-total* **by** *blast*

**lemma** *inference-preserves-finite*:

**assumes** *inference*  $\psi \psi'$  **and** *finite*  $(\text{fst } \psi)$

**shows** *finite*  $(\text{fst } \psi')$

**using** *assms* **by** (*induct rule: inference.induct, auto simp add: simplify-preserves-finite*)

**lemma** *inference-clause-preserves-finite-snd*:

**assumes** *inference-clause*  $\psi \psi'$  **and** *finite*  $(\text{snd } \psi)$

**shows** *finite*  $(\text{snd } \psi')$

**using** *assms* **by** (*induct rule: inference-clause.induct, auto*)

**lemma** *inference-preserves-finite-snd*:

**assumes** *inference*  $\psi \psi'$  **and** *finite*  $(\text{snd } \psi)$

**shows** *finite* (*snd*  $\psi'$ )  
**using** *assms* *inference-clause-preserves-finite-snd* **by** (*induct* *rule*: *inference.induct*, *fastforce*)

**lemma** *rtranclp-inference-preserves-finite*:  
**assumes** *rtranclp* *inference*  $\psi$   $\psi'$  **and** *finite* (*fst*  $\psi$ )  
**shows** *finite* (*fst*  $\psi'$ )  
**using** *assms* **by** (*induct* *rule*: *rtranclp-induct*)  
*(auto simp add: simplify-preserves-finite inference-preserves-finite)*

**lemma** *consistent-interp-insert*:  
**assumes** *consistent-interp* *I*  
**and** *atm-of* *P*  $\notin$  *atm-of* '*I*  
**shows** *consistent-interp* (*insert* *P* *I*)  
**proof** –  
**have** *P*: *insert* *P* *I* = *I*  $\cup$  {*P*} **by** *auto*  
**show** *?thesis* **unfolding** *P*  
**apply** (*rule* *consistent-interp-disjoint*)  
**using** *assms* **by** (*auto simp*: *image-iff*)  
**qed**

**lemma** *simplify-clause-preserves-sat*:  
**assumes** *simp*: *simplify*  $\psi$   $\psi'$   
**and** *satisfiable*  $\psi'$   
**shows** *satisfiable*  $\psi$   
**using** *assms*  
**proof** *induction*  
**case** (*tautology-deletion* *A* *P*) **note** *AP* = *this*(1) **and** *sat* = *this*(2)  
**let**  $?A' = A + \{\#Pos\ P\# \} + \{\#Neg\ P\# \}$   
**let**  $? \psi' = \psi - \{?A'\}$   
**obtain** *I* **where**  
*I*: *I*  $\models_s$   $? \psi'$  **and**  
*cons*: *consistent-interp* *I* **and**  
*tot*: *total-over-m* *I*  $? \psi'$   
**using** *sat* **unfolding** *satisfiable-def* **by** *auto*  
{ **assume** *Pos* *P*  $\in$  *I*  $\vee$  *Neg* *P*  $\in$  *I*  
**then** **have** *I*  $\models$   $?A'$  **by** *auto*  
**then** **have** *I*  $\models_s$   $\psi$  **using** *I* **by** (*metis* *insert-Diff* *tautology-deletion.hyps* *true-clss-insert*)  
**then** **have** *?case* **using** *cons* *tot* **by** *auto*  
}  
**moreover** {  
**assume** *Pos*: *Pos* *P*  $\notin$  *I* **and** *Neg*: *Neg* *P*  $\notin$  *I*  
**then** **have** *consistent-interp* (*I*  $\cup$  {*Pos* *P*}) **using** *cons* **by** *simp*  
**moreover** **have** *I'A*: *I*  $\cup$  {*Pos* *P*}  $\models$   $?A'$  **by** *auto*  
**have** {*Pos* *P*}  $\cup$  *I*  $\models_s$   $\psi - \{A + \{\#Pos\ P\# \} + \{\#Neg\ P\# \}\}$   
**using**  $\langle I \models_s \psi - \{A + \{\#Pos\ P\# \} + \{\#Neg\ P\# \}\rangle$  *true-clss-union-increase'* **by** *blast*  
**then** **have** *I*  $\cup$  {*Pos* *P*}  $\models_s$   $\psi$   
**by** (*metis* (*no-types*) *Un-empty-right* *Un-insert-left* *Un-insert-right* *I'A* *insert-Diff*  
*sup-bot.left-neutral* *tautology-deletion.hyps* *true-clss-insert*)  
**ultimately** **have** *?case* **using** *satisfiable-carac'* **by** *blast*  
}  
**ultimately** **show** *?case* **by** *blast*  
**next**  
**case** (*condensation* *A* *L*) **note** *AL* = *this*(1) **and** *sat* = *this*(2)  
**have** *f3*: *simplify*  $\psi$  ( $\psi - \{A + \{\#L\# \} + \{\#L\# \}\} \cup \{A + \{\#L\# \}\}$ )

```

    using AL simplify.condensation by blast
  obtain LL :: 'a literal multiset set  $\Rightarrow$  'a literal set where
    f4: LL ( $\psi - \{A + \{\#L\# \} + \{\#L\#\} \cup \{A + \{\#L\#\} \}$ )  $\models_s \psi - \{A + \{\#L\# \} + \{\#L\#\} \cup \{A + \{\#L\#\} \}$ 
     $\wedge$  consistent-interp (LL ( $\psi - \{A + \{\#L\# \} + \{\#L\#\} \cup \{A + \{\#L\#\} \}$ ))
     $\wedge$  total-over-m (LL ( $\psi - \{A + \{\#L\# \} + \{\#L\#\} \cup \{A + \{\#L\#\} \}$ )) ( $\psi - \{A + \{\#L\# \} + \{\#L\#\} \cup \{A + \{\#L\#\} \}$ )
    using sat by (meson satisfiable-def)
  have f5: insert (A +  $\{\#L\# \} + \{\#L\#\}$ ) ( $\psi - \{A + \{\#L\# \} + \{\#L\#\} \}$ ) =  $\psi$ 
    using AL by fastforce
  have atms-of (A +  $\{\#L\# \} + \{\#L\#\}$ ) = atms-of ( $\{\#L\# \} + A$ )
    by simp
  then show ?case
    using f5 f4 f3 by (metis (no-types) add.commute satisfiable-def simplify-preserves-un-sat'
      total-over-m-insert total-over-m-union)
next
case (subsumption A B) note A = this(1) and AB = this(2) and B = this(3) and sat = this(4)
let ? $\psi'$  =  $\psi - \{B\}$ 
obtain I where I: I  $\models_s$  ? $\psi'$  and cons: consistent-interp I and tot: total-over-m I ? $\psi'$ 
  using sat unfolding satisfiable-def by auto
have I  $\models$  A using A I by (metis AB Diff-iff subset-mset.less-irrefl singletonD true-clss-def)
then have I  $\models$  B using AB subset-mset.less-imp-le true-clss-mono-leD by blast
then have I  $\models_s$   $\psi$  using I by (metis insert-Diff-single true-clss-insert)
then show ?case using cons satisfiable-carac' by blast
qed

```

```

lemma simplify-preserves-unsat:
  assumes inference  $\psi$   $\psi'$ 
  shows satisfiable (fst  $\psi'$ )  $\longrightarrow$  satisfiable (fst  $\psi$ )
  using assms apply (induct rule: inference.induct)
  using satisfiable-decreasing by (metis fst-conv)+

```

```

lemma inference-preserves-unsat:
  assumes inference** S S'
  shows satisfiable (fst S')  $\longrightarrow$  satisfiable (fst S)
  using assms apply (induct rule: rtranclp-induct)
  apply simp-all
  using simplify-preserves-unsat by blast

```

```

datatype 'v sem-tree = Node 'v 'v sem-tree 'v sem-tree | Leaf

```

```

fun sem-tree-size :: 'v sem-tree  $\Rightarrow$  nat where
  sem-tree-size Leaf = 0 |
  sem-tree-size (Node - ag ad) = 1 + sem-tree-size ag + sem-tree-size ad

```

```

lemma sem-tree-size[case-names bigger]:
  ( $\bigwedge xs:: 'v$  sem-tree. ( $\bigwedge ys:: 'v$  sem-tree. sem-tree-size ys < sem-tree-size xs  $\implies$  P ys)  $\implies$  P xs)
   $\implies$  P xs
  by (fact Nat.measure-induct-rule)

```

```

fun partial-interps :: 'v sem-tree  $\Rightarrow$  'v interp  $\Rightarrow$  'v clauses  $\Rightarrow$  bool where
  partial-interps Leaf I  $\psi$  = ( $\exists \chi. \neg I \models \chi \wedge \chi \in \psi \wedge$  total-over-m I  $\{\chi\}$ ) |
  partial-interps (Node v ag ad) I  $\psi \longleftrightarrow$ 
    (partial-interps ag (I  $\cup \{\text{Pos } v\}$ )  $\psi \wedge$  partial-interps ad (I  $\cup \{\text{Neg } v\}$ )  $\psi$ )

```

**lemma** *simplify-preserve-partial-leaf*:  
*simplify*  $N\ N' \implies \text{partial-interps Leaf } I\ N \implies \text{partial-interps Leaf } I\ N'$   
**apply** (*induct* rule: *simplify.induct*)  
**using** *union-lcomm* **apply** *auto*[1]  
**apply** (*simp*, *metis* *atms-of-plus* *total-over-set-union* *true-cls-union*)  
**apply** *simp*  
**by** (*metis* *atms-of-ms-singleton* *mset-le-exists-conv* *subset-mset-def* *true-cls-mono-leD*  
*total-over-m-def* *total-over-m-sum*)

**lemma** *simplify-preserve-partial-tree*:  
**assumes** *simplify*  $N\ N'$   
**and** *partial-interps*  $t\ I\ N$   
**shows** *partial-interps*  $t\ I\ N'$   
**using** *assms* **apply** (*induct*  $t$  arbitrary:  $I$ , *simp*)  
**using** *simplify-preserve-partial-leaf* **by** *metis*

**lemma** *inference-preserve-partial-tree*:  
**assumes** *inference*  $S\ S'$   
**and** *partial-interps*  $t\ I\ (\text{fst } S)$   
**shows** *partial-interps*  $t\ I\ (\text{fst } S')$   
**using** *assms* **apply** (*induct*  $t$  arbitrary:  $I$ , *simp-all*)  
**by** (*meson* *inference-increasing*)

**lemma** *rtranclp-inference-preserve-partial-tree*:  
**assumes** *rtranclp* *inference*  $N\ N'$   
**and** *partial-interps*  $t\ I\ (\text{fst } N)$   
**shows** *partial-interps*  $t\ I\ (\text{fst } N')$   
**using** *assms* **apply** (*induct* rule: *rtranclp-induct*, *auto*)  
**using** *inference-preserve-partial-tree* **by** *force*

**function** *build-sem-tree* ::  $'v :: \text{linorder set} \Rightarrow 'v \text{ clauses} \Rightarrow 'v \text{ sem-tree}$  **where**  
*build-sem-tree* *atms*  $\psi =$   
 (*if* *atms* =  $\{\}$   $\vee \neg \text{finite } \text{atms}$   
*then* *Leaf*  
*else* *Node* (*Min* *atms*) (*build-sem-tree* (*Set.remove* (*Min* *atms*) *atms*)  $\psi$ )  
 (*build-sem-tree* (*Set.remove* (*Min* *atms*) *atms*)  $\psi$ )  
**by** *auto*  
**termination**  
**apply** (*relation* *measure*  $(\lambda(A, -). \text{card } A)$ , *simp-all*)  
**apply** (*metis* *Min-in* *card-Diff1-less* *remove-def*)  
**done**  
**declare** *build-sem-tree.induct*[*case-names tree*]

**lemma** *unsatisfiable-empty*[*simp*]:  
 $\neg \text{unsatisfiable } \{\}$   
**unfolding** *satisfiable-def* **apply** *auto*  
**using** *consistent-interp-def* **unfolding** *total-over-m-def* *total-over-set-def* *atms-of-ms-def* **by** *blast*

**lemma** *partial-interps-build-sem-tree-atms-general*:

**fixes**  $\psi :: 'v :: \text{linorder clauses}$  **and**  $p :: 'v \text{ literal list}$   
**assumes** *unsat*: unsatisfiable  $\psi$  **and** *finite*  $\psi$  **and** *consistent-interp*  $I$   
**and** *finite* *atms*  
**and** *atms-of-ms*  $\psi = \text{atms} \cup \text{atms-of-s } I$  **and**  $\text{atms} \cap \text{atms-of-s } I = \{\}$   
**shows** *partial-interps* (*build-sem-tree* *atms*  $\psi$ )  $I$   $\psi$   
**using** *assms*  
**proof** (*induct arbitrary*:  $I$  *rule*: *build-sem-tree.induct*)  
**case** ( $1 \text{ atms } \psi \text{ Ia}$ ) **note**  $IH1 = \text{this}(1)$  **and**  $IH2 = \text{this}(2)$  **and**  $\text{unsat} = \text{this}(3)$  **and**  $\text{finite} = \text{this}(4)$   
**and**  $\text{cons} = \text{this}(5)$  **and**  $f = \text{this}(6)$  **and**  $\text{un} = \text{this}(7)$  **and**  $\text{disj} = \text{this}(8)$   
{  
**assume** *atms*:  $\text{atms} = \{\}$   
**then have** *atmsIa*:  $\text{atms-of-ms } \psi = \text{atms-of-s } \text{Ia}$  **using** *un* **by** *auto*  
**then have** *total-over-m*  $\text{Ia } \psi$  **unfolding** *total-over-m-def* *atmsIa* **by** *auto*  
**then have**  $\chi: \exists \chi \in \psi. \neg \text{Ia} \models \chi$   
**using** *unsat cons* **unfolding** *true-clss-def* *satisfiable-def* **by** *auto*  
**then have** *build-sem-tree* *atms*  $\psi = \text{Leaf}$  **using** *atms* **by** *auto*  
**moreover**  
**have** *tot*:  $\bigwedge \chi. \chi \in \psi \implies \text{total-over-m } \text{Ia } \{\chi\}$   
**unfolding** *total-over-m-def* *total-over-set-def* *atms-of-ms-def* *atms-of-s-def*  
**using** *atmsIa* *atms-of-ms-def* **by** *fastforce*  
**have** *partial-interps* *Leaf*  $\text{Ia } \psi$   
**using**  $\chi$  *tot* **by** (*auto simp add*: *total-over-m-def* *total-over-set-def* *atms-of-ms-def*)  
  
**ultimately have** *?case* **by** *metis*  
}  
**moreover** {  
**assume** *atms*:  $\text{atms} \neq \{\}$   
**have** *build-sem-tree* *atms*  $\psi = \text{Node } (\text{Min } \text{atms}) (\text{build-sem-tree } (\text{Set.remove } (\text{Min } \text{atms}) \text{atms}) \psi)$   
(*build-sem-tree* (*Set.remove* (*Min* *atms*) *atms*)  $\psi$ )  
**using** *build-sem-tree.simps*[*of* *atms*  $\psi$ ] *f* *atms* **by** *metis*  
  
**have** *consistent-interp* ( $\text{Ia} \cup \{\text{Pos } (\text{Min } \text{atms})\}$ ) **unfolding** *consistent-interp-def*  
**by** (*metis Int-iff Min-in Un-iff atm-of-uminus atms cons consistent-interp-def disj empty-iff*  
*f in-atms-of-s-decomp insert-iff literal.distinct(1) literal.exhaust-sel literal.sel(2)*  
*uminus-Neg uminus-Pos*)  
**moreover have** *atms-of-ms*  $\psi = \text{Set.remove } (\text{Min } \text{atms}) \text{atms} \cup \text{atms-of-s } (\text{Ia} \cup \{\text{Pos } (\text{Min } \text{atms})\})$   
**using** *Min-in atms f un* **by** *fastforce*  
**moreover have** *disj'*:  $\text{Set.remove } (\text{Min } \text{atms}) \text{atms} \cap \text{atms-of-s } (\text{Ia} \cup \{\text{Pos } (\text{Min } \text{atms})\}) = \{\}$   
**by** *simp* (*metis disj disjoint-iff-not-equal member-remove*)  
**moreover have** *finite* ( $\text{Set.remove } (\text{Min } \text{atms}) \text{atms}$ ) **using** *f* **by** (*simp add*: *remove-def*)  
**ultimately have** *subtree1*: *partial-interps* (*build-sem-tree* ( $\text{Set.remove } (\text{Min } \text{atms}) \text{atms}$ )  $\psi$ )  
( $\text{Ia} \cup \{\text{Pos } (\text{Min } \text{atms})\}$ )  $\psi$   
**using**  $IH1$ [*of*  $\text{Ia} \cup \{\text{Pos } (\text{Min } (\text{atms}))\}$ ] *atms f unsat finite* **by** *metis*  
  
**have** *consistent-interp* ( $\text{Ia} \cup \{\text{Neg } (\text{Min } \text{atms})\}$ ) **unfolding** *consistent-interp-def*  
**by** (*metis Int-iff Min-in Un-iff atm-of-uminus atms cons consistent-interp-def disj empty-iff*  
*f in-atms-of-s-decomp insert-iff literal.distinct(1) literal.exhaust-sel literal.sel(2)*  
*uminus-Neg*)  
**moreover have** *atms-of-ms*  $\psi = \text{Set.remove } (\text{Min } \text{atms}) \text{atms} \cup \text{atms-of-s } (\text{Ia} \cup \{\text{Neg } (\text{Min } \text{atms})\})$   
**using**  $\langle \text{atms-of-ms } \psi = \text{Set.remove } (\text{Min } \text{atms}) \text{atms} \cup \text{atms-of-s } (\text{Ia} \cup \{\text{Pos } (\text{Min } \text{atms})\}) \rangle$  **by**  
*blast*  
  
**moreover have** *disj'*:  $\text{Set.remove } (\text{Min } \text{atms}) \text{atms} \cap \text{atms-of-s } (\text{Ia} \cup \{\text{Neg } (\text{Min } \text{atms})\}) = \{\}$   
**using** *disj* **by** *auto*  
**moreover have** *finite* ( $\text{Set.remove } (\text{Min } \text{atms}) \text{atms}$ ) **using** *f* **by** (*simp add*: *remove-def*)



```

ultimately have subtree2: partial-interps (build-sem-tree (Set.remove (Min atms) atms)  $\psi$ )
  (Ia  $\cup$  {Neg (Min atms)})  $\psi$ 
using IH2[of Ia  $\cup$  {Neg (Min (atms))}] atms f unsat finite by metis

then have ?case
  using IH1 subtree1 subtree2 f local.finite unsat atms by simp
}
ultimately show ?case by metis
qed

```

**lemma** *partial-interps-build-sem-tree-atms:*

```

fixes  $\psi :: 'v :: \text{linorder clauses}$  and  $p :: 'v \text{ literal list}$ 
assumes unsat: unsatisfiable  $\psi$  and finite: finite  $\psi$ 
shows partial-interps (build-sem-tree (atms-of-ms  $\psi$ )  $\psi$ ) {}  $\psi$ 
proof -
  have consistent-interp {} unfolding consistent-interp-def by auto
  moreover have atms-of-ms  $\psi$  = atms-of-ms  $\psi \cup$  atms-of-s {} unfolding atms-of-s-def by auto
  moreover have atms-of-ms  $\psi \cap$  atms-of-s {} = {} unfolding atms-of-s-def by auto
  moreover have finite (atms-of-ms  $\psi$ ) unfolding atms-of-ms-def using finite by simp
  ultimately show partial-interps (build-sem-tree (atms-of-ms  $\psi$ )  $\psi$ ) {}  $\psi$ 
    using partial-interps-build-sem-tree-atms-general[of  $\psi$  {} atms-of-ms  $\psi$ ] assms by metis
qed

```

**lemma** *can-decrease-count:*

```

fixes  $\psi'' :: 'v \text{ clauses} \times ('v \text{ clause} \times 'v \text{ clause} \times 'v) \text{ set}$ 
assumes count  $\chi L = n$ 
and  $L \in \# \chi$  and  $\chi \in \text{fst } \psi$ 
shows  $\exists \psi' \chi'. \text{inference}^{**} \psi \psi' \wedge \chi' \in \text{fst } \psi' \wedge (\forall L. L \in \# \chi \longleftrightarrow L \in \# \chi')$ 
   $\wedge \text{count } \chi' L = 1$ 
   $\wedge (\forall \varphi. \varphi \in \text{fst } \psi \longrightarrow \varphi \in \text{fst } \psi')$ 
   $\wedge (I \models \chi \longleftrightarrow I \models \chi')$ 
   $\wedge (\forall I'. \text{total-over-}m I' \{\chi\} \longrightarrow \text{total-over-}m I' \{\chi'\})$ 

```

using assms

**proof** (induct  $n$  arbitrary:  $\chi \psi$ )

case 0

then show ?case by (simp add: not-in-iff[symmetric])

next

case (Suc  $n \chi$ )

note IH = this(1) and count = this(2) and  $L = \text{this}(3)$  and  $\chi = \text{this}(4)$

{

assume  $n = 0$

then have inference\*\*  $\psi \psi$

and  $\chi \in \text{fst } \psi$

and  $\forall L. (L \in \# \chi) \longleftrightarrow (L \in \# \chi)$

and count  $\chi L = (1::\text{nat})$

and  $\forall \varphi. \varphi \in \text{fst } \psi \longrightarrow \varphi \in \text{fst } \psi$

by (auto simp add: count L  $\chi$ )

then have ?case by metis

}

moreover {

assume  $n > 0$

then have  $\exists C. \chi = C + \{\#L, L\# \}$

by (smt L Suc-eq-plus1-left add.left-commute add-diff-cancel-left' add-diff-cancel-right'
count-greater-zero-iff count-single local.count multi-member-split plus-multiset.rep-eq)

```

then obtain  $C$  where  $C: \chi = C + \{\#L, L\# \}$  by metis
let  $? \chi' = C + \{\#L\# \}$ 
let  $? \psi' = (\text{fst } \psi \cup \{? \chi'\}, \text{snd } \psi)$ 
have  $\varphi: \forall \varphi \in \text{fst } \psi. (\varphi \in \text{fst } \psi \vee \varphi \neq ? \chi') \longleftrightarrow \varphi \in \text{fst } ? \psi'$  unfolding  $C$  by auto
have inf: inference  $\psi ? \psi'$ 
  using  $C$  factoring  $\chi$  prod.collapse union-commute inference-step by metis
moreover have count': count  $? \chi' L = n$  using  $C$  count by auto
moreover have  $L_{\chi'}: L \in \# ? \chi'$  by auto
moreover have  $\chi' \psi': ? \chi' \in \text{fst } ? \psi'$  by auto
ultimately obtain  $\psi''$  and  $\chi''$ 
where
  inference**  $? \psi' \psi''$  and
   $\alpha: \chi'' \in \text{fst } \psi''$  and
   $\forall La. (La \in \# ? \chi') \longleftrightarrow (La \in \# \chi'')$  and
   $\beta: \text{count } \chi'' L = (1::\text{nat})$  and
   $\varphi': \forall \varphi. \varphi \in \text{fst } ? \psi' \longrightarrow \varphi \in \text{fst } \psi''$  and
   $I_{\chi}: I \models ? \chi' \longleftrightarrow I \models \chi''$  and
  tot:  $\forall I'. \text{total-over-m } I' \{? \chi'\} \longrightarrow \text{total-over-m } I' \{\chi''\}$ 
  using  $IH[\text{of } ? \chi' ? \psi']$  count'  $L_{\chi'}$   $\chi' \psi'$  by blast

then have inference**  $\psi \psi''$ 
and  $\forall La. (La \in \# \chi) \longleftrightarrow (La \in \# \chi'')$ 
using inf unfolding  $C$  by auto
moreover have  $\forall \varphi. \varphi \in \text{fst } \psi \longrightarrow \varphi \in \text{fst } \psi''$  using  $\varphi \varphi'$  by metis
moreover have  $I \models \chi \longleftrightarrow I \models \chi''$  using  $I_{\chi}$  unfolding true-cls-def  $C$  by auto
moreover have  $\forall I'. \text{total-over-m } I' \{\chi\} \longrightarrow \text{total-over-m } I' \{\chi''\}$ 
  using tot unfolding  $C$  total-over-m-def by auto
ultimately have ?case using  $\varphi \varphi' \alpha \beta$  by metis
}
ultimately show ?case by auto
qed

```

**lemma** *can-decrease-tree-size*:

```

fixes  $\psi :: 'v$  state and  $\text{tree} :: 'v$  sem-tree
assumes finite (fst  $\psi$ ) and already-used-inv  $\psi$ 
and partial-interps  $\text{tree } I$  (fst  $\psi$ )
shows  $\exists (\text{tree}' :: 'v \text{ sem-tree}) \psi'. \text{inference** } \psi \psi' \wedge \text{partial-interps } \text{tree}' I (\text{fst } \psi')$ 
   $\wedge (\text{sem-tree-size } \text{tree}' < \text{sem-tree-size } \text{tree} \vee \text{sem-tree-size } \text{tree} = 0)$ 
using assms
proof (induct arbitrary:  $I$  rule: sem-tree-size)
case (bigger xs I) note  $IH = \text{this}(1)$  and finite = this(2) and a-u-i = this(3) and part = this(4)

```

```

{
  assume sem-tree-size xs = 0
  then have ?case using part by blast
}

```

```

moreover {
  assume sn0: sem-tree-size xs > 0
  obtain ag ad v where xs: xs = Node v ag ad using sn0 by (cases xs, auto)
  {
    assume sem-tree-size ag = 0 and sem-tree-size ad = 0
    then have ag: ag = Leaf and ad: ad = Leaf by (cases ag, auto) (cases ad, auto)

    then obtain  $\chi \chi'$  where

```

```

 $\chi: \neg I \cup \{Pos\ v\} \models \chi$  and
 $tot\chi: total-over-m\ (I \cup \{Pos\ v\})\ \{\chi\}$  and
 $\chi\psi: \chi \in fst\ \psi$  and
 $\chi': \neg I \cup \{Neg\ v\} \models \chi'$  and
 $tot\chi': total-over-m\ (I \cup \{Neg\ v\})\ \{\chi'\}$  and
 $\chi'\psi: \chi' \in fst\ \psi$ 
using part unfolding  $xs$  by auto
have  $Posv: \neg Pos\ v \in \# \chi$  using  $\chi$  unfolding  $true-cls-def\ true-lit-def$  by auto
have  $Negv: \neg Neg\ v \in \# \chi'$  using  $\chi'$  unfolding  $true-cls-def\ true-lit-def$  by auto
{
  assume  $Neg\chi: \neg Neg\ v \in \# \chi$ 
  have  $\neg I \models \chi$  using  $\chi\ Posv$  unfolding  $true-cls-def\ true-lit-def$  by auto
  moreover have  $total-over-m\ I\ \{\chi\}$ 
    using  $Posv\ Neg\chi\ atm-imp-pos-or-neg-lit\ tot\chi$  unfolding  $total-over-m-def\ total-over-set-def$ 
    by fastforce
  ultimately have  $partial-interps\ Leaf\ I\ (fst\ \psi)$ 
  and  $sem-tree-size\ Leaf < sem-tree-size\ xs$ 
  and  $inference^{**}\ \psi\ \psi$ 
    unfolding  $xs$  by  $(auto\ simp\ add: \chi\psi)$ 
}
moreover {
  assume  $Pos\chi: \neg Pos\ v \in \# \chi'$ 
  then have  $I\chi: \neg I \models \chi'$  using  $\chi'\ Posv$  unfolding  $true-cls-def\ true-lit-def$  by auto
  moreover have  $total-over-m\ I\ \{\chi'\}$ 
    using  $Negv\ Pos\chi\ atm-imp-pos-or-neg-lit\ tot\chi'$ 
    unfolding  $total-over-m-def\ total-over-set-def$  by fastforce
  ultimately have  $partial-interps\ Leaf\ I\ (fst\ \psi)$  and
     $sem-tree-size\ Leaf < sem-tree-size\ xs$  and
     $inference^{**}\ \psi\ \psi$ 
    using  $\chi'\psi\ I\chi$  unfolding  $xs$  by auto
}
moreover {
  assume  $neg: Neg\ v \in \# \chi$  and  $pos: Pos\ v \in \# \chi'$ 
  then obtain  $\psi'\ \chi^2$  where  $inf: rtranclp\ inference\ \psi\ \psi'$  and  $\chi^2incl: \chi^2 \in fst\ \psi'$ 
    and  $\chi\chi^2incl: \forall L. L \in \# \chi \longleftrightarrow L \in \# \chi^2$ 
    and  $count\chi^2: count\ \chi^2\ (Neg\ v) = 1$ 
    and  $\varphi: \forall \varphi::'v\ literal\ multiset. \varphi \in fst\ \psi \longrightarrow \varphi \in fst\ \psi'$ 
    and  $I\chi: I \models \chi \longleftrightarrow I \models \chi^2$ 
    and  $tot-imp\chi: \forall I'. total-over-m\ I'\ \{\chi\} \longrightarrow total-over-m\ I'\ \{\chi^2\}$ 
    using  $can-decrease-count[of\ \chi\ Neg\ v\ count\ \chi\ (Neg\ v)\ \psi\ I]\ \chi\psi\ \chi'\psi$  by auto

  have  $\chi' \in fst\ \psi'$  by  $(simp\ add: \chi'\psi\ \varphi)$ 
  with  $pos$ 
  obtain  $\psi''\ \chi^2'$  where
     $inf': inference^{**}\ \psi'\ \psi''$ 
    and  $\chi^2'-incl: \chi^2' \in fst\ \psi''$ 
    and  $\chi'\chi^2incl: \forall L::'v\ literal. (L \in \# \chi') = (L \in \# \chi^2')$ 
    and  $count\chi^2': count\ \chi^2'\ (Pos\ v) = (1::nat)$ 
    and  $\varphi': \forall \varphi::'v\ literal\ multiset. \varphi \in fst\ \psi' \longrightarrow \varphi \in fst\ \psi''$ 
    and  $I\chi': I \models \chi' \longleftrightarrow I \models \chi^2'$ 
    and  $tot-imp\chi': \forall I'. total-over-m\ I'\ \{\chi'\} \longrightarrow total-over-m\ I'\ \{\chi^2'\}$ 
    using  $can-decrease-count[of\ \chi'\ Pos\ v\ count\ \chi'\ (Pos\ v)\ \psi'\ I]\$  by auto

  obtain  $C$  where  $\chi^2: \chi^2 = C + \{\#Neg\ v\# \}$  and  $negC: Neg\ v \notin \# C$  and  $posC: Pos\ v \notin \# C$ 
  proof -

```

```

have  $\bigwedge m. \text{Suc } 0 - \text{count } m (\text{Neg } v) = \text{count } (\chi^2 - m) (\text{Neg } v)$ 
  by (simp add: count $\chi^2$ )
then show ?thesis
  using that by (metis (no-types) One-nat-def Posv Suc-inject Suc-pred  $\chi\chi^2\text{-incl}$ 
    count-diff count-single insert-DiffM2 mem-Collect-eq multi-member-skip neg
    not-gr0 set-mset-def union-commute)
qed

obtain  $C'$  where
 $\chi^2': \chi^2' = C' + \{\#Pos\ v\# \}$  and
 $posC': Pos\ v \notin \# C'$  and
 $negC': Neg\ v \notin \# C'$ 
proof -
  assume a1:  $\bigwedge C'. [\chi^2' = C' + \{\#Pos\ v\# \}; Pos\ v \notin \# C'; Neg\ v \notin \# C'] \implies thesis$ 
  have f2:  $\bigwedge n. (n::nat) - n = 0$ 
    by simp
  have  $Neg\ v \notin \# \chi^2' - \{\#Pos\ v\# \}$ 
    using Negv  $\chi'\chi^2\text{-incl}$  by (auto simp: not-in-iff)
  have count  $\{\#Pos\ v\# \} (Pos\ v) = 1$ 
    by simp
  then show ?thesis
    by (metis  $\chi'\chi^2\text{-incl}$   $\langle Neg\ v \notin \# \chi^2' - \{\#Pos\ v\# \} \rangle$  a1 count $\chi^2'$  count-diff f2
      insert-DiffM2 less-numeral-extra(3) mem-Collect-eq pos set-mset-def)
qed

have already-used-inv  $\psi'$ 
  using rtranclp-inference-preserves-already-used-inv[of  $\psi\ \psi'$ ] a-u-i inf by blast
then have a-u-i- $\psi''$ : already-used-inv  $\psi''$ 
  using rtranclp-inference-preserves-already-used-inv a-u-i inf' unfolding tautology-def
  by simp

have totC: total-over-m  $I\ \{C\}$ 
  using tot-imp $\chi$  tot $\chi$  tot-over-m-remove[of  $I\ Pos\ v\ C$ ] negC posC unfolding  $\chi^2$ 
  by (metis total-over-m-sum uminus-Neg uminus-of-uminus-id)
have totC': total-over-m  $I\ \{C'\}$ 
  using tot-imp $\chi'$  tot $\chi'$  total-over-m-sum tot-over-m-remove[of  $I\ Neg\ v\ C'$ ] negC' posC'
  unfolding  $\chi^2'$  by (metis total-over-m-sum uminus-Neg)
have  $\neg I \models C + C'$ 
  using  $\chi\ I\chi\ \chi'\ I\chi'$  unfolding  $\chi^2\ \chi^2'$  true-cls-def by auto
then have part-I- $\psi'''$ : partial-interps Leaf  $I\ (fst\ \psi'' \cup \{C + C'\})$ 
  using totC totC' by simp
  (metis  $\neg I \models C + C'$  atms-of-ms-singleton total-over-m-def total-over-m-sum)
{
  assume  $(\{\#Pos\ v\# \} + C', \{\#Neg\ v\# \} + C) \notin snd\ \psi''$ 
  then have inf'': inference  $\psi'' (fst\ \psi'' \cup \{C + C'\}, snd\ \psi'' \cup \{(\chi^2', \chi^2)\})$ 
    using add.commute  $\varphi'\ \chi^2\text{incl}\ \langle \chi^2' \in fst\ \psi'' \rangle$  unfolding  $\chi^2\ \chi^2'$ 
    by (metis prod.collapse inference-step resolution)
  have inference**  $\psi (fst\ \psi'' \cup \{C + C'\}, snd\ \psi'' \cup \{(\chi^2', \chi^2)\})$ 
    using inf inf' inf'' rtranclp-trans by auto
  moreover have sem-tree-size Leaf < sem-tree-size xs unfolding xs by auto
  ultimately have ?case using part-I- $\psi'''$  by (metis fst-conv)
}
moreover {
  assume a:  $(\{\#Pos\ v\# \} + C', \{\#Neg\ v\# \} + C) \in snd\ \psi''$ 
  then have  $(\exists \chi \in fst\ \psi''. (\forall I. total-over-m\ I\ \{C + C'\} \longrightarrow total-over-m\ I\ \{\chi\}))$ 

```

$\wedge (\forall I. \text{total-over-m } I \{ \chi \} \longrightarrow I \models \chi \longrightarrow I \models C' + C)$   
 $\vee \text{tautology } (C' + C)$   
**proof** –  
**obtain**  $p$  **where**  $p: \text{Pos } p \in \# (\{\# \text{Pos } v\} + C')$  **and**  
 $n: \text{Neg } p \in \# (\{\# \text{Neg } v\} + C)$  **and**  
 $\text{decomp}: ((\exists \chi \in \text{fst } \psi'').$   
 $(\forall I. \text{total-over-m } I \{ (\{\# \text{Pos } v\} + C') - \{\# \text{Pos } p\}$   
 $+ ((\{\# \text{Neg } v\} + C) - \{\# \text{Neg } p\}))$   
 $\longrightarrow \text{total-over-m } I \{ \chi \})$   
 $\wedge (\forall I. \text{total-over-m } I \{ \chi \} \longrightarrow I \models \chi$   
 $\longrightarrow I \models (\{\# \text{Pos } v\} + C') - \{\# \text{Pos } p\} + ((\{\# \text{Neg } v\} + C) - \{\# \text{Neg } p\}))$   
 $)$   
 $\vee \text{tautology } ((\{\# \text{Pos } v\} + C') - \{\# \text{Pos } p\} + ((\{\# \text{Neg } v\} + C) - \{\# \text{Neg } p\})))$   
**using**  $a$  **by** ( $\text{blast intro: allE[OF a-u-i-}\psi''[\text{unfolded subsumes-def Ball-def}]$ ,  
 $\text{of } (\{\# \text{Pos } v\} + C', \{\# \text{Neg } v\} + C))$   
**{ assume**  $p \neq v$   
**then have**  $\text{Pos } p \in \# C' \wedge \text{Neg } p \in \# C$  **using**  $p \ n$  **by force**  
**then have**  $?thesis$  **unfolding**  $\text{Bex-def}$  **by auto**  
**}**  
**moreover {**  
**assume**  $p = v$   
**then have**  $?thesis$  **using**  $\text{decomp}$  **by** ( $\text{metis add.commute add-diff-cancel-left'}$ )  
**}**  
**ultimately show**  $?thesis$  **by auto**  
**qed**  
**moreover {**  
**assume**  $\exists \chi \in \text{fst } \psi''. (\forall I. \text{total-over-m } I \{ C+C' \} \longrightarrow \text{total-over-m } I \{ \chi \})$   
 $\wedge (\forall I. \text{total-over-m } I \{ \chi \} \longrightarrow I \models \chi \longrightarrow I \models C' + C)$   
**then obtain**  $\vartheta$  **where**  $\vartheta: \vartheta \in \text{fst } \psi''$  **and**  
 $\text{tot-}\vartheta\text{-CC': } \forall I. \text{total-over-m } I \{ C+C' \} \longrightarrow \text{total-over-m } I \{ \vartheta \}$  **and**  
 $\vartheta\text{-inv: } \forall I. \text{total-over-m } I \{ \vartheta \} \longrightarrow I \models \vartheta \longrightarrow I \models C' + C$  **by blast**  
**have**  $\text{partial-interps Leaf } I (\text{fst } \psi'')$   
**using**  $\text{tot-}\vartheta\text{-CC' } \vartheta\text{-inv totC totC' } \langle \neg I \models C + C' \rangle \text{total-over-m-sum}$  **by fastforce**  
**moreover have**  $\text{sem-tree-size Leaf} < \text{sem-tree-size } xs$  **unfolding**  $xs$  **by auto**  
**ultimately have**  $?case$  **by** ( $\text{metis inf inf' rtranclp-trans}$ )  
**}**  
**moreover {**  
**assume**  $\text{tautCC': tautology } (C' + C)$   
**have**  $\text{total-over-m } I \{ C'+C \}$  **using**  $\text{totC totC' total-over-m-sum}$  **by auto**  
**then have**  $\neg \text{tautology } (C' + C)$   
**using**  $\langle \neg I \models C + C' \rangle$  **unfolding**  $\text{add.commute[of } C \ C'] \text{total-over-m-def}$   
**unfolding**  $\text{tautology-def}$  **by auto**  
**then have**  $\text{False}$  **using**  $\text{tautCC'}$  **unfolding**  $\text{tautology-def}$  **by auto**  
**}**  
**ultimately have**  $?case$  **by auto**  
**}**  
**ultimately have**  $?case$  **by auto**  
**}**  
**ultimately have**  $?case$  **using part** **by** ( $\text{metis (no-types) sem-tree-size.simps(1)}$ )  
**}**  
**moreover {**  
**assume**  $\text{size-ag: sem-tree-size ag} > 0$   
**have**  $\text{sem-tree-size ag} < \text{sem-tree-size } xs$  **unfolding**  $xs$  **by auto**  
**moreover have**  $\text{partial-interps ag } (I \cup \{\text{Pos } v\}) (\text{fst } \psi)$   
**and partad: partial-interps ad } (I \cup \{\text{Neg } v\}) (\text{fst } \psi)**

```

    using part partial-interps.simps(2) unfolding xs by metis+
  moreover have sem-tree-size ag < sem-tree-size xs  $\longrightarrow$  finite (fst  $\psi$ )  $\longrightarrow$  already-used-inv  $\psi$ 
     $\longrightarrow$  ( partial-interps ag (I  $\cup$  {Pos v}) (fst  $\psi$ )  $\longrightarrow$ 
      ( $\exists$  tree'  $\psi'$ . inference**  $\psi$   $\psi'$   $\wedge$  partial-interps tree' (I  $\cup$  {Pos v}) (fst  $\psi'$ )
         $\wedge$  (sem-tree-size tree' < sem-tree-size ag  $\vee$  sem-tree-size ag = 0)))
    using IH by auto
  ultimately obtain  $\psi' :: 'v$  state and tree' :: 'v sem-tree where
    inf: inference**  $\psi$   $\psi'$ 
    and part: partial-interps tree' (I  $\cup$  {Pos v}) (fst  $\psi'$ )
    and size: sem-tree-size tree' < sem-tree-size ag  $\vee$  sem-tree-size ag = 0
    using finite part rtranclp.rtrancl-refl a-u-i by blast

  have partial-interps ad (I  $\cup$  {Neg v}) (fst  $\psi'$ )
    using rtranclp-inference-preserve-partial-tree inf partad by metis
  then have partial-interps (Node v tree' ad) I (fst  $\psi'$ ) using part by auto
  then have ?case using inf size size-ag part unfolding xs by fastforce
}
moreover {
  assume size-ad: sem-tree-size ad > 0
  have sem-tree-size ad < sem-tree-size xs unfolding xs by auto
  moreover have partag: partial-interps ag (I  $\cup$  {Pos v}) (fst  $\psi$ ) and
    partial-interps ad (I  $\cup$  {Neg v}) (fst  $\psi$ )
    using part partial-interps.simps(2) unfolding xs by metis+
  moreover have sem-tree-size ad < sem-tree-size xs  $\longrightarrow$  finite (fst  $\psi$ )  $\longrightarrow$  already-used-inv  $\psi$ 
     $\longrightarrow$  ( partial-interps ad (I  $\cup$  {Neg v}) (fst  $\psi$ )
       $\longrightarrow$  ( $\exists$  tree'  $\psi'$ . inference**  $\psi$   $\psi'$   $\wedge$  partial-interps tree' (I  $\cup$  {Neg v}) (fst  $\psi'$ )
         $\wedge$  (sem-tree-size tree' < sem-tree-size ad  $\vee$  sem-tree-size ad = 0)))
    using IH by auto
  ultimately obtain  $\psi' :: 'v$  state and tree' :: 'v sem-tree where
    inf: inference**  $\psi$   $\psi'$ 
    and part: partial-interps tree' (I  $\cup$  {Neg v}) (fst  $\psi'$ )
    and size: sem-tree-size tree' < sem-tree-size ad  $\vee$  sem-tree-size ad = 0
    using finite part rtranclp.rtrancl-refl a-u-i by blast

  have partial-interps ag (I  $\cup$  {Pos v}) (fst  $\psi'$ )
    using rtranclp-inference-preserve-partial-tree inf partag by metis
  then have partial-interps (Node v ag tree') I (fst  $\psi'$ ) using part by auto
  then have ?case using inf size size-ad unfolding xs by fastforce
}
ultimately have ?case by auto
}
ultimately show ?case by auto
qed

```

```

lemma inference-completeness-inv:
  fixes  $\psi :: 'v :: \text{linorder}$  state
  assumes
    unsat:  $\neg$ satisfiable (fst  $\psi$ ) and
    finite: finite (fst  $\psi$ ) and
    a-u-v: already-used-inv  $\psi$ 
  shows  $\exists \psi'. (\text{inference** } \psi \ \psi' \wedge \{\#\} \in \text{fst } \psi')$ 
proof -
  obtain tree where partial-interps tree {} (fst  $\psi$ )
    using partial-interps-build-sem-tree-atms assms by metis
  then show ?thesis

```

```

using unsat finite a-u-v
proof (induct tree arbitrary:  $\psi$  rule: sem-tree-size)
  case (bigger tree  $\psi$ ) note  $H = \text{this}$ 
  {
    fix  $\chi$ 
    assume tree: tree = Leaf
    obtain  $\chi$  where  $\chi: \neg \{\} \models \chi$  and tot $\chi$ : total-over-m  $\{\} \{\chi\}$  and  $\chi\psi: \chi \in \text{fst } \psi$ 
    using  $H$  unfolding tree by auto
    moreover have  $\{\#\} = \chi$ 
    using tot $\chi$  unfolding total-over-m-def total-over-set-def by fastforce
    moreover have inference**  $\psi \psi$  by auto
    ultimately have ?case by metis
  }
moreover {
  fix  $v$  tree1 tree2
  assume tree: tree = Node v tree1 tree2
  obtain
    tree'  $\psi'$  where inf: inference**  $\psi \psi'$  and
    part': partial-interps tree'  $\{\}$  (fst  $\psi'$ ) and
    decrease: sem-tree-size tree' < sem-tree-size tree  $\vee$  sem-tree-size tree = 0
    using can-decrease-tree-size[of  $\psi$ ] H(2,4,5) unfolding tautology-def by meson
    have sem-tree-size tree' < sem-tree-size tree using decrease unfolding tree by auto
    moreover have finite (fst  $\psi'$ ) using rtranclp-inference-preserves-finite inf H(4) by metis
    moreover have unsatisfiable (fst  $\psi'$ )
    using inference-preserves-unsat inf bigger.prem(2) by blast
    moreover have already-used-inv  $\psi'$ 
    using H(5) inf rtranclp-inference-preserves-already-used-inv[of  $\psi \psi'$ ] by auto
    ultimately have ?case using inf rtranclp-trans part' H(1) by fastforce
  }
  ultimately show ?case by (cases tree, auto)
qed
qed

```

```

lemma inference-completeness:
  fixes  $\psi :: 'v :: \text{linorder state}$ 
  assumes unsat:  $\neg \text{satisfiable (fst } \psi)$ 
  and finite: finite (fst  $\psi$ )
  and snd  $\psi = \{\}$ 
  shows  $\exists \psi'. (\text{rtranclp inference } \psi \psi' \wedge \{\#\} \in \text{fst } \psi')$ 
proof –
  have already-used-inv  $\psi$  unfolding assms by auto
  then show ?thesis using assms inference-completeness-inv by blast
qed

```

```

lemma inference-soundness:
  fixes  $\psi :: 'v :: \text{linorder state}$ 
  assumes rtranclp inference  $\psi \psi'$  and  $\{\#\} \in \text{fst } \psi'$ 
  shows unsatisfiable (fst  $\psi$ )
  using assms by (meson rtranclp-inference-preserves-un-sat satisfiable-def true-cls-empty true-cls-def)

```

```

lemma inference-soundness-and-completeness:
  fixes  $\psi :: 'v :: \text{linorder state}$ 
  assumes finite: finite (fst  $\psi$ )
  and snd  $\psi = \{\}$ 

```

**shows**  $(\exists \psi'. (\text{inference}^{**} \psi \psi' \wedge \{\#\} \in \text{fst } \psi')) \longleftrightarrow \text{unsatisfiable } (\text{fst } \psi)$   
**using** *assms inference-completeness inference-soundness* **by** *metis*

### 13.4 Lemma about the simplified state

**abbreviation** *simplified*  $\psi \equiv (\text{no-step simplify } \psi)$

**lemma** *simplified-count*:

**assumes** *simp*: *simplified*  $\psi$  **and**  $\chi: \chi \in \psi$

**shows** *count*  $\chi$   $L \leq 1$

**proof** –

```
{
  let ? $\chi'$  =  $\chi - \{\#L, L\# \}$ 
  assume count  $\chi$   $L \geq 2$ 
  then have f1: count  $(\chi - \{\#L, L\# \} + \{\#L, L\# \})$   $L = \text{count } \chi$   $L$ 
    by simp
  then have  $L \in \# \chi - \{\#L\# \}$ 
    by (metis (no-types) add.left-neutral add-diff-cancel-left' count-union diff-diff-add
      diff-single-trivial insert-DiffM mem-Collect-eq multi-member-this not-gr0 set-mset-def)
  then have  $\chi'$ :  $? \chi' + \{\#L\# \} + \{\#L\# \} = \chi$ 
    using f1 by (metis diff-diff-add diff-single-eq-union in-diffD)

  have  $\exists \psi'. \text{simplify } \psi \psi'$ 
    by (metis (no-types, hide-lams)  $\chi \chi'$  add.commute factoring-imp-simplify union-assoc)
  then have False using simp by auto
}
```

**then show** *?thesis* **by** *arith*

**qed**

**lemma** *simplified-no-both*:

**assumes** *simp*: *simplified*  $\psi$  **and**  $\chi: \chi \in \psi$

**shows**  $\neg (L \in \# \chi \wedge -L \in \# \chi)$

**proof** (*rule ccontr*)

**assume**  $\neg \neg (L \in \# \chi \wedge -L \in \# \chi)$

**then have**  $L \in \# \chi \wedge -L \in \# \chi$  **by** *metis*

**then obtain**  $\chi'$  **where**  $\chi = \chi' + \{\#Pos \text{ (atm-of } L)\# \} + \{\#Neg \text{ (atm-of } L)\# \}$

**by** (*metis Neg-atm-of-iff Pos-atm-of-iff diff-union-swap insert-DiffM2 uminus-Neg uminus-Pos*)

**then show** *False* **using**  $\chi$  *simp tautology-deletion* **by** *fastforce*

**qed**

**lemma** *simplified-not-tautology*:

**assumes** *simplified*  $\{\psi\}$

**shows**  $\sim \text{tautology } \psi$

**proof** (*rule ccontr*)

**assume**  $\sim ?thesis$

**then obtain**  $p$  **where**  $Pos \ p \in \# \psi \wedge Neg \ p \in \# \psi$  **using** *tautology-decomp* **by** *metis*

**then obtain**  $\chi$  **where**  $\psi = \chi + \{\#Pos \ p\# \} + \{\#Neg \ p\# \}$

**by** (*metis insert-noteq-member literal.distinct(1) multi-member-split*)

**then have**  $\sim \text{simplified } \{\psi\}$  **by** (*auto intro: tautology-deletion*)

**then show** *False* **using** *assms* **by** *auto*

**qed**

**lemma** *simplified-remove*:

**assumes** *simplified*  $\{\psi\}$

**shows** *simplified*  $\{\psi - \{\#l\# \}\}$

**proof** (*rule ccontr*)



```

assume ns:  $\neg$  simplified  $\{\psi - \{\#l\#\}\}$ 
{
  assume  $\neg l \in \# \psi$ 
  then have  $\psi - \{\#l\#\} = \psi$  by simp
  then have False using ns assms by auto
}
moreover {
  assume  $l\psi: l \in \# \psi$ 
  have  $A: \bigwedge A. A \in \{\psi - \{\#l\#\}\} \longleftrightarrow A + \{\#l\#\} \in \{\psi\}$  by (auto simp add: lψ)
  obtain  $l'$  where  $l': \text{simplify } \{\psi - \{\#l\#\}\} \ l'$  using ns by metis
  then have  $\exists l'. \text{simplify } \{\psi\} \ l'$ 
  proof (induction rule: simplify.induct)
    case (tautology-deletion A P)
    have  $\{\#Neg \ P\# \} + (\{\#Pos \ P\# \} + (A + \{\#l\#\})) \in \{\psi\}$ 
      by (metis (no-types) A add.commute tautology-deletion.hyps union-lcomm)
    then show ?thesis
      by (metis simplify.tautology-deletion[of A+{\#l\#} P {\psi}] add.commute)
  next
    case (condensation A L)
    have  $A + \{\#L\# \} + \{\#L\# \} + \{\#l\#\} \in \{\psi\}$ 
      using A condensation.hyps by blast
    then have  $\{\#L, L\# \} + (A + \{\#l\#\}) \in \{\psi\}$ 
      by (metis (no-types) union-assoc union-commute)
    then show ?case
      using factoring-imp-simplify by blast
  next
    case (subsumption A B)
    then show ?case by blast
  qed
  then have False using assms(1) by blast
}
ultimately show False by auto
qed

```

```

lemma in-simplified-simplified:
  assumes simp: simplified ψ and incl: ψ' ⊆ ψ
  shows simplified ψ'
proof (rule ccontr)
  assume  $\neg ?thesis$ 
  then obtain  $\psi''$  where simplify ψ' ψ'' by metis
  then have  $\exists l'. \text{simplify } \psi \ l'$ 
  proof (induction rule: simplify.induct)
    case (tautology-deletion A P)
    then show ?thesis using simplify.tautology-deletion[of A P ψ] incl by blast
  next
    case (condensation A L)
    then show ?case using simplify.condensation[of A L ψ] incl by blast
  next
    case (subsumption A B)
    then show ?case using simplify.subsumption[of A ψ B] incl by auto
  qed
  then show False using assms(1) by blast
qed

```

```

lemma simplified-in:
  assumes simplified  $\psi$ 
  and  $N \in \psi$ 
  shows simplified  $\{N\}$ 
  using assms by (metis Set.set-insert empty-subsetI in-simplified-simplified insert-mono)

lemma subsumes-imp-formula:
  assumes  $\psi \leq \# \varphi$ 
  shows  $\{\psi\} \models_p \varphi$ 
  unfolding true-clss-clss-def apply auto
  using assms true-clss-mono-leD by blast

lemma simplified-imp-distinct-mset-tauto:
  assumes simp: simplified  $\psi'$ 
  shows distinct-mset-set  $\psi'$  and  $\forall \chi \in \psi'. \neg \text{tautology } \chi$ 
proof -
  show  $\forall \chi \in \psi'. \neg \text{tautology } \chi$ 
    using simp by (auto simp add: simplified-in simplified-not-tautology)

  show distinct-mset-set  $\psi'$ 
    proof (rule ccontr)
      assume  $\neg ?thesis$ 
      then obtain  $\chi$  where  $\chi \in \psi'$  and  $\neg \text{distinct-mset } \chi$  unfolding distinct-mset-set-def by auto
      then obtain  $L$  where count  $\chi$   $L \geq 2$ 
        unfolding distinct-mset-def
        by (meson count-greater-eq-one-iff le-antisym simp simplified-count)
      then show False by (metis Suc-1  $\langle \chi \in \psi' \rangle$  not-less-eq-eq simp simplified-count)
    qed
  qed

lemma simplified-no-more-full1-simplified:
  assumes simplified  $\psi$ 
  shows  $\neg \text{full1 simplify } \psi \psi'$ 
  using assms unfolding full1-def by (meson tranclpD)

```

## 13.5 Resolution and Invariants

```

inductive resolution :: 'v state  $\Rightarrow$  'v state  $\Rightarrow$  bool where
  full1-simp: full1 simplify  $N N' \Longrightarrow \text{resolution } (N, \text{already-used}) (N', \text{already-used})$  |
  inferring: inference  $(N, \text{already-used}) (N', \text{already-used}') \Longrightarrow \text{simplified } N$ 
   $\Longrightarrow \text{full simplify } N' N'' \Longrightarrow \text{resolution } (N, \text{already-used}) (N'', \text{already-used}')$ 

```

### 13.5.1 Invariants

```

lemma resolution-finite:
  assumes resolution  $\psi \psi'$  and finite (fst  $\psi$ )
  shows finite (fst  $\psi'$ )
  using assms by (induct rule: resolution.induct)
  (auto simp add: full1-def full-def rtranclp-simplify-preserves-finite
    dest: tranclp-into-rtranclp inference-preserves-finite)

lemma rtranclp-resolution-finite:
  assumes resolution**  $\psi \psi'$  and finite (fst  $\psi$ )
  shows finite (fst  $\psi'$ )
  using assms by (induct rule: rtranclp-induct, auto simp add: resolution-finite)

```

**lemma** *resolution-finite-snd*:  
**assumes** *resolution*  $\psi$   $\psi'$  **and** *finite* (*snd*  $\psi$ )  
**shows** *finite* (*snd*  $\psi'$ )  
**using** *assms* **apply** (*induct* rule: *resolution.induct*, *auto simp add: inference-preserves-finite-snd*)  
**using** *inference-preserves-finite-snd snd-conv* **by** *metis*

**lemma** *rtrancpl-resolution-finite-snd*:  
**assumes** *resolution*\*\*  $\psi$   $\psi'$  **and** *finite* (*snd*  $\psi$ )  
**shows** *finite* (*snd*  $\psi'$ )  
**using** *assms* **by** (*induct* rule: *rtrancpl-induct*, *auto simp add: resolution-finite-snd*)

**lemma** *resolution-always-simplified*:  
**assumes** *resolution*  $\psi$   $\psi'$   
**shows** *simplified* (*fst*  $\psi'$ )  
**using** *assms* **by** (*induct* rule: *resolution.induct*)  
(*auto simp add: full1-def full-def*)

**lemma** *trancpl-resolution-always-simplified*:  
**assumes** *trancpl resolution*  $\psi$   $\psi'$   
**shows** *simplified* (*fst*  $\psi'$ )  
**using** *assms* **by** (*induct* rule: *trancpl.induct*, *auto simp add: resolution-always-simplified*)

**lemma** *resolution-atms-of*:  
**assumes** *resolution*  $\psi$   $\psi'$  **and** *finite* (*fst*  $\psi$ )  
**shows** *atms-of-ms* (*fst*  $\psi'$ )  $\subseteq$  *atms-of-ms* (*fst*  $\psi$ )  
**using** *assms* **apply** (*induct* rule: *resolution.induct*)  
**apply** (*simp add: rtrancpl-simplify-atms-of-ms trancpl-into-rtrancpl full1-def*)  
**by** (*metis* (*no-types*, *lifting*) *contra-subsetD fst-conv full-def*  
*inference-preserves-atms-of-ms rtrancpl-simplify-atms-of-ms subsetI*)

**lemma** *rtrancpl-resolution-atms-of*:  
**assumes** *resolution*\*\*  $\psi$   $\psi'$  **and** *finite* (*fst*  $\psi$ )  
**shows** *atms-of-ms* (*fst*  $\psi'$ )  $\subseteq$  *atms-of-ms* (*fst*  $\psi$ )  
**using** *assms* **apply** (*induct* rule: *rtrancpl-induct*)  
**using** *resolution-atms-of rtrancpl-resolution-finite* **by** *blast+*

**lemma** *resolution-include*:  
**assumes** *res: resolution*  $\psi$   $\psi'$  **and** *finite: finite* (*fst*  $\psi$ )  
**shows** *fst*  $\psi' \subseteq$  *simple-clss* (*atms-of-ms* (*fst*  $\psi$ ))  
**proof** –  
**have** *finite'*: *finite* (*fst*  $\psi'$ ) **using** *local.finite res resolution-finite* **by** *blast*  
**have** *simplified* (*fst*  $\psi'$ ) **using** *res finite' resolution-always-simplified* **by** *blast*  
**then have** *fst*  $\psi' \subseteq$  *simple-clss* (*atms-of-ms* (*fst*  $\psi'$ ))  
**using** *simplified-in-simple-clss finite' simplified-imp-distinct-mset-tauto*[*of* *fst*  $\psi'$ ] **by** *auto*  
**moreover have** *atms-of-ms* (*fst*  $\psi'$ )  $\subseteq$  *atms-of-ms* (*fst*  $\psi$ )  
**using** *res finite resolution-atms-of*[*of*  $\psi$   $\psi'$ ] **by** *auto*  
**ultimately show** *?thesis* **by** (*meson* *atms-of-ms-finite local.finite order.trans rev-finite-subset*  
*simple-clss-mono*)  
**qed**

**lemma** *rtrancpl-resolution-include*:  
**assumes** *res: trancpl resolution*  $\psi$   $\psi'$  **and** *finite: finite* (*fst*  $\psi$ )  
**shows** *fst*  $\psi' \subseteq$  *simple-clss* (*atms-of-ms* (*fst*  $\psi$ ))  
**using** *assms* **apply** (*induct* rule: *trancpl.induct*)  
**apply** (*simp add: resolution-include*)

by (meson simple-clss-mono order-class.le-trans resolution-include  
 rtrancpl-resolution-atms-of rtrancpl-resolution-finite trancpl-into-rtrancpl)

**abbreviation** *already-used-all-simple*

:: ('a literal multiset  $\times$  'a literal multiset) set  $\Rightarrow$  'a set  $\Rightarrow$  bool **where**  
*already-used-all-simple* *already-used* vars  $\equiv$   
 $(\forall (A, B) \in \text{already-used. simplified } \{A\} \wedge \text{simplified } \{B\} \wedge \text{atms-of } A \subseteq \text{vars} \wedge \text{atms-of } B \subseteq \text{vars})$

**lemma** *already-used-all-simple-vars-incl*:

**assumes** *vars*  $\subseteq$  *vars'*  
**shows** *already-used-all-simple* *a vars*  $\implies$  *already-used-all-simple* *a vars'*  
**using** *assms* **by** *fast*

**lemma** *inference-clause-preserves-already-used-all-simple*:

**assumes** *inference-clause* *S S'*  
**and** *already-used-all-simple* (snd *S*) *vars*  
**and** *simplified* (fst *S*)  
**and** *atms-of-ms* (fst *S*)  $\subseteq$  *vars*  
**shows** *already-used-all-simple* (snd (fst *S*  $\cup$  {fst *S'*}, snd *S'*)) *vars*  
**using** *assms*

**proof** (induct rule: *inference-clause.induct*)

**case** (factoring *L C N* *already-used*)  
**then show** ?case **by** (simp add: *simplified-in* factoring-imp-simplify)

**next**

**case** (resolution *P C N D* *already-used*) **note** *H* = *this*

**show** ?case **apply** *clarify*

**proof** –

**fix** *A B v*

**assume**  $(A, B) \in \text{snd (fst (N, already-used))}$

$\cup \{\text{fst (C + D, already-used} \cup \{(\{\#Pos P\# \} + C, \{\#Neg P\# \} + D)\}),$   
 $\text{snd (C + D, already-used} \cup \{(\{\#Pos P\# \} + C, \{\#Neg P\# \} + D)\})\}$

**then have**  $(A, B) \in \text{already-used} \vee (A, B) = (\{\#Pos P\# \} + C, \{\#Neg P\# \} + D)$  **by** *auto*

**moreover** {

**assume**  $(A, B) \in \text{already-used}$

**then have** *simplified* {*A*}  $\wedge$  *simplified* {*B*}  $\wedge$  *atms-of* *A*  $\subseteq$  *vars*  $\wedge$  *atms-of* *B*  $\subseteq$  *vars*

**using** *H(4)* **by** *auto*

}

**moreover** {

**assume** *eq*:  $(A, B) = (\{\#Pos P\# \} + C, \{\#Neg P\# \} + D)$

**then have** *simplified* {*A*} **using** *simplified-in* *H(1,5)* **by** *auto*

**moreover have** *simplified* {*B*} **using** *eq* *simplified-in* *H(2,5)* **by** *auto*

**moreover have** *atms-of* *A*  $\subseteq$  *atms-of-ms* *N*

**using** *eq* *H(1)*

**using** *atms-of-atms-of-ms-mono*[of *A N*] **by** *auto*

**moreover have** *atms-of* *B*  $\subseteq$  *atms-of-ms* *N*

**using** *eq* *H(2)* *atms-of-atms-of-ms-mono*[of *B N*] **by** *auto*

**ultimately have** *simplified* {*A*}  $\wedge$  *simplified* {*B*}  $\wedge$  *atms-of* *A*  $\subseteq$  *vars*  $\wedge$  *atms-of* *B*  $\subseteq$  *vars*

**using** *H(6)* **by** *auto*

}

**ultimately show** *simplified* {*A*}  $\wedge$  *simplified* {*B*}  $\wedge$  *atms-of* *A*  $\subseteq$  *vars*  $\wedge$  *atms-of* *B*  $\subseteq$  *vars*  
**by** *fast*

**qed**

**qed**

**lemma** *inference-preserves-already-used-all-simple*:

```

assumes inference  $S\ S'$ 
and already-used-all-simple (snd  $S$ ) vars
and simplified (fst  $S$ )
and atms-of-ms (fst  $S$ )  $\subseteq$  vars
shows already-used-all-simple (snd  $S'$ ) vars
using assms
proof (induct rule: inference.induct)
  case (inference-step  $S$  clause already-used)
  then show ?case
    using inference-clause-preserves-already-used-all-simple[of  $S$  (clause, already-used) vars]
    by auto
qed

```

```

lemma already-used-all-simple-inv:
  assumes resolution  $S\ S'$ 
  and already-used-all-simple (snd  $S$ ) vars
  and atms-of-ms (fst  $S$ )  $\subseteq$  vars
  shows already-used-all-simple (snd  $S'$ ) vars
  using assms
proof (induct rule: resolution.induct)
  case (full1-simp  $N\ N'$ )
  then show ?case by simp
next
  case (inferring  $N$  already-used  $N'$  already-used'  $N''$ )
  then show already-used-all-simple (snd ( $N''$ , already-used') vars)
    using inference-preserves-already-used-all-simple[of ( $N$ , already-used)] by simp
qed

```

```

lemma rtranclp-already-used-all-simple-inv:
  assumes resolution**  $S\ S'$ 
  and already-used-all-simple (snd  $S$ ) vars
  and atms-of-ms (fst  $S$ )  $\subseteq$  vars
  and finite (fst  $S$ )
  shows already-used-all-simple (snd  $S'$ ) vars
  using assms
proof (induct rule: rtranclp-induct)
  case base
  then show ?case by simp
next
  case (step  $S'\ S''$ ) note infstar = this(1) and IH = this(3) and res = this(2) and
    already = this(4) and atms = this(5) and finite = this(6)
  have already-used-all-simple (snd  $S'$ ) vars using IH already atms finite by simp
  moreover have atms-of-ms (fst  $S'$ )  $\subseteq$  atms-of-ms (fst  $S$ )
    by (simp add: infstar local.finite rtranclp-resolution-atms-of)
  then have atms-of-ms (fst  $S'$ )  $\subseteq$  vars using atms by auto
  ultimately show ?case
    using already-used-all-simple-inv[OF res] by simp
qed

```

```

lemma inference-clause-simplified-already-used-subset:
  assumes inference-clause  $S\ S'$ 
  and simplified (fst  $S$ )
  shows snd  $S \subset$  snd  $S'$ 
  using assms apply (induct rule: inference-clause.induct, auto)
  using factoring-imp-simplify by blast

```

**lemma** *inference-simplified-already-used-subset*:  
**assumes** *inference*  $S\ S'$   
**and** *simplified* (*fst*  $S$ )  
**shows**  $\text{snd } S \subset \text{snd } S'$   
**using** *assms* **apply** (*induct* rule: *inference.induct*)  
**by** (*metis* *inference-clause-simplified-already-used-subset* *snd-conv*)

**lemma** *resolution-simplified-already-used-subset*:  
**assumes** *resolution*  $S\ S'$   
**and** *simplified* (*fst*  $S$ )  
**shows**  $\text{snd } S \subset \text{snd } S'$   
**using** *assms* **apply** (*induct* rule: *resolution.induct*, *simp-all* add: *full1-def*)  
**apply** (*meson* *trancpD*)  
**by** (*metis* *inference-simplified-already-used-subset* *fst-conv* *snd-conv*)

**lemma** *trancp-resolution-simplified-already-used-subset*:  
**assumes** *trancp* *resolution*  $S\ S'$   
**and** *simplified* (*fst*  $S$ )  
**shows**  $\text{snd } S \subset \text{snd } S'$   
**using** *assms* **apply** (*induct* rule: *trancp.induct*)  
**using** *resolution-simplified-already-used-subset* **apply** *metis*  
**by** (*meson* *trancp-resolution-always-simplified* *resolution-simplified-already-used-subset* *less-trans*)

**abbreviation** *already-used-top vars*  $\equiv$  *simple-clss vars*  $\times$  *simple-clss vars*

**lemma** *already-used-all-simple-in-already-used-top*:  
**assumes** *already-used-all-simple*  $s\ \text{vars}$  **and** *finite vars*  
**shows**  $s \subseteq \text{already-used-top vars}$   
**proof**  
**fix**  $x$   
**assume**  $x \in s$   
**obtain**  $A\ B$  **where**  $x = (A, B)$  **by** (*cases*  $x$ , *auto*)  
**then have** *simplified*  $\{A\}$  **and** *atms-of*  $A \subseteq \text{vars}$  **using** *assms*(1)  $x \in s$  **by** *fastforce* +  
**then have**  $A: A \in \text{simple-clss vars}$   
**using** *simple-clss-mono*[*of* *atms-of*  $A\ \text{vars}$ ]  $x \in s$  *assms*(2)  
*simplified-imp-distinct-mset-tauto*[*of*  $\{A\}$ ]  
*distinct-mset-not-tautology-implies-in-simple-clss* **by** *fast*  
**moreover have** *simplified*  $\{B\}$  **and** *atms-of*  $B \subseteq \text{vars}$  **using** *assms*(1)  $x = (A, B)$  **by** *fast* +  
**then have**  $B: B \in \text{simple-clss vars}$   
**using** *simplified-imp-distinct-mset-tauto*[*of*  $\{B\}$ ]  
*distinct-mset-not-tautology-implies-in-simple-clss*  
*simple-clss-mono*[*of* *atms-of*  $B\ \text{vars}$ ]  $x = (A, B)$  *assms*(2) **by** *fast*  
**ultimately show**  $x \in \text{simple-clss vars} \times \text{simple-clss vars}$   
**unfolding**  $x$  **by** *auto*  
**qed**

**lemma** *already-used-top-finite*:  
**assumes** *finite vars*  
**shows** *finite* (*already-used-top vars*)  
**using** *simple-clss-finite* *assms* **by** *auto*

**lemma** *already-used-top-increasing*:  
**assumes**  $\text{var} \subseteq \text{var}'$  **and** *finite var'*

**shows** *already-used-top var*  $\subseteq$  *already-used-top var'*  
**using** *assms simple-clss-mono* **by** *auto*

**lemma** *already-used-all-simple-finite*:  
**fixes** *s* :: ('a literal multiset  $\times$  'a literal multiset) *set* **and** *vars* :: 'a *set*  
**assumes** *already-used-all-simple s vars* **and** *finite vars*  
**shows** *finite s*  
**using** *assms already-used-all-simple-in-already-used-top* [*OF assms(1)*]  
*rev-finite-subset* [*OF already-used-top-finite* [*of vars*]] **by** *auto*

**abbreviation** *card-simple vars  $\psi \equiv$  card (already-used-top vars  $- \psi$ )*

**lemma** *resolution-card-simple-decreasing*:  
**assumes** *res: resolution  $\psi \psi'$*   
**and** *a-u-s: already-used-all-simple (snd  $\psi$ ) vars*  
**and** *finite-v: finite vars*  
**and** *finite-fst: finite (fst  $\psi$ )*  
**and** *finite-snd: finite (snd  $\psi$ )*  
**and** *simp: simplified (fst  $\psi$ )*  
**and** *atms-of-ms (fst  $\psi$ )  $\subseteq$  vars*  
**shows** *card-simple vars (snd  $\psi'$ ) < card-simple vars (snd  $\psi$ )*  
**proof** –  
**let** *?vars = vars*  
**let** *?top = simple-clss ?vars  $\times$  simple-clss ?vars*  
**have** *1: card-simple vars (snd  $\psi$ ) = card ?top – card (snd  $\psi$ )*  
**using** *card-Diff-subset finite-snd already-used-all-simple-in-already-used-top* [*OF a-u-s*]  
*finite-v* **by** *metis*  
**have** *a-u-s': already-used-all-simple (snd  $\psi'$ ) vars*  
**using** *already-used-all-simple-inv res a-u-s assms(7)* **by** *blast*  
**have** *f: finite (snd  $\psi'$ )* **using** *already-used-all-simple-finite a-u-s' finite-v* **by** *auto*  
**have** *2: card-simple vars (snd  $\psi'$ ) = card ?top – card (snd  $\psi'$ )*  
**using** *card-Diff-subset* [*OF f*] *already-used-all-simple-in-already-used-top* [*OF a-u-s' finite-v*]  
**by** *auto*  
**have** *card (already-used-top vars)  $\geq$  card (snd  $\psi'$ )*  
**using** *already-used-all-simple-in-already-used-top* [*OF a-u-s' finite-v*]  
*card-mono* [*of already-used-top vars snd  $\psi'$* ] *already-used-top-finite* [*OF finite-v*] **by** *metis*  
**then show** *?thesis*  
**using** *psubset-card-mono* [*OF f resolution-simplified-already-used-subset* [*OF res simp*]]  
*unfolding* *1 2* **by** *linarith*  
**qed**

**lemma** *trancp-resolution-card-simple-decreasing*:  
**assumes** *trancp resolution  $\psi \psi'$*  **and** *finite-fst: finite (fst  $\psi$ )*  
**and** *already-used-all-simple (snd  $\psi$ ) vars*  
**and** *atms-of-ms (fst  $\psi$ )  $\subseteq$  vars*  
**and** *finite-v: finite vars*  
**and** *finite-snd: finite (snd  $\psi$ )*  
**and** *simplified (fst  $\psi$ )*  
**shows** *card-simple vars (snd  $\psi'$ ) < card-simple vars (snd  $\psi$ )*  
**using** *assms*  
**proof** (*induct rule: trancp-induct*)  
**case** (*base  $\psi'$* )  
**then show** *?case* **by** (*simp add: resolution-card-simple-decreasing*)  
**next**

**case** (*step*  $\psi' \psi''$ ) **note**  $\text{res} = \text{this}(1)$  **and**  $\text{res}' = \text{this}(2)$  **and**  $a\text{-}u\text{-}s = \text{this}(5)$  **and**  
 $\text{atms} = \text{this}(6)$  **and**  $f\text{-}v = \text{this}(7)$  **and**  $f\text{-}fst = \text{this}(4)$  **and**  $H = \text{this}$   
**then have** *card-simple vars* ( $\text{snd } \psi'$ )  $<$  *card-simple vars* ( $\text{snd } \psi$ ) **by** *auto*  
**moreover have**  $a\text{-}u\text{-}s'$ : *already-used-all-simple* ( $\text{snd } \psi'$ ) *vars*  
**using** *rtrancpl-already-used-all-simple-inv*[*OF* *trancpl-into-rtrancpl*[*OF*  $\text{res}$ ]  $a\text{-}u\text{-}s$   $\text{atms}$   $f\text{-}fst$ ] .  
**have** *finite* ( $\text{fst } \psi'$ )  
**by** (*meson* *finite-fst res rtrancpl-resolution-finite trancpl-into-rtrancpl*)  
**moreover have** *finite* ( $\text{snd } \psi'$ ) **using** *already-used-all-simple-finite*[*OF*  $a\text{-}u\text{-}s'$   $f\text{-}v$ ] .  
**moreover have** *simplified* ( $\text{fst } \psi'$ ) **using**  $\text{res}$  *trancpl-resolution-always-simplified* **by** *blast*  
**moreover have**  $\text{atms-of-ms}$  ( $\text{fst } \psi'$ )  $\subseteq$  *vars*  
**by** (*meson*  $\text{atms}$   $f\text{-}fst$  *order.trans res rtrancpl-resolution-atms-of trancpl-into-rtrancpl*)  
**ultimately show** ?*case*  
**using** *resolution-card-simple-decreasing*[*OF*  $\text{res}'$   $a\text{-}u\text{-}s'$   $f\text{-}v$ ]  $f\text{-}v$   
*less-trans*[*of* *card-simple vars* ( $\text{snd } \psi''$ ) *card-simple vars* ( $\text{snd } \psi'$ )  
*card-simple vars* ( $\text{snd } \psi$ )]  
**by** *blast*  
**qed**

**lemma** *trancpl-resolution-card-simple-decreasing-2*:  
**assumes** *trancpl resolution*  $\psi \psi'$   
**and** *finite-fst*: *finite* ( $\text{fst } \psi$ )  
**and** *empty-snd*:  $\text{snd } \psi = \{\}$   
**and** *simplified* ( $\text{fst } \psi$ )  
**shows** *card-simple* ( $\text{atms-of-ms}$  ( $\text{fst } \psi$ )) ( $\text{snd } \psi'$ )  $<$  *card-simple* ( $\text{atms-of-ms}$  ( $\text{fst } \psi$ )) ( $\text{snd } \psi$ )  
**proof** –  
**let** ?*vars* = ( $\text{atms-of-ms}$  ( $\text{fst } \psi$ ))  
**have** *already-used-all-simple* ( $\text{snd } \psi$ ) ?*vars* **unfolding** *empty-snd* **by** *auto*  
**moreover have**  $\text{atms-of-ms}$  ( $\text{fst } \psi$ )  $\subseteq$  ?*vars* **by** *auto*  
**moreover have** *finite-v*: *finite* ?*vars* **using** *finite-fst* **by** *auto*  
**moreover have** *finite-snd*: *finite* ( $\text{snd } \psi$ ) **unfolding** *empty-snd* **by** *auto*  
**ultimately show** ?*thesis*  
**using** *assms*(1,2,4) *trancpl-resolution-card-simple-decreasing*[*of*  $\psi \psi'$ ] **by** *presburger*  
**qed**

### 13.5.2 well-foundedness if the relation

**lemma** *wf-simplified-resolution*:  
**assumes**  $f\text{-vars}$ : *finite vars*  
**shows** *wf*  $\{(y:: 'v:: \text{linorder state}, x). (\text{atms-of-ms}$  ( $\text{fst } x$ )  $\subseteq$  *vars*  $\wedge$  *simplified* ( $\text{fst } x$ )  
 $\wedge$  *finite* ( $\text{snd } x$ )  $\wedge$  *finite* ( $\text{fst } x$ )  $\wedge$  *already-used-all-simple* ( $\text{snd } x$ ) *vars*)  $\wedge$  *resolution*  $x y\}$   
**proof** –  
**{**  
**fix**  $a b :: 'v:: \text{linorder state}$   
**assume**  $(b, a) \in \{(y, x). (\text{atms-of-ms}$  ( $\text{fst } x$ )  $\subseteq$  *vars*  $\wedge$  *simplified* ( $\text{fst } x$ )  $\wedge$  *finite* ( $\text{snd } x$ )  
 $\wedge$  *finite* ( $\text{fst } x$ )  $\wedge$  *already-used-all-simple* ( $\text{snd } x$ ) *vars*)  $\wedge$  *resolution*  $x y\}$   
**then have**  
 $\text{atms-of-ms}$  ( $\text{fst } a$ )  $\subseteq$  *vars* **and**  
*simp*: *simplified* ( $\text{fst } a$ ) **and**  
*finite* ( $\text{snd } a$ ) **and**  
*finite* ( $\text{fst } a$ ) **and**  
 $a\text{-}u\text{-}v$ : *already-used-all-simple* ( $\text{snd } a$ ) *vars* **and**  
 $\text{res}$ : *resolution*  $a b$  **by** *auto*  
**have** *finite* ( $\text{already-used-top vars}$ ) **using**  $f\text{-vars}$  *already-used-top-finite* **by** *blast*  
**moreover have**  $\text{already-used-top vars} \subseteq$  *already-used-top vars* **by** *auto*  
**moreover have**  $\text{snd } b \subseteq$  *already-used-top vars*



```

    using already-used-all-simple-in-already-used-top[of snd b vars]
    a-u-v already-used-all-simple-inv[OF res] ⟨finite (fst a)⟩ ⟨atms-of-ms (fst a) ⊆ vars⟩ f-vars
    by presburger
  moreover have snd a ⊆ snd b using resolution-simplified-already-used-subset[OF res simp] .
  ultimately have finite (already-used-top vars) ∧ already-used-top vars ⊆ already-used-top vars
    ∧ snd b ⊆ already-used-top vars ∧ snd a ⊆ snd b by metis
}
then show ?thesis using wf-bounded-set[of {(y:: 'v:: linorder state, x).
  (atms-of-ms (fst x) ⊆ vars
  ∧ simplified (fst x) ∧ finite (snd x) ∧ finite (fst x) ∧ already-used-all-simple (snd x) vars)
  ∧ resolution x y} λ-. already-used-top vars snd] by auto
qed

```

**lemma** *wf-simplified-resolution'*:

```

  assumes f-vars: finite vars
  shows wf {(y:: 'v:: linorder state, x). (atms-of-ms (fst x) ⊆ vars ∧ ¬simplified (fst x)
    ∧ finite (snd x) ∧ finite (fst x) ∧ already-used-all-simple (snd x) vars) ∧ resolution x y}
  unfolding wf-def
  apply (simp add: resolution-always-simplified)
  by (metis (mono-tags, hide-lams) fst-conv resolution-always-simplified)

```

**lemma** *wf-resolution*:

```

  assumes f-vars: finite vars
  shows wf {(y:: 'v:: linorder state, x). (atms-of-ms (fst x) ⊆ vars ∧ simplified (fst x)
    ∧ finite (snd x) ∧ finite (fst x) ∧ already-used-all-simple (snd x) vars) ∧ resolution x y}
    ∪ {(y, x). (atms-of-ms (fst x) ⊆ vars ∧ ¬simplified (fst x) ∧ finite (snd x) ∧ finite (fst x)
    ∧ already-used-all-simple (snd x) vars) ∧ resolution x y} (is wf (?R ∪ ?S))

```

**proof** –

```

  have Domain ?R Int Range ?S = {} using resolution-always-simplified by auto blast
  then show wf (?R ∪ ?S)
    using wf-simplified-resolution[OF f-vars] wf-simplified-resolution'[OF f-vars] wf-Un[of ?R ?S]
    by fast

```

**qed**

**lemma** *rtrancp-simplify-already-used-inv*:

```

  assumes simplify** S S'
  and already-used-inv (S, N)
  shows already-used-inv (S', N)
  using assms apply induction
  using simplify-preserves-already-used-inv by fast+

```

**lemma** *full1-simplify-already-used-inv*:

```

  assumes full1 simplify S S'
  and already-used-inv (S, N)
  shows already-used-inv (S', N)
  using assms trancp-into-rtrancp[of simplify S S'] rtrancp-simplify-already-used-inv
  unfolding full1-def by fast

```

**lemma** *full-simplify-already-used-inv*:

```

  assumes full simplify S S'
  and already-used-inv (S, N)
  shows already-used-inv (S', N)
  using assms rtrancp-simplify-already-used-inv unfolding full-def by fast

```

**lemma** *resolution-already-used-inv*:

```

  assumes resolution S S'

```

```

and already-used-inv S
shows already-used-inv S'
using assms
proof induction
case (full1-simp N N' already-used)
then show ?case using full1-simplify-already-used-inv by fast
next
case (inferring N already-used N' already-used' N'') note inf = this(1) and full = this(3) and
a-u-v = this(4)
then show ?case
using inference-preserves-already-used-inv[OF inf a-u-v] full-simplify-already-used-inv full
by fast
qed

```

```

lemma rtranclp-resolution-already-used-inv:
assumes resolution** S S'
and already-used-inv S
shows already-used-inv S'
using assms apply induction
using resolution-already-used-inv by fast+

```

```

lemma rtranclp-simplify-preserves-unsat:
assumes simplify**  $\psi$   $\psi'$ 
shows satisfiable  $\psi' \longrightarrow$  satisfiable  $\psi$ 
using assms apply induction
using simplify-clause-preserves-sat by blast+

```

```

lemma full1-simplify-preserves-unsat:
assumes full1 simplify  $\psi$   $\psi'$ 
shows satisfiable  $\psi' \longrightarrow$  satisfiable  $\psi$ 
using assms rtranclp-simplify-preserves-unsat[of  $\psi$   $\psi'$ ] tranclp-into-rtranclp
unfolding full1-def by metis

```

```

lemma full-simplify-preserves-unsat:
assumes full simplify  $\psi$   $\psi'$ 
shows satisfiable  $\psi' \longrightarrow$  satisfiable  $\psi$ 
using assms rtranclp-simplify-preserves-unsat[of  $\psi$   $\psi'$ ] unfolding full-def by metis

```

```

lemma resolution-preserves-unsat:
assumes resolution  $\psi$   $\psi'$ 
shows satisfiable (fst  $\psi'$ )  $\longrightarrow$  satisfiable (fst  $\psi$ )
using assms apply (induct rule: resolution.induct)
using full1-simplify-preserves-unsat apply (metis fst-conv)
using full-simplify-preserves-unsat simplify-preserves-unsat by fastforce

```

```

lemma rtranclp-resolution-preserves-unsat:
assumes resolution**  $\psi$   $\psi'$ 
shows satisfiable (fst  $\psi'$ )  $\longrightarrow$  satisfiable (fst  $\psi$ )
using assms apply induction
using resolution-preserves-unsat by fast+

```

```

lemma rtranclp-simplify-preserve-partial-tree:
assumes simplify** N N'
and partial-interps t I N
shows partial-interps t I N'

```

```

using assms apply (induction, simp)
using simplify-preserve-partial-tree by metis

lemma full1-simplify-preserve-partial-tree:
  assumes full1 simplify N N'
  and partial-interps t I N
  shows partial-interps t I N'
  using assms rtrancp-simplify-preserve-partial-tree[of N N' t I] trancp-into-rtrancp
  unfolding full1-def by fast

lemma full-simplify-preserve-partial-tree:
  assumes full simplify N N'
  and partial-interps t I N
  shows partial-interps t I N'
  using assms rtrancp-simplify-preserve-partial-tree[of N N' t I] trancp-into-rtrancp
  unfolding full-def by fast

lemma resolution-preserve-partial-tree:
  assumes resolution S S'
  and partial-interps t I (fst S)
  shows partial-interps t I (fst S')
  using assms apply induction
    using full1-simplify-preserve-partial-tree fst-conv apply metis
  using full-simplify-preserve-partial-tree inference-preserve-partial-tree by fastforce

lemma rtrancp-resolution-preserve-partial-tree:
  assumes resolution** S S'
  and partial-interps t I (fst S)
  shows partial-interps t I (fst S')
  using assms apply induction
  using resolution-preserve-partial-tree by fast+
  thm nat-less-induct nat.induct

lemma nat-ge-induct[case-names 0 Suc]:
  assumes P 0
  and  $(\bigwedge n. (\bigwedge m. m < \text{Suc } n \implies P m) \implies P (\text{Suc } n))$ 
  shows P n
  using assms apply (induct rule: nat-less-induct)
  by (rename-tac n, case-tac n) auto

lemma wf-always-more-step-False:
  assumes wf R
  shows  $(\forall x. \exists z. (z, x) \in R) \implies \text{False}$ 
  using assms unfolding wf-def by (meson Domain.DomainI assms wfE-min)

lemma finite-finite-mset-element-of-mset[simp]:
  assumes finite N
  shows finite {f  $\varphi$  L |  $\varphi$  L.  $\varphi \in N \wedge L \in \# \varphi \wedge P \varphi L$ }
  using assms
proof (induction N rule: finite-induct)
  case empty
  show ?case by auto
next
  case (insert x N) note finite = this(1) and IH = this(3)
  have  $\{f \varphi L \mid \varphi L. (\varphi = x \vee \varphi \in N) \wedge L \in \# \varphi \wedge P \varphi L\} \subseteq \{f x L \mid L. L \in \# x \wedge P x L\}$ 

```

$\cup \{f \varphi L \mid \varphi L. \varphi \in N \wedge L \in \# \varphi \wedge P \varphi L\}$  **by** *auto*  
**moreover have** *finite*  $\{f x L \mid L. L \in \# x\}$  **by** *auto*  
**ultimately show** *?case* **using** *IH finite-subset* **by** *fastforce*  
**qed**

**value** *card*  
**value** *filter-mset*  
**value**  $\{\#count \varphi L \mid L \in \# \varphi. 2 \leq count \varphi L\# \}$   
**value**  $(\lambda \varphi. msetsum \{\#count \varphi L \mid L \in \# \varphi. 2 \leq count \varphi L\# \})$

**syntax**

$-comprehension1'-mset :: 'a \Rightarrow 'b \Rightarrow 'b \text{ multiset} \Rightarrow 'a \text{ multiset}$   
 $((\{\#-/. - : setof -\# \}))$

**translations**

$\{\#e. x: setof M\# \} == CONST \text{ set-mset } (CONST \text{ image-mset } (\%x. e) M)$   
**value**  $\{\# a. a : setof \{\#1,1,2::int\}\# \} = \{1,2\}$

**definition** *sum-count-ge-2*  $:: 'a \text{ multiset set} \Rightarrow nat (\Xi)$  **where**

*sum-count-ge-2*  $\equiv folding.F (\lambda \varphi. op + (msetsum \{\#count \varphi L \mid L \in \# \varphi. 2 \leq count \varphi L\# \})) 0$

**interpretation** *sum-count-ge-2*:

*folding*  $(\lambda \varphi. op + (msetsum \{\#count \varphi L \mid L \in \# \varphi. 2 \leq count \varphi L\# \})) 0$

**rewrites**

*folding.F*  $(\lambda \varphi. op + (msetsum \{\#count \varphi L \mid L \in \# \varphi. 2 \leq count \varphi L\# \})) 0 = \text{sum-count-ge-2}$

**proof** –

**show** *folding*  $(\lambda \varphi. op + (msetsum (\text{image-mset } (count \varphi) \{\# L \in \# \varphi. 2 \leq count \varphi L\# \})))$   
**by** *standard auto*

**then interpret** *sum-count-ge-2*:

*folding*  $(\lambda \varphi. op + (msetsum \{\#count \varphi L \mid L \in \# \varphi. 2 \leq count \varphi L\# \})) 0 .$

**show** *folding.F*  $(\lambda \varphi. op + (msetsum (\text{image-mset } (count \varphi) \{\# L \in \# \varphi. 2 \leq count \varphi L\# \}))) 0$   
 $= \text{sum-count-ge-2}$  **by**  $(\text{auto simp add: sum-count-ge-2-def})$

**qed**

**lemma** *finite-incl-le-setsum*:

*finite*  $(B::'a \text{ multiset set}) \Longrightarrow A \subseteq B \Longrightarrow \Xi A \leq \Xi B$

**proof**  $(\text{induction arbitrary:} A \text{ rule: finite-induct})$

**case** *empty*

**then show** *?case* **by** *simp*

**next**

**case**  $(\text{insert } a \ F)$  **note** *finite*  $= \text{this}(1)$  **and**  $aF = \text{this}(2)$  **and** *IH*  $= \text{this}(3)$  **and**  $AF = \text{this}(4)$

**show** *?case*

**proof**  $(\text{cases } a \in A)$

**assume**  $a \notin A$

**then have**  $A \subseteq F$  **using** *AF* **by** *auto*

**then show** *?case* **using** *IH[of A]* **by**  $(\text{simp add: } aF \text{ local.finite})$

**next**

**assume**  $aA: a \in A$

**then have**  $A - \{a\} \subseteq F$  **using** *AF* **by** *auto*

**then have**  $\Xi (A - \{a\}) \leq \Xi F$  **using** *IH* **by** *blast*

**then show** *?case*

**proof** –

**obtain**  $nn :: nat \Rightarrow nat \Rightarrow nat$  **where**

$\forall x0 \ x1. (\exists v2. x0 = x1 + v2) = (x0 = x1 + nn \ x0 \ x1)$

```

    by moura
  then have  $\Xi F = \Xi (A - \{a\}) + nn (\Xi F) (\Xi (A - \{a\}))$ 
    by (meson  $\langle \Xi (A - \{a\}) \leq \Xi F \rangle$  le-iff-add)
  then show ?thesis
    by (metis (no-types) le-iff-add aA aF add.assoc finite.insertI finite-subset
        insert.prem local.finite sum-count-ge-2.insert sum-count-ge-2.remove)
qed
qed
qed

lemma simplify-finite-measure-decrease:
  simplify  $N N' \implies$  finite  $N \implies$  card  $N' + \Xi N' <$  card  $N + \Xi N$ 
proof (induction rule: simplify.induct)
  case (tautology-deletion A P) note an = this(1) and fin = this(2)
  let  $?N' = N - \{A + \{\#Pos P\# \} + \{\#Neg P\# \}\}$ 
  have card  $?N' <$  card  $N$ 
    by (meson card-Diff1-less tautology-deletion.hyps tautology-deletion.prem)
  moreover have  $?N' \subseteq N$  by auto
  then have sum-count-ge-2  $?N' \leq$  sum-count-ge-2  $N$  using finite-incl-le-setsum[OF fin] by blast
  ultimately show ?case by linarith
next
  case (condensation A L) note AN = this(1) and fin = this(2)
  let  $?C' = A + \{\#L\#\}$ 
  let  $?C = A + \{\#L\#\} + \{\#L\#\}$ 
  let  $?N' = N - \{?C\} \cup \{?C'\}$ 
  have card  $?N' \leq$  card  $N$ 
    using AN by (metis (no-types, lifting) Diff-subset Un-empty-right Un-insert-right card.remove
        card-insert-if card-mono fin finite-Diff order-refl)
  moreover have  $\Xi \{?C'\} <$   $\Xi \{?C\}$ 
  proof -
    have mset-decomp:
       $\{\# La \in \# A. (L = La \longrightarrow La \in \# A) \wedge (L \neq La \longrightarrow 2 \leq \text{count } A La)\#\}$ 
      =  $\{\# La \in \# A. L \neq La \wedge 2 \leq \text{count } A La\#\} +$ 
       $\{\# La \in \# A. L = La \wedge \text{Suc } 0 \leq \text{count } A L\#\}$ 
      by (auto simp: multiset-eq-iff ac-simps)
    have mset-decomp2:  $\{\# La \in \# A. L \neq La \longrightarrow 2 \leq \text{count } A La\#\} =$ 
       $\{\# La \in \# A. L \neq La \wedge 2 \leq \text{count } A La\#\} + \text{replicate-mset } (\text{count } A L) L$ 
      by (auto simp: multiset-eq-iff)
    show ?thesis
      by (auto simp: mset-decomp mset-decomp2 filter-mset-eq ac-simps)
  qed
qed
have  $\Xi ?N' <$   $\Xi N$ 
proof cases
  assume a1:  $?C' \in N$ 
  then show ?thesis
    proof -
      have f2:  $\bigwedge m M. \text{insert } (m::'a \text{ literal multiset}) (M - \{m\}) = M \cup \{ \} \vee m \notin M$ 
        using Un-empty-right insert-Diff by blast
      have f3:  $\bigwedge m M Ma. \text{insert } (m::'a \text{ literal multiset}) M - \text{insert } m Ma = M - \text{insert } m Ma$ 
        by simp
      then have f4:  $\bigwedge M m. M - \{m::'a \text{ literal multiset}\} = M \cup \{ \} \vee m \in M$ 
        using Diff-insert-absorb Un-empty-right by fastforce
      have f5:  $\text{insert } (A + \{\#L\#\} + \{\#L\#\}) N = N$ 
        using f3 f2 Un-empty-right condensation.hyps insert-iff by fastforce
      have  $\bigwedge m M. \text{insert } (m::'a \text{ literal multiset}) M = M \cup \{ \} \vee m \notin M$ 

```

```

    using f3 f2 Un-empty-right add.right-neutral insert-iff by fastforce
  then have  $\Xi (N - \{A + \{\#L\#\} + \{\#L\#\}\}) < \Xi N$ 
    using f5 f4 by (metis Un-empty-right  $\langle \Xi \{A + \{\#L\#\}\} < \Xi \{A + \{\#L\#\} + \{\#L\#\}\} \rangle$ 
      add.right-neutral add-diff-cancel-left' add-gr-0 diff-less fin finite.emptyI not-le
      sum-count-ge-2.empty sum-count-ge-2.insert-remove trans-le-add2)
  then show ?thesis
    using f3 f2 a1 by (metis (no-types) Un-empty-right Un-insert-right condensation.hyps
      insert-iff multi-self-add-other-not-self)
  qed
next
assume  $?C' \notin N$ 
have mset-decomp:
   $\{\# La \in \# A. (L = La \longrightarrow \text{Suc } 0 \leq \text{count } A \text{ } La) \wedge (L \neq La \longrightarrow 2 \leq \text{count } A \text{ } La)\#\}$ 
  =  $\{\# La \in \# A. L \neq La \wedge 2 \leq \text{count } A \text{ } La\#\} +$ 
   $\{\# La \in \# A. L = La \wedge \text{Suc } 0 \leq \text{count } A \text{ } L\#\}$ 
  by (auto simp: multiset-eq-iff ac-simps)
have mset-decomp2:  $\{\# La \in \# A. L \neq La \longrightarrow 2 \leq \text{count } A \text{ } La\#\} =$ 
   $\{\# La \in \# A. L \neq La \wedge 2 \leq \text{count } A \text{ } La\#\} + \text{replicate-mset } (\text{count } A \text{ } L) \text{ } L$ 
  by (auto simp: multiset-eq-iff)

show ?thesis
  using  $\langle \Xi \{A + \{\#L\#\}\} < \Xi \{A + \{\#L\#\} + \{\#L\#\}\} \rangle$  condensation.hyps fin
  sum-count-ge-2.remove[of -  $A + \{\#L\#\} + \{\#L\#\}$ ]  $\langle ?C' \notin N \rangle$ 
  by (auto simp: mset-decomp mset-decomp2 filter-mset-eq)
qed
ultimately show ?case by linarith
next
case (subsumption A B) note AN = this(1) and AB = this(2) and BN = this(3) and fin = this(4)
have card  $(N - \{B\}) < \text{card } N$  using BN by (meson card-Diff1-less subsumption.prem)
moreover have  $\Xi (N - \{B\}) \leq \Xi N$ 
  by (simp add: Diff-subset finite-incl-le-setsum subsumption.prem)
ultimately show ?case by linarith
qed

lemma simplify-terminates:
  wf  $\{(N', N). \text{finite } N \wedge \text{simplify } N \text{ } N'\}$ 
  using assms apply (rule wfP-if-measure[of finite simplify  $\lambda N. \text{card } N + \Xi N$ ])
  using simplify-finite-measure-decrease by blast

lemma wf-terminates:
  assumes wf r
  shows  $\exists N'. (N', N) \in r^* \wedge (\forall N''. (N'', N') \notin r)$ 
proof -
  let ?P =  $\lambda N. (\exists N'. (N', N) \in r^* \wedge (\forall N''. (N'', N') \notin r))$ 
  have  $(\forall x. (\forall y. (y, x) \in r \longrightarrow ?P y) \longrightarrow ?P x)$ 
  proof clarify
    fix x
    assume H:  $\forall y. (y, x) \in r \longrightarrow ?P y$ 
    { assume  $\exists y. (y, x) \in r$ 
      then obtain y where  $y: (y, x) \in r$  by blast
      then have ?P y using H by blast
      then have ?P x using y by (meson rtrancl.rtrancl-into-rtrancl)
    }
  qed

```

```

    moreover {
      assume  $\neg(\exists y. (y, x) \in r)$ 
      then have  $?P\ x$  by auto
    }
    ultimately show  $?P\ x$  by blast
  qed
moreover have  $(\forall x. (\forall y. (y, x) \in r \longrightarrow ?P\ y) \longrightarrow ?P\ x) \longrightarrow All\ ?P$ 
  using assms unfolding wf-def by (rule allE)
ultimately have  $All\ ?P$  by blast
then show  $?P\ N$  by blast
qed

lemma rtrancl-simplify-terminates:
  assumes fin: finite N
  shows  $\exists N'. simplify^{**}\ N\ N' \wedge simplified\ N'$ 
proof -
  have H:  $\{(N', N). finite\ N \wedge simplify\ N\ N'\} = \{(N', N). simplify\ N\ N' \wedge finite\ N\}$  by auto
  then have wf: wf  $\{(N', N). simplify\ N\ N' \wedge finite\ N\}$ 
    using simplify-terminates by (simp add: H)
  obtain N' where N':  $(N', N) \in \{(b, a). simplify\ a\ b \wedge finite\ a\}^*$  and
    more:  $(\forall N''. (N'', N') \notin \{(b, a). simplify\ a\ b \wedge finite\ a\})$ 
    using Prop-Resolution.wf-terminates[OF wf, of N] by blast
  have 1:  $simplify^{**}\ N\ N'$ 
    using N' by (induction rule: rtrancl.induct) auto
  then have finite N' using fin rtrancl-simplify-preserves-finite by blast
  then have 2:  $\forall N''. \neg simplify\ N'\ N''$  using more by auto

  show  $?thesis$  using 1 2 by blast
qed

lemma finite-simplified-full1-simp:
  assumes finite N
  shows  $simplified\ N \vee (\exists N'. full1\ simplify\ N\ N')$ 
  using rtrancl-simplify-terminates[OF assms] unfolding full1-def
  by (metis Nitpick.rtrancl-unfold)

lemma finite-simplified-full-simp:
  assumes finite N
  shows  $\exists N'. full\ simplify\ N\ N'$ 
  using rtrancl-simplify-terminates[OF assms] unfolding full-def by metis

lemma can-decrease-tree-size-resolution:
  fixes  $\psi :: 'v\ state$  and  $tree :: 'v\ sem-tree$ 
  assumes finite (fst  $\psi$ ) and already-used-inv  $\psi$ 
  and partial-interps  $tree\ I$  (fst  $\psi$ )
  and simplified (fst  $\psi$ )
  shows  $\exists (tree' :: 'v\ sem-tree)\ \psi'. resolution^{**}\ \psi\ \psi' \wedge partial-interps\ tree'\ I\ (fst\ \psi')$ 
     $\wedge (sem-tree-size\ tree' < sem-tree-size\ tree \vee sem-tree-size\ tree = 0)$ 
  using assms
proof (induct arbitrary: I rule: sem-tree-size)
  case (bigger xs I) note IH = this(1) and finite = this(2) and a-u-i = this(3) and part = this(4)
    and simp = this(5)

  { assume sem-tree-size xs = 0
    then have  $?case$  using part by blast

```

}

moreover {

assume  $sn0$ :  $sem-tree-size\ xs > 0$

obtain  $ag\ ad\ v$  where  $xs$ :  $xs = Node\ v\ ag\ ad$  using  $sn0$  by ( $cases\ xs$ ,  $auto$ )

{

assume  $sem-tree-size\ ag = 0 \wedge sem-tree-size\ ad = 0$

then have  $ag$ :  $ag = Leaf$  and  $ad$ :  $ad = Leaf$  by ( $cases\ ag$ ,  $auto$ ,  $cases\ ad$ ,  $auto$ )

then obtain  $\chi\ \chi'$  where

$\chi$ :  $\neg I \cup \{Pos\ v\} \models \chi$  and

$tot\chi$ :  $total-over-m\ (I \cup \{Pos\ v\})\ \{\chi\}$  and

$\chi\psi$ :  $\chi \in fst\ \psi$  and

$\chi'$ :  $\neg I \cup \{Neg\ v\} \models \chi'$  and

$tot\chi'$ :  $total-over-m\ (I \cup \{Neg\ v\})\ \{\chi'\}$  and  $\chi'\psi$ :  $\chi' \in fst\ \psi$

using  $part\ unfolding\ xs$  by  $auto$

have  $Posv$ :  $Pos\ v \notin \# \chi$  using  $\chi$  unfolding  $true-cls-def\ true-lit-def$  by  $auto$

have  $Negv$ :  $Neg\ v \notin \# \chi'$  using  $\chi'$  unfolding  $true-cls-def\ true-lit-def$  by  $auto$

{

assume  $Neg\chi$ :  $\neg Neg\ v \in \# \chi$

then have  $\neg I \models \chi$  using  $\chi\ Posv$  unfolding  $true-cls-def\ true-lit-def$  by  $auto$

moreover have  $total-over-m\ I\ \{\chi\}$

using  $Posv\ Neg\chi\ atm-imp-pos-or-neg-lit\ tot\chi$  unfolding  $total-over-m-def\ total-over-set-def$  by  $fastforce$

ultimately have  $partial-interps\ Leaf\ I\ (fst\ \psi)$

and  $sem-tree-size\ Leaf < sem-tree-size\ xs$

and  $resolution^{**}\ \psi\ \psi$

unfolding  $xs$  by ( $auto\ simp\ add$ :  $\chi\psi$ )

}

moreover {

assume  $Pos\chi$ :  $\neg Pos\ v \in \# \chi'$

then have  $I\chi$ :  $\neg I \models \chi'$  using  $\chi'\ Posv$  unfolding  $true-cls-def\ true-lit-def$  by  $auto$

moreover have  $total-over-m\ I\ \{\chi'\}$

using  $Negv\ Pos\chi\ atm-imp-pos-or-neg-lit\ tot\chi'$

unfolding  $total-over-m-def\ total-over-set-def$  by  $fastforce$

ultimately have  $partial-interps\ Leaf\ I\ (fst\ \psi)$

and  $sem-tree-size\ Leaf < sem-tree-size\ xs$

and  $resolution^{**}\ \psi\ \psi$  using  $\chi'\psi\ I\chi$  unfolding  $xs$  by  $auto$

}

moreover {

assume  $neg$ :  $Neg\ v \in \# \chi$  and  $pos$ :  $Pos\ v \in \# \chi'$

have  $count\ \chi\ (Neg\ v) = 1$

using  $simplified-count[OF\ simp\ \chi\psi]\ neg$

by ( $simp\ add$ :  $dual-order.antisym$ )

have  $count\ \chi'\ (Pos\ v) = 1$

using  $simplified-count[OF\ simp\ \chi'\psi]\ pos$

by ( $simp\ add$ :  $dual-order.antisym$ )

obtain  $C$  where  $\chi C$ :  $\chi = C + \{\#Neg\ v\#\}$  and  $negC$ :  $Neg\ v \notin \# C$  and  $posC$ :  $Pos\ v \notin \# C$

by ( $metis\ (no-types,\ lifting)\ One-nat-def\ Posv\ Suc-eq-plus1-left\ \langle count\ \chi\ (Neg\ v) = 1 \rangle$

$add-diff-cancel-left'\ count-diff\ count-greater-eq-one-iff\ count-single\ insert-DiffM$

$insert-DiffM2\ less-numeral-extra(3)\ multi-member-skip\ not-le\ not-less-eq-eq$ )

obtain  $C'$  where

$\chi C'$ :  $\chi' = C' + \{\#Pos\ v\#\}$  and



```

posC': Pos v ∈# C' and
negC': Neg v ∈# C'
by (metis (no-types, lifting) One-nat-def Negv Suc-eq-plus1-left ‹count χ' (Pos v) = 1›
    add-diff-cancel-left' count-diff count-greater-eq-one-iff count-single insert-DiffM
    insert-DiffM2 less-numeral-extra(3) multi-member-skip not-le not-less-eq-eq)

have totC: total-over-m I {C}
  using totχ tot-over-m-remove[of I Pos v C] negC posC unfolding χC
  by (metis total-over-m-sum uminus-Neg uminus-of-uminus-id)
have totC': total-over-m I {C'}
  using totχ' total-over-m-sum tot-over-m-remove[of I Neg v C'] negC' posC'
  unfolding χC' by (metis total-over-m-sum uminus-Neg)
have ¬ I ⊨ C + C'
  using χ χ' χC χC' by auto
then have part-I-ψ''': partial-interps Leaf I (fst ψ ∪ {C + C'})
  using totC totC' ‹¬ I ⊨ C + C'› by (metis Un-insert-right insertI1
    partial-interps.simps(1) total-over-m-sum)
{
  assume ({#Pos v#} + C', {#Neg v#} + C) ∉ snd ψ
  then have inf'': inference ψ (fst ψ ∪ {C + C'}, snd ψ ∪ {(χ', χ)})
    by (metis χ'ψ χC χC' χψ add commute inference-step prod.collapse resolution)
  obtain N' where full: full simplify (fst ψ ∪ {C + C'}) N'
  by (metis finite-simplified-full-simp fst-conv inf'' inference-preserves-finite
    local.finite)
  have resolution ψ (N', snd ψ ∪ {(χ', χ)})
    using resolution.intros(2)[OF - simp full, of snd ψ snd ψ ∪ {(χ', χ)}] inf''
    by (metis surjective-pairing)
  moreover have partial-interps Leaf I N'
    using full-simplify-preserve-partial-tree[OF full part-I-ψ'''] .
  moreover have sem-tree-size Leaf < sem-tree-size xs unfolding xs by auto
  ultimately have ?case
    by (metis (no-types) prod.sel(1) rtranclp.rtrancl-into-rtrancl rtranclp.rtrancl-refl)
}
moreover {
  assume a: ({#Pos v#} + C', {#Neg v#} + C) ∈ snd ψ
  then have (∃χ ∈ fst ψ. (∀I. total-over-m I {C+C'} → total-over-m I {χ})
    ∧ (∀I. total-over-m I {χ} → I ⊨ χ → I ⊨ C' + C)) ∨ tautology (C' + C)
  proof -
    obtain p where p: Pos p ∈# ({#Pos v#} + C') ∧ Neg p ∈# ({#Neg v#} + C)
      ∧ ((∃χ ∈ fst ψ. (∀I. total-over-m I {({#Pos v#} + C') - {#Pos p#} + (({#Neg v#}
+ C) - {#Neg p#}))) → total-over-m I {χ}) ∧ (∀I. total-over-m I {χ} → I ⊨ χ → I ⊨ ({#Pos
v#} + C') - {#Pos p#} + (({#Neg v#} + C) - {#Neg p#}))) ∨ tautology (({#Pos v#} + C') -
{#Pos p#} + (({#Neg v#} + C) - {#Neg p#})))
    using a by (blast intro: allE[OF a-u-i[unfolded subsumes-def Ball-def],
      of ({#Pos v#} + C', {#Neg v#} + C)])
    { assume p ≠ v
      then have Pos p ∈# C' ∧ Neg p ∈# C using p by force
      then have ?thesis by auto
    }
  }
  moreover {
    assume p = v
    then have ?thesis using p by (metis add commute add-diff-cancel-left')
  }
  ultimately show ?thesis by auto
qed

```

```

moreover {
  assume  $\exists \chi \in \text{fst } \psi. (\forall I. \text{total-over-}m \ I \ \{C+C'\} \longrightarrow \text{total-over-}m \ I \ \{\chi\})$ 
     $\wedge (\forall I. \text{total-over-}m \ I \ \{\chi\} \longrightarrow I \models \chi \longrightarrow I \models C' + C)$ 
  then obtain  $\vartheta$  where
     $\vartheta: \vartheta \in \text{fst } \psi$  and
     $\text{tot-}\vartheta\text{-}CC': \forall I. \text{total-over-}m \ I \ \{C+C'\} \longrightarrow \text{total-over-}m \ I \ \{\vartheta\}$  and
     $\vartheta\text{-inv}: \forall I. \text{total-over-}m \ I \ \{\vartheta\} \longrightarrow I \models \vartheta \longrightarrow I \models C' + C$  by blast
  have partial-interps Leaf I (fst  $\psi$ )
    using  $\text{tot-}\vartheta\text{-}CC' \ \vartheta \ \vartheta\text{-inv} \ \text{tot}C \ \text{tot}C' \ \langle \neg I \models C + C' \rangle \ \text{total-over-}m\text{-sum}$  by fastforce
  moreover have sem-tree-size Leaf  $< \text{sem-tree-size } xs$  unfolding xs by auto
  ultimately have ?case by blast
}
moreover {
  assume tautCC': tautology ( $C' + C$ )
  have total-over-}m \ I \ \{C'+C\} using totC totC' total-over-}m-sum by auto
  then have  $\neg \text{tautology} \ (C' + C)$ 
    using  $\langle \neg I \models C + C' \rangle$  unfolding add.commute[of C C'] total-over-}m-def
    unfolding tautology-def by auto
  then have False using tautCC' unfolding tautology-def by auto
}
ultimately have ?case by auto
}
ultimately have ?case using part by (metis (no-types) sem-tree-size.simps(1))
}
moreover {
  assume size-ag: sem-tree-size ag  $> 0$ 
  have sem-tree-size ag  $< \text{sem-tree-size } xs$  unfolding xs by auto
  moreover have partial-interps ag ( $I \cup \{\text{Pos } v\}$ ) (fst  $\psi$ )
  and partad: partial-interps ad ( $I \cup \{\text{Neg } v\}$ ) (fst  $\psi$ )
    using part partial-interps.simps(2) unfolding xs by metis+
  moreover
    have sem-tree-size ag  $< \text{sem-tree-size } xs \implies \text{finite} \ (\text{fst } \psi) \implies \text{already-used-inv } \psi$ 
       $\implies \text{partial-interps } \text{ag} \ (I \cup \{\text{Pos } v\}) \ (\text{fst } \psi) \implies \text{simplified} \ (\text{fst } \psi)$ 
       $\implies \exists \text{tree}' \ \psi'. \text{resolution}^{**} \ \psi \ \psi' \wedge \text{partial-interps } \text{tree}' \ (I \cup \{\text{Pos } v\}) \ (\text{fst } \psi')$ 
       $\wedge (\text{sem-tree-size } \text{tree}' < \text{sem-tree-size } \text{ag} \vee \text{sem-tree-size } \text{ag} = 0)$ 
    using IH[of ag I  $\cup$  {Pos v}] by auto
  ultimately obtain  $\psi' :: 'v \text{ state}$  and  $\text{tree}' :: 'v \text{ sem-tree}$  where
    inf: resolution**  $\psi \ \psi'$ 
    and part: partial-interps tree' ( $I \cup \{\text{Pos } v\}$ ) (fst  $\psi'$ )
    and size: sem-tree-size tree'  $< \text{sem-tree-size } \text{ag} \vee \text{sem-tree-size } \text{ag} = 0$ 
    using finite part rtranclp.rtrancl-refl a-u-i simp by blast

  have partial-interps ad ( $I \cup \{\text{Neg } v\}$ ) (fst  $\psi'$ )
    using rtranclp-resolution-preserve-partial-tree inf partad by fast
  then have partial-interps (Node v tree' ad) I (fst  $\psi'$ ) using part by auto
  then have ?case using inf size size-ag part unfolding xs by fastforce
}
moreover {
  assume size-ad: sem-tree-size ad  $> 0$ 
  have sem-tree-size ad  $< \text{sem-tree-size } xs$  unfolding xs by auto
  moreover
    have
      partag: partial-interps ag ( $I \cup \{\text{Pos } v\}$ ) (fst  $\psi$ ) and

```

```

    partial-interps ad (I ∪ {Neg v}) (fst ψ)
    using part partial-interps.simps(2) unfolding xs by metis+
  moreover have sem-tree-size ad < sem-tree-size xs ⟶ finite (fst ψ) ⟶ already-used-inv ψ
    ⟶ ( partial-interps ad (I ∪ {Neg v}) (fst ψ) ⟶ simplified (fst ψ)
    ⟶ (∃ tree' ψ'. resolution** ψ ψ' ∧ partial-interps tree' (I ∪ {Neg v}) (fst ψ')
      ∧ (sem-tree-size tree' < sem-tree-size ad ∨ sem-tree-size ad = 0)))
    using IH by blast
  ultimately obtain ψ' :: 'v state and tree' :: 'v sem-tree where
    inf: resolution** ψ ψ'
    and part: partial-interps tree' (I ∪ {Neg v}) (fst ψ')
    and size: sem-tree-size tree' < sem-tree-size ad ∨ sem-tree-size ad = 0
    using finite part rtranclp.rtrancl-refl a-u-i simp by blast

  have partial-interps ag (I ∪ {Pos v}) (fst ψ')
    using rtranclp-resolution-preserve-partial-tree inf partag by fast
  then have partial-interps (Node v ag tree') I (fst ψ') using part by auto
  then have ?case using inf size size-ad unfolding xs by fastforce
}
ultimately have ?case by auto
}
ultimately show ?case by auto
qed

```

**lemma** resolution-completeness-inv:

```

  fixes ψ :: 'v :: linorder state
  assumes
    unsat: ¬satisfiable (fst ψ) and
    finite: finite (fst ψ) and
    a-u-v: already-used-inv ψ
  shows ∃ ψ'. (resolution** ψ ψ' ∧ {#} ∈ fst ψ')
proof -
  obtain tree where partial-interps tree {} (fst ψ)
    using partial-interps-build-sem-tree-atms assms by metis
  then show ?thesis
    using unsat finite a-u-v
  proof (induct tree arbitrary: ψ rule: sem-tree-size)
    case (bigger tree ψ) note H = this
    {
      fix χ
      assume tree: tree = Leaf
      obtain χ where χ: ¬ {} ⊨ χ and totχ: total-over-m {} {χ} and χψ: χ ∈ fst ψ
        using H unfolding tree by auto
      moreover have {#} = χ
        using H atms-empty-iff-empty totχ
        unfolding true-cls-def total-over-m-def total-over-set-def by fastforce
      moreover have resolution** ψ ψ by auto
      ultimately have ?case by metis
    }
  moreover {
    fix v tree1 tree2
    assume tree: tree = Node v tree1 tree2
    obtain ψ₀ where ψ₀: resolution** ψ ψ₀ and simp: simplified (fst ψ₀)
    proof -
      { assume simplified (fst ψ)
        moreover have resolution** ψ ψ by auto
      }
    }
  }

```

```

ultimately have thesis using that by blast
}
moreover {
  assume  $\neg$ simplified (fst  $\psi$ )
  then have  $\exists \psi'. \text{full1 simplify } (\text{fst } \psi) \psi'$ 
    by (metis Nitpick.rtranclp-unfold bigger.prem(3) full1-def
        rtranclp-simplify-terminates)
  then obtain N where full1 simplify (fst  $\psi$ ) N by metis
  then have resolution  $\psi$  (N, snd  $\psi$ )
    using resolution.intros(1)[of fst  $\psi$  N snd  $\psi$ ] by auto
  moreover have simplified N
    using  $\langle \text{full1 simplify } (\text{fst } \psi) N \rangle$  unfolding full1-def by blast
  ultimately have ?thesis using that by force
}
ultimately show ?thesis by auto
qed

```

```

have p: partial-interps tree {} (fst  $\psi_0$ )
and uns: unsatisfiable (fst  $\psi_0$ )
and f: finite (fst  $\psi_0$ )
and a-u-v: already-used-inv  $\psi_0$ 
  using  $\psi_0$  bigger.prem(1) rtranclp-resolution-preserve-partial-tree apply blast
  using  $\psi_0$  bigger.prem(2) rtranclp-resolution-preserves-unsat apply blast
  using  $\psi_0$  bigger.prem(3) rtranclp-resolution-finite apply blast
  using rtranclp-resolution-already-used-inv[OF  $\psi_0$  bigger.prem(4)] by blast
obtain tree'  $\psi'$  where
  inf: resolution**  $\psi_0 \psi'$  and
  part': partial-interps tree' {} (fst  $\psi'$ ) and
  decrease: sem-tree-size tree' < sem-tree-size tree  $\vee$  sem-tree-size tree = 0
  using can-decrease-tree-size-resolution[OF f a-u-v p simp] unfolding tautology-def
  by meson
have s: sem-tree-size tree' < sem-tree-size tree using decrease unfolding tree by auto
have fin: finite (fst  $\psi'$ )
  using f inf rtranclp-resolution-finite by blast
have unsat: unsatisfiable (fst  $\psi'$ )
  using rtranclp-resolution-preserves-unsat inf uns by metis
have a-u-i': already-used-inv  $\psi'$ 
  using a-u-v inf rtranclp-resolution-already-used-inv[of  $\psi_0 \psi'$ ] by auto
have ?case
  using inf rtranclp-trans[of resolution] H(1)[OF s part' unsat fin a-u-i']  $\psi_0$  by blast
}
ultimately show ?case by (cases tree, auto)
qed
qed

```

```

lemma resolution-preserves-already-used-inv:
  assumes resolution S S'
  and already-used-inv S
  shows already-used-inv S'
  using assms
  apply (induct rule: resolution.induct)
  apply (rule full1-simplify-already-used-inv; simp)
  apply (rule full-simplify-already-used-inv, simp)
  apply (rule inference-preserves-already-used-inv, simp)

```

**apply** *blast*  
**done**

**lemma** *rtranclp-resolution-preserves-already-used-inv*:  
**assumes** *resolution\*\* S S'*  
**and** *already-used-inv S*  
**shows** *already-used-inv S'*  
**using** *assms*  
**apply** (*induct rule: rtranclp-induct*)  
**apply** *simp*  
**using** *resolution-preserves-already-used-inv* **by** *fast*

**lemma** *resolution-completeness*:  
**fixes**  $\psi :: 'v :: \text{linorder state}$   
**assumes** *unsat:  $\neg \text{satisfiable (fst } \psi)$*   
**and** *finite: finite (fst  $\psi$ )*  
**and** *snd  $\psi = \{\}$*   
**shows**  $\exists \psi'. (\text{resolution** } \psi \ \psi' \wedge \{\#\} \in \text{fst } \psi')$   
**proof** –  
**have** *already-used-inv  $\psi$  unfolding assms by auto*  
**then show** *?thesis using assms resolution-completeness-inv by blast*  
**qed**

**lemma** *rtranclp-preserves-sat*:  
**assumes** *simplify\*\* S S'*  
**and** *satisfiable S*  
**shows** *satisfiable S'*  
**using** *assms* **apply** *induction*  
**apply** *simp*  
**by** (*meson satisfiable-carac satisfiable-def simplify-preserves-un-sat-eq*)

**lemma** *resolution-preserves-sat*:  
**assumes** *resolution S S'*  
**and** *satisfiable (fst S)*  
**shows** *satisfiable (fst S')*  
**using** *assms* **apply** (*induction rule: resolution.induct*)  
**using** *rtranclp-preserves-sat tranclp-into-rtranclp unfolding full1-def apply fastforce*  
**by** (*metis fst-conv full-def inference-preserves-un-sat rtranclp-preserves-sat satisfiable-carac' satisfiable-def*)

**lemma** *rtranclp-resolution-preserves-sat*:  
**assumes** *resolution\*\* S S'*  
**and** *satisfiable (fst S)*  
**shows** *satisfiable (fst S')*  
**using** *assms* **apply** (*induction rule: rtranclp-induct*)  
**apply** *simp*  
**using** *resolution-preserves-sat* **by** *blast*

**lemma** *resolution-soundness*:  
**fixes**  $\psi :: 'v :: \text{linorder state}$   
**assumes** *resolution\*\*  $\psi \ \psi'$  and  $\{\#\} \in \text{fst } \psi'$*   
**shows** *unsatisfiable (fst  $\psi$ )*  
**using** *assms* **by** (*meson rtranclp-resolution-preserves-sat satisfiable-def true-cls-empty true-cls-def*)

```

lemma resolution-soundness-and-completeness:
fixes  $\psi :: 'v :: \text{linorder state}$ 
assumes finite: finite (fst  $\psi$ )
and snd: snd  $\psi = \{\}$ 
shows  $(\exists \psi'. (\text{resolution}^{**} \psi \psi' \wedge \{\#\} \in \text{fst } \psi')) \longleftrightarrow \text{unsatisfiable } (\text{fst } \psi)$ 
using assms resolution-completeness resolution-soundness by metis

lemma simplified-falsity:
assumes simp: simplified  $\psi$ 
and  $\{\#\} \in \psi$ 
shows  $\psi = \{\{\#\}\}$ 
proof (rule ccontr)
assume H:  $\neg ?thesis$ 
then obtain  $\chi$  where  $\chi \in \psi$  and  $\chi \neq \{\#\}$  using assms(2) by blast
then have  $\{\#\} \subsetneq \chi$  by (simp add: mset-less-empty-nonempty)
then have simplify  $\psi$  ( $\psi - \{\chi\}$ )
using simplify.subsumption[OF assms(2)  $\langle \{\#\} \subsetneq \chi \rangle \langle \chi \in \psi \rangle$ ] by blast
then show False using simp by blast
qed

lemma simplify-falsity-in-preserved:
assumes simplify  $\chi s \chi s'$ 
and  $\{\#\} \in \chi s$ 
shows  $\{\#\} \in \chi s'$ 
using assms
by induction auto

lemma rtranclp-simplify-falsity-in-preserved:
assumes simplify**  $\chi s \chi s'$ 
and  $\{\#\} \in \chi s$ 
shows  $\{\#\} \in \chi s'$ 
using assms
by induction (auto intro: simplify-falsity-in-preserved)

lemma resolution-falsity-get-falsity-alone:
assumes finite (fst  $\psi$ )
shows  $(\exists \psi'. (\text{resolution}^{**} \psi \psi' \wedge \{\#\} \in \text{fst } \psi')) \longleftrightarrow (\exists a-u-v. \text{resolution}^{**} \psi (\{\{\#\}\}, a-u-v))$ 
(is  $?A \longleftrightarrow ?B$ )
proof
assume  $?B$ 
then show  $?A$  by auto
next
assume  $?A$ 
then obtain  $\chi s$  a-u-v where  $\chi s: \text{resolution}^{**} \psi (\chi s, a-u-v)$  and  $F: \{\#\} \in \chi s$  by auto
{ assume simplified  $\chi s$ 
then have  $?B$  using simplified-falsity[OF - F]  $\chi s$  by blast
}
moreover {
assume  $\neg \text{simplified } \chi s$ 
then obtain  $\chi s'$  where full1 simplify  $\chi s \chi s'$ 
by (metis  $\chi s$  assms finite-simplified-full1-simp fst-conv rtranclp-resolution-finite)
then have  $\{\#\} \in \chi s'$ 
unfolding full1-def by (meson F rtranclp-simplify-falsity-in-preserved
trancplp-into-rtranclp)

```

```

    then have ?B
      by (metis  $\chi s$  (full1 simplify  $\chi s$   $\chi s'$ ) fst-conv full1-simp resolution-always-simplified
        rtrancp.rtranc1-into-rtranc1 simplified-falsity)
    }
    ultimately show ?B by blast
qed

lemma resolution-soundness-and-completeness':
  fixes  $\psi :: 'v :: \text{linorder state}$ 
  assumes
    finite: finite (fst  $\psi$ ) and
    snd: snd  $\psi = \{\}$ 
  shows  $(\exists a-u-v. (\text{resolution}^{**} \psi (\{\#\}, a-u-v))) \longleftrightarrow \text{unsatisfiable (fst } \psi)$ 
  using assms resolution-completeness resolution-soundness resolution-falsity-get-falsity-alone
  by metis

```

end

theory Partial-Annotated-Clausal-Logic  
 imports Partial-Clausal-Logic

begin

## 14 Partial Clausal Logic

We here define marked literals (that will be used in both DPLL and CDCL) and the entailment corresponding to it.

### 14.1 Marked Literals

#### 14.1.1 Definition

```

datatype ('v, 'lvl, 'mark) marked-lit =
  is-marked: Marked (lit-of: 'v literal) (level-of: 'lvl) |
  is-proped: Propagated (lit-of: 'v literal) (mark-of: 'mark)

```

```

lemma marked-lit-list-induct[case-names nil marked proped]:
  assumes  $P []$  and
     $\bigwedge L l xs. P xs \implies P (\text{Marked } L l \# xs)$  and
     $\bigwedge L m xs. P xs \implies P (\text{Propagated } L m \# xs)$ 
  shows  $P xs$ 
  using assms apply (induction xs, simp)
  by (rename-tac a xs, case-tac a) auto

```

```

lemma is-marked-ex-Marked:
  is-marked  $L \implies \exists K lvl. L = \text{Marked } K lvl$ 
  by (cases L) auto

```

```

type-synonym ('v, 'l, 'm) marked-lits = ('v, 'l, 'm) marked-lit list

```

```

definition lits-of :: ('a, 'b, 'c) marked-lit set  $\Rightarrow$  'a literal set where
  lits-of  $Ls = \text{lit-of } 'Ls$ 

```

```

abbreviation lits-of-l :: ('a, 'b, 'c) marked-lit list  $\Rightarrow$  'a literal set where
  lits-of-l  $Ls \equiv \text{lits-of (set } Ls)$ 

```

**lemma** *lits-of-l-empty[simp]*:  
*lits-of*  $\{\}$  =  $\{\}$   
**unfolding** *lits-of-def* **by** *auto*

**lemma** *lits-of-insert[simp]*:  
*lits-of* (*insert*  $L$   $Ls$ ) = *insert* (*lit-of*  $L$ ) (*lits-of*  $Ls$ )  
**unfolding** *lits-of-def* **by** *auto*

**lemma** *lits-of-l-append[simp]*:  
*lits-of* ( $l \cup l'$ ) = *lits-of*  $l \cup$  *lits-of*  $l'$   
**unfolding** *lits-of-def* **by** *auto*

**lemma** *finite-lits-of-def[simp]*:  
*finite* (*lits-of-l*  $L$ )  
**unfolding** *lits-of-def* **by** *auto*

**abbreviation** *unmark* **where**  
*unmark*  $\equiv (\lambda a. \{\#lit-of\ a\# \})$

**abbreviation** *unmark-s* **where**  
*unmark-s*  $M \equiv unmark\ 'M$

**abbreviation** *unmark-l* **where**  
*unmark-l*  $M \equiv unmark-s\ (set\ M)$

**lemma** *atms-of-ms-lambda-lit-of-is-atm-of-lit-of[simp]*:  
*atms-of-ms* (*unmark-l*  $M'$ ) = *atm-of* '*lits-of-l*  $M'$ '  
**unfolding** *atms-of-ms-def lits-of-def* **by** *auto*

**lemma** *lits-of-l-empty-is-empty[iff]*:  
*lits-of-l*  $M = \{\} \longleftrightarrow M = []$   
**by** (*induct*  $M$ ) (*auto simp: lits-of-def*)

### 14.1.2 Entailment

**definition** *true-annot* :: ( $'a, 'l, 'm$ ) *marked-lits*  $\Rightarrow 'a\ clause \Rightarrow bool$  (**infix**  $\models_a$  49) **where**  
 $I \models_a C \longleftrightarrow (lits-of-l\ I) \models C$

**definition** *true-annots* :: ( $'a, 'l, 'm$ ) *marked-lits*  $\Rightarrow 'a\ clauses \Rightarrow bool$  (**infix**  $\models_{as}$  49) **where**  
 $I \models_{as} CC \longleftrightarrow (\forall C \in CC. I \models_a C)$

**lemma** *true-annot-empty-model[simp]*:  
 $\neg [] \models_a \psi$   
**unfolding** *true-annot-def true-cls-def* **by** *simp*

**lemma** *true-annot-empty[simp]*:  
 $\neg I \models_a \{\#\}$   
**unfolding** *true-annot-def true-cls-def* **by** *simp*

**lemma** *empty-true-annots-def[iff]*:  
 $[] \models_{as} \psi \longleftrightarrow \psi = \{\}$   
**unfolding** *true-annots-def* **by** *auto*

**lemma** *true-annots-empty[simp]*:  
 $I \models_{as} \{\}$



**unfolding** *true-annots-def* **by** *auto*

**lemma** *true-annots-single-true-annot*[*iff*]:

$I \models_{as} \{C\} \longleftrightarrow I \models_a C$

**unfolding** *true-annots-def* **by** *auto*

**lemma** *true-annot-insert-l*[*simp*]:

$M \models_a A \implies L \# M \models_a A$

**unfolding** *true-annot-def* **by** *auto*

**lemma** *true-annots-insert-l* [*simp*]:

$M \models_{as} A \implies L \# M \models_{as} A$

**unfolding** *true-annots-def* **by** *auto*

**lemma** *true-annots-union*[*iff*]:

$M \models_{as} A \cup B \longleftrightarrow (M \models_{as} A \wedge M \models_{as} B)$

**unfolding** *true-annots-def* **by** *auto*

**lemma** *true-annots-insert*[*iff*]:

$M \models_{as} \text{insert } a \ A \longleftrightarrow (M \models_a a \wedge M \models_{as} A)$

**unfolding** *true-annots-def* **by** *auto*

Link between  $\models_{as}$  and  $\models_s$ :

**lemma** *true-annots-true-cls*:

$I \models_{as} CC \longleftrightarrow \text{lits-of-l } I \models_s CC$

**unfolding** *true-annots-def* *Ball-def* *true-annot-def* *true-clss-def* **by** *auto*

**lemma** *in-lit-of-true-annot*:

$a \in \text{lits-of-l } M \longleftrightarrow M \models_a \{\#a\# \}$

**unfolding** *true-annot-def* *lits-of-def* **by** *auto*

**lemma** *true-annot-lit-of-notin-skip*:

$L \# M \models_a A \implies \text{lit-of } L \notin \# A \implies M \models_a A$

**unfolding** *true-annot-def* *true-cls-def* **by** *auto*

**lemma** *true-clss-singleton-lit-of-implies-incl*:

$I \models_s \text{unmark-l } MLs \implies \text{lits-of-l } MLs \subseteq I$

**unfolding** *true-clss-def* *lits-of-def* **by** *auto*

**lemma** *true-annot-true-clss-cls*:

$MLs \models_a \psi \implies \text{set } (\text{map } \text{unmark } MLs) \models_p \psi$

**unfolding** *true-annot-def* *true-clss-cls-def* *true-cls-def*

**by** (*auto* *dest*: *true-clss-singleton-lit-of-implies-incl*)

**lemma** *true-annots-true-clss-cls*:

$MLs \models_{as} \psi \implies \text{set } (\text{map } \text{unmark } MLs) \models_{ps} \psi$

**by** (*auto*

*dest*: *true-clss-singleton-lit-of-implies-incl*

*simp* *add*: *true-clss-def* *true-annots-def* *true-annot-def* *lits-of-def* *true-cls-def* *true-clss-clss-def*)

**lemma** *true-annots-marked-true-cls*[*iff*]:

$\text{map } (\lambda M. \text{Marked } M \ a) \ M \models_{as} N \longleftrightarrow \text{set } M \models_s N$

**proof** –

**have** \*: *lit-of* ' ( $\lambda M. \text{Marked } M \ a$ ) ' *set*  $M = \text{set } M$  **unfolding** *lits-of-def* **by** *force*  
**show** ?thesis **by** (*simp add: true-annots-true-cls \* lits-of-def*)  
**qed**

**lemma** *true-annot-singleton[iff]*:  $M \models_a \{\#L\# \} \longleftrightarrow L \in \text{lits-of-}l \ M$   
**unfolding** *true-annot-def lits-of-def* **by** *auto*

**lemma** *true-annots-true-clss-clss*:  
 $A \models_{as} \Psi \implies \text{unmark-}l \ A \models_{ps} \Psi$   
**unfolding** *true-clss-clss-def true-annots-def true-clss-def*  
**by** (*auto*  
*dest!: true-clss-singleton-lit-of-implies-incl*  
*simp add: lits-of-def true-annot-def true-cls-def*)

**lemma** *true-annot-commute*:  
 $M @ M' \models_a D \longleftrightarrow M' @ M \models_a D$   
**unfolding** *true-annot-def* **by** (*simp add: Un-commute*)

**lemma** *true-annots-commute*:  
 $M @ M' \models_{as} D \longleftrightarrow M' @ M \models_{as} D$   
**unfolding** *true-annots-def* **by** (*auto simp add: true-annot-commute*)

**lemma** *true-annot-mono[dest]*:  
 $\text{set } I \subseteq \text{set } I' \implies I \models_a N \implies I' \models_a N$   
**using** *true-cls-mono-set-mset-l* **unfolding** *true-annot-def lits-of-def*  
**by** (*metis (no-types) Un-commute Un-upper1 image-Un sup.orderE*)

**lemma** *true-annots-mono*:  
 $\text{set } I \subseteq \text{set } I' \implies I \models_{as} N \implies I' \models_{as} N$   
**unfolding** *true-annots-def* **by** *auto*

### 14.1.3 Defined and undefined literals

**definition** *defined-lit* :: ('a, 'l, 'm) *marked-lit list*  $\Rightarrow$  'a *literal*  $\Rightarrow$  bool  
**where**  
 $\text{defined-lit } I \ L \longleftrightarrow (\exists l. \text{Marked } L \ l \in \text{set } I) \vee (\exists P. \text{Propagated } L \ P \in \text{set } I)$   
 $\vee (\exists l. \text{Marked } (-L) \ l \in \text{set } I) \vee (\exists P. \text{Propagated } (-L) \ P \in \text{set } I)$

**abbreviation** *undefined-lit* :: ('a, 'l, 'm) *marked-lit list*  $\Rightarrow$  'a *literal*  $\Rightarrow$  bool  
**where**  $\text{undefined-lit } I \ L \equiv \neg \text{defined-lit } I \ L$

**lemma** *defined-lit-rev[simp]*:  
 $\text{defined-lit } (\text{rev } M) \ L \longleftrightarrow \text{defined-lit } M \ L$   
**unfolding** *defined-lit-def* **by** *auto*

**lemma** *atm-imp-marked-or-proped*:  
**assumes**  $x \in \text{set } I$   
**shows**  
 $(\exists l. \text{Marked } (- \text{lit-of } x) \ l \in \text{set } I)$   
 $\vee (\exists l. \text{Marked } (\text{lit-of } x) \ l \in \text{set } I)$   
 $\vee (\exists l. \text{Propagated } (- \text{lit-of } x) \ l \in \text{set } I)$   
 $\vee (\exists l. \text{Propagated } (\text{lit-of } x) \ l \in \text{set } I)$   
**using** *assms marked-lit.exhaust-sel* **by** *metis*

**lemma** *literal-is-lit-of-marked*:  
**assumes**  $L = \text{lit-of } x$

**shows**  $(\exists l. x = \text{Marked } L \ l) \vee (\exists l'. x = \text{Propagated } L \ l')$   
**using** *assms* **by** (*cases* *x*) *auto*

**lemma** *true-annot-iff-marked-or-true-lit*:  
 $\text{defined-lit } I \ L \longleftrightarrow ((\text{lits-of-l } I) \models L \vee (\text{lits-of-l } I) \models \neg L)$   
**unfolding** *defined-lit-def* **by** (*auto simp add: lits-of-def rev-image-eqI*  
*dest!: literal-is-lit-of-marked*)

**lemma** *consistent-interp*  $(\text{lits-of-l } I) \Longrightarrow I \models_{as} N \Longrightarrow \text{satisfiable } N$   
**by** (*simp add: true-annots-true-cl*)

**lemma** *defined-lit-map*:  
 $\text{defined-lit } Ls \ L \longleftrightarrow \text{atm-of } L \in (\lambda l. \text{atm-of } (\text{lit-of } l)) \text{ 'set } Ls$   
**unfolding** *defined-lit-def* **apply** (*rule iffI*)  
**using** *image-iff* **apply** *fastforce*  
**by** (*fastforce simp add: atm-of-eq-atm-of dest: atm-imp-marked-or-proped*)

**lemma** *defined-lit-uminus[iff]*:  
 $\text{defined-lit } I \ (\neg L) \longleftrightarrow \text{defined-lit } I \ L$   
**unfolding** *defined-lit-def* **by** *auto*

**lemma** *Marked-Propagated-in-iff-in-lits-of-l*:  
 $\text{defined-lit } I \ L \longleftrightarrow (L \in \text{lits-of-l } I \vee \neg L \in \text{lits-of-l } I)$   
**unfolding** *lits-of-def defined-lit-def*  
**by** (*auto simp: rev-image-eqI*) (*rename-tac x, case-tac x, auto*)**+**

**lemma** *consistent-add-undefined-lit-consistent[simp]*:  
**assumes**  
 $\text{consistent-interp } (\text{lits-of-l } Ls) \text{ and }$   
 $\text{undefined-lit } Ls \ L$   
**shows**  $\text{consistent-interp } (\text{insert } L \ (\text{lits-of-l } Ls))$   
**using** *assms* **unfolding** *consistent-interp-def* **by** (*auto simp: Marked-Propagated-in-iff-in-lits-of-l*)

**lemma** *decided-empty[simp]*:  
 $\neg \text{defined-lit } [] \ L$   
**unfolding** *defined-lit-def* **by** *simp*

## 14.2 Backtracking

**fun** *backtrack-split* ::  $(v, l, m) \text{ marked-lits}$   
 $\Rightarrow (v, l, m) \text{ marked-lits} \times (v, l, m) \text{ marked-lits}$  **where**  
 $\text{backtrack-split } [] = ([], []) \mid$   
 $\text{backtrack-split } (\text{Propagated } L \ P \ \# \ mlits) = \text{apfst } ((op \ \#) \ (\text{Propagated } L \ P)) \ (\text{backtrack-split } mlits) \mid$   
 $\text{backtrack-split } (\text{Marked } L \ l \ \# \ mlits) = ([], \text{Marked } L \ l \ \# \ mlits)$

**lemma** *backtrack-split-fst-not-marked*:  $a \in \text{set } (\text{fst } (\text{backtrack-split } l)) \Longrightarrow \neg \text{is-marked } a$   
**by** (*induct l rule: marked-lit-list-induct*) *auto*

**lemma** *backtrack-split-snd-hd-marked*:  
 $\text{snd } (\text{backtrack-split } l) \neq [] \Longrightarrow \text{is-marked } (\text{hd } (\text{snd } (\text{backtrack-split } l)))$   
**by** (*induct l rule: marked-lit-list-induct*) *auto*

**lemma** *backtrack-split-list-eq[simp]*:  
 $\text{fst } (\text{backtrack-split } l) \ @ \ (\text{snd } (\text{backtrack-split } l)) = l$   
**by** (*induct l rule: marked-lit-list-induct*) *auto*

**lemma** *backtrack-snd-empty-not-marked*:

*backtrack-split*  $M = (M'', []) \implies \forall l \in \text{set } M. \neg \text{is-marked } l$

**by** (*metis* *append-Nil2* *backtrack-split-fst-not-marked* *backtrack-split-list-eq* *snd-conv*)

**lemma** *backtrack-split-some-is-marked-then-snd-has-hd*:

$\exists l \in \text{set } M. \text{is-marked } l \implies \exists M' L' M''. \text{backtrack-split } M = (M'', L' \# M')$

**by** (*metis* *backtrack-snd-empty-not-marked* *list.exhaust* *prod.collapse*)

Another characterisation of the result of *backtrack-split*. This view allows some simpler proofs, since *takeWhile* and *dropWhile* are highly automated:

**lemma** *backtrack-split-takeWhile-dropWhile*:

*backtrack-split*  $M = (\text{takeWhile } (\text{Not } o \text{ is-marked}) M, \text{dropWhile } (\text{Not } o \text{ is-marked}) M)$

**proof** (*induct*  $M$ )

**case** *Nil* **show** ?*case* **by** *simp*

**next**

**case** (*Cons*  $L M$ ) **then show** ?*case* **by** (*cases*  $L$ ) *auto*

**qed**

### 14.3 Decomposition with respect to the marked literals

The pattern *get-all-marked-decomposition*  $[] = [([], [])]$  is necessary otherwise, we can call the *hd* function in the other pattern.

**fun** *get-all-marked-decomposition* :: ('a, 'l, 'm) *marked-lits*

$\Rightarrow ((('a, 'l, 'm) \text{marked-lits} \times ('a, 'l, 'm) \text{marked-lits}) \text{list}) \text{ where}$

*get-all-marked-decomposition* (*Marked*  $L l \# Ls$ ) =

(*Marked*  $L l \# Ls, []$ )  $\#$  *get-all-marked-decomposition*  $Ls$  |

*get-all-marked-decomposition* (*Propagated*  $L P \# Ls$ ) =

(*apsnd* ((*op*  $\#$ ) (*Propagated*  $L P$ )) (*hd* (*get-all-marked-decomposition*  $Ls$ )))

$\#$  *tl* (*get-all-marked-decomposition*  $Ls$ ) |

*get-all-marked-decomposition*  $[] = [([], [])]$

**value** *get-all-marked-decomposition* [*Propagated*  $A5 B5$ , *Marked*  $C4 D4$ , *Propagated*  $A3 B3$ ,  
*Propagated*  $A2 B2$ , *Marked*  $C1 D1$ , *Propagated*  $A0 B0$ ]

**lemma** *get-all-marked-decomposition-never-empty[iff]*:

*get-all-marked-decomposition*  $M = [] \longleftrightarrow \text{False}$

**by** (*induct*  $M$ , *simp*) (*rename-tac*  $a$  *xs*, *case-tac*  $a$ , *auto*)

**lemma** *get-all-marked-decomposition-never-empty-sym[iff]*:

$[] = \text{get-all-marked-decomposition } M \longleftrightarrow \text{False}$

**using** *get-all-marked-decomposition-never-empty[of M]* **by** *presburger*

**lemma** *get-all-marked-decomposition-decomp*:

*hd* (*get-all-marked-decomposition*  $S$ ) = ( $a, c$ )  $\implies S = c @ a$

**proof** (*induct*  $S$  *arbitrary: a c*)

**case** *Nil*

**then show** ?*case* **by** *simp*

**next**

**case** (*Cons*  $x A$ )

**then show** ?*case* **by** (*cases*  $x$ ; *cases* *hd* (*get-all-marked-decomposition*  $A$ )) *auto*

**qed**

**lemma** *get-all-marked-decomposition-backtrack-split*:

*backtrack-split*  $S = (M, M') \longleftrightarrow \text{hd } (\text{get-all-marked-decomposition } S) = (M', M)$

**proof** (*induction S arbitrary: M M'*)  
 case Nil  
 then show ?case by auto  
**next**  
 case (Cons a S)  
 then show ?case using backtrack-split-takeWhile-dropWhile by (cases a) force+  
**qed**

**lemma** *get-all-marked-decomposition-nil-backtrack-split-snd-nil:*  
*get-all-marked-decomposition S = [([], A)]  $\implies$  snd (backtrack-split S) = []*  
 by (simp add: get-all-marked-decomposition-backtrack-split sndI)

**lemma** *get-all-marked-decomposition-length-1-fst-empty-or-length-1:*  
 assumes *get-all-marked-decomposition M = (a, b) # []*  
 shows  $a = [] \vee (\text{length } a = 1 \wedge \text{is-marked } (\text{hd } a) \wedge \text{hd } a \in \text{set } M)$   
 using *assms*

**proof** (*induct M arbitrary: a b rule: marked-lit-list-induct*)  
 case nil then show ?case by simp  
**next**  
 case (marked L mark M)  
 then show ?case by simp  
**next**  
 case (proped L mark M)  
 then show ?case by (cases get-all-marked-decomposition M) force+  
**qed**

**lemma** *get-all-marked-decomposition-fst-empty-or-hd-in-M:*  
 assumes *get-all-marked-decomposition M = (a, b) # l*  
 shows  $a = [] \vee (\text{is-marked } (\text{hd } a) \wedge \text{hd } a \in \text{set } M)$   
 using *assms* apply (*induct M arbitrary: a b rule: marked-lit-list-induct*)  
 apply auto[2]  
 by (metis UnCI backtrack-split-snd-hd-marked get-all-marked-decomposition-backtrack-split  
 get-all-marked-decomposition-decomp hd-in-set list.sel(1) set-append snd-conv)

**lemma** *get-all-marked-decomposition-snd-not-marked:*  
 assumes  $(a, b) \in \text{set } (\text{get-all-marked-decomposition } M)$   
 and  $L \in \text{set } b$   
 shows  $\neg \text{is-marked } L$   
 using *assms* apply (*induct M arbitrary: a b rule: marked-lit-list-induct, simp*)  
 by (rename-tac L' l xs a b, case-tac get-all-marked-decomposition xs; fastforce)+

**lemma** *tl-get-all-marked-decomposition-skip-some:*  
 assumes  $x \in \text{set } (\text{tl } (\text{get-all-marked-decomposition } M1))$   
 shows  $x \in \text{set } (\text{tl } (\text{get-all-marked-decomposition } (M0 @ M1)))$   
 using *assms*  
 by (*induct M0 rule: marked-lit-list-induct*)  
 (auto simp add: list.set-sel(2))

**lemma** *hd-get-all-marked-decomposition-skip-some:*  
 assumes  $(x, y) = \text{hd } (\text{get-all-marked-decomposition } M1)$   
 shows  $(x, y) \in \text{set } (\text{get-all-marked-decomposition } (M0 @ \text{Marked } K \ i \ # \ M1))$   
 using *assms*  
**proof** (*induct M0*)  
 case Nil  
 then show ?case by auto

```

next
case (Cons L M0)
then have xy: (x, y) ∈ set (get-all-marked-decomposition (M0 @ Marked K i # M1)) by blast
show ?case
proof (cases L)
case (Marked l m)
then show ?thesis using xy by auto
next
case (Propagated l m)
then show ?thesis
using xy Cons.prem by
by (cases get-all-marked-decomposition (M0 @ Marked K i # M1))
(auto dest!: get-all-marked-decomposition-decomp
arg-cong[of get-all-marked-decomposition - - hd])
qed
qed

```

**lemma** *get-all-marked-decomposition-snd-union:*  
 $set\ M = \bigcup (set\ 'snd\ 'set\ (get-all-marked-decomposition\ M)) \cup \{L \mid L.\ is-marked\ L \wedge L \in set\ M\}$   
(is ?M M = ?U M ∪ ?Ls M)  
**proof** (induct M arbitrary:)  
case Nil  
then show ?case by simp  
next  
case (Cons L M)  
show ?case  
**proof** (cases L)  
case (Marked a l) **note** L = this  
then have L ∈ ?Ls (L#M) by auto  
**moreover** have ?U (L#M) = ?U M **unfolding** L by auto  
**moreover** have ?M M = ?U M ∪ ?Ls M **using** Cons.hyps **by** auto  
**ultimately** show ?thesis **by** auto  
next  
case (Propagated a P)  
then show ?thesis **using** Cons.hyps **by** (cases (get-all-marked-decomposition M)) auto  
qed  
qed

**lemma** *in-get-all-marked-decomposition-in-get-all-marked-decomposition-prepend:*  
 $(a, b) \in set\ (get-all-marked-decomposition\ M') \implies$   
 $\exists b'. (a, b' @ b) \in set\ (get-all-marked-decomposition\ (M @ M'))$   
**apply** (induction M rule: marked-lit-list-induct)  
**apply** (metis append-Nil)  
**apply** auto[]  
**by** (rename-tac L' m xs, case-tac get-all-marked-decomposition (xs @ M')) auto

**lemma** *get-all-marked-decomposition-remove-unmark-ssed-length:*  
**assumes**  $\forall l \in set\ M'. \neg is-marked\ l$   
**shows**  $length\ (get-all-marked-decomposition\ (M' @ M''))$   
 $= length\ (get-all-marked-decomposition\ M'')$   
**using** assms **by** (induct M' arbitrary: M'' rule: marked-lit-list-induct) auto

**lemma** *get-all-marked-decomposition-not-is-marked-length:*  
**assumes**  $\forall l \in set\ M'. \neg is-marked\ l$   
**shows**  $1 + length\ (get-all-marked-decomposition\ (Propagated\ (-L)\ P\ \# M))$

$= \text{length } (\text{get-all-marked-decomposition } (M' @ \text{Marked } L \ l \ # \ M))$   
**using** *assms* **get-all-marked-decomposition-remove-unmark-ssed-length** **by** *fastforce*

**lemma** *get-all-marked-decomposition-last-choice*:

**assumes**  $tl \ (\text{get-all-marked-decomposition } (M' @ \text{Marked } L \ l \ # \ M)) \neq []$   
**and**  $\forall l \in \text{set } M'. \neg \text{is-marked } l$   
**and**  $hd \ (tl \ (\text{get-all-marked-decomposition } (M' @ \text{Marked } L \ l \ # \ M))) = (M0', M0)$   
**shows**  $hd \ (\text{get-all-marked-decomposition } (\text{Propagated } (-L) \ P \ # \ M)) = (M0', \text{Propagated } (-L) \ P \ # \ M0)$   
**using** *assms* **by** (*induct*  $M'$  *rule*: *marked-lit-list-induct*) *auto*

**lemma** *get-all-marked-decomposition-except-last-choice-equal*:

**assumes**  $\forall l \in \text{set } M'. \neg \text{is-marked } l$   
**shows**  $tl \ (\text{get-all-marked-decomposition } (\text{Propagated } (-L) \ P \ # \ M))$   
 $= tl \ (tl \ (\text{get-all-marked-decomposition } (M' @ \text{Marked } L \ l \ # \ M)))$   
**using** *assms* **by** (*induct*  $M'$  *rule*: *marked-lit-list-induct*) *auto*

**lemma** *get-all-marked-decomposition-hd-hd*:

**assumes**  $\text{get-all-marked-decomposition } Ls = (M, C) \# (M0, M0') \# l$   
**shows**  $tl \ M = M0' @ M0 \wedge \text{is-marked } (hd \ M)$   
**using** *assms*

**proof** (*induct*  $Ls$  *arbitrary*:  $M \ C \ M0 \ M0' \ l$ )

**case** *Nil*

**then show** *?case* **by** *simp*

**next**

**case** (*Cons*  $a \ Ls \ M \ C \ M0 \ M0' \ l$ ) **note**  $IH = \text{this}(1)$  **and**  $g = \text{this}(2)$

**{** **fix**  $L \ \text{level}$

**assume**  $a: a = \text{Marked } L \ \text{level}$

**have**  $Ls = M0' @ M0$

**using**  $g \ a$  **by** (*force intro*: *get-all-marked-decomposition-decomp*)

**then have**  $tl \ M = M0' @ M0 \wedge \text{is-marked } (hd \ M)$  **using**  $g \ a$  **by** *auto*

**}**

**moreover** **{**

**fix**  $L \ P$

**assume**  $a: a = \text{Propagated } L \ P$

**have**  $tl \ M = M0' @ M0 \wedge \text{is-marked } (hd \ M)$

**using**  $IH \ \text{Cons.premis}$  **unfolding**  $a$  **by** (*cases* *get-all-marked-decomposition*  $Ls$ ) *auto*

**}**

**ultimately show** *?case* **by** (*cases*  $a$ ) *auto*

**qed**

**lemma** *get-all-marked-decomposition-exists-prepend[dest]*:

**assumes**  $(a, b) \in \text{set } (\text{get-all-marked-decomposition } M)$

**shows**  $\exists c. M = c @ b @ a$

**using** *assms* **apply** (*induct*  $M$  *rule*: *marked-lit-list-induct*)

**apply** *simp*

**by** (*rename-tac*  $L' \ m \ xs$ , *case-tac* *get-all-marked-decomposition*  $xs$ ;

*auto* *dest*!: *arg-cong*[*of* *get-all-marked-decomposition* - - *hd*]

*get-all-marked-decomposition-decomp*) +

**lemma** *get-all-marked-decomposition-incl*:

**assumes**  $(a, b) \in \text{set } (\text{get-all-marked-decomposition } M)$

**shows**  $\text{set } b \subseteq \text{set } M$  **and**  $\text{set } a \subseteq \text{set } M$

**using** *assms* *get-all-marked-decomposition-exists-prepend* **by** *fastforce* +

**lemma** *get-all-marked-decomposition-exists-prepend'*:  
**assumes**  $(a, b) \in \text{set } (\text{get-all-marked-decomposition } M)$   
**obtains**  $c$  **where**  $M = c @ b @ a$   
**using** *assms* **apply** (*induct*  $M$  *rule*: *marked-lit-list-induct*)  
**apply** *auto*[1]  
**by** (*rename-tac*  $L' m xs$ , *case-tac* *hd* (*get-all-marked-decomposition*  $xs$ ),  
*auto* *dest*!: *get-all-marked-decomposition-decomp simp add*: *list.set-sel*(2))+

**lemma** *union-in-get-all-marked-decomposition-is-subset*:  
**assumes**  $(a, b) \in \text{set } (\text{get-all-marked-decomposition } M)$   
**shows**  $\text{set } a \cup \text{set } b \subseteq \text{set } M$   
**using** *assms* **by** *force*

**lemma** *Marked-cons-in-get-all-marked-decomposition-append-Marked-cons*:  
 $\exists M1 M2. (\text{Marked } K i \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (c @ \text{Marked } K i \# c'))$   
**apply** (*induction*  $c$  *rule*: *marked-lit-list-induct*)  
**apply** *auto*[2]  
**apply** (*rename-tac*  $L m xs$ ,  
*case-tac* *hd* (*get-all-marked-decomposition* ( $xs @ \text{Marked } K i \# c'$ )))  
**apply** (*case-tac* *get-all-marked-decomposition* ( $xs @ \text{Marked } K i \# c'$ ))  
**by** *auto*

**definition** *all-decomposition-implies* :: '*a* literal multiset set  
 $\Rightarrow ((\text{'a, 'l, 'm}) \text{ marked-lit list} \times (\text{'a, 'l, 'm}) \text{ marked-lit list}) \text{ list} \Rightarrow \text{bool})$  **where**  
*all-decomposition-implies*  $N S$   
 $\longleftrightarrow (\forall (Ls, \text{seen}) \in \text{set } S. \text{unmark-l } Ls \cup N \models_{ps} \text{unmark-l } \text{seen})$

**lemma** *all-decomposition-implies-empty*[*iff*]:  
*all-decomposition-implies*  $N []$  **unfolding** *all-decomposition-implies-def* **by** *auto*

**lemma** *all-decomposition-implies-single*[*iff*]:  
*all-decomposition-implies*  $N [(Ls, \text{seen})]$   
 $\longleftrightarrow \text{unmark-l } Ls \cup N \models_{ps} \text{unmark-l } \text{seen}$   
**unfolding** *all-decomposition-implies-def* **by** *auto*

**lemma** *all-decomposition-implies-append*[*iff*]:  
*all-decomposition-implies*  $N (S @ S')$   
 $\longleftrightarrow (\text{all-decomposition-implies } N S \wedge \text{all-decomposition-implies } N S')$   
**unfolding** *all-decomposition-implies-def* **by** *auto*

**lemma** *all-decomposition-implies-cons-pair*[*iff*]:  
*all-decomposition-implies*  $N ((Ls, \text{seen}) \# S')$   
 $\longleftrightarrow (\text{all-decomposition-implies } N [(Ls, \text{seen})] \wedge \text{all-decomposition-implies } N S')$   
**unfolding** *all-decomposition-implies-def* **by** *auto*

**lemma** *all-decomposition-implies-cons-single*[*iff*]:  
*all-decomposition-implies*  $N (l \# S') \longleftrightarrow$   
 $(\text{unmark-l } (\text{fst } l) \cup N \models_{ps} \text{unmark-l } (\text{snd } l) \wedge$   
*all-decomposition-implies*  $N S')$   
**unfolding** *all-decomposition-implies-def* **by** *auto*

**lemma** *all-decomposition-implies-trail-is-implied*:  
**assumes** *all-decomposition-implies*  $N (\text{get-all-marked-decomposition } M)$   
**shows**  $N \cup \{\text{unmark } L \mid L. \text{is-marked } L \wedge L \in \text{set } M\}$   
 $\models_{ps} \text{unmark } ' \bigcup (\text{set } ' \text{snd } ' \text{set } (\text{get-all-marked-decomposition } M))$



```

using assms
proof (induct length (get-all-marked-decomposition M) arbitrary: M)
  case 0
  then show ?case by auto
next
case (Suc n) note IH = this(1) and length = this(2) and decomp = this(3)
consider
  (le1) length (get-all-marked-decomposition M) ≤ 1
  | (gt1) length (get-all-marked-decomposition M) > 1
  by arith
then show ?case
proof cases
  case le1
  then obtain a b where g: get-all-marked-decomposition M = (a, b) # []
    by (cases get-all-marked-decomposition M) auto
  moreover {
    assume a = []
    then have ?thesis using Suc.prem1 g by auto
  }
  moreover {
    assume l: length a = 1 and m: is-marked (hd a) and hd: hd a ∈ set M
    then have unmark (hd a) ∈ {unmark L | L. is-marked L ∧ L ∈ set M} by auto
    then have H: unmark-l a ∪ N ⊆ N ∪ {unmark L | L. is-marked L ∧ L ∈ set M}
      using l by (cases a) auto
    have f1: unmark-l a ∪ N ⊢ps unmark-l b
      using decomp unfolding all-decomposition-implies-def g by simp
    have ?thesis
      apply (rule true-clss-clss-subset) using f1 H g by auto
  }
ultimately show ?thesis
  using get-all-marked-decomposition-length-1-fst-empty-or-length-1 by blast
next
case gt1
then obtain Ls0 seen0 M' where
  Ls0: get-all-marked-decomposition M = (Ls0, seen0) # get-all-marked-decomposition M' and
  length': length (get-all-marked-decomposition M') = n and
  M'-in-M: set M' ⊆ set M
  using length by (induct M rule: marked-lit-list-induct) (auto simp: subset-insertI2)
let ?d = ⋃ (set 'snd ' set (get-all-marked-decomposition M'))
let ?unM = {unmark L | L. is-marked L ∧ L ∈ set M}
let ?unM' = {unmark L | L. is-marked L ∧ L ∈ set M'}
{
  assume n = 0
  then have get-all-marked-decomposition M' = [] using length' by auto
  then have ?thesis using Suc.prem1 unfolding all-decomposition-implies-def Ls0 by auto
}
moreover {
  assume n: n > 0
  then obtain Ls1 seen1 l where
    Ls1: get-all-marked-decomposition M' = (Ls1, seen1) # l
    using length' by (induct M' rule: marked-lit-list-induct) auto

  have all-decomposition-implies N (get-all-marked-decomposition M')
    using decomp unfolding Ls0 by auto
  then have N: N ∪ ?unM' ⊢ps unmark-s ?d

```

```

    using IH length' by auto
  have l:  $N \cup ?unM' \subseteq N \cup ?unM$ 
    using M'-in-M by auto
  from true-clss-clss-subset[OF this N]
  have  $\Psi N: N \cup ?unM \models_{ps} unmark-s \ ?d$  by auto
  have is-marked (hd Ls0) and LS:  $tl \ Ls0 = seen1 \ @ \ Ls1$ 
    using get-all-marked-decomposition-hd-hd[of M] unfolding Ls0 Ls1 by auto

  have LSM:  $seen1 \ @ \ Ls1 = M'$  using get-all-marked-decomposition-decomp[of M'] Ls1 by auto
  have M':  $set \ M' = ?d \cup \{L \mid L. is-marked \ L \wedge L \in set \ M'\}$ 
    using get-all-marked-decomposition-snd-union by auto

  {
    assume Ls0  $\neq []$ 
    then have hd Ls0  $\in set \ M$ 
      using get-all-marked-decomposition-fst-empty-or-hd-in-M Ls0 by blast
    then have  $N \cup ?unM \models_p unmark \ (hd \ Ls0)$ 
      using  $\langle is-marked \ (hd \ Ls0) \rangle$  by (metis (mono-tags, lifting) UnCI mem-Collect-eq
        true-clss-clss-in)
  } note hd-Ls0 = this

  have l:  $unmark \ ' \ (?d \cup \{L \mid L. is-marked \ L \wedge L \in set \ M'\}) = unmark-s \ ?d \cup ?unM'$ 
    by auto
  have  $N \cup ?unM' \models_{ps} unmark \ ' \ (?d \cup \{L \mid L. is-marked \ L \wedge L \in set \ M'\})$ 
    unfolding l using N by (auto simp: all-in-true-clss-clss)
  then have t:  $N \cup ?unM' \models_{ps} unmark-l \ (tl \ Ls0)$ 
    using M' unfolding LS LSM by auto
  then have  $N \cup ?unM \models_{ps} unmark-l \ (tl \ Ls0)$ 
    using M'-in-M true-clss-clss-subset[OF - t, of  $N \cup ?unM$ ] by auto
  then have  $N \cup ?unM \models_{ps} unmark-l \ Ls0$ 
    using hd-Ls0 by (cases Ls0) auto

  moreover have  $unmark-l \ Ls0 \cup N \models_{ps} unmark-l \ seen0$ 
    using decomp unfolding Ls0 by simp
  moreover have  $\bigwedge M \ Ma. (M::'a \ literal \ multiset \ set) \cup Ma \models_{ps} M$ 
    by (simp add: all-in-true-clss-clss)
  ultimately have  $\Psi: N \cup ?unM \models_{ps} unmark-l \ seen0$ 
    by (meson true-clss-clss-left-right true-clss-clss-union-and true-clss-clss-union-l-r)

  moreover have  $unmark \ ' \ (set \ seen0 \cup ?d) = unmark-l \ seen0 \cup unmark-s \ ?d$ 
    by auto
  ultimately have ?thesis using  $\Psi N$  unfolding Ls0 by simp
}
ultimately show ?thesis by auto
qed
qed

lemma all-decomposition-implies-propagated-lits-are-implied:
  assumes all-decomposition-implies N (get-all-marked-decomposition M)
  shows  $N \cup \{unmark \ L \mid L. is-marked \ L \wedge L \in set \ M\} \models_{ps} unmark-l \ M$ 
    (is ?I  $\models_{ps} ?A$ )
proof -
  have ?I  $\models_{ps} unmark-s \ \{L \mid L. is-marked \ L \wedge L \in set \ M\}$ 
    by (auto intro: all-in-true-clss-clss)
  moreover have ?I  $\models_{ps} unmark \ ' \ \bigcup (set \ ' \ snd \ ' \ set \ (get-all-marked-decomposition \ M))$ 

```

**using** *all-decomposition-implies-trail-is-IMPLIED* *assms* **by** *blast*  
**ultimately have**  $N \cup \{\text{unmark } m \mid m. \text{is-marked } m \wedge m \in \text{set } M\}$   
 $\models_{ps} \text{unmark } ' \bigcup (\text{set } ' \text{snd } ' \text{set } (\text{get-all-marked-decomposition } M))$   
 $\cup \text{unmark } ' \{m \mid m. \text{is-marked } m \wedge m \in \text{set } M\}$   
**by** *blast*  
**then show** *?thesis*  
**by** (*metis* (*no-types*) *get-all-marked-decomposition-snd-union*[*of M*] *image-Un*)  
**qed**

**lemma** *all-decomposition-implies-insert-single*:  
*all-decomposition-implies*  $N \ M \implies \text{all-decomposition-implies } (\text{insert } C \ N) \ M$   
**unfolding** *all-decomposition-implies-def* **by** *auto*

## 14.4 Negation of Clauses

**definition**  $CNot :: 'v \text{ clause} \Rightarrow 'v \text{ clauses}$  **where**  
 $CNot \ \psi = \{ \{ \# - L \# \} \mid L. \ L \in \# \ \psi \}$

**lemma** *in-CNot-uminus*[*iff*]:  
**shows**  $\{ \# L \# \} \in CNot \ \psi \longleftrightarrow -L \in \# \ \psi$   
**unfolding** *CNot-def* **by** *force*

**lemma**  
**shows**  
*CNot-singleton*[*simp*]:  $CNot \ \{ \# L \# \} = \{ \{ \# - L \# \} \}$  **and**  
*CNot-empty*[*simp*]:  $CNot \ \{ \# \} = \{ \}$  **and**  
*CNot-plus*[*simp*]:  $CNot \ (A + B) = CNot \ A \cup CNot \ B$   
**unfolding** *CNot-def* **by** *auto*

**lemma** *CNot-eq-empty*[*iff*]:  
 $CNot \ D = \{ \} \longleftrightarrow D = \{ \# \}$   
**unfolding** *CNot-def* **by** (*auto simp add: multiset-eqI*)

**lemma** *in-CNot-implies-uminus*:  
**assumes**  $L \in \# \ D$  **and**  $M \models_{as} CNot \ D$   
**shows**  $M \models_a \{ \# - L \# \}$  **and**  $-L \in \text{lits-of-l } M$   
**using** *assms* **by** (*auto simp: true-annot-def true-annot-def CNot-def*)

**lemma** *CNot-remdups-mset*[*simp*]:  
 $CNot \ (\text{remdups-mset } A) = CNot \ A$   
**unfolding** *CNot-def* **by** *auto*

**lemma** *Ball-CNot-Ball-mset*[*simp*] :  
 $(\forall x \in CNot \ D. \ P \ x) \longleftrightarrow (\forall L \in \# \ D. \ P \ \{ \# - L \# \})$   
**unfolding** *CNot-def* **by** *auto*

**lemma** *consistent-CNot-not*:  
**assumes** *consistent-interp I*  
**shows**  $I \models_s CNot \ \varphi \implies \neg I \models \varphi$   
**using** *assms* **unfolding** *consistent-interp-def true-clss-def true-clss-def* **by** *auto*

**lemma** *total-not-true-clss-true-clss-CNot*:  
**assumes** *total-over-m I*  $\{ \varphi \}$  **and**  $\neg I \models \varphi$   
**shows**  $I \models_s CNot \ \varphi$   
**using** *assms* **unfolding** *total-over-m-def total-over-set-def true-clss-def true-clss-def CNot-def*  
**apply** *clarify*

by (rename-tac  $x$   $L$ , case-tac  $L$ ) (force intro: pos-lit-in-atms-of neg-lit-in-atms-of)+

**lemma** *total-not-CNot*:

assumes *total-over-m*  $I \{ \varphi \}$  and  $\neg I \models_s CNot \varphi$   
 shows  $I \models \varphi$   
 using *assms total-not-true-clss-true-clss-CNot* by auto

**lemma** *atms-of-ms-CNot-atms-of[simp]*:

*atms-of-ms* ( $CNot C$ ) = *atms-of*  $C$   
 unfolding *atms-of-ms-def atms-of-def CNot-def* by fastforce

**lemma** *true-clss-clss-contradiction-true-clss-clss-false*:

$C \in D \implies D \models_{ps} CNot C \implies D \models_p \{ \# \}$   
 unfolding *true-clss-clss-def true-clss-clss-def total-over-m-def*  
 by (metis *Un-commute atms-of-empty atms-of-ms-CNot-atms-of atms-of-ms-insert atms-of-ms-union consistent-CNot-not insert-absorb sup-bot.left-neutral true-clss-def*)

**lemma** *true-annots-CNot-all-atms-defined*:

assumes  $M \models_{as} CNot T$  and  $a1: L \in \# T$   
 shows *atm-of*  $L \in \text{atm-of } \text{'lits-of-l } M$   
 by (metis *assms atm-of-uminus image-eqI in-CNot-implies-uminus(1) true-annot-singleton*)

**lemma** *true-annots-CNot-all-uminus-atms-defined*:

assumes  $M \models_{as} CNot T$  and  $a1: -L \in \# T$   
 shows *atm-of*  $L \in \text{atm-of } \text{'lits-of-l } M$   
 by (metis *assms atm-of-uminus image-eqI in-CNot-implies-uminus(1) true-annot-singleton*)

**lemma** *true-clss-clss-false-left-right*:

assumes  $\{ \{ \#L\# \} \} \cup B \models_p \{ \# \}$   
 shows  $B \models_{ps} CNot \{ \#L\# \}$   
 unfolding *true-clss-clss-def true-clss-clss-def*

**proof** (intro *allI impI*)

fix  $I$

assume

*tot*: *total-over-m*  $I (B \cup CNot \{ \#L\# \})$  and

*cons*: *consistent-interp*  $I$  and

$I: I \models_s B$

have *total-over-m*  $I (\{ \{ \#L\# \} \} \cup B)$  using *tot* by auto

then have  $\neg I \models_s \text{insert } \{ \#L\# \} B$

using *assms cons* unfolding *true-clss-clss-def* by *simp*

then show  $I \models_s CNot \{ \#L\# \}$

using *tot I* by (cases  $L$ ) auto

qed

**lemma** *true-annots-true-clss-def-iff-negation-in-model*:

$M \models_{as} CNot C \longleftrightarrow (\forall L \in \# C. -L \in \text{lits-of-l } M)$   
 unfolding *CNot-def true-annots-true-clss-def true-clss-def* by auto

**lemma** *true-annot-CNot-diff*:

$I \models_{as} CNot C \implies I \models_{as} CNot (C - C')$

by (auto *simp*: *true-annots-true-clss-def-iff-negation-in-model dest: in-diffD*)

**lemma** *consistent-CNot-not-tautology*:

*consistent-interp*  $M \implies M \models_s CNot D \implies \neg \text{tautology } D$

**by** (*metis* *atms-of-ms-CNot-atms-of-consistent-CNot-not-satisfiable-carac'* *satisfiable-def*  
*tautology-def* *total-over-m-def*)

**lemma** *atms-of-ms-CNot-atms-of-ms*: *atms-of-ms* (*CNot* *CC*) = *atms-of-ms* {*CC*}  
**by** *simp*

**lemma** *total-over-m-CNot-toal-over-m*[*simp*]:  
*total-over-m* *I* (*CNot* *C*) = *total-over-set* *I* (*atms-of* *C*)  
**unfolding** *total-over-m-def* *total-over-set-def* **by** *auto*

The following lemma is very useful when in the goal appears an axioms like  $-L = K$ : this lemma allows the simplifier to rewrite L.

**lemma** *uminus-lit-swap*:  $-(a::'a \text{ literal}) = i \longleftrightarrow a = -i$   
**by** *auto*

**lemma** *true-clss-clss-plus-CNot*:  
**assumes** *CC-L*:  $A \models_p CC + \{\#L\# \}$   
**and** *CNot-CC*:  $A \models_{ps} CNot \ CC$   
**shows**  $A \models_p \{\#L\# \}$   
**unfolding** *true-clss-clss-def* *true-clss-clss-def* *CNot-def* *total-over-m-def*  
**proof** (*intro* *allI* *impI*)  
**fix** *I*  
**assume**  
*tot*: *total-over-set* *I* (*atms-of-ms* ( $A \cup \{\{\#L\#\}\}$ )) **and**  
*cons*: *consistent-interp* *I* **and**  
*I*:  $I \models_s A$   
**let**  $?I = I \cup \{Pos \ P | P. P \in \text{atms-of } CC \wedge P \notin \text{atm-of } 'I\}$   
**have** *cons'*: *consistent-interp*  $?I$   
**using** *cons* **unfolding** *consistent-interp-def*  
**by** (*auto* *simp*: *uminus-lit-swap* *atms-of-def* *rev-image-eqI*)  
**have** *I'*:  $?I \models_s A$   
**using** *I* *true-clss-union-increase* **by** *blast*  
**have** *tot-CNot*: *total-over-m*  $?I$  ( $A \cup CNot \ CC$ )  
**using** *tot* *atms-of-s-def* **by** (*fastforce* *simp*: *total-over-m-def* *total-over-set-def*)

**then have** *tot-I-A-CC-L*: *total-over-m*  $?I$  ( $A \cup \{CC + \{\#L\#\}\}$ )  
**using** *tot* **unfolding** *total-over-m-def* *total-over-set-atm-of* **by** *auto*  
**then have**  $?I \models CC + \{\#L\# \}$  **using** *CC-L* *cons'* *I'* **unfolding** *true-clss-clss-def* **by** *blast*  
**moreover**  
**have**  $?I \models_s CNot \ CC$  **using** *CNot-CC* *cons'* *I'* *tot-CNot* **unfolding** *true-clss-clss-def* **by** *auto*  
**then have**  $\neg A \models_p CC$   
**by** (*metis* (*no-types*, *lifting*) *I'* *atms-of-ms-CNot-atms-of-ms* *atms-of-ms-union* *cons'*  
*consistent-CNot-not* *tot-CNot* *total-over-m-def* *true-clss-clss-def*)  
**then have**  $\neg ?I \models CC$  **using** ( $?I \models_s CNot \ CC$ ) *cons'* *consistent-CNot-not* **by** *blast*  
**ultimately have**  $?I \models \{\#L\# \}$  **by** *blast*  
**then show**  $I \models \{\#L\# \}$   
**by** (*metis* (*no-types*, *lifting*) *atms-of-ms-union* *cons'* *consistent-CNot-not* *tot* *total-not-CNot*  
*total-over-m-def* *total-over-set-union* *true-clss-union-increase*)

**qed**

**lemma** *true-annots-CNot-lit-of-notin-skip*:  
**assumes** *LM*:  $L \# M \models_{as} CNot \ A$  **and** *LA*: *lit-of* *L*  $\notin \# \ A$   $\neg$  *lit-of* *L*  $\notin \# \ A$   
**shows**  $M \models_{as} CNot \ A$   
**using** *LM* **unfolding** *true-annots-def* *Ball-def*  
**proof** (*intro* *allI* *impI*)

**fix**  $l$   
**assume**  $H: \forall x. x \in CNot\ A \longrightarrow L \# M \models_a x$  **and**  $l: l \in CNot\ A$   
**then have**  $L \# M \models_a l$  **by** *auto*  
**then show**  $M \models_a l$  **using**  $LA\ l$  **by** (*cases*  $L$ ) (*auto simp: CNot-def*)  
**qed**

**lemma** *true-clss-clss-union-false-true-clss-clss-cnot*:  
 $A \cup \{B\} \models_{ps} \{\{\#\}\} \longleftrightarrow A \models_{ps} CNot\ B$   
**using** *total-not-CNot consistent-CNot-not unfolding total-over-m-def true-clss-clss-def*  
**by** *fastforce*

**lemma** *true-annot-remove-hd-if-notin-vars*:  
**assumes**  $a \# M' \models_a D$  **and**  $atm-of\ (lit-of\ a) \notin atms-of\ D$   
**shows**  $M' \models_a D$   
**using** *assms true-clss-remove-hd-if-notin-vars unfolding true-annot-def* **by** *auto*

**lemma** *true-annot-remove-if-notin-vars*:  
**assumes**  $M @ M' \models_a D$  **and**  $\forall x \in atms-of\ D. x \notin atm-of\ ' lits-of-l\ M$   
**shows**  $M' \models_a D$   
**using** *assms apply (induct M, simp)*  
**using** *true-annot-remove-hd-if-notin-vars* **by** *force+*

**lemma** *true-annots-remove-if-notin-vars*:  
**assumes**  $M @ M' \models_{as} D$  **and**  $\forall x \in atms-of-ms\ D. x \notin atm-of\ ' lits-of-l\ M$   
**shows**  $M' \models_{as} D$  **unfolding** *true-annots-def*  
**using** *assms true-annot-remove-if-notin-vars[of M M']*  
**unfolding** *true-annots-def atms-of-ms-def* **by** *force*

**lemma** *all-variables-defined-not-imply-cnot*:  
**assumes**  
 $\forall s \in atms-of-ms\ \{B\}. s \in atm-of\ ' lits-of-l\ A$  **and**  
 $\neg A \models_a B$   
**shows**  $A \models_{as} CNot\ B$   
**unfolding** *true-annot-def true-annots-def Ball-def CNot-def true-lit-def*

**proof** (*clarify, rule ccontr*)  
**fix**  $L$   
**assume**  $LB: L \in \# B$  **and**  $\neg lits-of-l\ A \models_l -L$   
**then have**  $atm-of\ L \in atm-of\ ' lits-of-l\ A$   
**using** *assms(1) by (simp add: atm-of-lit-in-atms-of lits-of-def)*  
**then have**  $L \in lits-of-l\ A \vee -L \in lits-of-l\ A$   
**using** *atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set* **by** *metis*  
**then have**  $L \in lits-of-l\ A$  **using**  $\langle \neg lits-of-l\ A \models_l -L \rangle$  **by** *auto*  
**then show** *False*  
**using**  $LB$  *assms(2) unfolding true-annot-def true-lit-def true-clss-def Bex-def*  
**by** *blast*  
**qed**

**lemma** *CNot-union-mset[simp]*:  
 $CNot\ (A \# \cup B) = CNot\ A \cup CNot\ B$   
**unfolding** *CNot-def* **by** *auto*

## 14.5 Other

**abbreviation** *no-dup*  $L \equiv distinct\ (map\ (\lambda l. atm-of\ (lit-of\ l))\ L)$

**lemma** *no-dup-rev[simp]*:

*no-dup* (*rev M*)  $\longleftrightarrow$  *no-dup M*  
**by** (*auto simp: rev-map[symmetric]*)

**lemma** *no-dup-length-eq-card-atm-of-lits-of-l*:  
**assumes** *no-dup M*  
**shows** *length M = card (atm-of ‘ lits-of-l M)*  
**using** *assms unfolding lits-of-def by (induct M) (auto simp add: image-image)*

**lemma** *distinct-consistent-interp*:  
*no-dup M  $\implies$  consistent-interp (lits-of-l M)*

**proof** (*induct M*)

**case** *Nil*  
**show** *?case by auto*

**next**

**case** (*Cons L M*)  
**then have** *a1: consistent-interp (lits-of-l M) by auto*  
**have** *a2: atm-of (lit-of L)  $\notin$  ( $\lambda l.$  atm-of (lit-of l)) ‘ set M* **using** *Cons.prem by auto*  
**have** *undefined-lit M (lit-of L)*  
**using** *a2 image-iff unfolding defined-lit-def by fastforce*  
**then show** *?case*  
**using** *a1 by simp*

**qed**

**lemma** *distinct-get-all-marked-decomposition-no-dup*:  
**assumes** (*a, b*)  $\in$  *set (get-all-marked-decomposition M)*  
**and** *no-dup M*  
**shows** *no-dup (a @ b)*  
**using** *assms by force*

**lemma** *true-annots-lit-of-notin-skip*:

**assumes** *L # M  $\models_{as}$  CNot A*  
**and**  $\neg$ *lit-of L  $\notin$  # A*  
**and** *no-dup (L # M)*  
**shows** *M  $\models_{as}$  CNot A*

**proof** –

**have**  $\forall l \in \# A. \neg l \in \text{lits-of-l } (L \# M)$   
**using** *assms(1) in-CNot-implies-uminus(2) by blast*

**moreover**

**have** *atm-of (lit-of L)  $\notin$  atm-of ‘ lits-of-l M*  
**using** *assms(3) unfolding lits-of-def by force*  
**then have**  $\neg$  *lit-of L  $\notin$  lits-of-l M* **unfolding** *lits-of-def*  
**by** (*metis (no-types) atm-of-uminus imageI*)

**ultimately have**  $\forall l \in \# A. \neg l \in \text{lits-of-l } M$

**using** *assms(2) by (metis insert-iff list.simps(15) lits-of-insert uminus-of-uminus-id)*

**then show** *?thesis by (auto simp add: true-annots-def)*

**qed**

**abbreviation** *true-annots-mset* (**infix**  $\models_{asm}$  50) **where**  
*I  $\models_{asm} C \equiv I \models_{as} (\text{set-mset } C)$*

**abbreviation** *true-clss-clss-m:: 'v clause multiset  $\Rightarrow$  'v clause multiset  $\Rightarrow$  bool* (**infix**  $\models_{psm}$  50)  
**where**

*I  $\models_{psm} C \equiv \text{set-mset } I \models_{ps} (\text{set-mset } C)$*

Analog of  $\llbracket ?N \models_{ps} ?B; ?A \subseteq ?B \rrbracket \implies ?N \models_{ps} ?A$

**lemma** *true-clss-clssm-subsetE*:  $N \models_{psm} B \implies A \subseteq_{\#} B \implies N \models_{psm} A$   
**using** *set-mset-mono true-clss-clss-subsetE* **by** *blast*

**abbreviation** *true-clss-clss-m*:: 'a clause multiset  $\Rightarrow$  'a clause  $\Rightarrow$  bool (**infix**  $\models_{pm}$  50) **where**  
 $I \models_{pm} C \equiv \text{set-mset } I \models_p C$

**abbreviation** *distinct-mset-mset* :: 'a multiset multiset  $\Rightarrow$  bool **where**  
 $\text{distinct-mset-mset } \Sigma \equiv \text{distinct-mset-set } (\text{set-mset } \Sigma)$

**abbreviation** *all-decomposition-implies-m* **where**  
 $\text{all-decomposition-implies-m } A B \equiv \text{all-decomposition-implies } (\text{set-mset } A) B$

**abbreviation** *atms-of-mm* :: 'a literal multiset multiset  $\Rightarrow$  'a set **where**  
 $\text{atms-of-mm } U \equiv \text{atms-of-ms } (\text{set-mset } U)$

Other definition using *Union-mset*

**lemma**  $\text{atms-of-mm } U \equiv \text{set-mset } (\bigcup_{\#} \text{image-mset } (\text{image-mset } \text{atm-of}) U)$   
**unfolding** *atms-of-ms-def* **by** (*auto simp: atms-of-def*)

**abbreviation** *true-clss-m*:: 'a interp  $\Rightarrow$  'a clause multiset  $\Rightarrow$  bool (**infix**  $\models_{sm}$  50) **where**  
 $I \models_{sm} C \equiv I \models_s \text{set-mset } C$

**abbreviation** *true-clss-ext-m* (**infix**  $\models_{sextm}$  49) **where**  
 $I \models_{sextm} C \equiv I \models_{sext} \text{set-mset } C$

**end**

**theory** *CDCL-Abstract-Clause-Representation*

**imports** *Main Partial-Clausal-Logic*

**begin**

**type-synonym** 'v clause = 'v literal multiset

**type-synonym** 'v clauses = 'v clause multiset

## 14.6 Abstract Clause Representation

We will abstract the representation of clause and clauses via two locales. We expect our representation to behave like multiset, but the internal representation can be done using list or whatever other representation.

We assume the following:

- there is an equivalent to adding and removing a literal and to taking the union of clauses.

**locale** *raw-cls* =

**fixes**

$\text{mset-cls} :: 'cls \Rightarrow 'v \text{ clause}$  **and**

$\text{insert-cls} :: 'v \text{ literal} \Rightarrow 'cls \Rightarrow 'cls$  **and**

$\text{remove-lit} :: 'v \text{ literal} \Rightarrow 'cls \Rightarrow 'cls$

**assumes**

$\text{insert-cls}[\text{simp}]: \text{mset-cls } (\text{insert-cls } L C) = \text{mset-cls } C + \{\#L\# \}$  **and**

$\text{remove-lit}[\text{simp}]: \text{mset-cls } (\text{remove-lit } L C) = \text{remove1-mset } L (\text{mset-cls } C)$

**begin**

**end**

**locale** *raw-ccls-union* =



**fixes**

*mset-cls* :: 'cls  $\Rightarrow$  'v clause **and**  
*union-cls* :: 'cls  $\Rightarrow$  'cls  $\Rightarrow$  'cls **and**  
*insert-cls* :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls **and**  
*remove-lit* :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls

**assumes**

*insert-ccls[simp]*: *mset-cls* (*insert-cls* L C) = *mset-cls* C + {#L#} **and**  
*mset-ccls-union-cls[simp]*: *mset-cls* (*union-cls* C D) = *mset-cls* C # $\cup$  *mset-cls* D **and**  
*remove-clit[simp]*: *mset-cls* (*remove-lit* L C) = *remove1-mset* L (*mset-cls* C)

**begin**

**end**

Instantiation of the previous locale, in an unnamed context to avoid polluting with simp rules

**context**

**begin**

**interpretation** *list-cls*: *raw-cls mset*  
*op* # *remove1*  
**by** *unfold-locales* (*auto simp: union-mset-list ex-mset*)

**interpretation** *cls-cls*: *raw-cls id*  
 $\lambda L C. C + \{\#L\# \}$  *remove1-mset*  
**by** *unfold-locales* (*auto simp: union-mset-list*)

**interpretation** *list-cls*: *raw-ccls-union mset*  
*union-mset-list*  
*op* # *remove1*  
**by** *unfold-locales* (*auto simp: union-mset-list ex-mset*)

**interpretation** *cls-cls*: *raw-ccls-union id*  
*op* # $\cup$   $\lambda L C. C + \{\#L\# \}$  *remove1-mset*  
**by** *unfold-locales* (*auto simp: union-mset-list*)

**end**

Over the abstract clauses, we have the following properties:

- We can insert a clause
- We can take the union (used only in proofs for the definition of *clauses*)
- there is an operator indicating whether the abstract clause is contained or not
- if a concrete clause is contained the abstract clauses, then there is an abstract clause

**locale** *raw-clss* =

*raw-cls mset-cls insert-cls remove-lit*

**for**

*mset-cls* :: 'cls  $\Rightarrow$  'v clause **and**  
*insert-cls* :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls **and**  
*remove-lit* :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls +

**fixes**

*mset-clss* :: 'clss  $\Rightarrow$  'v clauses **and**  
*union-clss* :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss **and**  
*in-clss* :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool **and**  
*insert-clss* :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss **and**  
*remove-from-clss* :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss

```

assumes
  insert-clss[simp]: mset-clss (insert-clss L C) = mset-clss C + {#mset-clss L#} and
  union-clss[simp]: mset-clss (union-clss C D) = mset-clss C + mset-clss D and
  mset-clss-union-clss[simp]: mset-clss (insert-clss C' D) = {#mset-clss C'#} + mset-clss D and
  in-clss-mset-clss[dest]: in-clss a C  $\implies$  mset-clss a  $\in$  # mset-clss C and
  in-mset-clss-exists-preimage: b  $\in$  # mset-clss C  $\implies \exists b'. \text{in-clss } b' C \wedge \text{mset-clss } b' = b$  and
  remove-from-clss-mset-clss[simp]:
    mset-clss (remove-from-clss a C) = mset-clss C - {#mset-clss a#} and
  in-clss-union-clss[simp]:
    in-clss a (union-clss C D)  $\longleftrightarrow$  in-clss a C  $\vee$  in-clss a D
begin

end

experiment
begin
  fun remove-first where
    remove-first - [] = [] |
    remove-first C (C' # L) = (if mset C = mset C' then L else C' # remove-first C L)

  lemma mset-map-mset-remove-first:
    mset (map mset (remove-first a C)) = remove1-mset (mset a) (mset (map mset C))
    by (induction C) (auto simp: ac-simps remove1-mset-single-add)

  interpretation clss-clss: raw-clss id  $\lambda L C. C + \{\#L\# \}$  remove1-mset
    id op + op  $\in$  #  $\lambda L C. C + \{\#L\# \}$  remove1-mset
    by unfold-locales (auto simp: ac-simps)

  interpretation list-clss: raw-clss mset
    op # remove1  $\lambda L. \text{mset (map mset L) op @ } \lambda L C. L \in \text{set } C \text{ op } \#$ 
    remove-first
    by unfold-locales (auto simp: ac-simps union-mset-list mset-map-mset-remove-first ex-mset)
end

end
theory CDCL-WNOT-Measure
imports Main
begin

```

## 15 Measure

This measure show the termination of the core of CDCL: each step improves the number of literals we know for sure.

This measure can also be seen as the increasing lexicographic order: it is an order on bounded sequences, when each element is bounded. The proof involves a measure like the one defined here (the same?).

**definition**  $\mu_C :: \text{nat} \Rightarrow \text{nat} \Rightarrow \text{nat list} \Rightarrow \text{nat}$  **where**  
 $\mu_C s b M \equiv (\sum i=0..<\text{length } M. M!i * b^{\wedge}(s+i - \text{length } M))$

**lemma**  $\mu_C\text{-nil}$ [simp]:  
 $\mu_C s b [] = 0$   
**unfolding**  $\mu_C\text{-def}$  **by** auto

**lemma**  $\mu_C\text{-single}$ [simp]:

$$\mu_C \ s \ b \ [L] = L * b \wedge (s - \text{Suc } 0)$$

**unfolding**  $\mu_C$ -def **by** auto

**lemma** *set-sum-atLeastLessThan-add*:

$$(\sum i=k..<k+(b::nat). f \ i) = (\sum i=0..<b. f \ (k + i))$$

**by** (induction b) auto

**lemma** *set-sum-atLeastLessThan-Suc*:

$$(\sum i=1..<\text{Suc } j. f \ i) = (\sum i=0..<j. f \ (\text{Suc } i))$$

**using** *set-sum-atLeastLessThan-add*[of - 1 j] **by** force

**lemma**  $\mu_C$ -cons:

$$\mu_C \ s \ b \ (L \# M) = L * b \wedge (s - 1 - \text{length } M) + \mu_C \ s \ b \ M$$

**proof** –

$$\text{have } \mu_C \ s \ b \ (L \# M) = (\sum i=0..<\text{length } (L \# M). (L \# M)!i * b \wedge (s + i - \text{length } (L \# M)))$$

**unfolding**  $\mu_C$ -def **by** blast

$$\text{also have } \dots = (\sum i=0..<1. (L \# M)!i * b \wedge (s + i - \text{length } (L \# M))) \\ + (\sum i=1..<\text{length } (L \# M). (L \# M)!i * b \wedge (s + i - \text{length } (L \# M)))$$

**by** (rule *setsum-add-nat-ivl[symmetric]*) *simp-all*

$$\text{finally have } \mu_C \ s \ b \ (L \# M) = L * b \wedge (s - 1 - \text{length } M) \\ + (\sum i=1..<\text{length } (L \# M). (L \# M)!i * b \wedge (s + i - \text{length } (L \# M)))$$

**by** auto

**moreover** {

$$\text{have } (\sum i=1..<\text{length } (L \# M). (L \# M)!i * b \wedge (s + i - \text{length } (L \# M))) = \\ (\sum i=0..<\text{length } (M). (L \# M)!(\text{Suc } i) * b \wedge (s + (\text{Suc } i) - \text{length } (L \# M)))$$

**unfolding** *length-Cons* *set-sum-atLeastLessThan-Suc* **by** blast

$$\text{also have } \dots = (\sum i=0..<\text{length } (M). M!i * b \wedge (s + i - \text{length } M))$$

**by** auto

$$\text{finally have } (\sum i=1..<\text{length } (L \# M). (L \# M)!i * b \wedge (s + i - \text{length } (L \# M))) = \mu_C \ s \ b \ M$$

**unfolding**  $\mu_C$ -def .

}

**ultimately show** ?thesis **by** presburger

qed

**lemma**  $\mu_C$ -append:

**assumes**  $s \geq \text{length } (M @ M')$

**shows**  $\mu_C \ s \ b \ (M @ M') = \mu_C \ (s - \text{length } M') \ b \ M + \mu_C \ s \ b \ M'$

**proof** –

$$\text{have } \mu_C \ s \ b \ (M @ M') = (\sum i=0..<\text{length } (M @ M'). (M @ M')!i * b \wedge (s + i - \text{length } (M @ M')))$$

**unfolding**  $\mu_C$ -def **by** blast

$$\text{moreover then have } \dots = (\sum i=0..<\text{length } M. (M @ M')!i * b \wedge (s + i - \text{length } (M @ M'))) \\ + (\sum i=\text{length } M..<\text{length } (M @ M'). (M @ M')!i * b \wedge (s + i - \text{length } (M @ M')))$$

**by** (auto intro!: *setsum-add-nat-ivl[symmetric]*)

**moreover**

$$\text{have } \forall i \in \{0..<\text{length } M\}. (M @ M')!i * b \wedge (s + i - \text{length } (M @ M')) = M!i * b \wedge (s - \text{length } M' \\ + i - \text{length } M)$$

**using**  $\langle s \geq \text{length } (M @ M') \rangle$  **by** (auto *simp add: nth-append ac-simps*)

$$\text{then have } \mu_C \ (s - \text{length } M') \ b \ M = (\sum i=0..<\text{length } M. (M @ M')!i * b \wedge (s + i - \text{length } (M @ M')))$$

**unfolding**  $\mu_C$ -def **by** auto

$$\text{ultimately have } \mu_C \ s \ b \ (M @ M') = \mu_C \ (s - \text{length } M') \ b \ M$$

$$+ (\sum i=\text{length } M..<\text{length } (M @ M'). (M @ M')!i * b \wedge (s + i - \text{length } (M @ M')))$$

**by** auto

**moreover** {

$$\text{have } (\sum i=\text{length } M..<\text{length } (M @ M'). (M @ M')!i * b \wedge (s + i - \text{length } (M @ M'))) =$$

```

      (∑ i=0.. $\text{length } M'$ .  $M!i * b^\wedge (s + i - \text{length } M')$ )
    unfolding length-append set-sum-atLeastLessThan-add by auto
  then have (∑ i= $\text{length } M$ .. $\text{length } (M @ M')$ .  $(M @ M')!i * b^\wedge (s + i - \text{length } (M @ M'))$ ) =  $\mu_C s b$ 
  M'
    unfolding  $\mu_C$ -def .
  }
  ultimately show ?thesis by presburger
qed

```

```

lemma  $\mu_C$ -cons-non-empty-inf:
  assumes M-ge-1:  $\forall i \in \text{set } M. i \geq 1$  and M:  $M \neq []$ 
  shows  $\mu_C s b M \geq b^\wedge (s - \text{length } M)$ 
  using assms by (cases M) (auto simp: mult-eq-if  $\mu_C$ -cons)

```

Copy of `~/src/HOL/ex/NatSum.thy` (but generalized to  $0 \leq k$ )

```

lemma sum-of-powers:  $0 \leq k \implies (k - 1) * (\sum i=0.. $n$ .  $k^\wedge i$ ) =  $k^\wedge n - (1::\text{nat})$ 
  apply (cases k = 0)
  apply (cases n; simp)
  by (induct n) (auto simp: Nat.nat-distrib)$ 
```

In the degenerated cases, we only have the large inequality holds. In the other cases, the following strict inequality holds:

```

lemma  $\mu_C$ -bounded-non-degenerated:
  fixes b :: nat
  assumes
    b > 0 and
    M  $\neq []$  and
    M-le:  $\forall i < \text{length } M. M!i < b$  and
    s  $\geq \text{length } M$ 
  shows  $\mu_C s b M < b^\wedge s$ 
proof -
  consider (b1)  $b = 1$  | (b)  $b > 1$  using  $\langle b > 0 \rangle$  by (cases b) auto
  then show ?thesis
  proof cases
    case b1
    then have  $\forall i < \text{length } M. M!i = 0$  using M-le by auto
    then have  $\mu_C s b M = 0$  unfolding  $\mu_C$ -def by auto
    then show ?thesis using  $\langle b > 0 \rangle$  by auto
  next
    case b
    have  $\forall i \in \{0..<\text{length } M\}. M!i * b^\wedge (s + i - \text{length } M) \leq (b-1) * b^\wedge (s + i - \text{length } M)$ 
      using M-le  $\langle b > 1 \rangle$  by auto
    then have  $\mu_C s b M \leq (\sum i=0.. $\text{length } M$ .  $(b-1) * b^\wedge (s + i - \text{length } M)$ )$ 
      using  $\langle M \neq [] \rangle$   $\langle b > 0 \rangle$  unfolding  $\mu_C$ -def by (auto intro: setsum-mono)
    also
      have  $\forall i \in \{0..<\text{length } M\}. (b-1) * b^\wedge (s + i - \text{length } M) = (b-1) * b^\wedge i * b^\wedge (s - \text{length } M)$ 
        by (metis Nat.add-diff-assoc2 add.commute assms(4) mult.assoc power-add)
      then have  $(\sum i=0.. $\text{length } M$ .  $(b-1) * b^\wedge (s + i - \text{length } M)$ )$ 
        =  $(\sum i=0.. $\text{length } M$ .  $(b-1) * b^\wedge i * b^\wedge (s - \text{length } M)$ )$ 
        by (auto simp add: ac-simps)
      also have  $\dots = (\sum i=0.. $\text{length } M$ .  $b^\wedge i$ ) *  $b^\wedge (s - \text{length } M) * (b-1)$ 
        by (simp add: setsum-left-distrib setsum-right-distrib ac-simps)
      finally have  $\mu_C s b M \leq (\sum i=0.. $\text{length } M$ .  $b^\wedge i$ ) *  $(b-1) * b^\wedge (s - \text{length } M)$ 
        by (simp add: ac-simps)$$ 
```

```

also
  have  $(\sum_{i=0..<\text{length } M}. b^i) * (b-1) = b^{\text{length } M} - 1$ 
    using sum-of-powers[of b length M] <b>1>
    by (auto simp add: ac-simps)
  finally have  $\mu_C \ s \ b \ M \leq (b^{\text{length } M} - 1) * b^{\text{length } M}$ 
    by auto
  also have  $\dots < b^{\text{length } M} * b^{\text{length } M}$ 
    using <b>1> by auto
  also have  $\dots = b^s$ 
    by (metis assms(4) le-add-diff-inverse power-add)
  finally show ?thesis unfolding  $\mu_C$ -def by (auto simp add: ac-simps)
qed
qed

```

In the degenerate case  $b = (0::'a)$ , the list  $M$  is empty (since the list cannot contain any element).

```

lemma  $\mu_C$ -bounded:
  fixes  $b :: \text{nat}$ 
  assumes
     $M\text{-le}: \forall i < \text{length } M. M!i < b$  and
     $s \geq \text{length } M$ 
     $b > 0$ 
  shows  $\mu_C \ s \ b \ M < b^s$ 
proof -
  consider  $(M0) \ M = [] \mid (M) \ b > 0$  and  $M \neq []$ 
  using  $M\text{-le}$  by (cases b, cases M) auto
  then show ?thesis
  proof cases
    case  $M0$ 
    then show ?thesis using  $M\text{-le} \ \langle b > 0 \rangle$  by auto
  next
    case  $M$ 
    show ?thesis using  $\mu_C$ -bounded-non-degenerated[OF M assms(1,2)] by arith
  qed
qed

```

When  $b = 0$ , we cannot show that the measure is empty, since  $0^0 = 1$ .

```

lemma  $\mu_C$ -base-0:
  assumes  $\text{length } M \leq s$ 
  shows  $\mu_C \ s \ 0 \ M \leq M!0$ 
proof -
  {
    assume  $s = \text{length } M$ 
    moreover {
      fix  $n$ 
      have  $(\sum_{i=0..<n}. M!i * (0::\text{nat})^i) \leq M!0$ 
        apply (induction n rule: nat-induct)
        by simp (rename-tac n, case-tac n, auto)
    }
    ultimately have ?thesis unfolding  $\mu_C$ -def by auto
  }
  moreover
  {
    assume  $\text{length } M < s$ 
    then have  $\mu_C \ s \ 0 \ M = 0$  unfolding  $\mu_C$ -def by auto
  }

```

ultimately show *?thesis* using *assms* unfolding  $\mu_C$ -def by *linarith*  
qed

end

theory *CDCL-NOT*

imports *CDCL-Abstract-Clause-Representation List-More Wellfounded-More CDCL-WNOT-Measure*  
*Partial-Annotated-Clausal-Logic*

begin

## 16 NOT's CDCL

### 16.1 Auxiliary Lemmas and Measure

**lemma** *no-dup-cannot-not-lit-and-uminus*:

*no-dup*  $M \implies - \text{lit-of } xa = \text{lit-of } x \implies x \in \text{set } M \implies xa \notin \text{set } M$   
**by** (*metis atm-of-uminus distinct-map inj-on-eq-iff uminus-not-id'*)

**lemma** *atms-of-ms-single-atm-of[simp]*:

*atms-of-ms*  $\{\text{unmark } L \mid L. P L\} = \text{atm-of } ' \{ \text{lit-of } L \mid L. P L \}$   
**unfolding** *atms-of-ms-def* **by** *force*

**lemma** *atms-of-uminus-lit-atm-of-lit-of*:

*atms-of*  $\{\# - \text{lit-of } x. x \in \# A \# \} = \text{atm-of } ' (\text{lit-of } ' (\text{set-mset } A))$   
**unfolding** *atms-of-def* **by** (*auto simp add: Fun.image-comp*)

**lemma** *atms-of-ms-single-image-atm-of-lit-of*:

*atms-of-ms* (*unmark-s*  $A$ ) = *atm-of* ' (*lit-of* '  $A$ )  
**unfolding** *atms-of-ms-def* **by** *auto*

### 16.2 Initial definitions

#### 16.2.1 The state

We define here an abstraction over operation on the state we are manipulating.

**locale** *dp11-state-ops* =

*raw-clss* *mset-clss* *insert-clss* *remove-lit*  
*mset-clss* *union-clss* *in-clss* *insert-clss* *remove-from-clss*

**for**

*mset-clss*:: '*cls*  $\Rightarrow$  '*v* *clause* **and**  
*insert-clss* :: '*v* *literal*  $\Rightarrow$  '*cls*  $\Rightarrow$  '*cls* **and**  
*remove-lit* :: '*v* *literal*  $\Rightarrow$  '*cls*  $\Rightarrow$  '*cls* **and**  
*mset-clss*:: '*clss*  $\Rightarrow$  '*v* *clauses* **and**  
*union-clss* :: '*clss*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*in-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  *bool* **and**  
*insert-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*remove-from-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* +

**fixes**

*trail* :: '*st*  $\Rightarrow$  ('*v*, *unit*, *unit*) *marked-lits* **and**  
*raw-clauses* :: '*st*  $\Rightarrow$  '*clss* **and**  
*prepend-trail* :: ('*v*, *unit*, *unit*) *marked-lit*  $\Rightarrow$  '*st*  $\Rightarrow$  '*st* **and**  
*tl-trail* :: '*st*  $\Rightarrow$  '*st* **and**  
*add-clss<sub>NOT</sub>* :: '*cls*  $\Rightarrow$  '*st*  $\Rightarrow$  '*st* **and**  
*remove-clss<sub>NOT</sub>* :: '*cls*  $\Rightarrow$  '*st*  $\Rightarrow$  '*st*

**begin**

**notation** *insert-cls* (**infix** !++ 50)

**notation** *in-clss* (**infix** !∈! 50)

**notation** *union-clss* (**infix** ⊕ 50)

**notation** *insert-clss* (**infix** !++! 50)

**abbreviation** *clauses<sub>NOT</sub>* **where**

*clauses<sub>NOT</sub>* *S* ≡ *mset-clss* (*raw-clauses* *S*)

**end**

**locale** *dpll-state* =

*dpll-state-ops* *mset-cls* *insert-cls* *remove-lit* — related to each clause

*mset-clss* *union-clss* *in-clss* *insert-clss* *remove-from-clss* — related to the clauses

*trail* *raw-clauses* *prepend-trail* *tl-trail* *add-cls<sub>NOT</sub>* *remove-cls<sub>NOT</sub>* — related to the state

**for**

*mset-cls*:: '*cls* ⇒ '*v* clause **and**

*insert-cls* :: '*v* literal ⇒ '*cls* ⇒ '*cls* **and**

*remove-lit* :: '*v* literal ⇒ '*cls* ⇒ '*cls* **and**

*mset-clss*:: '*clss* ⇒ '*v* clauses **and**

*union-clss* :: '*clss* ⇒ '*clss* ⇒ '*clss* **and**

*in-clss* :: '*cls* ⇒ '*clss* ⇒ *bool* **and**

*insert-clss* :: '*cls* ⇒ '*clss* ⇒ '*clss* **and**

*remove-from-clss* :: '*cls* ⇒ '*clss* ⇒ '*clss* **and**

*trail* :: '*st* ⇒ ('*v*, *unit*, *unit*) *marked-lits* **and**

*raw-clauses* :: '*st* ⇒ '*clss* **and**

*prepend-trail* :: ('*v*, *unit*, *unit*) *marked-lit* ⇒ '*st* ⇒ '*st* **and**

*tl-trail* :: '*st* ⇒ '*st* **and**

*add-cls<sub>NOT</sub>* :: '*cls* ⇒ '*st* ⇒ '*st* **and**

*remove-cls<sub>NOT</sub>* :: '*cls* ⇒ '*st* ⇒ '*st* +

**assumes**

*trail-prepend-trail*[*simp*]:

$\bigwedge st L. \text{undefined-lit } (trail\ st) (lit\text{-of } L) \implies trail\ (prepend\text{-trail } L\ st) = L \# trail\ st$

**and**

*tl-trail*[*simp*]:  $trail\ (tl\text{-trail } S) = tl\ (trail\ S)$  **and**

*trail-add-cls<sub>NOT</sub>*[*simp*]:  $\bigwedge st C. no\text{-dup } (trail\ st) \implies trail\ (add\text{-cls}_{NOT}\ C\ st) = trail\ st$  **and**

*trail-remove-cls<sub>NOT</sub>*[*simp*]:  $\bigwedge st C. trail\ (remove\text{-cls}_{NOT}\ C\ st) = trail\ st$  **and**

*clauses-prepend-trail*[*simp*]:

$\bigwedge st L. \text{undefined-lit } (trail\ st) (lit\text{-of } L) \implies$

$clauses_{NOT}\ (prepend\text{-trail } L\ st) = clauses_{NOT}\ st$

**and**

*clauses-tl-trail*[*simp*]:  $\bigwedge st. clauses_{NOT}\ (tl\text{-trail } st) = clauses_{NOT}\ st$  **and**

*clauses-add-cls<sub>NOT</sub>*[*simp*]:

$\bigwedge st C. no\text{-dup } (trail\ st) \implies clauses_{NOT}\ (add\text{-cls}_{NOT}\ C\ st) = \{\#mset\text{-cls } C\} + clauses_{NOT}\ st$

**and**

*clauses-remove-cls<sub>NOT</sub>*[*simp*]:

$\bigwedge st C. clauses_{NOT}\ (remove\text{-cls}_{NOT}\ C\ st) = removeAll\text{-mset } (mset\text{-cls } C) (clauses_{NOT}\ st)$

**begin**

**function** *reduce-trail-to<sub>NOT</sub>* :: '*a* list ⇒ '*st* ⇒ '*st* **where**

*reduce-trail-to<sub>NOT</sub>* *F* *S* =

(if *length* (*trail* *S*) = *length* *F* ∨ *trail* *S* = [] then *S* else *reduce-trail-to<sub>NOT</sub>* *F* (*tl-trail* *S*))

**by** *fast+*

**termination by** (*relation measure* ( $\lambda(-, S). \text{length } (\text{trail } S)$ )) *auto*  
**declare** *reduce-trail-to<sub>NOT</sub>.simps*[*simp del*]

**lemma**

**shows**

*reduce-trail-to<sub>NOT</sub>-nil*[*simp*]:  $\text{trail } S = [] \implies \text{reduce-trail-to}_{\text{NOT}} F S = S$  **and**  
*reduce-trail-to<sub>NOT</sub>-eq-length*[*simp*]:  $\text{length } (\text{trail } S) = \text{length } F \implies \text{reduce-trail-to}_{\text{NOT}} F S = S$   
**by** (*auto simp: reduce-trail-to<sub>NOT</sub>.simps*)

**lemma** *reduce-trail-to<sub>NOT</sub>-length-ne*[*simp*]:

$\text{length } (\text{trail } S) \neq \text{length } F \implies \text{trail } S \neq [] \implies$   
 $\text{reduce-trail-to}_{\text{NOT}} F S = \text{reduce-trail-to}_{\text{NOT}} F (\text{tl-trail } S)$   
**by** (*auto simp: reduce-trail-to<sub>NOT</sub>.simps*)

**lemma** *trail-reduce-trail-to<sub>NOT</sub>-length-le*:

**assumes**  $\text{length } F > \text{length } (\text{trail } S)$   
**shows**  $\text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S) = []$   
**using** *assms* **by** (*induction F S rule: reduce-trail-to<sub>NOT</sub>.induct*)  
(*simp add: less-imp-diff-less reduce-trail-to<sub>NOT</sub>.simps*)

**lemma** *trail-reduce-trail-to<sub>NOT</sub>-nil*[*simp*]:

$\text{trail } (\text{reduce-trail-to}_{\text{NOT}} [] S) = []$   
**by** (*induction [] S rule: reduce-trail-to<sub>NOT</sub>.induct*)  
(*simp add: less-imp-diff-less reduce-trail-to<sub>NOT</sub>.simps*)

**lemma** *clauses-reduce-trail-to<sub>NOT</sub>-nil*:

$\text{clauses}_{\text{NOT}} (\text{reduce-trail-to}_{\text{NOT}} [] S) = \text{clauses}_{\text{NOT}} S$   
**by** (*induction [] S rule: reduce-trail-to<sub>NOT</sub>.induct*)  
(*simp add: less-imp-diff-less reduce-trail-to<sub>NOT</sub>.simps*)

**lemma** *trail-reduce-trail-to<sub>NOT</sub>-drop*:

$\text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S) =$   
 (*if*  $\text{length } (\text{trail } S) \geq \text{length } F$   
*then*  $\text{drop } (\text{length } (\text{trail } S) - \text{length } F) (\text{trail } S)$   
*else*  $[]$ )  
**apply** (*induction F S rule: reduce-trail-to<sub>NOT</sub>.induct*)  
**apply** (*rename-tac F S, case-tac trail S*)  
**apply** *auto*  
**apply** (*rename-tac list, case-tac Suc (length list) > length F*)  
**prefer** 2 **apply** *simp*  
**apply** (*subgoal-tac Suc (length list) - length F = Suc (length list - length F)*)  
**apply** *simp*  
**apply** *simp*  
**done**

**lemma** *reduce-trail-to<sub>NOT</sub>-skip-beginning*:

**assumes**  $\text{trail } S = F' @ F$   
**shows**  $\text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S) = F$   
**using** *assms* **by** (*auto simp: trail-reduce-trail-to<sub>NOT</sub>-drop*)

**lemma** *reduce-trail-to<sub>NOT</sub>-clauses*[*simp*]:

$\text{clauses}_{\text{NOT}} (\text{reduce-trail-to}_{\text{NOT}} F S) = \text{clauses}_{\text{NOT}} S$   
**by** (*induction F S rule: reduce-trail-to<sub>NOT</sub>.induct*)  
(*simp add: less-imp-diff-less reduce-trail-to<sub>NOT</sub>.simps*)



**abbreviation** *trail-weight* **where**

*trail-weight*  $S \equiv \text{map } ((\lambda l. 1 + \text{length } l) \circ \text{snd}) (\text{get-all-marked-decomposition } (\text{trail } S))$

**definition** *state-eq<sub>NOT</sub>* :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool (**infix**  $\sim$  50) **where**

$S \sim T \iff \text{trail } S = \text{trail } T \wedge \text{clauses}_{\text{NOT}} S = \text{clauses}_{\text{NOT}} T$

**lemma** *state-eq<sub>NOT</sub>-ref[simp]*:

$S \sim S$

**unfolding** *state-eq<sub>NOT</sub>-def* **by** *auto*

**lemma** *state-eq<sub>NOT</sub>-sym*:

$S \sim T \iff T \sim S$

**unfolding** *state-eq<sub>NOT</sub>-def* **by** *auto*

**lemma** *state-eq<sub>NOT</sub>-trans*:

$S \sim T \implies T \sim U \implies S \sim U$

**unfolding** *state-eq<sub>NOT</sub>-def* **by** *auto*

**lemma**

**shows**

*state-eq<sub>NOT</sub>-trail*:  $S \sim T \implies \text{trail } S = \text{trail } T$  **and**

*state-eq<sub>NOT</sub>-clauses*:  $S \sim T \implies \text{clauses}_{\text{NOT}} S = \text{clauses}_{\text{NOT}} T$

**unfolding** *state-eq<sub>NOT</sub>-def* **by** *auto*

**lemmas** *state-simp<sub>NOT</sub>[simp]* = *state-eq<sub>NOT</sub>-trail* *state-eq<sub>NOT</sub>-clauses*

**lemma** *trail-eq-reduce-trail-to<sub>NOT</sub>-eq*:

$\text{trail } S = \text{trail } T \implies \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S) = \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F T)$

**apply** (*induction*  $F S$  *arbitrary*:  $T$  *rule*: *reduce-trail-to<sub>NOT</sub>.induct*)

**by** (*metis* *tl-trail* *reduce-trail-to<sub>NOT</sub>-eq-length* *reduce-trail-to<sub>NOT</sub>-length-ne* *reduce-trail-to<sub>NOT</sub>-nil*)

**lemma** *reduce-trail-to<sub>NOT</sub>-state-eq<sub>NOT</sub>-compatible*:

**assumes**  $ST$ :  $S \sim T$

**shows**  $\text{reduce-trail-to}_{\text{NOT}} F S \sim \text{reduce-trail-to}_{\text{NOT}} F T$

**proof** –

**have**  $\text{clauses}_{\text{NOT}} (\text{reduce-trail-to}_{\text{NOT}} F S) = \text{clauses}_{\text{NOT}} (\text{reduce-trail-to}_{\text{NOT}} F T)$

**using**  $ST$  **by** *auto*

**moreover have**  $\text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S) = \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F T)$

**using** *trail-eq-reduce-trail-to<sub>NOT</sub>-eq*[*of*  $S T F$ ]  $ST$  **by** *auto*

**ultimately show** *?thesis* **by** (*auto* *simp* *del*: *state-simp<sub>NOT</sub>* *simp*: *state-eq<sub>NOT</sub>-def*)

**qed**

**lemma** *trail-reduce-trail-to<sub>NOT</sub>-add-cl<sub>NOT</sub>[simp]*:

*no-dup* ( $\text{trail } S$ )  $\implies$

$\text{trail } (\text{reduce-trail-to}_{\text{NOT}} F (\text{add-cl}_{\text{NOT}} C S)) = \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S)$

**by** (*rule* *trail-eq-reduce-trail-to<sub>NOT</sub>-eq*) *simp*

**lemma** *reduce-trail-to<sub>NOT</sub>-trail-tl-trail-decomp[simp]*:

$\text{trail } S = F' @ \text{Marked } K () \# F \implies$

$\text{trail } (\text{reduce-trail-to}_{\text{NOT}} F (\text{tl-trail } S)) = F$

**apply** (*rule* *reduce-trail-to<sub>NOT</sub>-skip-beginning*[*of* -  $\text{tl } (F' @ \text{Marked } K () \# [])$ ])

**by** (*cases*  $F'$ ) (*auto* *simp* *add*:*tl-append* *reduce-trail-to<sub>NOT</sub>-skip-beginning*)

**lemma** *reduce-trail-to<sub>NOT</sub>-length*:

$\text{length } M = \text{length } M' \implies \text{reduce-trail-to}_{\text{NOT}} M S = \text{reduce-trail-to}_{\text{NOT}} M' S$

**apply** (*induction*  $M\ S$  *arbitrary*: *rule*: *reduce-trail-to*<sub>NOT</sub>.*induct*)  
**by** (*simp* *add*: *reduce-trail-to*<sub>NOT</sub>.*simps*)

**end**

### 16.2.2 Definition of the operation

**locale** *propagate-ops* =  
*dpll-state* *mset-cls* *insert-cls* *remove-lit*  
*mset-clss* *union-clss* *in-clss* *insert-clss* *remove-from-clss*  
*trail* *raw-clauses* *prepend-trail* *tl-trail* *add-cls*<sub>NOT</sub> *remove-cls*<sub>NOT</sub>  
**for**  
*mset-cls*:: '*cls*  $\Rightarrow$  '*v* *clause* **and**  
*insert-cls* :: '*v* *literal*  $\Rightarrow$  '*cls*  $\Rightarrow$  '*cls* **and**  
*remove-lit* :: '*v* *literal*  $\Rightarrow$  '*cls*  $\Rightarrow$  '*cls* **and**  
*mset-clss*:: '*clss*  $\Rightarrow$  '*v* *clauses* **and**  
*union-clss* :: '*clss*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*in-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  *bool* **and**  
*insert-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*remove-from-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*trail* :: '*st*  $\Rightarrow$  ('*v*, *unit*, *unit*) *marked-lits* **and**  
*raw-clauses* :: '*st*  $\Rightarrow$  '*clss* **and**  
*prepend-trail* :: ('*v*, *unit*, *unit*) *marked-lit*  $\Rightarrow$  '*st*  $\Rightarrow$  '*st* **and**  
*tl-trail* :: '*st*  $\Rightarrow$  '*st* **and**  
*add-cls*<sub>NOT</sub> :: '*cls*  $\Rightarrow$  '*st*  $\Rightarrow$  '*st* **and**  
*remove-cls*<sub>NOT</sub> :: '*cls*  $\Rightarrow$  '*st*  $\Rightarrow$  '*st* +  
**fixes**  
*propagate-cond* :: ('*v*, *unit*, *unit*) *marked-lit*  $\Rightarrow$  '*st*  $\Rightarrow$  *bool*  
**begin**  
**inductive** *propagate*<sub>NOT</sub> :: '*st*  $\Rightarrow$  '*st*  $\Rightarrow$  *bool* **where**  
*propagate*<sub>NOT</sub>[*intro*]:  $C + \{\#L\} \in \# \text{ clauses}_{NOT} \ S \Longrightarrow \text{trail } S \models_{as} CNot \ C$   
 $\Longrightarrow \text{undefined-lit } (\text{trail } S) \ L$   
 $\Longrightarrow \text{propagate-cond } (\text{Propagated } L \ ()) \ S$   
 $\Longrightarrow T \sim \text{prepend-trail } (\text{Propagated } L \ ()) \ S$   
 $\Longrightarrow \text{propagate}_{NOT} \ S \ T$   
**inductive-cases** *propagate*<sub>NOT</sub>*E*[*elim*]: *propagate*<sub>NOT</sub> *S* *T*  
**end**

**locale** *decide-ops* =  
*dpll-state* *mset-cls* *insert-cls* *remove-lit*  
*mset-clss* *union-clss* *in-clss* *insert-clss* *remove-from-clss*  
*trail* *raw-clauses* *prepend-trail* *tl-trail* *add-cls*<sub>NOT</sub> *remove-cls*<sub>NOT</sub>  
**for**  
*mset-cls*:: '*cls*  $\Rightarrow$  '*v* *clause* **and**  
*insert-cls* :: '*v* *literal*  $\Rightarrow$  '*cls*  $\Rightarrow$  '*cls* **and**  
*remove-lit* :: '*v* *literal*  $\Rightarrow$  '*cls*  $\Rightarrow$  '*cls* **and**  
*mset-clss*:: '*clss*  $\Rightarrow$  '*v* *clauses* **and**  
*union-clss* :: '*clss*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*in-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  *bool* **and**  
*insert-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*remove-from-clss* :: '*cls*  $\Rightarrow$  '*clss*  $\Rightarrow$  '*clss* **and**  
*trail* :: '*st*  $\Rightarrow$  ('*v*, *unit*, *unit*) *marked-lits* **and**  
*raw-clauses* :: '*st*  $\Rightarrow$  '*clss* **and**  
*prepend-trail* :: ('*v*, *unit*, *unit*) *marked-lit*  $\Rightarrow$  '*st*  $\Rightarrow$  '*st* **and**  
*tl-trail* :: '*st*  $\Rightarrow$  '*st* **and**

```

    add-clsNOT :: 'cls ⇒ 'st ⇒ 'st and
    remove-clsNOT :: 'cls ⇒ 'st ⇒ 'st
begin
inductive decideNOT :: 'st ⇒ 'st ⇒ bool where
decideNOT[intro]: undefined-lit (trail S) L ⇒ atm-of L ∈ atms-of-mm (clausesNOT S)
    ⇒ T ∼ prepend-trail (Marked L ()) S
    ⇒ decideNOT S T

inductive-cases decideNOTE[elim]: decideNOT S S'
end

locale backjumping-ops =
  dpll-state mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clsNOT remove-clsNOT
for
  mset-cls:: 'cls ⇒ 'v clause and
  insert-cls :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and
  mset-clss:: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  trail :: 'st ⇒ ('v, unit, unit) marked-lits and
  raw-clauses :: 'st ⇒ 'clss and
  prepend-trail :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and
  add-clsNOT :: 'cls ⇒ 'st ⇒ 'st and
  remove-clsNOT :: 'cls ⇒ 'st ⇒ 'st +
fixes
  backjump-conds :: 'v clause ⇒ 'v clause ⇒ 'v literal ⇒ 'st ⇒ 'st ⇒ bool
begin

inductive backjump where
trail S = F' @ Marked K ()# F
    ⇒ T ∼ prepend-trail (Propagated L ()) (reduce-trail-toNOT F S)
    ⇒ C ∈# clausesNOT S
    ⇒ trail S ⊨as CNot C
    ⇒ undefined-lit F L
    ⇒ atm-of L ∈ atms-of-mm (clausesNOT S) ∪ atm-of ' (lits-of-l (trail S))
    ⇒ clausesNOT S ⊨pm C' + {#L#}
    ⇒ F ⊨as CNot C'
    ⇒ backjump-conds C C' L S T
    ⇒ backjump S T
inductive-cases backjumpE: backjump S T

```

The condition  $\text{atm-of } L \in \text{atms-of-mm } (\text{clauses}_{\text{NOT}} S) \cup \text{atm-of ' (lits-of-l (trail S))}$  is not implied by the condition  $\text{clauses}_{\text{NOT}} S \models_{\text{pm}} C' + \{\#L\}$  (no negation).

end

### 16.3 DPLL with backjumping

```

locale dpll-with-backjumping-ops =
  propagate-ops mset-cls insert-cls remove-lit

```

```

mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clssNOT remove-clssNOT propagate-conds +
decide-ops mset-clss insert-clss remove-lit
mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clssNOT remove-clssNOT +
backjumping-ops mset-clss insert-clss remove-lit
mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clssNOT remove-clssNOT backjump-conds
for
  mset-clss :: 'cls  $\Rightarrow$  'v clause and
  insert-clss :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  mset-clss :: 'clss  $\Rightarrow$  'v clauses and
  union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and
  insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  trail :: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and
  raw-clauses :: 'st  $\Rightarrow$  'clss and
  prepend-trail :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and
  tl-trail :: 'st  $\Rightarrow$  'st and
  add-clssNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  remove-clssNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  inv :: 'st  $\Rightarrow$  bool and
  backjump-conds :: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool and
  propagate-conds :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  bool +
assumes
  bj-can-jump:
   $\bigwedge S C F' K F L.$ 
  inv  $S \Rightarrow$ 
  no-dup (trail  $S$ )  $\Rightarrow$ 
  trail  $S = F' @ \text{Marked } K () \# F \Rightarrow$ 
   $C \in \# \text{clauses}_{\text{NOT}} S \Rightarrow$ 
  trail  $S \models_{\text{as}} C \text{Not } C \Rightarrow$ 
  undefined-lit  $F L \Rightarrow$ 
  atm-of  $L \in \text{atms-of-mm} (\text{clauses}_{\text{NOT}} S) \cup \text{atm-of } ( \text{lits-of-l } (F' @ \text{Marked } K () \# F) ) \Rightarrow$ 
  clausesNOT  $S \models_{\text{pm}} C' + \{ \#L \# \} \Rightarrow$ 
   $F \models_{\text{as}} C \text{Not } C' \Rightarrow$ 
   $\neg \text{no-step backjump } S$ 
begin

```

We cannot add a like condition  $\text{atms-of } C' \subseteq \text{atms-of-ms } N$  because to ensure that we can backjump even if the last decision variable has disappeared.

The part of the condition  $\text{atm-of } L \in \text{atm-of } ( \text{lits-of-l } (F' @ \text{Marked } K () \# F) )$  is important, otherwise you are not sure that you can backtrack.

### 16.3.1 Definition

We define dpll with backjumping:

**inductive**  $\text{dpll-bj} :: 'st \Rightarrow 'st \Rightarrow \text{bool}$  **for**  $S :: 'st$  **where**  
 $\text{bj-decide}_{\text{NOT}}: \text{decide}_{\text{NOT}} S S' \Rightarrow \text{dpll-bj } S S' \mid$   
 $\text{bj-propagate}_{\text{NOT}}: \text{propagate}_{\text{NOT}} S S' \Rightarrow \text{dpll-bj } S S' \mid$   
 $\text{bj-backjump}: \text{backjump } S S' \Rightarrow \text{dpll-bj } S S'$

**lemmas** *dpll-bj-induct* = *dpll-bj.induct*[*split-format*(*complete*)]  
**thm** *dpll-bj-induct*[*OF dpll-with-backjumping-ops-axioms*]  
**lemma** *dpll-bj-all-induct*[*consumes 2, case-names decide<sub>NOT</sub> propagate<sub>NOT</sub> backjump*]:  
*fixes S T :: 'st*  
**assumes**  
*dpll-bj S T and*  
*inv S*  
 $\bigwedge L T. \text{undefined-lit } (\text{trail } S) L \implies \text{atm-of } L \in \text{atms-of-mm } (\text{clauses}_{NOT} S)$   
 $\implies T \sim \text{prepend-trail } (\text{Marked } L ()) S$   
 $\implies P S T$  **and**  
 $\bigwedge C L T. C + \{\#L\# \} \in \# \text{ clauses}_{NOT} S \implies \text{trail } S \models_{as} CNot C \implies \text{undefined-lit } (\text{trail } S) L$   
 $\implies T \sim \text{prepend-trail } (\text{Propagated } L ()) S$   
 $\implies P S T$  **and**  
 $\bigwedge C F' K F L C' T. C \in \# \text{ clauses}_{NOT} S \implies F' @ \text{Marked } K () \# F \models_{as} CNot C$   
 $\implies \text{trail } S = F' @ \text{Marked } K () \# F$   
 $\implies \text{undefined-lit } F L$   
 $\implies \text{atm-of } L \in \text{atms-of-mm } (\text{clauses}_{NOT} S) \cup \text{atm-of ' (lits-of-l } (F' @ \text{Marked } K () \# F))$   
 $\implies \text{clauses}_{NOT} S \models_{pm} C' + \{\#L\# \}$   
 $\implies F \models_{as} CNot C'$   
 $\implies T \sim \text{prepend-trail } (\text{Propagated } L ()) (\text{reduce-trail-to}_{NOT} F S)$   
 $\implies P S T$   
**shows** *P S T*  
**apply** (*induct T rule: dpll-bj-induct*[*OF local.dpll-with-backjumping-ops-axioms*])  
**apply** (*rule assms*(1))  
**using** *assms*(3) **apply** *blast*  
**apply** (*elim propagate<sub>NOT</sub>E*) **using** *assms*(4) **apply** *blast*  
**apply** (*elim backjumpE*) **using** *assms*(5) *<inv S>* **by** *simp*

### 16.3.2 Basic properties

**First, some better suited induction principle** **lemma** *dpll-bj-clauses*:

**assumes** *dpll-bj S T and inv S*  
**shows** *clauses<sub>NOT</sub> S = clauses<sub>NOT</sub> T*  
**using** *assms* **by** (*induction rule: dpll-bj-all-induct*) *auto*

**No duplicates in the trail** **lemma** *dpll-bj-no-dup*:

**assumes** *dpll-bj S T and inv S*  
**and** *no-dup (trail S)*  
**shows** *no-dup (trail T)*  
**using** *assms* **by** (*induction rule: dpll-bj-all-induct*)  
*(auto simp add: defined-lit-map reduce-trail-to<sub>NOT</sub>-skip-beginning)*

**Valuations** **lemma** *dpll-bj-sat-iff*:

**assumes** *dpll-bj S T and inv S*  
**shows**  $I \models_{sm} \text{clauses}_{NOT} S \longleftrightarrow I \models_{sm} \text{clauses}_{NOT} T$   
**using** *assms* **by** (*induction rule: dpll-bj-all-induct*) *auto*

**Clauses** **lemma** *dpll-bj-atms-of-ms-clauses-inv*:

**assumes**  
*dpll-bj S T and*  
*inv S*  
**shows**  $\text{atms-of-mm } (\text{clauses}_{NOT} S) = \text{atms-of-mm } (\text{clauses}_{NOT} T)$   
**using** *assms* **by** (*induction rule: dpll-bj-all-induct*) *auto*

**lemma** *dpll-bj-atms-in-trail*:

**assumes**  
*dpll-bj S T and*  
*inv S and*  
*atm-of ' (lits-of-l (trail S))  $\subseteq$  atms-of-mm (clauses<sub>NOT</sub> S)*  
**shows** *atm-of ' (lits-of-l (trail T))  $\subseteq$  atms-of-mm (clauses<sub>NOT</sub> S)*  
**using** *assms by (induction rule: dpll-bj-all-induct)*  
*(auto simp: in-plus-implies-atm-of-on-atms-of-ms reduce-trail-to<sub>NOT</sub>-skip-beginning)*

**lemma** *dpll-bj-atms-in-trail-in-set:*

**assumes** *dpll-bj S T and*  
*inv S and*  
*atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  A and*  
*atm-of ' (lits-of-l (trail S))  $\subseteq$  A*  
**shows** *atm-of ' (lits-of-l (trail T))  $\subseteq$  A*  
**using** *assms by (induction rule: dpll-bj-all-induct)*  
*(auto simp: in-plus-implies-atm-of-on-atms-of-ms)*

**lemma** *dpll-bj-all-decomposition-implies-inv:*

**assumes**  
*dpll-bj S T and*  
*inv: inv S and*  
*decomp: all-decomposition-implies-m (clauses<sub>NOT</sub> S) (get-all-marked-decomposition (trail S))*  
**shows** *all-decomposition-implies-m (clauses<sub>NOT</sub> T) (get-all-marked-decomposition (trail T))*  
**using** *assms(1,2)*

**proof** *(induction rule: dpll-bj-all-induct)*

**case** *decide<sub>NOT</sub>*

**then show** *?case using decomp by auto*

**next**

**case** *(propagate<sub>NOT</sub> C L T) note propa = this(1) and undef = this(3) and T = this(4)*  
**let** *?M' = trail (prepend-trail (Propagated L ()) S)*  
**let** *?N = clauses<sub>NOT</sub> S*  
**obtain** *a y l where ay: get-all-marked-decomposition ?M' = (a, y) # l*  
**by** *(cases get-all-marked-decomposition ?M') fastforce+*  
**then have** *M': ?M' = y @ a using get-all-marked-decomposition-decomp[of ?M'] by auto*  
**have** *M: get-all-marked-decomposition (trail S) = (a, tl y) # l*  
**using** *ay undef by (cases get-all-marked-decomposition (trail S)) auto*  
**have** *y<sub>0</sub>: y = (Propagated L ()) # (tl y)*  
**using** *ay undef by (auto simp add: M)*  
**from** *arg-cong[OF this, of set] have y[simp]: set y = insert (Propagated L ()) (set (tl y))*  
**by** *simp*  
**have** *tr-S: trail S = tl y @ a*  
**using** *arg-cong[OF M', of tl] y<sub>0</sub> M get-all-marked-decomposition-decomp by force*  
**have** *a-Un-N-M: unmark-l a  $\cup$  set-mset ?N  $\models_{ps}$  unmark-l (tl y)*  
**using** *decomp ay unfolding all-decomposition-implies-def by (simp add: M)+*

**moreover have** *unmark-l a  $\cup$  set-mset ?N  $\models_p$  {#L#} (is ?I  $\models_p$  -)*

**proof** *(rule true-clss-clss-plus-CNot)*

**show** *?I  $\models_p$  C + {#L#}*

**using** *propa propagate<sub>NOT</sub>.prems by (auto dest!: true-clss-clss-in-imp-true-clss-clss)*

**next**

**have** *unmark-l ?M'  $\models_{ps}$  CNot C*

**using** *(trail S  $\models_{as}$  CNot C) undef by (auto simp add: true-annots-true-clss-clss)*

**have** *a1: unmark-l a  $\cup$  unmark-l (tl y)  $\models_{ps}$  CNot C*

**using** *propagate<sub>NOT</sub>.hyps(2) tr-S true-annots-true-clss-clss*

**by** *(force simp add: image-Un sup-commute)*

```

    then have unmark-l a  $\cup$  set-mset (clausesNOT S)  $\models_{ps}$  unmark-l a  $\cup$  unmark-l (tl y)
      using a-Un-N-M true-clss-clss-def by blast
    then show unmark-l a  $\cup$  set-mset (clausesNOT S)  $\models_{ps}$  CNot C
      using a1 by (meson true-clss-clss-left-right true-clss-clss-union-and
        true-clss-clss-union-l-r)
    qed
  ultimately have unmark-l a  $\cup$  set-mset ?N  $\models_{ps}$  unmark-l ?M'
    unfolding M' by (auto simp add: all-in-true-clss-clss image-Un)
  then show ?case
    using decomp T M undef unfolding ay all-decomposition-implies-def by (auto simp add: ay)
next
case (backjump C F' K F L D T) note confl = this(2) and tr = this(3) and undef = this(4)
  and L = this(5) and N-C = this(6) and vars-D = this(5) and T = this(8)
have decomp: all-decomposition-implies-m (clausesNOT S) (get-all-marked-decomposition F)
  using decomp unfolding tr all-decomposition-implies-def
  by (metis (no-types, lifting) get-all-marked-decomposition.simps(1)
    get-all-marked-decomposition-never-empty hd-Cons-tl insert-iff list.sel(3) list.set(2)
    tl-get-all-marked-decomposition-skip-some)

obtain a b li where F: get-all-marked-decomposition F = (a, b) # li
  by (cases get-all-marked-decomposition F) auto
have F = b @ a
  using get-all-marked-decomposition-decomp[of F a b] F by auto
have a-N-b: unmark-l a  $\cup$  set-mset (clausesNOT S)  $\models_{ps}$  unmark-l b
  using decomp unfolding all-decomposition-implies-def by (auto simp add: F)

have F-D: unmark-l F  $\models_{ps}$  CNot D
  using  $\langle F \models_{as} CNot D \rangle$  by (simp add: true-annots-true-clss-clss)
then have unmark-l a  $\cup$  unmark-l b  $\models_{ps}$  CNot D
  unfolding  $\langle F = b @ a \rangle$  by (simp add: image-Un sup.commute)
have a-N-CNot-D: unmark-l a  $\cup$  set-mset (clausesNOT S)  $\models_{ps}$  CNot D  $\cup$  unmark-l b
  apply (rule true-clss-clss-left-right)
  using a-N-b F-D unfolding  $\langle F = b @ a \rangle$  by (auto simp add: image-Un ac-simps)

have a-N-D-L: unmark-l a  $\cup$  set-mset (clausesNOT S)  $\models_p$  D + {#L#}
  by (simp add: N-C)
have unmark-l a  $\cup$  set-mset (clausesNOT S)  $\models_p$  {#L#}
  using a-N-D-L a-N-CNot-D by (blast intro: true-clss-clss-plus-CNot)
then show ?case
  using decomp T tr undef unfolding all-decomposition-implies-def by (auto simp add: F)
qed

```

### 16.3.3 Termination

**Using a proper measure** lemma length-get-all-marked-decomposition-append-Marked:

$$\begin{aligned}
& \text{length (get-all-marked-decomposition (F' @ Marked K () \# F))} = \\
& \quad \text{length (get-all-marked-decomposition F')} \\
& \quad + \text{length (get-all-marked-decomposition (Marked K () \# F))} \\
& \quad - 1
\end{aligned}$$

by (induction F' rule: marked-lit-list-induct) auto

**lemma** take-length-get-all-marked-decomposition-marked-sandwich:

$$\begin{aligned}
& \text{take (length (get-all-marked-decomposition F))} \\
& \quad (\text{map (f o snd) (rev (get-all-marked-decomposition (F' @ Marked K () \# F)))}) \\
& \quad = \\
& \quad \text{map (f o snd) (rev (get-all-marked-decomposition F))}
\end{aligned}$$

```

proof (induction F' rule: marked-lit-list-induct)
  case nil
  then show ?case by auto
next
  case (marked K)
  then show ?case by (simp add: length-get-all-marked-decomposition-append-Marked)
next
  case (proped L m F') note IH = this(1)
  obtain a b l where F': get-all-marked-decomposition (F' @ Marked K () # F) = (a, b) # l
    by (cases get-all-marked-decomposition (F' @ Marked K () # F)) auto
  have length (get-all-marked-decomposition F) - length l = 0
    using length-get-all-marked-decomposition-append-Marked[of F' K F]
    unfolding F' by (cases get-all-marked-decomposition F') auto
  then show ?case
    using IH by (simp add: F')
qed

```

**lemma** length-get-all-marked-decomposition-length:  
 $\text{length } (\text{get-all-marked-decomposition } M) \leq 1 + \text{length } M$   
**by** (induction M rule: marked-lit-list-induct) auto

**lemma** length-in-get-all-marked-decomposition-bounded:

**assumes**  $i : i \in \text{set } (\text{trail-weight } S)$   
**shows**  $i \leq \text{Suc } (\text{length } (\text{trail } S))$

**proof** –

**obtain** a b **where**  
 $(a, b) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$  **and**  
 $ib : i = \text{Suc } (\text{length } b)$   
**using** i **by** auto  
**then obtain** c **where**  $\text{trail } S = c @ b @ a$   
**using** get-all-marked-decomposition-exists-prepend' **by** metis  
**from** arg-cong[OF this, of length] **show** ?thesis **using** i ib **by** auto  
**qed**

**Well-foundedness** The bounds are the following:

- $1 + \text{card } (\text{atms-of-ms } A)$ :  $\text{card } (\text{atms-of-ms } A)$  is an upper bound on the length of the list. As  $\text{get-all-marked-decomposition}$  appends an possibly empty couple at the end, adding one is needed.
- $2 + \text{card } (\text{atms-of-ms } A)$ :  $\text{card } (\text{atms-of-ms } A)$  is an upper bound on the number of elements, where adding one is necessary for the same reason as for the bound on the list, and one is needed to have a strict bound.

**abbreviation** unassigned-lit :: 'b literal multiset set  $\Rightarrow$  'a list  $\Rightarrow$  nat **where**

$\text{unassigned-lit } N M \equiv \text{card } (\text{atms-of-ms } N) - \text{length } M$

**lemma** dpll-bj-trail-mes-increasing-prop:

**fixes** M :: ('v, unit, unit) marked-lits **and** N :: 'v clauses

**assumes**

$\text{dpll-bj } S T$  **and**

$\text{inv } S$  **and**

$\text{NA} : \text{atms-of-mm } (\text{clauses}_{\text{NOT}} S) \subseteq \text{atms-of-ms } A$  **and**

$\text{MA} : \text{atm-of ' lits-of-l } (\text{trail } S) \subseteq \text{atms-of-ms } A$  **and**



$n\text{-d}$ :  $\text{no-dup } (\text{trail } S) \text{ and}$   
 $\text{finite}$ :  $\text{finite } A$   
**shows**  $\mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } T)$   
 $> \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } S)$   
**using**  $\text{assms}(1, 2)$   
**proof** ( $\text{induction rule: dpll-bj-all-induct}$ )  
**case** ( $\text{propagate}_{\text{NOT}} C L$ ) **note**  $\text{CLN} = \text{this}(1)$  **and**  $\text{MC} = \text{this}(2)$  **and**  $\text{undef-L} = \text{this}(3)$  **and**  $T = \text{this}(4)$   
**have**  $\text{incl: atm-of ' lits-of-l } (\text{Propagated } L () \# \text{trail } S) \subseteq \text{atms-of-ms } A$   
**using**  $\text{propagate}_{\text{NOT}} \text{dpll-bj-atms-in-trail-in-set bj-propagate}_{\text{NOT}} \text{NA MA CLN}$   
**by** ( $\text{auto simp: in-plus-implies-atm-of-on-atms-of-ms}$ )  
  
**have**  $\text{no-dup: no-dup } (\text{Propagated } L () \# \text{trail } S)$   
**using**  $\text{defined-lit-map } n\text{-d } \text{undef-L}$  **by**  $\text{auto}$   
**obtain**  $a b l$  **where**  $M$ :  $\text{get-all-marked-decomposition } (\text{trail } S) = (a, b) \# l$   
**by** ( $\text{cases get-all-marked-decomposition } (\text{trail } S)$ )  $\text{auto}$   
**have**  $b\text{-le-}M$ :  $\text{length } b \leq \text{length } (\text{trail } S)$   
**using**  $\text{get-all-marked-decomposition-decomp[of trail } S]$  **by** ( $\text{simp add: } M$ )  
**have**  $\text{finite } (\text{atms-of-ms } A)$  **using**  $\text{finite}$  **by**  $\text{simp}$   
  
**then have**  $\text{length } (\text{Propagated } L () \# \text{trail } S) \leq \text{card } (\text{atms-of-ms } A)$   
**using**  $\text{incl finite unfolding no-dup-length-eq-card-atm-of-lits-of-l[OF no-dup]}$   
**by** ( $\text{simp add: card-mono}$ )  
**then have**  $\text{latm: unassigned-lit } A b = \text{Suc } (\text{unassigned-lit } A (\text{Propagated } L d \# b))$   
**using**  $b\text{-le-}M$  **by**  $\text{auto}$   
**then show**  $?case$  **using**  $T \text{undef-L}$  **by** ( $\text{auto simp: latm } M \mu_C\text{-cons}$ )  
**next**  
**case** ( $\text{decide}_{\text{NOT}} L$ ) **note**  $\text{undef-L} = \text{this}(1)$  **and**  $\text{MC} = \text{this}(2)$  **and**  $T = \text{this}(3)$   
**have**  $\text{incl: atm-of ' lits-of-l } (\text{Marked } L () \# (\text{trail } S)) \subseteq \text{atms-of-ms } A$   
**using**  $\text{dpll-bj-atms-in-trail-in-set bj-decide}_{\text{NOT}} \text{decide}_{\text{NOT}}.\text{decide}_{\text{NOT}}[\text{OF decide}_{\text{NOT}}.\text{hyps}] \text{NA MA}$   
 $\text{MC}$   
**by**  $\text{auto}$   
  
**have**  $\text{no-dup: no-dup } (\text{Marked } L () \# (\text{trail } S))$   
**using**  $\text{defined-lit-map } n\text{-d } \text{undef-L}$  **by**  $\text{auto}$   
**obtain**  $a b l$  **where**  $M$ :  $\text{get-all-marked-decomposition } (\text{trail } S) = (a, b) \# l$   
**by** ( $\text{cases get-all-marked-decomposition } (\text{trail } S)$ )  $\text{auto}$   
  
**then have**  $\text{length } (\text{Marked } L () \# (\text{trail } S)) \leq \text{card } (\text{atms-of-ms } A)$   
**using**  $\text{incl finite unfolding no-dup-length-eq-card-atm-of-lits-of-l[OF no-dup]}$   
**by** ( $\text{simp add: card-mono}$ )  
**show**  $?case$  **using**  $T \text{undef-L}$  **by** ( $\text{simp add: } \mu_C\text{-cons}$ )  
**next**  
**case** ( $\text{backjump } C F' K F L C' T$ ) **note**  $\text{undef-L} = \text{this}(4)$  **and**  $\text{MC} = \text{this}(1)$  **and**  $\text{tr-S} = \text{this}(3)$   
**and**  
 $L = \text{this}(5)$  **and**  $T = \text{this}(8)$   
**have**  $\text{incl: atm-of ' lits-of-l } (\text{Propagated } L () \# F) \subseteq \text{atms-of-ms } A$   
**using**  $\text{dpll-bj-atms-in-trail-in-set NA MA L}$  **by** ( $\text{auto simp: tr-S}$ )  
  
**have**  $\text{no-dup: no-dup } (\text{Propagated } L () \# F)$   
**using**  $\text{defined-lit-map } n\text{-d } \text{undef-L tr-S}$  **by**  $\text{auto}$   
**obtain**  $a b l$  **where**  $M$ :  $\text{get-all-marked-decomposition } (\text{trail } S) = (a, b) \# l$   
**by** ( $\text{cases get-all-marked-decomposition } (\text{trail } S)$ )  $\text{auto}$   
**have**  $b\text{-le-}M$ :  $\text{length } b \leq \text{length } (\text{trail } S)$   
**using**  $\text{get-all-marked-decomposition-decomp[of trail } S]$  **by** ( $\text{simp add: } M$ )

```

have fin-atms-A: finite (atms-of-ms A) using finite by simp

then have F-le-A: length (Propagated L () # F) ≤ card (atms-of-ms A)
  using incl finite unfolding no-dup-length-eq-card-atm-of-lits-of-l[OF no-dup]
  by (simp add: card-mono)
have tr-S-le-A: length (trail S) ≤ (card (atms-of-ms A))
  using n-d MA by (metis fin-atms-A card-mono no-dup-length-eq-card-atm-of-lits-of-l)
obtain a b l where F: get-all-marked-decomposition F = (a, b) # l
  by (cases get-all-marked-decomposition F) auto
then have F = b @ a
  using get-all-marked-decomposition-decomp[of Propagated L () # F a
    Propagated L () # b] by simp
then have latm: unassigned-lit A b = Suc (unassigned-lit A (Propagated L () # b))
  using F-le-A by simp
obtain rem where
  rem: map (λa. Suc (length (snd a))) (rev (get-all-marked-decomposition (F' @ Marked K () # F)))
    = map (λa. Suc (length (snd a))) (rev (get-all-marked-decomposition F)) @ rem
  using take-length-get-all-marked-decomposition-marked-sandwich[of F λa. Suc (length a) F' K]
  unfolding o-def by (metis append-take-drop-id)
then have rem: map (λa. Suc (length (snd a)))
  (get-all-marked-decomposition (F' @ Marked K () # F))
    = rev rem @ map (λa. Suc (length (snd a))) ((get-all-marked-decomposition F))
  by (simp add: rev-map[symmetric] rev-swap)
have length (rev rem @ map (λa. Suc (length (snd a))) (get-all-marked-decomposition F))
  ≤ Suc (card (atms-of-ms A))
  using arg-cong[OF rem, of length] tr-S-le-A
  length-get-all-marked-decomposition-length[of F' @ Marked K () # F] tr-S by auto
moreover
{ fix i :: nat and xs :: 'a list
  have i < length xs ⟹ length xs - Suc i < length xs
    by auto
  then have H: i < length xs ⟹ rev xs ! i ∈ set xs
    using rev-nth[of i xs] unfolding in-set-conv-nth by (force simp add: in-set-conv-nth)
} note H = this
have ∀ i < length rem. rev rem ! i < card (atms-of-ms A) + 2
  using tr-S-le-A length-in-get-all-marked-decomposition-bounded[of - S] unfolding tr-S
  by (force simp add: o-def rem dest!: H intro: length-get-all-marked-decomposition-length)
ultimately show ?case
  using μC-bounded[of rev rem card (atms-of-ms A)+2 unassigned-lit A l] T undef-L
  by (simp add: rem μC-append μC-cons F tr-S)
qed

```

**lemma** *dpll-bj-trail-mes-decreasing-prop:*

**assumes** *dpll*: *dpll-bj S T* **and** *inv*: *inv S* **and**  
*N-A*: *atms-of-mm (clauses<sub>NOT</sub> S) ⊆ atms-of-ms A* **and**  
*M-A*: *atm-of ' lits-of-l (trail S) ⊆ atms-of-ms A* **and**  
*nd*: *no-dup (trail S)* **and**  
*fin-A*: *finite A*

**shows**  $(2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$   
 $- \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } T)$   
 $< (2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$   
 $- \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } S)$

**proof** –

let ?b =  $2 + \text{card } (\text{atms-of-ms } A)$   
let ?s =  $1 + \text{card } (\text{atms-of-ms } A)$

```

let ?μ = μC ?s ?b
have M'-A: atm-of ' lits-of-l (trail T) ⊆ atms-of-ms A
  by (meson M-A N-A dpll dpll-bj-atms-in-trail-in-set inv)
have nd': no-dup (trail T)
  using ⟨dpll-bj S T⟩ dpll-bj-no-dup nd inv by blast
{ fix i :: nat and xs :: 'a list
  have i < length xs ⟹ length xs - Suc i < length xs
    by auto
  then have H: i < length xs ⟹ xs ! i ∈ set xs
    using rev-nth[of i xs] unfolding in-set-conv-nth by (force simp add: in-set-conv-nth)
} note H = this

have l-M-A: length (trail S) ≤ card (atms-of-ms A)
  by (simp add: fin-A M-A card-mono no-dup-length-eq-card-atm-of-lits-of-l nd)
have l-M'-A: length (trail T) ≤ card (atms-of-ms A)
  by (simp add: fin-A M'-A card-mono no-dup-length-eq-card-atm-of-lits-of-l nd')
have l-trail-weight-M: length (trail-weight T) ≤ 1 + card (atms-of-ms A)
  using l-M'-A length-get-all-marked-decomposition-length[of trail T] by auto
have bounded-M: ∀ i < length (trail-weight T). (trail-weight T)! i < card (atms-of-ms A) + 2
  using length-in-get-all-marked-decomposition-bounded[of - T] l-M'-A
  by (metis (no-types, lifting) H Nat.le-trans add-2-eq-Suc' not-le not-less-eq-eq)

from dpll-bj-trail-mes-increasing-prop[OF dpll inv N-A M-A nd fin-A]
have μC ?s ?b (trail-weight S) < μC ?s ?b (trail-weight T) by simp
moreover from μC-bounded[OF bounded-M l-trail-weight-M]
  have μC ?s ?b (trail-weight T) ≤ ?b ^ ?s by auto
ultimately show ?thesis by linarith
qed

```

```

lemma wf-dpll-bj:
  assumes fin: finite A
  shows wf {(T, S). dpll-bj S T
    ∧ atms-of-mm (clausesNOT S) ⊆ atms-of-ms A ∧ atm-of ' lits-of-l (trail S) ⊆ atms-of-ms A
    ∧ no-dup (trail S) ∧ inv S}
  (is wf ?A)
proof (rule wf-bounded-measure[of -
  λ-. (2 + card (atms-of-ms A))^(1 + card (atms-of-ms A))
  λS. μC (1 + card (atms-of-ms A)) (2 + card (atms-of-ms A)) (trail-weight S)])
fix a b :: 'st
let ?b = 2 + card (atms-of-ms A)
let ?s = 1 + card (atms-of-ms A)
let ?μ = μC ?s ?b
assume ab: (b, a) ∈ ?A

have fin-A: finite (atms-of-ms A)
  using fin by auto
have
  dpll-bj: dpll-bj a b and
  N-A: atms-of-mm (clausesNOT a) ⊆ atms-of-ms A and
  M-A: atm-of ' lits-of-l (trail a) ⊆ atms-of-ms A and
  nd: no-dup (trail a) and
  inv: inv a
  using ab by auto

have M'-A: atm-of ' lits-of-l (trail b) ⊆ atms-of-ms A

```

```

  by (meson M-A N-A (dpll-bj a b) dpll-bj-atms-in-trail-in-set inv)
have nd': no-dup (trail b)
  using (dpll-bj a b) dpll-bj-no-dup nd inv by blast
{ fix i :: nat and xs :: 'a list
  have i < length xs  $\implies$  length xs - Suc i < length xs
    by auto
  then have H: i < length xs  $\implies$  xs ! i  $\in$  set xs
    using rev-nth[of i xs] unfolding in-set-conv-nth by (force simp add: in-set-conv-nth)
} note H = this

have l-M-A: length (trail a)  $\leq$  card (atms-of-ms A)
  by (simp add: fin-A M-A card-mono no-dup-length-eq-card-atm-of-lits-of-l nd)
have l-M'-A: length (trail b)  $\leq$  card (atms-of-ms A)
  by (simp add: fin-A M'-A card-mono no-dup-length-eq-card-atm-of-lits-of-l nd')
have l-trail-weight-M: length (trail-weight b)  $\leq$  1 + card (atms-of-ms A)
  using l-M'-A length-get-all-marked-decomposition-length[of trail b] by auto
have bounded-M:  $\forall i < \text{length } (\text{trail-weight } b). (\text{trail-weight } b) ! i < \text{card } (\text{atms-of-ms } A) + 2$ 
  using length-in-get-all-marked-decomposition-bounded[of - b] l-M'-A
  by (metis (no-types, lifting) Nat.le-trans One-nat-def Suc-1 add.right-neutral add-Suc-right
    le-imp-less-Suc less-eq-Suc-le nth-mem)

from dpll-bj-trail-mes-increasing-prop[OF dpll-bj inv N-A M-A nd fin]
have  $\mu_C \text{ ?s ?b } (\text{trail-weight } a) < \mu_C \text{ ?s ?b } (\text{trail-weight } b)$  by simp
moreover from  $\mu_C$ -bounded[OF bounded-M l-trail-weight-M]
  have  $\mu_C \text{ ?s ?b } (\text{trail-weight } b) \leq \text{?b} \wedge \text{?s}$  by auto
ultimately show  $\text{?b} \wedge \text{?s} \leq \text{?b} \wedge \text{?s} \wedge$ 
   $\mu_C \text{ ?s ?b } (\text{trail-weight } b) \leq \text{?b} \wedge \text{?s} \wedge$ 
   $\mu_C \text{ ?s ?b } (\text{trail-weight } a) < \mu_C \text{ ?s ?b } (\text{trail-weight } b)$ 
  by blast
qed

```

### 16.3.4 Normal Forms

We prove that given a normal form of DPLL, with some invariants, the either  $N$  is satisfiable and the built valuation  $M$  is a model; or  $N$  is unsatisfiable.

Idea of the proof: We have to prove that *satisfiable*  $N$ ,  $\neg M \models N$  and there is no remaining step is incompatible.

1. The *decide* rules tells us that every variable in  $N$  has a value.
2.  $\neg M \models N$  tells us that there is conflict.
3. There is at least one decision in the trail (otherwise,  $M$  is a model of  $N$ ).
4. Now if we build the clause with all the decision literals of the trail, we can apply the *backjump* rule.

The assumption are saying that we have a finite upper bound  $A$  for the literals, that we cannot do any step *no-step*  $dpll\text{-}bj\ S$

**theorem** *dpll-backjump-final-state*:

```

fixes A :: 'v literal multiset set and S T :: 'st
assumes
  atms-of-mm (clausesNOT S)  $\subseteq$  atms-of-ms A and
  atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-ms A and

```

```

no-dup (trail S) and
finite A and
inv: inv S and
n-s: no-step dpll-bj S and
decomp: all-decomposition-implies-m (clausesNOT S) (get-all-marked-decomposition (trail S))
shows unsatisfiable (set-mset (clausesNOT S))
  ∨ (trail S ⊨asm clausesNOT S ∧ satisfiable (set-mset (clausesNOT S)))
proof -
let ?N = set-mset (clausesNOT S)
let ?M = trail S
consider
  (sat) satisfiable ?N and ?M ⊨as ?N
| (sat') satisfiable ?N and ¬ ?M ⊨as ?N
| (unsat) unsatisfiable ?N
by auto
then show ?thesis
proof cases
case sat' note sat = this(1) and M = this(2)
obtain C where C ∈ ?N and ¬ ?M ⊨a C using M unfolding true-annots-def by auto
obtain I :: 'v literal set where
  I ⊨s ?N and
  cons: consistent-interp I and
  tot: total-over-m I ?N and
  atm-I-N: atm-of 'I ⊆ atms-of-ms ?N
  using sat unfolding satisfiable-def-min by auto
let ?I = I ∪ {P | P. P ∈ lits-of-l ?M ∧ atm-of P ∉ atm-of 'I}
let ?O = {unmark L | L. is-marked L ∧ L ∈ set ?M ∧ atm-of (lit-of L) ∉ atms-of-ms ?N}
have cons-I': consistent-interp ?I
  using cons using ⟨no-dup ?M⟩ unfolding consistent-interp-def
  by (auto simp add: atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set lits-of-def
    dest!: no-dup-cannot-not-lit-and-uminus)
have tot-I': total-over-m ?I (?N ∪ unmark-l ?M)
  using tot atm-I-N unfolding total-over-m-def total-over-set-def
  by (fastforce simp: image-iff lits-of-def)
have {P | P. P ∈ lits-of-l ?M ∧ atm-of P ∉ atm-of 'I} ⊨s ?O
  using ⟨I ⊨s ?N⟩ atm-I-N by (auto simp add: atm-of-eq-atm-of true-clss-def lits-of-def)
then have I'-N: ?I ⊨s ?N ∪ ?O
  using ⟨I ⊨s ?N⟩ true-clss-union-increase by force
have tot': total-over-m ?I (?N ∪ ?O)
  using atm-I-N tot unfolding total-over-m-def total-over-set-def
  by (force simp: lits-of-def dest!: is-marked-ex-Marked)

have atms-N-M: atms-of-ms ?N ⊆ atm-of ' lits-of-l ?M
proof (rule ccontr)
assume ¬ ?thesis
then obtain l :: 'v where
  l-N: l ∈ atms-of-ms ?N and
  l-M: l ∉ atm-of ' lits-of-l ?M
by auto
have undefined-lit ?M (Pos l)
  using l-M by (metis Marked-Propagated-in-iff-in-lits-of-l
    atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set literal.sel(1))
from bj-decideNOT[OF decideNOT[OF this]] show False
  using l-N n-s by (metis literal.sel(1) state-eqNOT-ref)
qed

```

```

have ?M  $\models_{as}$  CNot C
  apply (rule all-variables-defined-not-imply-cnot)
  using (C  $\in$  set-mset (clausesNOT S))  $\langle \neg$  trail S  $\models_a$  C  $\rangle$ 
    atms-N-M by (auto dest: atms-of-atms-of-ms-mono)
have  $\exists l \in$  set ?M. is-marked l
  proof (rule ccontr)
    let ?O = {unmark L | L. is-marked L  $\wedge$  L  $\in$  set ?M  $\wedge$  atm-of (lit-of L)  $\notin$  atms-of-ms ?N}
    have  $\vartheta[\text{iff}]: \bigwedge I. \text{total-over-m } I \text{ } (?N \cup ?O \cup \text{unmark-l } ?M)$ 
       $\longleftrightarrow \text{total-over-m } I \text{ } (?N \cup \text{unmark-l } ?M)$ 
    unfolding total-over-set-def total-over-m-def atms-of-ms-def by blast
    assume  $\neg$  ?thesis
    then have [simp]: {unmark L | L. is-marked L  $\wedge$  L  $\in$  set ?M}
      = {unmark L | L. is-marked L  $\wedge$  L  $\in$  set ?M  $\wedge$  atm-of (lit-of L)  $\notin$  atms-of-ms ?N}
    by auto
    then have ?N  $\cup$  ?O  $\models_{ps}$  unmark-l ?M
      using all-decomposition-implies-propagated-lits-are-implied[OF decomp] by auto

    then have ?I  $\models_s$  unmark-l ?M
      using cons-I' I'-N tot-I'  $\langle ?I \models_s ?N \cup ?O \rangle$  unfolding  $\vartheta$  true-clss-clss-def by blast
    then have lits-of-l ?M  $\subseteq$  ?I
      unfolding true-clss-def lits-of-def by auto
    then have ?M  $\models_{as}$  ?N
      using I'-N  $\langle C \in ?N \rangle \langle \neg ?M \models_a C \rangle$  cons-I' atms-N-M
      by (meson  $\langle$  trail S  $\models_{as}$  CNot C  $\rangle$  consistent-CNot-not rev-subsetD sup-ge1 true-annot-def
        true-annots-def true-clss-mono-set-mset-l true-clss-def)
    then show False using M by fast
  qed
from List.split-list-first-propE[OF this] obtain K :: 'v literal and
  F F' :: ('v, unit, unit) marked-lit list where
  M-K: ?M = F' @ Marked K () # F and
  nm:  $\forall f \in$  set F'.  $\neg$  is-marked f
  unfolding is-marked-def by (metis (full-types) old.unit.exhaust)
let ?K = Marked K () :: ('v, unit, unit) marked-lit
have ?K  $\in$  set ?M
  unfolding M-K by auto
let ?C = image-mset lit-of {#L $\in$ #mset ?M. is-marked L  $\wedge$  L $\neq$ ?K#} :: 'v literal multiset
let ?C' = set-mset (image-mset ( $\lambda L::$ 'v literal. {#L#}) (?C + unmark ?K))
have ?N  $\cup$  {unmark L | L. is-marked L  $\wedge$  L  $\in$  set ?M}  $\models_{ps}$  unmark-l ?M
  using all-decomposition-implies-propagated-lits-are-implied[OF decomp] .
moreover have C': ?C' = {unmark L | L. is-marked L  $\wedge$  L  $\in$  set ?M}
  unfolding M-K by standard force+
ultimately have N-C-M: ?N  $\cup$  ?C'  $\models_{ps}$  unmark-l ?M
  by auto
have N-M-False: ?N  $\cup$  ( $\lambda L. \text{unmark } L$ ) ' (set ?M)  $\models_{ps}$  {{#}}
  using M  $\langle ?M \models_{as}$  CNot C  $\rangle$   $\langle C \in ?N \rangle$  unfolding true-clss-clss-def true-annots-def Ball-def
    true-annot-def by (metis consistent-CNot-not sup.orderE sup-commute true-clss-def
      true-clss-singleton-lit-of-implies-incl true-clss-union true-clss-union-increase)

have undefined-lit F K using  $\langle$  no-dup ?M  $\rangle$  unfolding M-K by (simp add: defined-lit-map)
moreover
  have ?N  $\cup$  ?C'  $\models_{ps}$  {{#}}
  proof -
    have A: ?N  $\cup$  ?C'  $\cup$  unmark-l ?M = ?N  $\cup$  unmark-l ?M
      unfolding M-K by auto
    show ?thesis

```

```

    using true-clss-clss-left-right[OF N-C-M, of {{#}}] N-M-False unfolding A by auto
  qed
have ?N  $\models_p$  image-mset uminus ?C + {#-K#}
  unfolding true-clss-clss-def true-clss-clss-def total-over-m-def
  proof (intro allI impI)
    fix I
    assume
      tot: total-over-set I (atms-of-ms (?N  $\cup$  {image-mset uminus ?C + {#-K#}})) and
      cons: consistent-interp I and
      I  $\models_s$  ?N
    have (K  $\in$  I  $\wedge$  -K  $\notin$  I)  $\vee$  (-K  $\in$  I  $\wedge$  K  $\notin$  I)
      using cons tot unfolding consistent-interp-def by (cases K) auto
    have {a  $\in$  set (trail S). is-marked a  $\wedge$  a  $\neq$  Marked K ()} =
      set (trail S)  $\cap$  {L. is-marked L  $\wedge$  L  $\neq$  Marked K ()}
    by auto
    then have tot': total-over-set I
      (atm-of 'lit-of ' (set ?M  $\cap$  {L. is-marked L  $\wedge$  L  $\neq$  Marked K ()}))
    using tot by (auto simp add: atms-of-uminus-lit-atm-of-lit-of)
    { fix x :: ('v, unit, unit) marked-lit
      assume
        a3: lit-of x  $\notin$  I and
        a1: x  $\in$  set ?M and
        a4: is-marked x and
        a5: x  $\neq$  Marked K ()
      then have Pos (atm-of (lit-of x))  $\in$  I  $\vee$  Neg (atm-of (lit-of x))  $\in$  I
        using a5 a4 tot' a1 unfolding total-over-set-def atms-of-s-def by blast
      moreover have f6: Neg (atm-of (lit-of x)) = - Pos (atm-of (lit-of x))
        by simp
      ultimately have - lit-of x  $\in$  I
        using f6 a3 by (metis (no-types) atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set
          literal.sel(1))
    } note H = this

    have  $\neg I \models_s ?C'$ 
      using  $\langle ?N \cup ?C' \models_{ps} \{\{\#\}\} \rangle$  tot cons (I  $\models_s$  ?N)
      unfolding true-clss-clss-def total-over-m-def
      by (simp add: atms-of-uminus-lit-atm-of-lit-of atms-of-ms-single-image-atm-of-lit-of)
    then show I  $\models$  image-mset uminus ?C + {#-K#}
      unfolding true-clss-def true-clss-def using  $\langle (K \in I \wedge -K \notin I) \vee (-K \in I \wedge K \notin I) \rangle$ 
      by (auto dest!: H)
  qed
moreover have F  $\models_{as}$  CNot (image-mset uminus ?C)
  using nm unfolding true-annots-def CNot-def M-K by (auto simp add: lits-of-def)
ultimately have False
  using bj-can-jump[of S F' K F C -K
    image-mset uminus (image-mset lit-of {# L :# mset ?M. is-marked L  $\wedge$  L  $\neq$  Marked K ()#})]
     $\langle C \in ?N \rangle$  n-s  $\langle ?M \models_{as} CNot C \rangle$  bj-backjump inv (no-dup (trail S)) unfolding M-K by auto
  then show ?thesis by fast
qed auto
qed
end

locale dpll-with-backjumping =
  dpll-with-backjumping-ops mset-cls insert-cls remove-lit

```

```

mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clssNOT remove-clssNOT inv backjump-conds
propagate-conds
for
  mset-clss :: 'cls  $\Rightarrow$  'v clause and
  insert-clss :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  mset-clss :: 'clss  $\Rightarrow$  'v clauses and
  union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and
  insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  trail :: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and
  raw-clauses :: 'st  $\Rightarrow$  'clss and
  prepend-trail :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and
  tl-trail :: 'st  $\Rightarrow$  'st and
  add-clssNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  remove-clssNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  inv :: 'st  $\Rightarrow$  bool and
  backjump-conds :: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool and
  propagate-conds :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  bool
+
assumes dpll-bj-inv:  $\bigwedge S T. \text{dpll-bj } S T \implies \text{inv } S \implies \text{inv } T$ 
begin

lemma rtranclp-dpll-bj-inv:
  assumes dpll-bj* S T and inv S
  shows inv T
  using assms by (induction rule: rtranclp-induct)
  (auto simp add: dpll-bj-no-dup intro: dpll-bj-inv)

lemma rtranclp-dpll-bj-no-dup:
  assumes dpll-bj* S T and inv S
  and no-dup (trail S)
  shows no-dup (trail T)
  using assms by (induction rule: rtranclp-induct)
  (auto simp add: dpll-bj-no-dup dest: rtranclp-dpll-bj-inv dpll-bj-inv)

lemma rtranclp-dpll-bj-atms-of-ms-clauses-inv:
  assumes
    dpll-bj* S T and inv S
  shows atms-of-mm (clausesNOT S) = atms-of-mm (clausesNOT T)
  using assms by (induction rule: rtranclp-induct)
  (auto dest: rtranclp-dpll-bj-inv dpll-bj-atms-of-ms-clauses-inv)

lemma rtranclp-dpll-bj-atms-in-trail:
  assumes
    dpll-bj* S T and
    inv S and
    atm-of ('(lits-of-l (trail S))  $\subseteq$  atms-of-mm (clausesNOT S))
  shows atm-of ('(lits-of-l (trail T))  $\subseteq$  atms-of-mm (clausesNOT T))
  using assms apply (induction rule: rtranclp-induct)
  using dpll-bj-atms-in-trail dpll-bj-atms-of-ms-clauses-inv rtranclp-dpll-bj-inv by auto

lemma rtranclp-dpll-bj-sat-iff:

```



**assumes**  $dpll\text{-}bj^{**} S T$  **and**  $inv S$   
**shows**  $I \models_{sm} clauses_{NOT} S \longleftrightarrow I \models_{sm} clauses_{NOT} T$   
**using** *assms* **by** (*induction rule: rtranclp-induct*)  
*(auto dest!: dpll-bj-sat-iff simp: rtranclp-dpll-bj-inv)*

**lemma** *rtranclp-dpll-bj-atms-in-trail-in-set:*

**assumes**  
 $dpll\text{-}bj^{**} S T$  **and**  
 $inv S$   
 $atms\text{-}of\text{-}mm (clauses_{NOT} S) \subseteq A$  **and**  
 $atm\text{-}of \text{ ' } (lits\text{-}of\text{-}l (trail S)) \subseteq A$   
**shows**  $atm\text{-}of \text{ ' } (lits\text{-}of\text{-}l (trail T)) \subseteq A$   
**using** *assms* **by** (*induction rule: rtranclp-induct*)  
*(auto dest: rtranclp-dpll-bj-inv*  
*simp: dpll-bj-atms-in-trail-in-set rtranclp-dpll-bj-atms-of-ms-clauses-inv rtranclp-dpll-bj-inv)*

**lemma** *rtranclp-dpll-bj-all-decomposition-implies-inv:*

**assumes**  
 $dpll\text{-}bj^{**} S T$  **and**  
 $inv S$   
 $all\text{-}decomposition\text{-}implies\text{-}m (clauses_{NOT} S) (get\text{-}all\text{-}marked\text{-}decomposition (trail S))$   
**shows**  $all\text{-}decomposition\text{-}implies\text{-}m (clauses_{NOT} T) (get\text{-}all\text{-}marked\text{-}decomposition (trail T))$   
**using** *assms* **by** (*induction rule: rtranclp-induct*)  
*(auto intro: dpll-bj-all-decomposition-implies-inv simp: rtranclp-dpll-bj-inv)*

**lemma** *rtranclp-dpll-bj-inv-incl-dpll-bj-inv-trancl:*

$\{(T, S). dpll\text{-}bj^{++} S T$   
 $\wedge atms\text{-}of\text{-}mm (clauses_{NOT} S) \subseteq atms\text{-}of\text{-}ms A \wedge atm\text{-}of \text{ ' } lits\text{-}of\text{-}l (trail S) \subseteq atms\text{-}of\text{-}ms A$   
 $\wedge no\text{-}dup (trail S) \wedge inv S\}$   
 $\subseteq \{(T, S). dpll\text{-}bj S T \wedge atms\text{-}of\text{-}mm (clauses_{NOT} S) \subseteq atms\text{-}of\text{-}ms A$   
 $\wedge atm\text{-}of \text{ ' } lits\text{-}of\text{-}l (trail S) \subseteq atms\text{-}of\text{-}ms A \wedge no\text{-}dup (trail S) \wedge inv S\}^+$   
*(is ?A  $\subseteq$  ?B<sup>+</sup>)*

**proof** *standard*

**fix**  $x$   
**assume**  $x\text{-}A: x \in ?A$   
**obtain**  $S T::'st$  **where**  
 $x[simp]: x = (T, S)$  **by** (*cases x*) *auto*  
**have**  
 $dpll\text{-}bj^{++} S T$  **and**  
 $atms\text{-}of\text{-}mm (clauses_{NOT} S) \subseteq atms\text{-}of\text{-}ms A$  **and**  
 $atm\text{-}of \text{ ' } lits\text{-}of\text{-}l (trail S) \subseteq atms\text{-}of\text{-}ms A$  **and**  
 $no\text{-}dup (trail S)$  **and**  
 $inv S$   
**using**  $x\text{-}A$  **by** *auto*  
**then show**  $x \in ?B^+$  **unfolding**  $x$   
**proof** (*induction rule: tranclp-induct*)  
**case** *base*  
**then show** *?case* **by** *auto*  
**next**  
**case** (*step T U*) **note**  $step = this(1)$  **and**  $ST = this(2)$  **and**  $IH = this(3)[OF this(4-7)]$   
**and**  $N\text{-}A = this(4)$  **and**  $M\text{-}A = this(5)$  **and**  $nd = this(6)$  **and**  $inv = this(7)$   
  
**have**  $[simp]: atms\text{-}of\text{-}mm (clauses_{NOT} S) = atms\text{-}of\text{-}mm (clauses_{NOT} T)$   
**using** *step rtranclp-dpll-bj-atms-of-ms-clauses-inv tranclp-into-rtranclp inv* **by** *fastforce*  
**have**  $no\text{-}dup (trail T)$

**using** *local.step nd rtrancpl-dpll-bj-no-dup trancpl-into-rtrancpl inv* **by** *fastforce*  
**moreover have** *atm-of ‘ (lits-of-l (trail T))  $\subseteq$  atms-of-ms A*  
**by** (*metis inv M-A N-A local.step rtrancpl-dpll-bj-atms-in-trail-in-set*  
*trancpl-into-rtrancpl*)  
**moreover have** *inv T*  
**using** *inv local.step rtrancpl-dpll-bj-inv trancpl-into-rtrancpl* **by** *fastforce*  
**ultimately have** (*U, T*)  $\in$  *?B* **using** *ST N-A M-A inv* **by** *auto*  
**then show** *?case* **using** *IH* **by** (*rule trancpl-into-trancpl2*)  
**qed**  
**qed**

**lemma** *wf-trancpl-dpll-bj*:  
**assumes** *fin: finite A*  
**shows** *wf {(T, S). dpll-bj<sup>++</sup> S T*  
 $\wedge$  *atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  atms-of-ms A  $\wedge$  atm-of ‘ lits-of-l (trail S)  $\subseteq$  atms-of-ms A*  
 $\wedge$  *no-dup (trail S)  $\wedge$  inv S}*  
**using** *wf-trancpl[OF wf-dpll-bj[OF fin]] rtrancpl-dpll-bj-inv-incl-dpll-bj-inv-trancpl*  
**by** (*rule wf-subset*)

**lemma** *dpll-bj-sat-ext-iff*:  
*dpll-bj S T  $\implies$  inv S  $\implies$  I $\models$ <sub>sextm</sub> clauses<sub>NOT</sub> S  $\longleftrightarrow$  I $\models$ <sub>sextm</sub> clauses<sub>NOT</sub> T*  
**by** (*simp add: dpll-bj-clauses*)

**lemma** *rtrancpl-dpll-bj-sat-ext-iff*:  
*dpll-bj<sup>\*\*</sup> S T  $\implies$  inv S  $\implies$  I $\models$ <sub>sextm</sub> clauses<sub>NOT</sub> S  $\longleftrightarrow$  I $\models$ <sub>sextm</sub> clauses<sub>NOT</sub> T*  
**by** (*induction rule: rtrancpl-induct*) (*simp-all add: rtrancpl-dpll-bj-inv dpll-bj-sat-ext-iff*)

**theorem** *full-dpll-backjump-final-state*:  
**fixes** *A :: ‘v literal multiset set and S T :: ‘st*  
**assumes**  
*full: full dpll-bj S T and*  
*atms-S: atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  atms-of-ms A and*  
*atms-trail: atm-of ‘ lits-of-l (trail S)  $\subseteq$  atms-of-ms A and*  
*n-d: no-dup (trail S) and*  
*finite A and*  
*inv: inv S and*  
*decomp: all-decomposition-implies-m (clauses<sub>NOT</sub> S) (get-all-marked-decomposition (trail S))*  
**shows** *unsatisfiable (set-mset (clauses<sub>NOT</sub> S))*  
 $\vee$  (*trail T  $\models$ <sub>asm</sub> clauses<sub>NOT</sub> S  $\wedge$  satisfiable (set-mset (clauses<sub>NOT</sub> S))*)

**proof** –  
**have** *st: dpll-bj<sup>\*\*</sup> S T and no-step dpll-bj T*  
**using** *full unfolding full-def* **by** *fast+*  
**moreover have** *atms-of-mm (clauses<sub>NOT</sub> T)  $\subseteq$  atms-of-ms A*  
**using** *atms-S inv rtrancpl-dpll-bj-atms-of-ms-clauses-inv st* **by** *blast*  
**moreover have** *atm-of ‘ lits-of-l (trail T)  $\subseteq$  atms-of-ms A*  
**using** *atms-S atms-trail inv rtrancpl-dpll-bj-atms-in-trail-in-set st* **by** *auto*  
**moreover have** *no-dup (trail T)*  
**using** *n-d inv rtrancpl-dpll-bj-no-dup st* **by** *blast*  
**moreover have** *inv: inv T*  
**using** *inv rtrancpl-dpll-bj-inv st* **by** *blast*  
**moreover**  
**have** *decomp: all-decomposition-implies-m (clauses<sub>NOT</sub> T) (get-all-marked-decomposition (trail T))*  
**using** (*inv S*) *decomp rtrancpl-dpll-bj-all-decomposition-implies-inv st* **by** *blast*  
**ultimately have** *unsatisfiable (set-mset (clauses<sub>NOT</sub> T))*  
 $\vee$  (*trail T  $\models$ <sub>asm</sub> clauses<sub>NOT</sub> T  $\wedge$  satisfiable (set-mset (clauses<sub>NOT</sub> T))*)

using  $\langle \text{finite } A \rangle$  *dpll-backjump-final-state* **by** *force*  
 then show *?thesis*  
 by (*meson*  $\langle \text{inv } S \rangle$  *rtranclp-dpll-bj-sat-iff* *satisfiable-carac* *st* *true-annots-true-cls*)  
 qed

**corollary** *full-dpll-backjump-final-state-from-init-state*:

fixes  $A :: 'v$  literal multiset set **and**  $S \ T :: 'st$

assumes

*full*: *full dpll-bj*  $S \ T$  **and**

*trail*  $S = []$  **and**

*clauses*<sub>NOT</sub>  $S = N$  **and**

*inv*  $S$

**shows** *unsatisfiable* (*set-mset*  $N$ )  $\vee$  (*trail*  $T \models_{asm} N \wedge$  *satisfiable* (*set-mset*  $N$ ))

**using** *assms full-dpll-backjump-final-state*[*of*  $S \ T$  *set-mset*  $N$ ] **by** *auto*

**lemma** *tranclp-dpll-bj-trail-mes-decreasing-prop*:

assumes *dpll*: *dpll-bj*<sup>++</sup>  $S \ T$  **and** *inv*: *inv*  $S$  **and**

$N\text{-}A$ : *atms-of-mm* (*clauses*<sub>NOT</sub>  $S$ )  $\subseteq$  *atms-of-ms*  $A$  **and**

$M\text{-}A$ : *atm-of* ' *lits-of-l* (*trail*  $S$ )  $\subseteq$  *atms-of-ms*  $A$  **and**

$n\text{-}d$ : *no-dup* (*trail*  $S$ ) **and**

$fin\text{-}A$ : *finite*  $A$

**shows**  $(2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$   
 $\quad - \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } T)$   
 $\quad < (2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$   
 $\quad - \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } S)$

**using** *dpll*

**proof** (*induction*)

**case** *base*

**then show** *?case*

**using**  $N\text{-}A \ M\text{-}A \ n\text{-}d$  *dpll-bj-trail-mes-decreasing-prop*  $fin\text{-}A \ inv$  **by** *blast*

**next**

**case** (*step*  $T \ U$ ) **note**  $st = \text{this}(1)$  **and** *dpll* = *this*(2) **and** *IH* = *this*(3)

**have** *atms-of-mm* (*clauses*<sub>NOT</sub>  $S$ ) = *atms-of-mm* (*clauses*<sub>NOT</sub>  $T$ )

**using** *rtranclp-dpll-bj-atms-of-ms-clauses-inv* **by** (*metis* *dpll-bj-clauses* *dpll-bj-inv* *inv* *st* *tranclpD*)

**then have**  $N\text{-}A'$ : *atms-of-mm* (*clauses*<sub>NOT</sub>  $T$ )  $\subseteq$  *atms-of-ms*  $A$

**using**  $N\text{-}A$  **by** *auto*

**moreover have**  $M\text{-}A'$ : *atm-of* ' *lits-of-l* (*trail*  $T$ )  $\subseteq$  *atms-of-ms*  $A$

**by** (*meson*  $M\text{-}A \ N\text{-}A \ inv$  *rtranclp-dpll-bj-atms-in-trail-in-set* *st* *dpll*  
*tranclp.r-into-trancl* *tranclp-into-rtranclp* *tranclp-trans*)

**moreover have**  $nd$ : *no-dup* (*trail*  $T$ )

**by** (*metis* *inv*  $n\text{-}d$  *rtranclp-dpll-bj-no-dup* *st* *tranclp-into-rtranclp*)

**moreover have** *inv*  $T$

**by** (*meson* *dpll* *dpll-bj-inv* *inv* *rtranclp-dpll-bj-inv* *st* *tranclp-into-rtranclp*)

**ultimately show** *?case*

**using** *IH* *dpll-bj-trail-mes-decreasing-prop*[*of*  $T \ U \ A$ ] *dpll*  $fin\text{-}A$  **by** *linarith*

qed

end

## 16.4 CDCL

### 16.4.1 Learn and Forget

**locale** *learn-ops* =

*dpll-state* *mset-cls* *insert-cls* *remove-lit*

```

mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clssNOT remove-clssNOT
for
  mset-clss :: 'cls ⇒ 'v clause and
  insert-clss :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and
  mset-clss :: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  trail :: 'st ⇒ ('v, unit, unit) marked-lits and
  raw-clauses :: 'st ⇒ 'clss and
  prepend-trail :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and
  add-clssNOT :: 'cls ⇒ 'st ⇒ 'st and
  remove-clssNOT :: 'cls ⇒ 'st ⇒ 'st +
fixes
  learn-cond :: 'cls ⇒ 'st ⇒ bool
begin
inductive learn :: 'st ⇒ 'st ⇒ bool where
  learnNOT-rule: clausesNOT S ⊨pm mset-cl C ⇒
    atms-of (mset-cl C) ⊆ atms-of-mm (clausesNOT S) ∪ atm-of ' (lits-of-l (trail S)) ⇒
    learn-cond C S ⇒
    T ~ add-clssNOT C S ⇒
    learn S T
inductive-cases learnNOTE: learn S T

lemma learn-μC-stable:
  assumes learn S T and no-dup (trail S)
  shows μC A B (trail-weight S) = μC A B (trail-weight T)
  using assms by (auto elim: learnNOTE)
end

locale forget-ops =
  dpll-state mset-clss insert-clss remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clssNOT remove-clssNOT
for
  mset-clss :: 'cls ⇒ 'v clause and
  insert-clss :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and
  mset-clss :: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  trail :: 'st ⇒ ('v, unit, unit) marked-lits and
  raw-clauses :: 'st ⇒ 'clss and
  prepend-trail :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and
  add-clssNOT :: 'cls ⇒ 'st ⇒ 'st and
  remove-clssNOT :: 'cls ⇒ 'st ⇒ 'st +
fixes
  forget-cond :: 'cls ⇒ 'st ⇒ bool

```

```

begin
inductive forgetNOT :: 'st ⇒ 'st ⇒ bool where
forgetNOT:
  removeAll-mset (mset-cls C)(clausesNOT S) ⊨pm mset-cls C ⇒
  forget-cond C S ⇒
  C !∈! raw-clauses S ⇒
  T ~ remove-clNOT C S ⇒
  forgetNOT S T
inductive-cases forgetNOTE: forgetNOT S T

lemma forget-μC-stable:
  assumes forgetNOT S T
  shows μC A B (trail-weight S) = μC A B (trail-weight T)
  using assms by (auto elim!: forgetNOTE)
end

locale learn-and-forgetNOT =
  learn-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT learn-cond +
  forget-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT forget-cond
for
  mset-cls:: 'cls ⇒ 'v clause and
  insert-cls :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and
  mset-clss:: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  trail :: 'st ⇒ ('v, unit, unit) marked-lits and
  raw-clauses :: 'st ⇒ 'clss and
  prepend-trail :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and
  add-clNOT :: 'cls ⇒ 'st ⇒ 'st and
  remove-clNOT :: 'cls ⇒ 'st ⇒ 'st and
  learn-cond forget-cond :: 'cls ⇒ 'st ⇒ bool
begin
inductive learn-and-forgetNOT :: 'st ⇒ 'st ⇒ bool
where
lf-learn: learn S T ⇒ learn-and-forgetNOT S T |
lf-forget: forgetNOT S T ⇒ learn-and-forgetNOT S T
end

```

#### 16.4.2 Definition of CDCL

```

locale conflict-driven-clause-learning-ops =
  dpll-with-backjumping-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT
  inv backjump-conds propagate-conds +
  learn-and-forgetNOT mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT learn-cond

```

*forget-cond*  
**for**  
*mset-cls* ::  $'cls \Rightarrow 'v \text{ clause}$  **and**  
*insert-cls* ::  $'v \text{ literal} \Rightarrow 'cls \Rightarrow 'cls$  **and**  
*remove-lit* ::  $'v \text{ literal} \Rightarrow 'cls \Rightarrow 'cls$  **and**  
*mset-clss* ::  $'clss \Rightarrow 'v \text{ clauses}$  **and**  
*union-clss* ::  $'clss \Rightarrow 'clss \Rightarrow 'clss$  **and**  
*in-clss* ::  $'cls \Rightarrow 'clss \Rightarrow \text{bool}$  **and**  
*insert-clss* ::  $'cls \Rightarrow 'clss \Rightarrow 'clss$  **and**  
*remove-from-clss* ::  $'cls \Rightarrow 'clss \Rightarrow 'clss$  **and**  
*trail* ::  $'st \Rightarrow ('v, \text{unit}, \text{unit}) \text{ marked-lits}$  **and**  
*raw-clauses* ::  $'st \Rightarrow 'clss$  **and**  
*prepend-trail* ::  $('v, \text{unit}, \text{unit}) \text{ marked-lit} \Rightarrow 'st \Rightarrow 'st$  **and**  
*tl-trail* ::  $'st \Rightarrow 'st$  **and**  
*add-cls<sub>NOT</sub>* ::  $'cls \Rightarrow 'st \Rightarrow 'st$  **and**  
*remove-cls<sub>NOT</sub>* ::  $'cls \Rightarrow 'st \Rightarrow 'st$  **and**  
*inv* ::  $'st \Rightarrow \text{bool}$  **and**  
*backjump-conds* ::  $'v \text{ clause} \Rightarrow 'v \text{ clause} \Rightarrow 'v \text{ literal} \Rightarrow 'st \Rightarrow 'st \Rightarrow \text{bool}$  **and**  
*propagate-conds* ::  $('v, \text{unit}, \text{unit}) \text{ marked-lit} \Rightarrow 'st \Rightarrow \text{bool}$  **and**  
*learn-cond forget-cond* ::  $'cls \Rightarrow 'st \Rightarrow \text{bool}$   
**begin**  
  
**inductive** *cdcl<sub>NOT</sub>* ::  $'st \Rightarrow 'st \Rightarrow \text{bool}$  **for**  $S :: 'st$  **where**  
*c-dpll-bj*:  $\text{dpll-bj } S S' \Longrightarrow \text{cdcl}_{NOT} S S' \mid$   
*c-learn*:  $\text{learn } S S' \Longrightarrow \text{cdcl}_{NOT} S S' \mid$   
*c-forget<sub>NOT</sub>*:  $\text{forget}_{NOT} S S' \Longrightarrow \text{cdcl}_{NOT} S S'$   
  
**lemma** *cdcl<sub>NOT</sub>-all-induct*[*consumes 1, case-names dpll-bj learn forget<sub>NOT</sub>*]:  
**fixes**  $S T :: 'st$   
**assumes** *cdcl<sub>NOT</sub>*  $S T$  **and**  
*dpll*:  $\bigwedge T. \text{dpll-bj } S T \Longrightarrow P S T$  **and**  
*learning*:  
 $\bigwedge C T. \text{clauses}_{NOT} S \models_{pm} \text{mset-cls } C \Longrightarrow$   
 $\text{atms-of } (\text{mset-cls } C) \subseteq \text{atms-of-mm } (\text{clauses}_{NOT} S) \cup \text{atm-of } '(\text{lits-of-l } (\text{trail } S)) \Longrightarrow$   
 $T \sim \text{add-cls}_{NOT} C S \Longrightarrow$   
 $P S T$  **and**  
*forgetting*:  $\bigwedge C T. \text{removeAll-mset } (\text{mset-cls } C) (\text{clauses}_{NOT} S) \models_{pm} \text{mset-cls } C \Longrightarrow$   
 $C !\in! \text{raw-clauses } S \Longrightarrow$   
 $T \sim \text{remove-cls}_{NOT} C S \Longrightarrow$   
 $P S T$   
**shows**  $P S T$   
**using** *assms*(1) **by** (*induction rule*: *cdcl<sub>NOT</sub>.induct*)  
(*auto intro*: *assms*(2, 3, 4) *elim!*: *learn<sub>NOT</sub>E forget<sub>NOT</sub>E*)**+**  
  
**lemma** *cdcl<sub>NOT</sub>-no-dup*:  
**assumes**  
 $\text{cdcl}_{NOT} S T$  **and**  
*inv*  $S$  **and**  
*no-dup* (*trail*  $S$ )  
**shows** *no-dup* (*trail*  $T$ )  
**using** *assms* **by** (*induction rule*: *cdcl<sub>NOT</sub>-all-induct*) (*auto intro*: *dpll-bj-no-dup*)  
  
**Consistency of the trail** **lemma** *cdcl<sub>NOT</sub>-consistent*:  
**assumes**  
 $\text{cdcl}_{NOT} S T$  **and**

```

  inv S and
  no-dup (trail S)
shows consistent-interp (lits-of-l (trail T))
using cdclNOT-no-dup[OF assms] distinct-consistent-interp by fast

```

The subtle problem here is that tautologies can be removed, meaning that some variable can disappear of the problem. It is also possible that some variable of the trail are not in the clauses anymore.

```

lemma cdclNOT-atms-of-ms-clauses-decreasing:
  assumes cdclNOT S T and inv S and no-dup (trail S)
  shows atms-of-mm (clausesNOT T)  $\subseteq$  atms-of-mm (clausesNOT S)  $\cup$  atm-of ' (lits-of-l (trail S))
  using assms by (induction rule: cdclNOT-all-induct)
  (auto dest!: dpll-bj-atms-of-ms-clauses-inv set-mp simp add: atms-of-ms-def Union-eq)

```

```

lemma cdclNOT-atms-in-trail:
  assumes cdclNOT S T and inv S and no-dup (trail S)
  and atm-of ' (lits-of-l (trail S))  $\subseteq$  atms-of-mm (clausesNOT S)
  shows atm-of ' (lits-of-l (trail T))  $\subseteq$  atms-of-mm (clausesNOT S)
  using assms by (induction rule: cdclNOT-all-induct) (auto simp add: dpll-bj-atms-in-trail)

```

```

lemma cdclNOT-atms-in-trail-in-set:
  assumes
    cdclNOT S T and inv S and no-dup (trail S) and
    atms-of-mm (clausesNOT S)  $\subseteq$  A and
    atm-of ' (lits-of-l (trail S))  $\subseteq$  A
  shows atm-of ' (lits-of-l (trail T))  $\subseteq$  A
  using assms
  by (induction rule: cdclNOT-all-induct)
  (simp-all add: dpll-bj-atms-in-trail-in-set dpll-bj-atms-of-ms-clauses-inv)

```

```

lemma cdclNOT-all-decomposition-implies:
  assumes cdclNOT S T and inv S and n-d[simp]: no-dup (trail S) and
    all-decomposition-implies-m (clausesNOT S) (get-all-marked-decomposition (trail S))
  shows
    all-decomposition-implies-m (clausesNOT T) (get-all-marked-decomposition (trail T))
  using assms(1,2,4)
proof (induction rule: cdclNOT-all-induct)
  case dpll-bj
  then show ?case
    using dpll-bj-all-decomposition-implies-inv n-d by blast
next
  case learn
  then show ?case by (auto simp add: all-decomposition-implies-def)
next
  case (forgetNOT C T) note cls-C = this(1) and C = this(2) and T = this(3) and inv = this(4)
  and
    decomp = this(5)
  show ?case
    unfolding all-decomposition-implies-def Ball-def
    proof (intro allI, clarify)
      fix a b
      assume (a, b)  $\in$  set (get-all-marked-decomposition (trail T))
      then have unmark-l a  $\cup$  set-mset (clausesNOT S)  $\models_{ps}$  unmark-l b
        using decomp T by (auto simp add: all-decomposition-implies-def)
      moreover

```

```

  have a1:mset-cls  $C \in \text{set-mset } (\text{clauses}_{NOT} S)$ 
    using  $C$  by blast
  have  $\text{clauses}_{NOT} T = \text{clauses}_{NOT} (\text{remove-cls}_{NOT} C S)$ 
    using  $T$  state-eq $_{NOT}$ -clauses by blast
  then have  $\text{set-mset } (\text{clauses}_{NOT} T) \models_{ps} \text{set-mset } (\text{clauses}_{NOT} S)$ 
    using a1 by (metis (no-types) clauses-remove-cls $_{NOT}$  cls- $C$  insert-Diff order-refl
      set-mset-minus-replicate-mset(1) true-clss-clss-def true-clss-clss-insert)
  ultimately show  $\text{unmark-l } a \cup \text{set-mset } (\text{clauses}_{NOT} T)$ 
     $\models_{ps} \text{unmark-l } b$ 
    using true-clss-clss-generalise-true-clss-clss by blast
qed
qed

```

**Extension of models** lemma  $\text{cdcl}_{NOT}\text{-bj-sat-ext-iff}$ :

```

  assumes  $\text{cdcl}_{NOT} S$  T and  $\text{inv } S$  and  $n\text{-d: no-dup } (\text{trail } S)$ 
  shows  $I \models_{\text{sextm}} \text{clauses}_{NOT} S \longleftrightarrow I \models_{\text{sextm}} \text{clauses}_{NOT} T$ 
  using assms
proof (induction rule:cdcl $_{NOT}$ -all-induct)
  case dpll-bj
  then show ?case by (simp add: dpll-bj-clauses)
next
  case (learn  $C T$ ) note  $T = \text{this}(3)$ 
  { fix  $J$ 
    assume
       $I \models_{\text{sextm}} \text{clauses}_{NOT} S$  and
       $I \subseteq J$  and
       $\text{tot: total-over-m } J (\text{set-mset } (\{\# \text{mset-cls } C\} + \text{clauses}_{NOT} S))$  and
       $\text{cons: consistent-interp } J$ 
    then have  $J \models_{sm} \text{clauses}_{NOT} S$  unfolding true-clss-ext-def by auto

    moreover
      with  $\langle \text{clauses}_{NOT} S \models_{pm} \text{mset-cls } C \rangle$  have  $J \models \text{mset-cls } C$ 
      using tot cons unfolding true-clss-clss-def by auto
    ultimately have  $J \models_{sm} \{\# \text{mset-cls } C\} + \text{clauses}_{NOT} S$  by auto
  }
  then have  $H: I \models_{\text{sextm}} (\text{clauses}_{NOT} S) \implies I \models_{\text{sext}} \text{insert } (\text{mset-cls } C) (\text{set-mset } (\text{clauses}_{NOT} S))$ 
    unfolding true-clss-ext-def by auto
  show ?case
    apply standard
    using  $T$  n-d apply (auto simp add:  $H$ )[]
    using  $T$  n-d apply simp
    by (metis Diff-insert-absorb insert-subset subsetI subset-antisym
      true-clss-ext-decrease-right-remove-r)
next
  case (forget $_{NOT} C T$ ) note  $\text{cls-}C = \text{this}(1)$  and  $T = \text{this}(3)$ 
  { fix  $J$ 
    assume
       $I \models_{\text{sext}} \text{set-mset } (\text{clauses}_{NOT} S) - \{\text{mset-cls } C\}$  and
       $I \subseteq J$  and
       $\text{tot: total-over-m } J (\text{set-mset } (\text{clauses}_{NOT} S))$  and
       $\text{cons: consistent-interp } J$ 
    then have  $J \models_s \text{set-mset } (\text{clauses}_{NOT} S) - \{\text{mset-cls } C\}$ 
      unfolding true-clss-ext-def by (meson Diff-subset total-over-m-subset)

    moreover

```



```

with cls-C have  $J \models \text{mset-cls } C$ 
  using tot cons unfolding true-clss-clss-def
  by (metis Un-commute forgetNOT.hyps(2) in-clss-mset-clss insert-Diff insert-is-Un order-refl
    set-mset-minus-replicate-mset(1))
  ultimately have  $J \models_{sm} (\text{clauses}_{NOT} S)$  by (metis insert-Diff-single true-clss-insert)
}
then have  $H: I \models_{sext} \text{set-mset} (\text{clauses}_{NOT} S) - \{\text{mset-cls } C\} \implies I \models_{sextm} (\text{clauses}_{NOT} S)$ 
  unfolding true-clss-ext-def by blast
show ?case using T by (auto simp: true-clss-ext-decrease-right-remove-r H)
qed

```

**end** — end of *conflict-driven-clause-learning-ops*

## 16.5 CDCL with invariant

```

locale conflict-driven-clause-learning =
  conflict-driven-clause-learning-ops +
  assumes cdclNOT-inv:  $\bigwedge S T. \text{cdcl}_{NOT} S T \implies \text{inv } S \implies \text{inv } T$ 
begin
sublocale dpll-with-backjumping
  apply unfold-locales
  using cdclNOT.simps cdclNOT-inv by auto

lemma rtranclp-cdclNOT-inv:
   $\text{cdcl}_{NOT}^{**} S T \implies \text{inv } S \implies \text{inv } T$ 
  by (induction rule: rtranclp-induct) (auto simp add: cdclNOT-inv)

lemma rtranclp-cdclNOT-no-dup:
  assumes  $\text{cdcl}_{NOT}^{**} S T$  and  $\text{inv } S$ 
  and no-dup (trail S)
  shows no-dup (trail T)
  using assms by (induction rule: rtranclp-induct) (auto intro: cdclNOT-no-dup rtranclp-cdclNOT-inv)

lemma rtranclp-cdclNOT-trail-clauses-bound:
  assumes
    cdcl:  $\text{cdcl}_{NOT}^{**} S T$  and
    inv:  $\text{inv } S$  and
    n-d: no-dup (trail S) and
    atms-clauses-S:  $\text{atms-of-mm} (\text{clauses}_{NOT} S) \subseteq A$  and
    atms-trail-S:  $\text{atm-of } (\text{lits-of-l } (\text{trail } S)) \subseteq A$ 
  shows  $\text{atm-of } (\text{lits-of-l } (\text{trail } T)) \subseteq A \wedge \text{atms-of-mm} (\text{clauses}_{NOT} T) \subseteq A$ 
  using cdcl
proof (induction rule: rtranclp-induct)
  case base
  then show ?case using atms-clauses-S atms-trail-S by simp
next
  case (step T U) note  $st = \text{this}(1)$  and  $\text{cdcl}_{NOT} = \text{this}(2)$  and  $IH = \text{this}(3)$ 
  have  $\text{inv } T$  using  $\text{inv } st$  rtranclp-cdclNOT-inv by blast
  have no-dup (trail T)
    using rtranclp-cdclNOT-no-dup[of S T]  $st \text{cdcl}_{NOT} \text{inv } n-d$  by blast
  then have  $\text{atms-of-mm} (\text{clauses}_{NOT} U) \subseteq A$ 
    using cdclNOT-atms-of-ms-clauses-decreasing[OF cdclNOT]  $IH \text{ } n-d \langle \text{inv } T \rangle$  by fast
  moreover
    have  $\text{atm-of } (\text{lits-of-l } (\text{trail } U)) \subseteq A$ 
      using cdclNOT-atms-in-trail-in-set[OF cdclNOT, of A]  $\langle \text{no-dup } (\text{trail } T) \rangle$ 
      by (meson atms-trail-S atms-clauses-S IH  $\langle \text{inv } T \rangle \text{cdcl}_{NOT}$ )

```

ultimately show ?case by fast  
qed

**lemma** *rtranclp-cdcl<sub>NOT</sub>-all-decomposition-implies*:  
**assumes** *cdcl<sub>NOT</sub>\*\* S T and inv S and no-dup (trail S) and*  
*all-decomposition-implies-m (clauses<sub>NOT</sub> S) (get-all-marked-decomposition (trail S))*  
**shows**  
*all-decomposition-implies-m (clauses<sub>NOT</sub> T) (get-all-marked-decomposition (trail T))*  
**using** *assms by (induction)*  
*(auto intro: rtranclp-cdcl<sub>NOT</sub>-inv cdcl<sub>NOT</sub>-all-decomposition-implies rtranclp-cdcl<sub>NOT</sub>-no-dup)*

**lemma** *rtranclp-cdcl<sub>NOT</sub>-bj-sat-ext-iff*:  
**assumes** *cdcl<sub>NOT</sub>\*\* S T and inv S and no-dup (trail S)*  
**shows** *I|=sextm clauses<sub>NOT</sub> S  $\longleftrightarrow$  I|=sextm clauses<sub>NOT</sub> T*  
**using** *assms apply (induction rule: rtranclp-induct)*  
**using** *cdcl<sub>NOT</sub>-bj-sat-ext-iff by (auto intro: rtranclp-cdcl<sub>NOT</sub>-inv rtranclp-cdcl<sub>NOT</sub>-no-dup)*

**definition** *cdcl<sub>NOT</sub>-NOT-all-inv where*  
*cdcl<sub>NOT</sub>-NOT-all-inv A S  $\longleftrightarrow$  (finite A  $\wedge$  inv S  $\wedge$  atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  atms-of-ms A*  
 *$\wedge$  atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-ms A  $\wedge$  no-dup (trail S))*

**lemma** *cdcl<sub>NOT</sub>-NOT-all-inv*:  
**assumes** *cdcl<sub>NOT</sub>\*\* S T and cdcl<sub>NOT</sub>-NOT-all-inv A S*  
**shows** *cdcl<sub>NOT</sub>-NOT-all-inv A T*  
**using** *assms unfolding cdcl<sub>NOT</sub>-NOT-all-inv-def*  
**by** *(simp add: rtranclp-cdcl<sub>NOT</sub>-inv rtranclp-cdcl<sub>NOT</sub>-no-dup rtranclp-cdcl<sub>NOT</sub>-trail-clauses-bound)*

**abbreviation** *learn-or-forget where*  
*learn-or-forget S T  $\equiv$  learn S T  $\vee$  forget<sub>NOT</sub> S T*

**lemma** *rtranclp-learn-or-forget-cdcl<sub>NOT</sub>*:  
*learn-or-forget\*\* S T  $\implies$  cdcl<sub>NOT</sub>\*\* S T*  
**using** *rtranclp-mono[of learn-or-forget cdcl<sub>NOT</sub>] by (blast intro: cdcl<sub>NOT</sub>.c-learn cdcl<sub>NOT</sub>.c-forget<sub>NOT</sub>)*

**lemma** *learn-or-forget-dpll- $\mu_C$* :  
**assumes**  
*l-f: learn-or-forget\*\* S T and*  
*dpll: dpll-bj T U and*  
*inv: cdcl<sub>NOT</sub>-NOT-all-inv A S*  
**shows** *(2+card (atms-of-ms A))  $\wedge$  (1+card (atms-of-ms A))*  
 *$- \mu_C$  (1+card (atms-of-ms A)) (2+card (atms-of-ms A)) (trail-weight U)*  
 *$<$  (2+card (atms-of-ms A))  $\wedge$  (1+card (atms-of-ms A))*  
 *$- \mu_C$  (1+card (atms-of-ms A)) (2+card (atms-of-ms A)) (trail-weight S)*  
*(is ? $\mu$  U  $<$  ? $\mu$  S)*

**proof** –  
**have** *? $\mu$  S = ? $\mu$  T*  
**using** *l-f*  
**proof** *(induction)*  
**case** *base*  
**then show** ?case **by** *simp*  
**next**  
**case** *(step T U)*  
**moreover then have** *no-dup (trail T)*  
**using** *rtranclp-cdcl<sub>NOT</sub>-no-dup[of S T] cdcl<sub>NOT</sub>-NOT-all-inv-def inv*  
*rtranclp-learn-or-forget-cdcl<sub>NOT</sub> by auto*

**ultimately show** *?case*  
 using *forget- $\mu_C$ -stable learn- $\mu_C$ -stable inv* **unfolding** *cdcl<sub>NOT</sub>-NOT-all-inv-def* **by** *presburger*  
**qed**  
**moreover have** *cdcl<sub>NOT</sub>-NOT-all-inv A T*  
 using *rtrancp-learn-or-forget-cdcl<sub>NOT</sub> cdcl<sub>NOT</sub>-NOT-all-inv l-f inv* **by** *blast*  
**ultimately show** *?thesis*  
 using *dpll-bj-trail-mes-decreasing-prop[of T U A, OF dpll] finite*  
**unfolding** *cdcl<sub>NOT</sub>-NOT-all-inv-def* **by** *presburger*  
**qed**

**lemma** *infinite-cdcl<sub>NOT</sub>-exists-learn-and-forget-infinite-chain:*

**assumes**  
 $\bigwedge i. \text{cdcl}_{NOT} (f i) (f (\text{Suc } i))$  **and**  
*inv: cdcl<sub>NOT</sub>-NOT-all-inv A (f 0)*  
**shows**  $\exists j. \forall i \geq j. \text{learn-or-forget} (f i) (f (\text{Suc } i))$   
**using** *assms*  
**proof** (*induction (2+card (atms-of-ms A))  $\wedge$  (1+card (atms-of-ms A))*  
 $- \mu_C (1+\text{card} (\text{atms-of-ms } A)) (2+\text{card} (\text{atms-of-ms } A)) (\text{trail-weight } (f 0))$   
*arbitrary: f*  
*rule: nat-less-induct-case*)  
**case** (*Suc n*) **note** *IH = this(1)* **and**  $\mu = \text{this}(2)$  **and** *cdcl<sub>NOT</sub> = this(3)* **and** *inv = this(4)*  
**consider**  
 $(\text{dpll-end}) \exists j. \forall i \geq j. \text{learn-or-forget} (f i) (f (\text{Suc } i))$   
 $| (\text{dpll-more}) \neg(\exists j. \forall i \geq j. \text{learn-or-forget} (f i) (f (\text{Suc } i)))$   
**by** *blast*  
**then show** *?case*  
**proof** *cases*  
**case** *dpll-end*  
**then show** *?thesis* **by** *auto*  
**next**  
**case** *dpll-more*  
**then have**  $j: \exists i. \neg \text{learn} (f i) (f (\text{Suc } i)) \wedge \neg \text{forget}_{NOT} (f i) (f (\text{Suc } i))$   
**by** *blast*  
**obtain** *i* **where**  
 $\neg \text{learn} (f i) (f (\text{Suc } i)) \wedge \neg \text{forget}_{NOT} (f i) (f (\text{Suc } i))$  **and**  
 $\forall k < i. \text{learn-or-forget} (f k) (f (\text{Suc } k))$   
**proof**  $-$   
**obtain**  $i_0$  **where**  $\neg \text{learn} (f i_0) (f (\text{Suc } i_0)) \wedge \neg \text{forget}_{NOT} (f i_0) (f (\text{Suc } i_0))$   
**using** *j* **by** *auto*  
**then have**  $\{i. i \leq i_0 \wedge \neg \text{learn} (f i) (f (\text{Suc } i)) \wedge \neg \text{forget}_{NOT} (f i) (f (\text{Suc } i))\} \neq \{\}$   
**by** *auto*  
**let**  $?I = \{i. i \leq i_0 \wedge \neg \text{learn} (f i) (f (\text{Suc } i)) \wedge \neg \text{forget}_{NOT} (f i) (f (\text{Suc } i))\}$   
**let**  $?i = \text{Min } ?I$   
**have** *finite ?I*  
**by** *auto*  
**have**  $\neg \text{learn} (f ?i) (f (\text{Suc } ?i)) \wedge \neg \text{forget}_{NOT} (f ?i) (f (\text{Suc } ?i))$   
**using** *Min-in[OF (finite ?I) (?I  $\neq$  {})]* **by** *auto*  
**moreover have**  $\forall k < ?i. \text{learn-or-forget} (f k) (f (\text{Suc } k))$   
**using** *Min.coboundedI[of {i. i  $\leq$  i<sub>0</sub>  $\wedge$   $\neg$  learn (f i) (f (Suc i))  $\wedge$   $\neg$  forget<sub>NOT</sub> (f i) (f (Suc i))}, simplified]*  
**by** (*meson ( $\neg$  learn (f i<sub>0</sub>) (f (Suc i<sub>0</sub>))  $\wedge$   $\neg$  forget<sub>NOT</sub> (f i<sub>0</sub>) (f (Suc i<sub>0</sub>))) less-imp-le dual-order.trans not-le*)  
**ultimately show** *?thesis* **using** *that* **by** *blast*  
**qed**  
**def** *g*  $\equiv \lambda n. f (n + \text{Suc } i)$

```

have dpll-bj (f i) (g 0)
  using  $\neg \text{learn } (f i) (f (Suc i)) \wedge \neg \text{forget}_{NOT} (f i) (f (Suc i)) \rangle \text{cdcl}_{NOT} \text{cdcl}_{NOT}.cases$ 
  g-def by auto
{
  fix j
  assume  $j \leq i$ 
  then have learn-or-forget** (f 0) (f j)
    apply (induction j)
    apply simp
    by (metis (no-types, lifting) Suc-leD Suc-le-lessD rtrancpl.simps
       $\langle \forall k < i. \text{learn } (f k) (f (Suc k)) \vee \text{forget}_{NOT} (f k) (f (Suc k)) \rangle$ )
  }
then have learn-or-forget** (f 0) (f i) by blast
then have  $(2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$ 
   $- \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } (g 0))$ 
 $< (2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$ 
   $- \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } (f 0))$ 
  using learn-or-forget-dpll- $\mu_C[\text{of } f 0 f i g 0 A]$  inv  $\langle \text{dpll-bj } (f i) (g 0) \rangle$ 
  unfolding cdclNOT-NOT-all-inv-def by linarith

moreover have cdclNOT-i: cdclNOT** (f 0) (g 0)
  using rtrancpl-learn-or-forget-cdclNOT[of f 0 f i]  $\langle \text{learn-or-forget** } (f 0) (f i) \rangle$ 
  cdclNOT[of i] unfolding g-def by auto
moreover have  $\bigwedge i. \text{cdcl}_{NOT} (g i) (g (Suc i))$ 
  using cdclNOT g-def by auto
moreover have cdclNOT-NOT-all-inv A (g 0)
  using inv cdclNOT-i rtrancpl-cdclNOT-trail-clauses-bound g-def cdclNOT-NOT-all-inv by auto
ultimately obtain j where  $j: \bigwedge i. i \geq j \implies \text{learn-or-forget } (g i) (g (Suc i))$ 
  using IH unfolding  $\mu[\text{symmetric}]$  by presburger
show ?thesis
proof
{
  fix k
  assume  $k \geq j + Suc i$ 
  then have learn-or-forget (f k) (f (Suc k))
    using j[of k-Suc i] unfolding g-def by auto
  }
  then show  $\forall k \geq j + Suc i. \text{learn-or-forget } (f k) (f (Suc k))$ 
    by auto
qed
qed
next
case 0 note H = this(1) and cdclNOT = this(2) and inv = this(3)
show ?case
proof (rule ccontr)
  assume  $\neg ?case$ 
  then have  $j: \exists i. \neg \text{learn } (f i) (f (Suc i)) \wedge \neg \text{forget}_{NOT} (f i) (f (Suc i))$ 
    by blast
  obtain i where
     $\neg \text{learn } (f i) (f (Suc i)) \wedge \neg \text{forget}_{NOT} (f i) (f (Suc i))$  and
     $\forall k < i. \text{learn-or-forget } (f k) (f (Suc k))$ 
  proof -
    obtain i0 where  $\neg \text{learn } (f i_0) (f (Suc i_0)) \wedge \neg \text{forget}_{NOT} (f i_0) (f (Suc i_0))$ 
      using j by auto
    then have  $\{i. i \leq i_0 \wedge \neg \text{learn } (f i) (f (Suc i)) \wedge \neg \text{forget}_{NOT} (f i) (f (Suc i))\} \neq \{\}$ 

```

```

    by auto
  let ?I = {i. i ≤ i0 ∧ ¬ learn (f i) (f (Suc i)) ∧ ¬ forgetNOT (f i) (f (Suc i))}
  let ?i = Min ?I
  have finite ?I
    by auto
  have ¬ learn (f ?i) (f (Suc ?i)) ∧ ¬ forgetNOT (f ?i) (f (Suc ?i))
    using Min-in[OF ⟨finite ?I⟩ ⟨?I ≠ {}⟩] by auto
  moreover have ∀ k < ?i. learn-or-forget (f k) (f (Suc k))
    using Min.coboundedI[of {i. i ≤ i0 ∧ ¬ learn (f i) (f (Suc i)) ∧ ¬ forgetNOT (f i) (f (Suc i))}, simplified]
    by (meson (¬ learn (f i0) (f (Suc i0)) ∧ ¬ forgetNOT (f i0) (f (Suc i0))) less-imp-le dual-order.trans not-le)
  ultimately show ?thesis using that by blast
qed
have dpll-bj (f i) (f (Suc i))
  using (¬ learn (f i) (f (Suc i)) ∧ ¬ forgetNOT (f i) (f (Suc i))) cdclNOT cdclNOT.cases
  by blast
{
  fix j
  assume j ≤ i
  then have learn-or-forget** (f 0) (f j)
    apply (induction j)
    apply simp
    by (metis (no-types, lifting) Suc-leD Suc-le-lessD rtranclp.simps
      ⟨∀ k < i. learn (f k) (f (Suc k)) ∨ forgetNOT (f k) (f (Suc k))⟩)
}
then have learn-or-forget** (f 0) (f i) by blast

then show False
  using learn-or-forget-dpll-μC[of f 0 f i f (Suc i) A] inv 0
  ⟨dpll-bj (f i) (f (Suc i))⟩ unfolding cdclNOT-NOT-all-inv-def by linarith
qed
qed

lemma wf-cdclNOT-no-learn-and-forget-infinite-chain:
  assumes
    no-infinite-lf: ∧ f j. ¬ (∀ i ≥ j. learn-or-forget (f i) (f (Suc i)))
  shows wf {(T, S). cdclNOT S T ∧ cdclNOT-NOT-all-inv A S} (is wf {(T, S). cdclNOT S T ∧ ?inv S})
  unfolding wf-iff-no-infinite-down-chain
proof (rule ccontr)
  assume ¬ (∃ f. ∀ i. (f (Suc i), f i) ∈ {(T, S). cdclNOT S T ∧ ?inv S})
  then obtain f where
    ∀ i. cdclNOT (f i) (f (Suc i)) ∧ ?inv (f i)
    by fast
  then have ∃ j. ∀ i ≥ j. learn-or-forget (f i) (f (Suc i))
    using infinite-cdclNOT-exists-learn-and-forget-infinite-chain[of f] by meson
  then show False using no-infinite-lf by blast
qed

lemma inv-and-tranclp-cdclNOT-tranclp-cdclNOT-and-inv:
  cdclNOT++ S T ∧ cdclNOT-NOT-all-inv A S ⟷ (λ S T. cdclNOT S T ∧ cdclNOT-NOT-all-inv A S)++ S T
  (is ?A ∧ ?I ⟷ ?B)
proof

```

```

assume ?A ∧ ?I
then have ?A and ?I by blast+
then show ?B
  apply induction
    apply (simp add: tranclp.r-into-trancl)
    by (subst tranclp.simps) (auto intro: cdclNOT-NOT-all-inv tranclp-into-rtranclp)
next
  assume ?B
  then have ?A by induction auto
  moreover have ?I using ⟨?B⟩ tranclpD by fastforce
  ultimately show ?A ∧ ?I by blast
qed

```

**lemma** *wf-tranclp-cdcl<sub>NOT</sub>-no-learn-and-forget-infinite-chain*:

```

assumes
  no-infinite-lf:  $\bigwedge f j. \neg (\forall i \geq j. \text{learn-or-forget } (f \ i) \ (f \ (\text{Suc } i)))$ 
shows wf  $\{(T, S). \text{cdcl}_{\text{NOT}}^{++} S \ T \wedge \text{cdcl}_{\text{NOT}}\text{-NOT-all-inv } A \ S\}$ 
using wf-trancl[OF wf-cdclNOT-no-learn-and-forget-infinite-chain[OF no-infinite-lf]]
apply (rule wf-subset)
by (auto simp: trancl-set-tranclp inv-and-tranclp-cdclNOT-tranclp-cdclNOT-and-inv)

```

**lemma** *cdcl<sub>NOT</sub>-final-state*:

```

assumes
  n-s: no-step cdclNOT S and
  inv: cdclNOT-NOT-all-inv A S and
  decomp: all-decomposition-implies-m (clausesNOT S) (get-all-marked-decomposition (trail S))
shows unsatisfiable (set-mset (clausesNOT S))
   $\vee (\text{trail } S \models_{\text{asm}} \text{clauses}_{\text{NOT}} S \wedge \text{satisfiable } (\text{set-mset } (\text{clauses}_{\text{NOT}} S)))$ 

```

**proof** –

```

have n-s': no-step dpll-bj S
  using n-s by (auto simp: cdclNOT.simps)
show ?thesis
  apply (rule dpll-backjump-final-state[of S A])
  using inv decomp n-s' unfolding cdclNOT-NOT-all-inv-def by auto

```

**qed**

**lemma** *full-cdcl<sub>NOT</sub>-final-state*:

```

assumes
  full: full cdclNOT S T and
  inv: cdclNOT-NOT-all-inv A S and
  n-d: no-dup (trail S) and
  decomp: all-decomposition-implies-m (clausesNOT S) (get-all-marked-decomposition (trail S))
shows unsatisfiable (set-mset (clausesNOT T))
   $\vee (\text{trail } T \models_{\text{asm}} \text{clauses}_{\text{NOT}} T \wedge \text{satisfiable } (\text{set-mset } (\text{clauses}_{\text{NOT}} T)))$ 

```

**proof** –

```

have st: cdclNOT** S T and n-s: no-step cdclNOT T
  using full unfolding full-def by blast+
have n-s': cdclNOT-NOT-all-inv A T
  using cdclNOT-NOT-all-inv inv st by blast
moreover have all-decomposition-implies-m (clausesNOT T) (get-all-marked-decomposition (trail T))
  using cdclNOT-NOT-all-inv-def decomp inv rtranclp-cdclNOT-all-decomposition-implies st by auto
ultimately show ?thesis
  using cdclNOT-final-state n-s by blast

```

**qed**

**end** — end of *conflict-driven-clause-learning*

## 16.6 Termination

### 16.6.1 Restricting learn and forget

**locale** *conflict-driven-clause-learning-learning-before-backjump-only-distinct-learn* =  
*dpll-state mset-cls insert-cls remove-lit*  
*mset-clss union-clss in-clss insert-clss remove-from-clss*  
*trail raw-clauses prepend-trail tl-trail add-cls<sub>NOT</sub> remove-cls<sub>NOT</sub> +*  
*conflict-driven-clause-learning mset-cls insert-cls remove-lit*  
*mset-clss union-clss in-clss insert-clss remove-from-clss*  
*trail raw-clauses prepend-trail tl-trail add-cls<sub>NOT</sub> remove-cls<sub>NOT</sub>*  
*inv backjump-conds propagate-conds*  
 $\lambda C S. \text{distinct-mset } (mset\text{-cls } C) \wedge \neg \text{tautology } (mset\text{-cls } C) \wedge \text{learn-restrictions } C S \wedge$   
 $(\exists F K d F' C' L. \text{trail } S = F' @ \text{Marked } K () \# F \wedge mset\text{-cls } C = C' + \{\#L\# \} \wedge F \models_{as} CNot$   
 $C'$   
 $\wedge C' + \{\#L\# \} \notin \# \text{clauses}_{NOT} S)$   
 $\lambda C S. \neg (\exists F' F K d L. \text{trail } S = F' @ \text{Marked } K () \# F \wedge F \models_{as} CNot (\text{remove1-mset } L (mset\text{-cls}$   
 $C)))$   
 $\wedge \text{forget-restrictions } C S$   
**for**  
*mset-cls:: 'cls  $\Rightarrow$  'v clause and*  
*insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and*  
*remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and*  
*mset-clss:: 'clss  $\Rightarrow$  'v clauses and*  
*union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and*  
*insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*trail :: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and*  
*raw-clauses :: 'st  $\Rightarrow$  'clss and*  
*prepend-trail :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*tl-trail :: 'st  $\Rightarrow$  'st and*  
*add-cls<sub>NOT</sub> :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*remove-cls<sub>NOT</sub> :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*inv :: 'st  $\Rightarrow$  bool and*  
*backjump-conds :: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool and*  
*propagate-conds :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  bool and*  
*learn-restrictions forget-restrictions :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  bool*  
**begin**

**lemma** *cdcl<sub>NOT</sub>-learn-all-induct*[*consumes 1, case-names dpll-bj learn forget<sub>NOT</sub>*]:

**fixes** *S T :: 'st*

**assumes** *cdcl<sub>NOT</sub> S T and*

*dpll:  $\bigwedge T. \text{dpll-bj } S T \Rightarrow P S T$  and*

*learning:*

$\bigwedge C F K F' C' L T. \text{clauses}_{NOT} S \models_{pm} mset\text{-cls } C \Rightarrow$   
 $\text{atms-of } (mset\text{-cls } C) \subseteq \text{atms-of-mm } (\text{clauses}_{NOT} S) \cup \text{atm-of ' (lits-of-l (trail } S)) \Rightarrow$   
 $\text{distinct-mset } (mset\text{-cls } C) \Rightarrow$   
 $\neg \text{tautology } (mset\text{-cls } C) \Rightarrow$   
 $\text{learn-restrictions } C S \Rightarrow$   
 $\text{trail } S = F' @ \text{Marked } K () \# F \Rightarrow$   
 $mset\text{-cls } C = C' + \{\#L\# \} \Rightarrow$   
 $F \models_{as} CNot C' \Rightarrow$   
 $C' + \{\#L\# \} \notin \# \text{clauses}_{NOT} S \Rightarrow$

```

    T ~ add-clNOT C S  $\implies$ 
    P S T and
  forgetting:  $\bigwedge C T. \text{removeAll-mset } (\text{mset-cls } C) (\text{clauses}_{NOT} S) \models_{pm} \text{mset-cls } C \implies$ 
    C ! $\in$ ! raw-clauses S  $\implies$ 
     $\neg(\exists F' F K L. \text{trail } S = F' @ \text{Marked } K () \# F \wedge F \models_{as} CNot (\text{mset-cls } C - \{\#L\# \})) \implies$ 
    T ~ remove-clNOT C S  $\implies$ 
    forget-restrictions C S  $\implies$ 
    P S T
  shows P S T
  using assms(1)
  apply (induction rule: cdclNOT.induct)
  apply (auto dest: assms(2) simp add: learn-ops-axioms)[]
  apply (auto elim!: learn-ops.learn.cases[OF learn-ops-axioms] dest: assms(3))[]
  apply (auto elim!: forget-ops.forgetNOT.cases[OF forget-ops-axioms] dest!: assms(4))
  done

```

**lemma** rtrancp-cdcl<sub>NOT</sub>-inv:  
 cdcl<sub>NOT</sub>\*\* S T  $\implies$  inv S  $\implies$  inv T  
**apply** (induction rule: rtrancp-induct)  
**apply** simp  
**using** cdcl<sub>NOT</sub>-inv **unfolding** conflict-driven-clause-learning-def  
 conflict-driven-clause-learning-axioms-def **by** blast

**lemma** learn-always-simple-clauses:

```

  assumes
    learn: learn S T and
    n-d: no-dup (trail S)
  shows set-mset (clausesNOT T - clausesNOT S)
     $\subseteq$  simple-clss (atms-of-mm (clausesNOT S)  $\cup$  atm-of ' lits-of-l (trail S))
  proof
    fix C assume C: C  $\in$  set-mset (clausesNOT T - clausesNOT S)
    have distinct-mset C  $\neg$ tautology C using learn C n-d by (elim learnNOTE; auto)+
    then have C  $\in$  simple-clss (atms-of C)
      using distinct-mset-not-tautology-implies-in-simple-clss by blast
    moreover have atms-of C  $\subseteq$  atms-of-mm (clausesNOT S)  $\cup$  atm-of ' lits-of-l (trail S)
      using learn C n-d by (elim learnNOTE) (auto simp: atms-of-ms-def atms-of-def image-Un
        true-annots-CNot-all-atms-defined)
    moreover have finite (atms-of-mm (clausesNOT S)  $\cup$  atm-of ' lits-of-l (trail S))
      by auto
    ultimately show C  $\in$  simple-clss (atms-of-mm (clausesNOT S)  $\cup$  atm-of ' lits-of-l (trail S))
      using simple-clss-mono by (metis (no-types) insert-subset mk-disjoint-insert)
  qed

```

**definition** conflicting-bj-clss S  $\equiv$

```

  {C + {\#L\#} | C L. C + {\#L\#}  $\in$  # clausesNOT S  $\wedge$  distinct-mset (C + {\#L\#})
   $\wedge$   $\neg$ tautology (C + {\#L\#})
   $\wedge$  ( $\exists F' K F. \text{trail } S = F' @ \text{Marked } K () \# F \wedge F \models_{as} CNot C$ )}

```

**lemma** conflicting-bj-clss-remove-cl<sub>NOT</sub>[simp]:  
 conflicting-bj-clss (remove-cl<sub>NOT</sub> C S) = conflicting-bj-clss S - {mset-cl<sub>s</sub> C}  
**unfolding** conflicting-bj-clss-def **by** fastforce

**lemma** conflicting-bj-clss-remove-cl<sub>NOT</sub>'[simp]:  
 T ~ remove-cl<sub>NOT</sub> C S  $\implies$  conflicting-bj-clss T = conflicting-bj-clss S - {mset-cl<sub>s</sub> C}  
**unfolding** conflicting-bj-clss-def **by** fastforce



**lemma** *conflicting-bj-clss-add-clss<sub>NOT</sub>-state-eq*:

**assumes**

$T: T \sim \text{add-clss}_{NOT} C' S$  **and**

$n\text{-d}: \text{no-dup } (\text{trail } S)$

**shows** *conflicting-bj-clss*  $T$

$= \text{conflicting-bj-clss } S$

$\cup (\text{if } \exists C L. \text{mset-clss } C' = C + \{\#L\# \} \wedge \text{distinct-mset } (C + \{\#L\# \}) \wedge \neg \text{tautology } (C + \{\#L\# \})$   
 $\wedge (\exists F' K d F. \text{trail } S = F' @ \text{Marked } K () \# F \wedge F \models_{as} CNot C)$   
 $\text{then } \{\text{mset-clss } C'\} \text{ else } \{\})$

**proof** –

**def**  $P \equiv \lambda C L T. \text{distinct-mset } (C + \{\#L\# \}) \wedge \neg \text{tautology } (C + \{\#L\# \}) \wedge$   
 $(\exists F' K F. \text{trail } T = F' @ \text{Marked } K () \# F \wedge F \models_{as} CNot C)$

**have**  $\text{conf}: \bigwedge T. \text{conflicting-bj-clss } T = \{C + \{\#L\# \} \mid C L. C + \{\#L\# \} \in \# \text{clauses}_{NOT} T \wedge P C L T\}$

**unfolding** *conflicting-bj-clss-def*  $P\text{-def}$  **by** *auto*

**have**  $P\text{-}S\text{-}T: \bigwedge C L. P C L T = P C L S$

**using**  $T\text{-}n\text{-}d$  **unfolding**  $P\text{-def}$  **by** *auto*

**have**  $P: \text{conflicting-bj-clss } T = \{C + \{\#L\# \} \mid C L. C + \{\#L\# \} \in \# \text{clauses}_{NOT} S \wedge P C L T\} \cup$   
 $\{C + \{\#L\# \} \mid C L. C + \{\#L\# \} \in \# \{\# \text{mset-clss } C'\# \} \wedge P C L T\}$

**using**  $T\text{-}n\text{-}d$  **unfolding**  $\text{conf}$  **by** *auto*

**moreover** **have**  $\{C + \{\#L\# \} \mid C L. C + \{\#L\# \} \in \# \text{clauses}_{NOT} S \wedge P C L T\} = \text{conflicting-bj-clss } S$

**using**  $T\text{-}n\text{-}d$  **unfolding**  $P\text{-def}$  *conflicting-bj-clss-def* **by** *auto*

**moreover** **have**  $\{C + \{\#L\# \} \mid C L. C + \{\#L\# \} \in \# \{\# \text{mset-clss } C'\# \} \wedge P C L T\} =$   
 $(\text{if } \exists C L. \text{mset-clss } C' = C + \{\#L\# \} \wedge P C L S \text{ then } \{\text{mset-clss } C'\} \text{ else } \{\})$

**using**  $n\text{-d } T$  **by** (*force simp: P-S-T*)

**ultimately show** *?thesis* **unfolding**  $P\text{-def}$  **by** *presburger*

**qed**

**lemma** *conflicting-bj-clss-add-clss<sub>NOT</sub>*:

$\text{no-dup } (\text{trail } S) \implies$

*conflicting-bj-clss*  $(\text{add-clss}_{NOT} C' S)$

$= \text{conflicting-bj-clss } S$

$\cup (\text{if } \exists C L. \text{mset-clss } C' = C + \{\#L\# \} \wedge \text{distinct-mset } (C + \{\#L\# \}) \wedge \neg \text{tautology } (C + \{\#L\# \})$   
 $\wedge (\exists F' K d F. \text{trail } S = F' @ \text{Marked } K () \# F \wedge F \models_{as} CNot C)$   
 $\text{then } \{\text{mset-clss } C'\} \text{ else } \{\})$

**using** *conflicting-bj-clss-add-clss<sub>NOT</sub>-state-eq* **by** *auto*

**lemma** *conflicting-bj-clss-incl-clauses*:

*conflicting-bj-clss*  $S \subseteq \text{set-mset } (\text{clauses}_{NOT} S)$

**unfolding** *conflicting-bj-clss-def* **by** *auto*

**lemma** *finite-conflicting-bj-clss[simp]*:

*finite*  $(\text{conflicting-bj-clss } S)$

**using** *conflicting-bj-clss-incl-clauses[of S]* *rev-finite-subset* **by** *blast*

**lemma** *learn-conflicting-increasing*:

$\text{no-dup } (\text{trail } S) \implies \text{learn } S T \implies \text{conflicting-bj-clss } S \subseteq \text{conflicting-bj-clss } T$

**apply** (*elim learn<sub>NOT</sub>E*)

**by** (*subst conflicting-bj-clss-add-clss<sub>NOT</sub>-state-eq[of T]*) *auto*

**abbreviation** *conflicting-bj-clss-yet*  $b S \equiv$

$3 \wedge b - \text{card } (\text{conflicting-bj-clss } S)$

**abbreviation**  $\mu_L :: \text{nat} \Rightarrow 'st \Rightarrow \text{nat} \times \text{nat}$  **where**  
 $\mu_L \ b \ S \equiv (\text{conflicting-bj-clss-yet } b \ S, \text{card } (\text{set-mset } (\text{clauses}_{NOT} \ S)))$

**lemma** *do-not-forget-before-backtrack-rule-clause-learned-clause-untouched*:

**assumes**  $\text{forget}_{NOT} \ S \ T$   
**shows**  $\text{conflicting-bj-clss } S = \text{conflicting-bj-clss } T$   
**using** *assms* **apply** ( $\text{elim } \text{forget}_{NOT} E$ )  
**apply** *auto*  
**unfolding** *conflicting-bj-clss-def*  
**apply** *clarify*  
**using** *diff-union-cancelR* **by** ( $\text{metis } \text{diff-union-cancelR}$ )

**lemma** *forget- $\mu_L$ -decrease*:

**assumes**  $\text{forget}_{NOT}: \text{forget}_{NOT} \ S \ T$   
**shows**  $(\mu_L \ b \ T, \mu_L \ b \ S) \in \text{less-than } <*\text{lex}*> \text{less-than}$

**proof** –

**have**  $\text{card } (\text{set-mset } (\text{clauses}_{NOT} \ S)) > 0$   
**using**  $\text{forget}_{NOT}$  **by** ( $\text{elim } \text{forget}_{NOT} E$ ) (*auto simp: size-mset-removeAll-mset-le-iff card-gt-0-iff*)  
**then have**  $\text{card } (\text{set-mset } (\text{clauses}_{NOT} \ T)) < \text{card } (\text{set-mset } (\text{clauses}_{NOT} \ S))$   
**using**  $\text{forget}_{NOT}$  **by** ( $\text{elim } \text{forget}_{NOT} E$ ) (*auto simp: size-mset-removeAll-mset-le-iff*)  
**then show** *?thesis*  
**unfolding** *do-not-forget-before-backtrack-rule-clause-learned-clause-untouched[OF forget<sub>NOT</sub>]*  
**by** *auto*

**qed**

**lemma** *set-condition-or-split*:

$\{a. (a = b \vee Q \ a) \wedge S \ a\} = (\text{if } S \ b \text{ then } \{b\} \text{ else } \{\}) \cup \{a. Q \ a \wedge S \ a\}$   
**by** *auto*

**lemma** *set-insert-neq*:

$A \neq \text{insert } a \ A \longleftrightarrow a \notin A$   
**by** *auto*

**lemma** *learn- $\mu_L$ -decrease*:

**assumes**  $\text{learnST}: \text{learn } S \ T$  **and**  $n\text{-d}: \text{no-dup } (\text{trail } S)$  **and**  
 $A: \text{atms-of-mm } (\text{clauses}_{NOT} \ S) \cup \text{atm-of } ' \text{lits-of-l } (\text{trail } S) \subseteq A$  **and**  
 $\text{fin-A}: \text{finite } A$   
**shows**  $(\mu_L \ (\text{card } A) \ T, \mu_L \ (\text{card } A) \ S) \in \text{less-than } <*\text{lex}*> \text{less-than}$

**proof** –

**have** [*simp*]:  $(\text{atms-of-mm } (\text{clauses}_{NOT} \ T) \cup \text{atm-of } ' \text{lits-of-l } (\text{trail } T))$   
 $= (\text{atms-of-mm } (\text{clauses}_{NOT} \ S) \cup \text{atm-of } ' \text{lits-of-l } (\text{trail } S))$   
**using**  $\text{learnST } n\text{-d}$  **by** ( $\text{elim } \text{learn}_{NOT} E$ ) *auto*

**then have**  $\text{card } (\text{atms-of-mm } (\text{clauses}_{NOT} \ T) \cup \text{atm-of } ' \text{lits-of-l } (\text{trail } T))$   
 $= \text{card } (\text{atms-of-mm } (\text{clauses}_{NOT} \ S) \cup \text{atm-of } ' \text{lits-of-l } (\text{trail } S))$   
**by** (*auto intro!: card-mono*)

**then have**  $3: (3::\text{nat}) \wedge \text{card } (\text{atms-of-mm } (\text{clauses}_{NOT} \ T) \cup \text{atm-of } ' \text{lits-of-l } (\text{trail } T))$   
 $= 3 \wedge \text{card } (\text{atms-of-mm } (\text{clauses}_{NOT} \ S) \cup \text{atm-of } ' \text{lits-of-l } (\text{trail } S))$   
**by** (*auto intro: power-mono*)

**moreover have**  $\text{conflicting-bj-clss } S \subseteq \text{conflicting-bj-clss } T$   
**using**  $\text{learnST } n\text{-d}$  **by** (*simp add: learn-conflicting-increasing*)

**moreover have**  $\text{conflicting-bj-clss } S \neq \text{conflicting-bj-clss } T$   
**using**  $\text{learnST}$

**proof** ( $\text{elim } \text{learn}_{NOT} E, \text{goal-cases}$ )

**case** (1 *C*) **note**  $\text{clss-S} = \text{this}(1)$  **and**  $\text{atms-C} = \text{this}(2)$  **and**  $\text{inv} = \text{this}(3)$  **and**  $T = \text{this}(4)$

**then obtain**  $F K F' C' L$  **where**  
*tr-S*:  $\text{trail } S = F' @ \text{Marked } K () \# F$  **and**  
*C*:  $\text{mset-clss } C = C' + \{\#L\# \}$  **and**  
*F*:  $F \models_{as} C \text{Not } C'$  **and**  
*C-S*:  $C' + \{\#L\# \} \notin \text{clauses}_{NOT} S$   
**by** *blast*  
**moreover have**  $\text{distinct-mset } (\text{mset-clss } C) \neg \text{tautology } (\text{mset-clss } C)$  **using** *inv* **by** *blast+*  
**ultimately have**  $C' + \{\#L\# \} \in \text{conflicting-bj-clss } T$   
**using**  $T \text{ n-d unfolding conflicting-bj-clss-def}$  **by** *fastforce*  
**moreover have**  $C' + \{\#L\# \} \notin \text{conflicting-bj-clss } S$   
**using**  $C\text{-S unfolding conflicting-bj-clss-def}$  **by** *auto*  
**ultimately show** *?case* **by** *blast*  
**qed**  
**moreover have**  $\text{fin-T: finite } (\text{conflicting-bj-clss } T)$   
**using** *learnST* **by** *induction (auto simp add: conflicting-bj-clss-add-clss\_{NOT})*  
**ultimately have**  $\text{card } (\text{conflicting-bj-clss } T) \geq \text{card } (\text{conflicting-bj-clss } S)$   
**using** *card-mono* **by** *blast*  
  
**moreover**  
**have**  $\text{fin': finite } (\text{atms-of-mm } (\text{clauses}_{NOT} T) \cup \text{atm-of ' lits-of-l } (\text{trail } T))$   
**by** *auto*  
**have**  $1: \text{atms-of-ms } (\text{conflicting-bj-clss } T) \subseteq \text{atms-of-mm } (\text{clauses}_{NOT} T)$   
**unfolding** *conflicting-bj-clss-def atms-of-ms-def* **by** *auto*  
**have**  $2: \bigwedge x. x \in \text{conflicting-bj-clss } T \implies \neg \text{tautology } x \wedge \text{distinct-mset } x$   
**unfolding** *conflicting-bj-clss-def* **by** *auto*  
**have**  $T: \text{conflicting-bj-clss } T$   
 $\subseteq \text{simple-clss } (\text{atms-of-mm } (\text{clauses}_{NOT} T) \cup \text{atm-of ' lits-of-l } (\text{trail } T))$   
**by** *standard (meson 1 2 fin' <finite (conflicting-bj-clss T)> simple-clss-mono distinct-mset-set-def simplified-in-simple-clss subsetCE sup.coboundedI1)*  
**moreover**  
**then have**  $\# : 3 \wedge \text{card } (\text{atms-of-mm } (\text{clauses}_{NOT} T) \cup \text{atm-of ' lits-of-l } (\text{trail } T))$   
 $\geq \text{card } (\text{conflicting-bj-clss } T)$   
**by** *(meson Nat.le-trans simple-clss-card simple-clss-finite card-mono fin')*  
**have**  $\text{atms-of-mm } (\text{clauses}_{NOT} T) \cup \text{atm-of ' lits-of-l } (\text{trail } T) \subseteq A$   
**using** *learn\_{NOT}E[OF learnST] A* **by** *simp*  
**then have**  $3 \wedge (\text{card } A) \geq \text{card } (\text{conflicting-bj-clss } T)$   
**using**  $\# \text{ fin-A}$  **by** *(meson simple-clss-card simple-clss-finite simple-clss-mono calculation(2) card-mono dual-order.trans)*  
**ultimately show** *?thesis*  
**using** *psubset-card-mono[OF fin-T]*  
**unfolding** *less-than-iff lex-prod-def* **by** *clarify*  
 $(\text{meson } \langle \text{conflicting-bj-clss } S \neq \text{conflicting-bj-clss } T \rangle$   
 $\langle \text{conflicting-bj-clss } S \subseteq \text{conflicting-bj-clss } T \rangle$   
 $\text{diff-less-mono2 le-less-trans not-le psubsetI})$   
**qed**

We have to assume the following:

- *inv S*: the invariant holds in the initial state.
- *A* is a (finite *finite A*) superset of the literals in the trail  $\text{atm-of ' lits-of-l } (\text{trail } S) \subseteq \text{atms-of-ms } A$  and in the clauses  $\text{atms-of-mm } (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms } A$ . This can be the set of all the literals in the starting set of clauses.
- *no-dup (trail S)*: no duplicate in the trail. This is invariant along the path.

**definition**  $\mu_{CDCL}$  **where**

$\mu_{CDCL} A T \equiv ((2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$   
 $\quad - \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } T),$   
 $\quad \text{conflicting-bj-clss-yet } (\text{card } (\text{atms-of-ms } A)) T, \text{card } (\text{set-mset } (\text{clauses}_{NOT} T)))$

**lemma**  $\text{cdcl}_{NOT}$ -decreasing-measure:

**assumes**

$\text{cdcl}_{NOT} S T$  **and**

$\text{inv: inv } S$  **and**

$\text{atm-clss: atms-of-mm } (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms } A$  **and**

$\text{atm-lits: atm-of ' lits-of-l } (\text{trail } S) \subseteq \text{atms-of-ms } A$  **and**

$n\text{-d: no-dup } (\text{trail } S)$  **and**

$\text{fin-A: finite } A$

**shows**  $(\mu_{CDCL} A T, \mu_{CDCL} A S)$

$\in \text{less-than } <*\text{lex}*> (\text{less-than } <*\text{lex}*> \text{less-than})$

**using**  $\text{assms}(1)$

**proof** *induction*

**case**  $(c\text{-dpll-bj } T)$

**from**  $\text{dpll-bj-trail-mes-decreasing-prop}[OF \text{ this}(1) \text{ inv atm-clss atm-lits n-d fin-A}]$

**show**  $?case$  **unfolding**  $\mu_{CDCL}\text{-def}$

**by**  $(\text{meson in-lex-prod less-than-iff})$

**next**

**case**  $(c\text{-learn } T)$  **note**  $\text{learn} = \text{this}(1)$

**then have**  $S: \text{trail } S = \text{trail } T$

**using**  $\text{inv atm-clss atm-lits n-d fin-A}$

**by**  $(\text{elim learn}_{NOT} E) \text{ auto}$

**show**  $?case$

**using**  $\text{learn-}\mu_L\text{-decrease}[OF \text{ learn n-d, of atms-of-ms } A] \text{ atm-clss atm-lits fin-A n-d}$

**unfolding**  $S \mu_{CDCL}\text{-def}$  **by**  $\text{auto}$

**next**

**case**  $(c\text{-forget}_{NOT} T)$  **note**  $\text{forget}_{NOT} = \text{this}(1)$

**have**  $\text{trail } S = \text{trail } T$  **using**  $\text{forget}_{NOT}$  **by**  $\text{induction auto}$

**then show**  $?case$

**using**  $\text{forget-}\mu_L\text{-decrease}[OF \text{ forget}_{NOT}]$  **unfolding**  $\mu_{CDCL}\text{-def}$  **by**  $\text{auto}$

**qed**

**lemma**  $\text{wf-cdcl}_{NOT}$ -restricted-learning:

**assumes**  $\text{finite } A$

**shows**  $\text{wf } \{(T, S).$

$(\text{atms-of-mm } (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms } A \wedge \text{atm-of ' lits-of-l } (\text{trail } S) \subseteq \text{atms-of-ms } A$

$\wedge \text{no-dup } (\text{trail } S)$

$\wedge \text{inv } S)$

$\wedge \text{cdcl}_{NOT} S T \}$

**by**  $(\text{rule wf-wf-if-measure}'[of \text{ less-than } <*\text{lex}*> (\text{less-than } <*\text{lex}*> \text{less-than})])$

$(\text{auto intro: cdcl}_{NOT}\text{-decreasing-measure}[OF \text{ - - - - assms}])$

**definition**  $\mu_C' :: 'v \text{ literal multiset set} \Rightarrow 'st \Rightarrow \text{nat}$  **where**

$\mu_C' A T \equiv \mu_C (1 + \text{card } (\text{atms-of-ms } A)) (2 + \text{card } (\text{atms-of-ms } A)) (\text{trail-weight } T)$

**definition**  $\mu_{CDCL}' :: 'v \text{ literal multiset set} \Rightarrow 'st \Rightarrow \text{nat}$  **where**

$\mu_{CDCL}' A T \equiv$

$((2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A)) - \mu_C' A T) * (1 + 3^{\text{card } (\text{atms-of-ms } A)}) *$

$2$

$+ \text{conflicting-bj-clss-yet } (\text{card } (\text{atms-of-ms } A)) T * 2$

$+ \text{card } (\text{set-mset } (\text{clauses}_{NOT} T))$

**lemma**  $cdcl_{NOT}$ -decreasing-measure':

**assumes**

$cdcl_{NOT} S T$  **and**

$inv: inv S$  **and**

$atms-clss: atms-of-mm (clauses_{NOT} S) \subseteq atms-of-ms A$  **and**

$atms-trail: atm-of \text{ ' } lits-of-l (trail S) \subseteq atms-of-ms A$  **and**

$n-d: no-dup (trail S)$  **and**

$fin-A: finite A$

**shows**  $\mu_{CDCL}' A T < \mu_{CDCL}' A S$

**using**  $assms(1)$

**proof** (induction rule:  $cdcl_{NOT}$ -learn-all-induct)

**case** ( $dpll-bj T$ )

**then have**  $(2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A T$

$< (2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A S$

**using**  $dpll-bj-trail-mes-decreasing-prop fin-A inv n-d atms-clss atms-trail$

**unfolding**  $\mu_C'$ -def **by** blast

**then have**  $XX: ((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A T) + 1$

$\leq (2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A S$

**by** auto

**from**  $mult-le-mono1[OF this, of (1 + 3 \wedge card (atms-of-ms A))]$

**have**  $((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A T) *$

$(1 + 3 \wedge card (atms-of-ms A)) + (1 + 3 \wedge card (atms-of-ms A))$

$\leq ((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A S)$

$* (1 + 3 \wedge card (atms-of-ms A))$

**unfolding**  $Nat.add-mult-distrib$

**by** presburger

**moreover**

**have**  $cl-T-S: clauses_{NOT} T = clauses_{NOT} S$

**using**  $dpll-bj.hyps inv dpll-bj-clauses$  **by** auto

**have**  $conflicting-bj-clss-yet (card (atms-of-ms A)) S < 1 + 3 \wedge card (atms-of-ms A)$

**by** simp

**ultimately have**  $((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A T)$

$* (1 + 3 \wedge card (atms-of-ms A)) + conflicting-bj-clss-yet (card (atms-of-ms A)) T$

$< ((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A S) * (1 + 3 \wedge card (atms-of-ms A))$

**by** linarith

**then have**  $((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A T)$

$* (1 + 3 \wedge card (atms-of-ms A))$

$+ conflicting-bj-clss-yet (card (atms-of-ms A)) T$

$< ((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A S)$

$* (1 + 3 \wedge card (atms-of-ms A))$

$+ conflicting-bj-clss-yet (card (atms-of-ms A)) S$

**by** linarith

**then have**  $((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A T)$

$* (1 + 3 \wedge card (atms-of-ms A)) * 2$

$+ conflicting-bj-clss-yet (card (atms-of-ms A)) T * 2$

$< ((2 + card (atms-of-ms A)) \wedge (1 + card (atms-of-ms A)) - \mu_C' A S)$

$* (1 + 3 \wedge card (atms-of-ms A)) * 2$

$+ conflicting-bj-clss-yet (card (atms-of-ms A)) S * 2$

**by** linarith

**then show** ?case **unfolding**  $\mu_{CDCL}'$ -def  $cl-T-S$  **by** presburger

**next**

**case** ( $learn C F' K F C' L T$ ) **note**  $clss-S-C = this(1)$  **and**  $atms-C = this(2)$  **and**  $dist = this(3)$

**and**  $tauto = this(4)$  **and**  $learn-restr = this(5)$  **and**  $tr-S = this(6)$  **and**  $C' = this(7)$  **and**

$F-C = this(8)$  **and**  $C-new = this(9)$  **and**  $T = this(10)$

```

have insert (mset-cls C) (conflicting-bj-clss S)  $\subseteq$  simple-clss (atms-of-ms A)
proof -
  have mset-cls C  $\in$  simple-clss (atms-of-ms A)
  using C'
  by (metis (no-types, hide-lams) Un-subset-iff simple-clss-mono
      contra-subsetD dist distinct-mset-not-tautology-implies-in-simple-clss
      dual-order.trans atms-C atms-clss atms-trail tauto)
  moreover have conflicting-bj-clss S  $\subseteq$  simple-clss (atms-of-ms A)
  proof
    fix x :: 'v literal multiset
    assume x  $\in$  conflicting-bj-clss S
    then have x  $\in$  # clausesNOT S  $\wedge$  distinct-mset x  $\wedge$   $\neg$  tautology x
    unfolding conflicting-bj-clss-def by blast
    then show x  $\in$  simple-clss (atms-of-ms A)
    by (meson atms-clss atms-of-atms-of-ms-mono atms-of-ms-finite simple-clss-mono
        distinct-mset-not-tautology-implies-in-simple-clss fin-A finite-subset
        set-rev-mp)
  qed
  ultimately show ?thesis
  by auto
qed
then have card (insert (mset-cls C) (conflicting-bj-clss S))  $\leq$  3  $\wedge$  (card (atms-of-ms A))
  by (meson Nat.le-trans atms-of-ms-finite simple-clss-card simple-clss-finite
      card-mono fin-A)
moreover have [simp]: card (insert (mset-cls C) (conflicting-bj-clss S))
  = Suc (card ((conflicting-bj-clss S)))
  by (metis (no-types) C' C-new card-insert-if conflicting-bj-clss-incl-clauses contra-subsetD
      finite-conflicting-bj-clss)
moreover have [simp]: conflicting-bj-clss (add-clsNOT C S) = conflicting-bj-clss S  $\cup$  {mset-cls C}
  using dist tauto F-C by (subst conflicting-bj-clss-add-clsNOT[OF n-d]) (force simp: C' tr-S n-d)
ultimately have [simp]: conflicting-bj-clss-yet (card (atms-of-ms A)) S
  = Suc (conflicting-bj-clss-yet (card (atms-of-ms A)) (add-clsNOT C S))
  by simp
have 1: clausesNOT T = clausesNOT (add-clsNOT C S) using T by auto
have 2: conflicting-bj-clss-yet (card (atms-of-ms A)) T
  = conflicting-bj-clss-yet (card (atms-of-ms A)) (add-clsNOT C S)
  using T unfolding conflicting-bj-clss-def by auto
have 3:  $\mu_{C'} A T = \mu_{C'} A (add-cls_{NOT} C S)$ 
  using T unfolding  $\mu_{C'}$ -def by auto
have ((2 + card (atms-of-ms A))  $\wedge$  (1 + card (atms-of-ms A)) -  $\mu_{C'} A (add-cls_{NOT} C S)$ )
  * (1 + 3  $\wedge$  card (atms-of-ms A)) * 2
  = ((2 + card (atms-of-ms A))  $\wedge$  (1 + card (atms-of-ms A)) -  $\mu_{C'} A S$ )
  * (1 + 3  $\wedge$  card (atms-of-ms A)) * 2
  using n-d unfolding  $\mu_{C'}$ -def by auto
moreover
  have conflicting-bj-clss-yet (card (atms-of-ms A)) (add-clsNOT C S)
    * 2
    + card (set-mset (clausesNOT (add-clsNOT C S)))
    < conflicting-bj-clss-yet (card (atms-of-ms A)) S * 2
    + card (set-mset (clausesNOT S))
  by (simp add: C' C-new n-d)
ultimately show ?case unfolding  $\mu_{CDCL}$ '-def 1 2 3 by presburger
next
case (forgetNOT C T) note T = this(4)
have [simp]:  $\mu_{C'} A (remove-cls_{NOT} C S) = \mu_{C'} A S$ 

```

unfolding  $\mu_C'$ -def by auto  
 have forget<sub>NOT</sub> S T  
 apply (rule forget<sub>NOT</sub>.intros) using forget<sub>NOT</sub> by auto  
 then have conflicting-bj-clss T = conflicting-bj-clss S  
 using do-not-forget-before-backtrack-rule-clause-learned-clause-untouched by blast  
 moreover have card (set-mset (clauses<sub>NOT</sub> T)) < card (set-mset (clauses<sub>NOT</sub> S))  
 by (metis T card-Diff1-less clauses-remove-clss<sub>NOT</sub> finite-set-mset forget<sub>NOT</sub>.hyps(2)  
 in-clss-mset-clss order-refl set-mset-minus-replicate-mset(1) state-eq<sub>NOT</sub>-clauses)  
 ultimately show ?case unfolding  $\mu_{CDCL}'$ -def  
 using T  $\langle \mu_C' A \text{ (remove-clss}_{NOT} C S) = \mu_C' A S \rangle$  by (metis (no-types) add-le-cancel-left  
 $\mu_C'$ -def not-le state-eq<sub>NOT</sub>-trail)  
 qed

lemma cdcl<sub>NOT</sub>-clauses-bound:

assumes  
 cdcl<sub>NOT</sub> S T and  
 inv S and  
 atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  A and  
 atm-of '(lits-of-l (trail S))  $\subseteq$  A and  
 n-d: no-dup (trail S) and  
 fin-A[simp]: finite A  
 shows set-mset (clauses<sub>NOT</sub> T)  $\subseteq$  set-mset (clauses<sub>NOT</sub> S)  $\cup$  simple-clss A  
 using assms  
 proof (induction rule: cdcl<sub>NOT</sub>-learn-all-induct)  
 case dpll-bj  
 then show ?case using dpll-bj-clauses by simp  
 next  
 case forget<sub>NOT</sub>  
 then show ?case using clauses-remove-clss<sub>NOT</sub> unfolding state-eq<sub>NOT</sub>-def by auto  
 next  
 case (learn C F K d F' C' L) note atms-C = this(2) and dist = this(3) and tauto = this(4) and  
 T = this(10) and atms-clss-S = this(12) and atms-trail-S = this(13)  
 have atms-of (mset-clss C)  $\subseteq$  A  
 using atms-C atms-clss-S atms-trail-S by fast  
 then have simple-clss (atms-of (mset-clss C))  $\subseteq$  simple-clss A  
 by (simp add: simple-clss-mono)  
 then have mset-clss C  $\in$  simple-clss A  
 using finite dist tauto by (auto dest: distinct-mset-not-tautology-implies-in-simple-clss)  
 then show ?case using T n-d by auto  
 qed

lemma rtrancpl-cdcl<sub>NOT</sub>-clauses-bound:

assumes  
 cdcl<sub>NOT</sub>\*\* S T and  
 inv S and  
 atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  A and  
 atm-of '(lits-of-l (trail S))  $\subseteq$  A and  
 n-d: no-dup (trail S) and  
 finite: finite A  
 shows set-mset (clauses<sub>NOT</sub> T)  $\subseteq$  set-mset (clauses<sub>NOT</sub> S)  $\cup$  simple-clss A  
 using assms(1-5)  
 proof induction  
 case base  
 then show ?case by simp  
 next

**case** (*step*  $T\ U$ ) **note**  $st = this(1)$  **and**  $cdcl_{NOT} = this(2)$  **and**  $IH = this(3)[OF\ this(4-7)]$  **and**  
 $inv = this(4)$  **and**  $atms-clss-S = this(5)$  **and**  $atms-trail-S = this(6)$  **and**  $finite-clss-S = this(7)$   
**have**  $inv\ T$   
**using**  $rtrancplp-cdcl_{NOT}-inv\ st\ inv$  **by** *blast*  
**moreover have**  $atms-of-mm\ (clauses_{NOT}\ T) \subseteq A$  **and**  $atm-of\ 'lits-of-l\ (trail\ T) \subseteq A$   
**using**  $rtrancplp-cdcl_{NOT}-trail-clauses-bound[OF\ st]\ inv\ atms-clss-S\ atms-trail-S\ n-d$  **by** *auto*  
**moreover have**  $no-dup\ (trail\ T)$   
**using**  $rtrancplp-cdcl_{NOT}-no-dup[OF\ st\ \langle inv\ S \rangle\ n-d]$  **by** *simp*  
**ultimately have**  $set-mset\ (clauses_{NOT}\ U) \subseteq set-mset\ (clauses_{NOT}\ T) \cup simple-clss\ A$   
**using**  $cdcl_{NOT}\ finite\ n-d$  **by** (*auto simp: cdcl<sub>NOT</sub>-clauses-bound*)  
**then show** *?case* **using**  $IH$  **by** *auto*  
**qed**

**lemma**  $rtrancplp-cdcl_{NOT}-card-clauses-bound$ :

**assumes**  
 $cdcl_{NOT}^{**}\ S\ T$  **and**  
 $inv\ S$  **and**  
 $atms-of-mm\ (clauses_{NOT}\ S) \subseteq A$  **and**  
 $atm-of\ '(lits-of-l\ (trail\ S)) \subseteq A$  **and**  
 $n-d$ :  $no-dup\ (trail\ S)$  **and**  
 $finite$ :  $finite\ A$   
**shows**  $card\ (set-mset\ (clauses_{NOT}\ T)) \leq card\ (set-mset\ (clauses_{NOT}\ S)) + 3 \wedge (card\ A)$   
**using**  $rtrancplp-cdcl_{NOT}-clauses-bound[OF\ assms]\ finite$  **by** (*meson Nat.le-trans*  
 $simple-clss-card\ simple-clss-finite\ card-Un-le\ card-mono\ finite-UnI$   
 $finite-set-mset\ nat-add-left-cancel-le$ )

**lemma**  $rtrancplp-cdcl_{NOT}-card-clauses-bound'$ :

**assumes**  
 $cdcl_{NOT}^{**}\ S\ T$  **and**  
 $inv\ S$  **and**  
 $atms-of-mm\ (clauses_{NOT}\ S) \subseteq A$  **and**  
 $atm-of\ '(lits-of-l\ (trail\ S)) \subseteq A$  **and**  
 $n-d$ :  $no-dup\ (trail\ S)$  **and**  
 $finite$ :  $finite\ A$   
**shows**  $card\ \{C \mid C. C \in \# clauses_{NOT}\ T \wedge (tautology\ C \vee \neg distinct-mset\ C)\}$   
 $\leq card\ \{C \mid C. C \in \# clauses_{NOT}\ S \wedge (tautology\ C \vee \neg distinct-mset\ C)\} + 3 \wedge (card\ A)$   
 $(is\ card\ ?T \leq card\ ?S + -)$   
**using**  $rtrancplp-cdcl_{NOT}-clauses-bound[OF\ assms]\ finite$   
**proof** –  
**have**  $?T \subseteq ?S \cup simple-clss\ A$   
**using**  $rtrancplp-cdcl_{NOT}-clauses-bound[OF\ assms]$  **by** *force*  
**then have**  $card\ ?T \leq card\ (?S \cup simple-clss\ A)$   
**using**  $finite$  **by** (*simp add: assms(5) simple-clss-finite card-mono*)  
**then show** *?thesis*  
**by** (*meson le-trans simple-clss-card card-Un-le local.finite nat-add-left-cancel-le*)  
**qed**

**lemma**  $rtrancplp-cdcl_{NOT}-card-simple-clauses-bound$ :

**assumes**  
 $cdcl_{NOT}^{**}\ S\ T$  **and**  
 $inv\ S$  **and**  
 $NA$ :  $atms-of-mm\ (clauses_{NOT}\ S) \subseteq A$  **and**  
 $MA$ :  $atm-of\ '(lits-of-l\ (trail\ S)) \subseteq A$  **and**  
 $n-d$ :  $no-dup\ (trail\ S)$  **and**  
 $finite$ :  $finite\ A$



**shows**  $\text{card } (\text{set-mset } (\text{clauses}_{NOT} T))$   
 $\leq \text{card } \{C. C \in \# \text{ clauses}_{NOT} S \wedge (\text{tautology } C \vee \neg \text{distinct-mset } C)\} + 3 \wedge (\text{card } A)$   
**(is**  $\text{card } ?T \leq \text{card } ?S + -)$   
**using**  $\text{rtrancpl-cdcl}_{NOT}\text{-clauses-bound}[OF \text{ assms}] \text{ finite}$   
**proof** –  
**have**  $\bigwedge x. x \in \# \text{ clauses}_{NOT} T \implies \neg \text{tautology } x \implies \text{distinct-mset } x \implies x \in \text{simple-clss } A$   
**using**  $\text{rtrancpl-cdcl}_{NOT}\text{-clauses-bound}[OF \text{ assms}]$  **by**  $(\text{metis } (\text{no-types}, \text{hide-lams}) \text{ Un-iff } NA$   
 $\text{atms-of-atms-of-ms-mono simple-clss-mono contra-subsetD subset-trans}$   
 $\text{distinct-mset-not-tautology-implies-in-simple-clss})$   
**then have**  $\text{set-mset } (\text{clauses}_{NOT} T) \subseteq ?S \cup \text{simple-clss } A$   
**using**  $\text{rtrancpl-cdcl}_{NOT}\text{-clauses-bound}[OF \text{ assms}]$  **by**  $\text{auto}$   
**then have**  $\text{card}(\text{set-mset } (\text{clauses}_{NOT} T)) \leq \text{card } (?S \cup \text{simple-clss } A)$   
**using**  $\text{finite}$  **by**  $(\text{simp add: assms}(5) \text{ simple-clss-finite card-mono})$   
**then show**  $?thesis$   
**by**  $(\text{meson le-trans simple-clss-card card-Un-le local.finite nat-add-left-cancel-le})$   
**qed**

**definition**  $\mu_{CDCL}'\text{-bound} :: 'v \text{ literal multiset set} \Rightarrow 'st \Rightarrow \text{nat}$  **where**  
 $\mu_{CDCL}'\text{-bound } A \ S =$   
 $((2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))) * (1 + 3 \wedge \text{card } (\text{atms-of-ms } A)) * 2$   
 $+ 2 * 3 \wedge (\text{card } (\text{atms-of-ms } A))$   
 $+ \text{card } \{C. C \in \# \text{ clauses}_{NOT} S \wedge (\text{tautology } C \vee \neg \text{distinct-mset } C)\} + 3 \wedge (\text{card } (\text{atms-of-ms } A))$

**lemma**  $\mu_{CDCL}'\text{-bound-reduce-trail-to}_{NOT}[\text{simp}]$ :  
 $\mu_{CDCL}'\text{-bound } A \ (\text{reduce-trail-to}_{NOT} M \ S) = \mu_{CDCL}'\text{-bound } A \ S$   
**unfolding**  $\mu_{CDCL}'\text{-bound-def}$  **by**  $\text{auto}$

**lemma**  $\text{rtrancpl-cdcl}_{NOT}\text{-}\mu_{CDCL}'\text{-bound-reduce-trail-to}_{NOT}$ :  
**assumes**  
 $\text{cdcl}_{NOT}^{**} \ S \ T$  **and**  
 $\text{inv } S$  **and**  
 $\text{atms-of-mm } (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms } A$  **and**  
 $\text{atm-of } '(\text{lits-of-l } (\text{trail } S)) \subseteq \text{atms-of-ms } A$  **and**  
 $n\text{-d: no-dup } (\text{trail } S)$  **and**  
 $\text{finite: finite } (\text{atms-of-ms } A)$  **and**  
 $U: U \sim \text{reduce-trail-to}_{NOT} M \ T$   
**shows**  $\mu_{CDCL}' A \ U \leq \mu_{CDCL}'\text{-bound } A \ S$   
**proof** –  
**have**  $((2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A)) - \mu_C' A \ U)$   
 $\leq (2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))$   
**by**  $\text{auto}$   
**then have**  $((2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A)) - \mu_C' A \ U)$   
 $* (1 + 3 \wedge \text{card } (\text{atms-of-ms } A)) * 2$   
 $\leq (2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A)) * (1 + 3 \wedge \text{card } (\text{atms-of-ms } A)) * 2$   
**using**  $\text{mult-le-mono1}$  **by**  $\text{blast}$   
**moreover**  
**have**  $\text{conflicting-bj-clss-yet } (\text{card } (\text{atms-of-ms } A)) \ T * 2 \leq 2 * 3 \wedge \text{card } (\text{atms-of-ms } A)$   
**by**  $\text{linarith}$   
**moreover have**  $\text{card } (\text{set-mset } (\text{clauses}_{NOT} U))$   
 $\leq \text{card } \{C. C \in \# \text{ clauses}_{NOT} S \wedge (\text{tautology } C \vee \neg \text{distinct-mset } C)\} + 3 \wedge \text{card } (\text{atms-of-ms } A)$   
**using**  $\text{rtrancpl-cdcl}_{NOT}\text{-card-simple-clauses-bound}[OF \text{ assms}(1-6)] \ U$  **by**  $\text{auto}$   
**ultimately show**  $?thesis$   
**unfolding**  $\mu_{CDCL}'\text{-def}$   $\mu_{CDCL}'\text{-bound-def}$  **by**  $\text{linarith}$   
**qed**

**lemma** *rtrancpl-cdcl<sub>NOT</sub>- $\mu_{CDCL}$ '-bound*:

**assumes**

*cdcl<sub>NOT</sub>\*\* S T and*

*inv S and*

*atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  atms-of-ms A and*

*atm-of '(lits-of-l (trail S))  $\subseteq$  atms-of-ms A and*

*n-d: no-dup (trail S) and*

*finite: finite (atms-of-ms A)*

**shows**  $\mu_{CDCL}' A T \leq \mu_{CDCL}'\text{-bound } A S$

**proof** –

**have**  $\mu_{CDCL}' A (\text{reduce-trail-to}_{NOT} (\text{trail } T) T) = \mu_{CDCL}' A T$

**unfolding**  $\mu_{CDCL}'\text{-def}$   $\mu_C'\text{-def}$  *conflicting-bj-clss-def* **by** *auto*

**then show** *?thesis* **using** *rtrancpl-cdcl<sub>NOT</sub>- $\mu_{CDCL}'$ -bound-reduce-trail-to<sub>NOT</sub>* [*OF assms, of - trail T*]  
*state-eq<sub>NOT</sub>-ref* **by** *fastforce*

**qed**

**lemma** *rtrancpl- $\mu_{CDCL}'$ -bound-decreasing*:

**assumes**

*cdcl<sub>NOT</sub>\*\* S T and*

*inv S and*

*atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  atms-of-ms A and*

*atm-of '(lits-of-l (trail S))  $\subseteq$  atms-of-ms A and*

*n-d: no-dup (trail S) and*

*finite[simp]: finite (atms-of-ms A)*

**shows**  $\mu_{CDCL}'\text{-bound } A T \leq \mu_{CDCL}'\text{-bound } A S$

**proof** –

**have**  $\{C. C \in \# \text{ clauses}_{NOT} T \wedge (\text{tautology } C \vee \neg \text{distinct-mset } C)\}$

$\subseteq \{C. C \in \# \text{ clauses}_{NOT} S \wedge (\text{tautology } C \vee \neg \text{distinct-mset } C)\}$  (**is**  $?T \subseteq ?S$ )

**proof** (*rule Set.subsetI*)

**fix** *C* **assume**  $C \in ?T$

**then have** *C-T*:  $C \in \# \text{ clauses}_{NOT} T$  **and** *t-d*: *tautology C  $\vee$   $\neg$  distinct-mset C*  
**by** *auto*

**then have**  $C \notin \text{simple-clss} (\text{atms-of-ms } A)$

**by** (*auto dest: simple-clssE*)

**then show**  $C \in ?S$

**using** *C-T* *rtrancpl-cdcl<sub>NOT</sub>-clauses-bound* [*OF assms*] *t-d* **by** *force*

**qed**

**then have**  $\text{card } \{C. C \in \# \text{ clauses}_{NOT} T \wedge (\text{tautology } C \vee \neg \text{distinct-mset } C)\} \leq$

$\text{card } \{C. C \in \# \text{ clauses}_{NOT} S \wedge (\text{tautology } C \vee \neg \text{distinct-mset } C)\}$

**by** (*simp add: card-mono*)

**then show** *?thesis*

**unfolding**  $\mu_{CDCL}'\text{-bound-def}$  **by** *auto*

**qed**

**end** — end of *conflict-driven-clause-learning-learning-before-backjump-only-distinct-learnt*

## 16.7 CDCL with restarts

### 16.7.1 Definition

**locale** *restart-ops* =

**fixes**

*cdcl<sub>NOT</sub> :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool and*

*restart :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool*

**begin**

**inductive** *cdcl<sub>NOT</sub>-raw-restart :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool* **where**

$cdcl_{NOT} S T \implies cdcl_{NOT\text{-raw-restart}} S T \mid$   
 $restart S T \implies cdcl_{NOT\text{-raw-restart}} S T$

**end**

**locale** *conflict-driven-clause-learning-with-restarts* =  
*conflict-driven-clause-learning mset-cls insert-cls remove-lit*  
*mset-clss union-clss in-clss insert-clss remove-from-clss*  
*trail raw-clauses prepend-trail tl-trail add-cls<sub>NOT</sub> remove-cls<sub>NOT</sub>*  
*inv backjump-conds propagate-conds learn-cond forget-cond*  
**for**  
*mset-cls* :: *'cls*  $\Rightarrow$  *'v clause* **and**  
*insert-cls* :: *'v literal*  $\Rightarrow$  *'cls*  $\Rightarrow$  *'cls* **and**  
*remove-lit* :: *'v literal*  $\Rightarrow$  *'cls*  $\Rightarrow$  *'cls* **and**  
*mset-clss* :: *'clss*  $\Rightarrow$  *'v clauses* **and**  
*union-clss* :: *'clss*  $\Rightarrow$  *'clss*  $\Rightarrow$  *'clss* **and**  
*in-clss* :: *'cls*  $\Rightarrow$  *'clss*  $\Rightarrow$  *bool* **and**  
*insert-clss* :: *'cls*  $\Rightarrow$  *'clss*  $\Rightarrow$  *'clss* **and**  
*remove-from-clss* :: *'cls*  $\Rightarrow$  *'clss*  $\Rightarrow$  *'clss* **and**  
*trail* :: *'st*  $\Rightarrow$  (*'v, unit, unit*) *marked-lits* **and**  
*raw-clauses* :: *'st*  $\Rightarrow$  *'clss* **and**  
*prepend-trail* :: (*'v, unit, unit*) *marked-lit*  $\Rightarrow$  *'st*  $\Rightarrow$  *'st* **and**  
*tl-trail* :: *'st*  $\Rightarrow$  *'st* **and**  
*add-cls<sub>NOT</sub>* :: *'cls*  $\Rightarrow$  *'st*  $\Rightarrow$  *'st* **and**  
*remove-cls<sub>NOT</sub>* :: *'cls*  $\Rightarrow$  *'st*  $\Rightarrow$  *'st* **and**  
*inv* :: *'st*  $\Rightarrow$  *bool* **and**  
*backjump-conds* :: *'v clause*  $\Rightarrow$  *'v clause*  $\Rightarrow$  *'v literal*  $\Rightarrow$  *'st*  $\Rightarrow$  *'st*  $\Rightarrow$  *bool* **and**  
*propagate-conds* :: (*'v, unit, unit*) *marked-lit*  $\Rightarrow$  *'st*  $\Rightarrow$  *bool* **and**  
*learn-cond forget-cond* :: *'cls*  $\Rightarrow$  *'st*  $\Rightarrow$  *bool*

**begin**

**lemma** *cdcl<sub>NOT</sub>-iff-cdcl<sub>NOT</sub>-raw-restart-no-restarts*:  
 $cdcl_{NOT} S T \longleftrightarrow restart\text{-ops}.cdcl_{NOT\text{-raw-restart}} cdcl_{NOT} (\lambda\text{-} \cdot. False) S T$   
**(is**  $?C S T \longleftrightarrow ?R S T$ **)**

**proof**

**fix** *S T*  
**assume**  $?C S T$   
**then show**  $?R S T$  **by** (*simp add: restart-ops.cdcl<sub>NOT</sub>-raw-restart.intros(1)*)  
**next**  
**fix** *S T*  
**assume**  $?R S T$   
**then show**  $?C S T$   
**apply** (*cases rule: restart-ops.cdcl<sub>NOT</sub>-raw-restart.cases*)  
**using**  $\langle ?R S T \rangle$  **by** *fast+*

**qed**

**lemma** *cdcl<sub>NOT</sub>-cdcl<sub>NOT</sub>-raw-restart*:  
 $cdcl_{NOT} S T \implies restart\text{-ops}.cdcl_{NOT\text{-raw-restart}} cdcl_{NOT} restart S T$   
**by** (*simp add: restart-ops.cdcl<sub>NOT</sub>-raw-restart.intros(1)*)  
**end**

## 16.7.2 Increasing restarts

To add restarts we need some assumptions on the predicate (called *cdcl<sub>NOT</sub>* here):

- a function *f* that is strictly monotonic. The first step is actually only used as a restart to

clean the state (e.g. to ensure that the trail is empty). Then we assume that  $(1::'a) \leq f$   $n$  for  $(1::'a) \leq n$ : it means that between two consecutive restarts, at least one step will be done. This is necessary to avoid sequence. like: full – restart – full – ...

- a measure  $\mu$ : it should decrease under the assumptions *bound-inv*, whenever a *cdcl<sub>NOT</sub>* or a *restart* is done. A parameter is given to  $\mu$ : for conflict- driven clause learning, it is an upper-bound of the clauses. We are assuming that such a bound can be found after a restart whenever the invariant holds.
- we also assume that the measure decrease after any *cdcl<sub>NOT</sub>* step.
- an invariant on the states *cdcl<sub>NOT</sub>-inv* that also holds after restarts.
- it is *not required* that the measure decrease with respect to restarts, but the measure has to be bound by some function  $\mu$ -*bound* taking the same parameter as  $\mu$  and the initial state of the considered *cdcl<sub>NOT</sub>* chain.

```

locale cdclNOT-increasing-restarts-ops =
  restart-ops cdclNOT restart for
    restart :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool and
    cdclNOT :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool +
fixes
  f :: nat  $\Rightarrow$  nat and
  bound-inv :: 'bound  $\Rightarrow$  'st  $\Rightarrow$  bool and
   $\mu$  :: 'bound  $\Rightarrow$  'st  $\Rightarrow$  nat and
  cdclNOT-inv :: 'st  $\Rightarrow$  bool and
   $\mu$ -bound :: 'bound  $\Rightarrow$  'st  $\Rightarrow$  nat
assumes
  f: unbounded f and
  f-ge-1:  $\bigwedge n. n \geq 1 \implies f\ n \neq 0$  and
  bound-inv:  $\bigwedge A\ S\ T. \text{cdcl}_{NOT}\text{-inv}\ S \implies \text{bound-inv}\ A\ S \implies \text{cdcl}_{NOT}\ S\ T \implies \text{bound-inv}\ A\ T$  and
  cdclNOT-measure:  $\bigwedge A\ S\ T. \text{cdcl}_{NOT}\text{-inv}\ S \implies \text{bound-inv}\ A\ S \implies \text{cdcl}_{NOT}\ S\ T \implies \mu\ A\ T < \mu$ 
  A S and
  measure-bound2:  $\bigwedge A\ T\ U. \text{cdcl}_{NOT}\text{-inv}\ T \implies \text{bound-inv}\ A\ T \implies \text{cdcl}_{NOT}^{**}\ T\ U$ 
     $\implies \mu\ A\ U \leq \mu\text{-bound}\ A\ T$  and
  measure-bound4:  $\bigwedge A\ T\ U. \text{cdcl}_{NOT}\text{-inv}\ T \implies \text{bound-inv}\ A\ T \implies \text{cdcl}_{NOT}^{**}\ T\ U$ 
     $\implies \mu\text{-bound}\ A\ U \leq \mu\text{-bound}\ A\ T$  and
  cdclNOT-restart-inv:  $\bigwedge A\ U\ V. \text{cdcl}_{NOT}\text{-inv}\ U \implies \text{restart}\ U\ V \implies \text{bound-inv}\ A\ U \implies \text{bound-inv}$ 
  A V
and
  exists-bound:  $\bigwedge R\ S. \text{cdcl}_{NOT}\text{-inv}\ R \implies \text{restart}\ R\ S \implies \exists A. \text{bound-inv}\ A\ S$  and
  cdclNOT-inv:  $\bigwedge S\ T. \text{cdcl}_{NOT}\text{-inv}\ S \implies \text{cdcl}_{NOT}\ S\ T \implies \text{cdcl}_{NOT}\text{-inv}\ T$  and
  cdclNOT-inv-restart:  $\bigwedge S\ T. \text{cdcl}_{NOT}\text{-inv}\ S \implies \text{restart}\ S\ T \implies \text{cdcl}_{NOT}\text{-inv}\ T$ 
begin

```

**lemma** *cdcl<sub>NOT</sub>-cdcl<sub>NOT</sub>-inv*:

**assumes**

$(\text{cdcl}_{NOT} \rightsquigarrow n)\ S\ T$  **and**

*cdcl<sub>NOT</sub>-inv* S

**shows** *cdcl<sub>NOT</sub>-inv* T

**using** *assms* **by** (*induction* n arbitrary: T) (*auto intro: bound-inv cdcl<sub>NOT</sub>-inv*)

**lemma** *cdcl<sub>NOT</sub>-bound-inv*:

**assumes**

$(\text{cdcl}_{NOT} \rightsquigarrow n)\ S\ T$  **and**

```

    cdclNOT-inv S
    bound-inv A S
shows bound-inv A T
using assms by (induction n arbitrary: T) (auto intro:bound-inv cdclNOT-cdclNOT-inv)

lemma rtrancp-cdclNOT-cdclNOT-inv:
assumes
    cdclNOT** S T and
    cdclNOT-inv S
shows cdclNOT-inv T
using assms by induction (auto intro: cdclNOT-inv)

lemma rtrancp-cdclNOT-bound-inv:
assumes
    cdclNOT** S T and
    bound-inv A S and
    cdclNOT-inv S
shows bound-inv A T
using assms by induction (auto intro:bound-inv rtrancp-cdclNOT-cdclNOT-inv)

lemma cdclNOT-comp-n-le:
assumes
    (cdclNOT  $\sim$  (Suc n)) S T and
    bound-inv A S
    cdclNOT-inv S
shows  $\mu$  A T <  $\mu$  A S - n
using assms
proof (induction n arbitrary: T)
  case 0
    then show ?case using cdclNOT-measure by auto
  next
    case (Suc n) note IH = this(1)[OF - this(3) this(4)] and S-T = this(2) and b-inv = this(3) and
    c-inv = this(4)
    obtain U :: 'st where S-U: (cdclNOT  $\sim$  (Suc n)) S U and U-T: cdclNOT U T using S-T by auto
    then have  $\mu$  A U <  $\mu$  A S - n using IH[of U] by simp
    moreover
      have bound-inv A U
      using S-U b-inv cdclNOT-bound-inv c-inv by blast
      then have  $\mu$  A T <  $\mu$  A U using cdclNOT-measure[OF - - U-T] S-U c-inv cdclNOT-cdclNOT-inv
    by auto
    ultimately show ?case by linarith
  qed

lemma wf-cdclNOT:
  wf {(T, S). cdclNOT S T  $\wedge$  cdclNOT-inv S  $\wedge$  bound-inv A S} (is wf ?A)
apply (rule wfP-if-measure2[of - -  $\mu$  A])
using cdclNOT-comp-n-le[of 0 - A] by auto

lemma rtrancp-cdclNOT-measure:
assumes
    cdclNOT** S T and
    bound-inv A S and
    cdclNOT-inv S
shows  $\mu$  A T  $\leq$   $\mu$  A S
using assms

```

**proof** (*induction rule: rtrancpl-induct*)  
**case** *base*  
**then show** ?*case* **by** *auto*  
**next**  
**case** (*step T U*) **note**  $IH = \text{this}(3)[OF \text{ this}(4) \text{ this}(5)]$  **and**  $st = \text{this}(1)$  **and**  $cdcl_{NOT} = \text{this}(2)$   
**and**  
 $b\text{-inv} = \text{this}(4)$  **and**  $c\text{-inv} = \text{this}(5)$   
**have**  $\text{bound-inv } A \ T$   
**by** (*meson cdcl<sub>NOT</sub>-bound-inv rtrancpl-imp-relpowp st step.premis*)  
**moreover have**  $cdcl_{NOT}\text{-inv } T$   
**using**  $c\text{-inv rtrancpl-cdcl}_{NOT}\text{-cdcl}_{NOT}\text{-inv st}$  **by** *blast*  
**ultimately have**  $\mu \ A \ U < \mu \ A \ T$  **using**  $cdcl_{NOT}\text{-measure}[OF \ - \ - \ cdcl_{NOT}]$  **by** *auto*  
**then show** ?*case* **using**  $IH$  **by** *linarith*  
**qed**

**lemma**  $cdcl_{NOT}\text{-comp-bounded}$ :

**assumes**  
 $\text{bound-inv } A \ S$  **and**  $cdcl_{NOT}\text{-inv } S$  **and**  $m \geq 1 + \mu \ A \ S$   
**shows**  $\neg(cdcl_{NOT} \rightsquigarrow^m) \ S \ T$   
**using** *assms cdcl<sub>NOT</sub>-comp-n-le[of m-1 S T A]* **by** *fastforce*

- $f \ n < m$  ensures that at least one step has been done.

**inductive**  $cdcl_{NOT}\text{-restart}$  **where**

*restart-step*:  $(cdcl_{NOT} \rightsquigarrow^m) \ S \ T \implies m \geq f \ n \implies \text{restart } T \ U$   
 $\implies cdcl_{NOT}\text{-restart } (S, n) \ (U, \text{Suc } n) \mid$   
*restart-full*:  $\text{full1 } cdcl_{NOT} \ S \ T \implies cdcl_{NOT}\text{-restart } (S, n) \ (T, \text{Suc } n)$

**lemmas**  $cdcl_{NOT}\text{-with-restart-induct} = cdcl_{NOT}\text{-restart.induct}[split-format(complete),$   
 $OF \ cdcl_{NOT}\text{-increasing-restarts-ops-axioms}]$

**lemma**  $cdcl_{NOT}\text{-restart-cdcl}_{NOT}\text{-raw-restart}$ :

$cdcl_{NOT}\text{-restart } S \ T \implies cdcl_{NOT}\text{-raw-restart}^{**} \ (fst \ S) \ (fst \ T)$

**proof** (*induction rule: cdcl<sub>NOT</sub>-restart.induct*)

**case** (*restart-step m S T n U*)  
**then have**  $cdcl_{NOT}^{**} \ S \ T$  **by** (*meson relpowp-imp-rtrancpl*)  
**then have**  $cdcl_{NOT}\text{-raw-restart}^{**} \ S \ T$  **using**  $cdcl_{NOT}\text{-raw-restart.intros}(1)$   
 $\text{rtrancpl-mono}[of \ cdcl_{NOT} \ cdcl_{NOT}\text{-raw-restart}]$  **by** *blast*  
**moreover have**  $cdcl_{NOT}\text{-raw-restart } T \ U$   
**using**  $\langle \text{restart } T \ U \rangle \ cdcl_{NOT}\text{-raw-restart.intros}(2)$  **by** *blast*  
**ultimately show** ?*case* **by** *auto*

**next**

**case** (*restart-full S T*)  
**then have**  $cdcl_{NOT}^{**} \ S \ T$  **unfolding** *full1-def* **by** *auto*  
**then show** ?*case* **using**  $cdcl_{NOT}\text{-raw-restart.intros}(1)$   
 $\text{rtrancpl-mono}[of \ cdcl_{NOT} \ cdcl_{NOT}\text{-raw-restart}]$  **by** *auto*  
**qed**

**lemma**  $cdcl_{NOT}\text{-with-restart-bound-inv}$ :

**assumes**  
 $cdcl_{NOT}\text{-restart } S \ T$  **and**  
 $\text{bound-inv } A \ (fst \ S)$  **and**  
 $cdcl_{NOT}\text{-inv } (fst \ S)$   
**shows**  $\text{bound-inv } A \ (fst \ T)$   
**using** *assms apply (induction rule: cdcl<sub>NOT</sub>-restart.induct)*

**prefer 2 apply** (*metis rtrancpl-unfold fstI full1-def rtrancpl-cdcl<sub>NOT</sub>-bound-inv*)  
**by** (*metis cdcl<sub>NOT</sub>-bound-inv cdcl<sub>NOT</sub>-cdcl<sub>NOT</sub>-inv cdcl<sub>NOT</sub>-restart-inv fst-conv*)

**lemma** *cdcl<sub>NOT</sub>-with-restart-cdcl<sub>NOT</sub>-inv*:

**assumes**  
*cdcl<sub>NOT</sub>-restart S T and*  
*cdcl<sub>NOT</sub>-inv (fst S)*  
**shows** *cdcl<sub>NOT</sub>-inv (fst T)*  
**using** *assms apply induction*  
**apply** (*metis cdcl<sub>NOT</sub>-cdcl<sub>NOT</sub>-inv cdcl<sub>NOT</sub>-inv-restart fst-conv*)  
**apply** (*metis fstI full-def full-unfold rtrancpl-cdcl<sub>NOT</sub>-cdcl<sub>NOT</sub>-inv*)  
**done**

**lemma** *rtrancpl-cdcl<sub>NOT</sub>-with-restart-cdcl<sub>NOT</sub>-inv*:

**assumes**  
*cdcl<sub>NOT</sub>-restart\*\* S T and*  
*cdcl<sub>NOT</sub>-inv (fst S)*  
**shows** *cdcl<sub>NOT</sub>-inv (fst T)*  
**using** *assms by induction (auto intro: cdcl<sub>NOT</sub>-with-restart-cdcl<sub>NOT</sub>-inv)*

**lemma** *rtrancpl-cdcl<sub>NOT</sub>-with-restart-bound-inv*:

**assumes**  
*cdcl<sub>NOT</sub>-restart\*\* S T and*  
*cdcl<sub>NOT</sub>-inv (fst S) and*  
*bound-inv A (fst S)*  
**shows** *bound-inv A (fst T)*  
**using** *assms apply induction*  
**apply** (*simp add: cdcl<sub>NOT</sub>-cdcl<sub>NOT</sub>-inv cdcl<sub>NOT</sub>-with-restart-bound-inv*)  
**using** *cdcl<sub>NOT</sub>-with-restart-bound-inv rtrancpl-cdcl<sub>NOT</sub>-with-restart-cdcl<sub>NOT</sub>-inv by blast*

**lemma** *cdcl<sub>NOT</sub>-with-restart-increasing-number*:

*cdcl<sub>NOT</sub>-restart S T  $\implies$  snd T = 1 + snd S*  
**by** (*induction rule: cdcl<sub>NOT</sub>-restart.induct*) *auto*  
**end**

**locale** *cdcl<sub>NOT</sub>-increasing-restarts =*

*cdcl<sub>NOT</sub>-increasing-restarts-ops restart cdcl<sub>NOT</sub> f bound-inv  $\mu$  cdcl<sub>NOT</sub>-inv  $\mu$ -bound +*  
*dpll-state mset-cls insert-cls remove-lit*  
*mset-clss union-clss in-clss insert-clss remove-from-clss*  
*trail raw-clauses prepend-trail tl-trail add-cl<sub>NOT</sub> remove-cl<sub>NOT</sub>*

**for**

*mset-cls:: 'cls  $\Rightarrow$  'v clause and*  
*insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and*  
*remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and*  
*mset-clss:: 'clss  $\Rightarrow$  'v clauses and*  
*union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and*  
*insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*trail :: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and*  
*raw-clauses :: 'st  $\Rightarrow$  'clss and*  
*prepend-trail :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*tl-trail :: 'st  $\Rightarrow$  'st and*  
*add-cl<sub>NOT</sub> :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*remove-cl<sub>NOT</sub> :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and*

```

f :: nat ⇒ nat and
restart :: 'st ⇒ 'st ⇒ bool and
bound-inv :: 'bound ⇒ 'st ⇒ bool and
μ :: 'bound ⇒ 'st ⇒ nat and
cdclNOT :: 'st ⇒ 'st ⇒ bool and
cdclNOT-inv :: 'st ⇒ bool and
μ-bound :: 'bound ⇒ 'st ⇒ nat +
assumes
  measure-bound:  $\bigwedge A\ T\ V\ n. \text{cdcl}_{NOT}\text{-inv}\ T \implies \text{bound-inv}\ A\ T$ 
     $\implies \text{cdcl}_{NOT}\text{-restart}\ (T, n)\ (V, \text{Suc}\ n) \implies \mu\ A\ V \leq \mu\text{-bound}\ A\ T$  and
  cdclNOT-raw-restart-μ-bound:
    cdclNOT-restart (T, a) (V, b)  $\implies \text{cdcl}_{NOT}\text{-inv}\ T \implies \text{bound-inv}\ A\ T$ 
     $\implies \mu\text{-bound}\ A\ V \leq \mu\text{-bound}\ A\ T$ 
begin

lemma rtrancp-cdclNOT-raw-restart-μ-bound:
  cdclNOT-restart** (T, a) (V, b)  $\implies \text{cdcl}_{NOT}\text{-inv}\ T \implies \text{bound-inv}\ A\ T$ 
     $\implies \mu\text{-bound}\ A\ V \leq \mu\text{-bound}\ A\ T$ 
apply (induction rule: rtrancp-induct2)
apply simp
by (metis cdclNOT-raw-restart-μ-bound dual-order.trans fst-conv
  rtrancp-cdclNOT-with-restart-bound-inv rtrancp-cdclNOT-with-restart-cdclNOT-inv)

lemma cdclNOT-raw-restart-measure-bound:
  cdclNOT-restart (T, a) (V, b)  $\implies \text{cdcl}_{NOT}\text{-inv}\ T \implies \text{bound-inv}\ A\ T$ 
     $\implies \mu\ A\ V \leq \mu\text{-bound}\ A\ T$ 
apply (cases rule: cdclNOT-restart.cases)
apply simp
using measure-bound relpowp-imp-rtrancp apply fastforce
by (metis full-def full-unfold measure-bound2 prod.inject)

lemma rtrancp-cdclNOT-raw-restart-measure-bound:
  cdclNOT-restart** (T, a) (V, b)  $\implies \text{cdcl}_{NOT}\text{-inv}\ T \implies \text{bound-inv}\ A\ T$ 
     $\implies \mu\ A\ V \leq \mu\text{-bound}\ A\ T$ 
apply (induction rule: rtrancp-induct2)
apply (simp add: measure-bound2)
by (metis dual-order.trans fst-conv measure-bound2 r-into-rtrancp rtrancp.rtrancp-refl
  rtrancp-cdclNOT-with-restart-bound-inv rtrancp-cdclNOT-with-restart-cdclNOT-inv
  rtrancp-cdclNOT-raw-restart-μ-bound)

lemma wf-cdclNOT-restart:
  wf {(T, S). cdclNOT-restart S T ∧ cdclNOT-inv (fst S)} (is wf ?A)
proof (rule ccontr)
assume  $\neg ?thesis$ 
then obtain g where
  g:  $\bigwedge i. \text{cdcl}_{NOT}\text{-restart}\ (g\ i)\ (g\ (\text{Suc}\ i))$  and
  cdclNOT-inv-g:  $\bigwedge i. \text{cdcl}_{NOT}\text{-inv}\ (\text{fst}\ (g\ i))$ 
unfolding wf-iff-no-infinite-down-chain by fast

have snd-g:  $\bigwedge i. \text{snd}\ (g\ i) = i + \text{snd}\ (g\ 0)$ 
apply (induct-tac i)
apply simp
by (metis Suc-eq-plus1-left add commute add.left-commute
  cdclNOT-with-restart-increasing-number g)
then have snd-g-0:  $\bigwedge i. i > 0 \implies \text{snd}\ (g\ i) = i + \text{snd}\ (g\ 0)$ 

```



```

by blast
have unbounded-f-g: unbounded ( $\lambda i. f (snd (g i))$ )
using f unfolding bounded-def by (metis add.commute f less-or-eq-imp-le snd-g
not-bounded-nat-exists-larger not-le le-iff-add)

{ fix i
  have H:  $\bigwedge T Ta m. (cdcl_{NOT} \rightsquigarrow m) T Ta \implies no\text{-}step\ cdcl_{NOT} T \implies m = 0$ 
    apply (case-tac m) by simp (meson relpowp-E2)
  have  $\exists T m. (cdcl_{NOT} \rightsquigarrow m) (fst (g i)) T \wedge m \geq f (snd (g i))$ 
    using g[of i] apply (cases rule: cdclNOT-restart.cases)
    apply auto[]
    using g[of Suc i] f-ge-1 apply (cases rule: cdclNOT-restart.cases)
    apply (auto simp add: full1-def full-def dest: H dest: tranclpD)
    using H Suc-leI leD by blast
} note H = this
obtain A where bound-inv A (fst (g 1))
using g[of 0] cdclNOT-inv-g[of 0] apply (cases rule: cdclNOT-restart.cases)
apply (metis One-nat-def cdclNOT-inv exists-bound fst-conv relpowp-imp-rtranclp
rtranclp-induct)
using H[of 1] unfolding full1-def by (metis One-nat-def Suc-eq-plus1 diff-is-0-eq' diff-zero
f-ge-1 fst-conv le-add2 relpowp-E2 snd-conv)
let ?j =  $\mu\text{-}bound\ A\ (fst\ (g\ 1)) + 1$ 
obtain j where
j:  $f (snd (g j)) > ?j$  and  $j > 1$ 
using unbounded-f-g not-bounded-nat-exists-larger by blast
{
  fix i j
  have cdclNOT-with-restart:  $j \geq i \implies cdcl_{NOT}\text{-}restart^{**} (g i) (g j)$ 
    apply (induction j)
    apply simp
    by (metis g le-Suc-eq rtranclp.rtrancl-into-rtrancl rtranclp.rtrancl-refl)
} note cdclNOT-restart = this
have cdclNOT-inv (fst (g (Suc 0)))
by (simp add: cdclNOT-inv-g)
have cdclNOT-restart** (fst (g 1), snd (g 1)) (fst (g j), snd (g j))
using <j> 1> by (simp add: cdclNOT-restart)
have  $\mu\ A\ (fst (g j)) \leq \mu\text{-}bound\ A\ (fst (g 1))$ 
apply (rule rtranclp-cdclNOT-raw-restart-measure-bound)
using <cdclNOT-restart** (fst (g 1), snd (g 1)) (fst (g j), snd (g j))> apply blast
apply (simp add: cdclNOT-inv-g)
using <bound-inv A (fst (g 1))> apply simp
done
then have  $\mu\ A\ (fst (g j)) \leq ?j$ 
by auto
have inv: bound-inv A (fst (g j))
using <bound-inv A (fst (g 1))> <cdclNOT-inv (fst (g (Suc 0)))>
<cdclNOT-restart** (fst (g 1), snd (g 1)) (fst (g j), snd (g j))>
rtranclp-cdclNOT-with-restart-bound-inv by auto
obtain T m where
cdclNOT-m:  $(cdcl_{NOT} \rightsquigarrow m) (fst (g j)) T$  and
f-m:  $f (snd (g j)) \leq m$ 
using H[of j] by blast
have ?j < m
using f-m j Nat.le-trans by linarith

```

**then show** *False*  
**using**  $\langle \mu \ A \ (fst \ (g \ j)) \leq \mu\text{-bound} \ A \ (fst \ (g \ 1)) \rangle$   
 $cdcl_{NOT}\text{-comp-bounded}[OF \ inv \ cdcl_{NOT}\text{-inv-g}, \ of \ ] \ cdcl_{NOT}\text{-inv-g} \ cdcl_{NOT}\text{-m}$   
 $\langle ?j < m \rangle$  **by** *auto*  
**qed**

**lemma** *cdcl<sub>NOT</sub>-restart-steps-bigger-than-bound*:  
**assumes**  
 $cdcl_{NOT}\text{-restart} \ S \ T$  **and**  
 $bound\text{-inv} \ A \ (fst \ S)$  **and**  
 $cdcl_{NOT}\text{-inv} \ (fst \ S)$  **and**  
 $f \ (snd \ S) > \mu\text{-bound} \ A \ (fst \ S)$   
**shows**  $full1 \ cdcl_{NOT} \ (fst \ S) \ (fst \ T)$   
**using** *assms*  
**proof** (*induction rule: cdcl<sub>NOT</sub>-restart.induct*)  
**case** *restart-full*  
**then show** *?case* **by** *auto*  
**next**  
**case** (*restart-step*  $m \ S \ T \ n \ U$ ) **note**  $st = this(1)$  **and**  $f = this(2)$  **and**  $bound\text{-inv} = this(4)$  **and**  
 $cdcl_{NOT}\text{-inv} = this(5)$  **and**  $\mu = this(6)$   
**then obtain**  $m'$  **where**  $m: m = Suc \ m'$  **by** (*cases*  $m$ ) *auto*  
**have**  $\mu \ A \ S - m' = 0$   
**using**  $f \ bound\text{-inv} \ cdcl_{NOT}\text{-inv} \ \mu \ m \ rtranclp\text{-}cdcl_{NOT}\text{-raw-restart-measure-bound}$  **by** *fastforce*  
**then have** *False* **using**  $cdcl_{NOT}\text{-comp-n-le}[of \ m' \ S \ T \ A]$  *restart-step* **unfolding**  $m$  **by** *simp*  
**then show** *?case* **by** *fast*  
**qed**

**lemma** *rtranclp-cdcl<sub>NOT</sub>-with-inv-inv-rtranclp-cdcl<sub>NOT</sub>*:  
**assumes**  
 $inv: cdcl_{NOT}\text{-inv} \ S$  **and**  
 $binv: bound\text{-inv} \ A \ S$   
**shows**  $(\lambda S \ T. \ cdcl_{NOT} \ S \ T \wedge \ cdcl_{NOT}\text{-inv} \ S \wedge \ bound\text{-inv} \ A \ S)^{**} \ S \ T \longleftrightarrow cdcl_{NOT}^{**} \ S \ T$   
**(is**  $?A^{**} \ S \ T \longleftrightarrow ?B^{**} \ S \ T$ **)**  
**apply** (*rule iffI*)  
**using**  $rtranclp\text{-mono}[of \ ?A \ ?B]$  **apply** *blast*  
**apply** (*induction rule: rtranclp-induct*)  
**using**  $inv \ binv$  **apply** *simp*  
**by** (*metis* (*mono-tags*, *lifting*)  $binv \ inv \ rtranclp.simps \ rtranclp\text{-}cdcl_{NOT}\text{-bound-inv} \ rtranclp\text{-}cdcl_{NOT}\text{-cdcl}_{NOT}\text{-inv}$ )

**lemma** *no-step-cdcl<sub>NOT</sub>-restart-no-step-cdcl<sub>NOT</sub>*:  
**assumes**  
 $n\text{-s}: no\text{-step} \ cdcl_{NOT}\text{-restart} \ S$  **and**  
 $inv: cdcl_{NOT}\text{-inv} \ (fst \ S)$  **and**  
 $binv: bound\text{-inv} \ A \ (fst \ S)$   
**shows**  $no\text{-step} \ cdcl_{NOT} \ (fst \ S)$   
**proof** (*rule ccontr*)  
**assume**  $\neg \ ?thesis$   
**then obtain**  $T$  **where**  $T: cdcl_{NOT} \ (fst \ S) \ T$   
**by** *blast*  
**then obtain**  $U$  **where**  $U: full \ (\lambda S \ T. \ cdcl_{NOT} \ S \ T \wedge \ cdcl_{NOT}\text{-inv} \ S \wedge \ bound\text{-inv} \ A \ S) \ T \ U$   
**using**  $wf\text{-exists-normal-form-full}[OF \ wf\text{-}cdcl_{NOT}, \ of \ A \ T]$  **by** *auto*  
**moreover have**  $inv\text{-}T: cdcl_{NOT}\text{-inv} \ T$   
**using**  $\langle cdcl_{NOT} \ (fst \ S) \ T \rangle \ cdcl_{NOT}\text{-inv} \ inv$  **by** *blast*  
**moreover have**  $b\text{-inv}\text{-}T: bound\text{-inv} \ A \ T$

```

    using  $\langle \text{cdcl}_{NOT} \text{ (fst } S) \text{ } T \rangle$  binv bound-inv inv by blast
ultimately have full  $\text{cdcl}_{NOT} \text{ } T \text{ } U$ 
    using rtrancpl-cdclNOT-with-inv-inv-rtrancpl-cdclNOT rtrancpl-cdclNOT-bound-inv
    rtrancpl-cdclNOT-cdclNOT-inv unfolding full-def by blast
then have full1  $\text{cdcl}_{NOT} \text{ (fst } S) \text{ } U$ 
    using  $T$  full-full1 by metis
then show False by (metis n-s prod.collapse restart-full)
qed

end

```

## 16.8 Merging backjump and learning

```

locale cdclNOT-merge-bj-learn-ops =
  decide-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT +
  forget-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT forget-cond +
  propagate-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT propagate-conds
for
  mset-cls:: 'cls  $\Rightarrow$  'v clause and
  insert-cls:: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lits:: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  mset-clss:: 'clss  $\Rightarrow$  'v clauses and
  union-clss:: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss:: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and
  insert-clss:: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  remove-from-clss:: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  trails:: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and
  raw-clauses:: 'st  $\Rightarrow$  'clss and
  prepend-trails:: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and
  tl-trails:: 'st  $\Rightarrow$  'st and
  add-clNOTs:: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  remove-clNOTs:: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  propagate-condss:: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  bool and
  forget-conds:: 'cls  $\Rightarrow$  'st  $\Rightarrow$  bool +
  fixes backjump-l-conds:: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool
begin
inductive backjump-l where
  backjump-l: trail  $S = F' @ \text{Marked } K \text{ } () \# F$ 
     $\Rightarrow$  no-dup (trail  $S$ )
     $\Rightarrow T \sim \text{prepend-trail } (\text{Propagated } L \text{ } ()) \text{ } (\text{reduce-trail-to}_{NOT} F \text{ } (\text{add-cl}_{NOT} C'' S))$ 
     $\Rightarrow C \in \# \text{ clauses}_{NOT} S$ 
     $\Rightarrow \text{trail } S \models_{as} C \text{Not } C$ 
     $\Rightarrow \text{undefined-lit } F L$ 
     $\Rightarrow \text{atm-of } L \in \text{atms-of-mm } (\text{clauses}_{NOT} S) \cup \text{atm-of } ' \text{ } (\text{lits-of-l } (\text{trail } S))$ 
     $\Rightarrow \text{clauses}_{NOT} S \models_{pm} C' + \{\#L\}$ 
     $\Rightarrow \text{mset-cls } C'' = C' + \{\#L\}$ 
     $\Rightarrow F \models_{as} C \text{Not } C'$ 
     $\Rightarrow \text{backjump-l-cond } C C' L S T$ 
     $\Rightarrow \text{backjump-l } S T$ 

```

Avoid (meaningless) simplification:

```
declare reduce-trail-toNOT-length-ne[simp del] Set.Un-iff[simp del] Set.insert-iff[simp del]
inductive-cases backjump-LE: backjump-l S T
thm backjump-LE
declare reduce-trail-toNOT-length-ne[simp] Set.Un-iff[simp] Set.insert-iff[simp]
```

```
inductive cdclNOT-merged-bj-learn :: 'st ⇒ 'st ⇒ bool for S :: 'st where
  cdclNOT-merged-bj-learn-decideNOT: decideNOT S S' ⇒ cdclNOT-merged-bj-learn S S' |
  cdclNOT-merged-bj-learn-propagateNOT: propagateNOT S S' ⇒ cdclNOT-merged-bj-learn S S' |
  cdclNOT-merged-bj-learn-backjump-l: backjump-l S S' ⇒ cdclNOT-merged-bj-learn S S' |
  cdclNOT-merged-bj-learn-forgetNOT: forgetNOT S S' ⇒ cdclNOT-merged-bj-learn S S'
```

```
lemma cdclNOT-merged-bj-learn-no-dup-inv:
  cdclNOT-merged-bj-learn S T ⇒ no-dup (trail S) ⇒ no-dup (trail T)
apply (induction rule: cdclNOT-merged-bj-learn.induct)
  using defined-lit-map apply fastforce
  using defined-lit-map apply fastforce
  apply (force simp: defined-lit-map elim!: backjump-LE)[]
using forgetNOT.simps apply auto[1]
done
end
```

```
locale cdclNOT-merge-bj-learn-proxy =
  cdclNOT-merge-bj-learn-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clsNOT remove-clsNOT propagate-conds
  forget-cond
  λC C' L' S T. backjump-l-cond C C' L' S T
  ∧ distinct-mset (C' + {#L'#}) ∧ ¬tautology (C' + {#L'#})
for
  mset-cls:: 'cls ⇒ 'v clause and
  insert-cls :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and
  mset-clss:: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  trail :: 'st ⇒ ('v, unit, unit) marked-lits and
  raw-clauses :: 'st ⇒ 'clss and
  prepend-trail :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and
  add-clsNOT :: 'cls ⇒ 'st ⇒ 'st and
  remove-clsNOT :: 'cls ⇒ 'st ⇒ 'st and
  propagate-conds :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ bool and
  forget-cond :: 'cls ⇒ 'st ⇒ bool and
  backjump-l-cond :: 'v clause ⇒ 'v clause ⇒ 'v literal ⇒ 'st ⇒ 'st ⇒ bool +
fixes
  inv :: 'st ⇒ bool
assumes
  bj-merge-can-jump:
  ∧S C F' K F L.
  inv S
  ⇒ trail S = F' @ Marked K () # F
  ⇒ C ∈# clausesNOT S
```

```

 $\Rightarrow \text{trail } S \models_{as} CNot \ C$ 
 $\Rightarrow \text{undefined-lit } F \ L$ 
 $\Rightarrow \text{atm-of } L \in \text{atms-of-mm } (\text{clauses}_{NOT} \ S) \cup \text{atm-of } ' \ (\text{lits-of-l } (F' @ \text{Marked } K \ () \ # \ F))$ 
 $\Rightarrow \text{clauses}_{NOT} \ S \models_{pm} C' + \{\#L\#\}$ 
 $\Rightarrow F \models_{as} CNot \ C'$ 
 $\Rightarrow \neg \text{no-step backjump-l } S \ \text{and}$ 
 $\text{cdcl-merged-inv: } \bigwedge S \ T. \ \text{cdcl}_{NOT}\text{-merged-bj-learn } S \ T \Rightarrow \text{inv } S \Rightarrow \text{inv } T$ 
begin

abbreviation backjump-conds :: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool
where
backjump-conds  $\equiv \lambda C \ C' \ L' \ S \ T. \ \text{distinct-mset } (C' + \{\#L'\#\}) \wedge \neg \text{tautology } (C' + \{\#L'\#\})$ 

Without additional knowledge on backjump-l-cond, it is impossible to have the same invariant.

sublocale dpll-with-backjumping-ops mset-cls insert-cls remove-lit
mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clss_{NOT} remove-clss_{NOT} inv
backjump-conds propagate-conds
proof (unfold-locales, goal-cases)
case 1
{ fix S S'
assume bj: backjump-l S S' and no-dup (trail S)
then obtain F' K F L C' C D where
S': S'  $\sim$  prepend-trail (Propagated L ()) (reduce-trail-to_{NOT} F (add-clss_{NOT} D S))
and
tr-S: trail S = F' @ Marked K () # F and
C: C  $\in$  # clauses_{NOT} S and
tr-S-C: trail S  $\models_{as} CNot \ C$  and
undef-L: undefined-lit F L and
atm-L:
atm-of L  $\in$  insert (atm-of K) (atms-of-mm (clauses_{NOT} S)  $\cup$  atm-of ' (lits-of-l F'  $\cup$  lits-of-l F))
and
cls-S-C': clauses_{NOT} S  $\models_{pm} C' + \{\#L\#\}$  and
F-C': F  $\models_{as} CNot \ C'$  and
dist: distinct-mset (C' + \{\#L\#\}) and
not-tauto:  $\neg$  tautology (C' + \{\#L\#\}) and
cond: backjump-l-cond C C' L S S'
mset-cls D = C' + \{\#L\#\}
by (elim backjump-lE) metis
interpret backjumping-ops mset-cls insert-cls remove-lit
mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clss_{NOT} remove-clss_{NOT}
backjump-conds
by unfold-locales
have  $\exists T. \ \text{backjump } S \ T$ 
apply rule
apply (rule backjump.intros)
using tr-S apply simp
apply (rule state-eq_{NOT}-ref)
using C apply simp
using tr-S-C apply simp
using undef-L apply simp
using atm-L tr-S apply simp
using cls-S-C' apply simp
using F-C' apply simp

```

```

    using dist not-tauto cond apply simp
  done
} note H = this(1)
then show ?case using 1 bj-merge-can-jump by meson
qed

end

locale cdclNOT-merge-bj-learn-proxy2 =
  cdclNOT-merge-bj-learn-proxy mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT
  propagate-conds forget-cond backjump-l-cond inv
for
  mset-cls:: 'cls  $\Rightarrow$  'v clause and
  insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  mset-clss:: 'clss  $\Rightarrow$  'v clauses and
  union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and
  insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  trail :: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and
  raw-clauses :: 'st  $\Rightarrow$  'clss and
  prepend-trail :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and
  tl-trail :: 'st  $\Rightarrow$  'st and
  add-clNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  remove-clNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  propagate-conds :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  bool and
  forget-cond :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  bool and
  backjump-l-cond :: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool and
  inv :: 'st  $\Rightarrow$  bool
begin

sublocale conflict-driven-clause-learning-ops mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT
  inv backjump-conds propagate-conds
   $\lambda C \cdot$  distinct-mset (mset-cls C)  $\wedge$   $\neg$ tautology (mset-cls C)
  forget-cond
by unfold-locales
end

locale cdclNOT-merge-bj-learn =
  cdclNOT-merge-bj-learn-proxy2 mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT
  propagate-conds forget-cond backjump-l-cond inv
for
  mset-cls:: 'cls  $\Rightarrow$  'v clause and
  insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  mset-clss:: 'clss  $\Rightarrow$  'v clauses and
  union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and

```

```

insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and
trail :: 'st ⇒ ('v, unit, unit) marked-lits and
raw-clauses :: 'st ⇒ 'clss and
prepend-trail :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ 'st and
tl-trail :: 'st ⇒ 'st and
add-clssNOT :: 'cls ⇒ 'st ⇒ 'st and
remove-clssNOT :: 'cls ⇒ 'st ⇒ 'st and
backjump-l-cond :: 'v clause ⇒ 'v clause ⇒ 'v literal ⇒ 'st ⇒ 'st ⇒ bool and
propagate-conds :: ('v, unit, unit) marked-lit ⇒ 'st ⇒ bool and
forget-cond :: 'cls ⇒ 'st ⇒ bool and
inv :: 'st ⇒ bool +
assumes
  dpll-merge-bj-inv:  $\bigwedge S T. \text{dpll-bj } S T \implies \text{inv } S \implies \text{inv } T$  and
  learn-inv:  $\bigwedge S T. \text{learn } S T \implies \text{inv } S \implies \text{inv } T$ 
begin

sublocale
  conflict-driven-clause-learning mset-cls insert-clss remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  trail raw-clauses prepend-trail tl-trail add-clssNOT remove-clssNOT
  inv backjump-conds propagate-conds
   $\lambda C -. \text{distinct-mset (mset-clss } C) \wedge \neg \text{tautology (mset-clss } C)$ 
  forget-cond
apply unfold-locales
using cdclNOT-merged-bj-learn-forgetNOT cdcl-merged-inv learn-inv
by (auto simp add: cdclNOT.simps dpll-merge-bj-inv)

lemma backjump-l-learn-backjump:
  assumes bt: backjump-l  $S T$  and inv: inv  $S$  and n-d: no-dup (trail  $S$ )
  shows  $\exists C' L D. \text{learn } S (\text{add-clss}_{\text{NOT}} D S)$ 
     $\wedge \text{mset-clss } D = (C' + \{\#L\# \})$ 
     $\wedge \text{backjump} (\text{add-clss}_{\text{NOT}} D S) T$ 
     $\wedge \text{atms-of } (C' + \{\#L\# \}) \subseteq \text{atms-of-mm (clauses}_{\text{NOT}} S) \cup \text{atm-of ' (lits-of-l (trail } S))$ 
proof -
  obtain  $C F' K F L l C' D$  where
    tr-S: trail  $S = F' @ \text{Marked } K () \# F$  and
    T:  $T \sim \text{prepend-trail (Propagated } L l) (\text{reduce-trail-to}_{\text{NOT}} F (\text{add-clss}_{\text{NOT}} D S))$  and
    C-clss-S:  $C \in \# \text{clauses}_{\text{NOT}} S$  and
    tr-S-CNot-C: trail  $S \models_{\text{as}} C\text{Not } C$  and
    undef: undefined-lit  $F L$  and
    atm-L: atm-of  $L \in \text{atms-of-mm (clauses}_{\text{NOT}} S) \cup \text{atm-of ' (lits-of-l (trail } S))$  and
    clss-C:  $\text{clauses}_{\text{NOT}} S \models_{\text{pm}} \text{mset-clss } D$  and
    D:  $\text{mset-clss } D = C' + \{\#L\# \}$ 
     $F \models_{\text{as}} C\text{Not } C'$  and
    distinct: distinct-mset (mset-clss  $D$ ) and
    not-tauto:  $\neg \text{tautology (mset-clss } D)$ 
  using bt inv by (elim backjump-lE) simp
  have atm-C': atm-of  $C' \subseteq \text{atm-of ' (lits-of-l } F)$ 
    by (metis D(2) atms-of-def image-subsetI true-annots-CNot-all-atms-defined)
  then have atm-of  $(C' + \{\#L\# \}) \subseteq \text{atms-of-mm (clauses}_{\text{NOT}} S) \cup \text{atm-of ' (lits-of-l (trail } S))$ 
    using atm-L tr-S by auto
  moreover have learn: learn  $S (\text{add-clss}_{\text{NOT}} D S)$ 
    apply (rule learn.intros)
    apply (rule clss-C)

```

using *atms-C' atm-L D* apply (*fastforce simp add: tr-S in-plus-implies-atm-of-on-atms-of-ms*)  
 apply *standard*  
 apply (*rule distinct*)  
 apply (*rule not-tauto*)  
 apply *simp*  
 done  
 moreover have *bj: backjump (add-cl<sub>NOT</sub> D S) T*  
 apply (*rule backjump.intros*)  
 using  $\langle F \models_{as} CNot\ C' \rangle$  *C-cl<sub>S</sub> tr-S-CNot-C undef T distinct not-tauto n-d D*  
 by (*auto simp: tr-S state-eq<sub>NOT</sub>-def simp del: state-simp<sub>NOT</sub>*)  
 ultimately show *?thesis using D by blast*  
 qed

**lemma** *cdcl<sub>NOT</sub>-merged-bj-learn-is-tranclp-cdcl<sub>NOT</sub>:*  
*cdcl<sub>NOT</sub>-merged-bj-learn S T  $\implies$  inv S  $\implies$  no-dup (trail S)  $\implies$  cdcl<sub>NOT</sub><sup>++</sup> S T*  
**proof** (*induction rule: cdcl<sub>NOT</sub>-merged-bj-learn.induct*)  
 case (*cdcl<sub>NOT</sub>-merged-bj-learn-decide<sub>NOT</sub> T*)  
 then have *cdcl<sub>NOT</sub> S T*  
 using *bj-decide<sub>NOT</sub> cdcl<sub>NOT</sub>.sims by fastforce*  
 then show *?case by auto*  
 next  
 case (*cdcl<sub>NOT</sub>-merged-bj-learn-propagate<sub>NOT</sub> T*)  
 then have *cdcl<sub>NOT</sub> S T*  
 using *bj-propagate<sub>NOT</sub> cdcl<sub>NOT</sub>.sims by fastforce*  
 then show *?case by auto*  
 next  
 case (*cdcl<sub>NOT</sub>-merged-bj-learn-forget<sub>NOT</sub> T*)  
 then have *cdcl<sub>NOT</sub> S T*  
 using *c-forget<sub>NOT</sub> by blast*  
 then show *?case by auto*  
 next  
 case (*cdcl<sub>NOT</sub>-merged-bj-learn-backjump-l T*) **note** *bt = this(1) and inv = this(2) and*  
*n-d = this(3)*  
**obtain** *C' :: 'v literal multiset and L :: 'v literal and D :: 'cls where*  
*f3: learn S (add-cl<sub>NOT</sub> D S)  $\wedge$*   
*backjump (add-cl<sub>NOT</sub> D S) T  $\wedge$*   
*atms-of (C' + {#L#})  $\subseteq$  atms-of-mm (clauses<sub>NOT</sub> S)  $\cup$  atm-of ' lits-of-l (trail S) and*  
*D: mset-cl<sub>S</sub> D = C' + {#L#}*  
 using *n-d backjump-l-learn-backjump[OF bt inv] by blast*  
 then have *f4: cdcl<sub>NOT</sub> S (add-cl<sub>NOT</sub> D S)*  
 using *n-d c-learn by blast*  
 have *cdcl<sub>NOT</sub> (add-cl<sub>NOT</sub> D S) T*  
 using *f3 n-d bj-backjump c-dpll-bj by blast*  
 then show *?case*  
 using *f4 by (meson tranclp.r-into-trancl tranclp.trancl-into-trancl)*  
 qed

**lemma** *rtranclp-cdcl<sub>NOT</sub>-merged-bj-learn-is-rtranclp-cdcl<sub>NOT</sub>-and-inv:*  
*cdcl<sub>NOT</sub>-merged-bj-learn\*\* S T  $\implies$  inv S  $\implies$  no-dup (trail S)  $\implies$  cdcl<sub>NOT</sub>\*\* S T  $\wedge$  inv T*  
**proof** (*induction rule: rtranclp-induct*)  
 case *base*  
 then show *?case by auto*  
 next  
 case (*step T U*) **note** *st = this(1) and cdcl<sub>NOT</sub> = this(2) and IH = this(3)[OF this(4-)] and*  
*inv = this(4) and n-d = this(5)*



**have**  $cdcl_{NOT}^{**} T U$   
**using**  $cdcl_{NOT}$ -merged-bj-learn-is-tranclp- $cdcl_{NOT}[OF\ cdcl_{NOT}] IH$   
 $rtranclp$ - $cdcl_{NOT}$ -no-dup  $inv\ n-d$  **by** *auto*  
**then have**  $cdcl_{NOT}^{**} S U$  **using**  $IH$  **by** *fastforce*  
**moreover have**  $inv\ U$  **using**  $n-d\ IH\ \langle cdcl_{NOT}^{**} T U \rangle\ rtranclp$ - $cdcl_{NOT}$ - $inv$  **by** *blast*  
**ultimately show**  $?case$  **using**  $st$  **by** *fast*  
**qed**

**lemma**  $rtranclp$ - $cdcl_{NOT}$ -merged-bj-learn-is- $rtranclp$ - $cdcl_{NOT}$ :  
 $cdcl_{NOT}$ -merged-bj-learn $^{**} S T \implies inv\ S \implies no\text{-}dup\ (trail\ S) \implies cdcl_{NOT}^{**} S T$   
**using**  $rtranclp$ - $cdcl_{NOT}$ -merged-bj-learn-is- $rtranclp$ - $cdcl_{NOT}$ -and- $inv$  **by** *blast*

**lemma**  $rtranclp$ - $cdcl_{NOT}$ -merged-bj-learn- $inv$ :  
 $cdcl_{NOT}$ -merged-bj-learn $^{**} S T \implies inv\ S \implies no\text{-}dup\ (trail\ S) \implies inv\ T$   
**using**  $rtranclp$ - $cdcl_{NOT}$ -merged-bj-learn-is- $rtranclp$ - $cdcl_{NOT}$ -and- $inv$  **by** *blast*

**definition**  $\mu_C' :: 'v\ literal\ multiset\ set \Rightarrow 'st \Rightarrow nat$  **where**  
 $\mu_C' A\ T \equiv \mu_C\ (1 + card\ (atms\text{-}of\text{-}ms\ A))\ (2 + card\ (atms\text{-}of\text{-}ms\ A))\ (trail\text{-}weight\ T)$

**definition**  $\mu_{CDCL}'$ -merged  $:: 'v\ literal\ multiset\ set \Rightarrow 'st \Rightarrow nat$  **where**  
 $\mu_{CDCL}'$ -merged  $A\ T \equiv$   
 $((2 + card\ (atms\text{-}of\text{-}ms\ A)) \wedge (1 + card\ (atms\text{-}of\text{-}ms\ A)) - \mu_C' A\ T) * 2 + card\ (set\text{-}mset\ (clauses_{NOT}\ T))$

**lemma**  $cdcl_{NOT}$ -decreasing-measure':  
**assumes**  
 $cdcl_{NOT}$ -merged-bj-learn  $S\ T$  **and**  
 $inv$ :  $inv\ S$  **and**  
 $atm\text{-}clss$ :  $atms\text{-}of\text{-}mm\ (clauses_{NOT}\ S) \subseteq atms\text{-}of\text{-}ms\ A$  **and**  
 $atm\text{-}trail$ :  $atm\text{-}of\ ' lits\text{-}of\text{-}l\ (trail\ S) \subseteq atms\text{-}of\text{-}ms\ A$  **and**  
 $n\text{-}d$ :  $no\text{-}dup\ (trail\ S)$  **and**  
 $fin\text{-}A$ :  $finite\ A$   
**shows**  $\mu_{CDCL}'$ -merged  $A\ T < \mu_{CDCL}'$ -merged  $A\ S$   
**using** *assms(1)*

**proof** *induction*  
**case** ( $cdcl_{NOT}$ -merged-bj-learn-decide $_{NOT}\ T$ )  
**have**  $clauses_{NOT}\ S = clauses_{NOT}\ T$   
**using**  $cdcl_{NOT}$ -merged-bj-learn-decide $_{NOT}$ .*hyps* **by** *auto*  
**moreover have**  
 $(2 + card\ (atms\text{-}of\text{-}ms\ A)) \wedge (1 + card\ (atms\text{-}of\text{-}ms\ A))$   
 $- \mu_C\ (1 + card\ (atms\text{-}of\text{-}ms\ A))\ (2 + card\ (atms\text{-}of\text{-}ms\ A))\ (trail\text{-}weight\ T)$   
 $< (2 + card\ (atms\text{-}of\text{-}ms\ A)) \wedge (1 + card\ (atms\text{-}of\text{-}ms\ A))$   
 $- \mu_C\ (1 + card\ (atms\text{-}of\text{-}ms\ A))\ (2 + card\ (atms\text{-}of\text{-}ms\ A))\ (trail\text{-}weight\ S)$   
**apply** (*rule dpll-bj-trail-mes-decreasing-prop*)  
**using**  $cdcl_{NOT}$ -merged-bj-learn-decide $_{NOT}\ fin\text{-}A\ atm\text{-}clss\ atm\text{-}trail\ n\text{-}d\ inv$   
**by** (*simp-all add: bj-decide $_{NOT}\ cdcl_{NOT}$ -merged-bj-learn-decide $_{NOT}$ .hyps*)  
**ultimately show**  $?case$   
**unfolding**  $\mu_{CDCL}'$ -merged-def  $\mu_C'$ -def **by** *simp*

**next**  
**case** ( $cdcl_{NOT}$ -merged-bj-learn-propagate $_{NOT}\ T$ )  
**have**  $clauses_{NOT}\ S = clauses_{NOT}\ T$   
**using**  $cdcl_{NOT}$ -merged-bj-learn-propagate $_{NOT}$ .*hyps*  
**by** (*simp add: bj-propagate $_{NOT}\ inv\ dpll$ -bj-clauses*)  
**moreover have**  
 $(2 + card\ (atms\text{-}of\text{-}ms\ A)) \wedge (1 + card\ (atms\text{-}of\text{-}ms\ A))$

$\begin{aligned} & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) (\text{trail-weight } T) \\ & < (2 + \text{card} (\text{atms-of-ms } A)) \wedge (1 + \text{card} (\text{atms-of-ms } A)) \\ & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) (\text{trail-weight } S) \end{aligned}$   
**apply** (rule *dp11-bj-trail-mes-decreasing-prop*)  
**using** *inv n-d atm-clss atm-trail fin-A* **by** (*simp-all add: bj-propagate<sub>NOT</sub>*  
*cdcl<sub>NOT</sub>-merged-bj-learn-propagate<sub>NOT</sub>.hyps*)  
**ultimately show** ?*case*  
**unfolding**  $\mu_{CDCL}'$ -merged-def  $\mu_C'$ -def **by** *simp*  
**next**  
**case** (*cdcl<sub>NOT</sub>-merged-bj-learn-forget<sub>NOT</sub> T*)  
**have** *card (set-mset (clauses<sub>NOT</sub> T)) < card (set-mset (clauses<sub>NOT</sub> S))*  
**using** *⟨forget<sub>NOT</sub> S T⟩ by (metis card-Diff1-less clauses-remove-cls<sub>NOT</sub> finite-set-mset*  
*forget<sub>NOT</sub>.cases in-clss-mset-clss linear set-mset-minus-replicate-mset(1) state-eq<sub>NOT</sub>-def)*  
**moreover**  
**have** *trail S = trail T*  
**using** *⟨forget<sub>NOT</sub> S T⟩ by (auto elim: forget<sub>NOT</sub>E)*  
**then have**  
 $\begin{aligned} & (2 + \text{card} (\text{atms-of-ms } A)) \wedge (1 + \text{card} (\text{atms-of-ms } A)) \\ & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) (\text{trail-weight } T) \\ & = (2 + \text{card} (\text{atms-of-ms } A)) \wedge (1 + \text{card} (\text{atms-of-ms } A)) \\ & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) (\text{trail-weight } S) \end{aligned}$   
**by** *auto*  
**ultimately show** ?*case*  
**unfolding**  $\mu_{CDCL}'$ -merged-def  $\mu_C'$ -def **by** *simp*  
**next**  
**case** (*cdcl<sub>NOT</sub>-merged-bj-learn-backjump-l T*) **note** *bj-l = this(1)*  
**obtain** *C' L D* **where**  
*learn: learn S (add-cls<sub>NOT</sub> D S) and*  
*bj: backjump (add-cls<sub>NOT</sub> D S) T and*  
*atms-C: atms-of (C' + {#L#})  $\subseteq$  atms-of-mm (clauses<sub>NOT</sub> S)  $\cup$  atm-of ' (lits-of-l (trail S)) and*  
*D: mset-cls D = C' + {#L#}*  
**using** *bj-l inv backjump-l-learn-backjump n-d atm-clss atm-trail* **by** *meson*  
**have** *card-T-S: card (set-mset (clauses<sub>NOT</sub> T))  $\leq$  1 + card (set-mset (clauses<sub>NOT</sub> S))*  
**using** *bj-l inv* **by** (*force elim!: backjump-lE simp: card-insert-if*)  
**have**  
 $\begin{aligned} & ((2 + \text{card} (\text{atms-of-ms } A)) \wedge (1 + \text{card} (\text{atms-of-ms } A)) \\ & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) (\text{trail-weight } T)) \\ & < ((2 + \text{card} (\text{atms-of-ms } A)) \wedge (1 + \text{card} (\text{atms-of-ms } A)) \\ & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) \\ & (\text{trail-weight } (\text{add-cls}_{NOT} D S))) \end{aligned}$   
**apply** (rule *dp11-bj-trail-mes-decreasing-prop*)  
**using** *bj bj-backjump* **apply** *blast*  
**using** *cdcl<sub>NOT</sub>.c-learn cdcl<sub>NOT</sub>-inv inv learn* **apply** *blast*  
**using** *atms-C atm-clss atm-trail D* **apply** (*simp add: n-d*) **apply** *fast*  
**using** *atm-trail n-d* **apply** *simp*  
**apply** (*simp add: n-d*)  
**using** *fin-A* **apply** *simp*  
**done**  
**then have**  $\begin{aligned} & ((2 + \text{card} (\text{atms-of-ms } A)) \wedge (1 + \text{card} (\text{atms-of-ms } A)) \\ & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) (\text{trail-weight } T)) \\ & < ((2 + \text{card} (\text{atms-of-ms } A)) \wedge (1 + \text{card} (\text{atms-of-ms } A)) \\ & - \mu_C (1 + \text{card} (\text{atms-of-ms } A)) (2 + \text{card} (\text{atms-of-ms } A)) (\text{trail-weight } S)) \end{aligned}$   
**using** *n-d* **by** *auto*  
**then show** ?*case*  
**using** *card-T-S* **unfolding**  $\mu_{CDCL}'$ -merged-def  $\mu_C'$ -def **by** *linarith*

qed

**lemma** *wf-cdcl<sub>NOT</sub>-merged-bj-learn*:

**assumes**

*fin-A*: *finite A*

**shows** *wf*  $\{(T, S).$

$(inv\ S \wedge atms-of-mm\ (clauses_{NOT}\ S) \subseteq atms-of-ms\ A \wedge atm-of\ 'lits-of-l\ (trail\ S) \subseteq atms-of-ms\ A$   
 $\wedge no-dup\ (trail\ S))$

$\wedge cdcl_{NOT}\text{-merged-bj-learn}\ S\ T\}$

**apply** (*rule wfP-if-measure*[*of* - -  $\mu_{CDCL}'$ -merged *A*])

**using** *cdcl<sub>NOT</sub>-decreasing-measure'* *fin-A* **by** *simp*

**lemma** *tranclp-cdcl<sub>NOT</sub>-cdcl<sub>NOT</sub>-tranclp*:

**assumes**

*cdcl<sub>NOT</sub>-merged-bj-learn*<sup>++</sup> *S T* **and**

*inv*: *inv S* **and**

*atm-clss*: *atms-of-mm* (*clauses<sub>NOT</sub> S*)  $\subseteq$  *atms-of-ms A* **and**

*atm-trail*: *atm-of* ' *lits-of-l* (*trail S*)  $\subseteq$  *atms-of-ms A* **and**

*n-d*: *no-dup* (*trail S*) **and**

*fin-A*[*simp*]: *finite A*

**shows**  $(T, S) \in \{(T, S).$

$(inv\ S \wedge atms-of-mm\ (clauses_{NOT}\ S) \subseteq atms-of-ms\ A \wedge atm-of\ 'lits-of-l\ (trail\ S) \subseteq atms-of-ms\ A$   
 $\wedge no-dup\ (trail\ S))$

$\wedge cdcl_{NOT}\text{-merged-bj-learn}\ S\ T\}^+ \text{ (is - } \in ?P^+)$

**using** *assms*(1)

**proof** (*induction rule*: *tranclp-induct*)

**case** *base*

**then show** ?*case* **using** *n-d atm-clss atm-trail inv* **by** *auto*

**next**

**case** (*step T U*) **note** *st* = *this*(1) **and** *cdcl<sub>NOT</sub>* = *this*(2) **and** *IH* = *this*(3)

**have** *cdcl<sub>NOT</sub>*<sup>\*\*</sup> *S T*

**apply** (*rule rtranclp-cdcl<sub>NOT</sub>-merged-bj-learn-is-rtranclp-cdcl<sub>NOT</sub>*)

**using** *st cdcl<sub>NOT</sub> inv n-d atm-clss atm-trail inv* **by** *auto*

**have** *inv T*

**apply** (*rule rtranclp-cdcl<sub>NOT</sub>-merged-bj-learn-inv*)

**using** *inv st cdcl<sub>NOT</sub> n-d atm-clss atm-trail inv* **by** *auto*

**moreover have** *atms-of-mm* (*clauses<sub>NOT</sub> T*)  $\subseteq$  *atms-of-ms A*

**using** *rtranclp-cdcl<sub>NOT</sub>-trail-clauses-bound*[*OF*  $\langle cdcl_{NOT}^{**}\ S\ T \rangle$  *inv n-d atm-clss atm-trail*]  
**by** *fast*

**moreover have** *atm-of* ' (*lits-of-l* (*trail T*))  $\subseteq$  *atms-of-ms A*

**using** *rtranclp-cdcl<sub>NOT</sub>-trail-clauses-bound*[*OF*  $\langle cdcl_{NOT}^{**}\ S\ T \rangle$  *inv n-d atm-clss atm-trail*]  
**by** *fast*

**moreover have** *no-dup* (*trail T*)

**using** *rtranclp-cdcl<sub>NOT</sub>-no-dup*[*OF*  $\langle cdcl_{NOT}^{**}\ S\ T \rangle$  *inv n-d*] **by** *fast*

**ultimately have**  $(U, T) \in ?P$

**using** *cdcl<sub>NOT</sub>* **by** *auto*

**then show** ?*case* **using** *IH* **by** (*simp add*: *trancl-into-trancl2*)

qed

**lemma** *wf-tranclp-cdcl<sub>NOT</sub>-merged-bj-learn*:

**assumes** *finite A*

**shows** *wf*  $\{(T, S).$

$(inv\ S \wedge atms-of-mm\ (clauses_{NOT}\ S) \subseteq atms-of-ms\ A \wedge atm-of\ 'lits-of-l\ (trail\ S) \subseteq atms-of-ms\ A$   
 $\wedge no-dup\ (trail\ S))$

$\wedge cdcl_{NOT}\text{-merged-bj-learn}^{++}\ S\ T\}$

```

apply (rule wf-subset)
apply (rule wf-trancl[OF wf-cdclNOT-merged-bj-learn])
using assms apply simp
using tranclp-cdclNOT-cdclNOT-tranclp[OF - - - - ⟨finite A⟩] by auto

```

```

lemma backjump-no-step-backjump-l:
  backjump S T  $\implies$  inv S  $\implies$   $\neg$ no-step backjump-l S
apply (elim backjumpE)
apply (rule bj-merge-can-jump)
  apply auto[7]
by blast

```

```

lemma cdclNOT-merged-bj-learn-final-state:
  fixes A :: 'v literal multiset set and S T :: 'st
  assumes
    n-s: no-step cdclNOT-merged-bj-learn S and
    atms-S: atms-of-mm (clausesNOT S)  $\subseteq$  atms-of-ms A and
    atms-trail: atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-ms A and
    n-d: no-dup (trail S) and
    finite A and
    inv: inv S and
    decomp: all-decomposition-implies-m (clausesNOT S) (get-all-marked-decomposition (trail S))
  shows unsatisfiable (set-mset (clausesNOT S))
     $\vee$  (trail S  $\models$ asm clausesNOT S  $\wedge$  satisfiable (set-mset (clausesNOT S)))

```

```

proof -
  let ?N = set-mset (clausesNOT S)
  let ?M = trail S
  consider
    (sat) satisfiable ?N and ?M  $\models_{as}$  ?N
  | (sat') satisfiable ?N and  $\neg$  ?M  $\models_{as}$  ?N
  | (unsat) unsatisfiable ?N
  by auto
  then show ?thesis
  proof cases
    case sat' note sat = this(1) and M = this(2)
    obtain C where C  $\in$  ?N and  $\neg$ ?M  $\models_a$  C using M unfolding true-annots-def by auto
    obtain I :: 'v literal set where
      I  $\models_s$  ?N and
      cons: consistent-interp I and
      tot: total-over-m I ?N and
      atm-I-N: atm-of ' I  $\subseteq$  atms-of-ms ?N
    using sat unfolding satisfiable-def-min by auto
    let ?I = I  $\cup$  {P | P. P  $\in$  lits-of-l ?M  $\wedge$  atm-of P  $\notin$  atm-of ' I}
    let ?O = {unmark L | L. is-marked L  $\wedge$  L  $\in$  set ?M  $\wedge$  atm-of (lit-of L)  $\notin$  atms-of-ms ?N}
    have cons-I': consistent-interp ?I
      using cons using ⟨no-dup ?M⟩ unfolding consistent-interp-def
      by (auto simp add: atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set lits-of-def
        dest!: no-dup-cannot-not-lit-and-uminus)
    have tot-I': total-over-m ?I (?N  $\cup$  unmark-l ?M)
      using tot atms-of-s-def unfolding total-over-m-def total-over-set-def
      by (fastforce simp: image-iff)
    have {P | P. P  $\in$  lits-of-l ?M  $\wedge$  atm-of P  $\notin$  atm-of ' I}  $\models_s$  ?O
      using ⟨I  $\models_s$  ?N⟩ atm-I-N by (auto simp add: atm-of-eq-atm-of true-clss-def lits-of-def)
    then have I'-N: ?I  $\models_s$  ?N  $\cup$  ?O
      using ⟨I  $\models_s$  ?N⟩ true-clss-union-increase by force

```

```

have tot': total-over-m ?I (?N ∪ ?O)
  using atm-I-N tot unfolding total-over-m-def total-over-set-def
  by (force simp: image-iff lits-of-def dest!: is-marked-ex-Marked)

have atms-N-M: atms-of-ms ?N ⊆ atm-of ' lits-of-l ?M
proof (rule ccontr)
  assume ¬ ?thesis
  then obtain l :: 'v where
    l-N: l ∈ atms-of-ms ?N and
    l-M: l ∉ atm-of ' lits-of-l ?M
  by auto
have undefined-lit ?M (Pos l)
  using l-M by (metis Marked-Propagated-in-iff-in-lits-of-l
    atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set literal.sel(1))
have decideNOT S (prepend-trail (Marked (Pos l) ()) S)
  by (metis ⟨undefined-lit ?M (Pos l)⟩ decideNOT.intros l-N literal.sel(1)
    state-eqNOT-ref)
then show False
  using cdclNOT-merged-bj-learn-decideNOT n-s by blast
qed

have ?M ⊨as CNot C
apply (rule all-variables-defined-not-imply-cnot)
  using atms-N-M ⟨C ∈ ?N⟩ ⟨¬ ?M ⊨a C⟩ atms-of-atms-of-ms-mono[OF ⟨C ∈ ?N⟩]
  by (auto dest: atms-of-atms-of-ms-mono)
have ∃ l ∈ set ?M. is-marked l
proof (rule ccontr)
  let ?O = {unmark L | L. is-marked L ∧ L ∈ set ?M ∧ atm-of (lit-of L) ∉ atms-of-ms ?N}
  have ∅[iff]: ∧ I. total-over-m I (?N ∪ ?O ∪ unmark-l ?M)
    ⟷ total-over-m I (?N ∪ unmark-l ?M)
  unfolding total-over-set-def total-over-m-def atms-of-ms-def by blast
  assume ¬ ?thesis
  then have [simp]: {unmark L | L. is-marked L ∧ L ∈ set ?M}
    = {unmark L | L. is-marked L ∧ L ∈ set ?M ∧ atm-of (lit-of L) ∉ atms-of-ms ?N}
  by auto
  then have ?N ∪ ?O ⊨ps unmark-l ?M
    using all-decomposition-implies-propagated-lits-are-implied[OF decomp] by auto

  then have ?I ⊨s unmark-l ?M
    using cons-I' I'-N tot-I' ⟨?I ⊨s ?N ∪ ?O⟩ unfolding ∅ true-clss-clss-def by blast
  then have lits-of-l ?M ⊆ ?I
    unfolding true-clss-def lits-of-def by auto
  then have ?M ⊨as ?N
    using I'-N ⟨C ∈ ?N⟩ ⟨¬ ?M ⊨a C⟩ cons-I' atms-N-M
    by (meson ⟨trail S ⊨as CNot C⟩ consistent-CNot-not rev-subsetD sup-ge1 true-annot-def
      true-annot-def true-cls-mono-set-mset-l true-clss-def)
  then show False using M by fast
qed

from List.split-list-first-propE[OF this] obtain K :: 'v literal and d :: unit and
  F F' :: ('v, unit, unit) marked-lit list where
  M-K: ?M = F' @ Marked K () # F and
  nm: ∀ f ∈ set F'. ¬ is-marked f
  unfolding is-marked-def by (metis (full-types) old.unit.exhaust)
let ?K = Marked K () :: ('v, unit, unit) marked-lit
have ?K ∈ set ?M

```

```

  unfolding M-K by auto
let ?C = image-mset lit-of {#L∈#mset ?M. is-marked L ∧ L≠?K#} :: 'v literal multiset
let ?C' = set-mset (image-mset (λL::'v literal. {#L#}) (?C + unmark ?K))
have ?N ∪ {unmark L | L. is-marked L ∧ L ∈ set ?M} ⊨ps unmark-l ?M
  using all-decomposition-implies-propagated-lits-are-implied[OF decomp] .
moreover have C': ?C' = {unmark L | L. is-marked L ∧ L ∈ set ?M}
  unfolding M-K apply standard
  apply force
  using IntI by auto
ultimately have N-C-M: ?N ∪ ?C' ⊨ps unmark-l ?M
  by auto
have N-M-False: ?N ∪ (λL. unmark L) ' (set ?M) ⊨ps {{#}}
  using M ⟨?M ⊨as CNot C⟩ ⟨C∈?N⟩ unfolding true-clss-clss-def true-annot-def Ball-def
  true-annot-def by (metis consistent-CNot-not sup.orderE sup-commute true-clss-def
    true-clss-singleton-lit-of-implies-incl true-clss-union true-clss-union-increase)

have undefined-lit F K using ⟨no-dup ?M⟩ unfolding M-K by (simp add: defined-lit-map)
moreover
  have ?N ∪ ?C' ⊨ps {{#}}
  proof -
    have A: ?N ∪ ?C' ∪ unmark-l ?M = ?N ∪ unmark-l ?M
      unfolding M-K by auto
    show ?thesis
      using true-clss-clss-left-right[OF N-C-M, of {{#}}] N-M-False unfolding A by auto
  qed
have ?N ⊨p image-mset uminus ?C + {#-K#}
  unfolding true-clss-clss-def true-clss-clss-def total-over-m-def
  proof (intro allI impI)
    fix I
    assume
      tot: total-over-set I (atms-of-ms (?N ∪ {image-mset uminus ?C + {#-K#}})) and
      cons: consistent-interp I and
      I ⊨s ?N
    have (K ∈ I ∧ -K ∉ I) ∨ (-K ∈ I ∧ K ∉ I)
      using cons tot unfolding consistent-interp-def by (cases K) auto
    have {a ∈ set (trail S). is-marked a ∧ a ≠ Marked K ()} =
      set (trail S) ∩ {L. is-marked L ∧ L ≠ Marked K ()}
      by auto
    then have tot': total-over-set I
      (atm-of ' lit-of ' (set ?M ∩ {L. is-marked L ∧ L ≠ Marked K ()}))
      using tot by (auto simp add: atms-of-uminus-lit-atm-of-lit-of)
    { fix x :: ('v, unit, unit) marked-lit
      assume
        a3: lit-of x ∉ I and
        a1: x ∈ set ?M and
        a4: is-marked x and
        a5: x ≠ Marked K ()
      then have Pos (atm-of (lit-of x)) ∈ I ∨ Neg (atm-of (lit-of x)) ∈ I
        using a5 a4 tot' a1 unfolding total-over-set-def atms-of-s-def by blast
      moreover have f6: Neg (atm-of (lit-of x)) = - Pos (atm-of (lit-of x))
        by simp
      ultimately have - lit-of x ∈ I
        using f6 a3 by (metis (no-types) atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set
          literal.sel(1))
    } note H = this
  }

```

```

have  $\neg I \models_s ?C'$ 
  using  $\langle ?N \cup ?C' \models_{ps} \{\{\#\}\} \rangle$  tot cons  $\langle I \models_s ?N \rangle$ 
  unfolding true-clss-clss-def total-over-m-def
  by (simp add: atms-of-uminus-lit-atm-of-lit-of atms-of-ms-single-image-atm-of-lit-of)
then show  $I \models$  image-mset uminus  $?C + \{\# - K\#$ 
  unfolding true-clss-def true-cl-def Bex-def
  using  $\langle (K \in I \wedge -K \notin I) \vee (-K \in I \wedge K \notin I) \rangle$ 
  by (auto dest!: H)
qed
moreover have  $F \models_{as} CNot$  (image-mset uminus  $?C$ )
  using nm unfolding true-annots-def CNot-def M-K by (auto simp add: lits-of-def)
ultimately have False
  using bj-merge-can-jump[of S F' K F C -K
    image-mset uminus (image-mset lit-of  $\{\# L : \#$  mset  $?M$ . is-marked  $L \wedge L \neq$  Marked  $K ()\#\}$ )]
     $\langle C \in ?N \rangle$  n-s  $\langle ?M \models_{as} CNot$  C  $\rangle$  bj-backjump inv unfolding M-K
  by (auto simp: cdclNOT-merged-bj-learn.simps)
then show ?thesis by fast
qed auto
qed

lemma full-cdclNOT-merged-bj-learn-final-state:
  fixes A :: 'v literal multiset set and S T :: 'st
  assumes
    full: full cdclNOT-merged-bj-learn S T and
    atms-S: atms-of-mm (clausesNOT S)  $\subseteq$  atms-of-ms A and
    atms-trail: atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-ms A and
    n-d: no-dup (trail S) and
    finite A and
    inv: inv S and
    decomp: all-decomposition-implies-m (clausesNOT S) (get-all-marked-decomposition (trail S))
  shows unsatisfiable (set-mset (clausesNOT T))
     $\vee$  (trail T  $\models_{asm}$  clausesNOT T  $\wedge$  satisfiable (set-mset (clausesNOT T)))
proof -
  have st: cdclNOT-merged-bj-learn** S T and n-s: no-step cdclNOT-merged-bj-learn T
    using full unfolding full-def by blast+
  then have st: cdclNOT** S T
    using inv rtranclp-cdclNOT-merged-bj-learn-is-rtranclp-cdclNOT-and-inv n-d by auto
  have atms-of-mm (clausesNOT T)  $\subseteq$  atms-of-ms A and atm-of ' lits-of-l (trail T)  $\subseteq$  atms-of-ms A
    using rtranclp-cdclNOT-trail-clauses-bound[OF st inv n-d atms-S atms-trail] by blast+
  moreover have no-dup (trail T)
    using rtranclp-cdclNOT-no-dup inv n-d st by blast
  moreover have inv T
    using rtranclp-cdclNOT-inv inv st by blast
  moreover have all-decomposition-implies-m (clausesNOT T) (get-all-marked-decomposition (trail T))
    using rtranclp-cdclNOT-all-decomposition-implies inv st decomp n-d by blast
  ultimately show ?thesis
    using cdclNOT-merged-bj-learn-final-state[of T A]  $\langle$ finite A  $\rangle$  n-s by fast
qed
end

```

### 16.8.1 Instantiations

locale cdcl<sub>NOT</sub>-with-backtrack-and-restarts =  
 conflict-driven-clause-learning-learning-before-backjump-only-distinct-learn<sub>t</sub>

```

mset-cls insert-cls remove-lit
mset-clss union-clss in-clss insert-clss remove-from-clss
trail raw-clauses prepend-trail tl-trail add-clNOT remove-clNOT
inv backjump-conds propagate-conds learn-restrictions forget-restrictions
for
  mset-cls:: 'cls  $\Rightarrow$  'v clause and
  insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  mset-clss:: 'clss  $\Rightarrow$  'v clauses and
  union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and
  insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  trail :: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and
  raw-clauses :: 'st  $\Rightarrow$  'clss and
  prepend-trail :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and
  tl-trail :: 'st  $\Rightarrow$  'st and
  add-clNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  remove-clNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  inv :: 'st  $\Rightarrow$  bool and
  backjump-conds :: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool and
  propagate-conds :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  bool and
  learn-restrictions forget-restrictions :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  bool
+
fixes f :: nat  $\Rightarrow$  nat
assumes
  unbounded: unbounded f and f-ge-1:  $\bigwedge n. n \geq 1 \Rightarrow f\ n \geq 1$  and
  inv-restart:  $\bigwedge S\ T. inv\ S \Rightarrow T \sim reduce\_trail\_to_{NOT} ([::'a\ list)\ S \Rightarrow inv\ T$ 
begin

lemma bound-inv-inv:
  assumes
    inv S and
    n-d: no-dup (trail S) and
    atms-clss-S-A: atms-of-mm (clausesNOT S)  $\subseteq$  atms-of-ms A and
    atms-trail-S-A: atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-ms A and
    finite A and
    cdclNOT: cdclNOT S T
  shows
    atms-of-mm (clausesNOT T)  $\subseteq$  atms-of-ms A and
    atm-of ' lits-of-l (trail T)  $\subseteq$  atms-of-ms A and
    finite A
proof -
  have cdclNOT S T
  using <inv S> cdclNOT by linarith
  then have atms-of-mm (clausesNOT T)  $\subseteq$  atms-of-mm (clausesNOT S)  $\cup$  atm-of ' lits-of-l (trail S)
  using <inv S>
  by (meson conflict-driven-clause-learning-ops.cdclNOT-atms-of-ms-clauses-decreasing
      conflict-driven-clause-learning-ops-axioms n-d)
  then show atms-of-mm (clausesNOT T)  $\subseteq$  atms-of-ms A
  using atms-clss-S-A atms-trail-S-A by blast
next
  show atm-of ' lits-of-l (trail T)  $\subseteq$  atms-of-ms A
  by (meson <inv S> atms-clss-S-A atms-trail-S-A cdclNOT cdclNOT-atms-in-trail-in-set n-d)
next

```



**show** *finite A*  
**using**  $\langle \text{finite } A \rangle$  **by** *simp*  
**qed**

**sublocale** *cdcl<sub>NOT</sub>-increasing-restarts-ops*  $\lambda S T. T \sim \text{reduce-trail-to}_{NOT} ([::'a \text{ list}) S \text{ cdcl}_{NOT} f$   
 $\lambda A S. \text{atms-of-mm} (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms } A \wedge \text{atm-of } ' \text{ lits-of-l } (\text{trail } S) \subseteq \text{atms-of-ms } A \wedge$   
*finite A*  
 $\mu_{CDCL}' \lambda S. \text{inv } S \wedge \text{no-dup } (\text{trail } S)$   
 $\mu_{CDCL}'\text{-bound}$   
**apply** *unfold-locales*  
**apply** (*simp add: unbounded*)  
**using** *f-ge-1* **apply** *force*  
**using** *bound-inv-inv* **apply** *meson*  
**apply** (*rule cdcl<sub>NOT</sub>-decreasing-measure'; simp*)  
**apply** (*rule rtrancpl-cdcl<sub>NOT</sub>- $\mu_{CDCL}'$ -bound; simp*)  
**apply** (*rule rtrancpl- $\mu_{CDCL}'$ -bound-decreasing; simp*)  
**apply** *auto*[]  
**apply** *auto*[]  
**using** *cdcl<sub>NOT</sub>-inv cdcl<sub>NOT</sub>-no-dup* **apply** *blast*  
**using** *inv-restart* **apply** *auto*[]  
**done**

**lemma** *cdcl<sub>NOT</sub>-with-restart- $\mu_{CDCL}'$ -le- $\mu_{CDCL}'$ -bound:*

**assumes**

*cdcl<sub>NOT</sub>: cdcl<sub>NOT</sub>-restart (T, a) (V, b) and*

*cdcl<sub>NOT</sub>-inv:*

*inv T*

*no-dup (trail T) and*

*bound-inv:*

*atms-of-mm (clauses<sub>NOT</sub> T)  $\subseteq$  atms-of-ms A*

*atm-of ' lits-of-l (trail T)  $\subseteq$  atms-of-ms A*

*finite A*

**shows**  $\mu_{CDCL}' A V \leq \mu_{CDCL}'\text{-bound } A T$

**using** *cdcl<sub>NOT</sub>-inv bound-inv*

**proof** (*induction rule: cdcl<sub>NOT</sub>-with-restart-induct[OF cdcl<sub>NOT</sub>]*)

**case** (*1 m S T n U*) **note** *U = this(3)*

**show** *?case*

**apply** (*rule rtrancpl-cdcl<sub>NOT</sub>- $\mu_{CDCL}'$ -bound-reduce-trail-to<sub>NOT</sub>[of S T]*)

**using**  $\langle (\text{cdcl}_{NOT} \rightsquigarrow m) S T \rangle$  **apply** (*fastforce dest!: relpowp-imp-rtrancpl*)

**using** *1* **by** *auto*

**next**

**case** (*2 S T n*) **note** *full = this(2)*

**show** *?case*

**apply** (*rule rtrancpl-cdcl<sub>NOT</sub>- $\mu_{CDCL}'$ -bound*)

**using** *full 2 unfolding full1-def* **by** *force+*

**qed**

**lemma** *cdcl<sub>NOT</sub>-with-restart- $\mu_{CDCL}'$ -bound-le- $\mu_{CDCL}'$ -bound:*

**assumes**

*cdcl<sub>NOT</sub>: cdcl<sub>NOT</sub>-restart (T, a) (V, b) and*

*cdcl<sub>NOT</sub>-inv:*

*inv T*

*no-dup (trail T) and*

*bound-inv:*

*atms-of-mm (clauses<sub>NOT</sub> T)  $\subseteq$  atms-of-ms A*

```

    atm-of ' lits-of-l (trail T)  $\subseteq$  atms-of-ms A
    finite A
  shows  $\mu_{CDCL}'$ -bound A V  $\leq$   $\mu_{CDCL}'$ -bound A T
  using cdclNOT-inv bound-inv
proof (induction rule: cdclNOT-with-restart-induct[OF cdclNOT])
  case (1 m S T n U) note U = this(3)
  have  $\mu_{CDCL}'$ -bound A T  $\leq$   $\mu_{CDCL}'$ -bound A S
  apply (rule rtrancp- $\mu_{CDCL}'$ -bound-decreasing)
  using  $\langle (cdcl_{NOT} \rightsquigarrow m) S T \rangle$  apply (fastforce dest: relpowp-imp-rtrancp)
  using 1 by auto
  then show ?case using U unfolding  $\mu_{CDCL}'$ -bound-def by auto
next
  case (2 S T n) note full = this(2)
  show ?case
  apply (rule rtrancp- $\mu_{CDCL}'$ -bound-decreasing)
  using full 2 unfolding full1-def by force+
qed

sublocale cdclNOT-increasing-restarts - - - - -
  f
   $\lambda S T. T \sim \text{reduce-trail-to}_{NOT} ([::'a \text{ list}] S$ 
 $\lambda A S. \text{atms-of-mm} (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms} A$ 
 $\wedge \text{atm-of ' lits-of-l} (\text{trail} S) \subseteq \text{atms-of-ms} A \wedge \text{finite} A$ 
 $\mu_{CDCL}' \text{ cdcl}_{NOT}$ 
 $\lambda S. \text{inv} S \wedge \text{no-dup} (\text{trail} S)$ 
 $\mu_{CDCL}'$ -bound
  apply unfold-locales
  using cdclNOT-with-restart- $\mu_{CDCL}'$ -le- $\mu_{CDCL}'$ -bound apply simp
  using cdclNOT-with-restart- $\mu_{CDCL}'$ -bound-le- $\mu_{CDCL}'$ -bound apply simp
  done

lemma cdclNOT-restart-all-decomposition-implies:
  assumes cdclNOT-restart S T and
    inv (fst S) and
    no-dup (trail (fst S))
  all-decomposition-implies-m (clausesNOT (fst S)) (get-all-marked-decomposition (trail (fst S)))
  shows
    all-decomposition-implies-m (clausesNOT (fst T)) (get-all-marked-decomposition (trail (fst T)))
  using assms apply (induction)
  using rtrancp-cdclNOT-all-decomposition-implies by (auto dest!: trancp-into-rtrancp
    simp: full1-def)

lemma rtrancp-cdclNOT-restart-all-decomposition-implies:
  assumes cdclNOT-restart** S T and
    inv: inv (fst S) and
    n-d: no-dup (trail (fst S)) and
    decomp:
      all-decomposition-implies-m (clausesNOT (fst S)) (get-all-marked-decomposition (trail (fst S)))
  shows
    all-decomposition-implies-m (clausesNOT (fst T)) (get-all-marked-decomposition (trail (fst T)))
  using assms(1)
proof (induction rule: rtrancp-induct)
  case base
  then show ?case using decomp by simp
next

```

**case** (*step*  $T\ u$ ) **note**  $st = \text{this}(1)$  **and**  $r = \text{this}(2)$  **and**  $IH = \text{this}(3)$   
**have**  $inv\ (fst\ T)$   
    **using**  $rtrancplp\text{-}cdcl_{NOT}\text{-with-restart-cdcl}_{NOT}\text{-inv}[OF\ st]\ inv\ n\text{-}d$  **by** *blast*  
**moreover** **have**  $no\text{-}dup\ (trail\ (fst\ T))$   
    **using**  $rtrancplp\text{-}cdcl_{NOT}\text{-with-restart-cdcl}_{NOT}\text{-inv}[OF\ st]\ inv\ n\text{-}d$  **by** *blast*  
**ultimately** **show**  $?case$   
    **using**  $cdcl_{NOT}\text{-restart-all-decomposition-implies}\ r\ IH\ n\text{-}d$  **by** *fast*  
**qed**

**lemma**  $cdcl_{NOT}\text{-restart-sat-ext-iff}$ :

**assumes**  
     $st: cdcl_{NOT}\text{-restart}\ S\ T$  **and**  
     $n\text{-}d: no\text{-}dup\ (trail\ (fst\ S))$  **and**  
     $inv: inv\ (fst\ S)$   
**shows**  $I \models_{sextm\ clauses_{NOT}} (fst\ S) \longleftrightarrow I \models_{sextm\ clauses_{NOT}} (fst\ T)$   
**using** *assms*  
**proof** (*induction*)  
**case** (*restart-step*  $m\ S\ T\ n\ U$ )  
**then** **show**  $?case$   
    **using**  $rtrancplp\text{-}cdcl_{NOT}\text{-bj-sat-ext-iff}\ n\text{-}d$  **by** (*fastforce dest!: relpowp-imp-rtrancplp*)  
**next**  
**case** *restart-full*  
**then** **show**  $?case$  **using**  $rtrancplp\text{-}cdcl_{NOT}\text{-bj-sat-ext-iff}$  **unfolding** *full1-def*  
    **by** (*fastforce dest!: trancplp-into-rtrancplp*)  
**qed**

**lemma**  $rtrancplp\text{-}cdcl_{NOT}\text{-restart-sat-ext-iff}$ :

**assumes**  
     $st: cdcl_{NOT}\text{-restart}^{**}\ S\ T$  **and**  
     $n\text{-}d: no\text{-}dup\ (trail\ (fst\ S))$  **and**  
     $inv: inv\ (fst\ S)$   
**shows**  $I \models_{sextm\ clauses_{NOT}} (fst\ S) \longleftrightarrow I \models_{sextm\ clauses_{NOT}} (fst\ T)$   
**using**  $st$   
**proof** (*induction*)  
**case** *base*  
**then** **show**  $?case$  **by** *simp*  
**next**  
**case** (*step*  $T\ U$ ) **note**  $st = \text{this}(1)$  **and**  $r = \text{this}(2)$  **and**  $IH = \text{this}(3)$   
**have**  $inv\ (fst\ T)$   
    **using**  $rtrancplp\text{-}cdcl_{NOT}\text{-with-restart-cdcl}_{NOT}\text{-inv}[OF\ st]\ inv\ n\text{-}d$  **by** *blast+*  
**moreover** **have**  $no\text{-}dup\ (trail\ (fst\ T))$   
    **using**  $rtrancplp\text{-}cdcl_{NOT}\text{-with-restart-cdcl}_{NOT}\text{-inv}\ rtrancplp\text{-}cdcl_{NOT}\text{-no-dup}\ st\ inv\ n\text{-}d$  **by** *blast*  
**ultimately** **show**  $?case$   
    **using**  $cdcl_{NOT}\text{-restart-sat-ext-iff}[OF\ r]\ IH$  **by** *blast*  
**qed**

**theorem**  $full\text{-}cdcl_{NOT}\text{-restart-backjump-final-state}$ :

**fixes**  $A :: 'v\ literal\ multiset\ set$  **and**  $S\ T :: 'st$   
**assumes**  
     $full: full\ cdcl_{NOT}\text{-restart}\ (S,\ n)\ (T,\ m)$  **and**  
     $atms\text{-}S: atms\text{-of}\text{-}mm\ (clauses_{NOT}\ S) \subseteq atms\text{-of}\text{-}ms\ A$  **and**  
     $atms\text{-}trail: atm\text{-of}\ 'lits\text{-of}\text{-}l\ (trail\ S) \subseteq atms\text{-of}\text{-}ms\ A$  **and**  
     $n\text{-}d: no\text{-}dup\ (trail\ S)$  **and**  
     $fin\text{-}A[simp]: finite\ A$  **and**  
     $inv: inv\ S$  **and**

*decomp*: *all-decomposition-implies-m* (*clauses*<sub>NOT</sub> *S*) (*get-all-marked-decomposition* (*trail* *S*))  
**shows** *unsatisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *S*))  
 $\vee$  (*lits-of-l* (*trail* *T*)  $\models$  *sextm* *clauses*<sub>NOT</sub> *S*  $\wedge$  *satisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *S*)))  
**proof** –  
**have** *st*: *cdcl*<sub>NOT</sub>-*restart*\*\* (*S*, *n*) (*T*, *m*) **and**  
*n-s*: *no-step cdcl*<sub>NOT</sub>-*restart* (*T*, *m*)  
**using** *full unfolding full-def* **by** *fast*+  
**have** *binv-T*: *atms-of-mm* (*clauses*<sub>NOT</sub> *T*)  $\subseteq$  *atms-of-ms* *A*  
*atm-of* ‘*lits-of-l* (*trail* *T*)  $\subseteq$  *atms-of-ms* *A*  
**using** *rtrancp-cdcl*<sub>NOT</sub>-*with-restart-bound-inv*[*OF st*, *of A*] *inv n-d atms-S atms-trail*  
**by** *auto*  
**moreover** **have** *inv-T*: *no-dup* (*trail* *T*) *inv T*  
**using** *rtrancp-cdcl*<sub>NOT</sub>-*with-restart-cdcl*<sub>NOT</sub>-*inv*[*OF st*] *inv n-d* **by** *auto*  
**moreover** **have** *all-decomposition-implies-m* (*clauses*<sub>NOT</sub> *T*) (*get-all-marked-decomposition* (*trail* *T*))  
**using** *rtrancp-cdcl*<sub>NOT</sub>-*restart-all-decomposition-implies*[*OF st*] *inv n-d*  
*decomp* **by** *auto*  
**ultimately** **have** *T*: *unsatisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *T*))  
 $\vee$  (*trail* *T*  $\models$  *asm* *clauses*<sub>NOT</sub> *T*  $\wedge$  *satisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *T*)))  
**using** *no-step-cdcl*<sub>NOT</sub>-*restart-no-step-cdcl*<sub>NOT</sub>[*of* (*T*, *m*) *A*] *n-s*  
*cdcl*<sub>NOT</sub>-*final-state*[*of T A*] **unfolding** *cdcl*<sub>NOT</sub>-*NOT-all-inv-def* **by** *auto*  
**have** *eq-sat-S-T*:  $\bigwedge I. I \models$  *sextm* *clauses*<sub>NOT</sub> *S*  $\longleftrightarrow$   $I \models$  *sextm* *clauses*<sub>NOT</sub> *T*  
**using** *rtrancp-cdcl*<sub>NOT</sub>-*restart-sat-ext-iff*[*OF st*] *inv n-d atms-S*  
*atms-trail* **by** *auto*  
**have** *cons-T*: *consistent-interp* (*lits-of-l* (*trail* *T*))  
**using** *inv-T*(1) *distinct-consistent-interp* **by** *blast*  
**consider**  
(*unsat*) *unsatisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *T*))  
| (*sat*) *trail* *T*  $\models$  *asm* *clauses*<sub>NOT</sub> *T* **and** *satisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *T*))  
**using** *T* **by** *blast*  
**then show** *?thesis*  
**proof** *cases*  
**case** *unsat*  
**then have** *unsatisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *S*))  
**using** *eq-sat-S-T* *consistent-true-clss-ext-satisfiable* *true-clss-imp-true-clss-ext*  
**unfolding** *satisfiable-def* **by** *blast*  
**then show** *?thesis* **by** *fast*  
**next**  
**case** *sat*  
**then have** *lits-of-l* (*trail* *T*)  $\models$  *sextm* *clauses*<sub>NOT</sub> *S*  
**using** *rtrancp-cdcl*<sub>NOT</sub>-*restart-sat-ext-iff*[*OF st*] *inv n-d atms-S*  
*atms-trail* **by** (*auto simp: true-clss-imp-true-clss-ext true-annots-true-clss*)  
**moreover then have** *satisfiable* (*set-mset* (*clauses*<sub>NOT</sub> *S*))  
**using** *cons-T* *consistent-true-clss-ext-satisfiable* **by** *blast*  
**ultimately show** *?thesis* **by** *blast*  
**qed**  
**qed**  
**end** — end of *cdcl*<sub>NOT</sub>-*with-backtrack-and-restarts* locale

The restart does only reset the trail, contrary to Weidenbach’s version. But there is a forget rule.

**locale** *cdcl*<sub>NOT</sub>-*merge-bj-learn-with-backtrack-restarts* =  
*cdcl*<sub>NOT</sub>-*merge-bj-learn* *mset-cls insert-cls remove-lit*  
*mset-clss union-clss in-clss insert-clss remove-from-clss*  
*trail raw-clauses prepend-trail tl-trail add-clss*<sub>NOT</sub> *remove-clss*<sub>NOT</sub>  
 $\lambda C\ C'\ L'\ S\ T. \text{distinct-mset}(C' + \{\#L'\#\}) \wedge \text{backjump-l-cond}\ C\ C'\ L'\ S\ T$

```

  propagate-conds forget-conds inv
for
  mset-cls:: 'cls  $\Rightarrow$  'v clause and
  insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  mset-clss:: 'clss  $\Rightarrow$  'v clauses and
  union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and
  insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  trail :: 'st  $\Rightarrow$  ('v, unit, unit) marked-lits and
  raw-clauses :: 'st  $\Rightarrow$  'clss and
  prepend-trail :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and
  tl-trail :: 'st  $\Rightarrow$  'st and
  add-clsNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  remove-clsNOT :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  propagate-conds :: ('v, unit, unit) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  bool and
  inv :: 'st  $\Rightarrow$  bool and
  forget-conds :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  bool and
  backjump-l-cond :: 'v clause  $\Rightarrow$  'v clause  $\Rightarrow$  'v literal  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  bool
+
fixes f :: nat  $\Rightarrow$  nat
assumes
  unbounded: unbounded f and f-ge-1:  $\bigwedge n. n \geq 1 \Rightarrow f\ n \geq 1$  and
  inv-restart:  $\bigwedge S\ T. inv\ S \Rightarrow T \sim \text{reduce-trail-to}_{NOT} \ \Box\ S \Rightarrow inv\ T$ 
begin

definition not-simplified-cls  $A = \{\#C \in \# A. \text{tautology } C \vee \neg \text{distinct-mset } C\# \}$ 

lemma simple-clss-or-not-simplified-cls:
  assumes atms-of-mm (clausesNOT S)  $\subseteq$  atms-of-ms A and
     $x \in \# \text{clauses}_{NOT} S$  and finite A
  shows  $x \in \text{simple-clss} (\text{atms-of-ms } A) \vee x \in \# \text{not-simplified-cls} (\text{clauses}_{NOT} S)$ 
proof –
  consider
    (simpl)  $\neg \text{tautology } x$  and distinct-mset x
  | (n-simp)  $\text{tautology } x \vee \neg \text{distinct-mset } x$ 
  by auto
  then show ?thesis
  proof cases
  case simpl
  then have  $x \in \text{simple-clss} (\text{atms-of-ms } A)$ 
    by (meson assms atms-of-atms-of-ms-mono atms-of-ms-finite simple-clss-mono
      distinct-mset-not-tautology-implies-in-simple-clss finite-subset
      subsetCE)
  then show ?thesis by blast
  next
  case n-simp
  then have  $x \in \# \text{not-simplified-cls} (\text{clauses}_{NOT} S)$ 
    using  $\langle x \in \# \text{clauses}_{NOT} S \rangle$  unfolding not-simplified-cls-def by auto
  then show ?thesis by blast
qed
qed

```

**lemma** cdcl<sub>NOT</sub>-merged-bj-learn-clauses-bound:

**assumes**  
*cdcl<sub>NOT</sub>-merged-bj-learn S T* **and**  
*inv: inv S* **and**  
*atms-clss: atms-of-mm (clauses<sub>NOT</sub> S) ⊆ atms-of-ms A* **and**  
*atms-trail: atm-of (lits-of-l (trail S)) ⊆ atms-of-ms A* **and**  
*n-d: no-dup (trail S)* **and**  
*fin-A[simp]: finite A*  
**shows** *set-mset (clauses<sub>NOT</sub> T) ⊆ set-mset (not-simplified-cls (clauses<sub>NOT</sub> S))*  
*∪ simple-clss (atms-of-ms A)*  
**using** *assms*  
**proof** (*induction rule: cdcl<sub>NOT</sub>-merged-bj-learn.induct*)  
**case** *cdcl<sub>NOT</sub>-merged-bj-learn-decide<sub>NOT</sub>*  
**then show** ?*case using dpll-bj-clauses by (force dest!: simple-clss-or-not-simplified-cls)*  
**next**  
**case** *cdcl<sub>NOT</sub>-merged-bj-learn-propagate<sub>NOT</sub>*  
**then show** ?*case using dpll-bj-clauses by (force dest!: simple-clss-or-not-simplified-cls)*  
**next**  
**case** *cdcl<sub>NOT</sub>-merged-bj-learn-forget<sub>NOT</sub>*  
**then show** ?*case using clauses-remove-cl<sub>NOT</sub> unfolding state-eq<sub>NOT</sub>-def*  
*by (force elim!: forget<sub>NOT</sub>E dest: simple-clss-or-not-simplified-cls)*  
**next**  
**case** (*cdcl<sub>NOT</sub>-merged-bj-learn-backjump-l T*) **note** *bj = this(1)* **and** *inv = this(2)* **and**  
*atms-clss = this(3)* **and** *atms-trail = this(4)* **and** *n-d = this(5)*  
  
**have** *cdcl<sub>NOT</sub>\*\* S T*  
**apply** (*rule rtrancpl-cdcl<sub>NOT</sub>-merged-bj-learn-is-rtrancpl-cdcl<sub>NOT</sub>*)  
**using** *⟨backjump-l S T⟩ inv cdcl<sub>NOT</sub>-merged-bj-learn.simps n-d* **by** *blast+*  
**have** *atm-of (lits-of-l (trail T)) ⊆ atms-of-ms A*  
**using** *rtrancpl-cdcl<sub>NOT</sub>-trail-clauses-bound[OF ⟨cdcl<sub>NOT</sub>\*\* S T⟩ inv atms-trail atms-clss*  
*n-d* **by** *auto*  
**have** *atms-of-mm (clauses<sub>NOT</sub> T) ⊆ atms-of-ms A*  
**using** *rtrancpl-cdcl<sub>NOT</sub>-trail-clauses-bound[OF ⟨cdcl<sub>NOT</sub>\*\* S T⟩ inv n-d atms-clss atms-trail]*  
**by** *fast*  
**moreover have** *no-dup (trail T)*  
**using** *rtrancpl-cdcl<sub>NOT</sub>-no-dup[OF ⟨cdcl<sub>NOT</sub>\*\* S T⟩ inv n-d]* **by** *fast*  
  
**obtain** *F' K F L l C' C D* **where**  
*tr-S: trail S = F' @ Marked K () # F* **and**  
*T: T ~ prepend-trail (Propagated L l) (reduce-trail-to<sub>NOT</sub> F (add-cl<sub>NOT</sub> D S))* **and**  
*C ∈# clauses<sub>NOT</sub> S* **and**  
*trail S ⊨<sub>as</sub> CNot C* **and**  
*undef: undefined-lit F L* **and**  
*clauses<sub>NOT</sub> S ⊨<sub>pm</sub> C' + {#L#}* **and**  
*F ⊨<sub>as</sub> CNot C'* **and**  
*D: mset-cl<sub>s</sub> D = C' + {#L#}* **and**  
*dist: distinct-mset (C' + {#L#})* **and**  
*tauto: ⊢ tautology (C' + {#L#})* **and**  
*backjump-l-cond C C' L S T*  
**using** *⟨backjump-l S T⟩ apply (elim backjump-lE)* **by** *auto*  
  
**have** *atms-of C' ⊆ atm-of (lits-of-l F)*  
**using** *⟨F ⊨<sub>as</sub> CNot C'⟩ by (simp add: atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set*  
*atms-of-def image-subset-iff in-CNot-implies-uminus(2))*  
**then have** *atms-of (C' + {#L#}) ⊆ atms-of-ms A*  
**using** *T ⟨atm-of (lits-of-l (trail T)) ⊆ atms-of-ms A⟩ tr-S undef n-d* **by** *auto*

**then have**  $\text{simple-clss} (\text{atms-of} (C' + \{\#L\# \})) \subseteq \text{simple-clss} (\text{atms-of-ms } A)$   
**apply** – **by** (*rule simple-clss-mono*) (*simp-all*)  
**then have**  $C' + \{\#L\# \} \in \text{simple-clss} (\text{atms-of-ms } A)$   
**using** *distinct-mset-not-tautology-implies-in-simple-clss*[*OF dist tauto*]  
**by** *auto*  
**then show** ?*case*  
**using** *T inv atms-clss undef tr-S n-d D* **by** (*force dest!*: *simple-clss-or-not-simplified-cls*)  
**qed**

**lemma** *cdcl<sub>NOT</sub>-merged-bj-learn-not-simplified-decreasing*:  
**assumes** *cdcl<sub>NOT</sub>-merged-bj-learn S T*  
**shows**  $(\text{not-simplified-cls} (\text{clauses}_{\text{NOT}} T)) \subseteq \# (\text{not-simplified-cls} (\text{clauses}_{\text{NOT}} S))$   
**using** *assms* **apply** *induction*  
**prefer** 4  
**unfolding** *not-simplified-cls-def* **apply** (*auto elim!*: *backjump-lE forget<sub>NOT</sub>E*)[3]  
**by** (*elim backjump-lE*) *auto*

**lemma** *rtranclp-cdcl<sub>NOT</sub>-merged-bj-learn-not-simplified-decreasing*:  
**assumes** *cdcl<sub>NOT</sub>-merged-bj-learn\*\* S T*  
**shows**  $(\text{not-simplified-cls} (\text{clauses}_{\text{NOT}} T)) \subseteq \# (\text{not-simplified-cls} (\text{clauses}_{\text{NOT}} S))$   
**using** *assms* **apply** *induction*  
**apply** *simp*  
**by** (*drule cdcl<sub>NOT</sub>-merged-bj-learn-not-simplified-decreasing*) *auto*

**lemma** *rtranclp-cdcl<sub>NOT</sub>-merged-bj-learn-clauses-bound*:  
**assumes**  
*cdcl<sub>NOT</sub>-merged-bj-learn\*\* S T and*  
*inv S and*  
*atms-of-mm (clauses<sub>NOT</sub> S)  $\subseteq$  atms-of-ms A and*  
*atm-of ' (lits-of-l (trail S))  $\subseteq$  atms-of-ms A and*  
*n-d: no-dup (trail S) and*  
*finite[simp]: finite A*  
**shows**  $\text{set-mset} (\text{clauses}_{\text{NOT}} T) \subseteq \text{set-mset} (\text{not-simplified-cls} (\text{clauses}_{\text{NOT}} S))$   
 $\cup \text{simple-clss} (\text{atms-of-ms } A)$   
**using** *assms*(1–5)

**proof** *induction*

**case** *base*

**then show** ?*case* **by** (*auto dest!*: *simple-clss-or-not-simplified-cls*)

**next**

**case** (*step T U*) **note** *st = this(1)* **and** *cdcl<sub>NOT</sub> = this(2)* **and** *IH = this(3)[OF this(4–7)]* **and**  
*inv = this(4)* **and** *atms-clss-S = this(5)* **and** *atms-trail-S = this(6)* **and** *finite-cls-S = this(7)*

**have** *st'*: *cdcl<sub>NOT</sub>\*\* S T*

**using** *inv rtranclp-cdcl<sub>NOT</sub>-merged-bj-learn-is-rtranclp-cdcl<sub>NOT</sub>-and-inv st n-d* **by** *blast*

**have** *inv T*

**using** *inv rtranclp-cdcl<sub>NOT</sub>-merged-bj-learn-inv st n-d* **by** *blast*

**moreover**

**have** *atms-of-mm (clauses<sub>NOT</sub> T)  $\subseteq$  atms-of-ms A and*

*atm-of ' lits-of-l (trail T)  $\subseteq$  atms-of-ms A*

**using** *rtranclp-cdcl<sub>NOT</sub>-trail-clauses-bound*[*OF st'*] *inv atms-clss-S atms-trail-S n-d*

**by** *blast+*

**moreover moreover have** *no-dup (trail T)*

**using** *rtranclp-cdcl<sub>NOT</sub>-no-dup*[*OF 'cdcl<sub>NOT</sub>\*\* S T' inv n-d*] **by** *fast*

**ultimately have** *set-mset (clauses<sub>NOT</sub> U)*

$\subseteq \text{set-mset} (\text{not-simplified-cls} (\text{clauses}_{\text{NOT}} T)) \cup \text{simple-clss} (\text{atms-of-ms } A)$

**using** *cdcl<sub>NOT</sub> finite cdcl<sub>NOT</sub>-merged-bj-learn-clauses-bound*

by (auto intro!: cdcl<sub>NOT</sub>-merged-bj-learn-clauses-bound)  
**moreover have** set-mset (not-simplified-cls (clauses<sub>NOT</sub> T))  
 ⊆ set-mset (not-simplified-cls (clauses<sub>NOT</sub> S))  
 using rtrancp-cdcl<sub>NOT</sub>-merged-bj-learn-not-simplified-decreasing[OF st] by auto  
**ultimately show** ?case using IH inv atms-clss-S  
 by (auto dest!: simple-clss-or-not-simplified-cls)  
**qed**

**abbreviation**  $\mu_{CDCL}'$ -bound **where**  
 $\mu_{CDCL}'$ -bound A T  $\equiv ((2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))) * 2$   
 + card (set-mset (not-simplified-cls (clauses<sub>NOT</sub> T)))  
 + 3  $\wedge$  card (atms-of-ms A)

**lemma** rtrancp-cdcl<sub>NOT</sub>-merged-bj-learn-clauses-bound-card:

**assumes**  
 cdcl<sub>NOT</sub>-merged-bj-learn\*\* S T **and**  
 inv S **and**  
 atms-of-mm (clauses<sub>NOT</sub> S) ⊆ atms-of-ms A **and**  
 atm-of ' (lits-of-l (trail S)) ⊆ atms-of-ms A **and**  
 n-d: no-dup (trail S) **and**  
 finite: finite A  
**shows**  $\mu_{CDCL}'$ -merged A T ≤  $\mu_{CDCL}'$ -bound A S  
**proof** –  
**have** set-mset (clauses<sub>NOT</sub> T) ⊆ set-mset (not-simplified-cls (clauses<sub>NOT</sub> S))  
 ∪ simple-clss (atms-of-ms A)  
 using rtrancp-cdcl<sub>NOT</sub>-merged-bj-learn-clauses-bound[OF assms] .  
**moreover have** card (set-mset (not-simplified-cls (clauses<sub>NOT</sub> S)))  
 ∪ simple-clss (atms-of-ms A))  
 ≤ card (set-mset (not-simplified-cls (clauses<sub>NOT</sub> S))) + 3  $\wedge$  card (atms-of-ms A)  
**by** (meson Nat.le-trans atms-of-ms-finite simple-clss-card card-Un-le finite  
 nat-add-left-cancel-le)  
**ultimately have** card (set-mset (clauses<sub>NOT</sub> T))  
 ≤ card (set-mset (not-simplified-cls (clauses<sub>NOT</sub> S))) + 3  $\wedge$  card (atms-of-ms A)  
**by** (meson Nat.le-trans atms-of-ms-finite simple-clss-finite card-mono  
 finite-UnI finite-set-mset local.finite)  
**moreover have** ((2 + card (atms-of-ms A))  $\wedge$  (1 + card (atms-of-ms A)) –  $\mu_C'$  A T) \* 2  
 ≤ (2 + card (atms-of-ms A))  $\wedge$  (1 + card (atms-of-ms A)) \* 2  
**by** auto  
**ultimately show** ?thesis **unfolding**  $\mu_{CDCL}'$ -merged-def **by** auto  
**qed**

**sublocale** cdcl<sub>NOT</sub>-increasing-restarts-ops  $\lambda S T. T \sim \text{reduce-trail-to}_{NOT} ([::'a \text{ list}]) S$   
 cdcl<sub>NOT</sub>-merged-bj-learn f  
 $\lambda A S. \text{atms-of-mm } (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms } A$   
 $\wedge \text{atm-of ' } (\text{lits-of-l } (\text{trail } S)) \subseteq \text{atms-of-ms } A \wedge \text{finite } A$   
 $\mu_{CDCL}'$ -merged  
 $\lambda S. \text{inv } S \wedge \text{no-dup } (\text{trail } S)$   
 $\mu_{CDCL}'$ -bound  
**apply** unfold-locales  
 using unbounded **apply** simp  
 using f-ge-1 **apply** force  
**apply** (blast dest!: cdcl<sub>NOT</sub>-merged-bj-learn-is-trancp-cdcl<sub>NOT</sub> trancp-into-rtrancp  
 rtrancp-cdcl<sub>NOT</sub>-trail-clauses-bound)  
**apply** (simp add: cdcl<sub>NOT</sub>-decreasing-measure)  
**using** rtrancp-cdcl<sub>NOT</sub>-merged-bj-learn-clauses-bound-card **apply** blast



```

    apply (drule rtrancpl-cdclNOT-merged-bj-learn-not-simplified-decreasing)
    apply (auto dest!: simp: card-mono set-mset-mono ) []
  apply simp
  apply auto []
  using cdclNOT-merged-bj-learn-no-dup-inv cdcl-merged-inv apply blast
  apply (auto simp: inv-restart) []
done

```

**lemma**  $cdcl_{NOT}\text{-restart-}\mu_{CDCL}'\text{-merged-le-}\mu_{CDCL}'\text{-bound}$ :

```

assumes
  cdclNOT-restart  $T\ V$ 
  inv (fst  $T$ ) and
  no-dup (trail (fst  $T$ )) and
  atms-of-mm (clausesNOT (fst  $T$ ))  $\subseteq$  atms-of-ms  $A$  and
  atm-of ' lits-of-l (trail (fst  $T$ ))  $\subseteq$  atms-of-ms  $A$  and
  finite  $A$ 
shows  $\mu_{CDCL}'\text{-merged}\ A\ (fst\ V) \leq \mu_{CDCL}'\text{-bound}\ A\ (fst\ T)$ 
using assms
proof induction
  case (restart-full  $S\ T\ n$ )
  show ?case
    unfolding fst-conv
    apply (rule rtrancpl-cdclNOT-merged-bj-learn-clauses-bound-card)
    using restart-full unfolding full1-def by (force dest!: trancpl-into-rtrancpl)+
next
  case (restart-step  $m\ S\ T\ n\ U$ ) note st = this(1) and  $U = \text{this}(3)$  and inv = this(4) and
    n-d = this(5) and atms-clss = this(6) and atms-trail = this(7) and finite = this(8)
  then have st':  $cdcl_{NOT}\text{-merged-bj-learn}^{**}\ S\ T$ 
    by (blast dest: relpowp-imp-rtrancpl)
  then have st'':  $cdcl_{NOT}^{**}\ S\ T$ 
    using inv n-d apply - by (rule rtrancpl-cdclNOT-merged-bj-learn-is-rtrancpl-cdclNOT) auto
  have inv  $T$ 
    apply (rule rtrancpl-cdclNOT-merged-bj-learn-inv)
    using inv st' n-d by auto
  then have inv  $U$ 
    using  $U$  by (auto simp: inv-restart)
  have atms-of-mm (clausesNOT  $T$ )  $\subseteq$  atms-of-ms  $A$ 
    using rtrancpl-cdclNOT-trail-clauses-bound[OF st''] inv atms-clss atms-trail n-d
    by simp
  then have atms-of-mm (clausesNOT  $U$ )  $\subseteq$  atms-of-ms  $A$ 
    using  $U$  by simp
  have not-simplified-cls (clausesNOT  $U$ )  $\subseteq\#$  not-simplified-cls (clausesNOT  $T$ )
    using  $\langle U \sim \text{reduce-trail-to}_{NOT} []\ T \rangle$  by auto
  moreover have not-simplified-cls (clausesNOT  $T$ )  $\subseteq\#$  not-simplified-cls (clausesNOT  $S$ )
    apply (rule rtrancpl-cdclNOT-merged-bj-learn-not-simplified-decreasing)
    using  $\langle (cdcl_{NOT}\text{-merged-bj-learn} \sim m)\ S\ T \rangle$  by (auto dest!: relpowp-imp-rtrancpl)
  ultimately have  $U\text{-S: not-simplified-cls (clauses}_{NOT}\ U) \subseteq\# \text{not-simplified-cls (clauses}_{NOT}\ S)$ 
    by auto

  have (set-mset (clausesNOT  $U$ ))
     $\subseteq$  set-mset (not-simplified-cls (clausesNOT  $U$ ))  $\cup$  simple-clss (atms-of-ms  $A$ )
  apply (rule rtrancpl-cdclNOT-merged-bj-learn-clauses-bound)
  apply simp
  using  $\langle inv\ U \rangle$  apply simp
  using  $\langle \text{atms-of-mm (clauses}_{NOT}\ U) \subseteq \text{atms-of-ms}\ A \rangle$  apply simp

```

```

    using U apply simp
    using U apply simp
    using finite apply simp
    done
  then have f1: card (set-mset (clausesNOT U)) ≤ card (set-mset (not-simplified-cls (clausesNOT U))
    ∪ simple-clss (atms-of-ms A))
    by (simp add: simple-clss-finite card-mono local.finite)

  moreover have set-mset (not-simplified-cls (clausesNOT U)) ∪ simple-clss (atms-of-ms A)
    ⊆ set-mset (not-simplified-cls (clausesNOT S)) ∪ simple-clss (atms-of-ms A)
    using U-S by auto
  then have f2:
    card (set-mset (not-simplified-cls (clausesNOT U)) ∪ simple-clss (atms-of-ms A))
      ≤ card (set-mset (not-simplified-cls (clausesNOT S)) ∪ simple-clss (atms-of-ms A))
    by (simp add: simple-clss-finite card-mono local.finite)

  moreover have card (set-mset (not-simplified-cls (clausesNOT S))
    ∪ simple-clss (atms-of-ms A))
    ≤ card (set-mset (not-simplified-cls (clausesNOT S))) + card (simple-clss (atms-of-ms A))
    using card-Un-le by blast
  moreover have card (simple-clss (atms-of-ms A)) ≤ 3 ^ card (atms-of-ms A)
    using atms-of-ms-finite simple-clss-card local.finite by blast
  ultimately have card (set-mset (clausesNOT U))
    ≤ card (set-mset (not-simplified-cls (clausesNOT S))) + 3 ^ card (atms-of-ms A)
    by linarith
  then show ?case unfolding  $\mu_{CDCL}'$ -merged-def by auto
qed

```

**lemma**  $cdcl_{NOT}$ -restart- $\mu_{CDCL}'$ -bound-le- $\mu_{CDCL}'$ -bound:

```

  assumes
    cdclNOT-restart T V and
    no-dup (trail (fst T)) and
    inv (fst T) and
    fin: finite A
  shows  $\mu_{CDCL}'$ -bound A (fst V) ≤  $\mu_{CDCL}'$ -bound A (fst T)
  using assms(1-3)
proof induction
  case (restart-full S T n)
  have not-simplified-cls (clausesNOT T) ⊆# not-simplified-cls (clausesNOT S)
    apply (rule rtrancp-cdclNOT-merged-bj-learn-not-simplified-decreasing)
    using ⟨full1 cdclNOT-merged-bj-learn S T⟩ unfolding full1-def
    by (auto dest: trancp-into-rtrancp)
  then show ?case by (auto simp: card-mono set-mset-mono)
next
  case (restart-step m S T n U) note st = this(1) and U = this(3) and n-d = this(4) and
    inv = this(5)
  then have st': cdclNOT-merged-bj-learn** S T
    by (blast dest: relpowp-imp-rtrancp)
  then have st'': cdclNOT** S T
    using inv n-d apply - by (rule rtrancp-cdclNOT-merged-bj-learn-is-rtrancp-cdclNOT) auto
  have inv T
    apply (rule rtrancp-cdclNOT-merged-bj-learn-inv)
    using inv st' n-d by auto
  then have inv U
    using U by (auto simp: inv-restart)

```

**have** *not-simplified-cl*s (*clauses*<sub>NOT</sub> *U*)  $\subseteq\#$  *not-simplified-cl*s (*clauses*<sub>NOT</sub> *T*)  
**using**  $\langle U \sim \text{reduce-trail-to}_{NOT} [] T \rangle$  **by** *auto*  
**moreover have** *not-simplified-cl*s (*clauses*<sub>NOT</sub> *T*)  $\subseteq\#$  *not-simplified-cl*s (*clauses*<sub>NOT</sub> *S*)  
**apply** (*rule rtranclp-cdcl*<sub>NOT</sub>-merged-bj-learn-not-simplified-decreasing)  
**using**  $\langle (\text{cdcl}_{NOT}\text{-merged-bj-learn} \hat{\sim} m) S T \rangle$  **by** (*auto dest!*: *relpowp-imp-rtranclp*)  
**ultimately have** *U-S*: *not-simplified-cl*s (*clauses*<sub>NOT</sub> *U*)  $\subseteq\#$  *not-simplified-cl*s (*clauses*<sub>NOT</sub> *S*)  
**by** *auto*  
**then show** ?*case* **by** (*auto simp*: *card-mono set-mset-mono*)  
**qed**

**sublocale** *cdcl*<sub>NOT</sub>-increasing-restarts - - - - - *f*  
 $\lambda S T. T \sim \text{reduce-trail-to}_{NOT} ([]::'a \text{ list}) S$   
 $\lambda A S. \text{atms-of-mm} (\text{clauses}_{NOT} S) \subseteq \text{atms-of-ms } A$   
 $\wedge \text{atm-of ' lits-of-l } (\text{trail } S) \subseteq \text{atms-of-ms } A \wedge \text{finite } A$   
 $\mu_{CDCL}'\text{-merged } \text{cdcl}_{NOT}\text{-merged-bj-learn}$   
 $\lambda S. \text{inv } S \wedge \text{no-dup } (\text{trail } S)$   
 $\lambda A T. ((2 + \text{card } (\text{atms-of-ms } A)) \wedge (1 + \text{card } (\text{atms-of-ms } A))) * 2$   
 $+ \text{card } (\text{set-mset } (\text{not-simplified-cl}(\text{clauses}_{NOT} T)))$   
 $+ 3 \wedge \text{card } (\text{atms-of-ms } A)$   
**apply** *unfold-locales*  
**using** *cdcl*<sub>NOT</sub>-restart- $\mu_{CDCL}'$ -merged-le- $\mu_{CDCL}'$ -bound **apply** *force*  
**using** *cdcl*<sub>NOT</sub>-restart- $\mu_{CDCL}'$ -bound-le- $\mu_{CDCL}'$ -bound **by** *fastforce*

**lemma** *cdcl*<sub>NOT</sub>-restart-eq-sat-iff:  
**assumes**  
 $\text{cdcl}_{NOT}\text{-restart } S T$  **and**  
 $\text{no-dup } (\text{trail } (\text{fst } S))$   
 $\text{inv } (\text{fst } S)$   
**shows**  $I \models_{\text{sextm}} \text{clauses}_{NOT} (\text{fst } S) \longleftrightarrow I \models_{\text{sextm}} \text{clauses}_{NOT} (\text{fst } T)$   
**using** *assms*  
**proof** (*induction rule: cdcl*<sub>NOT</sub>-restart.induct)  
**case** (*restart-full* *S T n*)  
**then have** *cdcl*<sub>NOT</sub>-merged-bj-learn\*\* *S T*  
**by** (*simp add: tranclp-into-rtranclp full1-def*)  
**then show** ?*case*  
**using** *rtranclp-cdcl*<sub>NOT</sub>-bj-sat-ext-iff *restart-full.prem*s(1,2)  
*rtranclp-cdcl*<sub>NOT</sub>-merged-bj-learn-is-rtranclp-*cdcl*<sub>NOT</sub> **by** *auto*  
**next**  
**case** (*restart-step* *m S T n U*)  
**then have** *cdcl*<sub>NOT</sub>-merged-bj-learn\*\* *S T*  
**by** (*auto simp: tranclp-into-rtranclp full1-def dest!*: *relpowp-imp-rtranclp*)  
**then have**  $I \models_{\text{sextm}} \text{clauses}_{NOT} S \longleftrightarrow I \models_{\text{sextm}} \text{clauses}_{NOT} T$   
**using** *rtranclp-cdcl*<sub>NOT</sub>-bj-sat-ext-iff *restart-step.prem*s(1,2)  
*rtranclp-cdcl*<sub>NOT</sub>-merged-bj-learn-is-rtranclp-*cdcl*<sub>NOT</sub> **by** *auto*  
**moreover have**  $I \models_{\text{sextm}} \text{clauses}_{NOT} T \longleftrightarrow I \models_{\text{sextm}} \text{clauses}_{NOT} U$   
**using** *restart-step.hyps*(3) **by** *auto*  
**ultimately show** ?*case* **by** *auto*  
**qed**

**lemma** *rtranclp-cdcl*<sub>NOT</sub>-restart-eq-sat-iff:  
**assumes**  
 $\text{cdcl}_{NOT}\text{-restart}^{**} S T$  **and**  
 $\text{inv: inv } (\text{fst } S)$  **and** *n-d*:  $\text{no-dup}(\text{trail } (\text{fst } S))$   
**shows**  $I \models_{\text{sextm}} \text{clauses}_{NOT} (\text{fst } S) \longleftrightarrow I \models_{\text{sextm}} \text{clauses}_{NOT} (\text{fst } T)$

```

using assms(1)
proof (induction rule: rtrancpl-induct)
  case base
  then show ?case by simp
next
  case (step T U) note st = this(1) and cdcl = this(2) and IH = this(3)
  have inv (fst T) and no-dup (trail (fst T))
    using rtrancpl-cdclNOT-with-restart-cdclNOT-inv using st inv n-d by blast+
  then have  $I \models_{\text{sextm}} \text{clauses}_{\text{NOT}}(\text{fst } T) \longleftrightarrow I \models_{\text{sextm}} \text{clauses}_{\text{NOT}}(\text{fst } U)$ 
    using cdclNOT-restart-eq-sat-iff cdcl by blast
  then show ?case using IH by blast
qed

lemma cdclNOT-restart-all-decomposition-implies-m:
  assumes
    cdclNOT-restart S T and
    inv: inv (fst S) and n-d: no-dup(trail (fst S)) and
    all-decomposition-implies-m (clausesNOT (fst S))
    (get-all-marked-decomposition (trail (fst S)))
  shows all-decomposition-implies-m (clausesNOT (fst T))
    (get-all-marked-decomposition (trail (fst T)))
  using assms
proof (induction)
  case (restart-full S T n) note full = this(1) and inv = this(2) and n-d = this(3) and
    decomp = this(4)
  have st: cdclNOT-merged-bj-learn** S T and
    n-s: no-step cdclNOT-merged-bj-learn T
    using full unfolding full1-def by (fast dest: trancpl-into-rtrancpl)+
  have st': cdclNOT** S T
    using inv rtrancpl-cdclNOT-merged-bj-learn-is-rtrancpl-cdclNOT-and-inv st n-d by auto
  have inv T
    using rtrancpl-cdclNOT-cdclNOT-inv[OF st] inv n-d by auto
  then show ?case
    using rtrancpl-cdclNOT-all-decomposition-implies[OF - - n-d decomp] st' inv by auto
next
  case (restart-step m S T n U) note st = this(1) and U = this(3) and inv = this(4) and
    n-d = this(5) and decomp = this(6)
  show ?case using U by auto
qed

```

```

lemma rtrancpl-cdclNOT-restart-all-decomposition-implies-m:
  assumes
    cdclNOT-restart** S T and
    inv: inv (fst S) and n-d: no-dup(trail (fst S)) and
    decomp: all-decomposition-implies-m (clausesNOT (fst S))
    (get-all-marked-decomposition (trail (fst S)))
  shows all-decomposition-implies-m (clausesNOT (fst T))
    (get-all-marked-decomposition (trail (fst T)))
  using assms
proof (induction)
  case base
  then show ?case using decomp by simp
next
  case (step T U) note st = this(1) and cdcl = this(2) and IH = this(3)[OF this(4-)] and
    inv = this(4) and n-d = this(5) and decomp = this(6)

```

**have**  $inv$  ( $fst$   $T$ ) **and**  $no-dup$  ( $trail$  ( $fst$   $T$ ))  
**using**  $rtrancplp-cdcl_{NOT}$ -with-restart- $cdcl_{NOT}$ - $inv$  **using**  $st$   $inv$   $n-d$  **by**  $blast+$   
**then show**  $?case$   
**using**  $cdcl_{NOT}$ -restart-all-decomposition-implies- $m[OF\ cdcl]$   $IH$  **by**  $auto$   
**qed**

**lemma**  $full-cdcl_{NOT}$ -restart-normal-form:

**assumes**

$full$ :  $full\ cdcl_{NOT}$ -restart  $S$   $T$  **and**  
 $inv$ :  $inv$  ( $fst$   $S$ ) **and**  $n-d$ :  $no-dup(trail\ (fst\ S))$  **and**  
 $decomp$ :  $all-decomposition-implies-m\ (clauses_{NOT}\ (fst\ S))$   
 $(get-all-marked-decomposition\ (trail\ (fst\ S)))$  **and**  
 $atms-cls$ :  $atms-of-mm\ (clauses_{NOT}\ (fst\ S)) \subseteq atms-of-ms\ A$  **and**  
 $atms-trail$ :  $atm-of\ 'lits-of-l\ (trail\ (fst\ S)) \subseteq atms-of-ms\ A$  **and**  
 $fin$ :  $finite\ A$

**shows**  $unsatisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ S)))$

$\vee\ lits-of-l\ (trail\ (fst\ T)) \models_{sextm}\ clauses_{NOT}\ (fst\ S) \wedge\ satisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ S)))$

**proof** –

**have**  $inv-T$ :  $inv$  ( $fst\ T$ ) **and**  $n-d-T$ :  $no-dup\ (trail\ (fst\ T))$

**using**  $rtrancplp-cdcl_{NOT}$ -with-restart- $cdcl_{NOT}$ - $inv$  **using**  $full\ inv\ n-d$  **unfolding**  $full-def$  **by**  $blast+$

**moreover have**

$atms-cls-T$ :  $atms-of-mm\ (clauses_{NOT}\ (fst\ T)) \subseteq atms-of-ms\ A$  **and**

$atms-trail-T$ :  $atm-of\ 'lits-of-l\ (trail\ (fst\ T)) \subseteq atms-of-ms\ A$

**using**  $rtrancplp-cdcl_{NOT}$ -with-restart-bound- $inv[of\ S\ T\ A]$   $full\ atms-cls\ atms-trail\ fin\ inv\ n-d$

**unfolding**  $full-def$  **by**  $blast+$

**ultimately have**  $no-step\ cdcl_{NOT}$ -merged- $bj$ -learn ( $fst\ T$ )

**apply** –

**apply** ( $rule\ no-step-cdcl_{NOT}$ -restart- $no-step-cdcl_{NOT}[of\ -\ A]$ )

**using**  $full$  **unfolding**  $full-def$  **apply**  $simp$

**apply**  $simp$

**using**  $fin$  **apply**  $simp$

**done**

**moreover have**  $all-decomposition-implies-m\ (clauses_{NOT}\ (fst\ T))$

$(get-all-marked-decomposition\ (trail\ (fst\ T)))$

**using**  $rtrancplp-cdcl_{NOT}$ -restart-all-decomposition-implies- $m[of\ S\ T]$   $inv\ n-d\ decomp$

$full$  **unfolding**  $full-def$  **by**  $auto$

**ultimately have**  $unsatisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ T)))$

$\vee\ trail\ (fst\ T) \models_{asm}\ clauses_{NOT}\ (fst\ T) \wedge\ satisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ T)))$

**apply** –

**apply** ( $rule\ cdcl_{NOT}$ -merged- $bj$ -learn-final-state)

**using**  $atms-cls-T\ atms-trail-T\ fin\ n-d-T\ fin\ inv-T$  **by**  $blast+$

**then consider**

$(unsat)\ unsatisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ T)))$

$| (sat)\ trail\ (fst\ T) \models_{asm}\ clauses_{NOT}\ (fst\ T)$  **and**  $satisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ T)))$

**by**  $auto$

**then show**  $unsatisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ S)))$

$\vee\ lits-of-l\ (trail\ (fst\ T)) \models_{sextm}\ clauses_{NOT}\ (fst\ S) \wedge\ satisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ S)))$

**proof cases**

**case**  $unsat$

**then have**  $unsatisfiable\ (set-mset\ (clauses_{NOT}\ (fst\ S)))$

**unfolding**  $satisfiable-def$  **apply**  $auto$

**using**  $rtrancplp-cdcl_{NOT}$ -restart- $eq$ -sat- $iff[of\ S\ T]$   $full\ inv\ n-d$

$consistent-true-clss-ext-satisfiable\ true-clss-imp-true-clss-ext$

**unfolding**  $satisfiable-def\ full-def$  **by**  $blast$

**then show**  $?thesis$  **by**  $blast$

```

next
  case sat
  then have lits-of-l (trail (fst T))  $\models_{\text{sextm}}$  clausesNOT (fst T)
    using true-clss-imp-true-cls-ext by (auto simp: true-annots-true-cls)
  then have lits-of-l (trail (fst T))  $\models_{\text{sextm}}$  clausesNOT (fst S)
    using rtrancpl-cdclNOT-restart-eq-sat-iff[of S T] full inv n-d unfolding full-def by blast
  moreover then have satisfiable (set-mset (clausesNOT (fst S)))
    using consistent-true-clss-ext-satisfiable distinct-consistent-interp n-d-T by fast
  ultimately show ?thesis by fast
qed
qed

```

**corollary** *full-cdcl<sub>NOT</sub>-restart-normal-form-init-state*:

```

assumes
  init-state: trail S = [] clausesNOT S = N and
  full: full cdclNOT-restart (S, 0) T and
  inv: inv S
shows unsatisfiable (set-mset N)
   $\vee$  lits-of-l (trail (fst T))  $\models_{\text{sextm}}$  N  $\wedge$  satisfiable (set-mset N)
using full-cdclNOT-restart-normal-form[of (S, 0) T] assms by auto

```

end

end

**theory** DPLL-NOT

**imports** CDCL-NOT

**begin**

## 17 DPLL as an instance of NOT

### 17.1 DPLL with simple backtrack

We are using a concrete couple instead of an abstract state.

**locale** *dppll-with-backtrack*

**begin**

**inductive** *backtrack* :: ('v, unit, unit) marked-lit list  $\times$  'v clauses

$\Rightarrow$  ('v, unit, unit) marked-lit list  $\times$  'v clauses  $\Rightarrow$  bool **where**

*backtrack-split* (fst S) = (M', L # M)  $\Longrightarrow$  is-marked L  $\Longrightarrow$  D  $\in$  # snd S

$\Longrightarrow$  fst S  $\models_{\text{as}}$  CNot D  $\Longrightarrow$  backtrack S (Propagated (– (lit-of L)) () # M, snd S)

**inductive-cases** *backtrackE*[elim]: *backtrack* (M, N) (M', N')

**lemma** *backtrack-is-backjump*:

**fixes** M M' :: ('v, unit, unit) marked-lit list

**assumes**

*backtrack*: *backtrack* (M, N) (M', N') **and**

*no-dup*: (no-dup  $\circ$  fst) (M, N) **and**

*decomp*: all-decomposition-implies-m N (get-all-marked-decomposition M)

**shows**

$\exists C F' K F L l C'$ .

$M = F' @ \text{Marked } K () \# F \wedge$

$M' = \text{Propagated } L l \# F \wedge N = N' \wedge C \in \# N \wedge F' @ \text{Marked } K d \# F \models_{\text{as}} \text{CNot } C \wedge$

$\text{undefined-lit } F L \wedge \text{atm-of } L \in \text{atms-of-mm } N \cup \text{atm-of } \text{'lits-of-l } (F' @ \text{Marked } K d \# F) \wedge$

$N \models_{\text{pm}} C' + \{\#L\} \wedge F \models_{\text{as}} \text{CNot } C'$

**proof** –

let ?S = (M, N)

```

let ?T = (M', N')
obtain F F' P L D where
  b-sp: backtrack-split M = (F', L # F) and
  is-marked L and
  D ∈# snd ?S and
  M ⊨as CNot D and
  bt: backtrack ?S (Propagated (− (lit-of L)) P # F, N) and
  M': M' = Propagated (− (lit-of L)) P # F and
  [simp]: N' = N
using backtrackE[OF backtrack] by (metis backtrack fstI sndI)
let ?K = lit-of L
let ?C = image-mset lit-of {#K ∈# mset M. is-marked K ∧ K ≠ L#} :: 'v literal multiset
let ?C' = set-mset (image-mset single (?C + {#?K#}))
obtain K where L: L = Marked K () using ⟨is-marked L⟩ by (cases L) auto

have M: M = F' @ Marked K () # F
  using b-sp by (metis L backtrack-split-list-eq fst-conv snd-conv)
moreover have F' @ Marked K () # F ⊨as CNot D
  using ⟨M ⊨as CNot D⟩ unfolding M .
moreover have undefined-lit F (−?K)
  using no-dup unfolding M L by (simp add: defined-lit-map)
moreover have atm-of (−K) ∈ atms-of-mm N ∪ atm-of ' lits-of-l (F' @ Marked K d # F)
  by auto
moreover
  have set-mset N ∪ ?C' ⊨ps {{#}}
  proof −
    have A: set-mset N ∪ ?C' ∪ unmark-l M =
      set-mset N ∪ unmark-l M
    unfolding M L by auto
    have set-mset N ∪ {{#lit-of L#} | L. is-marked L ∧ L ∈ set M}
      ⊨ps unmark-l M
    using all-decomposition-implies-propagated-lits-are-implied[OF decomp] .
    moreover have C': ?C' = {{#lit-of L#} | L. is-marked L ∧ L ∈ set M}
    unfolding M L apply standard
    apply force
    using IntI by auto
    ultimately have N-C-M: set-mset N ∪ ?C' ⊨ps unmark-l M
    by auto
    have set-mset N ∪ (λL. {#lit-of L#}) ' (set M) ⊨ps {{#}}
    unfolding true-clss-clss-def
    proof (intro allI impI, goal-cases)
      case (1 I) note tot = this(1) and cons = this(2) and I-N-M = this(3)
      have I ⊨ D
        using I-N-M ⟨D ∈# snd ?S⟩ unfolding true-clss-def by auto
      moreover have I ⊨s CNot D
        using ⟨M ⊨as CNot D⟩ unfolding M by (metis 1(3) ⟨M ⊨as CNot D⟩
          true-annots-true-cl true-cl-mono-set-mset-l true-clss-def
          true-clss-singleton-lit-of-implies-incl true-clss-union)
      ultimately show ?case using cons consistent-CNot-not by blast
    qed
  then show ?thesis
    using true-clss-clss-left-right[OF N-C-M, of {{#}}] unfolding A by auto
  qed
have N ⊨pm image-mset uminus ?C + {#−?K#}
  unfolding true-clss-clss-def true-clss-clss-def total-over-m-def

```

```

proof (intro allI impI)
  fix I
  assume
    tot: total-over-set I (atms-of-ms (set-mset N  $\cup$  {image-mset uminus ?C + {#- ?K#}})) and
    cons: consistent-interp I and
    I  $\models_{sm}$  N
  have (K  $\in$  I  $\wedge$   $\neg$ K  $\notin$  I)  $\vee$  ( $\neg$ K  $\in$  I  $\wedge$  K  $\notin$  I)
    using cons tot unfolding consistent-interp-def L by (cases K) auto
  have {a  $\in$  set M. is-marked a  $\wedge$  a  $\neq$  Marked K ()} =
    set M  $\cap$  {L. is-marked L  $\wedge$  L  $\neq$  Marked K ()}
    by auto
  then have
    tI: total-over-set I (atm-of 'lit-of ' (set M  $\cap$  {L. is-marked L  $\wedge$  L  $\neq$  Marked K d}))
    using tot by (auto simp add: L atms-of-uminus-lit-atm-of-lit-of)

  then have H:  $\bigwedge x.$ 
    lit-of x  $\notin$  I  $\implies$  x  $\in$  set M  $\implies$  is-marked x
     $\implies$  x  $\neq$  Marked K d  $\implies$   $\neg$ lit-of x  $\in$  I
  proof -
    fix x :: ('v, unit, unit) marked-lit
    assume a1: x  $\neq$  Marked K d
    assume a2: is-marked x
    assume a3: x  $\in$  set M
    assume a4: lit-of x  $\notin$  I
    have atm-of (lit-of x)  $\in$  atm-of 'lit-of '
      (set M  $\cap$  {m. is-marked m  $\wedge$  m  $\neq$  Marked K d})
      using a3 a2 a1 by blast
    then have Pos (atm-of (lit-of x))  $\in$  I  $\vee$  Neg (atm-of (lit-of x))  $\in$  I
      using tI unfolding total-over-set-def by blast
    then show  $\neg$  lit-of x  $\in$  I
      using a4 by (metis (no-types) atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set
        literal.sel(1,2))
  qed
  have  $\neg$ I  $\models_s$  ?C'
    using (set-mset N  $\cup$  ?C'  $\models_{ps}$  {{#}}) tot cons (I  $\models_{sm}$  N)
    unfolding true-clss-clss-def total-over-m-def
    by (simp add: atms-of-uminus-lit-atm-of-lit-of atms-of-ms-single-image-atm-of-lit-of)
  then show I  $\models$  image-mset uminus ?C + {#- lit-of L#}
    unfolding true-clss-def true-cls-def
    using (K  $\in$  I  $\wedge$   $\neg$ K  $\notin$  I)  $\vee$  ( $\neg$ K  $\in$  I  $\wedge$  K  $\notin$  I)
    unfolding L by (auto dest!: H)
  qed
moreover
  have set F'  $\cap$  {K. is-marked K  $\wedge$  K  $\neq$  L} = {}
    using backtrack-split-fst-not-marked[of - M] b-sp by auto
  then have F  $\models_{as}$  CNot (image-mset uminus ?C)
    unfolding M CNot-def true-annots-def by (auto simp add: L lits-of-def)
  ultimately show ?thesis
    using M' (D  $\in$  # snd ?S) L by force
qed

lemma backtrack-is-backjump':
  fixes M M' :: ('v, unit, unit) marked-lit list
  assumes
    backtrack: backtrack S T and

```



*no-dup*: (*no-dup*  $\circ$  *fst*) *S* **and**  
*decomp*: *all-decomposition-implies-m* (*snd* *S*) (*get-all-marked-decomposition* (*fst* *S*))  
**shows**  
 $\exists C F' K F L l C'.$   
 $fst\ S = F' @ \text{Marked } K\ () \# F \wedge$   
 $T = (\text{Propagated } L\ l \# F, snd\ S) \wedge C \in \# \text{ } snd\ S \wedge fst\ S \models_{as} CNot\ C$   
 $\wedge \text{undefined-lit } F\ L \wedge atm\text{-of } L \in atm\text{-of-mm } (snd\ S) \cup atm\text{-of } ' \text{ lits-of-l } (fst\ S) \wedge$   
 $snd\ S \models_{pm} C' + \{\#L\# \} \wedge F \models_{as} CNot\ C'$   
**apply** (*cases* *S*, *cases* *T*)  
**using** *backtrack-is-backjump*[*of* *fst* *S* *snd* *S* *fst* *T* *snd* *T*] *assms* **by** *fastforce*

**sublocale** *dpll-state*  
*id*  $\lambda L\ C. C + \{\#L\# \}$  *remove1-mset*  
*id*  $op + op \in \# \lambda L\ C. C + \{\#L\# \}$  *remove1-mset*  
*fst* *snd*  $\lambda L\ (M, N). (L \# M, N) \lambda(M, N). (tl\ M, N)$   
 $\lambda C\ (M, N). (M, \{\#C\# \} + N) \lambda C\ (M, N). (M, \text{removeAll-mset } C\ N)$   
**by** *unfold-locales* (*auto simp: ac-simps*)

**sublocale** *backjumping-ops*  
*id*  $\lambda L\ C. C + \{\#L\# \}$  *remove1-mset*  
*id*  $op + op \in \# \lambda L\ C. C + \{\#L\# \}$  *remove1-mset*  
*fst* *snd*  $\lambda L\ (M, N). (L \# M, N) \lambda(M, N). (tl\ M, N)$   
 $\lambda C\ (M, N). (M, \{\#C\# \} + N) \lambda C\ (M, N). (M, \text{removeAll-mset } C\ N) \lambda - - S\ T. \text{backtrack } S\ T$   
**by** *unfold-locales*

**lemma** *reduce-trail-to<sub>NOT</sub>-snd*:  
 $snd\ (\text{reduce-trail-to}_{NOT}\ F\ S) = snd\ S$   
**apply** (*induction* *F* *S* *rule: reduce-trail-to<sub>NOT</sub>.induct*)  
**by** (*cases* *S*, *rename-tac* *F* *Sa*, *case-tac* *Sa*)  
*(simp add: less-imp-diff-less reduce-trail-to<sub>NOT</sub>.simps)*

**lemma** *reduce-trail-to<sub>NOT</sub>*:  
 $\text{reduce-trail-to}_{NOT}\ F\ S =$   
*(if*  $\text{length } (fst\ S) \geq \text{length } F$   
*then*  $\text{drop } (\text{length } (fst\ S) - \text{length } F) (fst\ S)$   
*else*  $\square,$   
 $snd\ S)$  (*is*  $?R = ?C$ )  
**proof** –  
**have**  $?R = (fst\ ?R, snd\ ?R)$   
**by** *auto*  
**also have**  $(fst\ ?R, snd\ ?R) = ?C$   
**by** (*auto simp: trail-reduce-trail-to<sub>NOT</sub>-drop reduce-trail-to<sub>NOT</sub>-snd*)  
**finally show** *?thesis* .  
**qed**

**lemma** *backtrack-is-backjump''*:  
**fixes** *M* *M'* :: (*v*, *unit*, *unit*) *marked-lit list*  
**assumes**  
*backtrack*: *backtrack* *S* *T* **and**  
*no-dup*: (*no-dup*  $\circ$  *fst*) *S* **and**  
*decomp*: *all-decomposition-implies-m* (*snd* *S*) (*get-all-marked-decomposition* (*fst* *S*))  
**shows** *backjump* *S* *T*  
**proof** –  
**obtain** *C* *F'* *K* *F* *L* *l* *C'* **where**  
 $1: fst\ S = F' @ \text{Marked } K\ () \# F$  **and**

2:  $T = (\text{Propagated } L \text{ l } \# F, \text{snd } S)$  **and**  
 3:  $C \in \# \text{snd } S$  **and**  
 4:  $\text{fst } S \models_{\text{as}} \text{CNot } C$  **and**  
 5:  $\text{undefined-lit } F L$  **and**  
 6:  $\text{atm-of } L \in \text{atms-of-mm } (\text{snd } S) \cup \text{atm-of ' lits-of-l } (\text{fst } S)$  **and**  
 7:  $\text{snd } S \models_{\text{pm}} C' + \{\#L\# \}$  **and**  
 8:  $F \models_{\text{as}} \text{CNot } C'$   
**using** *backtrack-is-backjump'*[*OF assms*] **by force**  
**show** *?thesis*  
**apply** (*cases S*)  
**using** *backjump.intros*[*OF 1 - - 4 5 - - 8, of T*] 2 *backtrack 1 5 3 6 7*  
**by** (*auto simp: state-eq<sub>NOT</sub>-def trail-reduce-trail-to<sub>NOT</sub>-drop*  
*reduce-trail-to<sub>NOT</sub> simp del: state-simp<sub>NOT</sub>*)  
**qed**

**lemma** *can-do-bt-step*:  
**assumes**  
 $M: \text{fst } S = F' @ \text{Marked } K d \# F$  **and**  
 $C \in \# \text{snd } S$  **and**  
 $C: \text{fst } S \models_{\text{as}} \text{CNot } C$   
**shows**  $\neg \text{no-step backtrack } S$   
**proof** -  
**obtain**  $L G' G$  **where**  
 $\text{backtrack-split } (\text{fst } S) = (G', L \# G)$   
**unfolding**  $M$  **by** (*induction F' rule: marked-lit-list-induct*) *auto*  
**moreover then have** *is-marked L*  
**by** (*metis backtrack-split-snd-hd-marked list.distinct(1) list.sel(1) snd-conv*)  
**ultimately show** *?thesis*  
**using** *backtrack.intros*[*of S G' L G C*]  $\langle C \in \# \text{snd } S \rangle C$  **unfolding**  $M$  **by** *auto*  
**qed**

**end**

**sublocale** *dpll-with-backtrack*  $\subseteq$  *dpll-with-backjumping-ops*  
*id*  $\lambda L C. C + \{\#L\# \}$  *remove1-mset*  
*id*  $op + op \in \# \lambda L C. C + \{\#L\# \}$  *remove1-mset*  
*fst*  $\text{snd } \lambda L (M, N). (L \# M, N)$   
 $\lambda(M, N). (\text{tl } M, N) \lambda C (M, N). (M, \{\#C\# \} + N) \lambda C (M, N). (M, \text{removeAll-mset } C N)$   
 $\lambda(M, N). \text{no-dup } M \wedge \text{all-decomposition-implies-m } N$  (*get-all-marked-decomposition M*)  
 $\lambda - - S T. \text{backtrack } S T$   
 $\lambda - -. \text{True}$   
**apply** *unfold-locales*  
**by** (*metis (mono-tags, lifting) case-prod-beta comp-def dpll-with-backtrack.backtrack-is-backjump''*  
*dpll-with-backtrack.can-do-bt-step id-apply*)

**sublocale** *dpll-with-backtrack*  $\subseteq$  *dpll-with-backjumping*  
*id*  $\lambda L C. C + \{\#L\# \}$  *remove1-mset*  
*id*  $op + op \in \# \lambda L C. C + \{\#L\# \}$  *remove1-mset*  
*fst*  $\text{snd } \lambda L (M, N). (L \# M, N)$   
 $\lambda(M, N). (\text{tl } M, N) \lambda C (M, N). (M, \{\#C\# \} + N) \lambda C (M, N). (M, \text{removeAll-mset } C N)$   
 $\lambda(M, N). \text{no-dup } M \wedge \text{all-decomposition-implies-m } N$  (*get-all-marked-decomposition M*)  
 $\lambda - - S T. \text{backtrack } S T$   
 $\lambda - -. \text{True}$   
**apply** *unfold-locales*  
**using** *dpll-bj-no-dup dpll-bj-all-decomposition-implies-inv* **apply** *fastforce*

```

done

context dpll-with-backtrack
begin
term learn
end

context dpll-with-backtrack
begin
lemma wf-tranclp-dpll-inital-state:
  assumes fin: finite A
  shows wf {((M':('v, unit, unit) marked-lits, N':('v clauses), ([], N))|M' N' N.
    dpll-bj++ ([], N) (M', N') ∧ atms-of-mm N ⊆ atms-of-ms A}
  using wf-tranclp-dpll-bj[OF assms(1)] by (rule wf-subset) auto

corollary full-dpll-final-state-conclusive:
  fixes M M' :: ('v, unit, unit) marked-lit list
  assumes
    full: full dpll-bj ([], N) (M', N')
  shows unsatisfiable (set-mset N) ∨ (M' ⊨asm N ∧ satisfiable (set-mset N))
  using assms full-dpll-backjump-final-state[of ([],N) (M', N') set-mset N] by auto

corollary full-dpll-normal-form-from-init-state:
  fixes M M' :: ('v, unit, unit) marked-lit list
  assumes
    full: full dpll-bj ([], N) (M', N')
  shows M' ⊨asm N ⟷ satisfiable (set-mset N)
proof -
  have no-dup M'
  using rtranclp-dpll-bj-no-dup[of ([], N) (M', N')]
  full unfolding full-def by auto
  then have M' ⊨asm N ⟹ satisfiable (set-mset N)
  using distinct-consistent-interp satisfiable-carac' true-annots-true-cls by blast
  then show ?thesis
  using full-dpll-final-state-conclusive[OF full] by auto
qed

interpretation conflict-driven-clause-learning-ops
  id λL C. C + {#L#} remove1-mset
  id op + op ∈# λL C. C + {#L#} remove1-mset
  fst snd λL (M, N). (L # M, N)
  λ(M, N). (tl M, N) λC (M, N). (M, {#C#} + N) λC (M, N). (M, removeAll-mset C N)
  λ(M, N). no-dup M ∧ all-decomposition-implies-m N (get-all-marked-decomposition M)
  λ- - S T. backtrack S T
  λ- -. True λ- -. False λ- -. False
  by unfold-locales

interpretation conflict-driven-clause-learning
  id λL C. C + {#L#} remove1-mset
  id op + op ∈# λL C. C + {#L#} remove1-mset
  fst snd λL (M, N). (L # M, N)
  λ(M, N). (tl M, N) λC (M, N). (M, {#C#} + N) λC (M, N). (M, removeAll-mset C N)
  λ(M, N). no-dup M ∧ all-decomposition-implies-m N (get-all-marked-decomposition M)
  λ- - S T. backtrack S T

```

```

λ- -. True λ- -. False λ- -. False
apply unfold-locales
using cdclNOT-all-decomposition-implies cdclNOT-no-dup by fastforce

```

```

lemma cdclNOT-is-dpll:
  cdclNOT S T  $\longleftrightarrow$  dpll-bj S T
by (auto simp: cdclNOT.simps learn.simps forgetNOT.simps)

```

Another proof of termination:

```

lemma wf {(T, S). dpll-bj S T  $\wedge$  cdclNOT-NOT-all-inv A S}
  unfolding cdclNOT-is-dpll[symmetric]
  by (rule wf-cdclNOT-no-learn-and-forget-infinite-chain)
  (auto simp: learn.simps forgetNOT.simps)
end

```

## 17.2 Adding restarts

This was mainly a test whether it was possible to instantiate the assumption of the locale.

```

locale dpll-withbacktrack-and-restarts =
  dpll-with-backtrack +
  fixes f :: nat  $\Rightarrow$  nat
  assumes unbounded: unbounded f and f-ge-1:  $\bigwedge n. n \geq 1 \Rightarrow f n \geq 1$ 
begin
  sublocale cdclNOT-increasing-restarts
    id λL C. C + {#L#} remove1-mset
    id op + op ∈ # λL C. C + {#L#} remove1-mset
  fst snd λL (M, N). (L # M, N) λ(M, N). (tl M, N)
  λC (M, N). (M, {#C#} + N) λC (M, N). (M, removeAll-mset C N) f λ(-, N) S. S = ([], N)
  λA (M, N). atms-of-mm N  $\subseteq$  atms-of-ms A  $\wedge$  atm-of ' lits-of-l M  $\subseteq$  atms-of-ms A  $\wedge$  finite A
   $\wedge$  all-decomposition-implies-m N (get-all-marked-decomposition M)
  λA T. ( $2 + \text{card } (\text{atms-of-ms } A)$ )  $\wedge$  ( $1 + \text{card } (\text{atms-of-ms } A)$ )
    -  $\mu_C$  ( $1 + \text{card } (\text{atms-of-ms } A)$ ) ( $2 + \text{card } (\text{atms-of-ms } A)$ ) (trail-weight T) dpll-bj
  λ(M, N). no-dup M  $\wedge$  all-decomposition-implies-m N (get-all-marked-decomposition M)
  λA -. ( $2 + \text{card } (\text{atms-of-ms } A)$ )  $\wedge$  ( $1 + \text{card } (\text{atms-of-ms } A)$ )
apply unfold-locales
  apply (rule unbounded)
  using f-ge-1 apply fastforce
  apply (smt dpll-bj-all-decomposition-implies-inv dpll-bj-atms-in-trail-in-set
    dpll-bj-clauses id-apply prod.case-eq-if)
  apply (rule dpll-bj-trail-mes-decreasing-prop; auto)
  apply (rename-tac A T U, case-tac T, simp)
  apply (rename-tac A T U, case-tac U, simp)
  using dpll-bj-clauses dpll-bj-all-decomposition-implies-inv dpll-bj-no-dup by fastforce +
end

end
theory DPLL-W
imports Main Partial-Clausal-Logic Partial-Annotated-Clausal-Logic List-More Wellfounded-More
  DPLL-NOT
begin

```

## 18 DPLL

### 18.1 Rules

**type-synonym**  $'a \text{ dpll}_W\text{-marked-lit} = ('a, \text{unit}, \text{unit}) \text{ marked-lit}$   
**type-synonym**  $'a \text{ dpll}_W\text{-marked-lits} = ('a, \text{unit}, \text{unit}) \text{ marked-lits}$   
**type-synonym**  $'v \text{ dpll}_W\text{-state} = 'v \text{ dpll}_W\text{-marked-lits} \times 'v \text{ clauses}$

**abbreviation**  $\text{trail} :: 'v \text{ dpll}_W\text{-state} \Rightarrow 'v \text{ dpll}_W\text{-marked-lits}$  **where**  
 $\text{trail} \equiv \text{fst}$   
**abbreviation**  $\text{clauses} :: 'v \text{ dpll}_W\text{-state} \Rightarrow 'v \text{ clauses}$  **where**  
 $\text{clauses} \equiv \text{snd}$

The definition of DPLL is given in figure 2.13 page 70 of CW.

**inductive**  $\text{dpll}_W :: 'v \text{ dpll}_W\text{-state} \Rightarrow 'v \text{ dpll}_W\text{-state} \Rightarrow \text{bool}$  **where**  
 $\text{propagate: } C + \{\#L\# \} \in \# \text{ clauses } S \Longrightarrow \text{trail } S \models_{\text{as}} C \text{Not } C \Longrightarrow \text{undefined-lit } (\text{trail } S) \ L$   
 $\Longrightarrow \text{dpll}_W \ S \ (\text{Propagated } L \ () \ \# \ \text{trail } S, \text{ clauses } S) \mid$   
 $\text{decided: } \text{undefined-lit } (\text{trail } S) \ L \Longrightarrow \text{atm-of } L \in \text{atms-of-mm } (\text{clauses } S)$   
 $\Longrightarrow \text{dpll}_W \ S \ (\text{Marked } L \ () \ \# \ \text{trail } S, \text{ clauses } S) \mid$   
 $\text{backtrack: } \text{backtrack-split } (\text{trail } S) = (M', L \# M) \Longrightarrow \text{is-marked } L \Longrightarrow D \in \# \text{ clauses } S$   
 $\Longrightarrow \text{trail } S \models_{\text{as}} C \text{Not } D \Longrightarrow \text{dpll}_W \ S \ (\text{Propagated } (- \ (\text{lit-of } L)) \ () \ \# \ M, \text{ clauses } S)$

### 18.2 Invariants

**lemma**  $\text{dpll}_W\text{-distinct-inv:}$   
**assumes**  $\text{dpll}_W \ S \ S'$   
**and**  $\text{no-dup } (\text{trail } S)$   
**shows**  $\text{no-dup } (\text{trail } S')$   
**using**  $\text{assms}$   
**proof** ( $\text{induct rule: } \text{dpll}_W.\text{induct}$ )  
**case** ( $\text{decided } L \ S$ )  
**then show**  $?case$  **using**  $\text{defined-lit-map by force}$   
**next**  
**case** ( $\text{propagate } C \ L \ S$ )  
**then show**  $?case$  **using**  $\text{defined-lit-map by force}$   
**next**  
**case** ( $\text{backtrack } S \ M' \ L \ M \ D$ ) **note**  $\text{extracted} = \text{this}(1)$  **and**  $\text{no-dup} = \text{this}(5)$   
**show**  $?case$   
**using**  $\text{no-dup backtrack-split-list-eq[of trail } S, \text{ symmetric}]$  **unfolding**  $\text{extracted by auto}$   
**qed**

**lemma**  $\text{dpll}_W\text{-consistent-interp-inv:}$   
**assumes**  $\text{dpll}_W \ S \ S'$   
**and**  $\text{consistent-interp } (\text{lits-of-l } (\text{trail } S))$   
**and**  $\text{no-dup } (\text{trail } S)$   
**shows**  $\text{consistent-interp } (\text{lits-of-l } (\text{trail } S'))$   
**using**  $\text{assms}$   
**proof** ( $\text{induct rule: } \text{dpll}_W.\text{induct}$ )  
**case** ( $\text{backtrack } S \ M' \ L \ M \ D$ ) **note**  $\text{extracted} = \text{this}(1)$  **and**  $\text{marked} = \text{this}(2)$  **and**  $D = \text{this}(4)$  **and**  
 $\text{cons} = \text{this}(5)$  **and**  $\text{no-dup} = \text{this}(6)$   
**have**  $\text{no-dup}': \text{no-dup } M$   
**by** ( $\text{metis } (\text{no-types}) \text{backtrack-split-list-eq distinct.simps}(2) \text{distinct-append extracted}$   
 $\text{list.simps}(9) \text{map-append no-dup snd-conv}$ )  
**then have**  $\text{insert } (\text{lit-of } L) \ (\text{lits-of-l } M) \subseteq \text{lits-of-l } (\text{trail } S)$   
**using**  $\text{backtrack-split-list-eq[of trail } S, \text{ symmetric}]$  **unfolding**  $\text{extracted by auto}$   
**then have**  $\text{cons: consistent-interp } (\text{insert } (\text{lit-of } L) \ (\text{lits-of-l } M))$

using *consistent-interp-subset cons* by *blast*  
 moreover  
 have *lit-of L*  $\notin$  *lits-of-l M*  
   using *no-dup backtrack-split-list-eq*[of *trail S*, *symmetric*] *extracted*  
   unfolding *lits-of-def* by *force*  
 moreover  
 have *atm-of* ( $\neg$ *lit-of L*)  $\notin$  ( $\lambda m. \text{atm-of } (\text{lit-of } m)$ ) ‘*set M*’  
   using *no-dup backtrack-split-list-eq*[of *trail S*, *symmetric*] **unfolding** *extracted* by *force*  
 then have  $\neg$ *lit-of L*  $\notin$  *lits-of-l M*  
   unfolding *lits-of-def* by *force*  
 ultimately show ?*case* by *simp*  
 qed (*auto intro: consistent-add-undefined-lit-consistent*)

**lemma** *dpll<sub>W</sub>-vars-in-snd-inv*:  
 assumes *dpll<sub>W</sub> S S'*  
 and *atm-of* ‘(*lits-of-l* (*trail S*))  $\subseteq$  *atms-of-mm* (*clauses S*)’  
 shows *atm-of* ‘(*lits-of-l* (*trail S'*))  $\subseteq$  *atms-of-mm* (*clauses S'*)’  
 using *assms*  
**proof** (*induct rule: dpll<sub>W</sub>.induct*)  
 case (*backtrack S M' L M D*)  
 then have *atm-of* (*lit-of L*)  $\in$  *atms-of-mm* (*clauses S*)  
   using *backtrack-split-list-eq*[of *trail S*, *symmetric*] by *auto*  
 moreover  
 have *atm-of* ‘*lits-of-l* (*trail S*)  $\subseteq$  *atms-of-mm* (*clauses S*)’  
   using *backtrack*(5) by *simp*  
 then have  $\bigwedge x. x \in \text{set } M \implies \text{atm-of } (\text{lit-of } x) \in \text{atms-of-mm } (\text{clauses } S)$   
   using *backtrack-split-list-eq*[*symmetric*, of *trail S*] *backtrack.hyps*(1)  
   unfolding *lits-of-def* by *auto*  
 ultimately show ?*case* by (*auto simp : lits-of-def*)  
 qed (*auto simp: in-plus-implies-atm-of-on-atms-of-ms*)

**lemma** *atms-of-ms-lit-of-atms-of*: *atms-of-ms* (( $\lambda a. \{\# \text{lit-of } a \# \}$ ) ‘*c*’) = *atm-of* ‘*lit-of* ‘*c*’  
 unfolding *atms-of-ms-def* using *image-iff* by *force*

Lemma theorem 2.8.2 page 71 of CW

**lemma** *dpll<sub>W</sub>-propagate-is-conclusion*:  
 assumes *dpll<sub>W</sub> S S'*  
 and *all-decomposition-implies-m* (*clauses S*) (*get-all-marked-decomposition* (*trail S*))  
 and *atm-of* ‘*lits-of-l* (*trail S*)  $\subseteq$  *atms-of-mm* (*clauses S*)’  
 shows *all-decomposition-implies-m* (*clauses S'*) (*get-all-marked-decomposition* (*trail S'*))  
 using *assms*  
**proof** (*induct rule: dpll<sub>W</sub>.induct*)  
 case (*decided L S*)  
 then show ?*case* **unfolding** *all-decomposition-implies-def* by *simp*  
 next  
 case (*propagate C L S*) **note** *inS* = *this*(1) **and** *cnot* = *this*(2) **and** *IH* = *this*(4) **and** *undef* =  
*this*(3) **and** *atms-incl* = *this*(5)  
 let ?*I* = *set* (*map* ( $\lambda a. \{\# \text{lit-of } a \# \}$ ) (*trail S*))  $\cup$  *set-mset* (*clauses S*)  
 have ?*I*  $\models_p C + \{\# L \# \}$  by (*auto simp add: inS*)  
 moreover have ?*I*  $\models_{ps} C \text{Not } C$  using *true-annots-true-clss-cls cnot* by *fastforce*  
 ultimately have ?*I*  $\models_p \{\# L \# \}$  using *true-clss-cls-plus-CNot*[of ?*I* *C L*] *inS* by *blast*  
 {  
   assume *get-all-marked-decomposition* (*trail S*) = []  
   then have ?*case* by *blast*  
 }

```

moreover {
  assume  $n$ : get-all-marked-decomposition (trail  $S$ )  $\neq []$ 
  have  $1$ :  $\bigwedge a\ b. (a, b) \in \text{set } (\text{tl } (\text{get-all-marked-decomposition } (\text{trail } S)))$ 
     $\implies (\text{unmark-l } a \cup \text{set-mset } (\text{clauses } S)) \models_{ps} \text{unmark-l } b$ 
    using IH unfolding all-decomposition-implies-def by (fastforce simp add: list.set-sel(2) n)
  moreover have  $2$ :  $\bigwedge a\ c. \text{hd } (\text{get-all-marked-decomposition } (\text{trail } S)) = (a, c)$ 
     $\implies (\text{unmark-l } a \cup \text{set-mset } (\text{clauses } S)) \models_{ps} (\text{unmark-l } c)$ 
    by (metis IH all-decomposition-implies-cons-pair all-decomposition-implies-single list.collapse n)
  moreover have  $3$ :  $\bigwedge a\ c. \text{hd } (\text{get-all-marked-decomposition } (\text{trail } S)) = (a, c)$ 
     $\implies (\text{unmark-l } a \cup \text{set-mset } (\text{clauses } S)) \models_p \{\#L\#$ 
  proof –
    fix  $a\ c$ 
    assume  $h$ :  $\text{hd } (\text{get-all-marked-decomposition } (\text{trail } S)) = (a, c)$ 
    have  $h'$ :  $\text{trail } S = c @ a$  using get-all-marked-decomposition-decomp  $h$  by blast
    have  $I$ :  $\text{set } (\text{map } (\lambda a. \{\#lit\text{-of } a\#\})\ a) \cup \text{set-mset } (\text{clauses } S)$ 
       $\cup \text{unmark-l } c \models_{ps} \text{CNot } C$ 
    using  $\langle ?I \models_{ps} \text{CNot } C \rangle$  unfolding  $h'$  by (simp add: Un-commute Un-left-commute)
    have
       $\text{atms-of-ms } (\text{CNot } C) \subseteq \text{atms-of-ms } (\text{set } (\text{map } (\lambda a. \{\#lit\text{-of } a\#\})\ a) \cup \text{set-mset } (\text{clauses } S))$ 
      and
       $\text{atms-of-ms } (\text{unmark-l } c) \subseteq \text{atms-of-ms } (\text{set } (\text{map } (\lambda a. \{\#lit\text{-of } a\#\})\ a) \cup \text{set-mset } (\text{clauses } S))$ 
    apply (metis CNot-plus Un-subset-iff atms-of-atms-of-ms-mono atms-of-ms-CNot-atms-of atms-of-ms-union inS sup.coboundedI2)
    using inS atms-of-atms-of-ms-mono atms-incl by (fastforce simp: h')

    then have  $\text{unmark-l } a \cup \text{set-mset } (\text{clauses } S) \models_{ps} \text{CNot } C$ 
    using true-clss-clss-left-right[OF - I] h 2 by auto
    then show  $\text{unmark-l } a \cup \text{set-mset } (\text{clauses } S) \models_p \{\#L\#$ 
    by (metis (no-types) Un-insert-right inS insertI1 mk-disjoint-insert inS true-clss-clss-in true-clss-clss-plus-CNot)
    qed
  ultimately have  $?case$ 
    by (cases hd (get-all-marked-decomposition (trail S)))
    (auto simp: all-decomposition-implies-def)
}
ultimately show  $?case$  by auto
next
case (backtrack  $S\ M'\ L\ M\ D$ ) note  $\text{extracted} = \text{this}(1)$  and  $\text{marked} = \text{this}(2)$  and  $D = \text{this}(3)$  and
 $\text{cnot} = \text{this}(4)$  and  $\text{cons} = \text{this}(4)$  and  $IH = \text{this}(5)$  and  $\text{atms-incl} = \text{this}(6)$ 
have  $S$ :  $\text{trail } S = M' @ L \# M$ 
using backtrack-split-list-eq[of trail S] unfolding  $\text{extracted}$  by auto
have  $M'$ :  $\forall l \in \text{set } M'. \neg \text{is-marked } l$ 
using  $\text{extracted}$  backtrack-split-fst-not-marked[of - trail S] by simp
have  $n$ : get-all-marked-decomposition (trail  $S$ )  $\neq []$  by auto
then have all-decomposition-implies-m (clauses  $S$ )  $((L \# M, M')$ 
   $\# \text{tl } (\text{get-all-marked-decomposition } (\text{trail } S)))$ 
by (metis (no-types) IH extracted get-all-marked-decomposition-backtrack-split list.exhaust-sel)
then have  $1$ :  $\text{unmark-l } (L \# M) \cup \text{set-mset } (\text{clauses } S) \models_{ps} (\lambda a. \{\#lit\text{-of } a\#\})\ \text{'set } M'$ 
by simp
moreover
have  $\text{unmark-l } (L \# M) \cup \text{unmark-l } M' \models_{ps} \text{CNot } D$ 
by (metis (mono-tags, lifting) S Un-commute cons image-Un set-append true-annots-true-clss-clss)

```

```

then have 2: unmark-l (L # M) ∪ set-mset (clauses S) ∪ unmark-l M'
   $\models_{ps}$  CNot D
by (metis (no-types, lifting) Un-assoc Un-left-commute true-clss-clss-union-l-r)
ultimately
have set (map ( $\lambda a. \{\#lit\text{-of } a\# \}$ ) (L # M)) ∪ set-mset (clauses S)  $\models_{ps}$  CNot D
  using true-clss-clss-left-right by fastforce
then have set (map ( $\lambda a. \{\#lit\text{-of } a\# \}$ ) (L # M)) ∪ set-mset (clauses S)  $\models_p$   $\{\#\}$ 
  by (metis (mono-tags, lifting) D Un-def mem-Collect-eq
    true-clss-clss-contradiction-true-clss-clss-false)
then have IL: unmark-l M ∪ set-mset (clauses S)  $\models_p$   $\{\#-lit\text{-of } L\#\}$ 
  using true-clss-clss-false-left-right by auto
show ?case unfolding S all-decomposition-implies-def
proof
  fix x P level
  assume x: x ∈ set (get-all-marked-decomposition
    (fst (Propagated (- lit-of L) P # M, clauses S)))
  let ?M' = Propagated (- lit-of L) P # M
  let ?hd = hd (get-all-marked-decomposition ?M')
  let ?tl = tl (get-all-marked-decomposition ?M')
  have x = ?hd ∨ x ∈ set ?tl
    using x
    by (cases get-all-marked-decomposition ?M')
      auto
  moreover {
    assume x': x ∈ set ?tl
    have L': Marked (lit-of L) () = L using marked by (cases L, auto)
    have x ∈ set (get-all-marked-decomposition (M' @ L # M))
      using x' get-all-marked-decomposition-except-last-choice-equal[of M' lit-of L P M]
      L' by (metis (no-types) M' list.set-sel(2) tl-Nil)
    then have case x of (Ls, seen)  $\Rightarrow$  unmark-l Ls ∪ set-mset (clauses S)
       $\models_{ps}$  unmark-l seen
      using marked IH by (cases L) (auto simp add: S all-decomposition-implies-def)
  }
  moreover {
    assume x': x = ?hd
    have tl: tl (get-all-marked-decomposition (M' @ L # M))  $\neq$  []
    proof -
      have f1:  $\bigwedge ms. \text{length} (\text{get-all-marked-decomposition} (M' @ ms))$ 
        =  $\text{length} (\text{get-all-marked-decomposition } ms)$ 
      by (simp add: M' get-all-marked-decomposition-remove-unmark-ssed-length)
      have Suc ( $\text{length} (\text{get-all-marked-decomposition } M)$ )  $\neq$  Suc 0
      by blast
      then show ?thesis
        using f1 marked by (metis (no-types) get-all-marked-decomposition.simps(1) length-tl
          list.sel(3) list.size(3) marked-lit.collapse(1))
    qed
  }
  obtain M0' M0 where
    L0: hd (tl (get-all-marked-decomposition (M' @ L # M))) = (M0, M0')
    by (cases hd (tl (get-all-marked-decomposition (M' @ L # M))))
  have x'': x = (M0, Propagated (-lit-of L) P # M0')
    unfolding x' using get-all-marked-decomposition-last-choice tl M' L0
    by (metis marked marked-lit.collapse(1))
  obtain l-get-all-marked-decomposition where
    get-all-marked-decomposition (trail S) = (L # M, M') # (M0, M0') #
    l-get-all-marked-decomposition

```



**using** *get-all-marked-decomposition-backtrack-split* **extracted by** (*metis* (*no-types*) *L0 S*  
*hd-Cons-tl n tl*)  
**then have**  $M = M0' @ M0$  **using** *get-all-marked-decomposition-hd-hd* **by** *fastforce*  
**then have**  $IL'$ : *unmark-l*  $M0 \cup \text{set-mset}$  (*clauses S*)  
 $\cup \text{unmark-l } M0' \models_{ps} \{\{\# - \text{lit-of } L\#\}\}$   
**using**  $IL$  **by** (*simp add: Un-commute Un-left-commute image-Un*)  
**moreover have**  $H$ : *unmark-l*  $M0 \cup \text{set-mset}$  (*clauses S*)  
 $\models_{ps} \text{unmark-l } M0'$   
**using**  $IH x''$  **unfolding** *all-decomposition-implies-def* **by** (*metis* (*no-types*, *lifting*) *L0 S*  
*list.set-sel(1) list.set-sel(2) old.prod.case tl tl-Nil*)  
**ultimately have** *case x of (Ls, seen)  $\Rightarrow$  unmark-l Ls  $\cup \text{set-mset}$*  (*clauses S*)  
 $\models_{ps} \text{unmark-l seen}$   
**using** *true-clss-clss-left-right* **unfolding**  $x''$  **by** *auto*  
**}**  
**ultimately show** *case x of (Ls, seen)  $\Rightarrow$*   
*unmark-l Ls  $\cup \text{set-mset}$  (snd (?M', clauses S))*  
 $\models_{ps} \text{unmark-l seen}$   
**unfolding** *snd-conv* **by** *blast*  
**qed**  
**qed**

Lemma theorem 2.8.3 page 72 of CW

**theorem** *dpll<sub>W</sub>-propagate-is-conclusion-of-decided*:  
**assumes** *dpll<sub>W</sub> S S'*  
**and** *all-decomposition-implies-m* (*clauses S*) (*get-all-marked-decomposition* (*trail S*))  
**and** *atm-of* ' *lits-of-l* (*trail S*)  $\subseteq$  *atms-of-mm* (*clauses S*)  
**shows** *set-mset* (*clauses S'*)  $\cup \{\{\# \text{lit-of } L\#\} \mid L. \text{is-marked } L \wedge L \in \text{set} (\text{trail } S')\}$   
 $\models_{ps} (\lambda a. \{\# \text{lit-of } a\#\}) ' \bigcup (\text{set} ' \text{snd} ' \text{set} (\text{get-all-marked-decomposition} (\text{trail } S')))$   
**using** *all-decomposition-implies-trail-is-implied*[*OF dpll<sub>W</sub>-propagate-is-conclusion*[*OF assms*]] .

Lemma theorem 2.8.4 page 72 of CW

**lemma** *only-propagated-vars-unsat*:  
**assumes** *marked*:  $\forall x \in \text{set } M. \neg \text{is-marked } x$   
**and**  $DN$ :  $D \in N$  **and**  $D$ :  $M \models_{as} C \text{Not } D$   
**and** *inv*: *all-decomposition-implies*  $N$  (*get-all-marked-decomposition*  $M$ )  
**and** *atm-incl*: *atm-of* ' *lits-of-l*  $M \subseteq$  *atms-of-ms*  $N$   
**shows** *unsatisfiable*  $N$   
**proof** (*rule ccontr*)  
**assume**  $\neg \text{unsatisfiable } N$   
**then obtain**  $I$  **where**  
 $I$ :  $I \models_s N$  **and**  
*cons*: *consistent-interp*  $I$  **and**  
*tot*: *total-over-m*  $I N$   
**unfolding** *satisfiable-def* **by** *auto*  
**then have**  $I-D$ :  $I \models D$   
**using**  $DN$  **unfolding** *true-clss-def* **by** *auto*  
  
**have**  $l0$ :  $\{\{\# \text{lit-of } L\#\} \mid L. \text{is-marked } L \wedge L \in \text{set } M\} = \{\}$  **using** *marked* **by** *auto*  
**have** *atms-of-ms* ( $N \cup \text{unmark-l } M$ ) = *atms-of-ms*  $N$   
**using** *atm-incl* **unfolding** *atms-of-ms-def lits-of-def* **by** *auto*  
  
**then have** *total-over-m*  $I$  ( $N \cup (\lambda a. \{\# \text{lit-of } a\#\}) ' (\text{set } M)$ )  
**using** *tot* **unfolding** *total-over-m-def* **by** *auto*  
**then have**  $I \models_s (\lambda a. \{\# \text{lit-of } a\#\}) ' (\text{set } M)$   
**using** *all-decomposition-implies-propagated-lits-are-implied*[*OF inv*] *cons I*

```

  unfolding true-clss-clss-def l0 by auto
then have IM:  $I \models_s \text{unmark-l } M$  by auto
{
  fix K
  assume  $K \in \# D$ 
  then have  $-K \in \text{lits-of-l } M$ 
    by (auto split: if-split-asm
        intro: allE[OF D[unfolded true-annots-def Ball-def], of { $\#-K\#$ }])
  then have  $-K \in I$  using IM true-clss-singleton-lit-of-implies-incl by fastforce
}
then have  $\neg I \models D$  using cons unfolding true-clss-def consistent-interp-def by auto
then show False using I-D by blast
qed

```

**lemma** *dpll<sub>W</sub>-same-clauses*:

**assumes** *dpll<sub>W</sub> S S'*

**shows** *clauses S = clauses S'*

**using** *assms* **by** (*induct rule: dpll<sub>W</sub>.induct, auto*)

**lemma** *rtranclp-dpll<sub>W</sub>-inv*:

**assumes** *rtranclp dpll<sub>W</sub> S S'*

**and** *inv: all-decomposition-implies-m (clauses S) (get-all-marked-decomposition (trail S))*

**and** *atm-incl: atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-mm (clauses S)*

**and** *consistent-interp (lits-of-l (trail S))*

**and** *no-dup (trail S)*

**shows** *all-decomposition-implies-m (clauses S') (get-all-marked-decomposition (trail S'))*

**and** *atm-of ' lits-of-l (trail S')  $\subseteq$  atms-of-mm (clauses S')*

**and** *clauses S = clauses S'*

**and** *consistent-interp (lits-of-l (trail S'))*

**and** *no-dup (trail S')*

**using** *assms*

**proof** (*induct rule: rtranclp-induct*)

**case** *base*

**show**

*all-decomposition-implies-m (clauses S) (get-all-marked-decomposition (trail S))* **and**

*atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-mm (clauses S)* **and**

*clauses S = clauses S* **and**

*consistent-interp (lits-of-l (trail S))* **and**

*no-dup (trail S)* **using** *assms* **by** *auto*

**next**

**case** (*step S' S''*) **note** *dpll<sub>W</sub>Star = this(1)* **and** *IH = this(3,4,5,6,7)* **and**

*dpll<sub>W</sub> = this(2)*

**moreover**

**assume**

*inv: all-decomposition-implies-m (clauses S) (get-all-marked-decomposition (trail S))* **and**

*atm-incl: atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-mm (clauses S)* **and**

*cons: consistent-interp (lits-of-l (trail S))* **and**

*no-dup (trail S)*

**ultimately have** *decomp: all-decomposition-implies-m (clauses S')*

*(get-all-marked-decomposition (trail S'))* **and**

*atm-incl': atm-of ' lits-of-l (trail S')  $\subseteq$  atms-of-mm (clauses S')* **and**

*snd: clauses S = clauses S'* **and**

*cons': consistent-interp (lits-of-l (trail S'))* **and**

*no-dup': no-dup (trail S')* **by** *blast+*

**show** *clauses S = clauses S''* **using** *dpll<sub>W</sub>-same-clauses[OF dpll<sub>W</sub>] snd* **by** *metis*

```

show all-decomposition-implies-m (clauses S'') (get-all-marked-decomposition (trail S''))
  using dpllW-propagate-is-conclusion[OF dpllW] decomp atm-incl' by auto
show atm-of ' lits-of-l (trail S'')  $\subseteq$  atms-of-mm (clauses S'')
  using dpllW-vars-in-snd-inv[OF dpllW] atm-incl atm-incl' by auto
show no-dup (trail S'') using dpllW-distinct-inv[OF dpllW] no-dup' dpllW by auto
show consistent-interp (lits-of-l (trail S''))
  using cons' no-dup' dpllW-consistent-interp-inv[OF dpllW] by auto
qed

```

```

definition dpllW-all-inv S  $\equiv$ 
  (all-decomposition-implies-m (clauses S) (get-all-marked-decomposition (trail S))
   $\wedge$  atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-mm (clauses S)
   $\wedge$  consistent-interp (lits-of-l (trail S))
   $\wedge$  no-dup (trail S))

```

```

lemma dpllW-all-inv-dest[dest]:
  assumes dpllW-all-inv S
  shows all-decomposition-implies-m (clauses S) (get-all-marked-decomposition (trail S))
  and atm-of ' lits-of-l (trail S)  $\subseteq$  atms-of-mm (clauses S)
  and consistent-interp (lits-of-l (trail S))  $\wedge$  no-dup (trail S)
  using assms unfolding dpllW-all-inv-def lits-of-def by auto

```

```

lemma rtranclp-dpllW-all-inv:
  assumes rtranclp dpllW S S'
  and dpllW-all-inv S
  shows dpllW-all-inv S'
  using assms rtranclp-dpllW-inv[OF assms(1)] unfolding dpllW-all-inv-def lits-of-def by blast

```

```

lemma dpllW-all-inv:
  assumes dpllW S S'
  and dpllW-all-inv S
  shows dpllW-all-inv S'
  using assms rtranclp-dpllW-all-inv by blast

```

```

lemma rtranclp-dpllW-inv-starting-from-0:
  assumes rtranclp dpllW S S'
  and inv: trail S = []
  shows dpllW-all-inv S'
proof –
  have dpllW-all-inv S
    using assms unfolding all-decomposition-implies-def dpllW-all-inv-def by auto
  then show ?thesis using rtranclp-dpllW-all-inv[OF assms(1)] by blast
qed

```

```

lemma dpllW-can-do-step:
  assumes consistent-interp (set M)
  and distinct M
  and atm-of ' (set M)  $\subseteq$  atms-of-mm N
  shows rtranclp dpllW ([], N) (map ( $\lambda M. \text{Marked } M$  ()) M, N)
  using assms
proof (induct M)
  case Nil
  then show ?case by auto
next

```

```

case (Cons L M)
then have undefined-lit (map (λM. Marked M ()) M) L
  unfolding defined-lit-def consistent-interp-def by auto
moreover have atm-of L ∈ atms-of-mm N using Cons.premis(3) by auto
ultimately have dpllW (map (λM. Marked M ()) M, N) (map (λM. Marked M ()) (L # M), N)
  using dpllW.decided by auto
moreover have consistent-interp (set M) and distinct M and atm-of ‘ set M ⊆ atms-of-mm N
  using Cons.premis unfolding consistent-interp-def by auto
ultimately show ?case using Cons.hyps by auto
qed

```

**definition** *conclusive-dpll<sub>W</sub>-state* ( $S :: 'v \text{ dpll}_W\text{-state}$ )  $\longleftrightarrow$   
 $(\text{trail } S \models_{\text{asm}} \text{clauses } S \vee ((\forall L \in \text{set } (\text{trail } S). \neg \text{is-marked } L)$   
 $\wedge (\exists C \in \# \text{ clauses } S. \text{trail } S \models_{\text{as}} \text{CNot } C)))$

**lemma** *dpll<sub>W</sub>-strong-completeness*:

```

assumes set M ⊨sm N
and consistent-interp (set M)
and distinct M
and atm-of ‘ (set M) ⊆ atms-of-mm N
shows dpllW** ([], N) (map (λM. Marked M ()) M, N)
and conclusive-dpllW-state (map (λM. Marked M ()) M, N)
proof -
show rtrancp dpllW ([], N) (map (λM. Marked M ()) M, N) using dpllW-can-do-step assms by auto
have map (λM. Marked M ()) M ⊨asm N using assms(1) true-annots-marked-true-cl by auto
then show conclusive-dpllW-state (map (λM. Marked M ()) M, N)
  unfolding conclusive-dpllW-state-def by auto
qed

```

**lemma** *dpll<sub>W</sub>-sound*:

```

assumes
  rtrancp dpllW ([], N) (M, N) and
  ∀ S. ¬dpllW (M, N) S
shows M ⊨asm N ⟷ satisfiable (set-mset N) (is ?A ⟷ ?B)
proof
let ?M' = lits-of-l M
assume ?A
then have ?M' ⊨sm N by (simp add: true-annots-true-cl)
moreover have consistent-interp ?M'
  using rtrancp-dpllW-inv-starting-from-0[OF assms(1)] by auto
ultimately show ?B by auto
next
assume ?B
show ?A
proof (rule ccontr)
assume n: ¬ ?A
have (∃ L. undefined-lit M L ∧ atm-of L ∈ atms-of-mm N) ∨ (∃ D ∈ # N. M ⊨as CNot D)
proof -
obtain D :: 'a clause where D: D ∈ # N and ¬ M ⊨a D
  using n unfolding true-annots-def Ball-def by auto
then have (∃ L. undefined-lit M L ∧ atm-of L ∈ atms-of D) ∨ M ⊨as CNot D
  unfolding true-annots-def Ball-def CNot-def true-annot-def
  using atm-of-lit-in-atms-of true-annot-iff-marked-or-true-lit true-cl-def by blast

```

```

    then show ?thesis
    by (metis Bex-def D atms-of-atms-of-ms-mono rev-subsetD)
qed
moreover {
  assume  $\exists L. \text{undefined-lit } M \ L \wedge \text{atm-of } L \in \text{atms-of-mm } N$ 
  then have False using assms(2) decided by fastforce
}
moreover {
  assume  $\exists D \in \#N. M \models_{as} CNot \ D$ 
  then obtain D where DN:  $D \in \# \ N$  and MD:  $M \models_{as} CNot \ D$  by auto
  {
    assume  $\forall l \in \text{set } M. \neg \text{is-marked } l$ 
    moreover have dpllW-all-inv ([], N)
    using assms unfolding all-decomposition-implies-def dpllW-all-inv-def by auto
    ultimately have unsatisfiable (set-mset N)
    using only-propagated-vars-unsat[of M D set-mset N] DN MD
    rtranclp-dpllW-all-inv[OF assms(1)] by force
    then have False using <?B> by blast
  }
  moreover {
    assume  $l: \exists l \in \text{set } M. \text{is-marked } l$ 
    then have False
    using backtrack[of (M, N) - - - D] DN MD assms(2)
    backtrack-split-some-is-marked-then-snd-has-hd[OF l]
    by (metis backtrack-split-snd-hd-marked fst-conv list.distinct(1) list.sel(1) snd-conv)
  }
  ultimately have False by blast
}
ultimately show False by blast
qed
qed

```

### 18.3 Termination

**definition**  $dpll_W\text{-mes } M \ n =$   
 $\text{map } (\lambda l. \text{if is-marked } l \text{ then } 2 \text{ else } (1::nat)) (\text{rev } M) \ @ \ \text{replicate } (n - \text{length } M) \ 3$

**lemma**  $\text{length-dpll}_W\text{-mes}$ :  
**assumes**  $\text{length } M \leq n$   
**shows**  $\text{length } (dpll_W\text{-mes } M \ n) = n$   
**using** *assms* **unfolding**  $dpll_W\text{-mes-def}$  **by** *auto*

**lemma**  $\text{distinctcard-atm-of-lit-of-eq-length}$ :  
**assumes** *no-dup S*  
**shows**  $\text{card } (\text{atm-of } \text{' lits-of-l } S) = \text{length } S$   
**using** *assms* **by** (*induct S*) (*auto simp add: image-image lits-of-def*)

**lemma**  $dpll_W\text{-card-decrease}$ :  
**assumes**  $dpll: dpll_W \ S \ S' \text{ and } \text{length } (\text{trail } S') \leq \text{card vars}$   
**and**  $\text{length } (\text{trail } S) \leq \text{card vars}$   
**shows**  $(dpll_W\text{-mes } (\text{trail } S') \ (\text{card vars}), dpll_W\text{-mes } (\text{trail } S) \ (\text{card vars}))$   
 $\in \text{lexn } \{(a, b). a < b\} \ (\text{card vars})$   
**using** *assms*  
**proof** (*induct rule: dpll<sub>W</sub>.induct*)  
**case** (*propagate C L S*)  
**have**  $m: \text{map } (\lambda l. \text{if is-marked } l \text{ then } 2 \text{ else } 1) (\text{rev } (\text{trail } S))$

```

    @ replicate (card vars - length (trail S)) 3
  = map (λl. if is-marked l then 2 else 1) (rev (trail S)) @ 3
    # replicate (card vars - Suc (length (trail S))) 3
  using propagate.premis[simplified] using Suc-diff-le by fastforce
then show ?case
  using propagate.premis(1) unfolding dpllW-mes-def by (fastforce simp add: lexn-conv assms(2))
next
case (decided S L)
have m: map (λl. if is-marked l then 2 else 1) (rev (trail S))
  @ replicate (card vars - length (trail S)) 3
  = map (λl. if is-marked l then 2 else 1) (rev (trail S)) @ 3
  # replicate (card vars - Suc (length (trail S))) 3
  using decided.premis[simplified] using Suc-diff-le by fastforce
then show ?case
  using decided.premis unfolding dpllW-mes-def by (force simp add: lexn-conv assms(2))
next
case (backtrack S M' L M D)
have L: is-marked L using backtrack.hyps(2) by auto
have S: trail S = M' @ L # M
  using backtrack.hyps(1) backtrack-split-list-eq[of trail S] by auto
show ?case
  using backtrack.premis L unfolding dpllW-mes-def S by (fastforce simp add: lexn-conv assms(2))
qed

```

Proposition theorem 2.8.7 page 73 of CW

lemma *dpll<sub>W</sub>-card-decrease'*:

```

  assumes dpll: dpllW S S'
  and atm-incl: atm-of ' lits-of-l (trail S) ⊆ atms-of-mm (clauses S)
  and no-dup: no-dup (trail S)
  shows (dpllW-mes (trail S') (card (atms-of-mm (clauses S'))),
        dpllW-mes (trail S) (card (atms-of-mm (clauses S)))) ∈ lex {(a, b). a < b}

```

proof –

```

  have finite (atms-of-mm (clauses S)) unfolding atms-of-ms-def by auto
  then have 1: length (trail S) ≤ card (atms-of-mm (clauses S))
    using distinctcard-atm-of-lit-of-eq-length[OF no-dup] atm-incl card-mono by metis

```

moreover

```

  have no-dup': no-dup (trail S') using dpll dpllW-distinct-inv no-dup by blast
  have SS': clauses S' = clauses S using dpll by (auto dest!: dpllW-same-clauses)
  have atm-incl': atm-of ' lits-of-l (trail S') ⊆ atms-of-mm (clauses S')
    using atm-incl dpll dpllW-vars-in-snd-inv[OF dpll] by force
  have finite (atms-of-mm (clauses S'))
    unfolding atms-of-ms-def by auto
  then have 2: length (trail S') ≤ card (atms-of-mm (clauses S'))
    using distinctcard-atm-of-lit-of-eq-length[OF no-dup'] atm-incl' card-mono SS' by metis

```

```

ultimately have (dpllW-mes (trail S') (card (atms-of-mm (clauses S'))),
  dpllW-mes (trail S) (card (atms-of-mm (clauses S))))
  ∈ lexn {(a, b). a < b} (card (atms-of-mm (clauses S)))
  using dpllW-card-decrease[OF assms(1), of atms-of-mm (clauses S)] by blast
then have (dpllW-mes (trail S') (card (atms-of-mm (clauses S'))),
  dpllW-mes (trail S) (card (atms-of-mm (clauses S)))) ∈ lex {(a, b). a < b}
  unfolding lex-def by auto
then show (dpllW-mes (trail S') (card (atms-of-mm (clauses S'))),
  dpllW-mes (trail S) (card (atms-of-mm (clauses S)))) ∈ lex {(a, b). a < b}

```

```

    using dpllW-same-clauses[OF assms(1)] by auto
qed

lemma wf-lexn: wf (lexn {(a, b). (a::nat) < b} (card (atms-of-mm (clauses S))))
proof -
  have m: {(a, b). a < b} = measure id by auto
  show ?thesis apply (rule wf-lexn) unfolding m by auto
qed

lemma dpllW-wf:
  wf {(S', S). dpllW-all-inv S ∧ dpllW S S'}
  apply (rule wf-wf-if-measure'[OF wf-lex-less, of - -
    λS. dpllW-mes (trail S) (card (atms-of-mm (clauses S)))])
  using dpllW-card-decrease' by fast

lemma dpllW-trancp-star-commute:
  {(S', S). dpllW-all-inv S ∧ dpllW S S'}+ = {(S', S). dpllW-all-inv S ∧ trancp dpllW S S'}
  (is ?A = ?B)
proof
  { fix S S'
    assume (S, S') ∈ ?A
    then have (S, S') ∈ ?B
      by (induct rule: trancp.induct, auto)
  }
  then show ?A ⊆ ?B by blast
  { fix S S'
    assume (S, S') ∈ ?B
    then have dpllW++ S' S and dpllW-all-inv S' by auto
    then have (S, S') ∈ ?A
      proof (induct rule: trancp.induct)
        case r-into-trancp
        then show ?case by (simp-all add: r-into-trancp')
      next
        case (trancp-into-trancp S S' S'')
        then have (S', S) ∈ {a. case a of (S', S) ⇒ dpllW-all-inv S ∧ dpllW S S'}+ by blast
        moreover have dpllW-all-inv S'
          using rtrancp-dpllW-all-inv[OF trancp-into-rtrancp[OF trancp-into-trancp.hyps(1)]]
          trancp-into-trancp.prem by auto
        ultimately have (S'', S') ∈ {(pa, p). dpllW-all-inv p ∧ dpllW p pa}+
          using (dpllW-all-inv S') trancp-into-trancp.hyps(3) by blast
        then show ?case
          using (S', S) ∈ {a. case a of (S', S) ⇒ dpllW-all-inv S ∧ dpllW S S'}+ by auto
      qed
  }
  then show ?B ⊆ ?A by blast
qed

lemma dpllW-wf-trancp: wf {(S', S). dpllW-all-inv S ∧ dpllW++ S S'}
  unfolding dpllW-trancp-star-commute[symmetric] by (simp add: dpllW-wf wf-trancp)

lemma dpllW-wf-plus:
  shows wf {(S', ([], N)) | S'. dpllW++ ([], N) S'} (is wf ?P)
  apply (rule wf-subset[OF dpllW-wf-trancp, of ?P])
  using assms unfolding dpllW-all-inv-def by auto

```

## 18.4 Final States

**lemma** *dpll<sub>W</sub>-no-more-step-is-a-conclusive-state*:

**assumes**  $\forall S'. \neg \text{dpll}_W S S'$

**shows** *conclusive-dpll<sub>W</sub>-state*  $S$

**proof** –

**have** *vars*:  $\forall s \in \text{atms-of-mm} (\text{clauses } S). s \in \text{atm-of } \text{'lits-of-l'} (\text{trail } S)$

**proof** (*rule ccontr*)

**assume**  $\neg (\forall s \in \text{atms-of-mm} (\text{clauses } S). s \in \text{atm-of } \text{'lits-of-l'} (\text{trail } S))$

**then obtain**  $L$  **where**

$L\text{-in-atms}$ :  $L \in \text{atms-of-mm} (\text{clauses } S)$  **and**

$L\text{-notin-trail}$ :  $L \notin \text{atm-of } \text{'lits-of-l'} (\text{trail } S)$  **by** *metis*

**obtain**  $L'$  **where**  $L'$ :  $\text{atm-of } L' = L$  **by** (*meson literal.sel(2)*)

**then have** *undefined-lit* (*trail*  $S$ )  $L'$

**unfolding** *Marked-Propagated-in-iff-in-lits-of-l* **by** (*metis L-notin-trail atm-of-uminus imageI*)

**then show** *False* **using** *dpll<sub>W</sub>.decided assms(1)*  $L\text{-in-atms } L'$  **by** *blast*

**qed**

**show** *?thesis*

**proof** (*rule ccontr*)

**assume** *not-final*:  $\neg ?thesis$

**then have**

$\neg \text{trail } S \models_{\text{asm}} \text{clauses } S$  **and**

$(\exists L \in \text{set } (\text{trail } S). \text{is-marked } L) \vee (\forall C \in \# \text{clauses } S. \neg \text{trail } S \models_{\text{as}} C \text{Not } C)$

**unfolding** *conclusive-dpll<sub>W</sub>-state-def* **by** *auto*

**moreover** {

**assume**  $\exists L \in \text{set } (\text{trail } S). \text{is-marked } L$

**then obtain**  $L M' M$  **where**  $L$ : *backtrack-split* (*trail*  $S$ ) =  $(M', L \# M)$

**using** *backtrack-split-some-is-marked-then-snd-has-hd* **by** *blast*

**obtain**  $D$  **where**  $D \in \# \text{clauses } S$  **and**  $\neg \text{trail } S \models_a D$

**using**  $\langle \neg \text{trail } S \models_{\text{asm}} \text{clauses } S \rangle$  **unfolding** *true-annots-def* **by** *auto*

**then have**  $\forall s \in \text{atms-of-ms } \{D\}. s \in \text{atm-of } \text{'lits-of-l'} (\text{trail } S)$

**using** *vars* **unfolding** *atms-of-ms-def* **by** *auto*

**then have**  $\text{trail } S \models_{\text{as}} C \text{Not } D$

**using** *all-variables-defined-not-imply-cnot[of D]*  $\langle \neg \text{trail } S \models_a D \rangle$  **by** *auto*

**moreover have** *is-marked*  $L$

**using**  $L$  **by** (*metis backtrack-split-snd-hd-marked list.distinct(1) list.sel(1) snd-conv*)

**ultimately have** *False*

**using** *assms(1)* *dpll<sub>W</sub>.backtrack*  $L \langle D \in \# \text{clauses } S \rangle \langle \text{trail } S \models_{\text{as}} C \text{Not } D \rangle$  **by** *blast*

}

**moreover** {

**assume** *tr*:  $\forall C \in \# \text{clauses } S. \neg \text{trail } S \models_{\text{as}} C \text{Not } C$

**obtain**  $C$  **where**  $C\text{-in-cls}$ :  $C \in \# \text{clauses } S$  **and**  $\text{tr}C$ :  $\neg \text{trail } S \models_a C$

**using**  $\langle \neg \text{trail } S \models_{\text{asm}} \text{clauses } S \rangle$  **unfolding** *true-annots-def* **by** *auto*

**have**  $\forall s \in \text{atms-of-ms } \{C\}. s \in \text{atm-of } \text{'lits-of-l'} (\text{trail } S)$

**using** *vars*  $\langle C \in \# \text{clauses } S \rangle$  **unfolding** *atms-of-ms-def* **by** *auto*

**then have**  $\text{trail } S \models_{\text{as}} C \text{Not } C$

**by** (*meson C-in-cls tr trC all-variables-defined-not-imply-cnot*)

**then have** *False* **using** *tr C-in-cls* **by** *auto*

}

**ultimately show** *False* **by** *blast*

**qed**

**qed**

**lemma** *dpll<sub>W</sub>-conclusive-state-correct*:

**assumes** *dpll<sub>W</sub>\*\** ( $[], N$ ) ( $M, N$ ) **and** *conclusive-dpll<sub>W</sub>-state* ( $M, N$ )

**shows**  $M \models_{\text{asm}} N \longleftrightarrow \text{satisfiable } (\text{set-mset } N)$  (**is**  $?A \longleftrightarrow ?B$ )



```

proof
  let ?M' = lits-of-l M
  assume ?A
  then have ?M'  $\models_{sm}$  N by (simp add: true-annots-true-cls)
  moreover have consistent-interp ?M'
    using rtranclp-dpllW-inv-starting-from-0[OF assms(1)] by auto
  ultimately show ?B by auto
next
  assume ?B
  show ?A
  proof (rule ccontr)
    assume n:  $\neg$  ?A
    have no-mark:  $\forall L \in \text{set } M. \neg \text{is-marked } L \ \exists C \in \# N. M \models_{as} C \text{Not } C$ 
      using n assms(2) unfolding conclusive-dpllW-state-def by auto
    moreover obtain D where DN:  $D \in \# N$  and MD:  $M \models_{as} C \text{Not } D$  using no-mark by auto
    ultimately have unsatisfiable (set-mset N)
      using only-propagated-vars-unsat rtranclp-dpllW-all-inv[OF assms(1)]
      unfolding dpllW-all-inv-def by force
    then show False using ⟨?B⟩ by blast
  qed
qed

```

## 18.5 Link with NOT's DPLL

**interpretation** *dpll<sub>W</sub>-NOT*: *dpll-with-backtrack* .

```

declare dpllW-NOT.state-simpNOT[simp del]
lemma state-eqNOT-iff-eq[iff, simp]: dpllW-NOT.state-eqNOT S T  $\longleftrightarrow$  S = T
  unfolding dpllW-NOT.state-eqNOT-def by (cases S, cases T) auto
lemma dpllW-dpllW-bj:
  assumes inv: dpllW-all-inv S and dpll: dpllW S T
  shows dpllW-NOT.dpll-bj S T
  using dpll inv
  apply (induction rule: dpllW.induct)
    apply (rule dpllW-NOT.bj-propagateNOT)
    apply (rule dpllW-NOT.propagateNOT.propagateNOT; simp?)
    apply fastforce
    apply (rule dpllW-NOT.bj-decideNOT)
    apply (rule dpllW-NOT.decideNOT.decideNOT; simp?)
    apply fastforce
    apply (frule dpllW-NOT.backtrack.intros[of - - - -], simp-all)
    apply (rule dpllW-NOT.dpll-bj.bj-backjump)
    apply (rule dpllW-NOT.backtrack-is-backjump'',
      simp-all add: dpllW-all-inv-def)
  done

lemma dpllW-bj-dpll:
  assumes inv: dpllW-all-inv S and dpll: dpllW-NOT.dpll-bj S T
  shows dpllW S T
  using dpll
  apply (induction rule: dpllW-NOT.dpll-bj.induct)
    apply (elim dpllW-NOT.decideNOTE, cases S)
    apply (frule decided; simp)

  apply (elim dpllW-NOT.propagateNOTE, cases S)
  apply (auto intro!: propagate[of - - (-, -), simplified])[]

```

```

apply (elim  $dpll_{W-NOT}.backjumpE$ , cases  $S$ )
by (simp add:  $dpll_W.simps$   $dpll\_with\_backtrack.backtrack.simps$ )

lemma  $rtrancp\_dpll_W-rtrancp\_dpll_{W-NOT}$ :
  assumes  $dpll_W^{**} S T$  and  $dpll_W-all-inv S$ 
  shows  $dpll_{W-NOT}.dpll\_bj^{**} S T$ 
  using  $assms$  apply (induction)
  apply simp
  by (auto intro:  $rtrancp\_dpll_W-all-inv$   $dpll_W-dpll_W-bj$   $rtrancp.rtrancp\_into-rtrancp$ )

lemma  $rtrancp\_dpll-rtrancp\_dpll_W$ :
  assumes  $dpll_{W-NOT}.dpll\_bj^{**} S T$  and  $dpll_W-all-inv S$ 
  shows  $dpll_W^{**} S T$ 
  using  $assms$  apply (induction)
  apply simp
  by (auto intro:  $dpll_W-bj-dpll$   $rtrancp.rtrancp\_into-rtrancp$   $rtrancp\_dpll_W-all-inv$ )

lemma  $dpll-conclusive-state-correctness$ :
  assumes  $dpll_{W-NOT}.dpll\_bj^{**} ([], N) (M, N)$  and  $conclusive\_dpll_W-state (M, N)$ 
  shows  $M \models_{asm} N \longleftrightarrow satisfiable (set-mset N)$ 
proof –
  have  $dpll_W-all-inv ([], N)$ 
  unfolding  $dpll_W-all-inv-def$  by auto
  show ?thesis
  apply (rule  $dpll_W-conclusive-state-correct$ )
  apply (simp add:  $\langle dpll_W-all-inv ([], N) \rangle assms(1)$   $rtrancp\_dpll-rtrancp\_dpll_W$ )
  using  $assms(2)$  by simp
qed

end
theory  $CDCL-W-Level$ 
imports  $Partial-Annotated-Clausal-Logic$ 
begin

```

### 18.5.1 Level of literals and clauses

Getting the level of a variable, implies that the list has to be reversed. Here is the function after reversing.

```

fun  $get\_rev-level :: ('v, nat, 'a) marked-lits \Rightarrow nat \Rightarrow 'v literal \Rightarrow nat$  where
 $get\_rev-level [] - = 0$  |
 $get\_rev-level (Marked\ l\ level\ \# Ls)\ n\ L =$ 
  (if  $atm-of\ l = atm-of\ L$  then  $level$  else  $get\_rev-level\ Ls\ level\ L$ ) |
 $get\_rev-level (Propagated\ l - \# Ls)\ n\ L =$ 
  (if  $atm-of\ l = atm-of\ L$  then  $n$  else  $get\_rev-level\ Ls\ n\ L$ )

```

**abbreviation**  $get-level\ M\ L \equiv get\_rev-level\ (rev\ M)\ 0\ L$

**lemma**  $get\_rev-level-uminus[simp]$ :  $get\_rev-level\ M\ n(-L) = get\_rev-level\ M\ n\ L$   
**by** (induct arbitrary:  $n$  rule:  $get\_rev-level.induct$ ) auto

**lemma**  $atm-of-notin-get-rev-level-eq-0$ :  
**assumes**  $atm-of\ L \notin atm-of\ ' lits-of-l\ M$   
**shows**  $get\_rev-level\ M\ n\ L = 0$   
**using**  $assms$  **by** (induct  $M$  arbitrary:  $n$  rule:  $marked-lit-list-induct$ ) auto

**lemma** *get-rev-level-ge-0-atm-of-in*:  
**assumes** *get-rev-level*  $M\ n\ L > n$   
**shows**  $\text{atm-of } L \in \text{atm-of ' lits-of-l } M$   
**using** *assms* **by** (*induct*  $M$  *arbitrary*:  $n$  *rule*: *marked-lit-list-induct*)  
*(fastforce simp: atm-of-notin-get-rev-level-eq-0)+*

In *get-rev-level* (resp. *get-level*), the beginning (resp. the end) can be skipped if the literal is not in the beginning (resp. the end).

**lemma** *get-rev-level-skip[simp]*:  
**assumes**  $\text{atm-of } L \notin \text{atm-of ' lits-of-l } M$   
**shows**  $\text{get-rev-level } (M @ \text{Marked } K\ i \# M')\ n\ L = \text{get-rev-level } (\text{Marked } K\ i \# M')\ i\ L$   
**using** *assms* **by** (*induct*  $M$  *arbitrary*:  $n\ i$  *rule*: *marked-lit-list-induct*) *auto*

**lemma** *get-rev-level-notin-end[simp]*:  
**assumes**  $\text{atm-of } L \notin \text{atm-of ' lits-of-l } M'$   
**shows**  $\text{get-rev-level } (M @ M')\ n\ L = \text{get-rev-level } M\ n\ L$   
**using** *assms* **by** (*induct*  $M$  *arbitrary*:  $n$  *rule*: *marked-lit-list-induct*)  
*(auto simp: atm-of-notin-get-rev-level-eq-0)*

If the literal is at the beginning, then the end can be skipped

**lemma** *get-rev-level-skip-end[simp]*:  
**assumes**  $\text{atm-of } L \in \text{atm-of ' lits-of-l } M$   
**shows**  $\text{get-rev-level } (M @ M')\ n\ L = \text{get-rev-level } M\ n\ L$   
**using** *assms* **by** (*induct* *arbitrary*:  $n$  *rule*: *marked-lit-list-induct*) *auto*

**lemma** *get-level-skip-beginning*:  
**assumes**  $\text{atm-of } L' \neq \text{atm-of (lit-of } K)$   
**shows**  $\text{get-level } (K \# M)\ L' = \text{get-level } M\ L'$   
**using** *assms* **by** *auto*

**lemma** *get-level-skip-beginning-not-marked-rev*:  
**assumes**  $\text{atm-of } L \notin \text{atm-of ' lit-of ' (set } S)$   
**and**  $\forall s \in \text{set } S. \neg \text{is-marked } s$   
**shows**  $\text{get-level } (M @ \text{rev } S)\ L = \text{get-level } M\ L$   
**using** *assms* **by** (*induction*  $S$  *rule*: *marked-lit-list-induct*) *auto*

**lemma** *get-level-skip-beginning-not-marked[simp]*:  
**assumes**  $\text{atm-of } L \notin \text{atm-of ' lit-of ' (set } S)$   
**and**  $\forall s \in \text{set } S. \neg \text{is-marked } s$   
**shows**  $\text{get-level } (M @ S)\ L = \text{get-level } M\ L$   
**using** *get-level-skip-beginning-not-marked-rev*[*of*  $L\ \text{rev } S\ M$ ] *assms* **by** *auto*

**lemma** *get-rev-level-skip-beginning-not-marked[simp]*:  
**assumes**  $\text{atm-of } L \notin \text{atm-of ' lit-of ' (set } S)$   
**and**  $\forall s \in \text{set } S. \neg \text{is-marked } s$   
**shows**  $\text{get-rev-level } (\text{rev } S @ \text{rev } M)\ 0\ L = \text{get-level } M\ L$   
**using** *get-level-skip-beginning-not-marked-rev*[*of*  $L\ \text{rev } S\ M$ ] *assms* **by** *auto*

**lemma** *get-level-skip-in-all-not-marked*:  
**fixes**  $M :: ('a, \text{nat}, 'b)\ \text{marked-lit list}$  **and**  $L :: 'a\ \text{literal}$   
**assumes**  $\forall m \in \text{set } M. \neg \text{is-marked } m$   
**and**  $\text{atm-of } L \in \text{atm-of ' lit-of ' (set } M)$   
**shows**  $\text{get-rev-level } M\ n\ L = n$   
**using** *assms* **by** (*induction*  $M$  *rule*: *marked-lit-list-induct*) *auto*

**lemma** *get-level-skip-all-not-marked*[simp]:  
 fixes  $M$   
 defines  $M' \equiv \text{rev } M$   
 assumes  $\forall m \in \text{set } M. \neg \text{is-marked } m$   
 shows  $\text{get-level } M \ L = 0$   
**proof** –  
 have  $M: M = \text{rev } M'$   
   **unfolding**  $M'\text{-def}$  **by** *auto*  
 show ?thesis  
   **using** *assms* **unfolding**  $M$  **by** (*induction*  $M'$  *rule: marked-lit-list-induct*) *auto*  
**qed**

**abbreviation**  $M\text{Max } M \equiv \text{Max } (\text{set-mset } M)$

the  $\{\#0::'a\# \}$  is there to ensures that the set is not empty.

**definition** *get-maximum-level* ::  $('a, \text{nat}, 'b) \text{ marked-lit list} \Rightarrow 'a \text{ literal multiset} \Rightarrow \text{nat}$   
**where**  
*get-maximum-level*  $M \ D = M\text{Max } (\{\#0\# \} + \text{image-mset } (\text{get-level } M) \ D)$

**lemma** *get-maximum-level-ge-get-level*:  
 $L \in \# \ D \Longrightarrow \text{get-maximum-level } M \ D \geq \text{get-level } M \ L$   
**unfolding** *get-maximum-level-def* **by** *auto*

**lemma** *get-maximum-level-empty*[simp]:  
 $\text{get-maximum-level } M \ \{\#\} = 0$   
**unfolding** *get-maximum-level-def* **by** *auto*

**lemma** *get-maximum-level-exists-lit-of-max-level*:  
 $D \neq \{\#\} \Longrightarrow \exists L \in \# \ D. \text{get-level } M \ L = \text{get-maximum-level } M \ D$   
**unfolding** *get-maximum-level-def*  
**apply** (*induct*  $D$ )  
**apply** *simp*  
**by** (*rename-tac*  $D \ x$ , *case-tac*  $D = \{\#\}$ ) (*auto simp add: max-def*)

**lemma** *get-maximum-level-empty-list*[simp]:  
 $\text{get-maximum-level } [] \ D = 0$   
**unfolding** *get-maximum-level-def* **by** (*simp add: image-constant-conv*)

**lemma** *get-maximum-level-single*[simp]:  
 $\text{get-maximum-level } M \ \{\#L\# \} = \text{get-level } M \ L$   
**unfolding** *get-maximum-level-def* **by** *simp*

**lemma** *get-maximum-level-plus*:  
 $\text{get-maximum-level } M \ (D + D') = \max (\text{get-maximum-level } M \ D) (\text{get-maximum-level } M \ D')$   
**by** (*induct*  $D$ ) (*auto simp add: get-maximum-level-def*)

**lemma** *get-maximum-level-exists-lit*:  
 assumes  $n: n > 0$   
 and  $\text{max}: \text{get-maximum-level } M \ D = n$   
 shows  $\exists L \in \# \ D. \text{get-level } M \ L = n$   
**proof** –  
 have  $f: \text{finite } (\text{insert } 0 ((\lambda L. \text{get-level } M \ L) \text{ ` } \text{set-mset } D))$  **by** *auto*  
 then have  $n \in ((\lambda L. \text{get-level } M \ L) \text{ ` } \text{set-mset } D)$   
   **using**  $n \ \text{max}$  *Max-in*[*OF*  $f$ ] **unfolding** *get-maximum-level-def* **by** *simp*

**then show**  $\exists L \in \# D. \text{get-level } M \ L = n$  **by** *auto*  
**qed**

**lemma** *get-maximum-level-skip-first*[simp]:

**assumes** *atm-of*  $L \notin \text{atms-of } D$

**shows** *get-maximum-level* (*Propagated*  $L \ C \ \# \ M$ )  $D = \text{get-maximum-level } M \ D$

**using** *assms* **unfolding** *get-maximum-level-def* *atms-of-def*

*atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set*

**by** (*smt* *atm-of-in-atm-of-set-in-uminus* *get-level-skip-beginning* *image-iff* *marked-lit.sel*(2)  
*multiset.map-cong0*)

**lemma** *get-maximum-level-skip-beginning*:

**assumes**  $DH: \text{atms-of } D \subseteq \text{atm-of 'lits-of-l } H$

**shows** *get-maximum-level* ( $c \ @ \ \text{Marked } Kh \ i \ \# \ H$ )  $D = \text{get-maximum-level } H \ D$

**proof** –

**have** (*get-rev-level* (*rev*  $H \ @ \ \text{Marked } Kh \ i \ \# \ \text{rev } c$ )  $0$ ) ‘ *set-mset*  $D$

$= (\text{get-rev-level } (\text{rev } H) \ 0) \ \text{‘ set-mset } D$

**using**  $DH$  **unfolding** *atms-of-def*

**by** (*metis* (*no-types*, *lifting*) *get-rev-level-skip-end* *image-cong* *image-subset-iff* *set-rev*)

**then show** *?thesis* **using**  $DH$  **unfolding** *get-maximum-level-def* **by** *auto*

**qed**

**lemma** *get-maximum-level-D-single-propagated*:

*get-maximum-level* [*Propagated*  $x21 \ x22$ ]  $D = 0$

**proof** –

**have**  $A: \text{insert } 0 \ ((\lambda L. \ 0) \ \text{‘ } (\text{set-mset } D \cap \{L. \ \text{atm-of } x21 = \text{atm-of } L\})$

$\cup (\lambda L. \ 0) \ \text{‘ } (\text{set-mset } D \cap \{L. \ \text{atm-of } x21 \neq \text{atm-of } L\})) = \{0\}$

**by** *auto*

**show** *?thesis* **unfolding** *get-maximum-level-def* **by** (*simp* *add: A*)

**qed**

**lemma** *get-maximum-level-skip-notin*:

**assumes**  $D: \forall L \in \# D. \text{atm-of } L \in \text{atm-of 'lits-of-l } M$

**shows** *get-maximum-level*  $M \ D = \text{get-maximum-level } (\text{Propagated } x21 \ x22 \ \# \ M) \ D$

**proof** –

**have**  $A: (\text{get-rev-level } (\text{rev } M \ @ \ [\text{Propagated } x21 \ x22]) \ 0) \ \text{‘ set-mset } D$

$= (\text{get-rev-level } (\text{rev } M) \ 0) \ \text{‘ set-mset } D$

**using**  $D$  **by** (*auto* *intro!*: *image-cong* *simp* *add: lits-of-def*)

**show** *?thesis* **unfolding** *get-maximum-level-def* **by** (*auto* *simp: A*)

**qed**

**lemma** *get-maximum-level-skip-un-marked-not-present*:

**assumes**  $\forall L \in \# D. \text{atm-of } L \in \text{atm-of 'lits-of-l } aa$  **and**

$\forall m \in \text{set } M. \neg \text{is-marked } m$

**shows** *get-maximum-level*  $aa \ D = \text{get-maximum-level } (M \ @ \ aa) \ D$

**using** *assms* **by** (*induction*  $M$  *rule: marked-lit-list-induct*)

(*auto* *intro!*: *get-maximum-level-skip-notin*[*of*  $D - @ \ aa$ ] *simp* *add: image-Un*)

**lemma** *get-maximum-level-union-mset*:

*get-maximum-level*  $M \ (A \ \# \cup \ B) = \text{get-maximum-level } M \ (A + B)$

**unfolding** *get-maximum-level-def* **by** (*auto* *simp: image-Un*)

**fun** *get-maximum-possible-level*:: (*'b*, *nat*, *'c*) *marked-lit list*  $\Rightarrow$  *nat* **where**

*get-maximum-possible-level*  $[] = 0$  |

*get-maximum-possible-level* (*Marked*  $K \ i \ \# \ l$ ) =  $\max \ i \ (\text{get-maximum-possible-level } l) \ |$

*get-maximum-possible-level* (*Propagated* - - # *l*) = *get-maximum-possible-level l*

**lemma** *get-maximum-possible-level-append*[simp]:  
*get-maximum-possible-level* (*M*@*M'*)  
 = *max* (*get-maximum-possible-level M*) (*get-maximum-possible-level M'*)  
**by** (*induct M rule: marked-lit-list-induct*) *auto*

**lemma** *get-maximum-possible-level-rev*[simp]:  
*get-maximum-possible-level* (*rev M*) = *get-maximum-possible-level M*  
**by** (*induct M rule: marked-lit-list-induct*) *auto*

**lemma** *get-maximum-possible-level-ge-get-rev-level*:  
*max* (*get-maximum-possible-level M*) *i* ≥ *get-rev-level M i L*  
**by** (*induct M arbitrary: i rule: marked-lit-list-induct*) (*auto simp add: le-max-iff-disj*)

**lemma** *get-maximum-possible-level-ge-get-level*[simp]:  
*get-maximum-possible-level M* ≥ *get-level M L*  
**using** *get-maximum-possible-level-ge-get-rev-level*[of *rev - 0*] **by** *auto*

**lemma** *get-maximum-possible-level-ge-get-maximum-level*[simp]:  
*get-maximum-possible-level M* ≥ *get-maximum-level M D*  
**using** *get-maximum-level-exists-lit-of-max-level* **unfolding** *Bex-def*  
**by** (*metis get-maximum-level-empty get-maximum-possible-level-ge-get-level le0*)

**fun** *get-all-mark-of-propagated* **where**  
*get-all-mark-of-propagated* [] = [] |  
*get-all-mark-of-propagated* (*Marked* - - # *L*) = *get-all-mark-of-propagated L* |  
*get-all-mark-of-propagated* (*Propagated* - mark # *L*) = *mark* # *get-all-mark-of-propagated L*

**lemma** *get-all-mark-of-propagated-append*[simp]:  
*get-all-mark-of-propagated* (*A* @ *B*) = *get-all-mark-of-propagated A* @ *get-all-mark-of-propagated B*  
**by** (*induct A rule: marked-lit-list-induct*) *auto*

## 18.5.2 Properties about the levels

**fun** *get-all-levels-of-marked* :: ('b, 'a, 'c) *marked-lit list* ⇒ 'a *list* **where**  
*get-all-levels-of-marked* [] = [] |  
*get-all-levels-of-marked* (*Marked l level* # *Ls*) = *level* # *get-all-levels-of-marked Ls* |  
*get-all-levels-of-marked* (*Propagated* - - # *Ls*) = *get-all-levels-of-marked Ls*

**lemma** *get-all-levels-of-marked-nil-iff-not-is-marked*:  
*get-all-levels-of-marked xs* = [] ⇔ (∀ *x* ∈ *set xs*. ¬*is-marked x*)  
**using** *assms* **by** (*induction xs rule: marked-lit-list-induct*) *auto*

**lemma** *get-all-levels-of-marked-cons*:  
*get-all-levels-of-marked* (*a* # *b*) =  
 (*if is-marked a then* [*level-of a*] *else* []) @ *get-all-levels-of-marked b*  
**by** (*cases a*) *simp-all*

**lemma** *get-all-levels-of-marked-append*[simp]:  
*get-all-levels-of-marked* (*a* @ *b*) = *get-all-levels-of-marked a* @ *get-all-levels-of-marked b*  
**by** (*induct a*) (*simp-all add: get-all-levels-of-marked-cons*)

**lemma** *in-get-all-levels-of-marked-iff-decomp*:  
*i* ∈ *set* (*get-all-levels-of-marked M*) ⇔ (∃ *c K c'*. *M* = *c* @ *Marked K i* # *c'*) (**is** ?*A* ⇔ ?*B*)  
**proof**

```

  assume ?B
  then show ?A by auto
next
  assume ?A
  then show ?B
  apply (induction M rule: marked-lit-list-induct)
  apply auto[]
  apply (metis append-Cons append-Nil get-all-levels-of-marked.simps(2) set-ConsD)
  by (metis append-Cons get-all-levels-of-marked.simps(3))
qed

```

**lemma** *get-rev-level-less-max-get-all-levels-of-marked:*  
 $get\_rev\_level\ M\ n\ L \leq Max\ (set\ (n\ \# \ get\_all\_levels\_of\_marked\ M))$   
**by** (induct M arbitrary: n rule: get-all-levels-of-marked.induct)  
 (simp-all add: max.coboundedI2)

**lemma** *get-rev-level-ge-min-get-all-levels-of-marked:*  
**assumes**  $atm\_of\ L \in atm\_of\ ' \ lits\_of\_l\ M$   
**shows**  $get\_rev\_level\ M\ n\ L \geq Min\ (set\ (n\ \# \ get\_all\_levels\_of\_marked\ M))$   
**using** *assms* **by** (induct M arbitrary: n rule: get-all-levels-of-marked.induct)  
 (auto simp add: min-le-iff-disj)

**lemma** *get-all-levels-of-marked-rev-eq-rev-get-all-levels-of-marked[simp]:*  
 $get\_all\_levels\_of\_marked\ (rev\ M) = rev\ (get\_all\_levels\_of\_marked\ M)$   
**by** (induct M rule: get-all-levels-of-marked.induct)  
 (simp-all add: max.coboundedI2)

**lemma** *get-maximum-possible-level-max-get-all-levels-of-marked:*  
 $get\_maximum\_possible\_level\ M = Max\ (insert\ 0\ (set\ (get\_all\_levels\_of\_marked\ M)))$   
**by** (induct M rule: marked-lit-list-induct) (auto simp: insert-commute)

**lemma** *get-rev-level-in-levels-of-marked:*  
 $get\_rev\_level\ M\ n\ L \in \{0, n\} \cup set\ (get\_all\_levels\_of\_marked\ M)$   
**by** (induction M arbitrary: n rule: marked-lit-list-induct) (force simp add: atm-of-eq-atm-of)+

**lemma** *get-rev-level-in-atms-in-levels-of-marked:*  
 $atm\_of\ L \in atm\_of\ ' \ (lits\_of\_l\ M) \implies$   
 $get\_rev\_level\ M\ n\ L \in \{n\} \cup set\ (get\_all\_levels\_of\_marked\ M)$   
**by** (induction M arbitrary: n rule: marked-lit-list-induct) (auto simp add: atm-of-eq-atm-of)

**lemma** *get-all-levels-of-marked-no-marked:*  
 $(\forall l \in set\ Ls. \neg is\_marked\ l) \longleftrightarrow get\_all\_levels\_of\_marked\ Ls = []$   
**by** (induction Ls) (auto simp add: get-all-levels-of-marked-cons)

**lemma** *get-level-in-levels-of-marked:*  
 $get\_level\ M\ L \in \{0\} \cup set\ (get\_all\_levels\_of\_marked\ M)$   
**using** *get-rev-level-in-levels-of-marked[of rev M 0 L]* **by** auto

The zero is here to avoid empty-list issues with *last*:

**lemma** *get-level-get-rev-level-get-all-levels-of-marked:*  
**assumes**  $atm\_of\ L \notin atm\_of\ ' \ (lits\_of\_l\ M)$   
**shows**  
 $get\_level\ (K\ @\ M)\ L = get\_rev\_level\ (rev\ K)\ (last\ (0\ \# \ get\_all\_levels\_of\_marked\ (rev\ M)))\ L$   
**using** *assms*  
**proof** (induct M arbitrary: K)

```

case Nil
then show ?case by auto
next
case (Cons a M)
then have H:  $\bigwedge K. \text{get-level } (K @ M) L$ 
  =  $\text{get-rev-level } (\text{rev } K) (\text{last } (0 \# \text{get-all-levels-of-marked } (\text{rev } M))) L$ 
  by auto
have  $\text{get-level } ((K @ [a]) @ M) L$ 
  =  $\text{get-rev-level } (a \# \text{rev } K) (\text{last } (0 \# \text{get-all-levels-of-marked } (\text{rev } M))) L$ 
  using H[of K @ [a]] by simp
then show ?case using Cons(2) by (cases a) auto
qed

lemma get-rev-level-can-skip-correctly-ordered:
  assumes
    no-dup M and
    atm-of L  $\notin$  atm-of ' (lits-of-l M) and
     $\text{get-all-levels-of-marked } M = \text{rev } [\text{Suc } 0..<\text{Suc } (\text{length } (\text{get-all-levels-of-marked } M))]$ 
  shows  $\text{get-rev-level } (\text{rev } M @ K) 0 L = \text{get-rev-level } K (\text{length } (\text{get-all-levels-of-marked } M)) L$ 
  using assms
proof (induct M arbitrary: K rule: marked-lit-list-induct)
  case nil
  then show ?case by simp
next
  case (marked L' i M K)
  then have
    i:  $i = \text{Suc } (\text{length } (\text{get-all-levels-of-marked } M))$  and
     $\text{get-all-levels-of-marked } M = \text{rev } [\text{Suc } 0..<\text{Suc } (\text{length } (\text{get-all-levels-of-marked } M))]$ 
    by auto
  then have  $\text{get-rev-level } (\text{rev } M @ (\text{Marked } L' i \# K)) 0 L$ 
    =  $\text{get-rev-level } (\text{Marked } L' i \# K) (\text{length } (\text{get-all-levels-of-marked } M)) L$ 
    using marked by auto
  then show ?case using marked unfolding i by auto
next
  case (proped L' D M K)
  then have  $\text{get-all-levels-of-marked } M = \text{rev } [\text{Suc } 0..<\text{Suc } (\text{length } (\text{get-all-levels-of-marked } M))]$ 
    by auto
  then have  $\text{get-rev-level } (\text{rev } M @ (\text{Propagated } L' D \# K)) 0 L$ 
    =  $\text{get-rev-level } (\text{Propagated } L' D \# K) (\text{length } (\text{get-all-levels-of-marked } M)) L$ 
    using proped by auto
  then show ?case using proped by auto
qed

lemma get-level-skip-beginning-hd-get-all-levels-of-marked:
  assumes atm-of L  $\notin$  atm-of ' lits-of-l S and  $\text{get-all-levels-of-marked } S \neq []$ 
  shows  $\text{get-level } (M @ S) L = \text{get-rev-level } (\text{rev } M) (\text{hd } (\text{get-all-levels-of-marked } S)) L$ 
  using assms
proof (induction S arbitrary: M rule: marked-lit-list-induct)
  case nil
  then show ?case by (auto simp add: lits-of-def)
next
  case (marked K m)
  note notin = this(2)
  then show ?case by (auto simp add: lits-of-def)
next
  case (proped L l)
  note IH = this(1) and L = this(2) and neq = this(3)

```



```

  show ?case using IH[of M@[Propagated L l]] L neq by (auto simp add: atm-of-eq-atm-of)
qed

```

```

end

```

```

theory CDCL-W

```

```

imports CDCL-Abstract-Clause-Representation List-More CDCL-W-Level Wellfounded-More

```

```

begin

```

## 19 Weidenbach's CDCL

```

declare upt.simps(2)[simp del]

```

### 19.1 The State

We will abstract the representation of clause and clauses via two locales. We expect our representation to behave like multiset, but the internal representation can be done using list or whatever other representation.

```

locale stateW-ops =
  raw-clss mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  +
  raw-ccls-union mset-ccls union-ccls insert-ccls remove-clit
for
  — Clause
  mset-cls:: 'cls ⇒ 'v clause and
  insert-cls :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and

  — Multiset of Clauses
  mset-clss:: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and

  mset-ccls:: 'ccls ⇒ 'v clause and
  union-ccls :: 'ccls ⇒ 'ccls ⇒ 'ccls and
  insert-ccls :: 'v literal ⇒ 'ccls ⇒ 'ccls and
  remove-clit :: 'v literal ⇒ 'ccls ⇒ 'ccls
  +
fixes
  ccls-of-cls :: 'cls ⇒ 'ccls and
  cls-of-ccls :: 'ccls ⇒ 'cls and

  trail :: 'st ⇒ ('v, nat, 'v clause) marked-lits and
  hd-raw-trail :: 'st ⇒ ('v, nat, 'cls) marked-lit and
  raw-init-clss :: 'st ⇒ 'clss and
  raw-learned-clss :: 'st ⇒ 'clss and
  backtrack-lvl :: 'st ⇒ nat and
  raw-conflicting :: 'st ⇒ 'ccls option and

  cons-trail :: ('v, nat, 'cls) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and

```

```

add-init-cls :: 'cls ⇒ 'st ⇒ 'st and
add-learned-cls :: 'cls ⇒ 'st ⇒ 'st and
remove-cls :: 'cls ⇒ 'st ⇒ 'st and
update-backtrack-lvl :: nat ⇒ 'st ⇒ 'st and
update-conflicting :: 'ccls option ⇒ 'st ⇒ 'st and

init-state :: 'clss ⇒ 'st and
restart-state :: 'st ⇒ 'st
assumes
  mset-ccls-ccls-of-cls[simp]:
    mset-ccls (ccls-of-cls C) = mset-cls C and
  mset-cls-cls-of-ccls[simp]:
    mset-cls (cls-of-ccls D) = mset-ccls D and
  ex-mset-cls: ∃ a. mset-cls a = E
begin
fun mmset-of-mlit :: ('a, 'b, 'cls) marked-lit ⇒ ('a, 'b, 'v clause) marked-lit
  where
mmset-of-mlit (Propagated L C) = Propagated L (mset-cls C) |
mmset-of-mlit (Marked L i) = Marked L i

lemma lit-of-mmset-of-mlit[simp]:
  lit-of (mmset-of-mlit a) = lit-of a
by (cases a) auto

lemma lit-of-mmset-of-mlit-set-lit-of-l[simp]:
  lit-of ' mmset-of-mlit ' set M' = lits-of-l M'
by (induction M') auto

lemma map-mmset-of-mlit-true-annots-true-cls[simp]:
  map mmset-of-mlit M' ⊨as C ⟷ M' ⊨as C
by (simp add: true-annots-true-cls lits-of-def)

abbreviation init-clss ≡ λS. mset-clss (raw-init-clss S)
abbreviation learned-clss ≡ λS. mset-clss (raw-learned-clss S)
abbreviation conflicting ≡ λS. map-option mset-ccls (raw-conflicting S)

notation insert-cls (infix !++ 50)

notation in-clss (infix !∈! 50)
notation union-clss (infix ⊕ 50)
notation insert-clss (infix !++! 50)

notation union-ccls (infix !∪ 50)

definition raw-clauses :: 'st ⇒ 'clss where
raw-clauses S = union-clss (raw-init-clss S) (raw-learned-clss S)

abbreviation clauses :: 'st ⇒ 'v clauses where
clauses S ≡ mset-clss (raw-clauses S)

end

locale stateW =
  stateW-ops
  — functions for clauses:

```

*mset-cls insert-cls remove-lit*  
*mset-clss union-clss in-clss insert-clss remove-from-clss*

— functions for the conflicting clause:  
*mset-ccls union-ccls insert-ccls remove-clit*

— Conversion between conflicting and non-conflicting  
*ccls-of-cls cls-of-ccls*

— functions for the state:

— access functions:  
*trail hd-raw-trail raw-init-clss raw-learned-clss backtrack-lvl raw-conflicting*

— changing state:  
*cons-trail tl-trail add-init-cls add-learned-cls remove-cls update-backtrack-lvl*  
*update-conflicting*

— get state:

*init-state*  
*restart-state*

**for**

*mset-cls:: 'cls  $\Rightarrow$  'v clause and*  
*insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and*  
*remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and*

*mset-clss:: 'clss  $\Rightarrow$  'v clauses and*  
*union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and*  
*insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*  
*remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and*

*mset-ccls:: 'ccls  $\Rightarrow$  'v clause and*  
*union-ccls :: 'ccls  $\Rightarrow$  'ccls  $\Rightarrow$  'ccls and*  
*insert-ccls :: 'v literal  $\Rightarrow$  'ccls  $\Rightarrow$  'ccls and*  
*remove-clit :: 'v literal  $\Rightarrow$  'ccls  $\Rightarrow$  'ccls and*

*ccls-of-cls :: 'cls  $\Rightarrow$  'ccls and*  
*cls-of-ccls :: 'ccls  $\Rightarrow$  'cls and*

*trail :: 'st  $\Rightarrow$  ('v, nat, 'v clause) marked-lits and*  
*hd-raw-trail :: 'st  $\Rightarrow$  ('v, nat, 'cls) marked-lit and*  
*raw-init-clss :: 'st  $\Rightarrow$  'clss and*  
*raw-learned-clss :: 'st  $\Rightarrow$  'clss and*  
*backtrack-lvl :: 'st  $\Rightarrow$  nat and*  
*raw-conflicting :: 'st  $\Rightarrow$  'ccls option and*

*cons-trail :: ('v, nat, 'cls) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*tl-trail :: 'st  $\Rightarrow$  'st and*  
*add-init-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*add-learned-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*remove-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*update-backtrack-lvl :: nat  $\Rightarrow$  'st  $\Rightarrow$  'st and*  
*update-conflicting :: 'ccls option  $\Rightarrow$  'st  $\Rightarrow$  'st and*

*init-state :: 'clss  $\Rightarrow$  'st and*  
*restart-state :: 'st  $\Rightarrow$  'st +*

**assumes**

*hd-raw-trail*:  $\text{trail } S \neq [] \implies \text{mmset-of-mlit } (\text{hd-raw-trail } S) = \text{hd } (\text{trail } S) \text{ and}$

*trail-cons-trail*[simp]:

$\bigwedge L \text{ st. undefined-lit } (\text{trail } st) (\text{lit-of } L) \implies$

$\text{trail } (\text{cons-trail } L \text{ st}) = \text{mmset-of-mlit } L \# \text{ trail } st \text{ and}$

*trail-tl-trail*[simp]:  $\bigwedge st. \text{trail } (\text{tl-trail } st) = \text{tl } (\text{trail } st) \text{ and}$

*trail-add-init-cls*[simp]:

$\bigwedge st \ C. \text{no-dup } (\text{trail } st) \implies \text{trail } (\text{add-init-cls } C \text{ st}) = \text{trail } st \text{ and}$

*trail-add-learned-cls*[simp]:

$\bigwedge C \text{ st. no-dup } (\text{trail } st) \implies \text{trail } (\text{add-learned-cls } C \text{ st}) = \text{trail } st \text{ and}$

*trail-remove-cls*[simp]:

$\bigwedge C \text{ st. trail } (\text{remove-cls } C \text{ st}) = \text{trail } st \text{ and}$

*trail-update-backtrack-lvl*[simp]:  $\bigwedge st \ C. \text{trail } (\text{update-backtrack-lvl } C \text{ st}) = \text{trail } st \text{ and}$

*trail-update-conflicting*[simp]:  $\bigwedge C \text{ st. trail } (\text{update-conflicting } C \text{ st}) = \text{trail } st \text{ and}$

*init-clss-cons-trail*[simp]:

$\bigwedge M \text{ st. undefined-lit } (\text{trail } st) (\text{lit-of } M) \implies$

$\text{init-clss } (\text{cons-trail } M \text{ st}) = \text{init-clss } st$

**and**

*init-clss-tl-trail*[simp]:

$\bigwedge st. \text{init-clss } (\text{tl-trail } st) = \text{init-clss } st \text{ and}$

*init-clss-add-init-cls*[simp]:

$\bigwedge st \ C. \text{no-dup } (\text{trail } st) \implies \text{init-clss } (\text{add-init-cls } C \text{ st}) = \{\#mset-cls \ C\# \} + \text{init-clss } st$

**and**

*init-clss-add-learned-cls*[simp]:

$\bigwedge C \text{ st. no-dup } (\text{trail } st) \implies \text{init-clss } (\text{add-learned-cls } C \text{ st}) = \text{init-clss } st \text{ and}$

*init-clss-remove-cls*[simp]:

$\bigwedge C \text{ st. init-clss } (\text{remove-cls } C \text{ st}) = \text{removeAll-mset } (mset-cls \ C) (\text{init-clss } st) \text{ and}$

*init-clss-update-backtrack-lvl*[simp]:

$\bigwedge st \ C. \text{init-clss } (\text{update-backtrack-lvl } C \text{ st}) = \text{init-clss } st \text{ and}$

*init-clss-update-conflicting*[simp]:

$\bigwedge C \text{ st. init-clss } (\text{update-conflicting } C \text{ st}) = \text{init-clss } st \text{ and}$

*learned-clss-cons-trail*[simp]:

$\bigwedge M \text{ st. undefined-lit } (\text{trail } st) (\text{lit-of } M) \implies$

$\text{learned-clss } (\text{cons-trail } M \text{ st}) = \text{learned-clss } st \text{ and}$

*learned-clss-tl-trail*[simp]:

$\bigwedge st. \text{learned-clss } (\text{tl-trail } st) = \text{learned-clss } st \text{ and}$

*learned-clss-add-init-cls*[simp]:

$\bigwedge st \ C. \text{no-dup } (\text{trail } st) \implies \text{learned-clss } (\text{add-init-cls } C \text{ st}) = \text{learned-clss } st \text{ and}$

*learned-clss-add-learned-cls*[simp]:

$\bigwedge C \text{ st. no-dup } (\text{trail } st) \implies$

$\text{learned-clss } (\text{add-learned-cls } C \text{ st}) = \{\#mset-cls \ C\# \} + \text{learned-clss } st \text{ and}$

*learned-clss-remove-cls*[simp]:

$\bigwedge C \text{ st. learned-clss } (\text{remove-cls } C \text{ st}) = \text{removeAll-mset } (mset-cls \ C) (\text{learned-clss } st) \text{ and}$

*learned-clss-update-backtrack-lvl*[simp]:

$\bigwedge st \ C. \text{learned-clss } (\text{update-backtrack-lvl } C \text{ st}) = \text{learned-clss } st \text{ and}$

*learned-clss-update-conflicting*[simp]:

$\bigwedge C \text{ st. learned-clss } (\text{update-conflicting } C \text{ st}) = \text{learned-clss } st \text{ and}$

*backtrack-lvl-cons-trail*[simp]:

$\bigwedge M \text{ st. undefined-lit } (\text{trail } st) (\text{lit-of } M) \implies$

$\text{backtrack-lvl } (\text{cons-trail } M \text{ st}) = \text{backtrack-lvl } st \text{ and}$

*backtrack-lvl-tl-trail*[simp]:

$\bigwedge st. \text{backtrack-lvl } (\text{tl-trail } st) = \text{backtrack-lvl } st \text{ and}$

*backtrack-lvl-add-init-cls*[simp]:

$\bigwedge st\ C. no\_dup\ (trail\ st) \implies backtrack\_lvl\ (add\_init\_cls\ C\ st) = backtrack\_lvl\ st$  **and**  
*backtrack-lvl-add-learned-cls*[simp]:

$\bigwedge C\ st. no\_dup\ (trail\ st) \implies backtrack\_lvl\ (add\_learned\_cls\ C\ st) = backtrack\_lvl\ st$  **and**  
*backtrack-lvl-remove-cls*[simp]:

$\bigwedge C\ st. backtrack\_lvl\ (remove\_cls\ C\ st) = backtrack\_lvl\ st$  **and**  
*backtrack-lvl-update-backtrack-lvl*[simp]:

$\bigwedge st\ k. backtrack\_lvl\ (update\_backtrack\_lvl\ k\ st) = k$  **and**  
*backtrack-lvl-update-conflicting*[simp]:

$\bigwedge C\ st. backtrack\_lvl\ (update\_conflicting\ C\ st) = backtrack\_lvl\ st$  **and**

*conflicting-cons-trail*[simp]:

$\bigwedge M\ st. undefined\_lit\ (trail\ st)\ (lit\_of\ M) \implies$   
 $conflicting\ (cons\_trail\ M\ st) = conflicting\ st$  **and**

*conflicting-tl-trail*[simp]:

$\bigwedge st. conflicting\ (tl\_trail\ st) = conflicting\ st$  **and**

*conflicting-add-init-cls*[simp]:

$\bigwedge st\ C. no\_dup\ (trail\ st) \implies conflicting\ (add\_init\_cls\ C\ st) = conflicting\ st$  **and**  
*conflicting-add-learned-cls*[simp]:

$\bigwedge C\ st. no\_dup\ (trail\ st) \implies conflicting\ (add\_learned\_cls\ C\ st) = conflicting\ st$   
**and**

*conflicting-remove-cls*[simp]:

$\bigwedge C\ st. conflicting\ (remove\_cls\ C\ st) = conflicting\ st$  **and**

*conflicting-update-backtrack-lvl*[simp]:

$\bigwedge st\ C. conflicting\ (update\_backtrack\_lvl\ C\ st) = conflicting\ st$  **and**

*conflicting-update-conflicting*[simp]:

$\bigwedge C\ st. raw\_conflicting\ (update\_conflicting\ C\ st) = C$  **and**

*init-state-trail*[simp]:  $\bigwedge N. trail\ (init\_state\ N) = []$  **and**

*init-state-clss*[simp]:  $\bigwedge N. (init\_clss\ (init\_state\ N)) = mset\_clss\ N$  **and**

*init-state-learned-clss*[simp]:  $\bigwedge N. learned\_clss\ (init\_state\ N) = \{\#\}$  **and**

*init-state-backtrack-lvl*[simp]:  $\bigwedge N. backtrack\_lvl\ (init\_state\ N) = 0$  **and**

*init-state-conflicting*[simp]:  $\bigwedge N. conflicting\ (init\_state\ N) = None$  **and**

*trail-restart-state*[simp]:  $trail\ (restart\_state\ S) = []$  **and**

*init-clss-restart-state*[simp]:  $init\_clss\ (restart\_state\ S) = init\_clss\ S$  **and**

*learned-clss-restart-state*[intro]:

$learned\_clss\ (restart\_state\ S) \subseteq\# learned\_clss\ S$  **and**

*backtrack-lvl-restart-state*[simp]:  $backtrack\_lvl\ (restart\_state\ S) = 0$  **and**

*conflicting-restart-state*[simp]:  $conflicting\ (restart\_state\ S) = None$

**begin**

**lemma**

**shows**

*clauses-cons-trail*[simp]:

$undefined\_lit\ (trail\ S)\ (lit\_of\ M) \implies clauses\ (cons\_trail\ M\ S) = clauses\ S$  **and**

*clss-tl-trail*[simp]:  $clauses\ (tl\_trail\ S) = clauses\ S$  **and**

*clauses-add-learned-cls-unfolded*:

$no\_dup\ (trail\ S) \implies clauses\ (add\_learned\_cls\ U\ S) =$   
 $\{\#mset\_cls\ U\#\} + learned\_clss\ S + init\_clss\ S$

**and**

*clauses-add-init-cls*[simp]:

$no\_dup\ (trail\ S) \implies$

$clauses\ (add\_init\_cls\ N\ S) = \{\#mset\_cls\ N\#\} + init\_clss\ S + learned\_clss\ S$  **and**

*clauses-update-backtrack-lvl*[simp]: *clauses* (*update-backtrack-lvl* *k* *S*) = *clauses* *S* **and**  
*clauses-update-conflicting*[simp]: *clauses* (*update-conflicting* *D* *S*) = *clauses* *S* **and**  
*clauses-remove-cls*[simp]:  
*clauses* (*remove-cls* *C* *S*) = *removeAll-mset* (*mset-cls* *C*) (*clauses* *S*) **and**  
*clauses-add-learned-cls*[simp]:  
*no-dup* (*trail* *S*)  $\implies$  *clauses* (*add-learned-cls* *C* *S*) = {#*mset-cls* *C* #} + *clauses* *S* **and**  
*clauses-restart*[simp]: *clauses* (*restart-state* *S*)  $\subseteq$  # *clauses* *S* **and**  
*clauses-init-state*[simp]:  $\bigwedge N.$  *clauses* (*init-state* *N*) = *mset-clss* *N*  
**prefer 9 using** *raw-clauses-def* *learned-clss-restart-state* **apply** *fastforce*  
**by** (*auto simp: ac-simps replicate-mset-plus raw-clauses-def intro: multiset-eqI*)

**abbreviation** *state* :: '*st*  $\Rightarrow$  ('*v*, *nat*, '*v* clause) marked-lit list  $\times$  '*v* clauses  $\times$  '*v* clauses  
 $\times$  *nat*  $\times$  '*v* clause option **where**  
*state* *S*  $\equiv$  (*trail* *S*, *init-clss* *S*, *learned-clss* *S*, *backtrack-lvl* *S*, *conflicting* *S*)

**abbreviation** *incr-lvl* :: '*st*  $\Rightarrow$  '*st* **where**  
*incr-lvl* *S*  $\equiv$  *update-backtrack-lvl* (*backtrack-lvl* *S* + 1) *S*

**definition** *state-eq* :: '*st*  $\Rightarrow$  '*st*  $\Rightarrow$  *bool* (**infix**  $\sim$  50) **where**  
*S*  $\sim$  *T*  $\longleftrightarrow$  *state* *S* = *state* *T*

**lemma** *state-eq-ref*[*simp*, *intro*]:  
*S*  $\sim$  *S*  
**unfolding** *state-eq-def* **by** *auto*

**lemma** *state-eq-sym*:  
*S*  $\sim$  *T*  $\longleftrightarrow$  *T*  $\sim$  *S*  
**unfolding** *state-eq-def* **by** *auto*

**lemma** *state-eq-trans*:  
*S*  $\sim$  *T*  $\implies$  *T*  $\sim$  *U*  $\implies$  *S*  $\sim$  *U*  
**unfolding** *state-eq-def* **by** *auto*

**lemma**  
**shows**  
*state-eq-trail*: *S*  $\sim$  *T*  $\implies$  *trail* *S* = *trail* *T* **and**  
*state-eq-init-clss*: *S*  $\sim$  *T*  $\implies$  *init-clss* *S* = *init-clss* *T* **and**  
*state-eq-learned-clss*: *S*  $\sim$  *T*  $\implies$  *learned-clss* *S* = *learned-clss* *T* **and**  
*state-eq-backtrack-lvl*: *S*  $\sim$  *T*  $\implies$  *backtrack-lvl* *S* = *backtrack-lvl* *T* **and**  
*state-eq-conflicting*: *S*  $\sim$  *T*  $\implies$  *conflicting* *S* = *conflicting* *T* **and**  
*state-eq-clauses*: *S*  $\sim$  *T*  $\implies$  *clauses* *S* = *clauses* *T* **and**  
*state-eq-undefined-lit*: *S*  $\sim$  *T*  $\implies$  *undefined-lit* (*trail* *S*) *L* = *undefined-lit* (*trail* *T*) *L*  
**unfolding** *state-eq-def* *raw-clauses-def* **by** *auto*

**lemma** *state-eq-raw-conflicting-None*:  
*S*  $\sim$  *T*  $\implies$  *conflicting* *T* = *None*  $\implies$  *raw-conflicting* *S* = *None*  
**unfolding** *state-eq-def* *raw-clauses-def* **by** *auto*

**lemmas** *state-simp*[*simp*] = *state-eq-trail* *state-eq-init-clss* *state-eq-learned-clss*  
*state-eq-backtrack-lvl* *state-eq-conflicting* *state-eq-clauses* *state-eq-undefined-lit*  
*state-eq-raw-conflicting-None*

**lemma** *atms-of-ms-learned-clss-restart-state-in-atms-of-ms-learned-clssI*[*intro*]:  
 $x \in \text{atms-of-mm} (\text{learned-clss} (\text{restart-state } S)) \implies x \in \text{atms-of-mm} (\text{learned-clss } S)$   
**by** (*meson atms-of-ms-mono learned-clss-restart-state set-mset-mono subsetCE*)

**function** *reduce-trail-to* :: 'a list  $\Rightarrow$  'st  $\Rightarrow$  'st **where**  
*reduce-trail-to* *F S* =  
 (if *length* (*trail S*) = *length F*  $\vee$  *trail S* = [] then *S* else *reduce-trail-to F (tl-trail S)*)  
**by** *fast+*  
**termination**  
**by** (*relation measure* ( $\lambda(-, S). \text{length } (\text{trail } S)$ )) *simp-all*

**declare** *reduce-trail-to.simps*[*simp del*]

**lemma**  
**shows**  
*reduce-trail-to-nil*[*simp*]: *trail S* = []  $\implies$  *reduce-trail-to F S* = *S* **and**  
*reduce-trail-to-eq-length*[*simp*]: *length* (*trail S*) = *length F*  $\implies$  *reduce-trail-to F S* = *S*  
**by** (*auto simp: reduce-trail-to.simps*)

**lemma** *reduce-trail-to-length-ne*:  
*length* (*trail S*)  $\neq$  *length F*  $\implies$  *trail S*  $\neq$  []  $\implies$   
*reduce-trail-to F S* = *reduce-trail-to F (tl-trail S)*  
**by** (*auto simp: reduce-trail-to.simps*)

**lemma** *trail-reduce-trail-to-length-le*:  
**assumes** *length F* > *length* (*trail S*)  
**shows** *trail* (*reduce-trail-to F S*) = []  
**using** *assms* **apply** (*induction F S* rule: *reduce-trail-to.induct*)  
**by** (*metis* (*no-types*, *hide-lams*) *length-tl less-imp-diff-less less-irrefl trail-tl-trail*  
*reduce-trail-to.simps*)

**lemma** *trail-reduce-trail-to-nil*[*simp*]:  
*trail* (*reduce-trail-to* [] *S*) = []  
**apply** (*induction* []::('v, nat, 'v clause) *marked-lits S* rule: *reduce-trail-to.induct*)  
**by** (*metis* *length-0-conv reduce-trail-to-length-ne reduce-trail-to-nil*)

**lemma** *clauses-reduce-trail-to-nil*:  
*clauses* (*reduce-trail-to* [] *S*) = *clauses S*  
**proof** (*induction* [] *S* rule: *reduce-trail-to.induct*)  
**case** (1 *Sa*)  
**then have** *clauses* (*reduce-trail-to* ([]::'a list) (*tl-trail Sa*)) = *clauses* (*tl-trail Sa*)  
 $\vee$  *trail Sa* = []  
**by** *fastforce*  
**then show** *clauses* (*reduce-trail-to* ([]::'a list) *Sa*) = *clauses Sa*  
**by** (*metis* (*no-types*) *length-0-conv reduce-trail-to-eq-length clss-tl-trail*  
*reduce-trail-to-length-ne*)  
**qed**

**lemma** *reduce-trail-to-skip-beginning*:  
**assumes** *trail S* = *F' @ F*  
**shows** *trail* (*reduce-trail-to F S*) = *F*  
**using** *assms* **by** (*induction F'* arbitrary: *S*) (*auto simp: reduce-trail-to-length-ne*)

**lemma** *clauses-reduce-trail-to*[*simp*]:  
*clauses* (*reduce-trail-to F S*) = *clauses S*  
**apply** (*induction F S* rule: *reduce-trail-to.induct*)  
**by** (*metis* *clss-tl-trail reduce-trail-to.simps*)

**lemma** *conflicting-update-trail*[simp]:  
*conflicting* (reduce-trail-to  $F$   $S$ ) = *conflicting*  $S$   
**apply** (induction  $F$   $S$  rule: reduce-trail-to.induct)  
**by** (metis *conflicting-tl-trail* reduce-trail-to.simps)

**lemma** *backtrack-lvl-update-trail*[simp]:  
*backtrack-lvl* (reduce-trail-to  $F$   $S$ ) = *backtrack-lvl*  $S$   
**apply** (induction  $F$   $S$  rule: reduce-trail-to.induct)  
**by** (metis *backtrack-lvl-tl-trail* reduce-trail-to.simps)

**lemma** *init-clss-update-trail*[simp]:  
*init-clss* (reduce-trail-to  $F$   $S$ ) = *init-clss*  $S$   
**apply** (induction  $F$   $S$  rule: reduce-trail-to.induct)  
**by** (metis *init-clss-tl-trail* reduce-trail-to.simps)

**lemma** *learned-clss-update-trail*[simp]:  
*learned-clss* (reduce-trail-to  $F$   $S$ ) = *learned-clss*  $S$   
**apply** (induction  $F$   $S$  rule: reduce-trail-to.induct)  
**by** (metis *learned-clss-tl-trail* reduce-trail-to.simps)

**lemma** *raw-conflicting-reduce-trail-to*[simp]:  
*raw-conflicting* (reduce-trail-to  $F$   $S$ ) = None  $\longleftrightarrow$  *raw-conflicting*  $S$  = None  
**apply** (induction  $F$   $S$  rule: reduce-trail-to.induct)  
**by** (metis *conflicting-update-trail* map-option-is-None)

**lemma** *trail-eq-reduce-trail-to-eq*:  
*trail*  $S$  = *trail*  $T$   $\implies$  *trail* (reduce-trail-to  $F$   $S$ ) = *trail* (reduce-trail-to  $F$   $T$ )  
**apply** (induction  $F$   $S$  arbitrary:  $T$  rule: reduce-trail-to.induct)  
**by** (metis *trail-tl-trail* reduce-trail-to.simps)

**lemma** *reduce-trail-to-state-eq<sub>NOT</sub>-compatible*:  
**assumes**  $ST$ :  $S \sim T$   
**shows** reduce-trail-to  $F$   $S \sim$  reduce-trail-to  $F$   $T$   
**proof** –  
**have** *trail* (reduce-trail-to  $F$   $S$ ) = *trail* (reduce-trail-to  $F$   $T$ )  
**using** *trail-eq-reduce-trail-to-eq*[of  $S$   $T$   $F$ ]  $ST$  **by** auto  
**then show** ?thesis **using**  $ST$  **by** (auto simp del: state-simp simp: state-eq-def)  
**qed**

**lemma** *reduce-trail-to-trail-tl-trail-decomp*[simp]:  
*trail*  $S$  =  $F' @ \text{Marked } K \ d \ \# \ F \implies$  (*trail* (reduce-trail-to  $F$   $S$ )) =  $F$   
**apply** (rule reduce-trail-to-skip-beginning[of -  $F' @ \text{Marked } K \ d \ \# \ []$ ])  
**by** (cases  $F'$ ) (auto simp add:tl-append reduce-trail-to-skip-beginning)

**lemma** *reduce-trail-to-add-learned-cls*[simp]:  
*no-dup* (*trail*  $S$ )  $\implies$   
*trail* (reduce-trail-to  $F$  (add-learned-cls  $C$   $S$ )) = *trail* (reduce-trail-to  $F$   $S$ )  
**by** (rule *trail-eq-reduce-trail-to-eq*) auto

**lemma** *reduce-trail-to-add-init-cls*[simp]:  
*no-dup* (*trail*  $S$ )  $\implies$   
*trail* (reduce-trail-to  $F$  (add-init-cls  $C$   $S$ )) = *trail* (reduce-trail-to  $F$   $S$ )  
**by** (rule *trail-eq-reduce-trail-to-eq*) auto



**lemma** *reduce-trail-to-remove-learned-cls*[simp]:  
 trail (reduce-trail-to F (remove-cls C S)) = trail (reduce-trail-to F S)  
 by (rule trail-eq-reduce-trail-to-eq) auto

**lemma** *reduce-trail-to-update-conflicting*[simp]:  
 trail (reduce-trail-to F (update-conflicting C S)) = trail (reduce-trail-to F S)  
 by (rule trail-eq-reduce-trail-to-eq) auto

**lemma** *reduce-trail-to-update-backtrack-lvl*[simp]:  
 trail (reduce-trail-to F (update-backtrack-lvl C S)) = trail (reduce-trail-to F S)  
 by (rule trail-eq-reduce-trail-to-eq) auto

**lemma** *in-get-all-marked-decomposition-marked-or-empty*:  
 assumes  $(a, b) \in \text{set } (\text{get-all-marked-decomposition } M)$   
 shows  $a = [] \vee (\text{is-marked } (\text{hd } a))$   
 using *assms*  
**proof** (induct M arbitrary: a b)  
 case Nil then show ?case by simp  
**next**  
 case (Cons m M)  
 show ?case  
**proof** (cases m)  
 case (Marked l mark)  
 then show ?thesis using Cons by auto  
**next**  
 case (Propagated l mark)  
 then show ?thesis using Cons by (cases get-all-marked-decomposition M) force+  
**qed**  
**qed**

**lemma** *reduce-trail-to-length*:  
 $\text{length } M = \text{length } M' \implies \text{reduce-trail-to } M S = \text{reduce-trail-to } M' S$   
**apply** (induction M S arbitrary: rule: reduce-trail-to.induct)  
**by** (simp add: reduce-trail-to.simps)

**lemma** *trail-reduce-trail-to-drop*:  
 trail (reduce-trail-to F S) =  
 (if  $\text{length } (\text{trail } S) \geq \text{length } F$   
 then  $\text{drop } (\text{length } (\text{trail } S) - \text{length } F) (\text{trail } S)$   
 else [])  
**apply** (induction F S rule: reduce-trail-to.induct)  
**apply** (rename-tac F S, case-tac trail S)  
**apply** auto[]  
**apply** (rename-tac list, case-tac Suc ( $\text{length list} > \text{length } F$ ))  
**prefer** 2 **apply** (metis diff-is-0-eq drop-Cons' length-Cons nat-le-linear nat-less-le  
 reduce-trail-to-eq-length trail-reduce-trail-to-length-le)  
**apply** (subgoal-tac Suc ( $\text{length list} - \text{length } F = \text{Suc } (\text{length list} - \text{length } F)$ ))  
**by** (auto simp add: reduce-trail-to-length-ne)

**lemma** *in-get-all-marked-decomposition-trail-update-trail*[simp]:  
 assumes  $H: (L \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$   
 shows  $\text{trail } (\text{reduce-trail-to } M1 S) = M1$   
**proof** –  
 obtain K mark where  
 L:  $L = \text{Marked } K \text{ mark}$

```

    using H by (cases L) (auto dest!: in-get-all-marked-decomposition-marked-or-empty)
  obtain c where
    tr-S: trail S = c @ M2 @ L # M1
    using H by auto
  show ?thesis
    by (rule reduce-trail-to-trail-tl-trail-decomp[of - c @ M2 K mark])
    (auto simp: tr-S L)
qed

```

```

lemma raw-conflicting-cons-trail[simp]:
  assumes undefined-lit (trail S) (lit-of L)
  shows
    raw-conflicting (cons-trail L S) = None  $\longleftrightarrow$  raw-conflicting S = None
  using assms conflicting-cons-trail[of S L] map-option-is-None by fastforce+

```

```

lemma raw-conflicting-add-init-cls[simp]:
  no-dup (trail S)  $\implies$ 
    raw-conflicting (add-init-cls C S) = None  $\longleftrightarrow$  raw-conflicting S = None
  using map-option-is-None conflicting-add-init-cls[of S C] by fastforce+

```

```

lemma raw-conflicting-add-learned-cls[simp]:
  no-dup (trail S)  $\implies$ 
    raw-conflicting (add-learned-cls C S) = None  $\longleftrightarrow$  raw-conflicting S = None
  using map-option-is-None conflicting-add-learned-cls[of S C] by fastforce+

```

```

lemma raw-conflicting-update-backtrack-lvl[simp]:
  raw-conflicting (update-backtrack-lvl k S) = None  $\longleftrightarrow$  raw-conflicting S = None
  using map-option-is-None conflicting-update-backtrack-lvl[of k S] by fastforce+

```

**end** — end of *state<sub>W</sub>* locale

## 19.2 CDCL Rules

Because of the strategy we will later use, we distinguish propagate, conflict from the other rules

```

locale conflict-driven-clause-learningW =
  stateW
  — functions for clauses:
  mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss

  — functions for the conflicting clause:
  mset-ccls union-ccls insert-ccls remove-clit

  — conversion
  ccls-of-cls cls-of-ccls

  — functions for the state:
  — access functions:
  trail hd-raw-trail raw-init-clss raw-learned-clss backtrack-lvl raw-conflicting
  — changing state:
  cons-trail tl-trail add-init-cls add-learned-cls remove-cls update-backtrack-lvl
  update-conflicting

  — get state:
  init-state

```

```

  restart-state
for
  mset-cls:: 'cls  $\Rightarrow$  'v clause and
  insert-cls :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and
  remove-lit :: 'v literal  $\Rightarrow$  'cls  $\Rightarrow$  'cls and

  mset-clss:: 'clss  $\Rightarrow$  'v clauses and
  union-clss :: 'clss  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  in-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  bool and
  insert-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and
  remove-from-clss :: 'cls  $\Rightarrow$  'clss  $\Rightarrow$  'clss and

  mset-ccls:: 'ccls  $\Rightarrow$  'v clause and
  union-ccls :: 'ccls  $\Rightarrow$  'ccls  $\Rightarrow$  'ccls and
  insert-ccls :: 'v literal  $\Rightarrow$  'ccls  $\Rightarrow$  'ccls and
  remove-clit :: 'v literal  $\Rightarrow$  'ccls  $\Rightarrow$  'ccls and

  ccls-of-cls :: 'cls  $\Rightarrow$  'ccls and
  cls-of-ccls :: 'ccls  $\Rightarrow$  'cls and

  trail :: 'st  $\Rightarrow$  ('v, nat, 'v clause) marked-lits and
  hd-raw-trail :: 'st  $\Rightarrow$  ('v, nat, 'cls) marked-lit and
  raw-init-clss :: 'st  $\Rightarrow$  'clss and
  raw-learned-clss :: 'st  $\Rightarrow$  'clss and
  backtrack-lvl :: 'st  $\Rightarrow$  nat and
  raw-conflicting :: 'st  $\Rightarrow$  'ccls option and

  cons-trail :: ('v, nat, 'cls) marked-lit  $\Rightarrow$  'st  $\Rightarrow$  'st and
  tl-trail :: 'st  $\Rightarrow$  'st and
  add-init-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  add-learned-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  remove-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
  update-backtrack-lvl :: nat  $\Rightarrow$  'st  $\Rightarrow$  'st and
  update-conflicting :: 'ccls option  $\Rightarrow$  'st  $\Rightarrow$  'st and

  init-state :: 'clss  $\Rightarrow$  'st and
  restart-state :: 'st  $\Rightarrow$  'st
begin

inductive propagate :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool for S :: 'st where
propagate-rule: conflicting S = None  $\Rightarrow$ 
  E ! $\in$ ! raw-clauses S  $\Rightarrow$ 
  L  $\in$  # mset-cls E  $\Rightarrow$ 
  trail S  $\models_{as}$  CNot (mset-cls (remove-lit L E))  $\Rightarrow$ 
  undefined-lit (trail S) L  $\Rightarrow$ 
  T  $\sim$  cons-trail (Propagated L E) S  $\Rightarrow$ 
  propagate S T

inductive-cases propagateE: propagate S T

inductive conflict :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool for S :: 'st where
conflict-rule:
  conflicting S = None  $\Rightarrow$ 
  D ! $\in$ ! raw-clauses S  $\Rightarrow$ 
  trail S  $\models_{as}$  CNot (mset-cls D)  $\Rightarrow$ 

```

$T \sim \text{update-conflicting } (\text{Some } (\text{ccls-of-cls } D)) \ S \implies$   
 $\text{conflict } S \ T$

**inductive-cases** *conflictE*: *conflict* *S* *T*

**inductive** *backtrack* :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool **for** *S* :: 'st **where**

*backtrack-rule*:

$\text{raw-conflicting } S = \text{Some } D \implies$   
 $L \in \# \text{ mset-ccls } D \implies$   
 $(\text{Marked } K \ (i+1) \ \# \ M1, \ M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S)) \implies$   
 $\text{get-level } (\text{trail } S) \ L = \text{backtrack-lvl } S \implies$   
 $\text{get-level } (\text{trail } S) \ L = \text{get-maximum-level } (\text{trail } S) \ (\text{mset-ccls } D) \implies$   
 $\text{get-maximum-level } (\text{trail } S) \ (\text{mset-ccls } (\text{remove-clit } L \ D)) \equiv i \implies$   
 $T \sim \text{cons-trail } (\text{Propagated } L \ (\text{cls-of-ccls } D))$   
 $\quad (\text{reduce-trail-to } M1$   
 $\quad \quad (\text{add-learned-cls } (\text{cls-of-ccls } D)$   
 $\quad \quad \quad (\text{update-backtrack-lvl } i$   
 $\quad \quad \quad \quad (\text{update-conflicting } \text{None } S)))) \implies$   
 $\text{backtrack } S \ T$

**inductive-cases** *backtrackE*: *backtrack* *S* *T*

**thm** *backtrackE*

**inductive** *decide* :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool **for** *S* :: 'st **where**

*decide-rule*:

$\text{conflicting } S = \text{None} \implies$   
 $\text{undefined-lit } (\text{trail } S) \ L \implies$   
 $\text{atm-of } L \in \text{atms-of-mm } (\text{init-clss } S) \implies$   
 $T \sim \text{cons-trail } (\text{Marked } L \ (\text{backtrack-lvl } S + 1)) \ (\text{incr-lvl } S) \implies$   
 $\text{decide } S \ T$

**inductive-cases** *decideE*: *decide* *S* *T*

**inductive** *skip* :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool **for** *S* :: 'st **where**

*skip-rule*:

$\text{trail } S = \text{Propagated } L \ C' \ \# \ M \implies$   
 $\text{raw-conflicting } S = \text{Some } E \implies$   
 $-L \notin \# \text{ mset-ccls } E \implies$   
 $\text{mset-ccls } E \neq \{\#\} \implies$   
 $T \sim \text{tl-trail } S \implies$   
 $\text{skip } S \ T$

**inductive-cases** *skipE*: *skip* *S* *T*

$\text{get-maximum-level } (\text{Propagated } L \ (C + \{\#L\# \}) \ \# \ M) \ D = k \vee k = 0$  (that was in a previous version of the book) is equivalent to  $\text{get-maximum-level } (\text{Propagated } L \ (C + \{\#L\# \}) \ \# \ M) \ D = k$ , when the structural invariants holds.

**inductive** *resolve* :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool **for** *S* :: 'st **where**

*resolve-rule*:  $\text{trail } S \neq [] \implies$

$\text{hd-raw-trail } S = \text{Propagated } L \ E \implies$   
 $L \in \# \text{ mset-cls } E \implies$   
 $\text{raw-conflicting } S = \text{Some } D' \implies$   
 $-L \in \# \text{ mset-ccls } D' \implies$   
 $\text{get-maximum-level } (\text{trail } S) \ (\text{mset-ccls } (\text{remove-clit } (-L) \ D')) = \text{backtrack-lvl } S \implies$   
 $T \sim \text{update-conflicting } (\text{Some } (\text{union-ccls } (\text{remove-clit } (-L) \ D') \ (\text{ccls-of-cls } (\text{remove-lit } L \ E))))$

$(tl\text{-}trail\ S) \Rightarrow$   
 $resolve\ S\ T$

**inductive-cases**  $resolveE$ :  $resolve\ S\ T$

**inductive**  $restart :: 'st \Rightarrow 'st \Rightarrow bool$  **for**  $S :: 'st$  **where**  
 $restart$ :  $state\ S = (M, N, U, k, None) \Rightarrow \neg M \models_{asm} clauses\ S$   
 $\Rightarrow T \sim restart\text{-}state\ S$   
 $\Rightarrow restart\ S\ T$

**inductive-cases**  $restartE$ :  $restart\ S\ T$

We add the condition  $C \notin \# init\text{-}clss\ S$ , to maintain consistency even without the strategy.

**inductive**  $forget :: 'st \Rightarrow 'st \Rightarrow bool$  **where**

$forget$ -rule:

$conflicting\ S = None \Rightarrow$   
 $C \in ! raw\text{-}learned\text{-}clss\ S \Rightarrow$   
 $\neg(trail\ S) \models_{asm} clauses\ S \Rightarrow$   
 $mset\text{-}cls\ C \notin set\ (get\text{-}all\text{-}mark\text{-}of\text{-}propagated\ (trail\ S)) \Rightarrow$   
 $mset\text{-}cls\ C \notin \# init\text{-}clss\ S \Rightarrow$   
 $T \sim remove\text{-}cls\ C\ S \Rightarrow$   
 $forget\ S\ T$

**inductive-cases**  $forgetE$ :  $forget\ S\ T$

**inductive**  $cdcl_W\text{-}rf :: 'st \Rightarrow 'st \Rightarrow bool$  **for**  $S :: 'st$  **where**

$restart$ :  $restart\ S\ T \Rightarrow cdcl_W\text{-}rf\ S\ T \mid$   
 $forget$ :  $forget\ S\ T \Rightarrow cdcl_W\text{-}rf\ S\ T$

**inductive**  $cdcl_W\text{-}bj :: 'st \Rightarrow 'st \Rightarrow bool$  **where**

$skip$ :  $skip\ S\ S' \Rightarrow cdcl_W\text{-}bj\ S\ S' \mid$   
 $resolve$ :  $resolve\ S\ S' \Rightarrow cdcl_W\text{-}bj\ S\ S' \mid$   
 $backtrack$ :  $backtrack\ S\ S' \Rightarrow cdcl_W\text{-}bj\ S\ S'$

**inductive-cases**  $cdcl_W\text{-}bjE$ :  $cdcl_W\text{-}bj\ S\ T$

**inductive**  $cdcl_W\text{-}o :: 'st \Rightarrow 'st \Rightarrow bool$  **for**  $S :: 'st$  **where**

$decide$ :  $decide\ S\ S' \Rightarrow cdcl_W\text{-}o\ S\ S' \mid$   
 $bj$ :  $cdcl_W\text{-}bj\ S\ S' \Rightarrow cdcl_W\text{-}o\ S\ S'$

**inductive**  $cdcl_W :: 'st \Rightarrow 'st \Rightarrow bool$  **for**  $S :: 'st$  **where**

$propagate$ :  $propagate\ S\ S' \Rightarrow cdcl_W\ S\ S' \mid$   
 $conflict$ :  $conflict\ S\ S' \Rightarrow cdcl_W\ S\ S' \mid$   
 $other$ :  $cdcl_W\text{-}o\ S\ S' \Rightarrow cdcl_W\ S\ S' \mid$   
 $rf$ :  $cdcl_W\text{-}rf\ S\ S' \Rightarrow cdcl_W\ S\ S'$

**lemma**  $rtranclp\text{-}propagate\text{-}is\text{-}rtranclp\text{-}cdcl_W$ :

$propagate^{**}\ S\ S' \Rightarrow cdcl_W^{**}\ S\ S'$   
**apply** (induction rule:  $rtranclp\text{-}induct$ )  
**apply**  $simp$   
**apply** (frule  $propagate$ )  
**using**  $rtranclp\text{-}trans[of\ cdcl_W]$  **by**  $blast$

**lemma**  $cdcl_W\text{-}all\text{-}rules\text{-}induct[consumes\ 1, case\text{-}names\ propagate\ conflict\ forget\ restart\ decide\ skip\ resolve\ backtrack]$ :

```

fixes  $S :: 'st$ 
assumes
   $cdcl_W: cdcl_W\ S\ S' \text{ and}$ 
   $propagate: \bigwedge T. propagate\ S\ T \implies P\ S\ T \text{ and}$ 
   $conflict: \bigwedge T. conflict\ S\ T \implies P\ S\ T \text{ and}$ 
   $forget: \bigwedge T. forget\ S\ T \implies P\ S\ T \text{ and}$ 
   $restart: \bigwedge T. restart\ S\ T \implies P\ S\ T \text{ and}$ 
   $decide: \bigwedge T. decide\ S\ T \implies P\ S\ T \text{ and}$ 
   $skip: \bigwedge T. skip\ S\ T \implies P\ S\ T \text{ and}$ 
   $resolve: \bigwedge T. resolve\ S\ T \implies P\ S\ T \text{ and}$ 
   $backtrack: \bigwedge T. backtrack\ S\ T \implies P\ S\ T$ 
shows  $P\ S\ S'$ 
using  $assms(1)$ 
proof ( $induct\ S'$  rule:  $cdcl_W.induct$ )
  case ( $propagate\ S'$ ) note  $propagate = this(1)$ 
  then show  $?case$  using  $assms(2)$  by  $auto$ 
next
  case ( $conflict\ S'$ )
  then show  $?case$  using  $assms(3)$  by  $auto$ 
next
  case ( $other\ S'$ )
  then show  $?case$ 
  proof ( $induct\ rule: cdcl_W-o.induct$ )
    case ( $decide\ U$ )
    then show  $?case$  using  $assms(6)$  by  $auto$ 
  next
    case ( $bj\ S'$ )
    then show  $?case$  using  $assms(7-9)$  by ( $induction\ rule: cdcl_W-bj.induct$ )  $auto$ 
  qed
next
  case ( $rf\ S'$ )
  then show  $?case$ 
  by ( $induct\ rule: cdcl_W-rf.induct$ ) ( $fast\ dest: forget\ restart$ ) $+$ 
qed

lemma  $cdcl_W-all-induct[consumes\ 1, case-names\ propagate\ conflict\ forget\ restart\ decide\ skip$ 
   $resolve\ backtrack]:$ 
fixes  $S :: 'st$ 
assumes
   $cdcl_W: cdcl_W\ S\ S' \text{ and}$ 
   $propagateH: \bigwedge C\ L\ T. conflicting\ S = None \implies$ 
     $C !\in! raw-clauses\ S \implies$ 
     $L \in \# mset-cls\ C \implies$ 
     $trail\ S \models_{as} CNot\ (remove1-mset\ L\ (mset-cls\ C)) \implies$ 
     $undefined-lit\ (trail\ S)\ L \implies$ 
     $T \sim cons-trail\ (Propagated\ L\ C)\ S \implies$ 
     $P\ S\ T \text{ and}$ 
   $conflictH: \bigwedge D\ T. conflicting\ S = None \implies$ 
     $D !\in! raw-clauses\ S \implies$ 
     $trail\ S \models_{as} CNot\ (mset-cls\ D) \implies$ 
     $T \sim update-conflicting\ (Some\ (ccls-of-cls\ D))\ S \implies$ 
     $P\ S\ T \text{ and}$ 
   $forgetH: \bigwedge C\ U\ T. conflicting\ S = None \implies$ 
     $C !\in! raw-learned-clss\ S \implies$ 
     $\neg(trail\ S) \models_{asm}\ clauses\ S \implies$ 

```

$mset-cls\ C \notin set\ (get-all-mark-of-propagated\ (trail\ S)) \implies$   
 $mset-cls\ C \notin \# init-clss\ S \implies$   
 $T \sim remove-cls\ C\ S \implies$   
**P S T and**  
*restartH*:  $\bigwedge T. \neg trail\ S \models_{asm} clauses\ S \implies$   
 $conflicting\ S = None \implies$   
 $T \sim restart-state\ S \implies$   
**P S T and**  
*decideH*:  $\bigwedge L\ T. conflicting\ S = None \implies$   
 $undefined-lit\ (trail\ S)\ L \implies$   
 $atm-of\ L \in atms-of-mm\ (init-clss\ S) \implies$   
 $T \sim cons-trail\ (Marked\ L\ (backtrack-lvl\ S + 1))\ (incr-lvl\ S) \implies$   
**P S T and**  
*skipH*:  $\bigwedge L\ C'\ M\ E\ T.$   
 $trail\ S = Propagated\ L\ C'\ \# M \implies$   
 $raw-conflicting\ S = Some\ E \implies$   
 $-L \notin \# mset-ccls\ E \implies mset-ccls\ E \neq \{\#\} \implies$   
 $T \sim tl-trail\ S \implies$   
**P S T and**  
*resolveH*:  $\bigwedge L\ E\ M\ D\ T.$   
 $trail\ S = Propagated\ L\ (mset-cls\ E)\ \# M \implies$   
 $L \in \# mset-cls\ E \implies$   
 $hd-raw-trail\ S = Propagated\ L\ E \implies$   
 $raw-conflicting\ S = Some\ D \implies$   
 $-L \in \# mset-ccls\ D \implies$   
 $get-maximum-level\ (trail\ S)\ (mset-ccls\ (remove-clit\ (-L)\ D)) = backtrack-lvl\ S \implies$   
 $T \sim update-conflicting$   
 $(Some\ (union-ccls\ (remove-clit\ (-L)\ D)\ (ccls-of-cls\ (remove-lit\ L\ E))))\ (tl-trail\ S) \implies$   
**P S T and**  
*backtrackH*:  $\bigwedge L\ D\ K\ i\ M1\ M2\ T.$   
 $raw-conflicting\ S = Some\ D \implies$   
 $L \in \# mset-ccls\ D \implies$   
 $(Marked\ K\ (i+1)\ \# M1,\ M2) \in set\ (get-all-marked-decomposition\ (trail\ S)) \implies$   
 $get-level\ (trail\ S)\ L = backtrack-lvl\ S \implies$   
 $get-level\ (trail\ S)\ L = get-maximum-level\ (trail\ S)\ (mset-ccls\ D) \implies$   
 $get-maximum-level\ (trail\ S)\ (remove1-mset\ L\ (mset-ccls\ D)) \equiv i \implies$   
 $T \sim cons-trail\ (Propagated\ L\ (cls-of-ccls\ D))$   
 $(reduce-trail-to\ M1$   
 $(add-learned-cls\ (cls-of-ccls\ D)$   
 $(update-backtrack-lvl\ i$   
 $(update-conflicting\ None\ S)))) \implies$   
**P S T**  
**shows**  $P\ S\ S'$   
**using**  $cdcl_W$   
**proof** (*induct*  $S\ S'$  *rule*:  $cdcl_W$ -all-rules-induct)  
**case** (*propagate*  $S'$ )  
**then show** ?case  
**by** (*auto elim!*: *propagateE intro!*: *propagateH*)  
**next**  
**case** (*conflict*  $S'$ )  
**then show** ?case  
**by** (*auto elim!*: *conflictE intro!*: *conflictH*)  
**next**  
**case** (*restart*  $S'$ )  
**then show** ?case

```

    by (auto elim!: restartE intro!: restartH)
next
case (decide T)
then show ?case
  by (auto elim!: decideE intro!: decideH)
next
case (backtrack S')
then show ?case by (auto elim!: backtrackE intro!: backtrackH
  simp del: state-simp simp add: state-eq-def)
next
case (forget S')
then show ?case by (auto elim!: forgetE intro!: forgetH)
next
case (skip S')
then show ?case by (auto elim!: skipE intro!: skipH)
next
case (resolve S')
then show ?case
  using hd-raw-trail[of S] by (cases trail S) (auto elim!: resolveE intro!: resolveH)
qed

```

**lemma** *cdcl<sub>W</sub>-o-induct*[consumes 1, case-names decide skip resolve backtrack]:

**fixes**  $S :: 'st$

**assumes** *cdcl<sub>W</sub>*: *cdcl<sub>W</sub>-o*  $S$   $T$  **and**

*decideH*:  $\bigwedge L T. \text{conflicting } S = \text{None} \implies \text{undefined-lit } (\text{trail } S) L$   
 $\implies \text{atm-of } L \in \text{atms-of-mm } (\text{init-clss } S)$   
 $\implies T \sim \text{cons-trail } (\text{Marked } L (\text{backtrack-lvl } S + 1)) (\text{incr-lvl } S)$   
 $\implies P S T$  **and**

*skipH*:  $\bigwedge L C' M E T.$

$\text{trail } S = \text{Propagated } L C' \# M \implies$   
 $\text{raw-conflicting } S = \text{Some } E \implies$   
 $-L \notin \# \text{mset-ccls } E \implies \text{mset-ccls } E \neq \{\#\} \implies$   
 $T \sim \text{tl-trail } S \implies$   
 $P S T$  **and**

*resolveH*:  $\bigwedge L E M D T.$

$\text{trail } S = \text{Propagated } L (\text{mset-clc } E) \# M \implies$   
 $L \in \# \text{mset-clc } E \implies$   
 $\text{hd-raw-trail } S = \text{Propagated } L E \implies$   
 $\text{raw-conflicting } S = \text{Some } D \implies$   
 $-L \in \# \text{mset-ccls } D \implies$   
 $\text{get-maximum-level } (\text{trail } S) (\text{mset-ccls } (\text{remove-clit } (-L) D)) = \text{backtrack-lvl } S \implies$   
 $T \sim \text{update-conflicting}$   
 $(\text{Some } (\text{union-ccls } (\text{remove-clit } (-L) D) (\text{ccls-of-clc } (\text{remove-lit } L E)))) (\text{tl-trail } S) \implies$   
 $P S T$  **and**

*backtrackH*:  $\bigwedge L D K i M1 M2 T.$

$\text{raw-conflicting } S = \text{Some } D \implies$   
 $L \in \# \text{mset-ccls } D \implies$   
 $(\text{Marked } K (i+1) \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S)) \implies$   
 $\text{get-level } (\text{trail } S) L = \text{backtrack-lvl } S \implies$   
 $\text{get-level } (\text{trail } S) L = \text{get-maximum-level } (\text{trail } S) (\text{mset-ccls } D) \implies$   
 $\text{get-maximum-level } (\text{trail } S) (\text{remove1-mset } L (\text{mset-ccls } D)) \equiv i \implies$   
 $T \sim \text{cons-trail } (\text{Propagated } L (\text{cls-of-ccls } D))$   
 $(\text{reduce-trail-to } M1$   
 $(\text{add-learned-clc } (\text{cls-of-ccls } D)$   
 $(\text{update-backtrack-lvl } i$



```

      (update-conflicting None S))))  $\impl$ 
    P S T
shows P S T
using cdclW-o apply (induct T rule: cdclW-o.induct)
  using assms(2) apply (auto elim: decideE)[1]
apply (elim cdclW-bjE skipE resolveE backtrackE)
  apply (frule skipH; simp)
  using hd-raw-trail[of S] apply (cases trail S; auto elim!: resolveE intro!: resolveH)
apply (frule backtrackH; simp-all del: state-simp add: state-eq-def)
done

thm cdclW-o.induct
lemma cdclW-o-all-rules-induct[consumes 1, case-names decide backtrack skip resolve]:
  fixes S T :: 'st
  assumes
    cdclW-o S T and
     $\bigwedge T. \text{decide } S \ T \implies P \ S \ T$  and
     $\bigwedge T. \text{backtrack } S \ T \implies P \ S \ T$  and
     $\bigwedge T. \text{skip } S \ T \implies P \ S \ T$  and
     $\bigwedge T. \text{resolve } S \ T \implies P \ S \ T$ 
  shows P S T
  using assms by (induct T rule: cdclW-o.induct) (auto simp: cdclW-bj.simps)

lemma cdclW-o-rule-cases[consumes 1, case-names decide backtrack skip resolve]:
  fixes S T :: 'st
  assumes
    cdclW-o S T and
    decide S T  $\implies$  P and
    backtrack S T  $\implies$  P and
    skip S T  $\implies$  P and
    resolve S T  $\implies$  P
  shows P
  using assms by (auto simp: cdclW-o.simps cdclW-bj.simps)

```

## 19.3 Invariants

### 19.3.1 Properties of the trail

We here establish that: \* the marks are exactly 1..k where k is the level \* the consistency of the trail \* the fact that there is no duplicate in the trail.

**lemma** backtrack-lit-skipped:

```

assumes
  L: get-level (trail S) L = backtrack-lvl S and
  M1: (Marked K (i + 1) # M1, M2)  $\in$  set (get-all-marked-decomposition (trail S)) and
  no-dup: no-dup (trail S) and
  bt-l: backtrack-lvl S = length (get-all-levels-of-marked (trail S)) and
  order: get-all-levels-of-marked (trail S)
    = rev [1.. $(1 + \text{length (get-all-levels-of-marked (trail S))})$ ]
shows atm-of L  $\notin$  atm-of ' lits-of-l M1
proof (rule ccontr)
  let ?M = trail S
  assume L-in-M1:  $\neg \text{atm-of } L \notin \text{atm-of ' lits-of-l } M1$ 
  obtain c where
    Mc: trail S = c @ M2 @ Marked K (i + 1) # M1
  using M1 by blast

```

**have** *atm-of*  $L \notin \text{atm-of } \text{' lits-of-l } c$   
**using** *L-in-M1 no-dup unfolding*  $Mc$  *lits-of-def* **by** *force*  
**have** *g-M-eq-g-M1*: *get-level*  $?M L = \text{get-level } M1 L$   
**using** *L-in-M1 unfolding*  $Mc$  **by** *auto*  
**have** *g*: *get-all-levels-of-marked*  $M1 = \text{rev } [1..< \text{Suc } i]$   
**using** *order unfolding*  $Mc$  **by** (*auto simp del: upt-simps simp: rev-swap[symmetric]*  
*dest: append-cons-eq-upt-length-i*)  
**then have** *Max* (*set* ( $0 \# \text{get-all-levels-of-marked } (\text{rev } M1))) < \text{Suc } i$  **by** *auto*  
**then have** *get-level*  $M1 L < \text{Suc } i$   
**using** *get-rev-level-less-max-get-all-levels-of-marked*[*of*  $\text{rev } M1\ 0\ L$ ] **by** *linarith*  
**moreover have**  $\text{Suc } i \leq \text{backtrack-lvl } S$  **using** *bt-l* **by** (*simp add: Mc g*)  
**ultimately show** *False* **using** *L g-M-eq-g-M1* **by** *auto*  
**qed**

**lemma** *cdcl<sub>W</sub>-distinctinv-1*:

**assumes**  
*cdcl<sub>W</sub>*  $S\ S'$  **and**  
*no-dup* (*trail*  $S$ ) **and**  
*backtrack-lvl*  $S = \text{length } (\text{get-all-levels-of-marked } (\text{trail } S))$  **and**  
*get-all-levels-of-marked* (*trail*  $S$ ) =  $\text{rev } [1..< 1 + \text{length } (\text{get-all-levels-of-marked } (\text{trail } S))]$   
**shows** *no-dup* (*trail*  $S'$ )  
**using** *assms*  
**proof** (*induct rule: cdcl<sub>W</sub>-all-induct*)  
**case** (*backtrack*  $L\ D\ K\ i\ M1\ M2\ T$ ) **note** *decomp* = *this*(3) **and**  $L = \text{this}(4)$  **and**  $T = \text{this}(7)$  **and**  
 $n-d = \text{this}(8)$   
**obtain**  $c$  **where**  $Mc$ : *trail*  $S = c @ M2 @ \text{Marked } K\ (i + 1) \# M1$   
**using** *decomp* **by** *auto*  
**have** *no-dup* ( $M2 @ \text{Marked } K\ (i + 1) \# M1$ )  
**using**  $Mc\ n-d$  **by** *fastforce*  
**moreover have** *atm-of*  $L \notin (\lambda l. \text{atm-of } (\text{lit-of } l))\ \text{' set } M1$   
**using** *backtrack-lit-skipped*[*of*  $S\ L\ K\ i\ M1\ M2$ ]  $L\ \text{decomp}$  *backtrack.premis*  
**by** (*fastforce simp: lits-of-def*)  
**moreover then have** *undefined-lit*  $M1\ L$   
**by** (*simp add: defined-lit-map*)  
**ultimately show** *?case* **using** *decomp T n-d* **by** *simp*  
**qed** (*auto simp: defined-lit-map*)

**lemma** *cdcl<sub>W</sub>-consistent-inv-2*:

**assumes**  
*cdcl<sub>W</sub>*  $S\ S'$  **and**  
*no-dup* (*trail*  $S$ ) **and**  
*backtrack-lvl*  $S = \text{length } (\text{get-all-levels-of-marked } (\text{trail } S))$  **and**  
*get-all-levels-of-marked* (*trail*  $S$ ) =  $\text{rev } [1..< 1 + \text{length } (\text{get-all-levels-of-marked } (\text{trail } S))]$   
**shows** *consistent-interp* (*lits-of-l* (*trail*  $S'$ ))  
**using** *cdcl<sub>W</sub>-distinctinv-1* [*OF* *assms*] *distinct-consistent-interp* **by** *fast*

**lemma** *cdcl<sub>W</sub>-o-bt*:

**assumes**  
*cdcl<sub>W</sub>-o*  $S\ S'$  **and**  
*backtrack-lvl*  $S = \text{length } (\text{get-all-levels-of-marked } (\text{trail } S))$  **and**  
*get-all-levels-of-marked* (*trail*  $S$ ) =  
 $\text{rev } ([1..< (1 + \text{length } (\text{get-all-levels-of-marked } (\text{trail } S)))])$  **and**  
 $n-d[\text{simp}]: \text{no-dup } (\text{trail } S)$   
**shows** *backtrack-lvl*  $S' = \text{length } (\text{get-all-levels-of-marked } (\text{trail } S'))$   
**using** *assms*

**proof** (*induct rule: cdcl<sub>W</sub>-o-induct*)  
**case** (*backtrack L D K i M1 M2 T*) **note** *decomp = this(3)* **and** *T = this(7)* **and** *level = this(9)*  
**have** [*simp*]: *trail (reduce-trail-to M1 S) = M1*  
**using** *decomp* **by** *auto*  
**obtain** *c* **where** *M: trail S = c @ M2 @ Marked K (i + 1) # M1* **using** *decomp* **by** *auto*  
**have** *rev (get-all-levels-of-marked (trail S))*  
 $= [1..<1 + (\text{length } (\text{get-all-levels-of-marked } (\text{trail } S)))]$   
**using** *level* **by** (*auto simp: rev-swap[symmetric]*)  
**moreover** **have** *atm-of L ∉ (λl. atm-of (lit-of l))* ‘*set M1*  
**using** *backtrack-lit-skipped[of S L K i M1 M2]* *backtrack(4,8,9) decomp*  
**by** (*fastforce simp add: lits-of-def*)  
**moreover** **then** **have** *undefined-lit M1 L*  
**by** (*simp add: defined-lit-map*)  
**moreover** **then** **have** *no-dup (trail T)*  
**using** *T decomp n-d* **by** (*auto simp: defined-lit-map M*)  
**ultimately** **show** *?case*  
**using** *T n-d unfolding M* **by** (*auto dest!: append-cons-eq-upt-length simp del: upt-simps*)  
**qed** *auto*

**lemma** *cdcl<sub>W</sub>-rf-bt*:  
**assumes**  
*cdcl<sub>W</sub>-rf S S'* **and**  
*backtrack-lvl S = length (get-all-levels-of-marked (trail S))* **and**  
*get-all-levels-of-marked (trail S) = rev [1..<(1+length (get-all-levels-of-marked (trail S)))]*  
**shows** *backtrack-lvl S' = length (get-all-levels-of-marked (trail S'))*  
**using** *assms* **by** (*induct rule: cdcl<sub>W</sub>-rf.induct*) (*auto elim: restartE forgetE*)

**lemma** *cdcl<sub>W</sub>-bt*:  
**assumes**  
*cdcl<sub>W</sub> S S'* **and**  
*backtrack-lvl S = length (get-all-levels-of-marked (trail S))* **and**  
*get-all-levels-of-marked (trail S)*  
 $= \text{rev } ([1..<(1 + \text{length } (\text{get-all-levels-of-marked } (\text{trail } S)))])$  **and**  
*no-dup (trail S)*  
**shows** *backtrack-lvl S' = length (get-all-levels-of-marked (trail S'))*  
**using** *assms* **by** (*induct rule: cdcl<sub>W</sub>.induct*) (*auto simp add: cdcl<sub>W</sub>-o-bt cdcl<sub>W</sub>-rf-bt*  
*elim: conflictE propagateE*)

**lemma** *cdcl<sub>W</sub>-bt-level'*:  
**assumes**  
*cdcl<sub>W</sub> S S'* **and**  
*backtrack-lvl S = length (get-all-levels-of-marked (trail S))* **and**  
*get-all-levels-of-marked (trail S)*  
 $= \text{rev } ([1..<(1 + \text{length } (\text{get-all-levels-of-marked } (\text{trail } S)))])$  **and**  
*n-d: no-dup (trail S)*  
**shows** *get-all-levels-of-marked (trail S')*  
 $= \text{rev } [1..<1 + \text{length } (\text{get-all-levels-of-marked } (\text{trail } S'))]$   
**using** *assms*  
**proof** (*induct rule: cdcl<sub>W</sub>-all-induct*)  
**case** (*decide L T*) **note** *undef = this(2)* **and** *T = this(4)*  
**let** *?k = backtrack-lvl S*  
**let** *?M = trail S*  
**let** *?M' = Marked L (?k + 1) # trail S*  
**have** *H: get-all-levels-of-marked ?M = rev [Suc 0..<1+length (get-all-levels-of-marked ?M)]*  
**using** *decide.premis* **by** *simp*

```

have k: ?k = length (get-all-levels-of-marked ?M)
  using decide.premis by auto
have get-all-levels-of-marked ?M' = Suc ?k # get-all-levels-of-marked ?M by simp
then have get-all-levels-of-marked ?M' = Suc ?k #
  rev [Suc 0..<1+length (get-all-levels-of-marked ?M)]
  using H by auto
moreover have ... = rev [Suc 0..< Suc (1+length (get-all-levels-of-marked ?M))]
  unfolding k by simp
finally show ?case using T undef by (auto simp add: defined-lit-map)
next
case (backtrack L D K i M1 M2 T) note decomp = this(3) and confli = this(1) and T = this(7)
and
  all-marked = this(9) and bt-lvl = this(8)
have atm-of L ∉ atm-of ' lits-of-l M1
  using backtrack-lit-skipped[of S L K i M1 M2] backtrack(4,8-10) decomp
  by (fastforce simp add: lits-of-def)
moreover then have undefined-lit M1 L
  by (auto simp: defined-lit-map lits-of-def)
then have [simp]: trail T = Propagated L (mset-ccls D) # M1
  using T decomp n-d by auto
obtain c where M: trail S = c @ M2 @ Marked K (i + 1) # M1 using decomp by auto
have get-all-levels-of-marked (rev (trail S))
  = [Suc 0..<2+length (get-all-levels-of-marked c) + (length (get-all-levels-of-marked M2)
    + length (get-all-levels-of-marked M1))]
  using all-marked bt-lvl unfolding M by (auto simp: rev-swap[symmetric] simp del: upt-simps)
then show ?case
  using T by (auto simp: rev-swap M simp del: upt-simps dest!: append-cons-eq-upt(1))
qed auto

```

We write  $1 + \text{length } (\text{get-all-levels-of-marked } (\text{trail } S))$  instead of  $\text{backtrack-lvl } S$  to avoid non termination of rewriting.

**definition**  $\text{cdcl}_W\text{-}M\text{-level-inv} :: 'st \Rightarrow \text{bool}$  **where**  
 $\text{cdcl}_W\text{-}M\text{-level-inv } S \longleftrightarrow$   
 $\text{consistent-interp } (\text{lits-of-l } (\text{trail } S))$   
 $\wedge \text{no-dup } (\text{trail } S)$   
 $\wedge \text{backtrack-lvl } S = \text{length } (\text{get-all-levels-of-marked } (\text{trail } S))$   
 $\wedge \text{get-all-levels-of-marked } (\text{trail } S)$   
 $= \text{rev } [1..<1+\text{length } (\text{get-all-levels-of-marked } (\text{trail } S))]$

**lemma**  $\text{cdcl}_W\text{-}M\text{-level-inv-decomp}$ :  
**assumes**  $\text{cdcl}_W\text{-}M\text{-level-inv } S$   
**shows**  
 $\text{consistent-interp } (\text{lits-of-l } (\text{trail } S))$  **and**  
 $\text{no-dup } (\text{trail } S)$   
**using** *assms* **unfolding**  $\text{cdcl}_W\text{-}M\text{-level-inv-def}$  **by** *fastforce+*

**lemma**  $\text{cdcl}_W\text{-consistent-inv}$ :  
**fixes**  $S S' :: 'st$   
**assumes**  
 $\text{cdcl}_W S S'$  **and**  
 $\text{cdcl}_W\text{-}M\text{-level-inv } S$   
**shows**  $\text{cdcl}_W\text{-}M\text{-level-inv } S'$   
**using** *assms*  $\text{cdcl}_W\text{-consistent-inv-2}$   $\text{cdcl}_W\text{-distinctinv-1}$   $\text{cdcl}_W\text{-bt}$   $\text{cdcl}_W\text{-bt-level'}$   
**unfolding**  $\text{cdcl}_W\text{-}M\text{-level-inv-def}$  **by** *meson+*

**lemma** *rtracnp-cdcl<sub>W</sub>-consistent-inv*:

**assumes**

*cdcl<sub>W</sub><sup>\*\*</sup> S S' and*

*cdcl<sub>W</sub>-M-level-inv S*

**shows** *cdcl<sub>W</sub>-M-level-inv S'*

**using** *assms* **by** (*induct rule: rtracnp-induct*) (*auto intro: cdcl<sub>W</sub>-consistent-inv*)

**lemma** *tracnp-cdcl<sub>W</sub>-consistent-inv*:

**assumes**

*cdcl<sub>W</sub><sup>++</sup> S S' and*

*cdcl<sub>W</sub>-M-level-inv S*

**shows** *cdcl<sub>W</sub>-M-level-inv S'*

**using** *assms* **by** (*induct rule: tracnp-induct*)

(*auto intro: cdcl<sub>W</sub>-consistent-inv*)

**lemma** *cdcl<sub>W</sub>-M-level-inv-S0-cdcl<sub>W</sub>[simp]*:

*cdcl<sub>W</sub>-M-level-inv (init-state N)*

**unfolding** *cdcl<sub>W</sub>-M-level-inv-def* **by** *auto*

**lemma** *cdcl<sub>W</sub>-M-level-inv-get-level-le-backtrack-lvl*:

**assumes** *inv: cdcl<sub>W</sub>-M-level-inv S*

**shows** *get-level (trail S) L ≤ backtrack-lvl S*

**proof** –

**have** *get-all-levels-of-marked (trail S) = rev [1..*1* + backtrack-lvl S]*

**using** *inv* **unfolding** *cdcl<sub>W</sub>-M-level-inv-def* **by** *auto*

**then show** *?thesis*

**using** *get-rev-level-less-max-get-all-levels-of-marked[of rev (trail S) 0 L]*

**by** (*auto simp: Max-n-upt*)

**qed**

**lemma** *backtrack-ex-decomp*:

**assumes**

*M-l: cdcl<sub>W</sub>-M-level-inv S and*

*i-S: i < backtrack-lvl S*

**shows**  $\exists K M1 M2. (\text{Marked } K (i + 1) \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$

**proof** –

**let** *?M = trail S*

**have**

*g: get-all-levels-of-marked (trail S) = rev [Suc 0..*Suc* (backtrack-lvl S)]*

**using** *M-l* **unfolding** *cdcl<sub>W</sub>-M-level-inv-def* **by** *simp-all*

**then have** *i+1 ∈ set (get-all-levels-of-marked (trail S))*

**using** *i-S* **by** *auto*

**then obtain** *c K c' where tr-S: trail S = c @ Marked K (i + 1) # c'*

**using** *in-get-all-levels-of-marked-iff-decomp[of i+1 trail S]* **by** *auto*

**obtain** *M1 M2 where (Marked K (i + 1) # M1, M2) ∈ set (get-all-marked-decomposition (trail S))*

**using** *Marked-cons-in-get-all-marked-decomposition-append-Marked-cons* **unfolding** *tr-S* **by** *fast*

**then show** *?thesis* **by** *blast*

**qed**

### 19.3.2 Better-Suited Induction Principle

We generalise the induction principle defined previously: the induction case for *backtrack* now includes the assumption that *undefined-lit M1 L*. This helps the simplifier and thus the automa-

tion.

**lemma** *backtrack-induction-lev*[consumes 1, case-names *M-devel-inv backtrack*]:

**assumes**

*bt*: *backtrack S T* **and**

*inv*: *cdcl<sub>W</sub>-M-level-inv S* **and**

*backtrackH*:  $\bigwedge K i M1 M2 L D T.$

*raw-conflicting S* = *Some D*  $\implies$

$L \in \# \text{ mset-clcs } D \implies$

$(\text{Marked } K (\text{Suc } i) \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S)) \implies$

*get-level* (*trail S*) *L* = *backtrack-lvl S*  $\implies$

*get-level* (*trail S*) *L* = *get-maximum-level* (*trail S*) (*mset-clcs D*)  $\implies$

*get-maximum-level* (*trail S*) (*remove1-mset L (mset-clcs D)*)  $\equiv i \implies$

*undefined-lit M1 L*  $\implies$

$T \sim \text{cons-trail } (\text{Propagated } L (\text{cls-of-clcs } D))$

$(\text{reduce-trail-to } M1$

$(\text{add-learned-clcs } (\text{cls-of-clcs } D)$

$(\text{update-backtrack-lvl } i$

$(\text{update-conflicting } \text{None } S)))) \implies$

*P S T*

**shows** *P S T*

**proof** –

**obtain** *K i M1 M2 L D* **where**

*decomp*:  $(\text{Marked } K (\text{Suc } i) \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$  **and**

*L*: *get-level* (*trail S*) *L* = *backtrack-lvl S* **and**

*confl*: *raw-conflicting S* = *Some D* **and**

*LD*:  $L \in \# \text{ mset-clcs } D$  **and**

*lev-L*: *get-level* (*trail S*) *L* = *get-maximum-level* (*trail S*) (*mset-clcs D*) **and**

*lev-D*: *get-maximum-level* (*trail S*) (*remove1-mset L (mset-clcs D)*)  $\equiv i$  **and**

*T*:  $T \sim \text{cons-trail } (\text{Propagated } L (\text{cls-of-clcs } D))$

$(\text{reduce-trail-to } M1$

$(\text{add-learned-clcs } (\text{cls-of-clcs } D)$

$(\text{update-backtrack-lvl } i$

$(\text{update-conflicting } \text{None } S))))$

**using** *bt* **by** (*elim backtrackE*) *metis*

**have** *atm-of L*  $\notin$  *atm-of ' lits-of-l M1*

**using** *backtrack-lit-skipped*[*of S L K i M1 M2*] *L decomp bt confl lev-L lev-D inv*

**unfolding** *cdcl<sub>W</sub>-M-level-inv-def* **by** *force*

**then have** *undefined-lit M1 L*

**by** (*auto simp: defined-lit-map lits-of-def*)

**then show** *?thesis*

**using** *backtrackH*[*OF confl LD decomp L lev-L lev-D - T*] **by** *simp*

**qed**

**lemmas** *backtrack-induction-lev2* = *backtrack-induction-lev*[consumes 2, case-names *backtrack*]

**lemma** *cdcl<sub>W</sub>-all-induct-lev-full*:

**fixes** *S* :: 'st

**assumes**

*cdcl<sub>W</sub>*: *cdcl<sub>W</sub> S S'* **and**

*inv*[*simp*]: *cdcl<sub>W</sub>-M-level-inv S* **and**

*propagateH*:  $\bigwedge C L T. \text{conflicting } S = \text{None} \implies$

$C \notin \text{raw-clauses } S \implies$

$L \in \# \text{ mset-clcs } C \implies$

*trail S*  $\models_{\text{as}} C \text{Not } (\text{remove1-mset } L (\text{mset-clcs } C)) \implies$

$undefined\text{-}lit\ (trail\ S)\ L \implies$   
 $T \sim cons\text{-}trail\ (Propagated\ L\ C)\ S \implies$   
 $P\ S\ T\ \mathbf{and}$   
 $conflictH: \bigwedge D\ T. \ conflict\ S = None \implies$   
 $D \in! raw\text{-}clauses\ S \implies$   
 $trail\ S \models_{as}\ CNot\ (mset\text{-}cls\ D) \implies$   
 $T \sim update\text{-}conflicting\ (Some\ (ccls\text{-}of\text{-}cls\ D))\ S \implies$   
 $P\ S\ T\ \mathbf{and}$   
 $forgetH: \bigwedge C\ T. \ conflict\ S = None \implies$   
 $C \in! raw\text{-}learned\text{-}clss\ S \implies$   
 $\neg(trail\ S) \models_{asm}\ clauses\ S \implies$   
 $mset\text{-}cls\ C \notin set\ (get\text{-}all\text{-}mark\text{-}of\text{-}propagated\ (trail\ S)) \implies$   
 $mset\text{-}cls\ C \notin \# init\text{-}clss\ S \implies$   
 $T \sim remove\text{-}cls\ C\ S \implies$   
 $P\ S\ T\ \mathbf{and}$   
 $restartH: \bigwedge T. \neg trail\ S \models_{asm}\ clauses\ S \implies$   
 $conflicting\ S = None \implies$   
 $T \sim restart\text{-}state\ S \implies$   
 $P\ S\ T\ \mathbf{and}$   
 $decideH: \bigwedge L\ T. \ conflict\ S = None \implies$   
 $undefined\text{-}lit\ (trail\ S)\ L \implies$   
 $atm\text{-}of\ L \in atm\text{-}of\text{-}mm\ (init\text{-}clss\ S) \implies$   
 $T \sim cons\text{-}trail\ (Marked\ L\ (backtrack\text{-}lvl\ S + 1))\ (incr\text{-}lvl\ S) \implies$   
 $P\ S\ T\ \mathbf{and}$   
 $skipH: \bigwedge L\ C'\ M\ E\ T.$   
 $trail\ S = Propagated\ L\ C'\ \# M \implies$   
 $raw\text{-}conflicting\ S = Some\ E \implies$   
 $-L \notin \# mset\text{-}ccls\ E \implies mset\text{-}ccls\ E \neq \{\#\} \implies$   
 $T \sim tl\text{-}trail\ S \implies$   
 $P\ S\ T\ \mathbf{and}$   
 $resolveH: \bigwedge L\ E\ M\ D\ T.$   
 $trail\ S = Propagated\ L\ (mset\text{-}cls\ E)\ \# M \implies$   
 $L \in \# mset\text{-}cls\ E \implies$   
 $hd\text{-}raw\text{-}trail\ S = Propagated\ L\ E \implies$   
 $raw\text{-}conflicting\ S = Some\ D \implies$   
 $-L \in \# mset\text{-}ccls\ D \implies$   
 $get\text{-}maximum\text{-}level\ (trail\ S)\ (mset\text{-}ccls\ (remove\text{-}clit\ (-L)\ D)) = backtrack\text{-}lvl\ S \implies$   
 $T \sim update\text{-}conflicting$   
 $(Some\ (union\text{-}ccls\ (remove\text{-}clit\ (-L)\ D)\ (ccls\text{-}of\text{-}cls\ (remove\text{-}lit\ L\ E))))\ (tl\text{-}trail\ S) \implies$   
 $P\ S\ T\ \mathbf{and}$   
 $backtrackH: \bigwedge K\ i\ M1\ M2\ L\ D\ T.$   
 $raw\text{-}conflicting\ S = Some\ D \implies$   
 $L \in \# mset\text{-}ccls\ D \implies$   
 $(Marked\ K\ (Suc\ i)\ \# M1, M2) \in set\ (get\text{-}all\text{-}marked\text{-}decomposition\ (trail\ S)) \implies$   
 $get\text{-}level\ (trail\ S)\ L = backtrack\text{-}lvl\ S \implies$   
 $get\text{-}level\ (trail\ S)\ L = get\text{-}maximum\text{-}level\ (trail\ S)\ (mset\text{-}ccls\ D) \implies$   
 $get\text{-}maximum\text{-}level\ (trail\ S)\ (remove1\text{-}mset\ L\ (mset\text{-}ccls\ D)) \equiv i \implies$   
 $undefined\text{-}lit\ M1\ L \implies$   
 $T \sim cons\text{-}trail\ (Propagated\ L\ (cls\text{-}of\text{-}ccls\ D))$   
 $(reduce\text{-}trail\text{-}to\ M1$   
 $(add\text{-}learned\text{-}cls\ (cls\text{-}of\text{-}ccls\ D)$   
 $(update\text{-}backtrack\text{-}lvl\ i$   
 $(update\text{-}conflicting\ None\ S)))) \implies$   
 $P\ S\ T$   
**shows**  $P\ S\ S'$

```

using cdclW
proof (induct S' rule: cdclW-all-rules-induct)
  case (propagate S')
  then show ?case
    by (auto elim!: propagateE intro!: propagateH)
next
  case (conflict S')
  then show ?case
    by (auto elim!: conflictE intro!: conflictH)
next
  case (restart S')
  then show ?case
    by (auto elim!: restartE intro!: restartH)
next
  case (decide T)
  then show ?case
    by (auto elim!: decideE intro!: decideH)
next
  case (backtrack S')
  then show ?case
    apply (induction rule: backtrack-induction-lev)
    apply (rule inv)
    by (rule backtrackH;
        fastforce simp del: state-simp simp add: state-eq-def dest!: HOL.meta-eq-to-obj-eq)
next
  case (forget S')
  then show ?case by (auto elim!: forgetE intro!: forgetH)
next
  case (skip S')
  then show ?case by (auto elim!: skipE intro!: skipH)
next
  case (resolve S')
  then show ?case
    using hd-raw-trail[of S] by (cases trail S) (auto elim!: resolveE intro!: resolveH)
qed

lemmas cdclW-all-induct-lev2 = cdclW-all-induct-lev-full[consumes 2, case-names propagate conflict
forget restart decide skip resolve backtrack]

lemmas cdclW-all-induct-lev = cdclW-all-induct-lev-full[consumes 1, case-names lev-inv propagate
conflict forget restart decide skip resolve backtrack]

thm cdclW-o-induct
lemma cdclW-o-induct-lev[consumes 1, case-names M-lev decide skip resolve backtrack]:
  fixes S :: 'st
  assumes
    cdclW: cdclW-o S T and
    inv[simp]: cdclW-M-level-inv S and
    decideH:  $\bigwedge L. T. \text{conflicting } S = \text{None} \implies$ 
      undefined-lit (trail S) L  $\implies$ 
      atm-of L  $\in$  atms-of-mm (init-clss S)  $\implies$ 
      T  $\sim$  cons-trail (Marked L (backtrack-lvl S + 1)) (incr-lvl S)  $\implies$ 
      P S T and
    skipH:  $\bigwedge L. C' M E T. \text{trail } S = \text{Propagated } L \ C' \ \# \ M \implies$ 

```



```

raw-conflicting S = Some E  $\implies$ 
-L  $\notin$  # mset-ccls E  $\implies$  mset-ccls E  $\neq$  {#}  $\implies$ 
T  $\sim$  tl-trail S  $\implies$ 
P S T and
resolveH:  $\bigwedge$  L E M D T.
trail S = Propagated L (mset-ccls E) # M  $\implies$ 
L  $\in$  # mset-ccls E  $\implies$ 
hd-raw-trail S = Propagated L E  $\implies$ 
raw-conflicting S = Some D  $\implies$ 
-L  $\in$  # mset-ccls D  $\implies$ 
get-maximum-level (trail S) (mset-ccls (remove-clit (-L) D)) = backtrack-lvl S  $\implies$ 
T  $\sim$  update-conflicting
(Some (union-ccls (remove-clit (-L) D) (ccls-of-ccls (remove-lit L E)))) (tl-trail S)  $\implies$ 
P S T and
backtrackH:  $\bigwedge$  K i M1 M2 L D T.
raw-conflicting S = Some D  $\implies$ 
L  $\in$  # mset-ccls D  $\implies$ 
(Marked K (Suc i) # M1, M2)  $\in$  set (get-all-marked-decomposition (trail S))  $\implies$ 
get-level (trail S) L = backtrack-lvl S  $\implies$ 
get-level (trail S) L = get-maximum-level (trail S) (mset-ccls D)  $\implies$ 
get-maximum-level (trail S) (remove1-mset L (mset-ccls D))  $\equiv$  i  $\implies$ 
undefined-lit M1 L  $\implies$ 
T  $\sim$  cons-trail (Propagated L (cls-of-ccls D))
(reduce-trail-to M1
(add-learned-cls (cls-of-ccls D)
(update-backtrack-lvl i
(update-conflicting None S))))  $\implies$ 
P S T
shows P S T
using cdclW
proof (induct S T rule: cdclW-o-all-rules-induct)
case (decide T)
then show ?case
by (auto elim!: decideE intro!: decideH)
next
case (backtrack S')
then show ?case
apply (induction rule: backtrack-induction-lev)
apply (rule inv)
by (rule backtrackH;
fastforce simp del: state-simp simp add: state-eq-def dest!: HOL.meta-eq-to-obj-eq)
next
case (skip S')
then show ?case by (auto elim!: skipE intro!: skipH)
next
case (resolve S')
then show ?case
using hd-raw-trail[of S] by (cases trail S) (auto elim!: resolveE intro!: resolveH)
qed

lemmas cdclW-o-induct-lev2 = cdclW-o-induct-lev[consumes 2, case-names decide skip resolve backtrack]

```

### 19.3.3 Compatibility with $op \sim$

lemma propagate-state-eq-compatible:

```

assumes
  propa: propagate  $S$   $T$  and
  SS':  $S \sim S'$  and
  TT':  $T \sim T'$ 
shows propagate  $S'$   $T'$ 
proof –
obtain  $C$   $L$  where
  conf: conflicting  $S = \text{None}$  and
  C:  $C \notin \text{raw-clauses } S$  and
  L:  $L \in \# \text{mset-cls } C$  and
  tr: trail  $S \models_{\text{as}} \text{CNot } (\text{remove1-mset } L (\text{mset-cls } C))$  and
  undef: undefined-lit (trail  $S$ )  $L$  and
  T:  $T \sim \text{cons-trail } (\text{Propagated } L \ C) \ S$ 
using propa by (elim propagateE) auto

obtain  $C'$  where
  CC': mset-cls  $C' = \text{mset-cls } C$  and
  C':  $C' \notin \text{raw-clauses } S'$ 
using SS'  $C$ 
  in-mset-clss-exists-preimage[of mset-cls  $C$  raw-learned-clss  $S$ ]
  in-mset-clss-exists-preimage[of mset-cls  $C$  raw-init-clss  $S'$ ]
apply –
apply (frule in-clss-mset-clss)
by (auto simp: state-eq-def raw-clauses-def simp del: state-simp dest: in-clss-mset-clss)

show ?thesis
apply (rule propagate-rule[of -  $C'$ ])
using state-eq-sym[of  $S$   $S'$ ] SS' conf  $C'$  CC'  $L$  tr undef TT'  $T$ 
by (auto simp: state-eq-def simp del: state-simp)
qed

lemma conflict-state-eq-compatible:
assumes
  confl: conflict  $S$   $T$  and
  TT':  $T \sim T'$  and
  SS':  $S \sim S'$ 
shows conflict  $S'$   $T'$ 
proof –
obtain  $D$  where
  conf: conflicting  $S = \text{None}$  and
  D:  $D \notin \text{raw-clauses } S$  and
  tr: trail  $S \models_{\text{as}} \text{CNot } (\text{mset-cls } D)$  and
  T:  $T \sim \text{update-conflicting } (\text{Some } (\text{ccls-of-cls } D)) \ S$ 
using confl by (elim conflictE) auto

obtain  $D'$  where
  DD': mset-cls  $D' = \text{mset-cls } D$  and
  D':  $D' \notin \text{raw-clauses } S'$ 
using  $D$  SS' in-mset-clss-exists-preimage by fastforce

show ?thesis
apply (rule conflict-rule[of -  $D'$ ])
using state-eq-sym[of  $S$   $S'$ ] SS' conf  $D'$  DD' tr TT'  $T$ 
by (auto simp: state-eq-def simp del: state-simp)
qed

```

**lemma** *backtrack-levE[consumes 2]*:  
*backtrack S S'  $\implies$  cdcl<sub>W</sub>-M-level-inv S  $\implies$*   
*( $\bigwedge K i M1 M2 L D$ .*  
*raw-conflicting S = Some D  $\implies$*   
*L  $\in \#$  mset-ccls D  $\implies$*   
*(Marked K (Suc i)  $\#$  M1, M2)  $\in$  set (get-all-marked-decomposition (trail S))  $\implies$*   
*get-level (trail S) L = backtrack-lvl S  $\implies$*   
*get-level (trail S) L = get-maximum-level (trail S) (mset-ccls D)  $\implies$*   
*get-maximum-level (trail S) (remove1-mset L (mset-ccls D))  $\equiv$  i  $\implies$*   
*undefined-lit M1 L  $\implies$*   
*S'  $\sim$  cons-trail (Propagated L (cls-of-ccls D))*  
*(reduce-trail-to M1*  
*(add-learned-cls (cls-of-ccls D)*  
*(update-backtrack-lvl i*  
*(update-conflicting None S))))  $\implies$  P)  $\implies$*   
*P*  
**using** *assms* **by** (*induction rule: backtrack-induction-lev2*) *metis*  
**thm** *allI*

**lemma** *backtrack-state-eq-compatible*:  
**assumes**  
*bt: backtrack S T and*  
*SS': S  $\sim$  S' and*  
*TT': T  $\sim$  T' and*  
*inv: cdcl<sub>W</sub>-M-level-inv S*  
**shows** *backtrack S' T'*  
**proof** –  
**obtain** *D L K i M1 M2 where*  
*conf: raw-conflicting S = Some D and*  
*L: L  $\in \#$  mset-ccls D and*  
*decomp: (Marked K (Suc i)  $\#$  M1, M2)  $\in$  set (get-all-marked-decomposition (trail S)) and*  
*lev: get-level (trail S) L = backtrack-lvl S and*  
*max: get-level (trail S) L = get-maximum-level (trail S) (mset-ccls D) and*  
*max-D: get-maximum-level (trail S) (remove1-mset L (mset-ccls D))  $\equiv$  i and*  
*undef: undefined-lit M1 L and*  
*T: T  $\sim$  cons-trail (Propagated L (cls-of-ccls D))*  
*(reduce-trail-to M1*  
*(add-learned-cls (cls-of-ccls D)*  
*(update-backtrack-lvl i*  
*(update-conflicting None S))))*  
**using** *bt inv* **by** (*elim backtrack-levE*) *metis*  
**obtain** *D' where*  
*D': raw-conflicting S' = Some D'*  
**using** *SS' conf* **by** (*cases raw-conflicting S'*) *auto*  
**have** [*simp*]: *mset-ccls D = mset-ccls D'*  
**using** *SS' D' conf* **by** (*auto simp: state-eq-def simp del: state-simp*)[]  
**have** *T': T'  $\sim$  cons-trail (Propagated L (cls-of-ccls D'))*  
*(reduce-trail-to M1 (add-learned-cls (cls-of-ccls D')*  
*(update-backtrack-lvl i (update-conflicting None S'))))*  
**using** *TT' unfolding state-eq-def*  
**using** *decomp undef inv SS' T* **by** (*auto simp add: cdcl<sub>W</sub>-M-level-inv-def*)  
**show** *?thesis*

```

apply (rule backtrack-rule[of - D'])
  apply (rule D')
  using state-eq-sym[of S S'] TT' SS' D' conf L decomp lev max max-D undef T
  apply (auto simp: state-eq-def simp del: state-simp)[]
  using decomp SS' lev SS' max-D max T' by (auto simp: state-eq-def simp del: state-simp)
qed

```

**lemma** *decide-state-eq-compatible:*

```

assumes
  decide S T and
  S ~ S' and
  T ~ T'
shows decide S' T'
using assms apply (elim decideE)
by (rule decide-rule) (auto simp: state-eq-def raw-clauses-def simp del: state-simp)

```

**lemma** *skip-state-eq-compatible:*

```

assumes
  skip: skip S T and
  SS': S ~ S' and
  TT': T ~ T'
shows skip S' T'
proof -
  obtain L C' M E where
    tr: trail S = Propagated L C' # M and
    raw: raw-conflicting S = Some E and
    L: -L ∉ # mset-ccls E and
    E: mset-ccls E ≠ {#} and
    T: T ~ tl-trail S
  using skip by (elim skipE) simp
  obtain E' where E': raw-conflicting S' = Some E'
  using SS' raw by (cases raw-conflicting S') (auto simp: state-eq-def simp del: state-simp)
  show ?thesis
  apply (rule skip-rule)
  using tr raw L E T SS' apply (auto simp: simp del: )[]
  using E' apply simp
  using E' SS' L raw E apply (auto simp: state-eq-def simp del: state-simp)[2]
  using T TT' SS' by (auto simp: state-eq-def simp del: state-simp)
qed

```

**lemma** *resolve-state-eq-compatible:*

```

assumes
  res: resolve S T and
  TT': T ~ T' and
  SS': S ~ S'
shows resolve S' T'
proof -
  obtain E D L where
    tr: trail S ≠ [] and
    hd: hd-raw-trail S = Propagated L E and
    L: L ∈ # mset-ccls E and
    raw: raw-conflicting S = Some D and
    LD: -L ∈ # mset-ccls D and
    i: get-maximum-level (trail S) (mset-ccls (remove-clit (-L) D)) = backtrack-lvl S and

```

```

  T: T ~ update-conflicting (Some (union-ccls (remove-clit (-L) D)
    (ccls-of-cls (remove-lit L E)))) (tl-trail S)
using assms by (elim resolveE) simp

obtain E' where
  E': hd-raw-trail S' = Propagated L E'
  using SS' hd by (metis ⟨trail S ≠ []⟩ hd-raw-trail is-proped-def marked-lit.disc(3)
    marked-lit.inject(2) mset-of-mlit.elims state-eq-trail)
have [simp]: mset-cls E = mset-cls E'
  using hd-raw-trail[of S] tr hd-raw-trail[of S'] tr SS' hd E'
  by (metis marked-lit.inject(2) mset-of-mlit.simps(1) state-eq-trail)
obtain D' where
  D': raw-conflicting S' = Some D'
  using SS' raw by fastforce
have [simp]: mset-ccls D = mset-ccls D'
  using D' SS' raw state-simp(5) by fastforce
have T'T: T' ~ T
  using TT' state-eq-sym by auto
show ?thesis
  apply (rule resolve-rule)
    using tr SS' apply simp
    using E' apply simp
    using L apply simp
    using D' apply simp
    using D' SS' raw LD apply (auto simp add: state-eq-def simp del: state-simp)[]
    using D' SS' raw LD apply (auto simp add: state-eq-def simp del: state-simp)[]
    using raw SS' i apply (auto simp add: state-eq-def simp del: state-simp)[]
    using T T'T SS' by (auto simp: state-eq-def simp del: state-simp )
qed

lemma forget-state-eq-compatible:
  assumes
    forget: forget S T and
    SS': S ~ S' and
    TT': T ~ T'
  shows forget S' T'
proof -
  obtain C where
    conf: conflicting S = None and
    C !∈! raw-learned-clss S and
    tr: ¬(trail S) ⊨asm clauses S and
    C1: mset-cls C ∉ set (get-all-mark-of-propagated (trail S)) and
    C2: mset-cls C ∉# init-clss S and
    T: T ~ remove-cls C S
  using forget by (elim forgetE) simp

  obtain C' where
    C': C' !∈! raw-learned-clss S' and
    [simp]: mset-cls C' = mset-cls C
  using ⟨C !∈! raw-learned-clss S⟩ SS' in-mset-clss-exists-preimage by fastforce
  show ?thesis
    apply (rule forget-rule)
      using SS' conf apply simp
      using C' apply simp
      using SS' tr apply simp

```

```

    using SS' C1 apply simp
    using SS' C2 apply simp
    using T TT' SS' by (auto simp: state-eq-def simp del: state-simp)
qed

```

**lemma** *cdcl<sub>W</sub>-state-eq-compatible*:

```

assumes
  cdclW S T and  $\neg$ restart S T and
  S  $\sim$  S'
  T  $\sim$  T' and
  cdclW-M-level-inv S
shows cdclW S' T'
using assms by (meson backtrack backtrack-state-eq-compatible bj cdclW.simps cdclW-o-rule-cases
  cdclW-rf.cases conflict-state-eq-compatible decide decide-state-eq-compatible forget
  forget-state-eq-compatible propagate-state-eq-compatible resolve resolve-state-eq-compatible
  skip skip-state-eq-compatible state-eq-ref)

```

**lemma** *cdcl<sub>W</sub>-bj-state-eq-compatible*:

```

assumes
  cdclW-bj S T and cdclW-M-level-inv S
  T  $\sim$  T'
shows cdclW-bj S T'
using assms by (meson backtrack backtrack-state-eq-compatible cdclW-bjE resolve
  resolve-state-eq-compatible skip skip-state-eq-compatible state-eq-ref)

```

**lemma** *trancpl-cdcl<sub>W</sub>-bj-state-eq-compatible*:

```

assumes
  cdclW-bj++ S T and inv: cdclW-M-level-inv S and
  S  $\sim$  S' and
  T  $\sim$  T'
shows cdclW-bj++ S' T'
using assms
proof (induction arbitrary: S' T')
  case base
  then show ?case
    unfolding trancpl-unfold-end by (meson backtrack-state-eq-compatible cdclW-bj.simps
      resolve-state-eq-compatible rtrancpl-unfold skip-state-eq-compatible)
next
  case (step T U) note IH = this(3)[OF this(4-5)]
  have cdclW++ S T
    using trancpl-mono[of cdclW-bj cdclW] step.hyps(1) cdclW.other cdclW-o.bj by blast
  then have cdclW-M-level-inv T
    using inv trancpl-cdclW-consistent-inv by blast
  then have cdclW-bj++ T T'
    using  $\langle U \sim T \rangle$  cdclW-bj-state-eq-compatible[of T U]  $\langle$ cdclW-bj T U $\rangle$  by auto
  then show ?case
    using IH[of T] by auto
qed

```

### 19.3.4 Conservation of some Properties

**lemma** *cdcl<sub>W</sub>-o-no-more-init-clss*:

```

assumes
  cdclW-o S S' and
  inv: cdclW-M-level-inv S
shows init-clss S = init-clss S'

```

**using** *assms* **by** (*induct rule*: *cdcl<sub>W</sub>-o-induct-lev2*) (*auto simp*: *inv cdcl<sub>W</sub>-M-level-inv-decomp*)

**lemma** *trancpl-cdcl<sub>W</sub>-o-no-more-init-clss*:

**assumes**

*cdcl<sub>W</sub>-o<sup>++</sup> S S'* **and**

*inv*: *cdcl<sub>W</sub>-M-level-inv S*

**shows** *init-clss S = init-clss S'*

**using** *assms* **apply** (*induct rule*: *trancpl.induct*)

**by** (*auto dest*: *cdcl<sub>W</sub>-o-no-more-init-clss*

*dest!*: *trancpl-cdcl<sub>W</sub>-consistent-inv dest*: *trancpl-mono-explicit*[*of cdcl<sub>W</sub>-o - - cdcl<sub>W</sub>*]

*simp*: *other*)

**lemma** *rtrancpl-cdcl<sub>W</sub>-o-no-more-init-clss*:

**assumes**

*cdcl<sub>W</sub>-o<sup>\*\*</sup> S S'* **and**

*inv*: *cdcl<sub>W</sub>-M-level-inv S*

**shows** *init-clss S = init-clss S'*

**using** *assms* **unfolding** *rtrancpl-unfold* **by** (*auto intro*: *trancpl-cdcl<sub>W</sub>-o-no-more-init-clss*)

**lemma** *cdcl<sub>W</sub>-init-clss*:

**assumes**

*cdcl<sub>W</sub> S T* **and**

*inv*: *cdcl<sub>W</sub>-M-level-inv S*

**shows** *init-clss S = init-clss T*

**using** *assms* **by** (*induct rule*: *cdcl<sub>W</sub>-all-induct-lev2*)

(*auto simp*: *inv cdcl<sub>W</sub>-M-level-inv-decomp not-in-iff*)

**lemma** *rtrancpl-cdcl<sub>W</sub>-init-clss*:

*cdcl<sub>W</sub><sup>\*\*</sup> S T  $\implies$  cdcl<sub>W</sub>-M-level-inv S  $\implies$  init-clss S = init-clss T*

**by** (*induct rule*: *rtrancpl-induct*) (*auto dest*: *cdcl<sub>W</sub>-init-clss rtrimpl-cdcl<sub>W</sub>-consistent-inv*)

**lemma** *trancpl-cdcl<sub>W</sub>-init-clss*:

*cdcl<sub>W</sub><sup>++</sup> S T  $\implies$  cdcl<sub>W</sub>-M-level-inv S  $\implies$  init-clss S = init-clss T*

**using** *rtrancpl-cdcl<sub>W</sub>-init-clss*[*of S T*] **unfolding** *rtrancpl-unfold* **by** *auto*

### 19.3.5 Learned Clause

This invariant shows that:

- the learned clauses are entailed by the initial set of clauses.
- the conflicting clause is entailed by the initial set of clauses.
- the marks are entailed by the clauses. A more precise version would be to show that either these marked are learned or are in the set of clauses

**definition** *cdcl<sub>W</sub>-learned-clause* (*S*:: '*st*')  $\longleftrightarrow$

(*init-clss S  $\models_{psm}$  learned-clss S*

$\wedge (\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{init-clss } S \models_{pm} T)$

$\wedge \text{set } (\text{get-all-mark-of-propagated } (\text{trail } S)) \subseteq \text{set-mset } (\text{clauses } S))$

**lemma** *cdcl<sub>W</sub>-learned-clause-S0-cdcl<sub>W</sub>*[*simp*]:

*cdcl<sub>W</sub>-learned-clause* (*init-state N*)

**unfolding** *cdcl<sub>W</sub>-learned-clause-def* **by** *auto*

```

lemma cdclW-learned-clss:
  assumes
    cdclW S S' and
    learned: cdclW-learned-clause S and
    lev-inv: cdclW-M-level-inv S
  shows cdclW-learned-clause S'
  using assms(1) lev-inv learned
proof (induct rule: cdclW-all-induct-lev2)
  case (backtrack K i M1 M2 L D T) note decomp = this(3) and confl = this(1) and undef = this(7)
  and T = this(8)
  show ?case
    using decomp confl learned undef T unfolding cdclW-learned-clause-def
    by (auto dest!: get-all-marked-decomposition-exists-prepend
      simp: raw-clauses-def lev-inv cdclW-M-level-inv-decomp dest: true-clss-clss-left-right)
next
  case (resolve L C M D) note trail = this(1) and CL = this(2) and confl = this(4) and DL = this(5)
  and lvl = this(6) and T = this(7)
  moreover
    have init-clss S ⊨psm learned-clss S
      using learned trail unfolding cdclW-learned-clause-def raw-clauses-def by auto
    then have init-clss S ⊨pm mset-cls C + {#L#}
      using trail learned unfolding cdclW-learned-clause-def raw-clauses-def
      by (auto dest: true-clss-clss-in-imp-true-clss-cls)
    moreover have remove1-mset (− L) (mset-ccls D) + {#− L#} = mset-ccls D
      using DL by (auto simp: multiset-eq-iff)
    moreover have remove1-mset L (mset-cls C) + {#L#} = mset-cls C
      using CL by (auto simp: multiset-eq-iff)
    ultimately show ?case
      using learned T
      by (auto dest: mk-disjoint-insert
        simp add: cdclW-learned-clause-def raw-clauses-def
        intro!: true-clss-cls-union-mset-true-clss-cls-or-not-true-clss-cls-or[of - - L])
next
  case (restart T)
  then show ?case
    using learned learned-clss-restart-state[of T]
    by (auto
      simp: raw-clauses-def state-eq-def cdclW-learned-clause-def
      simp del: state-simp
      dest: true-clss-clssm-subsetE)
next
  case propagate
  then show ?case using learned by (auto simp: cdclW-learned-clause-def)
next
  case conflict
  then show ?case using learned
    by (fastforce simp: cdclW-learned-clause-def raw-clauses-def
      true-clss-clss-in-imp-true-clss-cls)
next
  case (forget U)
  then show ?case using learned
    by (auto simp: cdclW-learned-clause-def raw-clauses-def split: if-split-asm)
qed (auto simp: cdclW-learned-clause-def raw-clauses-def)

```



**lemma** *rtrancp-cdcl<sub>W</sub>-learned-clss*:  
**assumes**  
 $cdcl_W^{**} S S'$  **and**  
 $cdcl_W\text{-}M\text{-level-inv } S$   
 $cdcl_W\text{-learned-clause } S$   
**shows**  $cdcl_W\text{-learned-clause } S'$   
**using** *assms* **by induction** (*auto dest: cdcl<sub>W</sub>-learned-clss intro: rtrancp-cdcl<sub>W</sub>-consistent-inv*)

### 19.3.6 No alien atom in the state

This invariant means that all the literals are in the set of clauses.

**definition** *no-strange-atm*  $S' \longleftrightarrow$  (  
 $(\forall T. \text{conflicting } S' = \text{Some } T \longrightarrow \text{atms-of } T \subseteq \text{atms-of-mm } (\text{init-clss } S'))$   
 $\wedge (\forall L \text{ mark. } \text{Propagated } L \text{ mark} \in \text{set } (\text{trail } S') \longrightarrow \text{atms-of } (\text{mark}) \subseteq \text{atms-of-mm } (\text{init-clss } S'))$   
 $\wedge \text{atms-of-mm } (\text{learned-clss } S') \subseteq \text{atms-of-mm } (\text{init-clss } S')$   
 $\wedge \text{atm-of } ' (\text{lits-of-l } (\text{trail } S')) \subseteq \text{atms-of-mm } (\text{init-clss } S')$ )

**lemma** *no-strange-atm-decomp*:  
**assumes** *no-strange-atm*  $S$   
**shows**  $\text{conflicting } S = \text{Some } T \implies \text{atms-of } T \subseteq \text{atms-of-mm } (\text{init-clss } S)$   
**and**  $(\forall L \text{ mark. } \text{Propagated } L \text{ mark} \in \text{set } (\text{trail } S) \longrightarrow \text{atms-of } (\text{mark}) \subseteq \text{atms-of-mm } (\text{init-clss } S))$   
**and**  $\text{atms-of-mm } (\text{learned-clss } S) \subseteq \text{atms-of-mm } (\text{init-clss } S)$   
**and**  $\text{atm-of } ' (\text{lits-of-l } (\text{trail } S)) \subseteq \text{atms-of-mm } (\text{init-clss } S)$   
**using** *assms* **unfolding** *no-strange-atm-def* **by** *blast+*

**lemma** *no-strange-atm-S0* [*simp*]: *no-strange-atm* (*init-state*  $N$ )  
**unfolding** *no-strange-atm-def* **by** *auto*

**lemma** *in-atms-of-implies-atm-of-on-atms-of-ms*:  
 $C + \{\#L\# \} \in \# A \implies x \in \text{atms-of } C \implies x \in \text{atms-of-mm } A$   
**using** *multi-member-split* **by** *fastforce*

**lemma** *propagate-no-strange-atm-inv*:  
**assumes**  
 $\text{propagate } S T$  **and**  
 $\text{alien: no-strange-atm } S$   
**shows** *no-strange-atm*  $T$   
**using** *assms*(1)  
**proof** (*induction*)  
**case** (*propagate-rule*  $C L T$ ) **note**  $\text{confl} = \text{this}(1)$  **and**  $C = \text{this}(2)$  **and**  $C\text{-}L = \text{this}(3)$  **and**  
 $\text{tr} = \text{this}(4)$  **and**  $\text{undef} = \text{this}(5)$  **and**  $T = \text{this}(6)$   
**have** *atm-CL*:  $\text{atms-of } (\text{mset-clss } C) \subseteq \text{atms-of-mm } (\text{init-clss } S)$   
**using**  $C$  *alien* **unfolding** *no-strange-atm-def*  
**by** (*auto simp: raw-clauses-def atms-of-ms-def dest!: in-clss-mset-clss*)  
**show** ?*case*  
**unfolding** *no-strange-atm-def*  
**proof** (*intro conjI allI impI, goal-cases*)  
**case** 1  
**then show** ?*case*  
**using**  $\text{confl } T \text{ undef}$  **by** *auto*  
**next**  
**case** (2  $L' \text{ mark}'$ )  
**then show** ?*case*

```

using C-L T alien undef atm-CL

unfolding no-strange-atm-def raw-clauses-def apply auto by blast
next
  case (3)
  show ?case using T alien undef unfolding no-strange-atm-def by auto
next
  case (4)
  show ?case
    using T alien undef C-L atm-CL unfolding no-strange-atm-def by (auto simp: atms-of-def)
qed
qed

lemma in-atms-of-remove1-mset-in-atms-of:
   $x \in \text{atms-of } (\text{remove1-mset } L \ C) \implies x \in \text{atms-of } C$ 
using in-diffD unfolding atms-of-def by fastforce

lemma cdclW-no-strange-atm-explicit:
assumes
  cdclW S S' and
  lev: cdclW-M-level-inv S and
  conf:  $\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{atms-of } T \subseteq \text{atms-of-mm } (\text{init-clss } S)$  and
  marked:  $\forall L \text{ mark. } \text{Propagated } L \text{ mark} \in \text{set } (\text{trail } S)$ 
     $\longrightarrow \text{atms-of mark} \subseteq \text{atms-of-mm } (\text{init-clss } S)$  and
  learned:  $\text{atms-of-mm } (\text{learned-clss } S) \subseteq \text{atms-of-mm } (\text{init-clss } S)$  and
  trail:  $\text{atm-of } '(\text{lits-of-l } (\text{trail } S)) \subseteq \text{atms-of-mm } (\text{init-clss } S)$ 
shows
  ( $\forall T. \text{conflicting } S' = \text{Some } T \longrightarrow \text{atms-of } T \subseteq \text{atms-of-mm } (\text{init-clss } S')$ )  $\wedge$ 
  ( $\forall L \text{ mark. } \text{Propagated } L \text{ mark} \in \text{set } (\text{trail } S')$ 
     $\longrightarrow \text{atms-of } (\text{mark}) \subseteq \text{atms-of-mm } (\text{init-clss } S')$ )  $\wedge$ 
   $\text{atms-of-mm } (\text{learned-clss } S') \subseteq \text{atms-of-mm } (\text{init-clss } S') \wedge$ 
   $\text{atm-of } '(\text{lits-of-l } (\text{trail } S')) \subseteq \text{atms-of-mm } (\text{init-clss } S')$ 
  (is ?C S'  $\wedge$  ?M S'  $\wedge$  ?U S'  $\wedge$  ?V S')
using assms(1,2)
proof (induct rule: cdclW-all-induct-lev2)
  case (propagate C L T) note confl = this(1) and C-L = this(2) and tr = this(3) and undef =
  this(4)
  and T = this(5)
  show ?case
    using propagate-rule[OF propagate.hyps(1-3) - propagate.hyps(5,6), simplified]
    propagate.hyps(4) propagate-no-strange-atm-inv[of S T]
    conf marked learned trail unfolding no-strange-atm-def by presburger
next
  case (decide L)
  then show ?case using learned marked conf trail unfolding raw-clauses-def by auto
next
  case (skip L C M D)
  then show ?case using learned marked conf trail by auto
next
  case (conflict D T) note D-S = this(2) and T = this(4)
  have D:  $\text{atm-of } ' \text{set-mset } (\text{mset-cls } D) \subseteq \bigcup (\text{atms-of } ' (\text{set-mset } (\text{clauses } S)))$ 
    using D-S by (auto simp add: atms-of-def atms-of-ms-def)
  moreover {
    fix xa :: 'v literal
    assume a1:  $\text{atm-of } ' \text{set-mset } (\text{mset-cls } D) \subseteq (\bigcup x \in \text{set-mset } (\text{init-clss } S). \text{atms-of } x)$ 

```

```

     $\cup (\bigcup_{x \in \text{set-mset } (\text{learned-clss } S)}. \text{atms-of } x)$ 
assume  $a2$ :
     $(\bigcup_{x \in \text{set-mset } (\text{learned-clss } S)}. \text{atms-of } x) \subseteq (\bigcup_{x \in \text{set-mset } (\text{init-clss } S)}. \text{atms-of } x)$ 
assume  $xa \in \# \text{ mset-clss } D$ 
then have  $\text{atm-of } xa \in \text{UNION } (\text{set-mset } (\text{init-clss } S)) \text{ atms-of}$ 
    using  $a2 \ a1$  by  $(\text{metis } (\text{no-types}) \text{ Un-iff atm-of-lit-in-atms-of atms-of-def subset-Un-eq})$ 
then have  $\exists m \in \text{set-mset } (\text{init-clss } S). \text{atm-of } xa \in \text{atms-of } m$ 
    by blast
} note  $H = \text{this}$ 
ultimately show  $?case$  using conflict.premis T learned marked conf trail
    unfolding atms-of-def atms-of-ms-def raw-clauses-def
    by  $(\text{auto simp add: } H)$ 
next
case  $(\text{restart } T)$ 
then show  $?case$  using learned marked conf trail by auto
next
case  $(\text{forget } C \ T)$  note  $\text{confl} = \text{this}(1)$  and  $C = \text{this}(4)$  and  $C\text{-le} = \text{this}(5)$  and
     $T = \text{this}(6)$ 
have  $H: \bigwedge L \text{ mark. Propagated } L \text{ mark} \in \text{set } (\text{trail } S) \implies \text{atms-of mark} \subseteq \text{atms-of-mm } (\text{init-clss } S)$ 
    using marked by simp
show  $?case$  unfolding raw-clauses-def apply  $(\text{intro conjI})$ 
    using conf confl T trail C unfolding raw-clauses-def apply  $(\text{auto dest!:: } H)$ 
    using  $T \text{ trail } C \ C\text{-le}$  apply  $(\text{auto dest!:: } H)$ 
    using  $T \text{ learned } C\text{-le atms-of-ms-remove-subset[of set-mset (learned-clss } S)]$  apply auto
    using  $T \text{ trail } C\text{-le}$  apply  $(\text{auto simp: raw-clauses-def lits-of-def})$ 
done
next
case  $(\text{backtrack } K \ i \ M1 \ M2 \ L \ D \ T)$  note  $\text{confl} = \text{this}(1)$  and  $LD = \text{this}(2)$  and  $\text{decomp} = \text{this}(3)$ 
and
     $\text{undef} = \text{this}(7)$  and  $T = \text{this}(8)$ 
have  $?C \ T$ 
    using conf T decomp undef lev by  $(\text{auto simp: cdcl}_W\text{-M-level-inv-decomp})$ 
moreover have  $\text{set } M1 \subseteq \text{set } (\text{trail } S)$ 
    using decomp by auto
then have  $M: ?M \ T$ 
    using marked conf undef confl T decomp lev
    by  $(\text{auto simp: image-subset-iff raw-clauses-def cdcl}_W\text{-M-level-inv-decomp})$ 
moreover have  $?U \ T$ 
    using learned decomp conf confl T undef lev unfolding raw-clauses-def
    by  $(\text{auto simp: cdcl}_W\text{-M-level-inv-decomp})$ 
moreover have  $?V \ T$ 
    using  $M \ \text{conf confl trail } T \ \text{undef decomp lev } LD$ 
    by  $(\text{auto simp: cdcl}_W\text{-M-level-inv-decomp atms-of-def}$ 
         $\text{dest!:: get-all-marked-decomposition-exists-prepend})$ 
ultimately show  $?case$  by blast
next
case  $(\text{resolve } L \ C \ M \ D \ T)$  note  $\text{trail-S} = \text{this}(1)$  and  $\text{confl} = \text{this}(4)$  and  $T = \text{this}(7)$ 
let  $?T = \text{update-conflicting } (\text{Some } ((\text{remove-clit } (-L) \ D) \ !\cup \text{ ccls-of-clss } ((\text{remove-lit } L \ C))))$ 
     $(\text{tl-trail } S)$ 
have  $?C \ ?T$ 
    using confl trail-S conf marked by  $(\text{auto dest!:: in-atms-of-remove1-mset-in-atms-of})$ 
moreover have  $?M \ ?T$ 
    using confl trail-S conf marked by auto
moreover have  $?U \ ?T$ 
    using trail learned by auto

```

moreover have ?V ?T  
 using *confl trail-S trail* by *auto*  
 ultimately show ?case using *T* by *simp*  
 qed

**lemma** *cdcl<sub>W</sub>-no-strange-atm-inv*:  
 assumes *cdcl<sub>W</sub> S S'* and *no-strange-atm S* and *cdcl<sub>W</sub>-M-level-inv S*  
 shows *no-strange-atm S'*  
 using *cdcl<sub>W</sub>-no-strange-atm-explicit*[*OF assms(1)*] *assms(2,3)* **unfolding** *no-strange-atm-def* by *fast*

**lemma** *rtrancpl-cdcl<sub>W</sub>-no-strange-atm-inv*:  
 assumes *cdcl<sub>W</sub>\*\* S S'* and *no-strange-atm S* and *cdcl<sub>W</sub>-M-level-inv S*  
 shows *no-strange-atm S'*  
 using *assms* by *induction* (*auto intro: cdcl<sub>W</sub>-no-strange-atm-inv rtrancpl-cdcl<sub>W</sub>-consistent-inv*)

### 19.3.7 No duplicates all around

This invariant shows that there is no duplicate (no literal appearing twice in the formula). The last part could be proven using the previous invariant moreover.

**definition** *distinct-cdcl<sub>W</sub>-state (S::'st)*  
 $\longleftrightarrow ((\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{distinct-mset } T)$   
 $\wedge \text{distinct-mset-mset } (\text{learned-clss } S)$   
 $\wedge \text{distinct-mset-mset } (\text{init-clss } S)$   
 $\wedge (\forall L \text{ mark. } (\text{Propagated } L \text{ mark} \in \text{set } (\text{trail } S) \longrightarrow \text{distinct-mset } (\text{mark}))))$

**lemma** *distinct-cdcl<sub>W</sub>-state-decomp*:  
 assumes *distinct-cdcl<sub>W</sub>-state (S::'st)*  
 shows  $\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{distinct-mset } T$   
 and *distinct-mset-mset (learned-clss S)*  
 and *distinct-mset-mset (init-clss S)*  
 and  $\forall L \text{ mark. } (\text{Propagated } L \text{ mark} \in \text{set } (\text{trail } S) \longrightarrow \text{distinct-mset } (\text{mark}))$   
 using *assms* **unfolding** *distinct-cdcl<sub>W</sub>-state-def* by *blast+*

**lemma** *distinct-cdcl<sub>W</sub>-state-decomp-2*:  
 assumes *distinct-cdcl<sub>W</sub>-state (S::'st)*  
 shows *conflicting S = Some T  $\implies$  distinct-mset T*  
 using *assms* **unfolding** *distinct-cdcl<sub>W</sub>-state-def* by *auto*

**lemma** *distinct-cdcl<sub>W</sub>-state-S0-cdcl<sub>W</sub>[simp]*:  
*distinct-mset-mset (mset-clss N)  $\implies$  distinct-cdcl<sub>W</sub>-state (init-state N)*  
**unfolding** *distinct-cdcl<sub>W</sub>-state-def* by *auto*

**lemma** *distinct-cdcl<sub>W</sub>-state-inv*:  
 assumes  
   *cdcl<sub>W</sub> S S'* and  
   *lev-inv: cdcl<sub>W</sub>-M-level-inv S* and  
   *distinct-cdcl<sub>W</sub>-state S*  
 shows *distinct-cdcl<sub>W</sub>-state S'*  
 using *assms(1,2,2,3)*  
**proof** (*induct rule: cdcl<sub>W</sub>-all-induct-lev2*)  
 case (*backtrack L D K i M1 M2*)  
 then show ?case  
   using *lev-inv* **unfolding** *distinct-cdcl<sub>W</sub>-state-def*  
   by (*auto dest: get-all-marked-decomposition-incl simp: cdcl<sub>W</sub>-M-level-inv-decomp*)  
**next**

```

case restart
then show ?case
  unfolding distinct-cdclW-state-def distinct-mset-set-def raw-clauses-def
  using learned-clss-restart-state[of S] by auto
next
case resolve
then show ?case
  by (auto simp add: distinct-cdclW-state-def distinct-mset-set-def raw-clauses-def
    distinct-mset-single-add
    intro!: distinct-mset-union-mset)
qed (auto simp: distinct-cdclW-state-def distinct-mset-set-def raw-clauses-def
  dest!: in-clss-mset-clss in-diffD)

```

**lemma** *rtanclp-distinct-cdcl<sub>W</sub>-state-inv*:

```

assumes
  cdclW** S S' and
  cdclW-M-level-inv S and
  distinct-cdclW-state S
shows distinct-cdclW-state S'
using assms apply (induct rule: rtanclp-induct)
using distinct-cdclW-state-inv rtanclp-cdclW-consistent-inv by blast+

```

### 19.3.8 Conflicts and co

This invariant shows that each mark contains a contradiction only related to the previously defined variable.

**abbreviation** *every-mark-is-a-conflict* :: '*st*  $\Rightarrow$  bool' **where**

```

every-mark-is-a-conflict S  $\equiv$ 
 $\forall L \text{ mark } a \ b. \ a \ @ \ \text{Propagated } L \text{ mark } \# \ b = (\text{trail } S)$ 
 $\longrightarrow (b \models_{as} \text{CNot } (\text{mark} - \{\#L\}) \wedge L \in \# \text{ mark})$ 

```

**definition** *cdcl<sub>W</sub>-conflicting* *S*  $\equiv$

```

 $(\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{trail } S \models_{as} \text{CNot } T)$ 
 $\wedge \text{every-mark-is-a-conflict } S$ 

```

**lemma** *backtrack-atms-of-D-in-M1*:

**fixes** *M1* :: ('*v*, nat, '*v* clause) marked-lits

**assumes**

```

inv: cdclW-M-level-inv S and
undef: undefined-lit M1 L and
i: get-maximum-level (trail S) (mset-ccls (remove-clit L D))  $\equiv$  i and
decomp: (Marked K (Suc i)  $\#$  M1, M2)
 $\in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$  and
S-lvl: backtrack-lvl S = get-maximum-level (trail S) (mset-ccls D) and
S-conf: raw-conflicting S = Some D and
undef: undefined-lit M1 L and
T: T  $\sim$  cons-trail (Propagated L (cls-of-ccls D))

```

```

  (reduce-trail-to M1
    (add-learned-cls (cls-of-ccls D)
      (update-backtrack-lvl i
        (update-conflicting None S)))) and

```

*conf:  $\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{trail } S \models_{as} \text{CNot } T$*

**shows** *atms-of (mset-ccls (remove-clit L D))  $\subseteq$  atm-of ' lits-of-l (tl (trail T))*

**proof** (*rule ccontr*)

**let** ?*k* = *get-maximum-level (trail S) (mset-ccls D)*

```

let ?D = mset-ccls D
let ?D' = mset-ccls (remove-clit L D)
have trail S  $\models$ as CNot ?D using confl S-confl by auto
then have vars-of-D: atms-of ?D  $\subseteq$  atm-of ' lits-of-l (trail S) unfolding atms-of-def
  by (meson image-subsetI true-annots-CNot-all-atms-defined)

obtain M0 where M: trail S = M0 @ M2 @ Marked K (Suc i) # M1
  using decomp by auto

have max: ?k = length (get-all-levels-of-marked (M0 @ M2 @ Marked K (Suc i) # M1))
  using inv unfolding cdclW-M-level-inv-def S-lvl M by simp
assume a:  $\neg$  ?thesis
then obtain L' where
  L': L'  $\in$  atms-of ?D' and
  L'-notin-M1: L'  $\notin$  atm-of ' lits-of-l M1
  using T undef decomp inv by (auto simp: cdclW-M-level-inv-decomp)
then have L'-in: L'  $\in$  atm-of ' lits-of-l (M0 @ M2 @ Marked K (i + 1) # [])
  using vars-of-D unfolding M by (auto dest: in-atms-of-remove1-mset-in-atms-of)
then obtain L'' where
  L''  $\in$  # ?D' and
  L'': L' = atm-of L''
  using L' L'-notin-M1 unfolding atms-of-def by auto
have lev-L'':
  get-level (trail S) L'' = get-rev-level (Marked K (Suc i) # rev M2 @ rev M0) (Suc i) L''
  using L'-notin-M1 L'' M by (auto simp del: get-rev-level.simps)
have get-all-levels-of-marked (trail S) = rev [1..1+?k]
  using inv S-lvl unfolding cdclW-M-level-inv-def by auto
then have get-all-levels-of-marked (M0 @ M2) = rev [Suc (Suc i)..Suc ?k]
  unfolding M by (auto simp: rev-swap[symmetric] dest!: append-cons-eq-upt-length-i-end)

then have M: get-all-levels-of-marked M0 @ get-all-levels-of-marked M2
  = rev [Suc (Suc i)..Suc (length (get-all-levels-of-marked (M0 @ M2 @ Marked K (Suc i) # M1)))]
  unfolding max unfolding M by simp

have get-rev-level (Marked K (Suc i) # rev (M0 @ M2)) (Suc i) L''
   $\geq$  Min (set ((Suc i) # get-all-levels-of-marked (Marked K (Suc i) # rev (M0 @ M2))))
  using get-rev-level-ge-min-get-all-levels-of-marked[of L''
    rev (M0 @ M2 @ [Marked K (Suc i)]) Suc i] L'-in
  unfolding L'' by (fastforce simp add: lits-of-def)
also have Min (set ((Suc i) # get-all-levels-of-marked (Marked K (Suc i) # rev (M0 @ M2))))
  = Min (set ((Suc i) # get-all-levels-of-marked (rev (M0 @ M2)))) by auto
also have ... = Min (set ((Suc i) # get-all-levels-of-marked M0 @ get-all-levels-of-marked M2))
  by (simp add: Un-commute)
also have ... = Min (set ((Suc i) # [Suc (Suc i)..2 + length (get-all-levels-of-marked M0)
  + (length (get-all-levels-of-marked M2) + length (get-all-levels-of-marked M1))]))
  unfolding M by (auto simp add: Un-commute)
also have ... = Suc i by (auto intro: Min-eqI)
finally have get-rev-level (Marked K (Suc i) # rev (M0 @ M2)) (Suc i) L''  $\geq$  Suc i .
then have get-level (trail S) L''  $\geq$  i + 1
  using lev-L'' by simp
then have get-maximum-level (trail S) ?D'  $\geq$  i + 1
  using get-maximum-level-ge-get-level[OF «L''  $\in$  # ?D', of trail S] by auto
then show False using i by auto
qed

```

**lemma** *distinct-atms-of-incl-not-in-other*:

**assumes**

*a1*: *no-dup* (*M* @ *M'*) **and**

*a2*: *atms-of* *D*  $\subseteq$  *atm-of* ' *lits-of-l* *M'* **and**

*a3*: *x*  $\in$  *atms-of* *D*

**shows** *x*  $\notin$  *atm-of* ' *lits-of-l* *M*

**proof** –

**have** *ff1*:  $\bigwedge l$  *ms. undefined-lit* *ms* *l*  $\vee$  *atm-of* *l*

$\in$  *set* (*map* ( $\lambda m.$  *atm-of* (*lit-of* (*m*::('a, 'b, 'c) *marked-lit*))) *ms*)

**by** (*simp add: defined-lit-map*)

**have** *ff2*:  $\bigwedge a.$  *a*  $\notin$  *atms-of* *D*  $\vee$  *a*  $\in$  *atm-of* ' *lits-of-l* *M'*

**using** *a2* **by** (*meson subsetCE*)

**have** *ff3*:  $\bigwedge a.$  *a*  $\notin$  *set* (*map* ( $\lambda m.$  *atm-of* (*lit-of* *m*)) *M'*)

$\vee$  *a*  $\notin$  *set* (*map* ( $\lambda m.$  *atm-of* (*lit-of* *m*)) *M*)

**using** *a1* **by** (*metis* (*lifting*) *IntI* *distinct-append empty-iff map-append*)

**have**  $\forall L$  *a* *f*.  $\exists l.$  (*a*::'a)  $\notin$  *f* ' *L*  $\vee$  (*l*::'a *literal*)  $\in$  *L*)  $\wedge$  (*a*  $\notin$  *f* ' *L*  $\vee$  *f* *l* = *a*)

**by** *blast*

**then show** *x*  $\notin$  *atm-of* ' *lits-of-l* *M*

**using** *ff3 ff2 ff1 a3* **by** (*metis* (*no-types*) *Marked-Propagated-in-iff-in-lits-of-l*)

**qed**

**lemma** *cdcl<sub>W</sub>-propagate-is-conclusion*:

**assumes**

*cdcl<sub>W</sub>* *S* *S'* **and**

*inv*: *cdcl<sub>W</sub>-M-level-inv* *S* **and**

*decomp*: *all-decomposition-implies-m* (*init-clss* *S*) (*get-all-marked-decomposition* (*trail* *S*)) **and**

*learned*: *cdcl<sub>W</sub>-learned-clause* *S* **and**

*confl*:  $\forall T.$  *conflicting* *S* = *Some* *T*  $\longrightarrow$  *trail* *S*  $\models_{as}$  *CNot* *T* **and**

*alien*: *no-strange-atm* *S*

**shows** *all-decomposition-implies-m* (*init-clss* *S'*) (*get-all-marked-decomposition* (*trail* *S'*))

**using** *assms*(1,2)

**proof** (*induct rule: cdcl<sub>W</sub>-all-induct-lev2*)

**case** *restart*

**then show** ?*case* **by** *auto*

**next**

**case** *forget*

**then show** ?*case* **using** *decomp* **by** *auto*

**next**

**case** *conflict*

**then show** ?*case* **using** *decomp* **by** *auto*

**next**

**case** (*resolve* *L* *C* *M* *D*) **note** *tr* = *this*(1) **and** *T* = *this*(7)

**let** ?*decomp* = *get-all-marked-decomposition* *M*

**have** *M*: *set* ?*decomp* = *insert* (*hd* ?*decomp*) (*set* (*tl* ?*decomp*))

**by** (*cases* ?*decomp*) *auto*

**show** ?*case*

**using** *decomp* *tr* *T* **unfolding** *all-decomposition-implies-def*

**by** (*cases* *hd* (*get-all-marked-decomposition* *M*))

(*auto simp: M*)

**next**

**case** (*skip* *L* *C'* *M* *D*) **note** *tr* = *this*(1) **and** *T* = *this*(5)

**have** *M*: *set* (*get-all-marked-decomposition* *M*)

= *insert* (*hd* (*get-all-marked-decomposition* *M*)) (*set* (*tl* (*get-all-marked-decomposition* *M*)))

**by** (*cases* *get-all-marked-decomposition* *M*) *auto*

**show** ?*case*

```

    using decomp tr T unfolding all-decomposition-implies-def
    by (cases hd (get-all-marked-decomposition M))
      (auto simp add: M)
next
case decide note S = this(1) and undef = this(2) and T = this(4)
show ?case using decomp T undef unfolding S all-decomposition-implies-def by auto
next
case (propagate C L T) note propa = this(2) and L = this(3) and undef = this(5) and T = this(6)
obtain a y where ay: hd (get-all-marked-decomposition (trail S)) = (a, y)
  by (cases hd (get-all-marked-decomposition (trail S)))
then have M: trail S = y @ a using get-all-marked-decomposition-decomp by blast
have M': set (get-all-marked-decomposition (trail S))
  = insert (a, y) (set (tl (get-all-marked-decomposition (trail S))))
  using ay by (cases get-all-marked-decomposition (trail S)) auto
have unmark-l a ∪ set-mset (init-clss S) ⊨ps unmark-l y
  using decomp ay unfolding all-decomposition-implies-def
  by (cases get-all-marked-decomposition (trail S)) fastforce+
then have a-Un-N-M: unmark-l a ∪ set-mset (init-clss S)
  ⊨ps unmark-l (trail S)
  unfolding M by (auto simp add: all-in-true-clss-clss image-Un)

have unmark-l a ∪ set-mset (init-clss S) ⊨p {#L#} (is ?I ⊨p -)
proof (rule true-clss-clss-plus-CNot)
  show ?I ⊨p remove1-mset L (mset-clss C) + {#L#}
  apply (rule true-clss-clss-in-imp-true-clss-clss[of -
    set-mset (init-clss S) ∪ set-mset (learned-clss S)])
  using learned propa L by (auto simp: raw-clauses-def cdclW-learned-clause-def
    true-annot-CNot-diff)
next
have unmark-l (trail S) ⊨ps CNot (remove1-mset L (mset-clss C))
  using ⟨(trail S) ⊨as CNot (remove1-mset L (mset-clss C))⟩ true-annots-true-clss-clss
  by blast
then show ?I ⊨ps CNot (remove1-mset L (mset-clss C))
  using a-Un-N-M true-clss-clss-left-right true-clss-clss-union-l-r by blast
qed
moreover have ∧aa b.
  ∀ (Ls, seen) ∈ set (get-all-marked-decomposition (y @ a)).
    unmark-l Ls ∪ set-mset (init-clss S) ⊨ps unmark-l seen
  ⇒ (aa, b) ∈ set (tl (get-all-marked-decomposition (y @ a)))
  ⇒ unmark-l aa ∪ set-mset (init-clss S) ⊨ps unmark-l b
  by (metis (no-types, lifting) case-prod-conv get-all-marked-decomposition-never-empty-sym
    list.collapse list.set-intros(2))

ultimately show ?case
  using decomp T undef unfolding ay all-decomposition-implies-def
  using M ⟨unmark-l a ∪ set-mset (init-clss S) ⊨ps unmark-l y⟩
  ay by auto
next
case (backtrack K i M1 M2 L D T) note conf = this(1) and LD = this(2) and decomp' = this(3)
and
  lev-L = this(4) and undef = this(7) and T = this(8)
let ?D = mset-ccls D
let ?D' = mset-ccls (remove-clit L D)
have ∀ l ∈ set M2. ¬is-marked l
  using get-all-marked-decomposition-snd-not-marked decomp' by blast

```



```

obtain  $M0$  where  $M$ :  $trail\ S = M0\ @\ M2\ @\ Marked\ K\ (i + 1)\ \# \ M1$ 
using decomp' by auto
show ?case unfolding all-decomposition-implies-def
proof
  fix  $x$ 
  assume  $x \in set\ (get-all-marked-decomposition\ (trail\ T))$ 
  then have  $x$ :  $x \in set\ (get-all-marked-decomposition\ (Propagated\ L\ ?D\ \# \ M1))$ 
    using  $T\ decomp'$  undef inv by (simp add: cdclW-M-level-inv-decomp)
  let  $?m = get-all-marked-decomposition\ (Propagated\ L\ ?D\ \# \ M1)$ 
  let  $?hd = hd\ ?m$ 
  let  $?tl = tl\ ?m$ 
  consider
    ( $hd$ )  $x = ?hd$ 
    | ( $tl$ )  $x \in set\ ?tl$ 
  using  $x$  by (cases ?m) auto
  then show case x of (Ls, seen)  $\Rightarrow$  unmark-l Ls  $\cup$  set-mset (init-clss T)
     $\models_{ps}$  unmark-l seen
  proof cases
    case  $tl$ 
    then have  $x \in set\ (get-all-marked-decomposition\ (trail\ S))$ 
      using tl-get-all-marked-decomposition-skip-some[ $x$ ] by (simp add: list.set-sel(2) M)
    then show ?thesis
      using decomp learned decomp confl alien inv T undef M
      unfolding all-decomposition-implies-def cdclW-M-level-inv-def
      by auto
    next
    case  $hd$ 
    obtain  $M1'\ M1''$  where  $M1$ :  $hd\ (get-all-marked-decomposition\ M1) = (M1',\ M1'')$ 
      by (cases hd (get-all-marked-decomposition M1))
    then have  $x'$ :  $x = (M1',\ Propagated\ L\ ?D\ \# \ M1'')$ 
      using  $\langle x = ?hd \rangle$  by auto
    have  $(M1',\ M1'') \in set\ (get-all-marked-decomposition\ (trail\ S))$ 
      using  $M1[symmetric]$  hd-get-all-marked-decomposition-skip-some[OF  $M1[symmetric]$ ,
        of  $M0\ @\ M2 - i + 1$ ] unfolding  $M$  by fastforce
    then have  $1$ :  $unmark-l\ M1' \cup set-mset\ (init-clss\ S) \models_{ps} unmark-l\ M1''$ 
      using decomp unfolding all-decomposition-implies-def by auto

  moreover
    have vars-of-D: atms-of ?D'  $\subseteq$  atm-of ' lits-of-l M1
      using backtrack-atms-of-D-in-M1[of  $S\ M1\ L\ D\ i\ K\ M2\ T$ ] backtrack.hyps inv conf confl
      by (auto simp: cdclW-M-level-inv-decomp)
    have no-dup (trail S) using inv by (auto simp: cdclW-M-level-inv-decomp)
    then have vars-in-M1:
       $\forall x \in atms-of\ ?D'.\ x \notin atm-of\ ' \ lits-of-l\ (M0\ @\ M2\ @\ Marked\ K\ (i + 1)\ \# \ [])$ 
      using vars-of-D distinct-atms-of-incl-not-in-other[of
         $M0\ @\ M2\ @\ Marked\ K\ (i + 1)\ \# \ []\ M1$ ] unfolding  $M$  by auto
    have  $trail\ S \models_{as} CNot\ (remove1-mset\ L\ (mset-ccls\ D))$ 
      using conf confl LD unfolding M true-annots-true-clss-def-iff-negation-in-model
      by (auto dest!: Multiset.in-diffD)
    then have  $M1 \models_{as} CNot\ ?D'$ 
      using vars-in-M1 true-annots-remove-if-notin-vars[of  $M0\ @\ M2\ @\ Marked\ K\ (i + 1)\ \# \ []$ 
         $M1\ CNot\ ?D'$ ] conf confl unfolding  $M$  lits-of-def by simp
    have  $M1 = M1''\ @\ M1'$  by (simp add: M1 get-all-marked-decomposition-decomp)
    have  $TT$ :  $unmark-l\ M1' \cup set-mset\ (init-clss\ S) \models_{ps} CNot\ ?D'$ 
      using true-annots-true-clss-clss[OF  $\langle M1 \models_{as} CNot\ ?D' \rangle$ ] true-clss-clss-left-right[OF  $1$ ]

```

```

    unfolding (M1 = M1'' @ M1') by (auto simp add: inf-sup-aci(5,7))
  have init-clss S  $\models_{pm}$  ?D' + {#L#}
    using conf learned confL LD unfolding cdclW-learned-clause-def by auto
  then have T': unmark-l M1'  $\cup$  set-mset (init-clss S)  $\models_p$  ?D' + {#L#} by auto
  have atms-of (?D' + {#L#})  $\subseteq$  atms-of-mm (clauses S)
    using alien conf LD unfolding no-strange-atm-def raw-clauses-def by auto
  then have unmark-l M1'  $\cup$  set-mset (init-clss S)  $\models_p$  {#L#}
    using true-clss-clss-plus-CNot[OF T' TT] by auto

  ultimately show ?thesis
    using T' T decomp' undef inv unfolding x' by (simp add: cdclW-M-level-inv-decomp)
qed
qed
qed

lemma cdclW-propagate-is-false:
  assumes
    cdclW S S' and
    lev: cdclW-M-level-inv S and
    learned: cdclW-learned-clause S and
    decomp: all-decomposition-implies-m (init-clss S) (get-all-marked-decomposition (trail S)) and
    confl:  $\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{trail } S \models_{as} \text{CNot } T$  and
    alien: no-strange-atm S and
    mark-confL: every-mark-is-a-conflict S
  shows every-mark-is-a-conflict S'
  using assms(1,2)
proof (induct rule: cdclW-all-induct-lev2)
  case (propagate C L T) note LC = this(3) and confl = this(4) and undef = this(5) and T =
  this(6)
  show ?case
  proof (intro allI impI)
    fix L' mark a b
    assume a @ Propagated L' mark # b = trail T
    then consider
      (hd) a = [] and L = L' and mark = mset-clss C and b = trail S
      | (tl) tl a @ Propagated L' mark # b = trail S
    using T undef by (cases a) fastforce+
    then show b  $\models_{as}$  CNot (mark - {#L'#})  $\wedge$  L'  $\in$  # mark
      using mark-confL confl LC by cases auto
  qed
next
  case (decide L) note undef[simp] = this(2) and T = this(4)
  have  $\bigwedge a \text{ La mark } b. a @ \text{Propagated La mark \# } b = \text{Marked L (backtrack-lvl S+1) \# trail S}$ 
 $\implies \text{tl } a @ \text{Propagated La mark \# } b = \text{trail S}$  by (case-tac a) auto
  then show ?case using mark-confL T unfolding decide.hyps(1) by fastforce
next
  case (skip L C' M D T) note tr = this(1) and T = this(5)
  show ?case
  proof (intro allI impI)
    fix L' mark a b
    assume a @ Propagated L' mark # b = trail T
    then have a @ Propagated L' mark # b = M using tr T by simp
    then have (Propagated L C' # a) @ Propagated L' mark # b = Propagated L C' # M by auto
    moreover have  $\forall \text{La mark } a b. a @ \text{Propagated La mark \# } b = \text{Propagated L C' \# M}$ 
 $\longrightarrow b \models_{as} \text{CNot (mark - \{ \#La\# \})} \wedge \text{La} \in \# \text{ mark}$ 

```

```

    using mark-confl unfolding skip.hyps(1) by simp
    ultimately show  $b \models_{as} CNot (mark - \{\#L'\# \}) \wedge L' \in \# \text{ mark}$  by blast
  qed
next
case (conflict D)
then show ?case using mark-confl by simp
next
case (resolve L C M D T) note tr-S = this(1) and T = this(7)
show ?case unfolding resolve.hyps(1)
proof (intro allI impI)
  fix L' mark a b
  assume a @ Propagated L' mark # b = trail T
  then have (Propagated L (mset-cls (L !++ C)) # a) @ Propagated L' mark # b
    = Propagated L (mset-cls (L !++ C)) # M
  using T tr-S by auto
  then show  $b \models_{as} CNot (mark - \{\#L'\# \}) \wedge L' \in \# \text{ mark}$ 
  using mark-confl unfolding tr-S by (metis Cons-eq-appendI list.sel(3))
qed
next
case restart
then show ?case by auto
next
case forget
then show ?case using mark-confl by auto
next
case (backtrack K i M1 M2 L D T) note conf = this(1) and LD = this(2) and decomp = this(3)
and
  undef = this(7) and T = this(8)
have  $\forall l \in \text{set } M2. \neg \text{is-marked } l$ 
using get-all-marked-decomposition-snd-not-marked decomp by blast
obtain M0 where M: trail S = M0 @ M2 @ Marked K (i + 1) # M1
using decomp by auto
have [simp]: trail (reduce-trail-to M1 (add-learned-cls (cls-of-ccls (insert-ccls L D))
  (update-backtrack-lvl i (update-conflicting None S)))) = M1
using decomp lev by (auto simp: cdclW-M-level-inv-decomp)
let ?D = mset-ccls D
let ?D' = mset-ccls (remove-clit L D)
show ?case
proof (intro allI impI)
  fix La :: 'v literal and mark :: 'v literal multiset and
    a b :: ('v, nat, 'v literal multiset) marked-lit list
  assume a @ Propagated La mark # b = trail T
  then consider
    (hd-tr) a = [] and
      (Propagated La mark :: ('v, nat, 'v literal multiset) marked-lit)
      = Propagated L ?D and
      b = M1
  | (tl-tr) tl a @ Propagated La mark # b = M1
  using M T decomp undef lev by (cases a) (auto simp: cdclW-M-level-inv-def)
then show  $b \models_{as} CNot (mark - \{\#La\# \}) \wedge La \in \# \text{ mark}$ 
proof cases
  case hd-tr note A = this(1) and P = this(2) and b = this(3)
  have trail S  $\models_{as} CNot ?D$  using conf confl by auto
  then have vars-of-D: atms-of ?D  $\subseteq$  atm-of ' lits-of-l (trail S)
  unfolding atms-of-def

```

```

    by (meson image-subsetI true-annots-CNot-all-atms-defined)
  have vars-of-D: atms-of ?D'  $\subseteq$  atm-of ' lits-of-l M1
    using backtrack-atms-of-D-in-M1[of S M1 L D i K M2 T] T backtrack lev confl
    by (auto simp: cdclW-M-level-inv-decomp)
  have no-dup (trail S) using lev by (auto simp: cdclW-M-level-inv-decomp)
  then have  $\forall x \in \text{atms-of } ?D'. x \notin \text{atm-of ' lits-of-l } (M0 @ M2 @ \text{Marked } K (i + 1) \# [])$ 
    using vars-of-D distinct-atms-of-incl-not-in-other[of
      M0 @ M2 @ Marked K (i + 1)  $\# []$  M1] unfolding M by auto
  then have M1  $\models_{as}$  CNot ?D'
    using true-annots-remove-if-notin-vars[of M0 @ M2 @ Marked K (i + 1)  $\# []$ 
      M1 CNot ?D']  $\langle$ trail S  $\models_{as}$  CNot ?D $\rangle$  unfolding M lits-of-def
    by (simp add: true-annot-CNot-diff)
  then show b  $\models_{as}$  CNot (mark - {#La#})  $\wedge$  La  $\in \#$  mark
    using P LD b by auto
next
case tl-tr
then obtain c' where c' @ Propagated La mark  $\#$  b = trail S
  unfolding M by auto
then show b  $\models_{as}$  CNot (mark - {#La#})  $\wedge$  La  $\in \#$  mark
  using mark-confl by auto
qed
qed
qed

lemma cdclW-conflicting-is-false:
  assumes
    cdclW S S' and
    M-lev: cdclW-M-level-inv S and
    confl-inv:  $\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{trail } S \models_{as} \text{CNot } T$  and
    marked-confl:  $\forall L \text{ mark } a \ b. a @ \text{Propagated } L \text{ mark } \# b = (\text{trail } S) \longrightarrow (b \models_{as} \text{CNot } (\text{mark} - \{ \#L\ \}) \wedge L \in \# \text{ mark})$  and
    dist: distinct-cdclW-state S
  shows  $\forall T. \text{conflicting } S' = \text{Some } T \longrightarrow \text{trail } S' \models_{as} \text{CNot } T$ 
  using assms(1,2)
proof (induct rule: cdclW-all-induct-lev2)
case (skip L C' M D T) note tr-S = this(1) and confl = this(2) and L-D = this(3) and T = this(5)
let ?D = mset-ccls D
have D: Propagated L C'  $\#$  M  $\models_{as}$  CNot (mset-ccls D) using assms skip by auto
moreover
have L  $\notin \#$  ?D
proof (rule ccontr)
assume  $\neg$  ?thesis
then have - L  $\in$  lits-of-l M
  using in-CNot-implies-uminus(2)[of L ?D Propagated L C'  $\#$  M]
   $\langle$ Propagated L C'  $\#$  M  $\models_{as}$  CNot ?D $\rangle$  by simp
then show False
  by (metis (no-types, hide-lams) M-lev cdclW-M-level-inv-decomp(1) consistent-interp-def
    image-insert insert-iff list.set(2) lits-of-def marked-lit.sel(2) tr-S)
qed
ultimately show ?case
  using tr-S confl L-D T unfolding cdclW-M-level-inv-def
  by (auto intro: true-annots-CNot-lit-of-notin-skip)
next
case (resolve L C M D T) note tr = this(1) and LC = this(2) and confl = this(4) and LD =

```

```

this(5)
and T = this(7)
let ?C = remove1-mset L (mset-cls C)
let ?D = remove1-mset (-L) (mset-ccls D)
show ?case
proof (intro allI impI)
  fix T'
  have tl (trail S)  $\models_{as}$  CNot ?C using tr marked-confl by fastforce
  moreover
    have distinct-mset (?D + {#- L#}) using confl dist LD
      unfolding distinct-cdclW-state-def by auto
    then have -L  $\notin$  # ?D unfolding distinct-mset-def
      by (meson <distinct-mset (?D + {#- L#})> distinct-mset-single-add)
    have M  $\models_{as}$  CNot ?D
    proof -
      have Propagated L (?C + {#L#}) # M  $\models_{as}$  CNot ?D  $\cup$  CNot {#- L#}
        using confl tr confl-inv LC by (metis CNot-plus LD insert-DiffM2 option.simps(9))
      then show ?thesis
        using M-lev <- L  $\notin$  # ?D tr true-annots-lit-of-notin-skip
        unfolding cdclW-M-level-inv-def by force
    qed
  moreover assume conflicting T = Some T'
  ultimately
    show trail T  $\models_{as}$  CNot T'
    using tr T by auto
  qed
qed (auto simp: M-lev cdclW-M-level-inv-decomp)

```

**lemma** *cdcl<sub>W</sub>-conflicting-decomp*:

```

assumes cdclW-conflicting S
shows  $\forall T. \text{conflicting } S = \text{Some } T \longrightarrow \text{trail } S \models_{as} \text{CNot } T$ 
and  $\forall L \text{ mark } a \ b. a @ \text{Propagated } L \text{ mark } \# \ b = (\text{trail } S)$ 
 $\longrightarrow (b \models_{as} \text{CNot } (\text{mark} - \{ \#L\# \}) \wedge L \in \# \text{ mark})$ 
using assms unfolding cdclW-conflicting-def by blast+

```

**lemma** *cdcl<sub>W</sub>-conflicting-decomp2*:

```

assumes cdclW-conflicting S and conflicting S = Some T
shows trail S  $\models_{as}$  CNot T
using assms unfolding cdclW-conflicting-def by blast+

```

**lemma** *cdcl<sub>W</sub>-conflicting-S0-cdcl<sub>W</sub>[simp]*:

```

cdclW-conflicting (init-state N)
unfolding cdclW-conflicting-def by auto

```

### 19.3.9 Putting all the invariants together

**lemma** *cdcl<sub>W</sub>-all-inv*:

```

assumes
  cdclW: cdclW S S' and
  1: all-decomposition-implies-m (init-clss S) (get-all-marked-decomposition (trail S)) and
  2: cdclW-learned-clause S and
  4: cdclW-M-level-inv S and
  5: no-strange-atm S and
  7: distinct-cdclW-state S and
  8: cdclW-conflicting S
shows

```

*all-decomposition-implies-m* (*init-clss*  $S'$ ) (*get-all-marked-decomposition* (*trail*  $S'$ )) **and**  
*cdcl<sub>W</sub>-learned-clause*  $S'$  **and**  
*cdcl<sub>W</sub>-M-level-inv*  $S'$  **and**  
*no-strange-atm*  $S'$  **and**  
*distinct-cdcl<sub>W</sub>-state*  $S'$  **and**  
*cdcl<sub>W</sub>-conflicting*  $S'$   
**proof** –  
**show**  $S1$ : *all-decomposition-implies-m* (*init-clss*  $S'$ ) (*get-all-marked-decomposition* (*trail*  $S'$ ))  
**using** *cdcl<sub>W</sub>-propagate-is-conclusion*[*OF* *cdcl<sub>W</sub>* 4 1 2 - 5] 8 **unfolding** *cdcl<sub>W</sub>-conflicting-def*  
**by** *blast*  
**show**  $S2$ : *cdcl<sub>W</sub>-learned-clause*  $S'$  **using** *cdcl<sub>W</sub>-learned-clss*[*OF* *cdcl<sub>W</sub>* 2 4] .  
**show**  $S4$ : *cdcl<sub>W</sub>-M-level-inv*  $S'$  **using** *cdcl<sub>W</sub>-consistent-inv*[*OF* *cdcl<sub>W</sub>* 4] .  
**show**  $S5$ : *no-strange-atm*  $S'$  **using** *cdcl<sub>W</sub>-no-strange-atm-inv*[*OF* *cdcl<sub>W</sub>* 5 4] .  
**show**  $S7$ : *distinct-cdcl<sub>W</sub>-state*  $S'$  **using** *distinct-cdcl<sub>W</sub>-state-inv*[*OF* *cdcl<sub>W</sub>* 4 7] .  
**show**  $S8$ : *cdcl<sub>W</sub>-conflicting*  $S'$   
**using** *cdcl<sub>W</sub>-conflicting-is-false*[*OF* *cdcl<sub>W</sub>* 4 - - 7] 8 *cdcl<sub>W</sub>-propagate-is-false*[*OF* *cdcl<sub>W</sub>* 4 2 1 -  
5]  
**unfolding** *cdcl<sub>W</sub>-conflicting-def* **by** *fast*  
**qed**

**lemma** *rtranclp-cdcl<sub>W</sub>-all-inv*:

**assumes**

*cdcl<sub>W</sub>*: *rtranclp* *cdcl<sub>W</sub>*  $S$   $S'$  **and**

1: *all-decomposition-implies-m* (*init-clss*  $S$ ) (*get-all-marked-decomposition* (*trail*  $S$ )) **and**

2: *cdcl<sub>W</sub>-learned-clause*  $S$  **and**

4: *cdcl<sub>W</sub>-M-level-inv*  $S$  **and**

5: *no-strange-atm*  $S$  **and**

7: *distinct-cdcl<sub>W</sub>-state*  $S$  **and**

8: *cdcl<sub>W</sub>-conflicting*  $S$

**shows**

*all-decomposition-implies-m* (*init-clss*  $S'$ ) (*get-all-marked-decomposition* (*trail*  $S'$ )) **and**

*cdcl<sub>W</sub>-learned-clause*  $S'$  **and**

*cdcl<sub>W</sub>-M-level-inv*  $S'$  **and**

*no-strange-atm*  $S'$  **and**

*distinct-cdcl<sub>W</sub>-state*  $S'$  **and**

*cdcl<sub>W</sub>-conflicting*  $S'$

**using** *assms*

**proof** (*induct rule*: *rtranclp-induct*)

**case** *base*

**case** 1 **then** **show** ?*case* **by** *blast*

**case** 2 **then** **show** ?*case* **by** *blast*

**case** 3 **then** **show** ?*case* **by** *blast*

**case** 4 **then** **show** ?*case* **by** *blast*

**case** 5 **then** **show** ?*case* **by** *blast*

**case** 6 **then** **show** ?*case* **by** *blast*

**next**

**case** (*step*  $S'$   $S''$ ) **note**  $H = \text{this}$

**case** 1 **with**  $H(3-7)$ [*OF* *this*(1-6)] **show** ?*case* **using** *cdcl<sub>W</sub>-all-inv*[*OF*  $H(2)$ ]

$H$  **by** *presburger*

**case** 2 **with**  $H(3-7)$ [*OF* *this*(1-6)] **show** ?*case* **using** *cdcl<sub>W</sub>-all-inv*[*OF*  $H(2)$ ]

$H$  **by** *presburger*

**case** 3 **with**  $H(3-7)$ [*OF* *this*(1-6)] **show** ?*case* **using** *cdcl<sub>W</sub>-all-inv*[*OF*  $H(2)$ ]

$H$  **by** *presburger*

**case** 4 **with**  $H(3-7)$ [*OF* *this*(1-6)] **show** ?*case* **using** *cdcl<sub>W</sub>-all-inv*[*OF*  $H(2)$ ]

$H$  **by** *presburger*

**case 5 with**  $H(3-7)[OF \text{ this}(1-6)]$  **show**  $?case$  **using**  $cdcl_W\text{-all-inv}[OF H(2)]$   
 $H$  **by** *presburger*  
**case 6 with**  $H(3-7)[OF \text{ this}(1-6)]$  **show**  $?case$  **using**  $cdcl_W\text{-all-inv}[OF H(2)]$   
 $H$  **by** *presburger*  
**qed**

**lemma** *all-invariant-S0-cdcl<sub>W</sub>*:

**assumes** *distinct-mset-mset* (*mset-clss*  $N$ )

**shows**

$all\text{-decomposition-implies-}m \text{ (init-clss (init-state } N))$   
 $(get\text{-all-marked-decomposition (trail (init-state } N)))$  **and**  
 $cdcl_W\text{-learned-clause (init-state } N)$  **and**  
 $\forall T. \text{ conflicting (init-state } N) = \text{Some } T \longrightarrow (trail (init-state } N)) \models_{as} CNot \ T$  **and**  
 $no\text{-strange-atm (init-state } N)$  **and**  
 $consistent\text{-interp (lits-of-l (trail (init-state } N)))$  **and**  
 $\forall L \text{ mark } a \ b. a \ @ \ \text{Propagated } L \text{ mark } \# \ b = \text{trail (init-state } N) \longrightarrow$   
 $(b \models_{as} CNot \ (\text{mark} - \{\#L\}) \wedge L \in \# \text{ mark})$  **and**  
 $distinct\text{-cdcl}_W\text{-state (init-state } N)$

**using** *assms* **by** *auto*

**lemma** *cdcl<sub>W</sub>-only-propagated-vars-unsat*:

**assumes**

$marked: \forall x \in \text{set } M. \neg \text{is-marked } x$  **and**  
 $DN: D \in \# \text{ clauses } S$  **and**  
 $D: M \models_{as} CNot \ D$  **and**  
 $inv: all\text{-decomposition-implies-}m \ N \ (get\text{-all-marked-decomposition } M)$  **and**  
 $state: \text{state } S = (M, N, U, k, C)$  **and**  
 $learned\text{-cl: } cdcl_W\text{-learned-clause } S$  **and**  
 $atm\text{-incl: } no\text{-strange-atm } S$

**shows** *unsatisfiable* (*set-mset*  $N$ )

**proof** (*rule ccontr*)

**assume**  $\neg \text{unsatisfiable (set-mset } N)$

**then obtain**  $I$  **where**

$I: I \models_s \text{set-mset } N$  **and**  
 $cons: consistent\text{-interp } I$  **and**  
 $tot: total\text{-over-}m \ I \ (\text{set-mset } N)$   
**unfolding** *satisfiable-def* **by** *auto*

**have**  $atms\text{-of-mm } N \cup atms\text{-of-mm } U = atms\text{-of-mm } N$

**using**  $atm\text{-incl state}$  **unfolding**  $total\text{-over-}m\text{-def}$   $no\text{-strange-atm-def}$   
**by** (*auto simp add: raw-clauses-def*)

**then have**  $total\text{-over-}m \ I \ (\text{set-mset } N)$  **using**  $tot$  **unfolding**  $total\text{-over-}m\text{-def}$  **by** *auto*

**moreover then have**  $total\text{-over-}m \ I \ (\text{set-mset (learned-clss } S))$

**using**  $atm\text{-incl state}$  **unfolding**  $no\text{-strange-atm-def}$   $total\text{-over-}m\text{-def}$   $total\text{-over-set-def}$   
**by** *auto*

**moreover have**  $N \models_{psm} U$  **using**  $learned\text{-cl state}$  **unfolding**  $cdcl_W\text{-learned-clause-def}$  **by** *auto*

**ultimately have**  $I \models D$

**using**  $I \ DN \ cons \ state$  **unfolding**  $true\text{-clss-clss-def}$   $true\text{-clss-def}$   $Ball\text{-def}$   
**by** (*auto simp add: raw-clauses-def*)

**have**  $l0: \{\text{unmark } L \mid L. \text{is-marked } L \wedge L \in \text{set } M\} = \{\}$  **using**  $marked$  **by** *auto*

**have**  $atms\text{-of-ms (set-mset } N \cup \text{unmark-l } M) = atms\text{-of-mm } N$

**using**  $atm\text{-incl state}$  **unfolding**  $no\text{-strange-atm-def}$  **by** *auto*

**then have**  $total\text{-over-}m \ I \ (\text{set-mset } N \cup \text{unmark-l } M)$

**using**  $tot$  **unfolding**  $total\text{-over-}m\text{-def}$  **by** *auto*

```

then have  $I \models_s \text{unmark-l } M$ 
  using all-decomposition-implies-propagated-lits-are-implied[OF inv] cons I
  unfolding true-clss-clss-def l0 by auto
then have  $IM: I \models_s \text{unmark-l } M$  by auto
{
  fix  $K$ 
  assume  $K \in \# D$ 
  then have  $-K \in \text{lits-of-l } M$ 
    using D unfolding true-annots-def Ball-def CNot-def true-annot-def true-clss-def true-lit-def
    Bex-def by force
    then have  $-K \in I$  using  $IM$  true-clss-singleton-lit-of-implies-incl lits-of-def by fastforce }
  then have  $\neg I \models D$  using cons unfolding true-clss-def true-lit-def consistent-interp-def by auto
  then show False using I-D by blast
}
qed

```

We have actually a much stronger theorem, namely *all-decomposition-implies ?N* (*get-all-marked-decomposition ?M*)  $\implies ?N \cup \{\text{unmark } L \mid L. \text{is-marked } L \wedge L \in \text{set } ?M\} \models_{ps} \text{unmark-l } ?M$ , that show that the only choices we made are marked in the formula

```

lemma
  assumes all-decomposition-implies-m N (get-all-marked-decomposition M)
  and  $\forall m \in \text{set } M. \neg \text{is-marked } m$ 
  shows set-mset N  $\models_{ps} \text{unmark-l } M$ 
proof -
  have  $T: \{\text{unmark } L \mid L. \text{is-marked } L \wedge L \in \text{set } M\} = \{\}$  using assms(2) by auto
  then show ?thesis
    using all-decomposition-implies-propagated-lits-are-implied[OF assms(1)] unfolding T by simp
qed

```

**lemma** *conflict-with-false-implies-unsat*:

```

  assumes
    cdclW: cdclW S S' and
    lev: cdclW-M-level-inv S and
    [simp]: conflicting S' = Some {#} and
    learned: cdclW-learned-clause S
  shows unsatisfiable (set-mset (init-clss S))
  using assms
proof -
  have cdclW-learned-clause S' using cdclW-learned-clss cdclW learned lev by auto
  then have init-clss S'  $\models_{pm} \{\#\}$  using assms(3) unfolding cdclW-learned-clause-def by auto
  then have init-clss S  $\models_{pm} \{\#\}$ 
    using cdclW-init-clss[OF assms(1) lev] by auto
  then show ?thesis unfolding satisfiable-def true-clss-clss-def by auto
qed

```

**lemma** *conflict-with-false-implies-terminated*:

```

  assumes cdclW S S'
  and conflicting S = Some {#}
  shows False
  using assms by (induct rule: cdclW-all-induct) auto

```

### 19.3.10 No tautology is learned

This is a simple consequence of all we have shown previously. It is not strictly necessary, but helps finding a better bound on the number of learned clauses.



**lemma** *learned-clss-are-not-tautologies*:  
**assumes**  
*cdcl<sub>W</sub> S S' and*  
*lev: cdcl<sub>W</sub>-M-level-inv S and*  
*conflicting: cdcl<sub>W</sub>-conflicting S and*  
*no-tauto:  $\forall s \in \# \text{ learned-clss } S. \neg \text{tautology } s$*   
**shows**  $\forall s \in \# \text{ learned-clss } S'. \neg \text{tautology } s$   
**using** *assms*  
**proof** (*induct rule: cdcl<sub>W</sub>-all-induct-lev2*)  
**case** (*backtrack K i M1 M2 L D T*) **note** *confl = this(1)*  
**have** *consistent-interp (lits-of-l (trail S))* **using** *lev* **by** (*auto simp: cdcl<sub>W</sub>-M-level-inv-decomp*)  
**moreover**  
**have** *trail S  $\models_{as}$  CNot (mset-ccls D)*  
**using** *conflicting confl unfolding cdcl<sub>W</sub>-conflicting-def* **by** *auto*  
**then have** *lits-of-l (trail S)  $\models_s$  CNot (mset-ccls D)*  
**using** *true-annots-true-clb* **by** *blast*  
**ultimately have**  $\neg \text{tautology (mset-ccls D)}$  **using** *consistent-CNot-not-tautology* **by** *blast*  
**then show** *?case* **using** *backtrack no-tauto lev*  
**by** (*auto simp: cdcl<sub>W</sub>-M-level-inv-decomp split: if-split-asm*)  
**next**  
**case** *restart*  
**then show** *?case* **using** *learned-clss-restart-state state-eq-learned-clss no-tauto*  
**by** (*metis (no-types, lifting) set-mset-mono subsetCE*)  
**qed** (*auto dest!: in-diffD*)

**definition** *final-cdcl<sub>W</sub>-state* (*S:: 'st*)  
 $\longleftrightarrow (\text{trail } S \models_{asm} \text{init-clss } S$   
 $\vee ((\forall L \in \text{set } (\text{trail } S). \neg \text{is-marked } L) \wedge$   
 $(\exists C \in \# \text{ init-clss } S. \text{trail } S \models_{as} \text{CNot } C)))$

**definition** *termination-cdcl<sub>W</sub>-state* (*S:: 'st*)  
 $\longleftrightarrow (\text{trail } S \models_{asm} \text{init-clss } S$   
 $\vee ((\forall L \in \text{atms-of-mm } (\text{init-clss } S). L \in \text{atm-of ' lits-of-l } (\text{trail } S))$   
 $\wedge (\exists C \in \# \text{ init-clss } S. \text{trail } S \models_{as} \text{CNot } C)))$

## 19.4 CDCL Strong Completeness

**fun** *mapi* :: (*'a*  $\Rightarrow$  *nat*  $\Rightarrow$  *'b*)  $\Rightarrow$  *nat*  $\Rightarrow$  *'a list*  $\Rightarrow$  *'b list* **where**  
*mapi* - - [] = [] |  
*mapi* *f* *n* (*x* # *xs*) = *f* *x* *n* # *mapi* *f* (*n* - 1) *xs*

**lemma** *mark-not-in-set-mapi[simp]*:  $L \notin \text{set } M \Longrightarrow \text{Marked } L \ k \notin \text{set } (\text{mapi } \text{Marked } i \ M)$   
**by** (*induct M arbitrary: i*) *auto*

**lemma** *propagated-not-in-set-mapi[simp]*:  $L \notin \text{set } M \Longrightarrow \text{Propagated } L \ k \notin \text{set } (\text{mapi } \text{Marked } i \ M)$   
**by** (*induct M arbitrary: i*) *auto*

**lemma** *image-set-mapi*:  
 $f \text{ ' set } (\text{mapi } g \ i \ M) = \text{set } (\text{mapi } (\lambda x \ i. f \ (g \ x \ i)) \ i \ M)$   
**by** (*induction M arbitrary: i*) *auto*

**lemma** *mapi-map-convert*:  
 $\forall x \ i \ j. f \ x \ i = f \ x \ j \Longrightarrow \text{mapi } f \ i \ M = \text{map } (\lambda x. f \ x \ 0) \ M$   
**by** (*induction M arbitrary: i*) *auto*

**lemma** *defined-lit-mapi*:  $\text{defined-lit } (\text{mapi } \text{Marked } i \ M) \ L \longleftrightarrow \text{atm-of } L \in \text{atm-of ' set } M$

by (induction M) (auto simp: defined-lit-map image-set-mapi mapi-map-convert)

**lemma** *cdcl<sub>W</sub>-can-do-step*:

assumes  
 consistent-interp (set M) and  
 distinct M and  
 atm-of ' (set M)  $\subseteq$  atms-of-mm (mset-clss N)

shows  $\exists S$ . rtrancp cdcl<sub>W</sub> (init-state N) S  
 $\wedge$  state S = (mapi Marked (length M) M, mset-clss N, {#}, length M, None)

using assms

**proof** (induct M)

case Nil

then show ?case apply – by (rule exI[of - init-state N]) auto

next

case (Cons L M) note IH = this(1)

have consistent-interp (set M) and distinct M and atm-of ' set M  $\subseteq$  atms-of-mm (mset-clss N)  
 using Cons.prem(1–3) unfolding consistent-interp-def by auto

then obtain S where  
 st: cdcl<sub>W</sub><sup>\*\*</sup> (init-state N) S and  
 S: state S = (mapi Marked (length M) M, mset-clss N, {#}, length M, None)  
 using IH by blast

let ?S<sub>0</sub> = incr-lvl (cons-trail (Marked L (length M + 1)) S)

have undefined-lit (mapi Marked (length M) M) L  
 using Cons.prem(1,2) unfolding defined-lit-def consistent-interp-def by fastforce

moreover have init-clss S = mset-clss N  
 using S by blast

moreover have atm-of L  $\in$  atms-of-mm (mset-clss N) using Cons.prem(3) by auto

moreover have undef: undefined-lit (trail S) L  
 using S  $\langle$ distinct (L#M) $\rangle$  calculation(1) by (auto simp: defined-lit-mapi defined-lit-map)

ultimately have cdcl<sub>W</sub> S ?S<sub>0</sub>  
 using cdcl<sub>W</sub>.other[OF cdcl<sub>W</sub>-o.decide[OF decide-rule[of S L ?S<sub>0</sub>]] S  
 by (auto simp: state-eq-def simp del: state-simp)

then have cdcl<sub>W</sub><sup>\*\*</sup> (init-state N) ?S<sub>0</sub>  
 using st by auto

then show ?case  
 using S undef by (auto intro!: exI[of - ?S<sub>0</sub>] del: simp del: )

qed

**lemma** *cdcl<sub>W</sub>-strong-completeness*:

assumes  
 MN: set M  $\models_{sm}$  mset-clss N and  
 cons: consistent-interp (set M) and  
 dist: distinct M and  
 atm: atm-of ' (set M)  $\subseteq$  atms-of-mm (mset-clss N)

obtains S where  
 state S = (mapi Marked (length M) M, mset-clss N, {#}, length M, None) and  
 rtrancp cdcl<sub>W</sub> (init-state N) S and  
 final-cdcl<sub>W</sub>-state S

**proof** –

obtain S where  
 st: rtrancp cdcl<sub>W</sub> (init-state N) S and  
 S: state S = (mapi Marked (length M) M, mset-clss N, {#}, length M, None)  
 using cdcl<sub>W</sub>-can-do-step[OF cons dist atm] by auto

have lits-of-l (mapi Marked (length M) M) = set M  
 by (induct M, auto)

```

then have mapi Marked (length M) M  $\models_{asm}$  mset-cls N using MN true-annots-true-cls by metis
then have final-cdclW-state S
  using S unfolding final-cdclW-state-def by auto
then show ?thesis using that st S by blast
qed

```

## 19.5 Higher level strategy

The rules described previously do not lead to a conclusive state. We have to add a strategy.

### 19.5.1 Definition

```

lemma tranclp-conflict:
  tranclp conflict S S'  $\implies$  conflict S S'
  apply (induct rule: tranclp.induct)
  apply simp
  by (metis conflictE conflicting-update-conflicting option.distinct(1) option.simps(8,9)
      state-eq-conflicting)

lemma tranclp-conflict-iff[iff]:
  full1 conflict S S'  $\longleftrightarrow$  conflict S S'
proof -
  have tranclp conflict S S'  $\implies$  conflict S S' by (meson tranclp-conflict rtranclpD)
  then show ?thesis unfolding full1-def
  by (metis conflict.simps conflicting-update-conflicting option.distinct(1) option.simps(9)
      state-eq-conflicting tranclp.intros(1))
qed

```

```

inductive cdclW-cp :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool where
  conflict'[intro]: conflict S S'  $\implies$  cdclW-cp S S' |
  propagate': propagate S S'  $\implies$  cdclW-cp S S'

```

```

lemma rtranclp-cdclW-cp-rtranclp-cdclW:
  cdclW-cp** S T  $\implies$  cdclW** S T
  by (induction rule: rtranclp-induct) (auto simp: cdclW-cp.simps dest: cdclW.intros)

```

```

lemma cdclW-cp-state-eq-compatible:
  assumes
    cdclW-cp S T and
    S  $\sim$  S' and
    T  $\sim$  T'
  shows cdclW-cp S' T'
  using assms
  apply (induction)
  using conflict-state-eq-compatible apply auto[1]
  using propagate' propagate-state-eq-compatible by auto

```

```

lemma tranclp-cdclW-cp-state-eq-compatible:
  assumes
    cdclW-cp** S T and
    S  $\sim$  S' and
    T  $\sim$  T'
  shows cdclW-cp** S' T'
  using assms
proof induction

```

```

case base
then show ?case
  using cdclW-cp-state-eq-compatible by blast
next
case (step U V)
obtain ss :: 'st where
  cdclW-cp S ss  $\wedge$  cdclW-cp** ss U
  by (metis (no-types) step(1) tranclpD)
then show ?case
  by (meson cdclW-cp-state-eq-compatible rtranclp.rtrancl-into-rtrancl rtranclp-into-tranclp2
    state-eq-ref step(2) step(4) step(5))
qed

```

```

lemma option-full-cdclW-cp:
  conflicting S  $\neq$  None  $\implies$  full cdclW-cp S S
  unfolding full-def rtranclp-unfold tranclp-unfold
  by (auto simp add: cdclW-cp.simps elim: conflictE propagateE)

```

```

lemma skip-unique:
  skip S T  $\implies$  skip S T'  $\implies$  T  $\sim$  T'
  by (fastforce simp: state-eq-def simp del: state-simp elim: skipE)

```

```

lemma resolve-unique:
  resolve S T  $\implies$  resolve S T'  $\implies$  T  $\sim$  T'
  by (fastforce simp: state-eq-def simp del: state-simp elim: resolveE)

```

```

lemma cdclW-cp-no-more-clauses:
  assumes cdclW-cp S S'
  shows clauses S = clauses S'
  using assms by (induct rule: cdclW-cp.induct) (auto elim!: conflictE propagateE)

```

```

lemma tranclp-cdclW-cp-no-more-clauses:
  assumes cdclW-cp++ S S'
  shows clauses S = clauses S'
  using assms by (induct rule: tranclp.induct) (auto dest: cdclW-cp-no-more-clauses)

```

```

lemma rtranclp-cdclW-cp-no-more-clauses:
  assumes cdclW-cp** S S'
  shows clauses S = clauses S'
  using assms by (induct rule: rtranclp-induct) (fastforce dest: cdclW-cp-no-more-clauses)+

```

```

lemma no-conflict-after-conflict:
  conflict S T  $\implies$   $\neg$ conflict T U
  by (metis None-eq-map-option-iff conflictE conflicting-update-conflicting option.distinct(1)
    state-simp(5))

```

```

lemma no-propagate-after-conflict:
  conflict S T  $\implies$   $\neg$ propagate T U
  by (metis conflictE conflicting-update-conflicting map-option-is-None option.distinct(1)
    propagate.cases state-eq-conflicting)

```

```

lemma tranclp-cdclW-cp-propagate-with-conflict-or-not:
  assumes cdclW-cp++ S U
  shows (propagate++ S U  $\wedge$  conflicting U = None)
     $\vee$  ( $\exists$  T D. propagate** S T  $\wedge$  conflict T U  $\wedge$  conflicting U = Some D)

```

**proof** –

**have**  $\text{propagate}^{++} S U \vee (\exists T. \text{propagate}^{**} S T \wedge \text{conflict} T U)$   
**using** *assms* **by** *induction*  
*(force simp: cdcl<sub>W</sub>-cp.simps tranclp-into-rtranclp dest: no-conflict-after-conflict*  
*no-propagate-after-conflict)+*  
**moreover**  
**have**  $\text{propagate}^{++} S U \implies \text{conflicting} U = \text{None}$   
**unfolding** *tranclp-unfold-end* **by** *(auto elim!: propagateE)*  
**moreover**  
**have**  $\bigwedge T. \text{conflict} T U \implies \exists D. \text{conflicting} U = \text{Some } D$   
**by** *(auto elim!: conflictE simp: state-eq-def simp del: state-simp)*  
**ultimately show** *?thesis* **by** *meson*

**qed**

**lemma** *cdcl<sub>W</sub>-cp-conflicting-not-empty[simp]: conflicting S = Some D  $\implies \neg \text{cdcl}_W\text{-cp } S S'$*

**proof**

**assume** *cdcl<sub>W</sub>-cp S S'* **and** *conflicting S = Some D*  
**then show** *False* **by** *(induct rule: cdcl<sub>W</sub>-cp.induct)*  
*(auto elim: conflictE propagateE simp: state-eq-def simp del: state-simp)*

**qed**

**lemma** *no-step-cdcl<sub>W</sub>-cp-no-conflict-no-propagate:*

**assumes** *no-step cdcl<sub>W</sub>-cp S*  
**shows** *no-step conflict S and no-step propagate S*  
**using** *assms conflict'* **apply** *blast*  
**by** *(meson assms conflict' propagate')*

CDCL with the reasonable strategy: we fully propagate the conflict and propagate, then we apply any other possible rule *cdcl<sub>W</sub>-o S S'* and re-apply conflict and propagate *full cdcl<sub>W</sub>-cp S' S''*

**inductive** *cdcl<sub>W</sub>-stgy* :: *'st  $\Rightarrow$  'st  $\Rightarrow$  bool* **for** *S :: 'st* **where**

*conflict': full1 cdcl<sub>W</sub>-cp S S'  $\implies$  cdcl<sub>W</sub>-stgy S S' |*  
*other': cdcl<sub>W</sub>-o S S'  $\implies$  no-step cdcl<sub>W</sub>-cp S  $\implies$  full cdcl<sub>W</sub>-cp S' S''  $\implies$  cdcl<sub>W</sub>-stgy S S''*

## 19.5.2 Invariants

These are the same invariants as before, but lifted

**lemma** *cdcl<sub>W</sub>-cp-learned-clause-inv:*

**assumes** *cdcl<sub>W</sub>-cp S S'*  
**shows** *learned-clss S = learned-clss S'*  
**using** *assms* **by** *(induct rule: cdcl<sub>W</sub>-cp.induct) (fastforce elim: conflictE propagateE)+*

**lemma** *rtranclp-cdcl<sub>W</sub>-cp-learned-clause-inv:*

**assumes** *cdcl<sub>W</sub>-cp<sup>\*\*</sup> S S'*  
**shows** *learned-clss S = learned-clss S'*  
**using** *assms* **by** *(induct rule: rtranclp-induct) (fastforce dest: cdcl<sub>W</sub>-cp-learned-clause-inv)+*

**lemma** *tranclp-cdcl<sub>W</sub>-cp-learned-clause-inv:*

**assumes** *cdcl<sub>W</sub>-cp<sup>++</sup> S S'*  
**shows** *learned-clss S = learned-clss S'*  
**using** *assms* **by** *(simp add: rtranclp-cdcl<sub>W</sub>-cp-learned-clause-inv tranclp-into-rtranclp)*

**lemma** *cdcl<sub>W</sub>-cp-backtrack-lvl:*

**assumes** *cdcl<sub>W</sub>-cp S S'*  
**shows** *backtrack-lvl S = backtrack-lvl S'*

```

using assms by (induct rule: cdclW-cp.induct) (fastforce elim: conflictE propagateE)+

lemma rtrancpl-cdclW-cp-backtrack-lvl:
  assumes cdclW-cp** S S'
  shows backtrack-lvl S = backtrack-lvl S'
  using assms by (induct rule: rtrancpl-induct) (fastforce dest: cdclW-cp-backtrack-lvl)+

lemma cdclW-cp-consistent-inv:
  assumes cdclW-cp S S'
  and cdclW-M-level-inv S
  shows cdclW-M-level-inv S'
  using assms
proof (induct rule: cdclW-cp.induct)
  case (conflict')
  then show ?case using cdclW-consistent-inv cdclW.conflict by blast
next
  case (propagate' S S')
  have cdclW S S'
    using propagate'.hyps(1) propagate by blast
  then show cdclW-M-level-inv S'
    using propagate'.prems(1) cdclW-consistent-inv propagate by blast
qed

lemma full1-cdclW-cp-consistent-inv:
  assumes full1 cdclW-cp S S'
  and cdclW-M-level-inv S
  shows cdclW-M-level-inv S'
  using assms unfolding full1-def
  by (metis rtrancpl-cdclW-cp-rtrancpl-cdclW rtrancpl-unfold trancpl-cdclW-consistent-inv)

lemma rtrancpl-cdclW-cp-consistent-inv:
  assumes rtrancpl cdclW-cp S S'
  and cdclW-M-level-inv S
  shows cdclW-M-level-inv S'
  using assms unfolding full1-def
  by (induction rule: rtrancpl-induct) (blast intro: cdclW-cp-consistent-inv)+

lemma cdclW-stgy-consistent-inv:
  assumes cdclW-stgy S S'
  and cdclW-M-level-inv S
  shows cdclW-M-level-inv S'
  using assms apply (induct rule: cdclW-stgy.induct)
  unfolding full-unfold by (blast intro: cdclW-consistent-inv full1-cdclW-cp-consistent-inv
    cdclW.other)+

lemma rtrancpl-cdclW-stgy-consistent-inv:
  assumes cdclW-stgy** S S'
  and cdclW-M-level-inv S
  shows cdclW-M-level-inv S'
  using assms by induction (auto dest!: cdclW-stgy-consistent-inv)

lemma cdclW-cp-no-more-init-clss:
  assumes cdclW-cp S S'
  shows init-clss S = init-clss S'
  using assms by (induct rule: cdclW-cp.induct) (auto elim: conflictE propagateE)

```

**lemma** *trancpl-cdcl<sub>W</sub>-cp-no-more-init-clss*:  
**assumes** *cdcl<sub>W</sub>-cp<sup>++</sup> S S'*  
**shows** *init-clss S = init-clss S'*  
**using** *assms* **by** (*induct rule: trancpl.induct*) (*auto dest: cdcl<sub>W</sub>-cp-no-more-init-clss*)

**lemma** *cdcl<sub>W</sub>-stgy-no-more-init-clss*:  
**assumes** *cdcl<sub>W</sub>-stgy S S' and cdcl<sub>W</sub>-M-level-inv S*  
**shows** *init-clss S = init-clss S'*  
**using** *assms*  
**apply** (*induct rule: cdcl<sub>W</sub>-stgy.induct*)  
**unfolding** *full1-def full-def* **apply** (*blast dest: trancpl-cdcl<sub>W</sub>-cp-no-more-init-clss*  
*trancpl-cdcl<sub>W</sub>-o-no-more-init-clss*)  
**by** (*metis cdcl<sub>W</sub>-o-no-more-init-clss rtrancpl-unfold trancpl-cdcl<sub>W</sub>-cp-no-more-init-clss*)

**lemma** *rtrancpl-cdcl<sub>W</sub>-stgy-no-more-init-clss*:  
**assumes** *cdcl<sub>W</sub>-stgy<sup>\*\*</sup> S S' and cdcl<sub>W</sub>-M-level-inv S*  
**shows** *init-clss S = init-clss S'*  
**using** *assms*  
**apply** (*induct rule: rtrancpl-induct, simp*)  
**using** *cdcl<sub>W</sub>-stgy-no-more-init-clss* **by** (*simp add: rtrancpl-cdcl<sub>W</sub>-stgy-consistent-inv*)

**lemma** *cdcl<sub>W</sub>-cp-dropWhile-trail'*:  
**assumes** *cdcl<sub>W</sub>-cp S S'*  
**obtains** *M where trail S' = M @ trail S and (∀ l ∈ set M. ¬is-marked l)*  
**using** *assms* **by** *induction (fastforce elim: conflictE propagateE)+*

**lemma** *rtrancpl-cdcl<sub>W</sub>-cp-dropWhile-trail'*:  
**assumes** *cdcl<sub>W</sub>-cp<sup>\*\*</sup> S S'*  
**obtains** *M :: ('v, nat, 'v clause) marked-lit list where*  
*trail S' = M @ trail S and ∀ l ∈ set M. ¬is-marked l*  
**using** *assms* **by** *induction (fastforce dest!: cdcl<sub>W</sub>-cp-dropWhile-trail')+*

**lemma** *cdcl<sub>W</sub>-cp-dropWhile-trail*:  
**assumes** *cdcl<sub>W</sub>-cp S S'*  
**shows** *∃ M. trail S' = M @ trail S ∧ (∀ l ∈ set M. ¬is-marked l)*  
**using** *assms* **by** *induction (fastforce elim: conflictE propagateE)+*

**lemma** *rtrancpl-cdcl<sub>W</sub>-cp-dropWhile-trail*:  
**assumes** *cdcl<sub>W</sub>-cp<sup>\*\*</sup> S S'*  
**shows** *∃ M. trail S' = M @ trail S ∧ (∀ l ∈ set M. ¬is-marked l)*  
**using** *assms* **by** *induction (fastforce dest: cdcl<sub>W</sub>-cp-dropWhile-trail)+*

This theorem can be seen as a termination theorem for *cdcl<sub>W</sub>-cp*.

**lemma** *length-model-le-vars*:  
**assumes**  
*no-strange-atm S and*  
*no-d: no-dup (trail S) and*  
*finite (atms-of-mm (init-clss S))*  
**shows** *length (trail S) ≤ card (atms-of-mm (init-clss S))*

**proof** –  
**obtain** *M N U k D where S: state S = (M, N, U, k, D)* **by** (*cases state S, auto*)  
**have** *finite (atm-of ' lits-of-l (trail S))*  
**using** *assms(1,3)* **unfolding** *S* **by** (*auto simp add: finite-subset*)  
**have** *length (trail S) = card (atm-of ' lits-of-l (trail S))*

```

    using no-dup-length-eq-card-atm-of-lits-of-l no-d by blast
  then show ?thesis using assms(1) unfolding no-strange-atm-def
  by (auto simp add: assms(3) card-mono)
qed

```

**lemma** *cdcl<sub>W</sub>-cp-decreasing-measure:*

```

  assumes
    cdclW: cdclW-cp S T and
    M-lev: cdclW-M-level-inv S and
    alien: no-strange-atm S
  shows (λS. card (atms-of-mm (init-clss S)) - length (trail S)
    + (if conflicting S = None then 1 else 0)) S
    > (λS. card (atms-of-mm (init-clss S)) - length (trail S)
    + (if conflicting S = None then 1 else 0)) T
  using assms
proof -
  have length (trail T) ≤ card (atms-of-mm (init-clss T))
  apply (rule length-model-le-vars)
    using cdclW-no-strange-atm-inv alien M-lev apply (meson cdclW cdclW.simps cdclW-cp.cases)
    using M-lev cdclW cdclW-cp-consistent-inv cdclW-M-level-inv-def apply blast
    using cdclW by (auto simp: cdclW-cp.simps)
  with assms
  show ?thesis by induction (auto elim!: conflictE propagateE
    simp del: state-simp simp: state-eq-def)+
qed

```

**lemma** *cdcl<sub>W</sub>-cp-wf:* wf {(*b,a*). (cdcl<sub>W</sub>-M-level-inv *a* ∧ no-strange-atm *a*)

∧ cdcl<sub>W</sub>-cp *a b*}

**apply** (rule wf-wf-if-measure'[of less-than - -

(λ*S*. card (atms-of-mm (init-clss *S*)) - length (trail *S*)

+ (if conflicting *S* = None then 1 else 0))])

**apply** simp

**using** cdcl<sub>W</sub>-cp-decreasing-measure **unfolding** less-than-iff **by** blast

**lemma** *rtranclp-cdcl<sub>W</sub>-all-struct-inv-cdcl<sub>W</sub>-cp-iff-rtranclp-cdcl<sub>W</sub>-cp:*

**assumes**

*lev*: cdcl<sub>W</sub>-M-level-inv *S* and

*alien*: no-strange-atm *S*

**shows** (λ*a b*. (cdcl<sub>W</sub>-M-level-inv *a* ∧ no-strange-atm *a*) ∧ cdcl<sub>W</sub>-cp *a b*)\*\* *S T*

↔ cdcl<sub>W</sub>-cp\*\* *S T*

(is ?*I S T* ↔ ?*C S T*)

**proof**

**assume**

?*I S T*

**then show** ?*C S T* **by** induction auto

**next**

**assume**

?*C S T*

**then show** ?*I S T*

**proof** induction

**case** base

**then show** ?*case* **by** simp

**next**

**case** (step *T U*) **note** *st* = this(1) **and** *cp* = this(2) **and** *IH* = this(3)

**have** cdcl<sub>W</sub>\*\* *S T*



```

    by (metis rtrancpl-unfold cdclW-cp-conflicting-not-empty cp st
      rtrancpl-propagate-is-rtrancpl-cdclW trancpl-cdclW-cp-propagate-with-conflict-or-not)
  then have
    cdclW-M-level-inv T and
    no-strange-atm T
    using ⟨cdclW** S T⟩ apply (simp add: assms(1) rtrancpl-cdclW-consistent-inv)
    using ⟨cdclW** S T⟩ alien rtrancpl-cdclW-no-strange-atm-inv lev by blast
  then have (λa b. (cdclW-M-level-inv a ∧ no-strange-atm a)
    ∧ cdclW-cp a b)** T U
    using cp by auto
  then show ?case using IH by auto
qed
qed

lemma cdclW-cp-normalized-element:
  assumes
    lev: cdclW-M-level-inv S and
    no-strange-atm S
  obtains T where full cdclW-cp S T
proof -
  let ?inv = λa. (cdclW-M-level-inv a ∧ no-strange-atm a)
  obtain T where T: full (λa b. ?inv a ∧ cdclW-cp a b) S T
  using cdclW-cp-wf wf-exists-normal-form[of λa b. ?inv a ∧ cdclW-cp a b]
  unfolding full-def by blast
  then have cdclW-cp** S T
    using rtrancpl-cdclW-all-struct-inv-cdclW-cp-iff-rtrancpl-cdclW-cp assms unfolding full-def
    by blast
  moreover
  then have cdclW** S T
    using rtrancpl-cdclW-cp-rtrancpl-cdclW by blast
  then have
    cdclW-M-level-inv T and
    no-strange-atm T
    using ⟨cdclW** S T⟩ apply (simp add: assms(1) rtrancpl-cdclW-consistent-inv)
    using ⟨cdclW** S T⟩ assms(2) rtrancpl-cdclW-no-strange-atm-inv lev by blast
  then have no-step cdclW-cp T
    using T unfolding full-def by auto
  ultimately show thesis using that unfolding full-def by blast
qed

lemma always-exists-full-cdclW-cp-step:
  assumes no-strange-atm S
  shows ∃ S''. full cdclW-cp S S''
  using assms
proof (induct card (atms-of-mm (init-clss S) - atm-of 'lits-of-l (trail S)) arbitrary: S)
  case 0 note card = this(1) and alien = this(2)
  then have atm: atms-of-mm (init-clss S) = atm-of 'lits-of-l (trail S)
    unfolding no-strange-atm-def by auto
  { assume a: ∃ S'. conflict S S'
    then obtain S' where S': conflict S S' by metis
    then have ∀ S''. ¬cdclW-cp S' S''
      by (auto simp: cdclW-cp.simps elim!: conflictE propagateE
        simp del: state-simp simp: state-eq-def)
    then have ?case using a S' cdclW-cp.conflict' unfolding full-def by blast
  }
}

```

```

moreover {
  assume  $a: \exists S'. \text{propagate } S S'$ 
  then obtain  $S'$  where  $\text{propagate } S S'$  by  $\text{blast}$ 
  then obtain  $E L$  where
     $S: \text{conflicting } S = \text{None}$  and
     $E: E \notin \text{raw-clauses } S$  and
     $LE: L \in \# \text{ mset-cls } E$  and
     $\text{tr}: \text{trail } S \models_{\text{as}} \text{CNot } (\text{mset-cls } (\text{remove-lit } L E))$  and
     $\text{undef}: \text{undefined-lit } (\text{trail } S) L$  and
     $S': S' \sim \text{cons-trail } (\text{Propagated } L E) S$ 
    by  $(\text{elim propagateE}) \text{ simp}$ 
  have  $\text{atms-of-mm } (\text{learned-clss } S) \subseteq \text{atms-of-mm } (\text{init-clss } S)$ 
    using  $\text{alien } S$  unfolding  $\text{no-strange-atm-def}$  by  $\text{auto}$ 
  then have  $\text{atm-of } L \in \text{atms-of-mm } (\text{init-clss } S)$ 
    using  $E LE S \text{ undef}$  unfolding  $\text{raw-clauses-def}$  by  $(\text{force simp: in-implies-atm-of-on-atms-of-ms})$ 
  then have  $\text{False}$  using  $\text{undef } S$  unfolding  $\text{atm}$  unfolding  $\text{lits-of-def}$ 
    by  $(\text{auto simp add: defined-lit-map})$ 
}
ultimately show  $?case$  unfolding  $\text{full-def}$  by  $(\text{metis cdcl}_W\text{-cp.cases rtranclp.rtrancl-refl})$ 
next
case  $(\text{Suc } n)$  note  $IH = \text{this}(1)$  and  $\text{card} = \text{this}(2)$  and  $\text{alien} = \text{this}(3)$ 
{ assume  $a: \exists S'. \text{conflict } S S'$ 
  then obtain  $S'$  where  $S': \text{conflict } S S'$  by  $\text{metis}$ 
  then have  $\forall S''. \neg \text{cdcl}_W\text{-cp } S' S''$ 
    by  $(\text{auto simp: cdcl}_W\text{-cp.simps elim!: conflictE propagateE}$ 
       $\text{simp del: state-simp simp: state-eq-def})$ 
  then have  $?case$  unfolding  $\text{full-def Ex-def}$  using  $S' \text{cdcl}_W\text{-cp.conflict'}$  by  $\text{blast}$ 
}
moreover {
  assume  $a: \exists S'. \text{propagate } S S'$ 
  then obtain  $S'$  where  $\text{propagate: propagate } S S'$  by  $\text{blast}$ 
  then obtain  $E L$  where
     $S: \text{conflicting } S = \text{None}$  and
     $E: E \notin \text{raw-clauses } S$  and
     $LE: L \in \# \text{ mset-cls } E$  and
     $\text{tr}: \text{trail } S \models_{\text{as}} \text{CNot } (\text{mset-cls } (\text{remove-lit } L E))$  and
     $\text{undef}: \text{undefined-lit } (\text{trail } S) L$  and
     $S': S' \sim \text{cons-trail } (\text{Propagated } L E) S$ 
    by  $(\text{elim propagateE}) \text{ simp}$ 
  then have  $\text{atm-of } L \notin \text{atm-of ' lits-of-l } (\text{trail } S)$ 
    unfolding  $\text{lits-of-def}$  by  $(\text{auto simp add: defined-lit-map})$ 
  moreover
    have  $\text{no-strange-atm } S'$  using  $\text{alien propagate propagate-no-strange-atm-inv}$  by  $\text{blast}$ 
    then have  $\text{atm-of } L \in \text{atms-of-mm } (\text{init-clss } S)$ 
      using  $S' LE E \text{ undef}$  unfolding  $\text{no-strange-atm-def}$ 
      by  $(\text{auto simp: raw-clauses-def in-implies-atm-of-on-atms-of-ms})$ 
    then have  $\bigwedge A. \{\text{atm-of } L\} \subseteq \text{atms-of-mm } (\text{init-clss } S) - A \vee \text{atm-of } L \in A$  by  $\text{force}$ 
  moreover have  $\text{Suc } n - \text{card } \{\text{atm-of } L\} = n$  by  $\text{simp}$ 
  moreover have  $\text{card } (\text{atms-of-mm } (\text{init-clss } S) - \text{atm-of ' lits-of-l } (\text{trail } S)) = \text{Suc } n$ 
    using  $\text{card } S S' \text{ by simp}$ 
  ultimately
    have  $\text{card } (\text{atms-of-mm } (\text{init-clss } S) - \text{atm-of ' insert } L (\text{lits-of-l } (\text{trail } S))) = n$ 
      by  $(\text{metis (no-types) Diff-insert card-Diff-subset finite.emptyI finite.insertI image-insert})$ 
    then have  $n = \text{card } (\text{atms-of-mm } (\text{init-clss } S') - \text{atm-of ' lits-of-l } (\text{trail } S'))$ 
      using  $\text{card } S S' \text{ undef by simp}$ 

```

```

then have a1: Ex (full cdclW-cp S') using IH ⟨no-strange-atm S'⟩ by blast
have ?case
proof -
  obtain S'' :: 'st where
    ff1: cdclW-cp** S' S'' ∧ no-step cdclW-cp S''
    using a1 unfolding full-def by blast
  have cdclW-cp** S S''
    using ff1 cdclW-cp.intros(2)[OF propagate]
    by (metis (no-types) converse-rtranclp-into-rtranclp)
  then have ∃ S''. cdclW-cp** S S'' ∧ (∀ S'''. ¬ cdclW-cp S'' S''')
    using ff1 by blast
  then show ?thesis unfolding full-def
    by meson
qed
}
ultimately show ?case unfolding full-def by (metis cdclW-cp.cases rtranclp.rtrancl-refl)
qed

```

### 19.5.3 Literal of highest level in conflicting clauses

One important property of the  $cdcl_W$  with strategy is that, whenever a conflict takes place, there is at least a literal of level  $k$  involved (except if we have derived the false clause). The reason is that we apply conflicts before a decision is taken.

**abbreviation** *no-clause-is-false* :: 'st  $\Rightarrow$  bool **where**  
*no-clause-is-false*  $\equiv$   
 $\lambda S. (\text{conflicting } S = \text{None} \longrightarrow (\forall D \in \# \text{ clauses } S. \neg \text{trail } S \models_{as} CNot D))$

**abbreviation** *conflict-is-false-with-level* :: 'st  $\Rightarrow$  bool **where**  
*conflict-is-false-with-level*  $S \equiv \forall D. \text{conflicting } S = \text{Some } D \longrightarrow D \neq \{\#\}$   
 $\longrightarrow (\exists L \in \# D. \text{get-level } (\text{trail } S) L = \text{backtrack-lvl } S)$

**lemma** *not-conflict-not-any-negated-init-clss*:  
**assumes**  $\forall S'. \neg \text{conflict } S S'$   
**shows** *no-clause-is-false*  $S$   
**proof** (clarify)  
**fix**  $D$   
**assume**  $D \in \# \text{ local.clauses } S$  **and** *raw-conflicting*  $S = \text{None}$  **and**  $\text{trail } S \models_{as} CNot D$   
**moreover then obtain**  $D'$  **where**  
 $\text{mset-cls } D' = D$  **and**  
 $D' \notin \# \text{ raw-clauses } S$   
**using** *in-mset-clss-exists-preimage* **unfolding** *raw-clauses-def* **by** *blast*  
**ultimately show** *False*  
**using** *conflict-rule*[of  $S D'$  *update-conflicting* ( $\text{Some } (\text{ccls-of-cls } D')$ )  $S$ ] *assms*  
**by** *auto*  
**qed**

**lemma** *full-cdcl<sub>W</sub>-cp-not-any-negated-init-clss*:  
**assumes** *full cdcl<sub>W</sub>-cp*  $S S'$   
**shows** *no-clause-is-false*  $S'$   
**using** *assms not-conflict-not-any-negated-init-clss* **unfolding** *full-def* **by** *auto*

**lemma** *full1-cdcl<sub>W</sub>-cp-not-any-negated-init-clss*:  
**assumes** *full1 cdcl<sub>W</sub>-cp*  $S S'$   
**shows** *no-clause-is-false*  $S'$   
**using** *assms not-conflict-not-any-negated-init-clss* **unfolding** *full1-def* **by** *auto*

```

lemma cdclW-stgy-not-non-negated-init-clss:
  assumes cdclW-stgy  $S S'$ 
  shows no-clause-is-false  $S'$ 
  using assms apply (induct rule: cdclW-stgy.induct)
  using full1-cdclW-cp-not-any-negated-init-clss full-cdclW-cp-not-any-negated-init-clss by metis+

lemma rtrancp-cdclW-stgy-not-non-negated-init-clss:
  assumes cdclW-stgy**  $S S'$  and no-clause-is-false  $S$ 
  shows no-clause-is-false  $S'$ 
  using assms by (induct rule: rtrancp-induct) (auto simp: cdclW-stgy-not-non-negated-init-clss)

lemma cdclW-stgy-conflict-ex-lit-of-max-level:
  assumes cdclW-cp  $S S'$ 
  and no-clause-is-false  $S$ 
  and cdclW-M-level-inv  $S$ 
  shows conflict-is-false-with-level  $S'$ 
  using assms
proof (induct rule: cdclW-cp.induct)
  case conflict'
  then show ?case by (auto elim: conflictE)
next
  case propagate'
  then show ?case by (auto elim: propagateE)
qed

lemma no-chained-conflict:
  assumes conflict  $S S'$ 
  and conflict  $S' S''$ 
  shows False
  using assms unfolding conflict.simps
  by (metis conflicting-update-conflicting option.distinct(1) option.simps(9) state-eq-conflicting)

lemma rtrancp-cdclW-cp-propa-or-propa-confl:
  assumes cdclW-cp**  $S U$ 
  shows propagate**  $S U \vee (\exists T. \text{propagate}^{**} S T \wedge \text{conflict } T U)$ 
  using assms
proof induction
  case base
  then show ?case by auto
next
  case (step  $U V$ ) note  $SU = \text{this}(1)$  and  $UV = \text{this}(2)$  and  $IH = \text{this}(3)$ 
  consider (confl)  $T$  where propagate**  $S T$  and conflict  $T U$ 
  | (propa) propagate**  $S U$  using  $IH$  by auto
  then show ?case
  proof cases
  case confl
  then have False using  $UV$  by (auto elim: conflictE)
  then show ?thesis by fast
next
  case propa
  also have conflict  $U V \vee \text{propagate } U V$  using  $UV$  by (auto simp add: cdclW-cp.simps)
  ultimately show ?thesis by force
qed
qed

```

```

lemma rtranclp-cdclW-co-conflict-ex-lit-of-max-level:
  assumes full: full cdclW-cp S U
  and cls-f: no-clause-is-false S
  and conflict-is-false-with-level S
  and lev: cdclW-M-level-inv S
  shows conflict-is-false-with-level U
proof (intro allI impI)
  fix D
  assume
    confl: conflicting U = Some D and
    D: D ≠ {#}
  consider (CT) conflicting S = None | (SD) D' where conflicting S = Some D'
  by (cases conflicting S) auto
  then show  $\exists L \in \#D. \text{get-level } (\text{trail } U) \ L = \text{backtrack-lvl } U$ 
  proof cases
    case SD
    then have S = U
    by (metis (no-types) assms(1) cdclW-cp-conflicting-not-empty full-def rtranclpD tranclpD)
    then show ?thesis using assms(3) confl D by blast-
  next
    case CT
    have init-clss U = init-clss S and learned-clss U = learned-clss S
    using full unfolding full-def
    apply (metis (no-types) rtranclpD tranclp-cdclW-cp-no-more-init-clss)
    by (metis (mono-tags, lifting) full full-def rtranclp-cdclW-cp-learned-clause-inv)
    obtain T where propagate** S T and TU: conflict T U
    proof –
      have f5: U ≠ S
      using confl CT by force
      then have cdclW-cp++ S U
      by (metis full full-def rtranclpD)
      have  $\bigwedge p \text{ pa. } \neg \text{propagate } p \text{ pa} \vee \text{conflicting pa} =$ 
        (None::'v clause option)
      by (auto elim: propagateE)
      then show ?thesis
      using f5 that tranclp-cdclW-cp-propagate-with-conflict-or-not[OF (cdclW-cp++ S U)]
      full confl CT unfolding full-def by auto
    qed
    obtain D' where
      raw-conflicting T = None and
      D': D' !∈! raw-clauses T and
      tr: trail T  $\models_{\text{as}} \text{CNot } (\text{mset-cls } D')$  and
      U: U ~ update-conflicting (Some (ccls-of-cls D')) T
      using TU by (auto elim!: conflictE)
    have init-clss T = init-clss S and learned-clss T = learned-clss S
    using U (init-clss U = init-clss S) (learned-clss U = learned-clss S) by auto
    then have D ∈# clauses S
    using confl U D' by (auto simp: raw-clauses-def)
    then have  $\neg \text{trail } S \models_{\text{as}} \text{CNot } D$ 
    using cls-f CT by simp

  moreover
    obtain M where tr-U: trail U = M @ trail S and nm:  $\forall m \in \text{set } M. \neg \text{is-marked } m$ 
    by (metis (mono-tags, lifting) assms(1) full-def rtranclp-cdclW-cp-dropWhile-trail)

```

```

have trail U  $\models_{as}$  CNot D
  using tr confl U by (auto elim!: conflictE)
ultimately obtain L where L  $\in \#$  D and  $-L \in \text{lits-of-l } M$ 
  unfolding tr-U CNot-def true-annot-def Ball-def true-annot-def true-cl-def by force

moreover have inv-U: cdclW-M-level-inv U
  by (metis cdclW-stgy.conflict' cdclW-stgy-consistent-inv full full-unfold lev)
moreover
  have backtrack-lvl U = backtrack-lvl S
    using full unfolding full-def by (auto dest: rtranclp-cdclW-cp-backtrack-lvl)

moreover
  have no-dup (trail U)
    using inv-U unfolding cdclW-M-level-inv-def by auto
  { fix x :: ('v, nat, 'v clause) marked-lit and
    xb :: ('v, nat, 'v clause) marked-lit
    assume a1: atm-of L = atm-of (lit-of xb)
    moreover assume a2:  $-L = \text{lit-of } x$ 
    moreover assume a3: ( $\lambda l. \text{atm-of } (\text{lit-of } l)$ ) 'set M
       $\cap (\lambda l. \text{atm-of } (\text{lit-of } l))$  'set (trail S) = {}
    moreover assume a4:  $x \in \text{set } M$ 
    moreover assume a5:  $xb \in \text{set } (\text{trail } S)$ 
    moreover have atm-of ( $-L$ ) = atm-of L
      by auto
    ultimately have False
      by auto
  }
  then have LS: atm-of L  $\notin$  atm-of 'lits-of-l (trail S)
    using  $\langle -L \in \text{lits-of-l } M \rangle \langle \text{no-dup } (\text{trail } U) \rangle$  unfolding tr-U lits-of-def by auto
ultimately have get-level (trail U) L = backtrack-lvl U
proof (cases get-all-levels-of-marked (trail S)  $\neq []$ , goal-cases)
  case 2 note LD = this(1) and LM = this(2) and inv-U = this(3) and US = this(4) and
    LS = this(5) and ne = this(6)
  have backtrack-lvl S = 0
    using lev ne unfolding cdclW-M-level-inv-def by auto
  moreover have get-rev-level (rev M) 0 L = 0
    using nm by auto
  ultimately show ?thesis using LS ne US unfolding tr-U
    by (simp add: get-all-levels-of-marked-nil-iff-not-is-marked lits-of-def)
next
  case 1 note LD = this(1) and LM = this(2) and inv-U = this(3) and US = this(4) and
    LS = this(5) and ne = this(6)

  have hd (get-all-levels-of-marked (trail S)) = backtrack-lvl S
    using ne lev unfolding cdclW-M-level-inv-def
    by (cases get-all-levels-of-marked (trail S)) auto
  moreover have atm-of L  $\in$  atm-of 'lits-of-l M
    using  $\langle -L \in \text{lits-of-l } M \rangle$  by (simp add: atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set
      lits-of-def)
  ultimately show ?thesis
    using nm ne get-level-skip-beginning-hd-get-all-levels-of-marked[OF LS, of M]
      get-level-skip-in-all-not-marked[of rev M L backtrack-lvl S]
      unfolding lits-of-def US tr-U
      by auto
qed

```

**then show**  $\exists L \in \#D. \text{get-level}(\text{trail } U) L = \text{backtrack-lvl } U$   
**using**  $\langle L \in \# D \rangle$  **by** *blast*  
**qed**  
**qed**

#### 19.5.4 Literal of highest level in marked literals

**definition** *mark-is-false-with-level* :: 'st  $\Rightarrow$  bool **where**

*mark-is-false-with-level*  $S' \equiv$

$\forall D M1 M2 L. M1 @ \text{Propagated } L D \# M2 = \text{trail } S' \longrightarrow D - \{\#L\# \} \neq \{\#\}$   
 $\longrightarrow (\exists L. L \in \# D \wedge \text{get-level}(\text{trail } S') L = \text{get-maximum-possible-level } M1)$

**definition** *no-more-propagation-to-do*:: 'st  $\Rightarrow$  bool **where**

*no-more-propagation-to-do*  $S \equiv$

$\forall D M M' L. D + \{\#L\# \} \in \# \text{ clauses } S \longrightarrow \text{trail } S = M' @ M \longrightarrow M \models_{as} CNot D$   
 $\longrightarrow \text{undefined-lit } M L \longrightarrow \text{get-maximum-possible-level } M < \text{backtrack-lvl } S$   
 $\longrightarrow (\exists L. L \in \# D \wedge \text{get-level}(\text{trail } S) L = \text{get-maximum-possible-level } M)$

**lemma** *propagate-no-more-propagation-to-do*:

**assumes** *propagate*: *propagate*  $S S'$   
**and**  $H$ : *no-more-propagation-to-do*  $S$   
**and** *lev-inv*: *cdcl<sub>W</sub>-M-level-inv*  $S$   
**shows** *no-more-propagation-to-do*  $S'$   
**using** *assms*

**proof** –

**obtain**  $E L$  **where**

$S$ : *conflicting*  $S = None$  **and**  
 $E$ :  $E ! \in !$  *raw-clauses*  $S$  **and**  
 $LE$ :  $L \in \# \text{ mset-cls } E$  **and**  
 $tr$ :  $\text{trail } S \models_{as} CNot (\text{mset-cls} (\text{remove-lit } L E))$  **and**  
 $undefL$ : *undefined-lit*  $(\text{trail } S) L$  **and**  
 $S'$ :  $S' \sim \text{cons-trail} (\text{Propagated } L E) S$

**using** *propagate* **by**  $(\text{elim } \text{propagate } E) \text{ simp}$

**let**  $?M' = \text{Propagated } L (\text{mset-cls } E) \# \text{trail } S$

**show** *?thesis unfolding no-more-propagation-to-do-def*

**proof**  $(\text{intro allI impI})$

**fix**  $D M1 M2 L'$

**assume**

$D-L$ :  $D + \{\#L'\# \} \in \# \text{ clauses } S'$  **and**  
 $\text{trail } S' = M2 @ M1$  **and**  
 $\text{get-max}$ :  $\text{get-maximum-possible-level } M1 < \text{backtrack-lvl } S'$  **and**  
 $M1 \models_{as} CNot D$  **and**  
 $undef$ : *undefined-lit*  $M1 L'$

**have**  $tl M2 @ M1 = \text{trail } S \vee (M2 = [] \wedge M1 = \text{Propagated } L (\text{mset-cls } E) \# \text{trail } S)$

**using**  $\langle \text{trail } S' = M2 @ M1 \rangle S' S \text{ undefL lev-inv}$

**by**  $(\text{cases } M2) (\text{auto simp:cdcl}_W\text{-M-level-inv-decomp})$

**moreover** {

**assume**  $tl M2 @ M1 = \text{trail } S$

**moreover** **have**  $D + \{\#L'\# \} \in \# \text{ clauses } S$

**using**  $D-L S S' \text{ undefL unfolding raw-clauses-def}$  **by** *auto*

**moreover** **have**  $\text{get-maximum-possible-level } M1 < \text{backtrack-lvl } S$

**using**  $\text{get-max } S S' \text{ undefL}$  **by** *auto*

**ultimately obtain**  $L'$  **where**  $L' \in \# D$  **and**

$\text{get-level}(\text{trail } S) L' = \text{get-maximum-possible-level } M1$

**using**  $H \langle M1 \models_{as} CNot D \rangle \text{ undef unfolding no-more-propagation-to-do-def}$  **by** *metis*

**moreover**

```

{ have cdclW-M-level-inv S'
  using cdclW-consistent-inv lev-inv cdclW.propagate[OF propagate] by blast
  then have no-dup ?M' using S' undefL unfolding cdclW-M-level-inv-def by auto
  moreover
    have atm-of L' ∈ atm-of ' (lits-of-l M1)
      using ⟨L' ∈# D⟩ ⟨M1 ⊨as CNot D⟩ by (metis atm-of-uminus image-eqI
        in-CNot-implies-uminus(2))
    then have atm-of L' ∈ atm-of ' (lits-of-l (trail S))
      using ⟨tl M2 @ M1 = trail S⟩[symmetric] S undefL by auto
    ultimately have atm-of L ≠ atm-of L' unfolding lits-of-def by auto
  }
  ultimately have ∃ L' ∈# D. get-level (trail S') L' = get-maximum-possible-level M1
    using S S' undefL by auto
}
moreover {
  assume M2 = [] and M1: M1 = Propagated L (mset-cls E) # trail S
  have cdclW-M-level-inv S'
    using cdclW-consistent-inv[OF - lev-inv] cdclW.propagate[OF propagate] by blast
  then have get-all-levels-of-marked (trail S') = rev [Suc 0..<(Suc 0+backtrack-lvl S)]
    using S' undefL unfolding cdclW-M-level-inv-def by auto
  then have get-maximum-possible-level M1 = backtrack-lvl S'
    using get-maximum-possible-level-max-get-all-levels-of-marked[of M1] S' M1 undefL
    by (auto intro: Max-eqI)
  then have False using get-max by auto
}
ultimately show ∃ L. L ∈# D ∧ get-level (trail S') L = get-maximum-possible-level M1
  by fast
qed
qed

```

**lemma** *conflict-no-more-propagation-to-do*:

```

assumes
  conflict: conflict S S' and
  H: no-more-propagation-to-do S and
  M: cdclW-M-level-inv S
shows no-more-propagation-to-do S'
using assms unfolding no-more-propagation-to-do-def by (force elim!: conflictE)

```

**lemma** *cdcl<sub>W</sub>-cp-no-more-propagation-to-do*:

```

assumes
  conflict: cdclW-cp S S' and
  H: no-more-propagation-to-do S and
  M: cdclW-M-level-inv S
shows no-more-propagation-to-do S'
using assms
proof (induct rule: cdclW-cp.induct)
case (conflict' S S')
then show ?case using conflict-no-more-propagation-to-do[of S S'] by blast
next
case (propagate' S S') note S = this
show 1: no-more-propagation-to-do S'
  using propagate-no-more-propagation-to-do[of S S'] S by blast
qed

```

**lemma** *cdcl<sub>W</sub>-then-exists-cdcl<sub>W</sub>-stgy-step*:



**assumes**  
*o*:  $cdcl_W\text{-}o\ S\ S'$  **and**  
*alien*:  $no\text{-}strange\text{-}atm\ S$  **and**  
*lev*:  $cdcl_W\text{-}M\text{-}level\text{-}inv\ S$   
**shows**  $\exists S'.\ cdcl_W\text{-}stgy\ S\ S'$   
**proof** –  
**obtain**  $S''$  **where**  $full\ cdcl_W\text{-}cp\ S'\ S''$   
**using**  $always\text{-}exists\text{-}full\text{-}cdcl_W\text{-}cp\text{-}step\ alien\ cdcl_W\text{-}no\text{-}strange\text{-}atm\text{-}inv\ cdcl_W\text{-}o\text{-}no\text{-}more\text{-}init\text{-}clss$   
*o* **other** *lev* **by** ( $meson\ cdcl_W\text{-}consistent\text{-}inv$ )  
**then show** *?thesis*  
**using** *assms* **by** ( $metis\ always\text{-}exists\text{-}full\text{-}cdcl_W\text{-}cp\text{-}step\ cdcl_W\text{-}stgy.\text{conflict}'\ full\text{-}unfold\ other'$ )  
**qed**

**lemma** *backtrack-no-decomp*:

**assumes**  
*S*:  $raw\text{-}conflicting\ S = Some\ E$  **and**  
*LE*:  $L \in \# \text{ mset-ccls } E$  **and**  
*L*:  $get\text{-}level\ (trail\ S)\ L = backtrack\text{-}lvl\ S$  **and**  
*D*:  $get\text{-}maximum\text{-}level\ (trail\ S)\ (remove1\text{-}mset\ L\ (mset\text{-}ccls\ E)) < backtrack\text{-}lvl\ S$  **and**  
*bt*:  $backtrack\text{-}lvl\ S = get\text{-}maximum\text{-}level\ (trail\ S)\ (mset\text{-}ccls\ E)$  **and**  
*M-L*:  $cdcl_W\text{-}M\text{-}level\text{-}inv\ S$   
**shows**  $\exists S'.\ cdcl_W\text{-}o\ S\ S'$   
**proof** –  
**have** *L-D*:  $get\text{-}level\ (trail\ S)\ L = get\text{-}maximum\text{-}level\ (trail\ S)\ (mset\text{-}ccls\ E)$   
**using** *L D bt* **by** ( $simp\ add:\ get\text{-}maximum\text{-}level\text{-}plus$ )  
**let** *?i* =  $get\text{-}maximum\text{-}level\ (trail\ S)\ (remove1\text{-}mset\ L\ (mset\text{-}ccls\ E))$   
**obtain** *K M1 M2* **where**  
*K*:  $(Marked\ K\ (?i + 1)\ \# \ M1,\ M2) \in set\ (get\text{-}all\text{-}marked\text{-}decomposition\ (trail\ S))$   
**using**  $backtrack\text{-}ex\text{-}decomp[OF\ M\text{-}L,\ of\ ?i]\ D\ S$  **by** *auto*  
**show** *?thesis* **using**  $backtrack\text{-}rule[OF\ S\ LE\ K\ L]\ bt\ L\ bj\ cdcl_W\text{-}bj.\text{sims}$  **by** *auto*  
**qed**

**lemma** *cdcl\_W-stgy-final-state-conclusive*:

**assumes**  
*termi*:  $\forall S'.\ \neg cdcl_W\text{-}stgy\ S\ S'$  **and**  
*decomp*:  $all\text{-}decomposition\text{-}implies\text{-}m\ (init\text{-}clss\ S)\ (get\text{-}all\text{-}marked\text{-}decomposition\ (trail\ S))$  **and**  
*learned*:  $cdcl_W\text{-}learned\text{-}clause\ S$  **and**  
*level-inv*:  $cdcl_W\text{-}M\text{-}level\text{-}inv\ S$  **and**  
*alien*:  $no\text{-}strange\text{-}atm\ S$  **and**  
*no-dup*:  $distinct\text{-}cdcl_W\text{-}state\ S$  **and**  
*confl*:  $cdcl_W\text{-}conflicting\ S$  **and**  
*confl-k*:  $conflict\text{-}is\text{-}false\text{-}with\text{-}level\ S$   
**shows**  $(conflicting\ S = Some\ \{\#\} \wedge unsatisfiable\ (set\text{-}mset\ (init\text{-}clss\ S)))$   
 $\vee (conflicting\ S = None \wedge trail\ S \models_{as}\ set\text{-}mset\ (init\text{-}clss\ S))$   
**proof** –  
**let** *?M* =  $trail\ S$   
**let** *?N* =  $init\text{-}clss\ S$   
**let** *?k* =  $backtrack\text{-}lvl\ S$   
**let** *?U* =  $learned\text{-}clss\ S$   
**consider**  
 $(None)\ raw\text{-}conflicting\ S = None$   
 $| (Some\text{-}Empty)\ E\ \textbf{where}\ raw\text{-}conflicting\ S = Some\ E\ \textbf{and}\ mset\text{-}ccls\ E = \{\#\}$   
 $| (Some)\ E'\ \textbf{where}\ raw\text{-}conflicting\ S = Some\ E'\ \textbf{and}$   
 $conflicting\ S = Some\ (mset\text{-}ccls\ E')\ \textbf{and}\ mset\text{-}ccls\ E' \neq \{\#\}$   
**by** (*cases conflicting S, simp*) *auto*

```

then show ?thesis
proof cases
  case (Some-Empty E)
  then have conflicting  $S = \text{Some } \{\#\}$  by auto
  then have unsatisfiable (set-mset (init-clss S))
    using assms(3) unfolding cdclW-learned-clause-def true-clss-cls-def
    by (metis (no-types, lifting) Un-insert-right atms-of-empty satisfiable-def
        sup-bot.right-neutral total-over-m-insert total-over-set-empty true-clss-empty)
  then show ?thesis using Some-Empty by auto
next
case None
{ assume  $\neg ?M \models_{asm} ?N$ 
  have atm-of ' (lits-of-l ?M) = atms-of-mm ?N (is ?A = ?B)
  proof
    show ?A  $\subseteq$  ?B using alien unfolding no-strange-atm-def by auto
    show ?B  $\subseteq$  ?A
    proof (rule ccontr)
      assume  $\neg ?B \subseteq ?A$ 
      then obtain l where  $l \in ?B$  and  $l \notin ?A$  by auto
      then have undefined-lit ?M (Pos l)
        using  $l \notin ?A$  unfolding lits-of-def by (auto simp add: defined-lit-map)
      moreover have conflicting  $S = \text{None}$ 
        using None by auto
      ultimately have  $\exists S'. \text{cdcl}_W\text{-o } S S'$ 
        using cdclW-o.decide decide-rule  $l \in ?B$  no-strange-atm-def
        by (metis literal.sel(1) state-eq-def)
      then show False
        using termi cdclW-then-exists-cdclW-stgy-step[OF - alien] level-inv by blast
    qed
  qed
  obtain D where  $\neg ?M \models_a D$  and  $D \in \# ?N$ 
    using  $\langle \neg ?M \models_{asm} ?N \rangle$  unfolding lits-of-def true-annots-def Ball-def by auto
  have atms-of  $D \subseteq \text{atm-of ' (lits-of-l ?M)}$ 
    using  $\langle D \in \# ?N \rangle$  unfolding  $\langle \text{atm-of ' (lits-of-l ?M) = atms-of-mm ?N} \rangle$  atms-of-ms-def
    by (auto simp add: atms-of-def)
  then have a1: atm-of ' set-mset  $D \subseteq \text{atm-of ' lits-of-l (trail S)}$ 
    by (auto simp add: atms-of-def lits-of-def)
  have total-over-m (lits-of-l ?M) {D}
    using  $\langle \text{atms-of } D \subseteq \text{atm-of ' (lits-of-l ?M)} \rangle$ 
    atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set by (fastforce simp: total-over-set-def)
  then have ?M  $\models_{as} \text{CNot } D$ 
    using total-not-true-clss-true-clss-CNot  $\langle \neg \text{trail } S \models_a D \rangle$  true-annot-def
    true-annots-true-clss by fastforce
  then have False
  proof -
    obtain S' where
      f2: full cdclW-cp S S'
      by (meson alien always-exists-full-cdclW-cp-step level-inv)
    then have S' = S
      using cdclW-stgy.conflict'[of S] by (metis (no-types) full-unfold termi)
    then show ?thesis
      using f2  $\langle D \in \# \text{init-clss } S \rangle$  None  $\langle \text{trail } S \models_{as} \text{CNot } D \rangle$ 
      raw-clauses-def full-cdclW-cp-not-any-negated-init-clss by auto
  qed
}

```

```

then have ?M  $\models_{asm}$  ?N by blast
then show ?thesis
  using None by auto
next
case (Some E') note raw-conf = this(1) and LD = this(2) and nempty = this(3)
then obtain L D where
  E'[simp]: mset-ccls E' = D + {#L#} and
  lev-L: get-level ?M L = ?k
  by (metis (mono-tags) confl-k insert-DiffM2)
let ?D = D + {#L#}
have ?D  $\neq$  {#} by auto
have ?M  $\models_{as}$  CNot ?D using confl LD unfolding cdclW-conflicting-def by auto
then have ?M  $\neq$  [] unfolding true-annots-def Ball-def true-annot-def true-cls-def by force
have M: ?M = hd ?M # tl ?M using ⟨?M  $\neq$  []⟩ list.collapse by fastforce
have g-a-l: get-all-levels-of-marked ?M = rev [1.. $1 + ?k$ ]
  using level-inv lev-L M unfolding cdclW-M-level-inv-def by auto
have g-k: get-maximum-level (trail S) D  $\leq$  ?k
  using get-maximum-possible-level-ge-get-maximum-level[of ?M]
  get-maximum-possible-level-max-get-all-levels-of-marked[of ?M]
  by (auto simp add: Max-n-upt g-a-l)
{
  assume marked: is-marked (hd ?M)
  then obtain k' where k': k' + 1 = ?k
    using level-inv M unfolding cdclW-M-level-inv-def
    by (cases hd (trail S); cases trail S) auto
  obtain L' l' where L': hd ?M = Marked L' l' using marked by (cases hd ?M) auto
  have marked-hd-tl: get-all-levels-of-marked (hd (trail S) # tl (trail S))
    = rev [1.. $1 + \text{length (get-all-levels-of-marked ?M)}$ ]
    using level-inv lev-L M unfolding cdclW-M-level-inv-def M[symmetric]
    by blast
  then have l'-tl: l' # get-all-levels-of-marked (tl ?M)
    = rev [1.. $1 + \text{length (get-all-levels-of-marked ?M)}$ ] unfolding L' by simp
  moreover have ... = length (get-all-levels-of-marked ?M)
    # rev [1.. $\text{length (get-all-levels-of-marked ?M)}$ ]
    using M Suc-le-mono calculation by (fastforce simp add: upt.simps(2))
  finally have
    l'-cons: l' # get-all-levels-of-marked (tl (trail S)) =
      length (get-all-levels-of-marked (trail S))
      # rev [1.. $\text{length (get-all-levels-of-marked (trail S))}$ ] and
    l' = ?k and
    g-r: get-all-levels-of-marked (tl (trail S))
      = rev [1.. $\text{length (get-all-levels-of-marked (trail S))}$ ]
    using level-inv lev-L M unfolding cdclW-M-level-inv-def by auto

  have *:  $\bigwedge \text{list. no-dup list} \implies$ 
    -  $L \in \text{lits-of-l list} \implies \text{atm-of } L \in \text{atm-of 'lits-of-l list}$ 
    by (metis atm-of-uminus imageI)
  have L'-L: L' = -L
  proof (rule ccontr)
    assume  $\neg$  ?thesis
    moreover have -L  $\in$  lits-of-l ?M using confl LD unfolding cdclW-conflicting-def by auto
    ultimately have get-level (hd (trail S) # tl (trail S)) L = get-level (tl ?M) L
      using cdclW-M-level-inv-decomp(1)[OF level-inv] L' M atm-of-eq-atm-of
      unfolding lits-of-def consistent-interp-def
      by (metis (mono-tags, hide-lams) marked-lit.sel(1) get-level-skip-beginning image-eqI)
  }

```

```

    list.set-intros(1))
  moreover
    have length (get-all-levels-of-marked (trail S)) = ?k
      using level-inv unfolding cdclW-M-level-inv-def by auto
    then have Max (set (0#get-all-levels-of-marked (tl (trail S)))) = ?k - 1
      unfolding g-r by (auto simp add: Max-n-upt)
    then have get-level (tl ?M) L < ?k
      using get-maximum-possible-level-ge-get-level[of tl ?M L]
      by (metis One-nat-def add.right-neutral add-Suc-right diff-add-inverse2
        get-maximum-possible-level-max-get-all-levels-of-marked k' le-imp-less-Suc
        list.simps(15))
    finally show False using lev-L M by auto
  qed
have L: hd ?M = Marked (-L) ?k using ⟨l' = ?k⟩ L'-L L' by auto

have get-maximum-level (trail S) D < ?k
  proof (rule ccontr)
    assume ¬ ?thesis
    then have get-maximum-level (trail S) D = ?k using M g-k unfolding L by auto
    then obtain L'' where L'' ∈# D and L-k: get-level ?M L'' = ?k
      using get-maximum-level-exists-lit[of ?k ?M D] unfolding k'[symmetric] by auto
    have L ≠ L'' using no-dup ⟨L'' ∈# D⟩
      unfolding distinct-cdclW-state-def LD
      by (metis E' add.right-neutral add-diff-cancel-right'
        distinct-mem-diff-mset union-commute union-single-eq-member)
    have L'' = -L
      proof (rule ccontr)
        assume ¬ ?thesis
        then have get-level ?M L'' = get-level (tl ?M) L''
          using M ⟨L ≠ L''⟩ get-level-skip-beginning[of L'' hd ?M tl ?M] unfolding L
          by (auto simp: atm-of-eq-atm-of)
        then show False
          by (metis L-k Max-n-upt One-nat-def Suc-n-not-le-n ⟨l' = backtrack-lvl S⟩
            add-Suc-right add-implies-diff g-r
            get-all-levels-of-marked-rev-eq-rev-get-all-levels-of-marked list.set(2)
            get-rev-level-less-max-get-all-levels-of-marked k' l'-cons list.sel(1)
            rev-rev-ident semiring-normalization-rules(6) set-upt)
      qed
    then have taut: tautology (D + {#L#})
      using ⟨L'' ∈# D⟩ by (metis add.commute mset-leD mset-le-add-left multi-member-this
        tautology-minus)
    have consistent-interp (lits-of-l ?M)
      using level-inv unfolding cdclW-M-level-inv-def by auto
    then have ¬?M ⊨as CNot ?D
      using taut by (metis ⟨L'' = -L⟩ ⟨L'' ∈# D⟩ add.commute consistent-interp-def
        diff-union-cancelR in-CNot-implies-uminus(2) in-diffD multi-member-this)
    moreover have ?M ⊨as CNot ?D
      using confl no-dup LD unfolding cdclW-conflicting-def by auto
    ultimately show False by blast
  qed note H = this
have get-maximum-level (trail S) D < get-maximum-level (trail S) (D + {#L#})
  using H by (auto simp: get-maximum-level-plus lev-L max-def)
moreover have backtrack-lvl S = get-maximum-level (trail S) (D + {#L#})
  using H by (auto simp: get-maximum-level-plus lev-L max-def)
ultimately have False

```

```

    using backtrack-no-decomp[OF raw-conf - lev-L] level-inv termi
    cdclW-then-exists-cdclW-stgy-step[of S] alien unfolding E'
    by (auto simp add: lev-L max-def)
  } note not-is-marked = this

moreover {
  let ?D = D + {#L#}
  have ?D ≠ {#} by auto
  have ?M ⊨as CNot ?D using confl LD unfolding cdclW-conflicting-def by auto
  then have ?M ≠ [] unfolding true-annots-def Ball-def true-annot-def true-cls-def by force
  assume nm: ¬is-marked (hd ?M)
  then obtain L' C where L'C: hd-raw-trail S = Propagated L' C
    by (metis ⟨trail S ≠ []⟩ hd-raw-trail is-marked-def mset-of-mlit.elims)
  then have hd ?M = Propagated L' (mset-cls C)
    using ⟨trail S ≠ []⟩ hd-raw-trail mset-of-mlit.simps(1) by fastforce
  then have M: ?M = Propagated L' (mset-cls C) # tl ?M
    using ⟨?M ≠ []⟩ list.collapse by fastforce
  then obtain C' where C': mset-cls C = C' + {#L'#}
    using confl unfolding cdclW-conflicting-def by (metis append-Nil diff-single-eq-union)
  { assume -L' ∈# ?D
    then have Ex (skip S)
      using skip-rule[OF M raw-conf] unfolding E' by auto
    then have False
      using cdclW-then-exists-cdclW-stgy-step[of S] alien level-inv termi
      by (auto dest: cdclW-o.intros cdclW-bj.intros)
  }
  moreover {
    assume L'D: -L' ∈# ?D
    then obtain D' where D': ?D = D' + {#-L'#} by (metis insert-DiffM2)
    have g-r: get-all-levels-of-marked (Propagated L' (mset-cls C) # tl (trail S))
      = rev [Suc 0..W-M-level-inv-def by auto
    have Max (insert 0
      (set (get-all-levels-of-marked (Propagated L' (mset-cls C) # tl (trail S))))) = ?k
      using level-inv M unfolding g-r cdclW-M-level-inv-def set-rev
      by (auto simp add: Max-n-upt)
    then have get-maximum-level (trail S) D' ≤ ?k
      using get-maximum-possible-level-ge-get-maximum-level[of
        Propagated L' (mset-cls C) # tl ?M] M
      unfolding get-maximum-possible-level-max-get-all-levels-of-marked by auto
    then have get-maximum-level (trail S) D' = ?k
      ∨ get-maximum-level (trail S) D' < ?k
      using le-neq-implies-less by blast
    moreover {
      assume g-D'-k: get-maximum-level (trail S) D' = ?k
      then have f1: get-maximum-level (trail S) D' = backtrack-lvl S
        using M by auto
      then have Ex (cdclW-o S)
        using f1 resolve-rule[of S L' C , OF ⟨trail S ≠ []⟩ - - raw-conf] raw-conf g-D'-k
        L'C L'D unfolding C' D' E'
        by (fastforce simp add: D' intro: cdclW-o.intros cdclW-bj.intros)
      then have False
        by (meson alien cdclW-then-exists-cdclW-stgy-step termi level-inv)
    }
  }
  moreover {

```

```

assume  $a1$ : get-maximum-level (trail S)  $D' < ?k$ 
then have  $f3$ : get-maximum-level (trail S)  $D' < \text{get-level } (\text{trail } S) (-L')$ 
  using  $a1$  lev-L by (metis  $D'$  get-maximum-level-ge-get-level insert-noteq-member not-less)
moreover have backtrack-lvl S = get-level (trail S) L'
  apply (subst M)
  unfolding rev.simps
  apply (subst get-rev-level-can-skip-correctly-ordered)
  using level-inv unfolding cdclW-M-level-inv-def
  apply (subst (asm) (2) M) apply (simp add: cdclW-M-level-inv-decomp)
  using level-inv unfolding cdclW-M-level-inv-def
  apply (subst (asm) (2) M) apply (auto simp: cdclW-M-level-inv-decomp lits-of-def)[]
  using level-inv unfolding cdclW-M-level-inv-def
  apply (subst (asm) (4) M) apply (auto simp add: cdclW-M-level-inv-decomp)[]
  using level-inv unfolding cdclW-M-level-inv-def
  apply (subst (asm) (4) M) by (auto simp add: cdclW-M-level-inv-decomp)[]
moreover
  then have get-level (trail S) L' = get-maximum-level (trail S) (D' + {#- L'#})
    using  $a1$  by (auto simp add: get-maximum-level-plus max-def)
  ultimately have False
    using  $M$  backtrack-no-decomp[of S - L', OF raw-conf]
    cdclW-then-exists-cdclW-stgy-step L'D level-inv termi alien
    unfolding  $D' E'$  by auto
  }
  ultimately have False by blast
}
ultimately have False by blast
}
ultimately show ?thesis by blast
qed
qed

```

```

lemma cdclW-cp-tranclp-cdclW:
  cdclW-cp S S'  $\implies$  cdclW++ S S'
  apply (induct rule: cdclW-cp.induct)
  by (meson cdclW.conflict cdclW.propagate tranclp.r-into-trancl tranclp.trancl-into-trancl)+

```

```

lemma tranclp-cdclW-cp-tranclp-cdclW:
  cdclW-cp++ S S'  $\implies$  cdclW++ S S'
  apply (induct rule: tranclp.induct)
  apply (simp add: cdclW-cp-tranclp-cdclW)
  by (meson cdclW-cp-tranclp-cdclW tranclp-trans)

```

```

lemma cdclW-stgy-tranclp-cdclW:
  cdclW-stgy S S'  $\implies$  cdclW++ S S'
proof (induct rule: cdclW-stgy.induct)
  case conflict'
  then show ?case
    unfolding full1-def by (simp add: tranclp-cdclW-cp-tranclp-cdclW)
next
  case (other' S' S'')
  then have  $S' = S'' \vee \text{cdcl}_W\text{-cp}^{++} S' S''$ 
    by (simp add: rtranclp-unfold full-def)
  then show ?case
    using other' by (meson cdclW.other tranclp.r-into-trancl)

```

*trancpl-cdcl<sub>W</sub>-cp-trancpl-cdcl<sub>W</sub> trancpl-trans*)  
**qed**

**lemma** *trancpl-cdcl<sub>W</sub>-stgy-trancpl-cdcl<sub>W</sub>:*  
*cdcl<sub>W</sub>-stgy<sup>++</sup> S S'  $\implies$  cdcl<sub>W</sub><sup>++</sup> S S'*  
**apply** (*induct rule: trancpl.induct*)  
**using** *cdcl<sub>W</sub>-stgy-trancpl-cdcl<sub>W</sub> apply blast*  
**by** (*meson cdcl<sub>W</sub>-stgy-trancpl-cdcl<sub>W</sub> trancpl-trans*)

**lemma** *rtrancpl-cdcl<sub>W</sub>-stgy-rtrancpl-cdcl<sub>W</sub>:*  
*cdcl<sub>W</sub>-stgy<sup>\*\*</sup> S S'  $\implies$  cdcl<sub>W</sub><sup>\*\*</sup> S S'*  
**using** *rtrancpl-unfold[of cdcl<sub>W</sub>-stgy S S'] trancpl-cdcl<sub>W</sub>-stgy-trancpl-cdcl<sub>W</sub>[of S S'] by auto*

**lemma** *not-empty-get-maximum-level-exists-lit:*

**assumes** *n: D  $\neq$  {#}*  
**and** *max: get-maximum-level M D = n*  
**shows**  $\exists L \in \#D. \text{get-level } M L = n$

**proof** –

**have** *f: finite (insert 0 (( $\lambda L. \text{get-level } M L$ ) ‘ set-mset D))* **by** *auto*  
**then have** *n  $\in$  (( $\lambda L. \text{get-level } M L$ ) ‘ set-mset D)*  
**using** *n max get-maximum-level-exists-lit-of-max-level image-iff*  
**unfolding** *get-maximum-level-def* **by** *force*  
**then show**  $\exists L \in \#D. \text{get-level } M L = n$  **by** *auto*

**qed**

**lemma** *cdcl<sub>W</sub>-o-conflict-is-false-with-level-inv:*

**assumes**  
*cdcl<sub>W</sub>-o S S' and*  
*lev: cdcl<sub>W</sub>-M-level-inv S and*  
*confl-inv: conflict-is-false-with-level S and*  
*n-d: distinct-cdcl<sub>W</sub>-state S and*  
*conflicting: cdcl<sub>W</sub>-conflicting S*  
**shows** *conflict-is-false-with-level S'*  
**using** *assms(1,2)*

**proof** (*induct rule: cdcl<sub>W</sub>-o-induct-lev2*)

**case** (*resolve L C M D T*) **note** *tr-S = this(1) and confl = this(4) and LD = this(5) and T = this(7)*

**have** *uL-not-D:  $-L \notin \# \text{remove1-mset } (-L) (\text{mset-ccls } D)$*

**using** *n-d confl unfolding distinct-cdcl<sub>W</sub>-state-def distinct-mset-def*

**by** (*metis distinct-cdcl<sub>W</sub>-state-def distinct-mem-diff-mset multi-member-last n-d option.simps(9)*)

**moreover have** *L-not-D:  $L \notin \# \text{remove1-mset } (-L) (\text{mset-ccls } D)$*

**proof** (*rule ccontr*)

**assume**  $\neg ?thesis$

**then have** *L  $\in \# \text{mset-ccls } D$*

**by** (*auto simp: in-remove1-mset-neq*)

**moreover have** *Propagated L (mset-clc C)  $\# M \models_{as} CNot (\text{mset-ccls } D)$*

**using** *conflicting confl tr-S unfolding cdcl<sub>W</sub>-conflicting-def* **by** *auto*

**ultimately have**  $-L \in \text{lits-of-l } (\text{Propagated } L (\text{mset-clc } C) \# M)$

**using** *in-CNot-implies-uminus(2)* **by** *blast*

**moreover have** *no-dup (Propagated L (mset-clc C)  $\# M$ )*

**using** *lev tr-S unfolding cdcl<sub>W</sub>-M-level-inv-def* **by** *auto*

**ultimately show** *False* **unfolding** *lits-of-def* **by** (*metis consistent-interp-def image-eqI*

*list.set-intros(1) lits-of-def marked-lit.sel(2) distinct-consistent-interp*)

**qed**

```

ultimately
  have g-D: get-maximum-level (Propagated L (mset-cls C) # M) (remove1-mset (-L) (mset-ccls D))
    = get-maximum-level M (remove1-mset (-L) (mset-ccls D))
  proof -
    have  $\forall a f L. ((a::'v) \in f \text{ ' } L) = (\exists l. (l::'v \text{ literal}) \in L \wedge a = f l)$ 
      by blast
    then show ?thesis
      using get-maximum-level-skip-first[of L remove1-mset (-L) (mset-ccls D) mset-cls C M]
      unfolding atms-of-def
      by (metis (no-types) uL-not-D L-not-D atm-of-eq-atm-of)
  qed
  have lev-L[simp]: get-level M L = 0
  apply (rule atm-of-notin-get-rev-level-eq-0)
  using lev unfolding cdclW-M-level-inv-def tr-S by (auto simp: lits-of-def)

  have D: get-maximum-level M (remove1-mset (-L) (mset-ccls D)) = backtrack-lvl S
    using resolve.hyps(6) LD unfolding tr-S by (auto simp: get-maximum-level-plus max-def g-D)
  have get-all-levels-of-marked M = rev [Suc 0..W-M-level-inv-def by auto
  then have get-maximum-level M (remove1-mset L (mset-cls C)) ≤ backtrack-lvl S
    using get-maximum-possible-level-ge-get-maximum-level[of M]
    get-maximum-possible-level-max-get-all-levels-of-marked[of M] by (auto simp: Max-n-upt)
  then have
    get-maximum-level M (remove1-mset (- L) (mset-ccls D) #U remove1-mset L (mset-cls C)) =
      backtrack-lvl S
    by (auto simp: get-maximum-level-union-mset get-maximum-level-plus max-def D)
  then show ?case
    using tr-S not-empty-get-maximum-level-exists-lit[of
      remove1-mset (- L) (mset-ccls D) #U remove1-mset L (mset-cls C) M] T
    by auto
next
case (skip L C' M D T) note tr-S = this(1) and D = this(2) and T = this(5)
then obtain La where
  La ∈# mset-ccls D and
  get-level (Propagated L C' # M) La = backtrack-lvl S
  using skip confl-inv by auto
moreover
  have atm-of La ≠ atm-of L
  proof (rule ccontr)
    assume ¬ ?thesis
    then have La: La = L using ⟨La ∈# mset-ccls D⟩ ⟨- L ∉# mset-ccls D⟩
      by (auto simp add: atm-of-eq-atm-of)
    have Propagated L C' # M ⊨as CNot (mset-ccls D)
      using conflicting tr-S D unfolding cdclW-conflicting-def by auto
    then have -L ∈ lits-of-l M
      using ⟨La ∈# mset-ccls D⟩ in-CNot-implies-uminus(2)[of L mset-ccls D
        Propagated L C' # M] unfolding La
      by auto
    then show False using lev tr-S unfolding cdclW-M-level-inv-def consistent-interp-def by auto
  qed
  then have get-level (Propagated L C' # M) La = get-level M La by auto
ultimately show ?case using D tr-S T by auto
next
case backtrack
then show ?case

```



by (auto split: if-split-asm simp: cdcl<sub>W</sub>-M-level-inv-decomp lev)  
qed auto

### 19.5.5 Strong completeness

**lemma** cdcl<sub>W</sub>-cp-propagate-confl:

assumes cdcl<sub>W</sub>-cp  $S\ T$

shows propagate\*\*  $S\ T \vee (\exists S'. \text{propagate** } S\ S' \wedge \text{conflict } S'\ T)$

using assms by induction blast+

**lemma** rtrancpl-cdcl<sub>W</sub>-cp-propagate-confl:

assumes cdcl<sub>W</sub>-cp\*\*  $S\ T$

shows propagate\*\*  $S\ T \vee (\exists S'. \text{propagate** } S\ S' \wedge \text{conflict } S'\ T)$

by (simp add: assms rtrancpl-cdcl<sub>W</sub>-cp-propa-or-propa-confl)

**lemma** propagate-high-levelE:

assumes propagate  $S\ T$

obtains  $M'\ N'\ U\ k\ L\ C$  where

state  $S = (M', N', U, k, \text{None})$  and

state  $T = (\text{Propagated } L\ (C + \{\#L\}) \# M', N', U, k, \text{None})$  and

$C + \{\#L\} \in \# \text{local.clauses } S$  and

$M' \models_{\text{as}} \text{CNot } C$  and

undefined-lit (trail  $S$ )  $L$

**proof** –

**obtain**  $E\ L$  where

conf: conflicting  $S = \text{None}$  and

$E: E \in \# \text{raw.clauses } S$  and

$LE: L \in \# \text{mset-cls } E$  and

tr: trail  $S \models_{\text{as}} \text{CNot } (\text{mset-cls } (\text{remove-lit } L\ E))$  and

undef: undefined-lit (trail  $S$ )  $L$  and

$T: T \sim \text{cons-trail } (\text{Propagated } L\ E)\ S$

using assms by (elim propagateE) simp

**obtain**  $M\ N\ U\ k$  where

$S: \text{state } S = (M, N, U, k, \text{None})$

using conf by auto

**show** thesis

using that[of  $M\ N\ U\ k\ L\ \text{remove1-mset } L\ (\text{mset-cls } E)$ ]  $S\ T\ LE\ E\ \text{tr}\ \text{undef}$

by auto

qed

**lemma** cdcl<sub>W</sub>-cp-propagate-completeness:

assumes  $MN: \text{set } M \models_s \text{set-mset } N$  and

cons: consistent-interp (set  $M$ ) and

tot: total-over-m (set  $M$ ) (set-mset  $N$ ) and

lits-of-l (trail  $S$ )  $\subseteq \text{set } M$  and

init-clss  $S = N$  and

propagate\*\*  $S\ S'$  and

learned-clss  $S = \{\#\}$

shows  $\text{length } (\text{trail } S) \leq \text{length } (\text{trail } S') \wedge \text{lits-of-l } (\text{trail } S') \subseteq \text{set } M$

using assms(6,4,5,7)

**proof** (induction rule: rtrancpl-induct)

case base

then show ?case by auto

next

case (step  $Y\ Z$ )

note  $st = \text{this}(1)$  and  $\text{propa} = \text{this}(2)$  and  $IH = \text{this}(3)$  and  $\text{lits}' = \text{this}(4)$  and  $NS = \text{this}(5)$  and

$learned = this(6)$   
**then have**  $len: length (trail\ S) \leq length (trail\ Y)$  **and**  $LM: lits-of-l (trail\ Y) \subseteq set\ M$   
**by** *blast+*  
  
**obtain**  $M' N' U k C L$  **where**  
 $Y: state\ Y = (M', N', U, k, None)$  **and**  
 $Z: state\ Z = (Propagated\ L\ (C + \{\#L\# \}) \# M', N', U, k, None)$  **and**  
 $C: C + \{\#L\# \} \in \# clauses\ Y$  **and**  
 $M'-C: M' \models_{as} CNot\ C$  **and**  
 $undefined-lit (trail\ Y)\ L$   
**using** *propa* **by** (*auto elim: propagate-high-levelE*)  
**have**  $init-clss\ S = init-clss\ Y$   
**using** *st* **by** *induction (auto elim: propagateE)*  
**then have**  $[simp]: N' = N$  **using** *NS Y Z* **by** *simp*  
**have**  $learned-clss\ Y = \{\#\}$   
**using** *st* **learned** **by** *induction (auto elim: propagateE)*  
**then have**  $[simp]: U = \{\#\}$  **using** *Y* **by** *auto*  
**have**  $set\ M \models_s CNot\ C$   
**using**  $M'-C\ LM\ Y$  **unfolding** *true-annots-def Ball-def true-annot-def true-clss-def true-cl-def*  
**by** *force*  
**moreover**  
**have**  $set\ M \models C + \{\#L\# \}$   
**using**  $MN\ C\ learned\ Y\ NS$   $\langle init-clss\ S = init-clss\ Y \rangle \langle learned-clss\ Y = \{\#\} \rangle$   
**unfolding** *true-clss-def raw-clauses-def* **by** *fastforce*  
**ultimately have**  $L \in set\ M$  **by** (*simp add: cons consistent-CNot-not*)  
**then show** *?case* **using**  $LM\ len\ Y\ Z$  **by** *auto*  
**qed**

**lemma**  
**assumes** *propagate\*\* S X*  
**shows**  
 $rtranclp-propagate-init-clss: init-clss\ X = init-clss\ S$  **and**  
 $rtranclp-propagate-learned-clss: learned-clss\ X = learned-clss\ S$   
**using** *assms* **by** (*induction rule: rtranclp-induct*) (*auto elim: propagateE*)

**lemma** *completeness-is-a-full1-propagation:*  
**fixes**  $S :: 'st$  **and**  $M :: 'v\ literal\ list$   
**assumes**  $MN: set\ M \models_s set-mset\ N$   
**and**  $cons: consistent-interp (set\ M)$   
**and**  $tot: total-over-m (set\ M) (set-mset\ N)$   
**and**  $alien: no-strange-atm\ S$   
**and**  $learned: learned-clss\ S = \{\#\}$   
**and**  $clsS[simp]: init-clss\ S = N$   
**and**  $lits: lits-of-l (trail\ S) \subseteq set\ M$   
**shows**  $\exists S'. propagate^{**}\ S\ S' \wedge full\ cdcl_W-cp\ S\ S'$

**proof** –  
**obtain**  $S'$  **where**  $full: full\ cdcl_W-cp\ S\ S'$   
**using** *always-exists-full-cdcl\_W-cp-step alien* **by** *blast*  
**then consider** (*propa*)  $propagate^{**}\ S\ S'$   
 $| (confl) \exists X. propagate^{**}\ S\ X \wedge conflict\ X\ S'$   
**using**  $rtranclp-cdcl_W-cp-propagate-confl$  **unfolding** *full-def* **by** *blast*  
**then show** *?thesis*  
**proof** *cases*  
**case** *propa* **then show** *?thesis* **using** *full* **by** *blast*  
**next**

```

case confl
then obtain  $X$  where
   $X$ : propagate**  $S$   $X$  and
   $Xconf$ : conflict  $X$   $S'$ 
by blast
have  $clsX$ : init-clss  $X$  = init-clss  $S$ 
  using  $X$  by (blast dest: rtrancpl-propagate-init-clss)
have  $learnedX$ : learned-clss  $X$  =  $\{\#\}$ 
  using  $X$  learned by (auto dest: rtrancpl-propagate-learned-clss)
obtain  $E$  where
   $E$ :  $E \in \#$  init-clss  $X$  + learned-clss  $X$  and
   $Not-E$ : trail  $X \models_{as} CNot$   $E$ 
  using  $Xconf$  by (auto simp add: raw-clauses-def elim!: conflictE)
have lits-of-l (trail  $X$ )  $\subseteq$  set  $M$ 
  using cdclW-cp-propagate-completeness[OF assms(1-3) lits - X learned] learned by auto
then have  $MNE$ : set  $M \models_s CNot$   $E$ 
  using  $Not-E$ 
  by (fastforce simp add: true-annots-def true-annot-def true-clss-def true-clss-def)
have  $\neg$  set  $M \models_s$  set-mset  $N$ 
  using  $E$  consistent-CNot-not[OF cons MNE]
  unfolding  $learnedX$  true-clss-def unfolding  $clsX$   $clsS$  by auto
then show ?thesis using  $MN$  by blast
qed
qed

```

See also *cdcl<sub>W</sub>-cp*\*\*  $?S ?S' \implies \exists M. \text{trail } ?S' = M @ \text{trail } ?S \wedge (\forall l \in \text{set } M. \neg \text{is-marked } l)$

**lemma** *rtrancpl-propagate-is-trail-append*:  
*propagate*\*\*  $S$   $T \implies \exists c. \text{trail } T = c @ \text{trail } S$   
**by** (*induction rule: rtrancpl-induct*) (*auto elim: propagateE*)

**lemma** *rtrancpl-propagate-is-update-trail*:  
*propagate*\*\*  $S$   $T \implies \text{cdcl}_W\text{-}M\text{-level-inv } S \implies$   
*init-clss*  $S$  = *init-clss*  $T \wedge$  *learned-clss*  $S$  = *learned-clss*  $T \wedge$  *backtrack-lvl*  $S$  = *backtrack-lvl*  $T$   
 $\wedge$  *conflicting*  $S$  = *conflicting*  $T$

**proof** (*induction rule: rtrancpl-induct*)

**case** *base*  
**then show** *?case* **unfolding** *state-eq-def* **by** (*auto simp: cdcl<sub>W</sub>-M-level-inv-decomp*)  
**next**

**case** (*step*  $T$   $U$ ) **note**  $IH = \text{this}(3)[\text{OF } \text{this}(4)]$   
**moreover have** *cdcl<sub>W</sub>-M-level-inv*  $U$   
**using** *rtrancpl-cdcl<sub>W</sub>-consistent-inv*  $\langle \text{propagate}^{**} S T \rangle \langle \text{propagate } T U \rangle$   
*rtrancpl-mono*[*of propagate cdcl<sub>W</sub>*] *cdcl<sub>W</sub>-cp-consistent-inv* *propagate'*  
*rtrancpl-propagate-is-rtrancpl-cdcl<sub>W</sub>* *step.prem*s **by** *blast*  
**then have** *no-dup* (*trail*  $U$ ) **unfolding** *cdcl<sub>W</sub>-M-level-inv-def* **by** *auto*  
**ultimately show** *?case* **using**  $\langle \text{propagate } T U \rangle$  **unfolding** *state-eq-def*  
**by** (*fastforce simp: elim: propagateE*)  
**qed**

**lemma** *cdcl<sub>W</sub>-stgy-strong-completeness-n*:

**assumes**

$MN$ : *set*  $M \models_s$  *set-mset* (*mset-clss*  $N$ ) **and**  
 $cons$ : *consistent-interp* (*set*  $M$ ) **and**  
 $tot$ : *total-over-m* (*set*  $M$ ) (*set-mset* (*mset-clss*  $N$ )) **and**  
 $atm\text{-}incl$ : *atm-of* ' (*set*  $M$ )  $\subseteq$  *atms-of-mm* (*mset-clss*  $N$ ) **and**  
 $distM$ : *distinct*  $M$  **and**

$length: n \leq length\ M$   
**shows**  
 $\exists M' k S. length\ M' \geq n \wedge$   
 $lits-of-l\ M' \subseteq set\ M \wedge$   
 $no-dup\ M' \wedge$   
 $state\ S = (M', mset-clss\ N, \{\#\}, k, None) \wedge$   
 $cdcl_W-stgy^{**}\ (init-state\ N)\ S$   
**using**  $length$   
**proof** ( $induction\ n$ )  
**case**  $0$   
**have**  $state\ (init-state\ N) = ([], mset-clss\ N, \{\#\}, 0, None)$   
**by** ( $auto\ simp: state-eq-def\ simp\ del: state-simp$ )  
**moreover have**  
 $0 \leq length\ []$  **and**  
 $lits-of-l\ [] \subseteq set\ M$  **and**  
 $cdcl_W-stgy^{**}\ (init-state\ N)\ (init-state\ N)$   
**and**  $no-dup\ []$   
**by** ( $auto\ simp: state-eq-def\ simp\ del: state-simp$ )  
**ultimately show**  $?case$  **using**  $state-eq-sym$  **by**  $blast$   
**next**  
**case** ( $Suc\ n$ ) **note**  $IH = this(1)$  **and**  $n = this(2)$   
**then obtain**  $M' k S$  **where**  
 $l-M': length\ M' \geq n$  **and**  
 $M': lits-of-l\ M' \subseteq set\ M$  **and**  
 $n-d[simp]: no-dup\ M'$  **and**  
 $S: state\ S = (M', mset-clss\ N, \{\#\}, k, None)$  **and**  
 $st: cdcl_W-stgy^{**}\ (init-state\ N)\ S$   
**by**  $auto$   
**have**  
 $M: cdcl_W-M-level-inv\ S$  **and**  
 $alien: no-strange-atm\ S$   
**using**  $cdcl_W-M-level-inv-S0-cdcl_W\ rtranclp-cdcl_W-stgy-consistent-inv\ st$  **apply**  $blast$   
**using**  $cdcl_W-M-level-inv-S0-cdcl_W\ no-strange-atm-S0\ rtranclp-cdcl_W-no-strange-atm-inv$   
 $rtranclp-cdcl_W-stgy-rtranclp-cdcl_W\ st$  **by**  $blast$   
  
**{ assume**  $no-step: \neg no-step\ propagate\ S$   
**obtain**  $S'$  **where**  $S': propagate^{**}\ S\ S'$  **and**  $full: full\ cdcl_W-cp\ S\ S'$   
**using**  $completeness-is-a-full1-propagation[OF\ assms(1-3),\ of\ S]\ alien\ M'\ S$   
**by** ( $auto\ simp: comp-def$ )  
**have**  $lev: cdcl_W-M-level-inv\ S'$   
**using**  $M\ S'\ rtranclp-cdcl_W-consistent-inv\ rtranclp-propagate-is-rtranclp-cdcl_W$  **by**  $blast$   
**then have**  $n-d'[simp]: no-dup\ (trail\ S')$   
**unfolding**  $cdcl_W-M-level-inv-def$  **by**  $auto$   
**have**  $length\ (trail\ S) \leq length\ (trail\ S') \wedge lits-of-l\ (trail\ S') \subseteq set\ M$   
**using**  $S'\ full\ cdcl_W-cp-propagate-completeness[OF\ assms(1-3),\ of\ S]\ M'\ S$   
**by** ( $auto\ simp: comp-def$ )  
**moreover**  
**have**  $full: full1\ cdcl_W-cp\ S\ S'$   
**using**  $full\ no-step\ no-step-cdcl_W-cp-no-conflict-no-propagate(2)$  **unfolding**  $full1-def\ full-def$   
 $rtranclp-unfold$  **by**  $blast$   
**then have**  $cdcl_W-stgy\ S\ S'$  **by** ( $simp\ add: cdcl_W-stgy.conflict'$ )  
**moreover**  
**have**  $propa: propagate^{++}\ S\ S'$  **using**  $S'\ full$  **unfolding**  $full1-def$  **by** ( $metis\ rtranclpD\ tranclpD$ )  
**have**  $trail\ S = M'$   
**using**  $S$  **by** ( $auto\ simp: comp-def\ rev-map$ )

```

with propa have length (trail S') > n
  using l-M' propa by (induction rule: tranclp.induct) (auto elim: propagateE)
moreover
  have stS': cdclW-stgy** (init-state N) S'
    using st cdclW-stgy.conflict'[OF full] by auto
  then have init-clss S' = mset-clss N
    using stS' rtranclp-cdclW-stgy-no-more-init-clss by fastforce
moreover
  have
    [simp]: learned-clss S' = {#} and
    [simp]: init-clss S' = init-clss S and
    [simp]: conflicting S' = None
    using tranclp-into-rtranclp[OF ⟨propagate++ S S'⟩] S
      rtranclp-propagate-is-update-trail[of S S'] S M unfolding state-eq-def
    by (auto simp: comp-def)
  have S-S': state S' = (trail S', mset-clss N, {#}, backtrack-lvl S', None)
    using S by auto
  have cdclW-stgy** (init-state N) S'
    apply (rule rtranclp.rtrancl-into-rtrancl)
    using st apply simp
    using ⟨cdclW-stgy S S'⟩ by simp
ultimately have ?case
  apply -
  apply (rule exI[of - trail S'], rule exI[of - backtrack-lvl S'], rule exI[of - S'])
  using S-S' by (auto simp: state-eq-def simp del: state-simp)
}
moreover {
  assume no-step: no-step propagate S
  have ?case
    proof (cases length M' ≥ Suc n)
    case True
      then show ?thesis using l-M' M' st M alien S n-d by blast
    next
    case False
      then have n': length M' = n using l-M' by auto
      have no-conf: no-step conflict S
        proof -
          { fix D
            assume D ∈ # mset-clss N and M' ⊨as CNot D
            then have set M ⊨ D using MN unfolding true-clss-def by auto
            moreover have set M ⊨s CNot D
              using ⟨M' ⊨as CNot D⟩ M'
              by (metis le-iff-sup true-annots-true-clss true-clss-union-increase)
            ultimately have False using cons consistent-CNot-not by blast
          }
          then show ?thesis
            using S by (auto simp: true-clss-def comp-def rev-map
              raw-clauses-def dest!: in-clss-mset-clss elim!: conflictE)
        qed
      have lenM: length M = card (set M) using distM by (induction M) auto
      have no-dup M' using S M unfolding cdclW-M-level-inv-def by auto
      then have card (lits-of-l M') = length M'
        by (induction M') (auto simp add: lits-of-def card-insert-if)
      then have lits-of-l M' ⊂ set M
        using n M' n' lenM by auto

```

**then obtain  $m$  where  $m: m \in \text{set } M$  and  $\text{undef-}m: m \notin \text{lits-of-}l \ M'$  by auto**  
**moreover have  $\text{undef}: \text{undefined-lit } M' \ m$**   
**using  $M' \text{ Marked-Propagated-in-iff-in-lits-of-}l \text{ calculation}(1,2) \text{ cons}$**   
 **$\text{consistent-interp-def}$  by  $(\text{metis } (\text{no-types, lifting}) \text{ subset-eq})$**   
**moreover have  $\text{atm-of } m \in \text{atms-of-mm } (\text{init-clss } S)$**   
**using  $\text{atm-incl calculation } S$  by auto**  
**ultimately**  
**have  $\text{dec}: \text{decide } S \ (\text{cons-trail } (\text{Marked } m \ (k+1)) \ (\text{incr-lvl } S))$**   
**using  $\text{decide-rule}[of \ S -$**   
 **$\text{cons-trail } (\text{Marked } m \ (k + 1)) \ (\text{incr-lvl } S)] \ S$**   
**by auto**  
**let  $?S' = \text{cons-trail } (\text{Marked } m \ (k+1)) \ (\text{incr-lvl } S)$**   
**have  $\text{lits-of-}l \ (\text{trail } ?S') \subseteq \text{set } M$  using  $m \ M' \ S \ \text{undef}$  by auto**  
**moreover have  $\text{no-strange-atm } ?S'$**   
**using  $\text{alien dec } M$  by  $(\text{meson } \text{cdcl}_W\text{-no-strange-atm-inv decide other})$**   
**ultimately obtain  $S''$  where  $S'': \text{propagate}^{**} \ ?S' \ S''$  and  $\text{full}: \text{full } \text{cdcl}_W\text{-cp } ?S' \ S''$**   
**using  $\text{completeness-is-a-full1-propagation}[OF \ \text{assms}(1-3), \text{ of } ?S'] \ S \ \text{undef}$**   
**by auto**  
**have  $\text{cdcl}_W\text{-M-level-inv } ?S'$**   
**using  $M \text{ dec } \text{rtranclp-mono}[of \text{decide } \text{cdcl}_W]$  by  $(\text{meson } \text{cdcl}_W\text{-consistent-inv decide other})$**   
**then have  $\text{lev}'': \text{cdcl}_W\text{-M-level-inv } S''$**   
**using  $S'' \text{ rtranclp-cdcl}_W\text{-consistent-inv rtranclp-propagate-is-rtranclp-cdcl}_W$  by blast**  
**then have  $\text{n-d}'': \text{no-dup } (\text{trail } S'')$**   
**unfolding  $\text{cdcl}_W\text{-M-level-inv-def}$  by auto**  
**have  $\text{length } (\text{trail } ?S') \leq \text{length } (\text{trail } S'') \wedge \text{lits-of-}l \ (\text{trail } S'') \subseteq \text{set } M$**   
**using  $S'' \text{ full } \text{cdcl}_W\text{-cp-propagate-completeness}[OF \ \text{assms}(1-3), \text{ of } ?S' \ S''] \ m \ M' \ S \ \text{undef}$**   
**by simp**  
**then have  $\text{Suc } n \leq \text{length } (\text{trail } S'') \wedge \text{lits-of-}l \ (\text{trail } S'') \subseteq \text{set } M$**   
**using  $\text{l-M}' \ S \ \text{undef}$  by auto**  
**moreover**  
**have  $\text{cdcl}_W\text{-M-level-inv } (\text{cons-trail } (\text{Marked } m \ (\text{Suc } (\text{backtrack-lvl } S))))$**   
 **$(\text{update-backtrack-lvl } (\text{Suc } (\text{backtrack-lvl } S)) \ S))$**   
**using  $S \ \langle \text{cdcl}_W\text{-M-level-inv } (\text{cons-trail } (\text{Marked } m \ (k + 1)) \ (\text{incr-lvl } S)) \rangle$  by auto**  
**then have  $S''$ :**  
 **$\text{state } S'' = (\text{trail } S'', \text{mset-clss } N, \{\#\}, \text{backtrack-lvl } S'', \text{None})$**   
**using  $\text{rtranclp-propagate-is-update-trail}[OF \ S''] \ S \ \text{undef } \text{n-d}'' \ \text{lev}''$**   
**by auto**  
**then have  $\text{cdcl}_W\text{-stgy}^{**} \ (\text{init-state } N) \ S''$**   
**using  $\text{cdcl}_W\text{-stgy.intros}(2)[OF \text{decide}[OF \text{dec}] - \text{full}] \text{ no-step no-confl } st$**   
**by  $(\text{auto simp: } \text{cdcl}_W\text{-cp.simps})$**   
**ultimately show  $?thesis$  using  $S'' \ \text{n-d}''$  by blast**  
**qed**  
**}**  
**ultimately show  $?case$  by blast**  
**qed**

**lemma  $\text{cdcl}_W\text{-stgy-strong-completeness}$ :**

**assumes**

$MN: \text{set } M \models_s \text{set-mset } (\text{mset-clss } N)$  **and**

$\text{cons: consistent-interp } (\text{set } M)$  **and**

$\text{tot: total-over-m } (\text{set } M) \ (\text{set-mset } (\text{mset-clss } N))$  **and**

$\text{atm-incl: atm-of } ' \ (\text{set } M) \subseteq \text{atms-of-mm } (\text{mset-clss } N)$  **and**

$\text{distM: distinct } M$

**shows**

$\exists M' \ k \ S.$

```

    lits-of-l M' = set M ∧
    state S = (M', mset-clss N, {#}, k, None) ∧
    cdclW-stgy** (init-state N) S ∧
    final-cdclW-state S
proof –
  from cdclW-stgy-strong-completeness-n[OF assms, of length M]
obtain M' k T where
    l: length M ≤ length M' and
    M'-M: lits-of-l M' ⊆ set M and
    no-dup: no-dup M' and
    T: state T = (M', mset-clss N, {#}, k, None) and
    st: cdclW-stgy** (init-state N) T
  by auto
have card (set M) = length M using distM by (simp add: distinct-card)
moreover
  have cdclW-M-level-inv T
    using rtrancp-cdclW-stgy-consistent-inv[OF st] T by auto
  then have card (set ((map (λl. atm-of (lit-of l)) M'))) = length M'
    using distinct-card no-dup by fastforce
moreover have card (lits-of-l M') = card (set ((map (λl. atm-of (lit-of l)) M')))
  using no-dup unfolding lits-of-def apply (induction M') by (auto simp add: card-insert-if)
ultimately have card (set M) ≤ card (lits-of-l M') using l unfolding lits-of-def by auto
then have set M = lits-of-l M'
  using M'-M card-seteq by blast
moreover
  then have M' ⊨asm mset-clss N
    using MN unfolding true-annots-def Ball-def true-annot-def true-clss-def by auto
  then have final-cdclW-state T
    using T no-dup unfolding final-cdclW-state-def by auto
ultimately show ?thesis using st T by blast
qed

```

### 19.5.6 No conflict with only variables of level less than backtrack level

This invariant is stronger than the previous argument in the sense that it is a property about all possible conflicts.

**definition** no-smaller-conf (S::'st) ≡  
 (∀ M K i M' D. M' @ Marked K i # M = trail S ⟶ D ∈ # clauses S  
 ⟶ ¬M ⊨<sub>as</sub> CNot D)

**lemma** no-smaller-conf-init-sate[simp]:  
 no-smaller-conf (init-state N) **unfolding** no-smaller-conf-def **by** auto

**lemma** cdcl<sub>W</sub>-o-no-smaller-conf-inv:

```

fixes S S' :: 'st
assumes
  cdclW-o S S' and
  lev: cdclW-M-level-inv S and
  max-lev: conflict-is-false-with-level S and
  smaller: no-smaller-conf S and
  no-f: no-clause-is-false S
shows no-smaller-conf S'
using assms(1,2) unfolding no-smaller-conf-def
proof (induct rule: cdclW-o-induct-lev2)
  case (decide L T) note conf = this(1) and undef = this(2) and T = this(4)

```

```

have [simp]: clauses T = clauses S
  using T undef by auto
show ?case
proof (intro allI impI)
  fix M'' K i M' Da
  assume M'' @ Marked K i # M' = trail T
  and D: Da ∈# local.clauses T
  then have tl M'' @ Marked K i # M' = trail S
    ∨ (M'' = [] ∧ Marked K i # M' = Marked L (backtrack-lvl S + 1) # trail S)
    using T undef by (cases M'') auto
  moreover {
    assume tl M'' @ Marked K i # M' = trail S
    then have ¬M' ⊨as CNot Da
      using D T undef no-f confl smaller unfolding no-smaller-confl-def smaller by fastforce
  }
  moreover {
    assume Marked K i # M' = Marked L (backtrack-lvl S + 1) # trail S
    then have ¬M' ⊨as CNot Da using no-f D confl T by auto
  }
  ultimately show ¬M' ⊨as CNot Da by fast
qed
next
case resolve
then show ?case using smaller no-f max-lev unfolding no-smaller-confl-def by auto
next
case skip
then show ?case using smaller no-f max-lev unfolding no-smaller-confl-def by auto
next
case (backtrack K i M1 M2 L D T) note confl = this(1) and LD = this(2) and decomp = this(3)
and
  undef = this(7) and T = this(8)
obtain c where M: trail S = c @ M2 @ Marked K (i+1) # M1
  using decomp by auto

show ?case
proof (intro allI impI)
  fix M ia K' M' Da

  assume M' @ Marked K' ia # M = trail T
  then have tl M' @ Marked K' ia # M = M1
    using T decomp undef lev by (cases M') (auto simp: cdclW-M-level-inv-decomp)
  let ?S' = (cons-trail (Propagated L (cls-of-ccls D))
    (reduce-trail-to M1 (add-learned-cls (cls-of-ccls D))
      (update-backtrack-lvl i (update-conflicting None S))))))
  assume D: Da ∈# clauses T
  moreover{
    assume Da ∈# clauses S
    then have ¬M ⊨as CNot Da using (tl M' @ Marked K' ia # M = M1) M confl undef smaller
      unfolding no-smaller-confl-def by auto
  }
  moreover {
    assume Da: Da = mset-ccls D
    have ¬M ⊨as CNot Da
    proof (rule ccontr)
      assume ¬ ?thesis

```



```

then have  $-L \in \text{ lits-of-}l\ M$ 
  using LD unfolding Da by (simp add: in-CNot-implies-uminus(2))
then have  $-L \in \text{ lits-of-}l\ (\text{Propagated } L\ (\text{mset-ccls } D)\ \# M1)$ 
  using UnI2  $\langle \text{tl } M' @ \text{Marked } K' \text{ ia } \# M = M1 \rangle$ 
  by auto
moreover
  have backtrack  $S\ ?S'$ 
    using backtrack-rule[of S] backtrack.hyps
    by (force simp: state-eq-def simp del: state-simp)
  then have cdclW-M-level-inv  $?S'$ 
    using cdclW-consistent-inv[OF - lev] other[OF bj] by (auto intro: cdclW-bj.intros)
  then have no-dup  $(\text{Propagated } L\ (\text{mset-ccls } D)\ \# M1)$ 
    using decomp undef lev unfolding cdclW-M-level-inv-def by auto
  ultimately show False
    using undef by (auto simp: Marked-Propagated-in-iff-in-lits-of-l)
qed
}
ultimately show  $\neg M \models_{as} CNot\ Da$ 
  using T undef decomp lev unfolding cdclW-M-level-inv-def by fastforce
qed
qed

```

**lemma** *conflict-no-smaller-conflict-inv*:

```

assumes conflict  $S\ S'$ 
and no-smaller-conflict  $S$ 
shows no-smaller-conflict  $S'$ 
using assms unfolding no-smaller-conflict-def by (fastforce elim: conflictE)

```

**lemma** *propagate-no-smaller-conflict-inv*:

```

assumes propagate: propagate  $S\ S'$ 
and n-l: no-smaller-conflict  $S$ 
shows no-smaller-conflict  $S'$ 
unfolding no-smaller-conflict-def
proof (intro allI impI)
  fix  $M' K i M'' D$ 
  assume  $M': M'' @ \text{Marked } K\ i\ \# M' = \text{trail } S'$ 
  and  $D \in \# \text{ clauses } S'$ 
  obtain  $M N U k C L$  where
     $S$ : state  $S = (M, N, U, k, None)$  and
     $S'$ : state  $S' = (\text{Propagated } L\ (C + \{\#L\})\ \# M, N, U, k, None)$  and
     $C + \{\#L\} \in \# \text{ clauses } S$  and
     $M \models_{as} CNot\ C$  and
    undefined-lit  $M\ L$ 
  using propagate by (auto elim: propagate-high-levelE)
  have  $\text{tl } M'' @ \text{Marked } K\ i\ \# M' = \text{trail } S$  using  $M' S S'$ 
  by (metis Pair-inject list.inject list.sel(3) marked-lit.distinct(1) self-append-conv2
    tl-append2)
  then have  $\neg M' \models_{as} CNot\ D$ 
    using  $\langle D \in \# \text{ clauses } S' \rangle$  n-l  $S\ S'$  raw-clauses-def unfolding no-smaller-conflict-def by auto
  then show  $\neg M' \models_{as} CNot\ D$  by auto
qed

```

**lemma** *cdcl<sub>W</sub>-cp-no-smaller-conflict-inv*:

```

assumes propagate: cdclW-cp  $S\ S'$ 
and n-l: no-smaller-conflict  $S$ 

```

```

  shows no-smaller-confl  $S'$ 
  using assms
proof (induct rule: cdclW-cp.induct)
  case (conflict'  $S S'$ )
  then show ?case using conflict-no-smaller-confl-inv[of  $S S'$ ] by blast
next
  case (propagate'  $S S'$ )
  then show ?case using propagate-no-smaller-confl-inv[of  $S S'$ ] by fastforce
qed

```

```

lemma rtrancp-cdclW-cp-no-smaller-confl-inv:
  assumes propagate: cdclW-cp*  $S S'$ 
  and n-l: no-smaller-confl  $S$ 
  shows no-smaller-confl  $S'$ 
  using assms
proof (induct rule: rtrancp-induct)
  case base
  then show ?case by simp
next
  case (step  $S' S''$ )
  then show ?case using cdclW-cp-no-smaller-confl-inv[of  $S' S''$ ] by fast
qed

```

```

lemma trancp-cdclW-cp-no-smaller-confl-inv:
  assumes propagate: cdclW-cp++  $S S'$ 
  and n-l: no-smaller-confl  $S$ 
  shows no-smaller-confl  $S'$ 
  using assms
proof (induct rule: trancp.induct)
  case (r-into-tranc  $S S'$ )
  then show ?case using cdclW-cp-no-smaller-confl-inv[of  $S S'$ ] by blast
next
  case (tranc-into-tranc  $S S' S''$ )
  then show ?case using cdclW-cp-no-smaller-confl-inv[of  $S' S''$ ] by fast
qed

```

```

lemma full-cdclW-cp-no-smaller-confl-inv:
  assumes full cdclW-cp  $S S'$ 
  and n-l: no-smaller-confl  $S$ 
  shows no-smaller-confl  $S'$ 
  using assms unfolding full-def
  using rtrancp-cdclW-cp-no-smaller-confl-inv[of  $S S'$ ] by blast

```

```

lemma full1-cdclW-cp-no-smaller-confl-inv:
  assumes full1 cdclW-cp  $S S'$ 
  and n-l: no-smaller-confl  $S$ 
  shows no-smaller-confl  $S'$ 
  using assms unfolding full1-def
  using trancp-cdclW-cp-no-smaller-confl-inv[of  $S S'$ ] by blast

```

```

lemma cdclW-stgy-no-smaller-confl-inv:
  assumes cdclW-stgy  $S S'$ 
  and n-l: no-smaller-confl  $S$ 
  and conflict-is-false-with-level  $S$ 
  and cdclW-M-level-inv  $S$ 

```

```

shows no-smaller-confl  $S'$ 
using assms
proof (induct rule: cdclW-stgy.induct)
  case (conflict'  $S'$ )
  then show ?case using full1-cdclW-cp-no-smaller-confl-inv[of  $S S'$ ] by blast
next
  case (other'  $S' S''$ )
  have no-smaller-confl  $S'$ 
    using cdclW-o-no-smaller-confl-inv[OF other'.hyps(1) other'.prems(3,2,1)]
    not-conflict-not-any-negated-init-clss other'.hyps(2) cdclW-cp.simps by auto
  then show ?case using full-cdclW-cp-no-smaller-confl-inv[of  $S' S''$ ] other'.hyps by blast
qed

```

**lemma** *is-conflicting-exists-conflict*:

```

assumes  $\neg(\forall D \in \#init-clss S' + learned-clss S'. \neg trail S' \models_{as} CNot D)$ 
and conflicting  $S' = None$ 
shows  $\exists S''. conflict S' S''$ 
using assms raw-clauses-def not-conflict-not-any-negated-init-clss by fastforce

```

**lemma** *cdcl<sub>W</sub>-o-conflict-is-no-clause-is-false*:

```

fixes  $S S' :: 'st$ 
assumes
  cdclW-o  $S S'$  and
  lev: cdclW-M-level-inv  $S$  and
  max-lev: conflict-is-false-with-level  $S$  and
  no-f: no-clause-is-false  $S$  and
  no-l: no-smaller-confl  $S$ 
shows no-clause-is-false  $S'$ 
   $\vee (conflicting S' = None$ 
     $\longrightarrow (\forall D \in \# clauses S'. trail S' \models_{as} CNot D$ 
       $\longrightarrow (\exists L. L \in \# D \wedge get-level (trail S') L = backtrack-lvl S')))$ 
  using assms(1,2)
proof (induct rule: cdclW-o-induct-lev2)
  case (decide  $L T$ ) note  $S = this(1)$  and undef = this(2) and  $T = this(4)$ 
  show ?case
    proof (rule HOL.disjI2, clarify)
      fix  $D$ 
      assume  $D: D \in \# clauses T$  and  $M-D: trail T \models_{as} CNot D$ 
      let ? $M = trail S$ 
      let ? $M' = trail T$ 
      let ? $k = backtrack-lvl S$ 
      have  $\neg ?M \models_{as} CNot D$ 
        using no-f  $D S T undef$  by auto
      have  $-L \in \# D$ 
      proof (rule ccontr)
        assume  $\neg ?thesis$ 
        have ? $M \models_{as} CNot D$ 
          unfolding true-annots-def Ball-def true-annot-def CNot-def true-cls-def
          proof (intro allI impI)
            fix  $x$ 
            assume  $x: x \in \{\{\#- L\# \} \mid L. L \in \# D\}$ 

            then obtain  $L'$  where  $L': x = \{\#-L'\# \}$   $L' \in \# D$  by auto
            obtain  $L''$  where  $L'' \in \# x$  and lits-of-l (Marked  $L$  ( $?k + 1$ )  $\#$  ? $M$ )  $\models_l L''$ 
              using  $M-D x T undef$  unfolding true-annots-def Ball-def true-annot-def CNot-def

```

```

      true-clb-def Bex-def by auto
    show  $\exists L \in \# x. \text{ lits-of-l } ?M \models_l L$  unfolding Bex-def
      using  $L'(1) \ L'(2) \langle \neg L \notin \# D \rangle \langle L'' \in \# x \rangle$ 
       $\langle \text{ lits-of-l } (\text{Marked } L \ (\text{backtrack-lvl } S + 1) \ \# \ \text{trail } S) \models_l L'' \rangle$  by auto
    qed
    then show False using  $\langle \neg ?M \models_{as} CNot \ D \rangle$  by auto
  qed
  have atm-of  $L \notin \text{ atm-of } ' (\text{ lits-of-l } ?M)$ 
    using undef defined-lit-map unfolding lits-of-def by fastforce
  then have get-level  $(\text{Marked } L \ ( ?k + 1) \ \# \ ?M) \ (-L) = ?k + 1$  by simp
  then show  $\exists La. La \in \# D \wedge \text{ get-level } ?M' \ La = \text{ backtrack-lvl } T$ 
    using  $\langle \neg L \in \# D \rangle \ T \ \text{undef}$  by auto
  qed
next
case resolve
then show ?case by auto
next
case skip
then show ?case by auto
next
case (backtrack  $K \ i \ M1 \ M2 \ L \ D \ T$ ) note decomp = this(3) and undef = this(7) and  $T = \text{this}(8)$ 
show ?case
proof (rule HOL.disjI2, clarify)
  fix Da
  assume Da:  $Da \in \# \text{ clauses } T$ 
  and M-D:  $\text{trail } T \models_{as} CNot \ Da$ 
  obtain c where  $M: \text{trail } S = c @ M2 @ \text{Marked } K \ (i + 1) \ \# \ M1$ 
    using decomp by auto
  have tr-T:  $\text{trail } T = \text{Propagated } L \ (\text{mset-ccls } D) \ \# \ M1$ 
    using  $T \ \text{decomp} \ \text{undef} \ \text{lev}$  by (auto simp: cdclW-M-level-inv-decomp)
  have backtrack  $S \ T$ 
    using backtrack-rule[of  $S$ ] backtrack.hyps  $T$ 
    by (force simp del: state-simp simp: state-eq-def)
  then have lev':  $\text{cdcl}_W\text{-M-level-inv } T$ 
    using  $\text{cdcl}_W\text{-consistent-inv } \text{lev} \ \text{other } \text{cdcl}_W\text{-bj.backtrack } \text{cdcl}_W\text{-o.bj}$  by blast
  then have  $\neg L \notin \text{ lits-of-l } M1$ 
    using  $\text{lev } \text{cdcl}_W\text{-M-level-inv-def } \text{Marked-Propagated-in-iff-in-lits-of-l} \ \text{undef}$  by blast
  { assume  $Da \in \# \text{ clauses } S$ 
    then have  $\neg M1 \models_{as} CNot \ Da$  using no-l  $M$  unfolding no-smaller-confl-def by auto
  }
  moreover {
    assume  $Da: Da = \text{mset-ccls } D$ 
    have  $\neg M1 \models_{as} CNot \ Da$  using  $\langle \neg L \notin \text{ lits-of-l } M1 \rangle$  unfolding  $Da$ 
      using backtrack.hyps(2) in-CNot-implies-uminus(2) by auto
  }
  ultimately have  $\neg M1 \models_{as} CNot \ Da$ 
    using  $Da \ T \ \text{undef} \ \text{decomp} \ \text{lev}$  by (fastforce simp:  $\text{cdcl}_W\text{-M-level-inv-decomp}$ )
  then have  $\neg L \in \# Da$ 
    using  $M\text{-D} \ \langle \neg L \notin \text{ lits-of-l } M1 \rangle \ T$  unfolding tr-T true-annots-true-clb true-clss-def
    by (auto simp: uminus-lit-swap)
  have g-M1:  $\text{get-all-levels-of-marked } M1 = \text{rev } [1..<i+1]$ 
    using  $\text{lev } \text{lev}' \ T \ \text{decomp} \ \text{undef}$  unfolding  $\text{cdcl}_W\text{-M-level-inv-def}$  by auto
  have no-dup  $(\text{Propagated } L \ (\text{mset-ccls } D) \ \# \ M1)$ 
    using  $\text{lev } \text{lev}' \ T \ \text{decomp} \ \text{undef}$  unfolding  $\text{cdcl}_W\text{-M-level-inv-def}$  by auto
  then have  $L: \text{atm-of } L \notin \text{ atm-of } ' \text{ lits-of-l } M1$  unfolding lits-of-def by auto

```

```

have get-level (Propagated L (mset-ccls D) # M1) (¬L) = i
  using get-level-get-rev-level-get-all-levels-of-marked[OF L,
    of [Propagated L (mset-ccls D)]]
  by (simp add: g-M1 split: if-splits)
then show ∃ La. La ∈# Da ∧ get-level (trail T) La = backtrack-lvl T
  using (¬L ∈# Da) T decomp undef lev by (auto simp: cdclW-M-level-inv-def)
qed
qed

lemma full1-cdclW-cp-exists-conflict-decompose:
  assumes
    confl: ∃ D ∈ #clauses S. trail S ⊨as CNot D and
    full: full cdclW-cp S U and
    no-confl: conflicting S = None and
    lev: cdclW-M-level-inv S
  shows ∃ T. propagate** S T ∧ conflict T U
proof -
  consider (propa) propagate** S U
    | (confl) T where propagate** S T and conflict T U
  using full unfolding full-def by (blast dest: rtranclp-cdclW-cp-propa-or-propa-confl)
then show ?thesis
proof cases
  case confl
  then show ?thesis by blast
next
  case propa
  then have conflicting U = None and
    [simp]: learned-clss U = learned-clss S and
    [simp]: init-clss U = init-clss S
  using no-confl rtranclp-propagate-is-update-trail lev by auto
  moreover
  obtain D where D: D ∈ #clauses U and
    trS: trail S ⊨as CNot D
  using confl raw-clauses-def by auto
  obtain M where M: trail U = M @ trail S
  using full rtranclp-cdclW-cp-dropWhile-trail unfolding full-def by meson
  have tr-U: trail U ⊨as CNot D
  apply (rule true-annots-mono)
  using trS unfolding M by simp-all
  have ∃ V. conflict U V
  using (conflicting U = None) D raw-clauses-def not-conflict-not-any-negated-init-clss tr-U
  by meson
  then have False using full cdclW-cp.conflict' unfolding full-def by blast
  then show ?thesis by fast
qed
qed

lemma full1-cdclW-cp-exists-conflict-full1-decompose:
  assumes
    confl: ∃ D ∈ #clauses S. trail S ⊨as CNot D and
    full: full cdclW-cp S U and
    no-confl: conflicting S = None and
    lev: cdclW-M-level-inv S
  shows ∃ T D. propagate** S T ∧ conflict T U
    ∧ trail T ⊨as CNot D ∧ conflicting U = Some D ∧ D ∈ #clauses S

```

**proof** –

**obtain**  $T$  **where**  $\text{propa}$ :  $\text{propagate}^{**} S T$  **and**  $\text{conf}$ :  $\text{conflict} T U$   
**using**  $\text{full1-cdcl}_W\text{-cp-exists-conflict-decompose}[OF \text{ assms}]$  **by**  $\text{blast}$   
**have**  $p$ :  $\text{learned-clss } T = \text{learned-clss } S \text{ init-clss } T = \text{init-clss } S$   
**using**  $\text{propa lev rtrancplp-propagate-is-update-trail}$  **by**  $\text{auto}$   
**have**  $c$ :  $\text{learned-clss } U = \text{learned-clss } T \text{ init-clss } U = \text{init-clss } T$   
**using**  $\text{conf}$  **by**  $(\text{auto elim: conflictE})$   
**obtain**  $D$  **where**  $\text{trail } T \models_{as} CNot D \wedge \text{conflicting } U = \text{Some } D \wedge D \in \# \text{ clauses } S$   
**using**  $\text{conf } p c$  **by**  $(\text{fastforce simp: raw-clauses-def elim!: conflictE})$   
**then show**  $?thesis$   
**using**  $\text{propa conf}$  **by**  $\text{blast}$   
**qed**

**lemma**  $\text{cdcl}_W\text{-stgy-no-smaller-conf}$ :

**assumes**  
 $\text{cdcl}_W\text{-stgy } S S'$  **and**  
 $n\text{-l: no-smaller-conf } S$  **and**  
 $\text{conflict-is-false-with-level } S$  **and**  
 $\text{cdcl}_W\text{-M-level-inv } S$  **and**  
 $\text{no-clause-is-false } S$  **and**  
 $\text{distinct-cdcl}_W\text{-state } S$  **and**  
 $\text{cdcl}_W\text{-conflicting } S$

**shows**  $\text{no-smaller-conf } S'$

**using**  $\text{assms}$

**proof** ( $\text{induct rule: cdcl}_W\text{-stgy.induct}$ )

**case**  $(\text{conflict}' S')$

**show**  $\text{no-smaller-conf } S'$

**using**  $\text{conflict}'.\text{hyps conflict}'.\text{prems}(1)$   $\text{full1-cdcl}_W\text{-cp-no-smaller-conf-inv}$  **by**  $\text{blast}$

**next**

**case**  $(\text{other}' S' S'')$

**have**  $\text{lev}'$ :  $\text{cdcl}_W\text{-M-level-inv } S'$

**using**  $\text{cdcl}_W\text{-consistent-inv other other}'.\text{hyps}(1)$   $\text{other}'.\text{prems}(3)$  **by**  $\text{blast}$

**show**  $\text{no-smaller-conf } S''$

**using**  $\text{cdcl}_W\text{-stgy-no-smaller-conf-inv}[OF \text{ cdcl}_W\text{-stgy.other}'[OF \text{ other}'.\text{hyps}(1-3)]]$   
 $\text{other}'.\text{prems}(1-3)$  **by**  $\text{blast}$

**qed**

**lemma**  $\text{cdcl}_W\text{-stgy-ex-lit-of-max-level}$ :

**assumes**

$\text{cdcl}_W\text{-stgy } S S'$  **and**  
 $n\text{-l: no-smaller-conf } S$  **and**  
 $\text{conflict-is-false-with-level } S$  **and**  
 $\text{cdcl}_W\text{-M-level-inv } S$  **and**  
 $\text{no-clause-is-false } S$  **and**  
 $\text{distinct-cdcl}_W\text{-state } S$  **and**  
 $\text{cdcl}_W\text{-conflicting } S$

**shows**  $\text{conflict-is-false-with-level } S'$

**using**  $\text{assms}$

**proof** ( $\text{induct rule: cdcl}_W\text{-stgy.induct}$ )

**case**  $(\text{conflict}' S')$

**have**  $\text{no-smaller-conf } S'$

**using**  $\text{conflict}'.\text{hyps conflict}'.\text{prems}(1)$   $\text{full1-cdcl}_W\text{-cp-no-smaller-conf-inv}$  **by**  $\text{blast}$

**moreover have**  $\text{conflict-is-false-with-level } S'$

**using**  $\text{conflict}'.\text{hyps conflict}'.\text{prems}(2-4)$   
 $\text{rtrancplp-cdcl}_W\text{-co-conflict-ex-lit-of-max-level}[of S S']$

```

    unfolding full-def full1-def rtrancpl-unfold by presburger
  then show ?case by blast
next
case (other' S' S'')
have lev': cdclW-M-level-inv S'
  using cdclW-consistent-inv other other'.hyps(1) other'.prems(3) by blast
moreover
  have no-clause-is-false S'
     $\vee$  (conflicting S' = None  $\longrightarrow$  ( $\forall D \in \# \text{clauses } S'. \text{trail } S' \models_{\text{as}} \text{CNot } D$ 
       $\longrightarrow$  ( $\exists L. L \in \# D \wedge \text{get-level } (\text{trail } S') L = \text{backtrack-lvl } S'$ )))
    using cdclW-o-conflict-is-no-clause-is-false[of S S'] other'.hyps(1) other'.prems(1-4) by fast
moreover {
  assume no-clause-is-false S'
  {
    assume conflicting S' = None
    then have conflict-is-false-with-level S' by auto
    moreover have full cdclW-cp S' S''
      by (metis (no-types) other'.hyps(3))
    ultimately have conflict-is-false-with-level S''
      using rtrancpl-cdclW-co-conflict-ex-lit-of-max-level[of S' S''] lev' <no-clause-is-false S'>
      by blast
  }
  moreover
  {
    assume c: conflicting S'  $\neq$  None
    have conflicting S  $\neq$  None using other'.hyps(1) c
      by (induct rule: cdclW-o-induct) auto
    then have conflict-is-false-with-level S'
      using cdclW-o-conflict-is-false-with-level-inv[OF other'.hyps(1)]
      other'.prems(3,5,6,2) by blast
    moreover have cdclW-cp** S' S'' using other'.hyps(3) unfolding full-def by auto
    then have S' = S'' using c
      by (induct rule: rtrancpl-induct)
      (fastforce intro: option.exhaust)+
    ultimately have conflict-is-false-with-level S'' by auto
  }
  ultimately have conflict-is-false-with-level S'' by blast
}
moreover {
  assume
    confl: conflicting S' = None and
    D-L:  $\forall D \in \# \text{clauses } S'. \text{trail } S' \models_{\text{as}} \text{CNot } D$ 
     $\longrightarrow$  ( $\exists L. L \in \# D \wedge \text{get-level } (\text{trail } S') L = \text{backtrack-lvl } S'$ )
  { assume  $\forall D \in \# \text{clauses } S'. \neg \text{trail } S' \models_{\text{as}} \text{CNot } D$ 
    then have no-clause-is-false S' using confl by simp
    then have conflict-is-false-with-level S'' using calculation(3) by presburger
  }
  moreover {
    assume  $\neg(\forall D \in \# \text{clauses } S'. \neg \text{trail } S' \models_{\text{as}} \text{CNot } D)$ 
    then obtain T D where
      propagate** S' T and
      conflict T S'' and
      D: D  $\in \# \text{clauses } S'$  and
      trail S''  $\models_{\text{as}} \text{CNot } D$  and
      conflicting S'' = Some D
  }
}

```

```

using full1-cdclW-cp-exists-conflict-full1-decompose[OF - - conf]
other'(3) lev' by (metis (mono-tags, lifting) conflictE state-eq-trail
  trail-update-conflicting)
obtain M where M: trail S'' = M @ trail S' and nm:  $\forall m \in \text{set } M. \neg \text{is-marked } m$ 
using rtrancp-cdclW-cp-dropWhile-trail other'(3) unfolding full-def by meson
have btS: backtrack-lvl S'' = backtrack-lvl S'
using other'.hypos(3) unfolding full-def by (metis rtrancp-cdclW-cp-backtrack-lvl)
have inv: cdclW-M-level-inv S''
by (metis (no-types) cdclW-stgy.conflict' cdclW-stgy-consistent-inv full-unfold lev'
  other'.hypos(3))
then have nd: no-dup (trail S'')
by (metis (no-types) cdclW-M-level-inv-decomp(2))
have conflict-is-false-with-level S''
proof cases
assume trail S'  $\models_{as} CNot\ D$ 
moreover then obtain L where
  L  $\in \# D$  and
  lev-L: get-level (trail S') L = backtrack-lvl S'
using D-L D by blast
moreover
have LS':  $-L \in \text{lits-of-l (trail } S')$ 
using  $\langle \text{trail } S' \models_{as} CNot\ D \rangle \langle L \in \# D \rangle$  in-CNot-implies-uminus(2) by blast
{ fix x :: ('v, nat, 'v clause) marked-lit and
  xb :: ('v, nat, 'v clause) marked-lit
assume a1: x  $\in \text{set (trail } S')$  and
  a2: xb  $\in \text{set } M$  and
  a3:  $(\lambda l. \text{atm-of (lit-of } l)) \text{ ' set } M \cap (\lambda l. \text{atm-of (lit-of } l)) \text{ ' set (trail } S') = \{\}$  and
  a4:  $-L = \text{lit-of } x$  and
  a5: atm-of L = atm-of (lit-of xb)
moreover have atm-of (lit-of x) = atm-of L
using a4 by (metis (no-types) atm-of-uminus)
ultimately have False
using a5 a3 a2 a1 by auto
}
then have atm-of L  $\notin \text{atm-of ' lits-of-l } M$ 
using nd LS' unfolding M by (auto simp add: lits-of-def)
then have get-level (trail S'') L = get-level (trail S') L
unfolding M by (simp add: lits-of-def)
ultimately show ?thesis using btS  $\langle \text{conflicting } S'' = \text{Some } D \rangle$  by auto
next
assume  $\neg \text{trail } S' \models_{as} CNot\ D$ 
then obtain L where L  $\in \# D$  and LM:  $-L \in \text{lits-of-l } M$ 
using  $\langle \text{trail } S'' \models_{as} CNot\ D \rangle$  unfolding M
by (auto simp add: true-cls-def M true-annots-def true-annot-def
  split: if-split-asm)
{ fix x :: ('v, nat, 'v clause) marked-lit and
  xb :: ('v, nat, 'v clause) marked-lit
assume a1: xb  $\in \text{set (trail } S')$  and
  a2: x  $\in \text{set } M$  and
  a3: atm-of L = atm-of (lit-of xb) and
  a4:  $-L = \text{lit-of } x$  and
  a5:  $(\lambda l. \text{atm-of (lit-of } l)) \text{ ' set } M \cap (\lambda l. \text{atm-of (lit-of } l)) \text{ ' set (trail } S') = \{\}$ 
moreover have atm-of (lit-of xb) = atm-of ( $-L$ )

```



```

    using a3 by simp
    ultimately have False
    by auto }
then have  $LS'$ :  $\text{atm-of } L \notin \text{atm-of ' lits-of-l (trail } S')$ 
    using nd  $\langle L \in \# D \rangle$  LM unfolding M by (auto simp add: lits-of-def)
show ?thesis
proof cases
  assume ne:  $\text{get-all-levels-of-marked (trail } S') = []$ 
  have backtrack-lvl  $S'' = 0$ 
    using inv ne nm unfolding  $\text{cdcl}_W$ -M-level-inv-def M
    by (simp add: get-all-levels-of-marked-nil-iff-not-is-marked)
  moreover
  have a1:  $\text{get-level } M L = 0$ 
    using nm by auto
  then have  $\text{get-level (M @ trail } S') L = 0$ 
    by (metis  $LS'$  get-all-levels-of-marked-nil-iff-not-is-marked
      get-level-skip-beginning-not-marked lits-of-def ne)
  ultimately show ?thesis using  $\langle \text{conflicting } S'' = \text{Some } D \rangle \langle L \in \# D \rangle$  unfolding M
    by auto
next
  assume ne:  $\text{get-all-levels-of-marked (trail } S') \neq []$ 
  have hd  $(\text{get-all-levels-of-marked (trail } S')) = \text{backtrack-lvl } S'$ 
    using ne lev' M nm unfolding  $\text{cdcl}_W$ -M-level-inv-def
    by (cases  $\text{get-all-levels-of-marked (trail } S')$ )
    (simp-all add: get-all-levels-of-marked-nil-iff-not-is-marked[symmetric])
  moreover have  $\text{atm-of } L \in \text{atm-of ' lits-of-l } M$ 
    using  $\langle -L \in \text{lits-of-l } M \rangle$ 
    by (simp add: atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set lits-of-def)
  ultimately show ?thesis
    using nm ne  $\langle L \in \# D \rangle \langle \text{conflicting } S'' = \text{Some } D \rangle$ 
      get-level-skip-beginning-hd-get-all-levels-of-marked[OF  $LS'$ , of M]
      get-level-skip-in-all-not-marked[of rev M L backtrack-lvl  $S'$ ]
    unfolding lits-of-def btS M
    by auto
qed
qed
}
ultimately have  $\text{conflict-is-false-with-level } S''$  by blast
}
moreover
{
  assume conflicting  $S' \neq \text{None}$ 
  have no-clause-is-false  $S'$  using  $\langle \text{conflicting } S' \neq \text{None} \rangle$  by auto
  then have  $\text{conflict-is-false-with-level } S''$  using calculation(3) by presburger
}
ultimately show ?case by fast
qed

lemma rtrancp-cdclW-stgy-no-smaller-confl-inv:
  assumes
     $\text{cdcl}_W\text{-stgy}^{**} S S'$  and
     $n\text{-l: no-smaller-confl } S$  and
     $\text{cls-false: conflict-is-false-with-level } S$  and
     $\text{lev: cdcl}_W\text{-M-level-inv } S$  and
     $\text{no-f: no-clause-is-false } S$  and

```

*dist*: *distinct-cdcl<sub>W</sub>-state* *S* **and**  
*conflicting*: *cdcl<sub>W</sub>-conflicting* *S* **and**  
*decomp*: *all-decomposition-implies-m* (*init-clss* *S*) (*get-all-marked-decomposition* (*trail* *S*)) **and**  
*learned*: *cdcl<sub>W</sub>-learned-clause* *S* **and**  
*alien*: *no-strange-atm* *S*  
**shows** *no-smaller-confl* *S'*  $\wedge$  *conflict-is-false-with-level* *S'*  
**using** *assms*(1)  
**proof** (*induct* rule: *rtranclp-induct*)  
**case** *base*  
**then show** ?*case* **using** *n-l cls-false* **by** *auto*  
**next**  
**case** (*step* *S' S''*) **note** *st* = *this*(1) **and** *cdcl* = *this*(2) **and** *IH* = *this*(3)  
**have** *no-smaller-confl* *S'* **and** *conflict-is-false-with-level* *S'*  
**using** *IH* **by** *blast*+  
**moreover have** *cdcl<sub>W</sub>-M-level-inv* *S'*  
**using** *st lev rtranclp-cdcl<sub>W</sub>-stgy-rtranclp-cdcl<sub>W</sub>*  
**by** (*blast intro: rtranclp-cdcl<sub>W</sub>-consistent-inv*)+  
**moreover have** *no-clause-is-false* *S'*  
**using** *st no-f rtranclp-cdcl<sub>W</sub>-stgy-not-non-negated-init-clss* **by** *presburger*  
**moreover have** *distinct-cdcl<sub>W</sub>-state* *S'*  
**using** *rtanclp-distinct-cdcl<sub>W</sub>-state-inv*[*of S S'*] *lev rtranclp-cdcl<sub>W</sub>-stgy-rtranclp-cdcl<sub>W</sub>*[*OF st*]  
*dist* **by** *auto*  
**moreover have** *cdcl<sub>W</sub>-conflicting* *S'*  
**using** *rtranclp-cdcl<sub>W</sub>-all-inv*(6)[*of S S'*] *st alien conflicting decomp dist learned lev*  
*rtranclp-cdcl<sub>W</sub>-stgy-rtranclp-cdcl<sub>W</sub>* **by** *blast*  
**ultimately show** ?*case*  
**using** *cdcl<sub>W</sub>-stgy-no-smaller-confl*[*OF cdcl*] *cdcl<sub>W</sub>-stgy-ex-lit-of-max-level*[*OF cdcl*] **by** *fast*  
**qed**

### 19.5.7 Final States are Conclusive

**lemma** *full-cdcl<sub>W</sub>-stgy-final-state-conclusive-non-false*:  
**fixes** *S' :: 'st*  
**assumes** *full*: *full cdcl<sub>W</sub>-stgy* (*init-state* *N*) *S'*  
**and** *no-d*: *distinct-mset-mset* (*mset-clss* *N*)  
**and** *no-empty*:  $\forall D \in \#mset-clss\ N. D \neq \{\#\}$   
**shows** (*conflicting* *S'* = *Some*  $\{\#\}$   $\wedge$  *unsatisfiable* (*set-mset* (*init-clss* *S'*)))  
 $\vee$  (*conflicting* *S'* = *None*  $\wedge$  *trail* *S'*  $\models_{asm}$  *init-clss* *S'*)  
**proof** –  
**let** ?*S* = *init-state* *N*  
**have**  
*termi*:  $\forall S''. \neg cdcl_W-stgy\ S'\ S''$  **and**  
*step*: *cdcl<sub>W</sub>-stgy*\*\* ?*S S'* **using** *full unfolding full-def* **by** *auto*  
**moreover have**  
*learned*: *cdcl<sub>W</sub>-learned-clause* *S'* **and**  
*level-inv*: *cdcl<sub>W</sub>-M-level-inv* *S'* **and**  
*alien*: *no-strange-atm* *S'* **and**  
*no-dup*: *distinct-cdcl<sub>W</sub>-state* *S'* **and**  
*confl*: *cdcl<sub>W</sub>-conflicting* *S'* **and**  
*decomp*: *all-decomposition-implies-m* (*init-clss* *S'*) (*get-all-marked-decomposition* (*trail* *S'*))  
**using** *no-d tranclp-cdcl<sub>W</sub>-stgy-tranclp-cdcl<sub>W</sub>*[*of ?S S'*] *step rtranclp-cdcl<sub>W</sub>-all-inv*(1–6)[*of ?S S'*]  
**unfolding** *rtranclp-unfold* **by** *auto*  
**moreover**  
**have**  $\forall D \in \#mset-clss\ N. \neg [] \models_{as} CNot\ D$  **using** *no-empty* **by** *auto*  
**then have** *confl-k*: *conflict-is-false-with-level* *S'*  
**using** *rtranclp-cdcl<sub>W</sub>-stgy-no-smaller-confl-inv*[*OF step*] *no-d* **by** *auto*

**show** ?thesis  
 using *cdcl<sub>W</sub>-stgy-final-state-conclusive*[*OF termi decomp learned level-inv alien no-dup confl*  
*conf1-k*] .  
**qed**

**lemma** *conflict-is-full1-cdcl<sub>W</sub>-cp*:  
 assumes *cp*: *conflict S S'*  
 shows *full1 cdcl<sub>W</sub>-cp S S'*  
**proof** –  
 have *cdcl<sub>W</sub>-cp S S'* **and** *conflicting S' ≠ None*  
 using *cp cdcl<sub>W</sub>-cp.intros* **by** (*auto elim!*: *conflictE simp: state-eq-def simp del: state-simp*)  
 then have *cdcl<sub>W</sub>-cp<sup>++</sup> S S'* **by** *blast*  
 moreover have *no-step cdcl<sub>W</sub>-cp S'*  
 using *⟨conflicting S' ≠ None⟩* **by** (*metis cdcl<sub>W</sub>-cp-conflicting-not-empty*  
*option.exhaust*)  
 ultimately show *full1 cdcl<sub>W</sub>-cp S S'* **unfolding** *full1-def* **by** *blast+*  
**qed**

**lemma** *cdcl<sub>W</sub>-cp-fst-empty-conflicting-false*:  
 assumes  
   *cdcl<sub>W</sub>-cp S S'* **and**  
   *trail S = []* **and**  
   *conflicting S ≠ None*  
 shows *False*  
 using *assms* **by** (*induct rule: cdcl<sub>W</sub>-cp.induct*) (*auto elim: propagateE conflictE*)

**lemma** *cdcl<sub>W</sub>-o-fst-empty-conflicting-false*:  
 assumes *cdcl<sub>W</sub>-o S S'*  
 and *trail S = []*  
 and *conflicting S ≠ None*  
 shows *False*  
 using *assms* **by** (*induct rule: cdcl<sub>W</sub>-o.induct*) *auto*

**lemma** *cdcl<sub>W</sub>-stgy-fst-empty-conflicting-false*:  
 assumes *cdcl<sub>W</sub>-stgy S S'*  
 and *trail S = []*  
 and *conflicting S ≠ None*  
 shows *False*  
 using *assms* **apply** (*induct rule: cdcl<sub>W</sub>-stgy.induct*)  
 using *tranc1pD cdcl<sub>W</sub>-cp-fst-empty-conflicting-false* **unfolding** *full1-def* **apply** *metis*  
 using *cdcl<sub>W</sub>-o-fst-empty-conflicting-false* **by** *blast*  
**thm** *cdcl<sub>W</sub>-cp.induct[split-format(complete)]*

**lemma** *cdcl<sub>W</sub>-cp-conflicting-is-false*:  
*cdcl<sub>W</sub>-cp S S' ⟹ conflicting S = Some {#} ⟹ False*  
**by** (*induction rule: cdcl<sub>W</sub>-cp.induct*) (*auto elim: propagateE conflictE*)

**lemma** *rtranc1p-cdcl<sub>W</sub>-cp-conflicting-is-false*:  
*cdcl<sub>W</sub>-cp<sup>++</sup> S S' ⟹ conflicting S = Some {#} ⟹ False*  
**apply** (*induction rule: tranc1p.induct*)  
**by** (*auto dest: cdcl<sub>W</sub>-cp-conflicting-is-false*)

**lemma** *cdcl<sub>W</sub>-o-conflicting-is-false*:  
*cdcl<sub>W</sub>-o S S' ⟹ conflicting S = Some {#} ⟹ False*

```

by (induction rule: cdclW-o-induct) auto

lemma cdclW-stgy-conflicting-is-false:
  cdclW-stgy  $S S' \implies$  conflicting  $S = \text{Some } \{\#\} \implies \text{False}$ 
  apply (induction rule: cdclW-stgy.induct)
  unfolding full1-def apply (metis (no-types) cdclW-cp-conflicting-not-empty tranclpD)
  unfolding full-def by (metis conflict-with-false-implies-terminated other)

lemma rtranclp-cdclW-stgy-conflicting-is-false:
  cdclW-stgy**  $S S' \implies$  conflicting  $S = \text{Some } \{\#\} \implies S' = S$ 
  apply (induction rule: rtranclp-induct)
  apply simp
  using cdclW-stgy-conflicting-is-false by blast

lemma full-cdclW-init-clss-with-false-normal-form:
  assumes
     $\forall m \in \text{set } M. \neg \text{is-marked } m$  and
     $E = \text{Some } D$  and
    state  $S = (M, N, U, 0, E)$ 
  full cdclW-stgy  $S S'$  and
  all-decomposition-implies-m (init-clss  $S$ ) (get-all-marked-decomposition (trail  $S$ ))
  cdclW-learned-clause  $S$ 
  cdclW-M-level-inv  $S$ 
  no-strange-atm  $S$ 
  distinct-cdclW-state  $S$ 
  cdclW-conflicting  $S$ 
  shows  $\exists M''. \text{state } S' = (M'', N, U, 0, \text{Some } \{\#\})$ 
  using assms(10,9,8,7,6,5,4,3,2,1)
proof (induction  $M$  arbitrary:  $E D S$ )
  case Nil
  then show ?case
    using rtranclp-cdclW-stgy-conflicting-is-false unfolding full-def cdclW-conflicting-def
    by fastforce
next
  case (Cons  $L M$ ) note  $IH = \text{this}(1)$  and  $\text{full} = \text{this}(8)$  and  $E = \text{this}(10)$  and  $\text{inv} = \text{this}(2-7)$  and
     $S = \text{this}(9)$  and  $\text{nm} = \text{this}(11)$ 
  obtain  $K p$  where  $K: L = \text{Propagated } K p$ 
  using  $\text{nm}$  by (cases  $L$ ) auto
  have every-mark-is-a-conflict  $S$  using  $\text{inv}$  unfolding cdclW-conflicting-def by auto
  then have  $MpK: M \models_{\text{as}} \text{CNot } (p - \{\#K\# \})$  and  $Kp: K \in \# p$ 
  using  $S$  unfolding  $K$  by fastforce+
  then have  $p: p = (p - \{\#K\# \}) + \{\#K\# \}$ 
  by (auto simp add: multiset-eq-iff)
  then have  $K': L = \text{Propagated } K ((p - \{\#K\# \}) + \{\#K\# \})$ 
  using  $K$  by auto
  obtain  $p'$  where
     $p': \text{hd-raw-trail } S = \text{Propagated } K p'$  and
     $pp': \text{mset-cls } p' = p$ 
  using  $\text{hd-raw-trail}[of S] S K$  by (cases  $\text{hd-raw-trail } S$ ) auto
  obtain  $\text{raw-}D$  where
     $\text{raw-}D: \text{raw-conflicting } S = \text{Some raw-}D$ 
  using  $S E$  by (cases  $\text{raw-conflicting } S$ ) auto
  then have  $\text{raw-}DD: \text{mset-ccls raw-}D = D$ 
  using  $S E$  by auto
  consider  $(D) D = \{\#\} \mid (D') D \neq \{\#\}$  by blast

```

```

then show ?case
proof cases
  case D
  then show ?thesis
    using full rtrancpl-cdclW-stgy-conflicting-is-false S unfolding full-def E D by auto
next
  case D'
  then have no-p: no-step propagate S and no-c: no-step conflict S
    using S E by (auto elim: propagateE conflictE)
  then have no-step cdclW-cp S by (auto simp: cdclW-cp.simps)
  have res-skip:  $\exists T. (resolve\ S\ T \wedge no\text{-}step\ skip\ S \wedge full\ cdcl_W\text{-}cp\ T\ T) \vee (skip\ S\ T \wedge no\text{-}step\ resolve\ S \wedge full\ cdcl_W\text{-}cp\ T\ T)$ 
  proof cases
    assume  $\neg lit\text{-}of\ L \notin \# D$ 
    then obtain T where sk: skip S T
      using S D' K skip-rule unfolding E by fastforce
    then have res: no-step resolve S
      using  $\langle \neg lit\text{-}of\ L \notin \# D \rangle S\ D'\ K\ hd\text{-}raw\text{-}trail[of\ S]$  unfolding E
      by (auto elim!: skipE resolveE)
    have full cdclW-cp T T
      using sk by (auto intro!: option-full-cdclW-cp elim: skipE)
    then show ?thesis
      using sk res by blast
  next
    assume LD:  $\neg \neg lit\text{-}of\ L \notin \# D$ 
    then have D: Some D = Some ((D - { $\#lit\text{-}of\ L\ \#$ }) + { $\#lit\text{-}of\ L\ \#$ })
      by (auto simp add: multiset-eq-iff)

    have  $\bigwedge L. get\text{-}level\ M\ L = 0$ 
      by (simp add: nm)
    then have get-maximum-level (Propagated K (p - { $\#K\ \#$ } + { $\#K\ \#$ })  $\# M$ ) (D - { $\#lit\text{-}of\ L\ \#$ } - { $\#K\ \#$ }) = 0
      using LD get-maximum-level-exists-lit-of-max-level
    proof -
      obtain L' where get-level (L $\#M$ ) L' = get-maximum-level (L $\#M$ ) D
        using LD get-maximum-level-exists-lit-of-max-level[of D L $\#M$ ] by fastforce
      then show ?thesis by (metis (mono-tags) K' get-level-skip-all-not-marked
        get-maximum-level-exists-lit nm not-gr0)
    qed
    then obtain T where sk: resolve S T
      using resolve-rule[of S K p' raw-D] S p'  $\langle K \in \# p \rangle raw\text{-}D\ LD$ 
      unfolding K' D E pp' raw-DD by auto
    then have res: no-step skip S
      using LD S D' K hd-raw-trail[of S] unfolding E
      by (auto elim!: skipE resolveE)
    have full cdclW-cp T T
      using sk by (auto simp: option-full-cdclW-cp elim: resolveE)
    then show ?thesis
      using sk res by blast
  qed
then have step-s:  $\exists T. cdcl_W\text{-}stgy\ S\ T$ 
  using (no-step cdclW-cp S) other' by (meson bj resolve skip)
have get-all-marked-decomposition (L  $\# M$ ) = [( $\square$ ), L $\#M$ ]
  using nm unfolding K apply (induction M rule: marked-lit-list-induct, simp)
  by (rename-tac L l xs, case-tac hd (get-all-marked-decomposition xs), auto)+

```

```

then have no-b: no-step backtrack S
  using nm S by (auto elim: backtrackE)
have no-d: no-step decide S
  using S E by (auto elim: decideE)

have full-S-S: full cdclW-cp S S
  using S E by (auto simp add: option-full-cdclW-cp)
then have no-f: no-step (full1 cdclW-cp) S
  unfolding full-def full1-def rtrancpl-unfold by (meson trancplD)
obtain T where
  s: cdclW-stgy S T and st: cdclW-stgy** T S'
  using full step-s full unfolding full-def by (metis rtrancpl-unfold trancplD)
have resolve S T ∨ skip S T
  using s no-b no-d res-skip full-S-S cdclW-cp-state-eq-compatible resolve-unique
  skip-unique unfolding cdclW-stgy.simps cdclW-o.simps full-unfold
  full1-def by (blast dest!: trancplD elim!: cdclW-bj.cases)+
then obtain D' where T: state T = (M, N, U, 0, Some D')
  using S E by (auto elim!: skipE resolveE simp: state-eq-def simp del: state-simp)

have st-c: cdclW** S T
  using E T rtrancpl-cdclW-stgy-rtrancpl-cdclW s by blast
have cdclW-conflicting T
  using rtrancpl-cdclW-all-inv(6)[OF st-c inv(6,5,4,3,2,1)] .
show ?thesis
  apply (rule IH[of T])
    using rtrancpl-cdclW-all-inv(6)[OF st-c inv(6,5,4,3,2,1)] apply blast
    using rtrancpl-cdclW-all-inv(5)[OF st-c inv(6,5,4,3,2,1)] apply blast
    using rtrancpl-cdclW-all-inv(4)[OF st-c inv(6,5,4,3,2,1)] apply blast
    using rtrancpl-cdclW-all-inv(3)[OF st-c inv(6,5,4,3,2,1)] apply blast
    using rtrancpl-cdclW-all-inv(2)[OF st-c inv(6,5,4,3,2,1)] apply blast
    using rtrancpl-cdclW-all-inv(1)[OF st-c inv(6,5,4,3,2,1)] apply blast
  apply (metis full-def st full)
  using T E apply blast
  apply auto[]
  using nm by simp
qed
qed

lemma full-cdclW-stgy-final-state-conclusive-is-one-false:
  fixes S' :: 'st
  assumes full: full cdclW-stgy (init-state N) S'
  and no-d: distinct-mset-mset (mset-clss N)
  and empty: {#} ∈# (mset-clss N)
  shows conflicting S' = Some {#} ∧ unsatisfiable (set-mset (init-clss S'))
proof -
  let ?S = init-state N
  have cdclW-stgy** ?S S' and no-step cdclW-stgy S' using full unfolding full-def by auto
  then have plus-or-eq: cdclW-stgy++ ?S S' ∨ S' = ?S unfolding rtrancpl-unfold by auto
  have ∃ S''. conflict ?S S''
    using empty not-conflict-not-any-negated-init-clss[of init-state N] by auto
  then have cdclW-stgy: ∃ S'. cdclW-stgy ?S S'
    using cdclW-cp.conflict'[of ?S] conflict-is-full1-cdclW-cp cdclW-stgy.intros(1) by metis
  have S' ≠ ?S using (no-step cdclW-stgy S') cdclW-stgy by blast

```

```

then obtain St:: 'st where St: cdclW-stgy ?S St and cdclW-stgy** St S'
  using plus-or-eq by (metis (no-types) ⟨cdclW-stgy** ?S S'⟩ converse-rtranclpE)
have st: cdclW** ?S St
  by (simp add: rtranclp-unfold ⟨cdclW-stgy ?S St⟩ cdclW-stgy-tranclp-cdclW)

have ∃ T. conflict ?S T
  using empty not-conflict-not-any-negated-init-clss[of ?S] by force
then have fullSt: full1 cdclW-cp ?S St
  using St unfolding cdclW-stgy.simps by blast
then have bt: backtrack-lvl St = (0::nat)
  using rtranclp-cdclW-cp-backtrack-lvl unfolding full1-def
  by (fastforce dest!: tranclp-into-rtranclp)
have cls-St: init-clss St = mset-clss N
  using fullSt cdclW-stgy-no-more-init-clss[OF St] by auto
have conflicting St ≠ None
  proof (rule ccontr)
    assume conf: ¬ ?thesis
    obtain E where
      ES: E !∈! raw-init-clss St and
      E: mset-cls E = {#}
    using empty cls-St by (metis in-mset-clss-exists-preimage)
    then have ∃ T. conflict St T
      using empty cls-St conflict-rule[of St E] ES conf unfolding E
      by (auto simp: raw-clauses-def dest: in-mset-clss-exists-preimage)
    then show False using fullSt unfolding full1-def by blast
  qed

have 1: ∀ m∈set (trail St). ¬ is-marked m
  using fullSt unfolding full1-def by (auto dest!: tranclp-into-rtranclp
    rtranclp-cdclW-cp-dropWhile-trail)
have 2: full cdclW-stgy St S'
  using ⟨cdclW-stgy** St S'⟩ ⟨no-step cdclW-stgy S'⟩ bt unfolding full-def by auto
have 3: all-decomposition-implies-m
  (init-clss St)
  (get-all-marked-decomposition
    (trail St))
  using rtranclp-cdclW-all-inv(1)[OF st] no-d bt by simp
have 4: cdclW-learned-clause St
  using rtranclp-cdclW-all-inv(2)[OF st] no-d bt by simp
have 5: cdclW-M-level-inv St
  using rtranclp-cdclW-all-inv(3)[OF st] no-d bt by simp
have 6: no-strange-atm St
  using rtranclp-cdclW-all-inv(4)[OF st] no-d bt by simp
have 7: distinct-cdclW-state St
  using rtranclp-cdclW-all-inv(5)[OF st] no-d bt by simp
have 8: cdclW-conflicting St
  using rtranclp-cdclW-all-inv(6)[OF st] no-d bt by simp
have init-clss S' = init-clss St and conflicting S' = Some {#}
  using ⟨conflicting St ≠ None⟩ full-cdclW-init-clss-with-false-normal-form[OF 1, of - - St]
  2 3 4 5 6 7 8 St apply (metis ⟨cdclW-stgy** St S'⟩ rtranclp-cdclW-stgy-no-more-init-clss)
  using ⟨conflicting St ≠ None⟩ full-cdclW-init-clss-with-false-normal-form[OF 1, of - - St - -
    S'] 2 3 4 5 6 7 8 by (metis bt option.exhaust prod.inject)

moreover have init-clss S' = mset-clss N

```

```

    using ⟨cdclW-stgy** (init-state N) S'⟩ rtranclp-cdclW-stgy-no-more-init-clss by fastforce
  moreover have unsatisfiable (set-mset (mset-clss N))
    by (meson empty satisfiable-def true-clss-empty true-clss-def)
  ultimately show ?thesis by auto
qed

```

**lemma** *full-cdcl<sub>W</sub>-stgy-final-state-conclusive*:

```

  fixes S' :: 'st
  assumes full: full cdclW-stgy (init-state N) S' and no-d: distinct-mset-mset (mset-clss N)
  shows (conflicting S' = Some {#} ∧ unsatisfiable (set-mset (init-clss S')))
    ∨ (conflicting S' = None ∧ trail S' ⊨asm init-clss S')
  using assms full-cdclW-stgy-final-state-conclusive-is-one-false
  full-cdclW-stgy-final-state-conclusive-non-false by blast

```

**lemma** *full-cdcl<sub>W</sub>-stgy-final-state-conclusive-from-init-state*:

```

  fixes S' :: 'st
  assumes full: full cdclW-stgy (init-state N) S'
  and no-d: distinct-mset-mset (mset-clss N)
  shows (conflicting S' = Some {#} ∧ unsatisfiable (set-mset (mset-clss N)))
    ∨ (conflicting S' = None ∧ trail S' ⊨asm (mset-clss N) ∧ satisfiable (set-mset (mset-clss N)))

```

**proof** –

```

  have N: init-clss S' = (mset-clss N)
    using full unfolding full-def by (auto dest: rtranclp-cdclW-stgy-no-more-init-clss)
  consider

```

```

    (confl) conflicting S' = Some {#} and unsatisfiable (set-mset (init-clss S'))
  | (sat) conflicting S' = None and trail S' ⊨asm init-clss S'
  using full-cdclW-stgy-final-state-conclusive[OF assms] by auto

```

**then show** ?thesis

**proof** cases

case confl

then show ?thesis by (auto simp: N)

next

case sat

have cdcl<sub>W</sub>-M-level-inv (init-state N) by auto

then have cdcl<sub>W</sub>-M-level-inv S'

using full rtranclp-cdcl<sub>W</sub>-stgy-consistent-inv unfolding full-def by blast

then have consistent-interp (lits-of-l (trail S')) unfolding cdcl<sub>W</sub>-M-level-inv-def by blast

moreover have lits-of-l (trail S') ⊨<sub>s</sub> set-mset (init-clss S')

using sat(2) by (auto simp add: true-annots-def true-annot-def true-clss-def)

ultimately have satisfiable (set-mset (init-clss S')) by simp

then show ?thesis using sat unfolding N by blast

qed

qed

end

end

**theory** *CDCL-W-Termination*

**imports** *CDCL-W*

**begin**

**context** *conflict-driven-clause-learning<sub>W</sub>*

**begin**



## 19.6 Termination

The condition that no learned clause is a tautology is overkill (in the sense that the no-duplicate condition is enough), but we can reuse *simple-clss*.

The invariant contains all the structural invariants that holds,

**definition** *cdcl<sub>W</sub>-all-struct-inv* **where**

*cdcl<sub>W</sub>-all-struct-inv*  $S \longleftrightarrow$   
 $\text{no-strange-atm } S \wedge$   
 $\text{cdcl}_W\text{-M-level-inv } S \wedge$   
 $(\forall s \in \# \text{ learned-clss } S. \neg \text{tautology } s) \wedge$   
 $\text{distinct-cdcl}_W\text{-state } S \wedge$   
 $\text{cdcl}_W\text{-conflicting } S \wedge$   
 $\text{all-decomposition-implies-m } (\text{init-clss } S) (\text{get-all-marked-decomposition } (\text{trail } S)) \wedge$   
 $\text{cdcl}_W\text{-learned-clause } S$

**lemma** *cdcl<sub>W</sub>-all-struct-inv-inv*:

**assumes** *cdcl<sub>W</sub> S S'* **and** *cdcl<sub>W</sub>-all-struct-inv S*

**shows** *cdcl<sub>W</sub>-all-struct-inv S'*

**unfolding** *cdcl<sub>W</sub>-all-struct-inv-def*

**proof** (*intro HOL.conjI*)

**show** *no-strange-atm S'*

**using** *cdcl<sub>W</sub>-all-inv[OF assms(1)] assms(2)* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *auto*

**show** *cdcl<sub>W</sub>-M-level-inv S'*

**using** *cdcl<sub>W</sub>-all-inv[OF assms(1)] assms(2)* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *fast*

**show** *distinct-cdcl<sub>W</sub>-state S'*

**using** *cdcl<sub>W</sub>-all-inv[OF assms(1)] assms(2)* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *fast*

**show** *cdcl<sub>W</sub>-conflicting S'*

**using** *cdcl<sub>W</sub>-all-inv[OF assms(1)] assms(2)* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *fast*

**show** *all-decomposition-implies-m (init-clss S') (get-all-marked-decomposition (trail S'))*

**using** *cdcl<sub>W</sub>-all-inv[OF assms(1)] assms(2)* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *fast*

**show** *cdcl<sub>W</sub>-learned-clause S'*

**using** *cdcl<sub>W</sub>-all-inv[OF assms(1)] assms(2)* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *fast*

**show**  $\forall s \in \# \text{learned-clss } S'. \neg \text{tautology } s$

**using** *assms(1)[THEN learned-clss-are-not-tautologies] assms(2)*

**unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *fast*

**qed**

**lemma** *rtrancpl-cdcl<sub>W</sub>-all-struct-inv-inv*:

**assumes** *cdcl<sub>W</sub>\*\* S S'* **and** *cdcl<sub>W</sub>-all-struct-inv S*

**shows** *cdcl<sub>W</sub>-all-struct-inv S'*

**using** *assms* **by** *induction (auto intro: cdcl<sub>W</sub>-all-struct-inv-inv)*

**lemma** *cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-all-struct-inv*:

*cdcl<sub>W</sub>-stgy S T  $\implies$  cdcl<sub>W</sub>-all-struct-inv S  $\implies$  cdcl<sub>W</sub>-all-struct-inv T*

**by** (*meson cdcl<sub>W</sub>-stgy-trancpl-cdcl<sub>W</sub> rtrancpl-cdcl<sub>W</sub>-all-struct-inv-inv rtrancpl-unfold*)

**lemma** *rtrancpl-cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-all-struct-inv*:

*cdcl<sub>W</sub>-stgy\*\* S T  $\implies$  cdcl<sub>W</sub>-all-struct-inv S  $\implies$  cdcl<sub>W</sub>-all-struct-inv T*

**by** (*induction rule: rtrancpl-induct*) (*auto intro: cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-all-struct-inv*)

## 19.7 No Relearning of a clause

**lemma** *cdcl<sub>W</sub>-o-new-clause-learned-is-backtrack-step*:

**assumes** *learned: D  $\in$  # learned-clss T* **and**

*new*:  $D \notin \# \text{ learned-clss } S$  **and**  
*cdcl<sub>W</sub>*: *cdcl<sub>W</sub>-o*  $S \ T$  **and**  
*lev*: *cdcl<sub>W</sub>-M-level-inv*  $S$   
**shows** *backtrack*  $S \ T \wedge \text{conflicting } S = \text{Some } D$   
**using** *cdcl<sub>W</sub>* *lev* *learned new*  
**proof** (*induction rule*: *cdcl<sub>W</sub>-o-induct-lev2*)  
**case** (*backtrack*  $K \ i \ M1 \ M2 \ L \ C \ T$ ) **note** *decomp* = *this*(3) **and** *undef* = *this*(6) **and** *andef* = *this*(7)  
**and**  
 $T = \text{this}(8)$  **and**  $D-T = \text{this}(9)$  **and**  $D-S = \text{this}(10)$   
**then have**  $D = \text{mset-ccls } C$   
**using** *not-gr0 lev* **by** (*auto simp*: *cdcl<sub>W</sub>-M-level-inv-decomp*)  
**then show** ?*case*  
**using**  $T$  *backtrack.hyps*(1–5) *backtrack.intros*[*OF backtrack.hyps*(1,2)] *backtrack.hyps*(3–6)  
**by** *auto*  
**qed** *auto*

**lemma** *cdcl<sub>W</sub>-cp-new-clause-learned-has-backtrack-step*:  
**assumes** *learned*:  $D \in \# \text{ learned-clss } T$  **and**  
*new*:  $D \notin \# \text{ learned-clss } S$  **and**  
*cdcl<sub>W</sub>*: *cdcl<sub>W</sub>-stgy*  $S \ T$  **and**  
*lev*: *cdcl<sub>W</sub>-M-level-inv*  $S$   
**shows**  $\exists S'. \text{backtrack } S \ S' \wedge \text{cdcl}_W\text{-stgy}^{**} S' \ T \wedge \text{conflicting } S = \text{Some } D$   
**using** *cdcl<sub>W</sub>* *learned new*  
**proof** (*induction rule*: *cdcl<sub>W</sub>-stgy.induct*)  
**case** (*conflict'*  $S'$ )  
**then show** ?*case*  
**unfolding** *full1-def* **by** (*metis* (*mono-tags*, *lifting*) *rtranclp-cdcl<sub>W</sub>-cp-learned-clause-inv*  
*trancplp-into-rtranclp*)  
**next**  
**case** (*other'*  $S' \ S''$ )  
**then have**  $D \in \# \text{ learned-clss } S'$   
**unfolding** *full-def* **by** (*auto dest*: *rtranclp-cdcl<sub>W</sub>-cp-learned-clause-inv*)  
**then show** ?*case*  
**using** *cdcl<sub>W</sub>-o-new-clause-learned-is-backtrack-step*[*OF* -  $\langle D \notin \# \text{ learned-clss } S \rangle \langle \text{cdcl}_W\text{-o } S \ S' \rangle$ ]  
 $\langle \text{full cdcl}_W\text{-cp } S' \ S'' \rangle$  *lev* **by** (*metis* *cdcl<sub>W</sub>-stgy.conflict'* *full-unfold r-into-rtranclp*  
*rtranclp.rtrancl-refl*)  
**qed**

**lemma** *rtranclp-cdcl<sub>W</sub>-cp-new-clause-learned-has-backtrack-step*:  
**assumes** *learned*:  $D \in \# \text{ learned-clss } T$  **and**  
*new*:  $D \notin \# \text{ learned-clss } S$  **and**  
*cdcl<sub>W</sub>*: *cdcl<sub>W</sub>-stgy*<sup>\*\*</sup>  $S \ T$  **and**  
*lev*: *cdcl<sub>W</sub>-M-level-inv*  $S$   
**shows**  $\exists S' \ S''. \text{cdcl}_W\text{-stgy}^{**} S \ S' \wedge \text{backtrack } S' \ S'' \wedge \text{conflicting } S' = \text{Some } D \wedge$   
 $\text{cdcl}_W\text{-stgy}^{**} S'' \ T$   
**using** *cdcl<sub>W</sub>* *learned new*  
**proof** (*induction rule*: *rtranclp-induct*)  
**case** *base*  
**then show** ?*case* **by** *blast*  
**next**  
**case** (*step*  $T \ U$ ) **note**  $st = \text{this}(1)$  **and**  $o = \text{this}(2)$  **and**  $IH = \text{this}(3)$  **and**  
 $D-U = \text{this}(4)$  **and**  $D-S = \text{this}(5)$   
**show** ?*case*  
**proof** (*cases*  $D \in \# \text{ learned-clss } T$ )  
**case** *True*

```

then obtain  $S' S''$  where
   $st'$ :  $cdcl_W\text{-stgy}^{**} S S'$  and
   $bt$ :  $backtrack S' S''$  and
   $confl$ :  $conflicting S' = Some D$  and
   $st''$ :  $cdcl_W\text{-stgy}^{**} S'' T$ 
  using  $IH D\text{-}S$  by  $metis$ 
have  $cdcl_W\text{-stgy}^{++} S'' U$ 
  using  $st'' o$  by  $force$ 
then show  $?thesis$ 
  by ( $meson bt confl rtrancpl\text{-}unfold st'$ )
next
case  $False$ 
have  $cdcl_W\text{-}M\text{-level}\text{-}inv T$ 
  using  $lev rtrancpl\text{-}cdcl_W\text{-stgy}\text{-consistent}\text{-}inv st$  by  $blast$ 
then obtain  $S'$  where
   $bt$ :  $backtrack T S'$  and
   $st'$ :  $cdcl_W\text{-stgy}^{**} S' U$  and
   $confl$ :  $conflicting T = Some D$ 
  using  $cdcl_W\text{-cp}\text{-new}\text{-clause}\text{-learned}\text{-has}\text{-backtrack}\text{-step}[OF D\text{-}U False o]$ 
  by  $metis$ 
then have  $cdcl_W\text{-stgy}^{**} S T$  and
   $backtrack T S'$  and
   $conflicting T = Some D$  and
   $cdcl_W\text{-stgy}^{**} S' U$ 
  using  $o st$  by  $auto$ 
then show  $?thesis$  by  $blast$ 
qed
qed

```

**lemma**  $propagate\text{-no}\text{-more}\text{-Marked}\text{-lit}$ :

```

assumes  $propagate S S'$ 
shows  $Marked K i \in set (trail S) \longleftrightarrow Marked K i \in set (trail S')$ 
using  $assms$  by ( $auto elim: propagateE$ )

```

**lemma**  $conflict\text{-no}\text{-more}\text{-Marked}\text{-lit}$ :

```

assumes  $conflict S S'$ 
shows  $Marked K i \in set (trail S) \longleftrightarrow Marked K i \in set (trail S')$ 
using  $assms$  by ( $auto elim: conflictE$ )

```

**lemma**  $cdcl_W\text{-cp}\text{-no}\text{-more}\text{-Marked}\text{-lit}$ :

```

assumes  $cdcl_W\text{-cp} S S'$ 
shows  $Marked K i \in set (trail S) \longleftrightarrow Marked K i \in set (trail S')$ 
using  $assms$  apply ( $induct rule: cdcl_W\text{-cp.induct}$ )
using  $conflict\text{-no}\text{-more}\text{-Marked}\text{-lit} propagate\text{-no}\text{-more}\text{-Marked}\text{-lit}$  by  $auto$ 

```

**lemma**  $rtrancpl\text{-}cdcl_W\text{-cp}\text{-no}\text{-more}\text{-Marked}\text{-lit}$ :

```

assumes  $cdcl_W\text{-cp}^{**} S S'$ 
shows  $Marked K i \in set (trail S) \longleftrightarrow Marked K i \in set (trail S')$ 
using  $assms$  apply ( $induct rule: rtrancpl\text{-}induct$ )
using  $cdcl_W\text{-cp}\text{-no}\text{-more}\text{-Marked}\text{-lit}$  by  $blast+$ 

```

**lemma**  $cdcl_W\text{-o}\text{-no}\text{-more}\text{-Marked}\text{-lit}$ :

```

assumes  $cdcl_W\text{-o} S S'$  and  $lev: cdcl_W\text{-}M\text{-level}\text{-}inv S$  and  $\neg decide S S'$ 
shows  $Marked K i \in set (trail S') \longrightarrow Marked K i \in set (trail S)$ 
using  $assms$ 

```

**proof** (*induct rule: cdcl<sub>W</sub>-o-induct-lev2*)  
**case** *backtrack* **note** *decomp = this(3)* **and** *undef = this(7)* **and** *T = this(8)*  
**then show** ?*case* **using** *lev* **by** (*auto simp: cdcl<sub>W</sub>-M-level-inv-decomp*)  
**next**  
**case** (*decide L T*)  
**then show** ?*case* **using** *decide-rule[OF decide.hyps]* **by** *blast*  
**qed** *auto*

**lemma** *cdcl<sub>W</sub>-new-marked-at-beginning-is-decide:*  
**assumes** *cdcl<sub>W</sub>-stgy S S'* **and**  
*lev: cdcl<sub>W</sub>-M-level-inv S* **and**  
*trail S' = M' @ Marked L i # M* **and**  
*trail S = M*  
**shows**  $\exists T. \text{decide } S \ T \wedge \text{no-step } \text{cdcl}_W\text{-cp } S$   
**using** *assms*

**proof** (*induct rule: cdcl<sub>W</sub>-stgy.induct*)  
**case** (*conflict' S'*) **note** *st = this(1)* **and** *no-dup = this(2)* **and** *S' = this(3)* **and** *S = this(4)*  
**have** *cdcl<sub>W</sub>-M-level-inv S'*  
**using** *full1-cdcl<sub>W</sub>-cp-consistent-inv no-dup st* **by** *blast*  
**then have** *Marked L i ∈ set (trail S')* **and** *Marked L i ∉ set (trail S)*  
**using** *no-dup unfolding S S' cdcl<sub>W</sub>-M-level-inv-def* **by** (*auto simp add: rev-image-eqI*)  
**then have** *False*  
**using** *st rtranclp-cdcl<sub>W</sub>-cp-no-more-Marked-lit[of S S']*  
**unfolding** *full1-def rtranclp-unfold* **by** *blast*  
**then show** ?*case* **by** *fast*

**next**  
**case** (*other' T U*) **note** *o = this(1)* **and** *ns = this(2)* **and** *st = this(3)* **and** *no-dup = this(4)* **and**  
*S' = this(5)* **and** *S = this(6)*  
**have** *cdcl<sub>W</sub>-M-level-inv U*  
**by** (*metis (full-types) lev cdcl<sub>W</sub>.simps cdcl<sub>W</sub>-consistent-inv full-def o*  
*other'.hyps(3) rtranclp-cdcl<sub>W</sub>-cp-consistent-inv*)  
**then have** *Marked L i ∈ set (trail U)* **and** *Marked L i ∉ set (trail S)*  
**using** *no-dup unfolding S S' cdcl<sub>W</sub>-M-level-inv-def* **by** (*auto simp add: rev-image-eqI*)  
**then have** *Marked L i ∈ set (trail T)*  
**using** *st rtranclp-cdcl<sub>W</sub>-cp-no-more-Marked-lit* **unfolding** *full-def* **by** *blast*  
**then show** ?*case*  
**using** *cdcl<sub>W</sub>-o-no-more-Marked-lit[OF o] ⟨Marked L i ∉ set (trail S)⟩ ns lev* **by** *meson*  
**qed**

**lemma** *cdcl<sub>W</sub>-o-is-decide:*  
**assumes** *cdcl<sub>W</sub>-o S T* **and** *lev: cdcl<sub>W</sub>-M-level-inv S*  
*trail T = drop (length M<sub>0</sub>) M' @ Marked L i # H @ M* **and**  
 $\neg (\exists M'. \text{trail } S = M' @ \text{Marked } L \ i \ # \ H @ M)$   
**shows** *decide S T*  
**using** *assms*

**proof** (*induction rule: cdcl<sub>W</sub>-o-induct-lev2*)  
**case** (*backtrack K i M1 M2 L D T*)  
**then obtain** *c* **where** *trail S = c @ M2 @ Marked K (Suc i) # M1*  
**by** *auto*  
**show** ?*case*  
**using** *backtrack lev*  
**apply** (*cases drop (length M<sub>0</sub>) M'*)  
**apply** (*auto simp: cdcl<sub>W</sub>-M-level-inv-decomp*)  
**using**  $\langle \text{trail } S = c @ M2 @ \text{Marked } K \ (Suc \ i) \ # \ M1 \rangle$   
**by** (*auto simp: cdcl<sub>W</sub>-M-level-inv-decomp*)

```

next
  case decide
  show ?case using decide-rule[of S] decide(1-4) by auto
qed auto

lemma rtrancpl-cdclW-new-marked-at-beginning-is-decide:
  assumes cdclW-stgy** R U and
  trail U = M' @ Marked L i # H @ M and
  trail R = M and
  cdclW-M-level-inv R
  shows
     $\exists S T T'. \text{cdcl}_W\text{-stgy}^{**} R S \wedge \text{decide } S T \wedge \text{cdcl}_W\text{-stgy}^{**} T U \wedge \text{cdcl}_W\text{-stgy}^{**} S U \wedge$ 
    no-step cdclW-cp S  $\wedge$  trail T = Marked L i # H @ M  $\wedge$  trail S = H @ M  $\wedge$  cdclW-stgy S T'  $\wedge$ 
    cdclW-stgy** T' U
  using assms
proof (induct arbitrary: M H M' i rule: rtrancpl-induct)
  case base
  then show ?case by auto
next
  case (step T U) note st = this(1) and IH = this(3) and s = this(2) and
    U = this(4) and S = this(5) and lev = this(6)
  show ?case
  proof (cases  $\exists M'. \text{trail } T = M' @ \text{Marked } L i \# H @ M$ )
    case False
    with s show ?thesis using U s st S
  proof induction
    case (conflict' W) note cp = this(1) and nd = this(2) and W = this(3)
    then obtain M0 where trail W = M0 @ trail T and nmarked:  $\forall l \in \text{set } M_0. \neg \text{is-marked } l$ 
      using rtrancpl-cdclW-cp-dropWhile-trail unfolding full1-def rtrancpl-unfold by meson
    then have MV:  $M' @ \text{Marked } L i \# H @ M = M_0 @ \text{trail } T$  unfolding W by simp
    then have V: trail T = drop (length M0) (M' @ Marked L i # H @ M)
      by auto
    have takeWhile (Not o is-marked) M' = M0 @ takeWhile (Not o is-marked) (trail T)
      using arg-cong[OF MV, of takeWhile (Not o is-marked)] nmarked
      by (simp add: takeWhile-tail)
    from arg-cong[OF this, of length] have length M0 ≤ length M'
      unfolding length-append by (metis (no-types, lifting) Nat.le-trans le-add1
        length-takeWhile-le)
    then have False using nd V by auto
    then show ?case by fast
  next
    case (other' T' U) note o = this(1) and ns = this(2) and cp = this(3) and nd = this(4)
      and U = this(5) and st = this(6)
    obtain M0 where trail U = M0 @ trail T' and nmarked:  $\forall l \in \text{set } M_0. \neg \text{is-marked } l$ 
      using rtrancpl-cdclW-cp-dropWhile-trail cp unfolding full-def by meson
    then have MV:  $M' @ \text{Marked } L i \# H @ M = M_0 @ \text{trail } T'$  unfolding U by simp
    then have V: trail T' = drop (length M0) (M' @ Marked L i # H @ M)
      by auto
    have takeWhile (Not o is-marked) M' = M0 @ takeWhile (Not o is-marked) (trail T')
      using arg-cong[OF MV, of takeWhile (Not o is-marked)] nmarked
      by (simp add: takeWhile-tail)
    from arg-cong[OF this, of length] have length M0 ≤ length M'
      unfolding length-append by (metis (no-types, lifting) Nat.le-trans le-add1
        length-takeWhile-le)
    then have tr-T': trail T' = drop (length M0) M' @ Marked L i # H @ M using V by auto
  end
end

```

```

then have  $LT'$ : Marked  $L\ i \in \text{set } (\text{trail } T')$  by auto
moreover
  have  $\text{cdcl}_W\text{-}M\text{-level-inv } T$ 
    using  $\text{lev } r\text{trancp}\text{-}\text{cdcl}_W\text{-stgy-consistent-inv } \text{step.hyps}(1)$  by blast
  then have  $\text{decide } T\ T'$  using  $\text{ond } \text{tr-}T'\ \text{cdcl}_W\text{-o-is-decide}$  by metis
ultimately have  $\text{decide } T\ T'$  using  $\text{cdcl}_W\text{-o-no-more-Marked-lit}[OF\ o]$  by blast
then have 1:  $\text{cdcl}_W\text{-stgy}^{**}\ R\ T$  and 2:  $\text{decide } T\ T'$  and 3:  $\text{cdcl}_W\text{-stgy}^{**}\ T'\ U$ 
  using  $\text{st } \text{other'}.prems(4)$ 
  by ( $\text{metis } \text{cdcl}_W\text{-stgy.conflict' } \text{cp full-unfold } r\text{-into-rtrancp } r\text{trancp}.r\text{trancp-refl}$ ) +
have [ $\text{simp}$ ]:  $\text{drop } (\text{length } M_0)\ M' = []$ 
  using  $\langle \text{decide } T\ T' \rangle \langle \text{Marked } L\ i \in \text{set } (\text{trail } T') \rangle\ \text{nd } \text{tr-}T'$ 
  by ( $\text{auto simp add: Cons-eq-append-conv elim: decideE}$ )
have  $T'$ :  $\text{drop } (\text{length } M_0)\ M' @ \text{Marked } L\ i \# H @ M = \text{Marked } L\ i \# \text{trail } T$ 
  using  $\langle \text{decide } T\ T' \rangle \langle \text{Marked } L\ i \in \text{set } (\text{trail } T') \rangle\ \text{nd } \text{tr-}T'$ 
  by ( $\text{auto elim: decideE}$ )
have  $\text{trail } T' = \text{Marked } L\ i \# \text{trail } T$ 
  using  $\langle \text{decide } T\ T' \rangle \langle \text{Marked } L\ i \in \text{set } (\text{trail } T') \rangle\ \text{tr-}T'$ 
  by ( $\text{auto elim: decideE}$ )
then have 5:  $\text{trail } T' = \text{Marked } L\ i \# H @ M$ 
  using  $\text{append.simps}(1)\ \text{list.sel}(3)\ \text{local.other'}(5)\ \text{tl-append2}$  by ( $\text{simp add: tr-}T'$ )
have 6:  $\text{trail } T = H @ M$ 
  by ( $\text{metis } (\text{no-types})\ \langle \text{trail } T' = \text{Marked } L\ i \# \text{trail } T \rangle$ 
     $\langle \text{trail } T' = \text{drop } (\text{length } M_0)\ M' @ \text{Marked } L\ i \# H @ M \rangle\ \text{append-Nil list.sel}(3)\ \text{nd}$ 
     $\text{tl-append2}$ )
have 7:  $\text{cdcl}_W\text{-stgy}^{**}\ T\ U$  using  $\text{other'}.prems(4)\ \text{st}$  by auto
have 8:  $\text{cdcl}_W\text{-stgy}\ T\ U\ \text{cdcl}_W\text{-stgy}^{**}\ U\ U$ 
  using  $\text{cdcl}_W\text{-stgy.other'}[OF\ \text{other'}(1-3)]$  by  $\text{simp-all}$ 
show ?case apply (rule  $\text{exI}[of\ -\ T]$ , rule  $\text{exI}[of\ -\ T']$ , rule  $\text{exI}[of\ -\ U]$ )
  using  $\text{ns } 1\ 2\ 3\ 5\ 6\ 7\ 8$  by fast
qed
next
case True
then obtain  $M'$  where  $T$ :  $\text{trail } T = M' @ \text{Marked } L\ i \# H @ M$  by metis
from  $IH[OF\ \text{this } S\ \text{lev}]$  obtain  $S'\ S''\ S'''$  where
  1:  $\text{cdcl}_W\text{-stgy}^{**}\ R\ S'$  and
  2:  $\text{decide } S'\ S''$  and
  3:  $\text{cdcl}_W\text{-stgy}^{**}\ S''\ T$  and
  4:  $\text{no-step } \text{cdcl}_W\text{-cp } S'$  and
  6:  $\text{trail } S'' = \text{Marked } L\ i \# H @ M$  and
  7:  $\text{trail } S' = H @ M$  and
  8:  $\text{cdcl}_W\text{-stgy}^{**}\ S'\ T$  and
  9:  $\text{cdcl}_W\text{-stgy}\ S'\ S'''$  and
  10:  $\text{cdcl}_W\text{-stgy}^{**}\ S''' T$ 
  by blast
have  $\text{cdcl}_W\text{-stgy}^{**}\ S''\ U$  using  $s\ \langle \text{cdcl}_W\text{-stgy}^{**}\ S''\ T \rangle$  by auto
moreover have  $\text{cdcl}_W\text{-stgy}^{**}\ S'\ U$  using  $8\ s$  by auto
moreover have  $\text{cdcl}_W\text{-stgy}^{**}\ S''' U$  using  $10\ s$  by auto
ultimately show ?thesis apply – apply (rule  $\text{exI}[of\ -\ S]$ , rule  $\text{exI}[of\ -\ S']$ )
  using  $1\ 2\ 4\ 6\ 7\ 8\ 9$  by blast
qed
qed

```

**lemma**  $r\text{trancp}\text{-}\text{cdcl}_W\text{-new-marked-at-beginning-is-decide'}$ :

```

assumes  $\text{cdcl}_W\text{-stgy}^{**}\ R\ U$  and
 $\text{trail } U = M' @ \text{Marked } L\ i \# H @ M$  and

```

*trail*  $R = M$  **and**  
*cdcl<sub>W</sub>-M-level-inv*  $R$   
**shows**  $\exists y y'. \text{cdcl}_W\text{-stgy}^{**} R y \wedge \text{cdcl}_W\text{-stgy } y y' \wedge \neg (\exists c. \text{trail } y = c @ \text{Marked } L i \# H @ M)$   
 $\wedge (\lambda a b. \text{cdcl}_W\text{-stgy } a b \wedge (\exists c. \text{trail } a = c @ \text{Marked } L i \# H @ M))^{**} y' U$   
**proof** –  
**fix**  $T'$   
**obtain**  $S' T T'$  **where**  
*st*:  $\text{cdcl}_W\text{-stgy}^{**} R S'$  **and**  
*decide*  $S' T$  **and**  
*TU*:  $\text{cdcl}_W\text{-stgy}^{**} T U$  **and**  
*no-step*  $\text{cdcl}_W\text{-cp } S'$  **and**  
*trT*:  $\text{trail } T = \text{Marked } L i \# H @ M$  **and**  
*trS'*:  $\text{trail } S' = H @ M$  **and**  
*S'U*:  $\text{cdcl}_W\text{-stgy}^{**} S' U$  **and**  
*S'T'*:  $\text{cdcl}_W\text{-stgy } S' T'$  **and**  
*T'U*:  $\text{cdcl}_W\text{-stgy}^{**} T' U$   
**using** *rtranclp-cdcl<sub>W</sub>-new-marked-at-beginning-is-decide*[*OF assms*] **by** *blast*  
**have**  $n: \neg (\exists c. \text{trail } S' = c @ \text{Marked } L i \# H @ M)$  **using** *trS'* **by** *auto*  
**show** *?thesis*  
**using** *rtranclp-trans*[*OF st*] *rtranclp-exists-last-with-prop*[*of cdcl<sub>W</sub>-stgy S' T' -*  
 $\lambda a -. \neg (\exists c. \text{trail } a = c @ \text{Marked } L i \# H @ M), \text{OF } S'T' T'U n]$   
**by** *meson*  
**qed**

**lemma** *beginning-not-marked-invert*:  
**assumes**  $A: M @ A = M' @ \text{Marked } K i \# H$  **and**  
*nm*:  $\forall m \in \text{set } M. \neg \text{is-marked } m$   
**shows**  $\exists M. A = M @ \text{Marked } K i \# H$   
**proof** –  
**have**  $A = \text{drop } (\text{length } M) (M' @ \text{Marked } K i \# H)$   
**using** *arg-cong*[*OF A, of drop (length M)*] **by** *auto*  
**moreover have**  $\text{drop } (\text{length } M) (M' @ \text{Marked } K i \# H) = \text{drop } (\text{length } M) M' @ \text{Marked } K i \# H$   
**using** *nm* **by** (*metis* (*no-types, lifting*) *A drop-Cons' drop-append marked-lit.disc(1) not-gr0*  
 $\text{nth-append nth-append-length nth-mem zero-less-diff}$ )  
**finally show** *?thesis* **by** *fast*  
**qed**

**lemma** *cdcl<sub>W</sub>-stgy-trail-has-new-marked-is-decide-step*:  
**assumes**  $\text{cdcl}_W\text{-stgy } S T$   
 $\neg (\exists c. \text{trail } S = c @ \text{Marked } L i \# H @ M)$  **and**  
 $(\lambda a b. \text{cdcl}_W\text{-stgy } a b \wedge (\exists c. \text{trail } a = c @ \text{Marked } L i \# H @ M))^{**} T U$  **and**  
 $\exists M'. \text{trail } U = M' @ \text{Marked } L i \# H @ M$  **and**  
*lev*:  $\text{cdcl}_W\text{-M-level-inv } S$   
**shows**  $\exists S'. \text{decide } S S' \wedge \text{full } \text{cdcl}_W\text{-cp } S' T \wedge \text{no-step } \text{cdcl}_W\text{-cp } S$   
**using** *assms(3,1,2,4,5)*  
**proof** *induction*  
**case** (*step*  $T U$ )  
**then show** *?case* **by** *fastforce*  
**next**  
**case** *base*  
**then show** *?case*  
**proof** (*induction rule: cdcl<sub>W</sub>-stgy.induct*)  
**case** (*conflict' T*) **note**  $\text{cp} = \text{this}(1)$  **and**  $\text{nd} = \text{this}(2)$  **and**  $M' = \text{this}(3)$  **and**  $\text{no-dup} = \text{this}(3)$   
**then obtain**  $M'$  **where**  $M': \text{trail } T = M' @ \text{Marked } L i \# H @ M$  **by** *metis*  
**obtain**  $M''$  **where**  $M'': \text{trail } T = M'' @ \text{trail } S$  **and** *nm*:  $\forall m \in \text{set } M''. \neg \text{is-marked } m$

```

    using cp unfolding full1-def
    by (metis rtranclp-cdclW-cp-dropWhile-trail' tranclp-into-rtranclp)
have False
  using beginning-not-marked-invert[of M'' trail S M' L i H @ M] M' nm nd unfolding M''
  by fast
then show ?case by fast
next
case (other' T U') note o = this(1) and ns = this(2) and cp = this(3) and nd = this(4)
  and trU' = this(5)
have cdclW-cp** T U' using cp unfolding full-def by blast
from rtranclp-cdclW-cp-dropWhile-trail[OF this]
have  $\exists M'. \text{trail } T = M' @ \text{Marked } L \ i \ \# \ H @ M$ 
  using trU' beginning-not-marked-invert[of - trail T - L i H @ M] by metis
then obtain M' where M': trail T = M' @ Marked L i # H @ M
  by auto
with o lev nd cp ns
show ?case
proof (induction rule: cdclW-o-induct-lev2)
  case (decide L) note dec = this(1) and cp = this(5) and ns = this(4)
  then have decide S (cons-trail (Marked L (backtrack-lvl S + 1)) (incr-lvl S))
    using decide.hyps decide.intros[of S] by force
  then show ?case using cp decide.premis by (meson decide-state-eq-compatible ns state-eq-ref
    state-eq-sym)
next
case (backtrack K j M1 M2 L' D T) note decomp = this(3) and undef = this(7) and
  T = this(8) and trT = this(12)
obtain MS3 where MS3: trail S = MS3 @ M2 @ Marked K (Suc j) # M1
  using get-all-marked-decomposition-exists-prepend[OF decomp] by metis
have tl (M' @ Marked L i # H @ M) = tl M' @ Marked L i # H @ M
  using lev trT T lev undef decomp by (cases M') (auto simp: cdclW-M-level-inv-decomp)
then have M'': M1 = tl M' @ Marked L i # H @ M
  using arg-cong[OF trT[simplified], of tl] T decomp undef lev
  by (simp add: cdclW-M-level-inv-decomp)
have False using nd MS3 T undef decomp unfolding M'' by auto
then show ?case by fast
qed auto
qed
qed

```

**lemma** *rtranclp-cdcl<sub>W</sub>-stgy-with-trail-end-has-trail-end:*

```

assumes (λa b. cdclW-stgy a b ∧ (∃ c. trail a = c @ Marked L i # H @ M))** T U and
  ∃ M'. trail U = M' @ Marked L i # H @ M
shows ∃ M'. trail T = M' @ Marked L i # H @ M
using assms by (induction rule: rtranclp-induct) auto

```

**lemma** *remove1-mset-eq-remove1-mset-same:*

```

remove1-mset L D = remove1-mset L' D  $\implies$  L ∈# D  $\implies$  L = L'
by (metis diff-single-trivial insert-DiffM multi-drop-mem-not-eq single-eq-single
  union-right-cancel)

```

**lemma** *cdcl<sub>W</sub>-o-cannot-learn:*

```

assumes
  cdclW-o y z and
  lev: cdclW-M-level-inv y and
  trM: trail y = c @ Marked Kh i # H and

```



$DL: D \notin \# \text{ learned-clss } y$  **and**  
 $LD: L \in \# D$  **and**  
 $DH: \text{atms-of } (\text{remove1-mset } L \ D) \subseteq \text{atm-of 'lits-of-l } H$  **and**  
 $LH: \text{atm-of } L \notin \text{atm-of 'lits-of-l } H$  **and**  
 $\text{learned: } \forall T. \text{ conflicting } y = \text{Some } T \longrightarrow \text{trail } y \models_{\text{as}} \text{CNot } T$  **and**  
 $z: \text{trail } z = c' @ \text{Marked } Kh \ i \ \# \ H$   
**shows**  $D \notin \# \text{ learned-clss } z$   
**using**  $\text{assms}(1-2) \ \text{trM } DL \ DH \ LH \ \text{learned } z$   
**proof** (*induction rule: cdcl<sub>W</sub>-o-induct-lev2*)  
**case** ( $\text{backtrack } K \ j \ M1 \ M2 \ L' \ D' \ T$ ) **note**  $\text{confl} = \text{this}(1)$  **and**  $LD' = \text{this}(2)$  **and**  $\text{decomp} = \text{this}(3)$   
**and**  $\text{levL} = \text{this}(4)$  **and**  $\text{levD} = \text{this}(5)$  **and**  $j = \text{this}(6)$  **and**  $\text{undef} = \text{this}(7)$  **and**  $T = \text{this}(8)$  **and**  
 $z = \text{this}(14)$   
  
**obtain**  $M3$  **where**  $M3: \text{trail } y = M3 @ M2 @ \text{Marked } K \ (\text{Suc } j) \ \# \ M1$   
**using**  $\text{decomp}$   $\text{get-all-marked-decomposition-exists-prepend}$  **by**  $\text{metis}$   
**have**  $M: \text{trail } y = c @ \text{Marked } Kh \ i \ \# \ H$  **using**  $\text{trM}$  **by**  $\text{simp}$   
**have**  $H: \text{get-all-levels-of-marked } (\text{trail } y) = \text{rev } [1..<1 + \text{backtrack-lvl } y]$   
**using**  $\text{lev unfolding cdcl}_W\text{-M-level-inv-def}$  **by**  $\text{auto}$   
**have**  $c' @ \text{Marked } Kh \ i \ \# \ H = \text{Propagated } L' \ (\text{mset-ccls } D') \ \# \ \text{trail } (\text{reduce-trail-to } M1 \ y)$   
**using**  $z \ \text{decomp } \text{undef } T \ \text{lev}$  **by** ( $\text{force simp: cdcl}_W\text{-M-level-inv-def}$ )  
**then obtain**  $d$  **where**  $d: M1 = d @ \text{Marked } Kh \ i \ \# \ H$   
**by** ( $\text{metis (no-types) decomp in-get-all-marked-decomposition-trail-update-trail list.inject}$   
 $\text{list.sel}(3) \ \text{marked-lit.distinct}(1) \ \text{self-append-conv2 tl-append2}$ )  
**have**  $i \in \text{set } (\text{get-all-levels-of-marked } (M3 @ M2 @ \text{Marked } K \ (\text{Suc } j) \ \# \ d @ \text{Marked } Kh \ i \ \# \ H))$   
**by**  $\text{auto}$   
**then have**  $i > 0$  **unfolding**  $H[\text{unfolded } M3 \ d]$  **by**  $\text{auto}$   
**show**  $?case$   
**proof**  
**assume**  $D \in \# \text{ learned-clss } T$   
**then have**  $DLD': D = \text{mset-ccls } D'$   
**using**  $DL \ T \ \text{neq0-conv } \text{undef } \text{decomp } \text{lev}$  **by** ( $\text{fastforce simp: cdcl}_W\text{-M-level-inv-def}$ )  
**have**  $L\text{-cKh}: \text{atm-of } L \in \text{atm-of 'lits-of-l } (c @ [\text{Marked } Kh \ i])$   
**using**  $LH \ \text{learned } M \ DLD'[\text{symmetric}] \ \text{confl } LD' \ LD$   
  
**apply** ( $\text{auto simp add: image-iff dest!: in-CNot-implies-uminus}$ )  
**apply** ( $\text{metis atm-of-uminus}$ ) **done**  
**have**  $\text{get-all-levels-of-marked } (M3 @ M2 @ \text{Marked } K \ (j + 1) \ \# \ M1)$   
 $= \text{rev } [1..<1 + \text{backtrack-lvl } y]$   
**using**  $\text{lev unfolding cdcl}_W\text{-M-level-inv-def } M3$  **by**  $\text{auto}$   
**from**  $\text{arg-cong}[OF \ \text{this}, \text{ of } \lambda a. (\text{Suc } j) \in \text{set } a]$  **have**  $\text{backtrack-lvl } y \geq j$  **by**  $\text{auto}$   
  
**have**  $DD'[\text{simp}]: \text{remove1-mset } L \ D = \text{mset-ccls } D' - \{\#L'\#\}$   
**proof** (*rule ccontr*)  
**assume**  $DD': \neg ?thesis$   
**then have**  $L' \in \# \text{remove1-mset } L \ D$  **using**  $DLD' \ LD$  **by** ( $\text{metis } LD' \ \text{in-remove1-mset-neq}$ )  
**then have**  $\text{get-level } (\text{trail } y) \ L' \leq \text{get-maximum-level } (\text{trail } y) \ (\text{remove1-mset } L \ D)$   
**using**  $\text{get-maximum-level-ge-get-level}$  **by**  $\text{blast}$   
**moreover** {  
**have**  $\text{get-maximum-level } (\text{trail } y) \ (\text{remove1-mset } L \ D) =$   
 $\text{get-maximum-level } H \ (\text{remove1-mset } L \ D)$   
**using**  $DH \ \text{unfolding } M$  **by** ( $\text{simp add: get-maximum-level-skip-beginning}$ )  
**moreover**  
**have**  $\text{get-all-levels-of-marked } (\text{trail } y) = \text{rev } [1..<1 + \text{backtrack-lvl } y]$   
**using**  $\text{lev unfolding cdcl}_W\text{-M-level-inv-def}$  **by**  $\text{auto}$   
**then have**  $\text{get-all-levels-of-marked } H = \text{rev } [1..< \ i]$

```

    unfolding M by (auto dest: append-cons-eq-upt-length-i
      simp add: rev-swap[symmetric])
  then have get-maximum-possible-level H < i
    using get-maximum-possible-level-max-get-all-levels-of-marked[of H] ⟨i > 0⟩ by auto
  ultimately have get-maximum-level (trail y) (remove1-mset L D) < i
    by (metis (full-types) dual-order.strict-trans nat-neq-iff not-le
      get-maximum-possible-level-ge-get-maximum-level) }
moreover
  have L ∈# remove1-mset L' (mset-ccls D')
    using DLD'[symmetric] DD' LD by (metis in-remove1-mset-neq)
  then have get-maximum-level (trail y) (remove1-mset L' (mset-ccls D')) ≥
    get-level (trail y) L
    using get-maximum-level-ge-get-level by blast
moreover {
  have get-all-levels-of-marked (c @ [Marked Kh i]) = rev [i..< backtrack-lvl y+1]
    using append-cons-eq-upt-length-i-end[of rev (get-all-levels-of-marked H) i
      rev (get-all-levels-of-marked c) Suc 0 Suc (backtrack-lvl y)] H
  unfolding M apply (auto simp add: rev-swap[symmetric])
    by (metis (no-types, hide-lams) Nil-is-append-conv Suc-le-eq less-Suc-eq list.sel(1)
      rev.simps(2) rev-rev-ident upt-Suc upt-rec)
  have get-level (trail y) L = get-level (c @ [Marked Kh i]) L
    using L-cKh LH unfolding M by simp
  have get-level (c @ [Marked Kh i]) L ≥ i
    using L-cKh levL
      ⟨get-all-levels-of-marked (c @ [Marked Kh i]) = rev [i..<backtrack-lvl y + 1]⟩
      calculation(1,2) by auto
  then have get-level (trail y) L ≥ i
    using M ⟨get-level (trail y) L = get-level (c @ [Marked Kh i]) L⟩ by auto }
moreover
  have get-maximum-level (trail y) (remove1-mset L' (mset-ccls D'))
    < get-level (trail y) L
    using ⟨j ≤ backtrack-lvl y⟩ levL j calculation(1-4) by linarith
  ultimately show False using backtrack.hyps(4) by linarith
qed
then have LL': L = L'
  using LD LD' remove1-mset-eq-remove1-mset-same unfolding DLD'[symmetric] by fast
have nd: no-dup (trail y) using lev unfolding cdclW-M-level-inv-def by auto

{ assume D: remove1-mset L (mset-ccls D') = {#}
  then have j: j = 0 using levD j by (simp add: LL')
  have ∀ m ∈ set M1. ¬is-marked m
    using H unfolding M3 j
    by (auto simp add: rev-swap[symmetric] get-all-levels-of-marked-no-marked
      dest!: append-cons-eq-upt-length-i)
  then have False using d by auto
}
moreover {
  assume D[simp]: remove1-mset L (mset-ccls D') ≠ {#}
  have i ≤ j
    using H unfolding M3 d by (auto simp add: rev-swap[symmetric]
      dest: upt-decomp-lt)
  have j > 0 apply (rule ccontr)
    using H ⟨i > 0⟩ unfolding M3 d
    by (auto simp add: rev-swap[symmetric] dest!: upt-decomp-lt)
  obtain L'' where

```

```

    L'' ∈ # remove1-mset L (mset-ccls D') and
    L''D': get-level (trail y) L'' = get-maximum-level (trail y)
      (remove1-mset L (mset-ccls D'))
    using get-maximum-level-exists-lit-of-max-level[OF D, of trail y] by auto
  have L''M: atm-of L'' ∈ atm-of ' lits-of-l (trail y)
    using get-rev-level-ge-0-atm-of-in[of 0 rev (trail y) L''] ⟨j>0⟩ levD L''D'
      ⟨j ≤ backtrack-lvl y⟩ levL by (simp add: LL' j)
  then have L'' ∈ lits-of-l (Marked Kh i # d)
  proof -
    {
      assume L''H: atm-of L'' ∈ atm-of ' lits-of-l H
      have get-all-levels-of-marked H = rev [1..i]
        using H unfolding M
        by (auto simp add: rev-swap[symmetric] dest!: append-cons-eq-upt-length-i)
      moreover have get-level (trail y) L'' = get-level H L''
        using L''H unfolding M by simp
      ultimately have False
        using levD ⟨j>0⟩ get-rev-level-in-levels-of-marked[of rev H 0 L''] ⟨i ≤ j⟩
        unfolding L''D'[symmetric] nd
        by (metis L''D' LL' Max-n-upt Nat.le-trans One-nat-def Suc-pred ⟨0 < i⟩
          get-all-levels-of-marked-rev-eq-rev-get-all-levels-of-marked
          get-rev-level-less-max-get-all-levels-of-marked j lessI list.simps(15)
          not-less rev-rev-ident set-upt)
    }
  moreover
    have atm-of L'' ∈ atm-of ' lits-of-l H
      using DD' DH ⟨L'' ∈ # remove1-mset L (mset-ccls D')⟩ atm-of-lit-in-atms-of LL' LD
      LD' by fastforce
    ultimately show ?thesis
      using DD' DH ⟨L'' ∈ # remove1-mset L (mset-ccls D')⟩ atm-of-lit-in-atms-of
      by auto
  qed
  moreover
    have atm-of L'' ∈ atms-of ( remove1-mset L (mset-ccls D'))
      using ⟨L'' ∈ # remove1-mset L (mset-ccls D')⟩ by (auto simp: atms-of-def)

    then have atm-of L'' ∈ atm-of ' lits-of-l H
      using DH unfolding DD' unfolding LL' by blast
    ultimately have False
      using nd unfolding M3 d LL' by (auto simp: lits-of-def)
  }
  ultimately show False by blast
  qed
qed auto

```

**lemma** *cdcl<sub>W</sub>-stgy-with-trail-end-has-not-been-learned:*

**assumes**

*cdcl<sub>W</sub>-stgy y z* **and**

*cdcl<sub>W</sub>-M-level-inv y* **and**

*trail y = c @ Marked Kh i # H* **and**

*D ∉ # learned-clss y* **and**

*LD: L ∈ # D* **and**

*DH: atms-of (remove1-mset L D) ⊆ atm-of ' lits-of-l H* **and**

*LH: atm-of L ∉ atm-of ' lits-of-l H* **and**

$\forall T. \text{conflicting } y = \text{Some } T \longrightarrow \text{trail } y \models_{\text{as}} \text{CNot } T$  **and**

```

    trail z = c' @ Marked Kh i # H
  shows D ∉# learned-clss z
  using assms
proof induction
  case conflict'
  then show ?case
    unfolding full1-def using tranclp-cdclW-cp-learned-clause-inv by auto
next
  case (other' T U) note o = this(1) and cp = this(3) and lev = this(4) and trY = this(5) and
    notin = this(6) and LD = this(7) and DH = this(8) and LH = this(9) and confl = this(10) and
    trU = this(11)
  obtain c' where c': trail T = c' @ Marked Kh i # H
  using cp beginning-not-marked-invert[of - trail T c' Kh i H]
    rtranclp-cdclW-cp-dropWhile-trail[of T U] unfolding trU full-def by fastforce
  show ?case
    using cdclW-o-cannot-learn[OF o lev trY notin LD DH LH confl c']
      rtranclp-cdclW-cp-learned-clause-inv cp unfolding full-def by auto
qed

```

**lemma** *rtranclp-cdcl<sub>W</sub>-stgy-with-trail-end-has-not-been-learned*:

```

  assumes
    (λa b. cdclW-stgy a b ∧ (∃ c. trail a = c @ Marked K i # H @ []))** S z and
    cdclW-all-struct-inv S and
    trail S = c @ Marked K i # H and
    D ∉# learned-clss S and
    LD: L ∈# D and
    DH: atm-of (remove1-mset L D) ⊆ atm-of ' lits-of-l H and
    LH: atm-of L ∉ atm-of ' lits-of-l H and
    ∃ c'. trail z = c' @ Marked K i # H
  shows D ∉# learned-clss z
  using assms(1-4,8)
proof (induction rule: rtranclp-induct)
  case base
  then show ?case by auto[1]
next
  case (step T U) note st = this(1) and s = this(2) and IH = this(3)[OF this(4-6)]
    and lev = this(4) and trS = this(5) and DL-S = this(6) and trU = this(7)
  obtain c where c: trail T = c @ Marked K i # H using s by auto
  obtain c' where c': trail U = c' @ Marked K i # H using trU by blast
  have cdclW** S T
  proof -
    have ∀ p pa. ∃ s sa. ∀ sb sc sd se. (¬ p** (sb::'st) sc ∨ p s sa ∨ pa** sb sc)
      ∧ (¬ pa s sa ∨ ¬ p** sd se ∨ pa** sd se)
    by (metis (no-types) mono-rtranclp)
    then have cdclW-stgy** S T
    using st by blast
    then show ?thesis
      using rtranclp-cdclW-stgy-rtranclp-cdclW by blast
  qed
  then have lev': cdclW-all-struct-inv T
  using rtranclp-cdclW-all-struct-inv-inv[of S T] lev by auto
  then have confl': ∀ Ta. conflicting T = Some Ta ⟶ trail T ⊨as CNot Ta
  unfolding cdclW-all-struct-inv-def cdclW-conflicting-def by blast
  show ?case
    apply (rule cdclW-stgy-with-trail-end-has-not-been-learned[OF - - c - LD DH LH confl' c'])

```

```

    using  $s$  lev' IH  $c$  unfolding  $cdcl_W$ -all-struct-inv-def by blast+
qed

lemma  $cdcl_W$ -stgy-new-learned-clause:
  assumes  $cdcl_W$ -stgy  $S$   $T$  and
    lev:  $cdcl_W$ -M-level-inv  $S$  and
     $E \notin \#$  learned-clss  $S$  and
     $E \in \#$  learned-clss  $T$ 
  shows  $\exists S'. \text{backtrack } S S' \wedge \text{conflicting } S = \text{Some } E \wedge \text{full } cdcl_W\text{-cp } S' T$ 
  using assms
proof induction
  case conflict'
  then show ?case unfolding full1-def by (auto dest: tranclp-cdcl_W-cp-learned-clause-inv)
next
  case (other'  $T$   $U$ ) note  $o = \text{this}(1)$  and  $cp = \text{this}(3)$  and  $\text{not-yet} = \text{this}(5)$  and  $\text{learned} = \text{this}(6)$ 
  have  $E \in \#$  learned-clss  $T$ 
    using learned  $cp$  rtranclp-cdcl_W-cp-learned-clause-inv unfolding full-def by auto
  then have backtrack  $S$   $T$  and conflicting  $S = \text{Some } E$ 
    using  $cdcl_W$ -o-new-clause-learned-is-backtrack-step[ $OF$  -  $\text{not-yet } o$ ] lev by blast+
  then show ?case using  $cp$  by blast
qed

lemma  $cdcl_W$ -stgy-no-relearned-clause:
  assumes
    invR:  $cdcl_W$ -all-struct-inv  $R$  and
    st':  $cdcl_W$ -stgy**  $R$   $S$  and
    bt: backtrack  $S$   $T$  and
    confl: raw-conflicting  $S = \text{Some } E$  and
    already-learned:  $mset\text{-ccls } E \in \#$  clauses  $S$  and
     $R$ : trail  $R = []$ 
  shows False
proof -
  have M-lev:  $cdcl_W$ -M-level-inv  $R$ 
    using invR unfolding  $cdcl_W$ -all-struct-inv-def by auto
  have  $cdcl_W$ -M-level-inv  $S$ 
    using M-lev assms(2) rtranclp-cdcl_W-stgy-consistent-inv by blast
  with bt obtain  $L$   $M1$   $M2\text{-loc } K$   $i$  where
     $T$ :  $T \sim \text{cons-trail } (\text{Propagated } L \text{ (cls-of-ccls } E))$ 
    (reduce-trail-to  $M1$  (add-learned-cls (cls-of-ccls  $E$ )
      (update-backtrack-lvl  $i$  (update-conflicting None  $S$ ))))
    and
    decomp: (Marked  $K$  (Suc  $i$ )  $\#$   $M1$ ,  $M2\text{-loc}$ )  $\in$ 
      set (get-all-marked-decomposition (trail  $S$ )) and
    LD:  $L \in \#$  mset-ccls  $E$  and
    k: get-level (trail  $S$ )  $L = \text{backtrack-lvl } S$  and
    level: get-level (trail  $S$ )  $L = \text{get-maximum-level } (\text{trail } S) \text{ (mset-ccls } E)$  and
    confl-S: raw-conflicting  $S = \text{Some } E$  and
    i:  $i = \text{get-maximum-level } (\text{trail } S) \text{ (remove1-mset } L \text{ (mset-ccls } E))$  and
    undef: undefined-lit  $M1$   $L$ 
    using confl by (induction rule: backtrack-induction-lev2) fastforce
  obtain  $M2$  where
     $M$ : trail  $S = M2 @ \text{Marked } K \text{ (Suc } i) \# M1$ 
    using get-all-marked-decomposition-exists-prepend[ $OF$  decomp] unfolding  $i$  by (metis append-assoc)
  let ? $E$  = mset-ccls  $E$ 
  let ? $E'$  = remove1-mset  $L$  ? $E$ 

```

```

have invS: cdclW-all-struct-inv S
  using invR rtrancp-cdclW-all-struct-inv-inv rtrancp-cdclW-stgy-rtrancp-cdclW st' by blast
then have conf: cdclW-conflicting S unfolding cdclW-all-struct-inv-def by blast
then have trail S ⊨as CNot ?E unfolding cdclW-conflicting-def confl-S by auto
then have MD: trail S ⊨as CNot ?E by auto
then have MD': trail S ⊨as CNot ?E' using true-annot-CNot-diff by blast
have lev': cdclW-M-level-inv S using invS unfolding cdclW-all-struct-inv-def by blast

have get-lvls-M: get-all-levels-of-marked (trail S) = rev [1..Suc (backtrack-lvl S)]
  using lev' unfolding cdclW-M-level-inv-def by auto

have lev: cdclW-M-level-inv R using invR unfolding cdclW-all-struct-inv-def by blast
then have vars-of-D: atms-of ?E' ⊆ atm-of ' lits-of-l M1
  using backtrack-atms-of-D-in-M1[OF lev' undef - decomp - - T] confl-S conf T decomp k level
  lev' i undef unfolding cdclW-conflicting-def by (auto simp: cdclW-M-level-inv-decomp)
have no-dup (trail S) using lev' by (auto simp: cdclW-M-level-inv-decomp)
have vars-in-M1:
   $\forall x \in \text{atms-of } ?E'. x \notin \text{atm-of ' lits-of-l } (M2 @ [\text{Marked } K (i + 1)])$ 
  unfolding Set.Ball-def apply (intro impI allI)
  apply (rule vars-of-D distinct-atms-of-incl-not-in-other[of
    M2 @ Marked K (i + 1) # [] M1 ?E'])
  using (no-dup (trail S)) M vars-of-D by simp-all
have M1-D: M1 ⊨as CNot ?E'
  using vars-in-M1 true-annots-remove-if-notin-vars[of M2 @ Marked K (i + 1) # [] M1 CNot ?E']
  MD' M by simp

have get-lvls-M: get-all-levels-of-marked (trail S) = rev [1..Suc (backtrack-lvl S)]
  using lev' unfolding cdclW-M-level-inv-def by auto
then have backtrack-lvl S > 0 unfolding M by (auto split: if-split-asm simp add: upt.simps(2))

obtain M1' K' Ls where
  M': trail S = Ls @ Marked K' (backtrack-lvl S) # M1' and
  Ls:  $\forall l \in \text{set } Ls. \neg \text{is-marked } l$  and
  set M1 ⊆ set M1'
proof –
  let ?Ls = takeWhile (Not o is-marked) (trail S)
  have MLs: trail S = ?Ls @ dropWhile (Not o is-marked) (trail S)
    by auto
  have dropWhile (Not o is-marked) (trail S) ≠ [] unfolding M by auto
moreover
  from hd-dropWhile[OF this] have is-marked(hd (dropWhile (Not o is-marked) (trail S)))
    by simp
ultimately
  obtain K' K'k where
    K'k: dropWhile (Not o is-marked) (trail S)
       $= \text{Marked } K' K'k \# \text{tl } (\text{dropWhile } (\text{Not } o \text{ is-marked}) (\text{trail } S))$ 
    by (cases dropWhile (Not o is-marked) (trail S);
      cases hd (dropWhile (Not o is-marked) (trail S)))
    simp-all
moreover have  $\forall l \in \text{set } ?Ls. \neg \text{is-marked } l$  using set-takeWhileD by force
moreover
  have get-all-levels-of-marked (trail S)
     $= K'k \# \text{get-all-levels-of-marked}(\text{tl } (\text{dropWhile } (\text{Not } o \text{ is-marked}) (\text{trail } S)))$ 
    apply (subst MLs, subst K'k)
    using calculation(2) by (auto simp add: get-all-levels-of-marked-no-marked)

```

```

    then have  $K'k = \text{backtrack-lvl } S$ 
    using  $\text{calculation}(2)$  by (auto split: if-split-asm simp add: get-lvs-M upt.simps(2))
  moreover have  $\text{set } M1 \subseteq \text{set } (\text{tl } (\text{dropWhile } (\text{Not } o \text{ is-marked}) (\text{trail } S)))$ 
    unfolding  $M$  by (induction  $M2$ ) auto
  ultimately show  $?thesis$  using that  $MLs$  by metis
qed

have  $\text{get-lvs-M}: \text{get-all-levels-of-marked } (\text{trail } S) = \text{rev } [1..<\text{Suc } (\text{backtrack-lvl } S)]$ 
  using  $\text{lev}'$  unfolding  $\text{cdcl}_W\text{-M-level-inv-def}$  by auto
then have  $\text{backtrack-lvl } S > 0$  unfolding  $M$  by (auto split: if-split-asm simp add: upt.simps(2) i)

have  $M1'-D: M1' \models_{as} CNot ?E'$  using  $M1-D \langle \text{set } M1 \subseteq \text{set } M1' \rangle$  by (auto intro: true-annots-mono)
have  $-L \in \text{lits-of-l } (\text{trail } S)$  using  $\text{conf } \text{conft-S } LD$  unfolding  $\text{cdcl}_W\text{-conflicting-def}$ 
  by (auto simp: in-CNot-implies-uminus)
have  $\text{lvs-M1}': \text{get-all-levels-of-marked } M1' = \text{rev } [1..<\text{backtrack-lvl } S]$ 
  using  $\text{get-lvs-M } Ls$  by (auto simp add: get-all-levels-of-marked-no-marked  $M'$  upt.simps(2)
    split: if-split-asm)
have  $L\text{-notin}: \text{atm-of } L \in \text{atm-of } \langle \text{lits-of-l } Ls \vee \text{atm-of } L = \text{atm-of } K' \rangle$ 
  proof (rule ccontr)
    assume  $\neg ?thesis$ 
    then have  $\text{atm-of } L \notin \text{atm-of } \langle \text{lits-of-l } (\text{Marked } K' (\text{backtrack-lvl } S) \# \text{rev } Ls) \rangle$  by simp
    then have  $\text{get-level } (\text{trail } S) L = \text{get-level } M1' L$ 
      unfolding  $M'$  by auto
    then show  $False$  using  $\text{get-level-in-levels-of-marked}[of M1' L] \langle \text{backtrack-lvl } S > 0 \rangle$ 
      unfolding  $k \text{ lvs-M1}'$  by auto
  qed
obtain  $Y Z$  where
   $RY: \text{cdcl}_W\text{-stgy}^{**} R Y$  and
   $YZ: \text{cdcl}_W\text{-stgy } Y Z$  and
   $nt: \neg (\exists c. \text{trail } Y = c @ \text{Marked } K' (\text{backtrack-lvl } S) \# M1' @ [])$  and
   $Z: (\lambda a b. \text{cdcl}_W\text{-stgy } a b \wedge (\exists c. \text{trail } a = c @ \text{Marked } K' (\text{backtrack-lvl } S) \# M1' @ []))^{**} Z S$ 
  using  $\text{rtranclp-cdcl}_W\text{-new-marked-at-beginning-is-decide}'[OF st' - lev, of Ls K'$ 
     $\text{backtrack-lvl } S M1' []]$  unfolding  $R M'$  by auto
have  $[simp]: \text{cdcl}_W\text{-M-level-inv } Y$ 
  using  $RY \text{ lev } \text{rtranclp-cdcl}_W\text{-stgy-consistent-inv}$  by blast
obtain  $M'$  where  $\text{trZ}: \text{trail } Z = M' @ \text{Marked } K' (\text{backtrack-lvl } S) \# M1'$ 
  using  $\text{rtranclp-cdcl}_W\text{-stgy-with-trail-end-has-trail-end}[OF Z] M'$  by auto
have  $\text{no-dup } (\text{trail } Y)$ 
  using  $RY \text{ lev } \text{rtranclp-cdcl}_W\text{-stgy-consistent-inv}$  unfolding  $\text{cdcl}_W\text{-M-level-inv-def}$  by blast
then obtain  $Y'$  where
   $\text{dec}: \text{decide } Y Y'$  and
   $Y'Z: \text{full } \text{cdcl}_W\text{-cp } Y' Z$  and
   $\text{no-step } \text{cdcl}_W\text{-cp } Y$ 
  using  $\text{cdcl}_W\text{-stgy-trail-has-new-marked-is-decide-step}[OF YZ nt Z] M'$  by auto
have  $\text{trY}: \text{trail } Y = M1'$ 
  proof -
    obtain  $M'$  where  $M: \text{trail } Z = M' @ \text{Marked } K' (\text{backtrack-lvl } S) \# M1'$ 
      using  $\text{rtranclp-cdcl}_W\text{-stgy-with-trail-end-has-trail-end}[OF Z] M'$  by auto
    obtain  $M''$  where  $M'': \text{trail } Z = M'' @ \text{trail } Y'$  and  $\forall m \in \text{set } M''. \neg \text{is-marked } m$ 
      using  $Y'Z \text{ rtranclp-cdcl}_W\text{-cp-dropWhile-trail}'$  unfolding  $\text{full-def}$  by blast
    obtain  $M'''$  where  $\text{trail } Y' = M''' @ \text{Marked } K' (\text{backtrack-lvl } S) \# M1'$ 
      using  $M''$  unfolding  $M$ 
      by (metis (no-types, lifting)  $\langle \forall m \in \text{set } M''. \neg \text{is-marked } m \rangle$  beginning-not-marked-invert)
    then show  $?thesis$  using  $\text{dec } nt$  by (induction  $M'''$ ) (auto elim: decideE)
  qed

```

```

have Y-CT: conflicting Y = None using ⟨decide Y Y'⟩ by (auto elim: decideE)
have cdclW** R Y by (simp add: RY rtrancp-cdclW-stgy-rtrancp-cdclW)
then have init-clss Y = init-clss R using rtrancp-cdclW-init-clss[of R Y] M-lev by auto
{ assume DL: mset-ccls E ∈ # clauses Y
  have atm-of L ∉ atm-of ' lits-of-l M1
    apply (rule backtrack-lit-skipped[of S])
    using decomp i k lev' unfolding cdclW-M-level-inv-def by auto
  then have LM1: undefined-lit M1 L
    by (metis Marked-Propagated-in-iff-in-lits-of-l atm-of-uminus image-eqI)
  have L-trY: undefined-lit (trail Y) L
    using L-notin ⟨no-dup (trail S)⟩ unfolding defined-lit-map trY M'
    by (auto simp add: image-iff lits-of-def)
  obtain E' where
    E': E' !∈ raw-clauses Y and
    EE': mset-ccls E' = mset-ccls E
    using DL in-mset-clss-exists-preimage by blast
  have Ex (propagate Y)
    using propagate-rule[of Y E' L] DL M1'-D L-trY Y-CT trY LD E'
    by (auto simp: EE')
  then have False using ⟨no-step cdclW-cp Y⟩ propagate' by blast
}
moreover {
  assume DL: mset-ccls E ∉ # clauses Y
  have lY-lZ: learned-clss Y = learned-clss Z
    using dec Y'Z rtrancp-cdclW-cp-learned-clause-inv[of Y' Z] unfolding full-def
    by (auto elim: decideE)
  have invZ: cdclW-all-struct-inv Z
    by (meson RY YZ invR r-into-rtrancp rtrancp-cdclW-all-struct-inv-inv
        rtrancp-cdclW-stgy-rtrancp-cdclW)
  have n: mset-ccls E ∉ # learned-clss Z
    using DL lY-lZ YZ unfolding raw-clauses-def by auto
  have ?E ∉ # learned-clss S
    apply (rule rtrancp-cdclW-stgy-with-trail-end-has-not-been-learned[OF Z invZ trZ])
    apply (simp add: n)
    using LD apply simp
    apply (metis (no-types, lifting) ⟨set M1 ⊆ set M1'⟩ image-mono order-trans
        vars-of-D lits-of-def)
    using L-notin ⟨no-dup (trail S)⟩ unfolding M' by (auto simp add: image-iff lits-of-def)
  then have False
    using already-learned DL confl st' M-lev rtrancp-cdclW-stgy-no-more-init-clss[of R S]
    unfolding M'
    by (simp add: ⟨init-clss Y = init-clss R⟩ raw-clauses-def confl-S
        rtrancp-cdclW-stgy-no-more-init-clss)
}
ultimately show False by blast
qed

```

**lemma** *rtrancp-cdcl<sub>W</sub>-stgy-distinct-mset-clauses:*

```

assumes
  invR: cdclW-all-struct-inv R and
  st: cdclW-stgy** R S and
  dist: distinct-mset (clauses R) and
  R: trail R = []
shows distinct-mset (clauses S)
using st

```



```

proof (induction)
  case base
  then show ?case using dist by simp
next
  case (step S T) note st = this(1) and s = this(2) and IH = this(3)
  from s show ?case
    proof (cases rule: cdclW-stgy.cases)
      case conflict'
      then show ?thesis
        using IH unfolding full1-def by (auto dest: tranclp-cdclW-cp-no-more-clauses)
    next
      case (other' S') note o = this(1) and full = this(3)
      have [simp]: clauses T = clauses S'
        using full unfolding full-def by (auto dest: rtranclp-cdclW-cp-no-more-clauses)
      show ?thesis
        using o IH
        proof (cases rule: cdclW-o-rule-cases)
          case backtrack
          moreover
            have cdclW-all-struct-inv S
              using invR rtranclp-cdclW-stgy-cdclW-all-struct-inv st by blast
            then have cdclW-M-level-inv S
              unfolding cdclW-all-struct-inv-def by auto
          ultimately obtain E where
            conflicting S = Some E and
            cls-S': clauses S' = {#E#} + clauses S
            using <cdclW-M-level-inv S>
            by (induction rule: backtrack-induction-lev2) (auto simp: cdclW-M-level-inv-decomp)
          then have E  $\notin$  # clauses S
            using cdclW-stgy-no-relearned-clause R invR local.backtrack st by blast
          then show ?thesis using IH by (simp add: distinct-mset-add-single cls-S')
        qed (auto elim: decideE skipE resolveE)
      qed
    qed

```

```

lemma cdclW-stgy-distinct-mset-clauses:
  assumes
    st: cdclW-stgy** (init-state N) S and
    no-duplicate-clause: distinct-mset (mset-cls N) and
    no-duplicate-in-clause: distinct-mset-mset (mset-cls N)
  shows distinct-mset (clauses S)
  using rtranclp-cdclW-stgy-distinct-mset-clauses[OF - st] assms
  by (auto simp: cdclW-all-struct-inv-def distinct-cdclW-state-def)

```

## 19.8 Decrease of a measure

```

fun cdclW-measure where
  cdclW-measure S =
    [( $\beta::nat$ )  $\wedge$  (card (atms-of-mm (init-cls S))) - card (set-mset (learned-cls S))],
    if conflicting S = None then 1 else 0,
    if conflicting S = None then card (atms-of-mm (init-cls S)) - length (trail S)
    else length (trail S)
  ]

```

```

lemma length-model-le-vars-all-inv:
  assumes cdclW-all-struct-inv S

```

```

shows  $\text{length } (\text{trail } S) \leq \text{card } (\text{atms-of-mm } (\text{init-clss } S))$ 
using assms length-model-le-vars[of S] unfolding cdclW-all-struct-inv-def
by (auto simp: cdclW-M-level-inv-decomp)
end

```

```

context conflict-driven-clause-learningW
begin

```

```

lemma learned-clss-less-upper-bound:
  fixes S :: 'st
  assumes
    distinct-cdclW-state S and
     $\forall s \in \# \text{learned-clss } S. \neg \text{tautology } s$ 
  shows  $\text{card}(\text{set-mset } (\text{learned-clss } S)) \leq 3 \wedge \text{card } (\text{atms-of-mm } (\text{learned-clss } S))$ 
proof –
  have  $\text{set-mset } (\text{learned-clss } S) \subseteq \text{simple-clss } (\text{atms-of-mm } (\text{learned-clss } S))$ 
  apply (rule simplified-in-simple-clss)
  using assms unfolding distinct-cdclW-state-def by auto
  then have  $\text{card}(\text{set-mset } (\text{learned-clss } S))$ 
     $\leq \text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{learned-clss } S)))$ 
  by (simp add: simple-clss-finite card-mono)
  then show ?thesis
  by (meson atms-of-ms-finite simple-clss-card finite-set-mset order-trans)
qed

```

```

lemma cdclW-measure-decreasing:
  fixes S :: 'st
  assumes
    cdclW S S' and
    no-restart:
       $\neg(\text{learned-clss } S \subseteq \# \text{learned-clss } S' \wedge [] = \text{trail } S' \wedge \text{conflicting } S' = \text{None})$ 
    and
    no-forget:  $\text{learned-clss } S \subseteq \# \text{learned-clss } S'$  and
    no-relearn:  $\bigwedge S'. \text{backtrack } S S' \implies \forall T. \text{conflicting } S = \text{Some } T \longrightarrow T \notin \# \text{learned-clss } S$ 
    and
    alien: no-strange-atm S and
    M-level: cdclW-M-level-inv S and
    no-taut:  $\forall s \in \# \text{learned-clss } S. \neg \text{tautology } s$  and
    no-dup: distinct-cdclW-state S and
    confl: cdclW-conflicting S
  shows  $(\text{cdcl}_W\text{-measure } S', \text{cdcl}_W\text{-measure } S) \in \text{lexn } \{(a, b). a < b\} \ 3$ 
  using assms(1) M-level assms(2,3)
proof (induct rule: cdclW-all-induct-lev2)
  case (propagate C L) note conf = this(1) and undef = this(5) and T = this(6)
  have propa: propagate S (cons-trail (Propagated L C) S)
  using propagate-rule[OF propagate.hyps(1,2)] propagate.hyps by auto
  then have no-dup': no-dup (Propagated L (mset-cls C) # trail S)
  using M-level cdclW-M-level-inv-decomp(2) undef defined-lit-map by auto

  let ?N = init-clss S
  have no-strange-atm (cons-trail (Propagated L C) S)
  using alien cdclW.propagate cdclW-no-strange-atm-inv propa M-level by blast
  then have atm-of ' lits-of-l (Propagated L (mset-cls C) # trail S)
     $\subseteq \text{atms-of-mm } (\text{init-clss } S)$ 

```

```

    using undef unfolding no-strange-atm-def by auto
  then have card (atm-of ' lits-of-l (Propagated L (mset-cls C) # trail S))
    ≤ card (atms-of-mm (init-clss S))
    by (meson atms-of-ms-finite card-mono finite-set-mset)
  then have length (Propagated L (mset-cls C) # trail S) ≤ card (atms-of-mm ?N)
    using no-dup-length-eq-card-atm-of-lits-of-l no-dup' by fastforce
  then have H: card (atms-of-mm (init-clss S)) - length (trail S)
    = Suc (card (atms-of-mm (init-clss S)) - Suc (length (trail S)))
    by simp
  show ?case using conf T undef by (auto simp: H lexn3-conv)
next
case (decide L) note conf = this(1) and undef = this(2) and T = this(4)
moreover
  have dec: decide S (cons-trail (Marked L (backtrack-lvl S + 1)) (incr-lvl S))
    using decide-rule decide.hyps by force
  then have cdclW:cdclW S (cons-trail (Marked L (backtrack-lvl S + 1)) (incr-lvl S))
    using cdclW.simps cdclW-o.intros by blast
moreover
  have lev: cdclW-M-level-inv (cons-trail (Marked L (backtrack-lvl S + 1)) (incr-lvl S))
    using cdclW M-level cdclW-consistent-inv[OF cdclW] by auto
  then have no-dup: no-dup (Marked L (backtrack-lvl S + 1) # trail S)
    using undef unfolding cdclW-M-level-inv-def by auto
  have no-strange-atm (cons-trail (Marked L (backtrack-lvl S + 1)) (incr-lvl S))
    using M-level alien calculation(4) cdclW-no-strange-atm-inv by blast
  then have length (Marked L ((backtrack-lvl S) + 1) # (trail S))
    ≤ card (atms-of-mm (init-clss S))
    using no-dup undef
    length-model-le-vars[of cons-trail (Marked L (backtrack-lvl S + 1)) (incr-lvl S)]
    by fastforce
  ultimately show ?case using conf by (simp add: lexn3-conv)
next
case (skip L C' M D) note tr = this(1) and conf = this(2) and T = this(5)
show ?case using conf T by (simp add: tr lexn3-conv)
next
case conflict
then show ?case by (simp add: lexn3-conv)
next
case resolve
then show ?case using finite by (simp add: lexn3-conv)
next
case (backtrack K i M1 M2 L D T) note conf = this(1) and decomp = this(3) and undef = this(7)
and
  T = this(8) and lev = this(9)
let ?S' = T
have bt: backtrack S ?S'
  using backtrack.hyps backtrack.intros[of S D L K i] by auto
have mset-ccls D ∉ # learned-clss S
  using no-relearn conf bt by auto
then have card-T:
  card (set-mset ({#mset-ccls D#} + learned-clss S)) = Suc (card (set-mset (learned-clss S)))
  by simp
have distinct-cdclW-state ?S'
  using bt M-level distinct-cdclW-state-inv no-dup other cdclW-o.intros cdclW-bj.intros by blast
moreover have ∀ s ∈ #learned-clss ?S'. ¬ tautology s
  using learned-clss-are-not-tautologies[OF cdclW.other[OF cdclW-o.bj[OF

```

```

    cdclW-bj.backtrack[OF bt]]] M-level no-taut confl by auto
ultimately have card (set-mset (learned-clss T)) ≤ 3 ^ card (atms-of-mm (learned-clss T))
  by (auto simp: learned-clss-less-upper-bound)
then have H: card (set-mset ({#mset-ccls D#} + learned-clss S))
  ≤ 3 ^ card (atms-of-mm ({#mset-ccls D#} + learned-clss S))
  using T undef decomp M-level by (simp add: cdclW-M-level-inv-decomp)
moreover
  have atms-of-mm ({#mset-ccls D#} + learned-clss S) ⊆ atms-of-mm (init-clss S)
    using alien conf unfolding no-strange-atm-def by auto
  then have card-f: card (atms-of-mm ({#mset-ccls D#} + learned-clss S))
    ≤ card (atms-of-mm (init-clss S))
    by (meson atms-of-ms-finite card-mono finite-set-mset)
  then have (3::nat) ^ card (atms-of-mm ({#mset-ccls D#} + learned-clss S))
    ≤ 3 ^ card (atms-of-mm (init-clss S)) by simp
ultimately have (3::nat) ^ card (atms-of-mm (init-clss S))
  ≥ card (set-mset ({#mset-ccls D#} + learned-clss S))
  using le-trans by blast
then show ?case using decomp undef diff-less-mono2 card-T T M-level
  by (auto simp: cdclW-M-level-inv-decomp le3-conv)
next
  case restart
  then show ?case using alien by (auto simp: state-eq-def simp del: state-simp)
next
  case (forget C T) note no-forget = this(8)
  then have mset-clc C ∈# learned-clss S and mset-clc C ∉# learned-clss T
    using forget.hyps by auto
  then show ?case using no-forget by (auto simp add: mset-leD)
qed

```

```

lemma propagate-measure-decreasing:
  fixes S :: 'st
  assumes propagate S S' and cdclW-all-struct-inv S
  shows (cdclW-measure S', cdclW-measure S) ∈ le3 {(a, b). a < b} 3
  apply (rule cdclW-measure-decreasing)
  using assms(1) propagate apply blast
    using assms(1) apply (auto simp add: propagate.simps)[3]
    using assms(2) apply (auto simp add: cdclW-all-struct-inv-def)
  done

```

```

lemma conflict-measure-decreasing:
  fixes S :: 'st
  assumes conflict S S' and cdclW-all-struct-inv S
  shows (cdclW-measure S', cdclW-measure S) ∈ le3 {(a, b). a < b} 3
  apply (rule cdclW-measure-decreasing)
  using assms(1) conflict apply blast
    using assms(1) apply (auto simp: state-eq-def simp del: state-simp elim!: conflictE)[3]
    using assms(2) apply (auto simp add: cdclW-all-struct-inv-def elim: conflictE)
  done

```

```

lemma decide-measure-decreasing:
  fixes S :: 'st
  assumes decide S S' and cdclW-all-struct-inv S
  shows (cdclW-measure S', cdclW-measure S) ∈ le3 {(a, b). a < b} 3
  apply (rule cdclW-measure-decreasing)
  using assms(1) decide other apply blast

```

```

    using assms(1) apply (auto simp: state-eq-def simp del: state-simp elim!: decideE)[3]
    using assms(2) apply (auto simp add: cdclW-all-struct-inv-def elim: decideE)
done

lemma trans-le:
  trans {(a, (b::nat)). a < b}
  unfolding trans-def by auto

lemma cdclW-cp-measure-decreasing:
  fixes S :: 'st
  assumes cdclW-cp S S' and cdclW-all-struct-inv S
  shows (cdclW-measure S', cdclW-measure S) ∈ lexn {(a, b). a < b} 3
  using assms
proof induction
  case conflict'
  then show ?case using conflict-measure-decreasing by blast
next
  case propagate'
  then show ?case using propagate-measure-decreasing by blast
qed

lemma tranclp-cdclW-cp-measure-decreasing:
  fixes S :: 'st
  assumes cdclW-cp++ S S' and cdclW-all-struct-inv S
  shows (cdclW-measure S', cdclW-measure S) ∈ lexn {(a, b). a < b} 3
  using assms
proof induction
  case base
  then show ?case using cdclW-cp-measure-decreasing by blast
next
  case (step T U) note st = this(1) and step = this(2) and IH = this(3) and inv = this(4)
  then have (cdclW-measure T, cdclW-measure S) ∈ lexn {a. case a of (a, b) ⇒ a < b} 3 by blast

  moreover have (cdclW-measure U, cdclW-measure T) ∈ lexn {a. case a of (a, b) ⇒ a < b} 3
  using cdclW-cp-measure-decreasing[OF step] rtranclp-cdclW-all-struct-inv-inv inv
  tranclp-cdclW-cp-tranclp-cdclW[OF st]
  unfolding trans-def rtranclp-unfold
  by blast
  ultimately show ?case using lexn-transI[OF trans-le] unfolding trans-def by blast
qed

lemma cdclW-stgy-step-decreasing:
  fixes R S T :: 'st
  assumes cdclW-stgy S T and
  cdclW-stgy** R S
  trail R = [] and
  cdclW-all-struct-inv R
  shows (cdclW-measure T, cdclW-measure S) ∈ lexn {(a, b). a < b} 3
proof -
  have cdclW-all-struct-inv S
  using assms
  by (metis rtranclp-unfold rtranclp-cdclW-all-struct-inv-inv tranclp-cdclW-stgy-tranclp-cdclW)
  with assms show ?thesis
  proof induction
    case (conflict' V) note cp = this(1) and inv = this(5)

```

```

show ?case
  using tranclp-cdclW-cp-measure-decreasing[OF HOL.conjunct1[OF cp[unfolded full1-def]] inv]
.
next
case (other' T U) note st = this(1) and H = this(4,5,6,7) and cp = this(3)
have cdclW-all-struct-inv T
  using cdclW-all-struct-inv-inv other other'.hyps(1) other'.prems(4) by blast
from tranclp-cdclW-cp-measure-decreasing[OF - this]
have le-or-eq: (cdclW-measure U, cdclW-measure T) ∈ lern {a. case a of (a, b) ⇒ a < b} 3 ∨
  cdclW-measure U = cdclW-measure T
  using cp unfolding full-def rtranclp-unfold by blast
moreover
have cdclW-M-level-inv S
  using cdclW-all-struct-inv-def other'.prems(4) by blast
with st have (cdclW-measure T, cdclW-measure S) ∈ lern {a. case a of (a, b) ⇒ a < b} 3
proof (induction rule:cdclW-o-induct-lev2)
  case (decide T)
  then show ?case using decide-measure-decreasing H decide.intros[OF decide.hyps] by blast
next
case (backtrack K i M1 M2 L D T) note conf = this(1) and decomp = this(3) and
  undef = this(7) and T = this(8)
have bt: backtrack S T
  apply (rule backtrack-rule)
  using backtrack.hyps by auto
then have no-relearn: ∀ T. conflicting S = Some T ⟶ T ∉ learned-clss S
  using cdclW-stgy-no-relearned-clause[of R S T] H conf
  unfolding cdclW-all-struct-inv-def raw-clauses-def by auto
have inv: cdclW-all-struct-inv S
  using ⟨cdclW-all-struct-inv S⟩ by blast
show ?case
  apply (rule cdclW-measure-decreasing)
  using bt cdclW-bj.backtrack cdclW-o.bj other apply simp
  using bt T undef decomp inv unfolding cdclW-all-struct-inv-def
    cdclW-M-level-inv-def apply auto[]
  using bt T undef decomp inv unfolding cdclW-all-struct-inv-def
    cdclW-M-level-inv-def apply auto[]
  using bt no-relearn apply auto[]
  using inv unfolding cdclW-all-struct-inv-def apply simp
  using inv unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def apply simp
  using inv unfolding cdclW-all-struct-inv-def apply simp
  using inv unfolding cdclW-all-struct-inv-def apply simp
  using inv unfolding cdclW-all-struct-inv-def by simp
next
case skip
then show ?case by (auto simp: lern3-conv)
next
case resolve
then show ?case by (auto simp: lern3-conv)
qed
ultimately show ?case
  by (metis (full-types) lern-transI transD trans-le)
qed
qed

```

lemma tranclp-cdcl<sub>W</sub>-stgy-decreasing:

```

fixes  $R\ S\ T :: 'st$ 
assumes  $cdcl_W\text{-stgy}^{++}\ R\ S$ 
 $trail\ R = []$  and
 $cdcl_W\text{-all-struct-inv}\ R$ 
shows  $(cdcl_W\text{-measure}\ S,\ cdcl_W\text{-measure}\ R) \in le_{rn}\ \{(a,\ b).\ a < b\}\ \exists$ 
using  $assms$ 
apply  $induction$ 
  using  $cdcl_W\text{-stgy-step-decreasing}[of\ R - R]$  apply  $blast$ 
using  $cdcl_W\text{-stgy-step-decreasing}[of\ - - R]$   $trancpl\text{-into-rtrancpl}[of\ cdcl_W\text{-stgy}\ R]$ 
 $le_{rn}\text{-transI}[OF\ trans\text{-le},\ of\ \exists]$  unfolding  $trans\text{-def}$  by  $blast$ 

lemma  $trancpl\text{-}cdcl_W\text{-stgy}\text{-}S0\text{-decreasing}$ :
fixes  $R\ S\ T :: 'st$ 
assumes
   $pl: cdcl_W\text{-stgy}^{++}\ (init\text{-state}\ N)\ S$  and
   $no\text{-dup}: distinct\text{-mset-mset}\ (mset\text{-class}\ N)$ 
shows  $(cdcl_W\text{-measure}\ S,\ cdcl_W\text{-measure}\ (init\text{-state}\ N)) \in le_{rn}\ \{(a,\ b).\ a < b\}\ \exists$ 
proof -
  have  $cdcl_W\text{-all-struct-inv}\ (init\text{-state}\ N)$ 
    using  $no\text{-dup}$  unfolding  $cdcl_W\text{-all-struct-inv-def}$  by  $auto$ 
  then show  $?thesis$  using  $pl\ trancpl\text{-}cdcl_W\text{-stgy}\text{-decreasing}\ init\text{-state-trail}$  by  $blast$ 
qed

lemma  $wf\text{-}trancpl\text{-}cdcl_W\text{-stgy}$ :
 $wf\ \{(S::'st,\ init\text{-state}\ N) |$ 
   $S\ N.\ distinct\text{-mset-mset}\ (mset\text{-class}\ N) \wedge cdcl_W\text{-stgy}^{++}\ (init\text{-state}\ N)\ S\}$ 
apply  $(rule\ wf\text{-}wf\text{-if-measure}'\text{-notation2}[of\ le_{rn}\ \{(a,\ b).\ a < b\}\ \exists - - cdcl_W\text{-measure}])$ 
apply  $(simp\ add: wf\ wf\text{-le}_{rn})$ 
using  $trancpl\text{-}cdcl_W\text{-stgy}\text{-}S0\text{-decreasing}$  by  $blast$ 

lemma  $cdcl_W\text{-cp}\text{-}wf\text{-all-inv}$ :
 $wf\ \{(S',\ S).\ cdcl_W\text{-all-struct-inv}\ S \wedge cdcl_W\text{-cp}\ S\ S'\}$ 
 $(is\ wf\ ?R)$ 
proof  $(rule\ wf\text{-bounded-measure}[of\ -$ 
   $\lambda S.\ card\ (atms\text{-of-mm}\ (init\text{-class}\ S)) + 1$ 
   $\lambda S.\ length\ (trail\ S) + (if\ conflicting\ S = None\ then\ 0\ else\ 1)]$ ,  $goal\text{-cases}$ )
case  $(1\ S\ S')$ 
then have  $cdcl_W\text{-all-struct-inv}\ S$  and  $cdcl_W\text{-cp}\ S\ S'$  by  $auto$ 
moreover then have  $cdcl_W\text{-all-struct-inv}\ S'$ 
  using  $cdcl_W\text{-cp.simps}\ cdcl_W\text{-all-struct-inv-inv}\ conflict\ cdcl_W.intros\ cdcl_W\text{-all-struct-inv-inv}$ 
by  $blast+$ 
ultimately show  $?case$ 
  by  $(auto\ simp: cdcl_W\text{-cp.simps}\ state\text{-eq-def}\ simp\ del: state\text{-simp}\ elim!: conflictE\ propagateE$ 
     $dest: length\text{-model-le-vars-all-inv})$ 
qed

end

end

theory  $DPLL\text{-}CDCL\text{-}W\text{-Implementation}$ 
imports  $Partial\text{-Annotated}\text{-Clausal}\text{-Logic}$ 
begin

```

## 20 Simple Implementation of the DPLL and CDCL

### 20.1 Common Rules

#### 20.1.1 Propagation

The following theorem holds:

**lemma** *lits-of-l-unfold*[iff]:

$(\forall c \in \text{set } C. -c \in \text{lits-of-l } Ms) \longleftrightarrow Ms \models_{as} CNot \ (mset \ C)$   
**unfolding** *true-annot-def Ball-def true-annot-def CNot-def* **by** *auto*

The right-hand version is written at a high-level, but only the left-hand side is executable.

**definition** *is-unit-clause* :: 'a literal list  $\Rightarrow$  ('a, 'b, 'c) marked-lit list  $\Rightarrow$  'a literal option

**where**

*is-unit-clause* *l* *M* =

(case *List.filter* ( $\lambda a. \text{atm-of } a \notin \text{atm-of ' lits-of-l } M$ ) *l* of  
 $a \# [] \Rightarrow \text{if } M \models_{as} CNot \ (mset \ l - \{\#a\# \}) \text{ then } Some \ a \text{ else } None$   
 $| - \Rightarrow None$ )

**definition** *is-unit-clause-code* :: 'a literal list  $\Rightarrow$  ('a, 'b, 'c) marked-lit list

$\Rightarrow$  'a literal option **where**

*is-unit-clause-code* *l* *M* =

(case *List.filter* ( $\lambda a. \text{atm-of } a \notin \text{atm-of ' lits-of-l } M$ ) *l* of  
 $a \# [] \Rightarrow \text{if } (\forall c \in \text{set } (remove1 \ a \ l). -c \in \text{lits-of-l } M) \text{ then } Some \ a \text{ else } None$   
 $| - \Rightarrow None$ )

**lemma** *is-unit-clause-is-unit-clause-code*[code]:

*is-unit-clause* *l* *M* = *is-unit-clause-code* *l* *M*

**proof** –

**have**  $1: \bigwedge a. (\forall c \in \text{set } (remove1 \ a \ l). -c \in \text{lits-of-l } M) \longleftrightarrow M \models_{as} CNot \ (mset \ l - \{\#a\# \})$

**using** *lits-of-l-unfold*[of *remove1* - *l*, of - *M*] **by** *simp*

**thus** *?thesis*

**unfolding** *is-unit-clause-code-def is-unit-clause-def 1* **by** *blast*

**qed**

**lemma** *is-unit-clause-some-undef*:

**assumes** *is-unit-clause* *l* *M* = *Some a*

**shows** *undefined-lit* *M* *a*

**proof** –

**have** (case [*a* ← *l* . *atm-of* *a*  $\notin$  *atm-of ' lits-of-l* *M*] of []  $\Rightarrow None$

$| [a] \Rightarrow \text{if } M \models_{as} CNot \ (mset \ l - \{\#a\# \}) \text{ then } Some \ a \text{ else } None$

$| a \# ab \# xa \Rightarrow Map.empty \ xa) = Some \ a$

**using** *assms* **unfolding** *is-unit-clause-def* .

**hence**  $a \in \text{set } [a \leftarrow l . \text{atm-of } a \notin \text{atm-of ' lits-of-l } M]$

**apply** (cases [*a* ← *l* . *atm-of* *a*  $\notin$  *atm-of ' lits-of-l* *M*])

**apply** *simp*

**apply** (*rename-tac aa list*; *case-tac list*) **by** (*auto split: if-split-asm*)

**hence** *atm-of* *a*  $\notin$  *atm-of ' lits-of-l* *M* **by** *auto*

**thus** *?thesis*

**by** (*simp add: Marked-Propagated-in-iff-in-lits-of-l*  
*atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set* )

**qed**

**lemma** *is-unit-clause-some-CNot*: *is-unit-clause* *l* *M* = *Some a*  $\implies M \models_{as} CNot \ (mset \ l - \{\#a\# \})$

**unfolding** *is-unit-clause-def*

**proof** –



```

assume (case [a ← l . atm-of a ∉ atm-of ‘ lits-of-l M] of [] ⇒ None
  | [a] ⇒ if M ⊨as CNot (mset l - {#a#}) then Some a else None
  | a # ab # xa ⇒ Map.empty xa) = Some a
thus ?thesis
apply (cases [a ← l . atm-of a ∉ atm-of ‘ lits-of-l M], simp)
apply simp
apply (rename-tac aa list, case-tac list) by (auto split: if-split-asm)
qed

```

**lemma** *is-unit-clause-some-in*: *is-unit-clause l M = Some a ⇒ a ∈ set l*  
**unfolding** *is-unit-clause-def*

**proof** –

```

assume (case [a ← l . atm-of a ∉ atm-of ‘ lits-of-l M] of [] ⇒ None
  | [a] ⇒ if M ⊨as CNot (mset l - {#a#}) then Some a else None
  | a # ab # xa ⇒ Map.empty xa) = Some a
thus a ∈ set l
by (cases [a ← l . atm-of a ∉ atm-of ‘ lits-of-l M])
  (fastforce dest: filter-eq-ConsD split: if-split-asm split: list.splits)+
qed

```

**lemma** *is-unit-clause-nil[simp]*: *is-unit-clause [] M = None*  
**unfolding** *is-unit-clause-def* **by** auto

## 20.1.2 Unit propagation for all clauses

Finding the first clause to propagate

```

fun find-first-unit-clause :: 'a literal list list ⇒ ('a, 'b, 'c) marked-lit list
  ⇒ ('a literal × 'a literal list) option where
find-first-unit-clause (a # l) M =
  (case is-unit-clause a M of
    None ⇒ find-first-unit-clause l M
  | Some L ⇒ Some (L, a)) |
find-first-unit-clause [] - = None

```

**lemma** *find-first-unit-clause-some*:

```

find-first-unit-clause l M = Some (a, c)
⇒ c ∈ set l ∧ M ⊨as CNot (mset c - {#a#}) ∧ undefined-lit M a ∧ a ∈ set c
apply (induction l)
apply simp
by (auto split: option.splits dest: is-unit-clause-some-in is-unit-clause-some-CNot
  is-unit-clause-some-undef)

```

**lemma** *propagate-is-unit-clause-not-None*:

```

assumes dist: distinct c and
M: M ⊨as CNot (mset c - {#a#}) and
undef: undefined-lit M a and
ac: a ∈ set c
shows is-unit-clause c M ≠ None

```

**proof** –

```

have [a ← c . atm-of a ∉ atm-of ‘ lits-of-l M] = [a]
using assms
proof (induction c)
case Nil thus ?case by simp
next
case (Cons ac c)

```

```

show ?case
  proof (cases a = ac)
    case True
      thus ?thesis using Cons
        by (auto simp del: lits-of-l-unfold
          simp add: lits-of-l-unfold[symmetric] Marked-Propagated-in-iff-in-lits-of-l
            atm-of-eq-atm-of atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set)
    next
      case False
        hence T: mset c + {#ac#} - {#a#} = mset c - {#a#} + {#ac#}
          by (auto simp add: multiset-eq-iff)
        show ?thesis using False Cons
          by (auto simp add: T atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set)
      qed
    qed
thus ?thesis
using M unfolding is-unit-clause-def by auto
qed

```

**lemma** find-first-unit-clause-none:

distinct c  $\implies$  c  $\in$  set l  $\implies$  M  $\models$ as CNot (mset c - {#a#})  $\implies$  undefined-lit M a  $\implies$  a  $\in$  set c  
 $\implies$  find-first-unit-clause l M  $\neq$  None  
**by** (induction l)  
 (auto split: option.split simp add: propagate-is-unit-clause-not-None)

### 20.1.3 Decide

**fun** find-first-unused-var :: 'a literal list list  $\Rightarrow$  'a literal set  $\Rightarrow$  'a literal option **where**

find-first-unused-var (a # l) M =  
 (case List.find ( $\lambda$ lit. lit  $\notin$  M  $\wedge$   $\neg$ lit  $\notin$  M) a of  
 None  $\Rightarrow$  find-first-unused-var l M  
 | Some a  $\Rightarrow$  Some a) |  
 find-first-unused-var [] - = None

**lemma** find-none[iff]:

List.find ( $\lambda$ lit. lit  $\notin$  M  $\wedge$   $\neg$ lit  $\notin$  M) a = None  $\longleftrightarrow$  atm-of ' set a  $\subseteq$  atm-of ' M  
**apply** (induct a)  
**using** atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set  
**by** (force simp add: atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set)+

**lemma** find-some: List.find ( $\lambda$ lit. lit  $\notin$  M  $\wedge$   $\neg$ lit  $\notin$  M) a = Some b  $\implies$  b  $\in$  set a  $\wedge$  b  $\notin$  M  $\wedge$   $\neg$ b  $\notin$  M  
**unfolding** find-Some-iff **by** (metis nth-mem)

**lemma** find-first-unused-var-None[iff]:

find-first-unused-var l M = None  $\longleftrightarrow$  ( $\forall$  a  $\in$  set l. atm-of ' set a  $\subseteq$  atm-of ' M)  
**by** (induct l)  
 (auto split: option.splits dest!: find-some  
 simp add: image-subset-iff atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set)

**lemma** find-first-unused-var-Some-not-all-incl:

**assumes** find-first-unused-var l M = Some c  
**shows**  $\neg(\forall$  a  $\in$  set l. atm-of ' set a  $\subseteq$  atm-of ' M)

**proof** -

**have** find-first-unused-var l M  $\neq$  None  
**using** assms **by** (cases find-first-unused-var l M) auto  
**thus**  $\neg(\forall$  a  $\in$  set l. atm-of ' set a  $\subseteq$  atm-of ' M) **by** auto

qed

**lemma** *find-first-unused-var-Some*:

*find-first-unused-var*  $l$   $M = \text{Some } a \implies (\exists m \in \text{set } l. a \in \text{set } m \wedge a \notin M \wedge -a \notin M)$   
**by** (induct  $l$ ) (auto split: option.splits dest: find-some)

**lemma** *find-first-unused-var-undefined*:

*find-first-unused-var*  $l$  (*lits-of-l*  $Ms$ ) = *Some*  $a \implies \text{undefined-lit } Ms$   $a$   
**using** *find-first-unused-var-Some*[of  $l$  *lits-of-l*  $Ms$   $a$ ] *Marked-Propagated-in-iff-in-lits-of-l*  
**by** blast

end

**theory** *DPLL-W-Implementation*

**imports** *DPLL-CDCL-W-Implementation* *DPLL-W*  $\sim\sim$  /src/HOL/Library/Code-Target-Numeral

**begin**

## 20.2 Simple Implementation of DPLL

### 20.2.1 Combining the propagate and decide: a DPLL step

**definition** *DPLL-step* ::  $\text{int } dpll_W\text{-marked-lits} \times \text{int literal list list}$

$\Rightarrow \text{int } dpll_W\text{-marked-lits} \times \text{int literal list list}$  **where**

*DPLL-step* =  $(\lambda(Ms, N).$

(*case find-first-unit-clause*  $N$   $Ms$  of

*Some* ( $L, -$ )  $\Rightarrow$  (*Propagated*  $L$  ())  $\#$   $Ms, N$ )

|  $- \Rightarrow$

if  $\exists C \in \text{set } N. (\forall c \in \text{set } C. -c \in \text{lits-of-l } Ms)$

then

(*case backtrack-split*  $Ms$  of

( $-, L \# M$ )  $\Rightarrow$  (*Propagated* ( $-(\text{lit-of } L)$ ) ())  $\#$   $M, N$ )

| ( $-, -$ )  $\Rightarrow$  ( $Ms, N$ )

)

else

(*case find-first-unused-var*  $N$  (*lits-of-l*  $Ms$ ) of

*Some*  $a \Rightarrow$  (*Marked*  $a$  ())  $\#$   $Ms, N$ )

| *None*  $\Rightarrow$  ( $Ms, N$ ))))

Example of propagation:

**value** *DPLL-step* ( $[\text{Marked } (Neg\ 1) ()], [[Pos\ (1::int), Neg\ 2]]$ )

We define the conversion function between the states as defined in *Prop-DPLL* (with multisets) and here (with lists).

**abbreviation** *toS*  $\equiv \lambda(Ms::(\text{int}, \text{unit}, \text{unit}) \text{ marked-lit list})$

$(N:: \text{int literal list list}). (Ms, \text{mset } (\text{map } \text{mset } N))$

**abbreviation** *toS'*  $\equiv \lambda(Ms::(\text{int}, \text{unit}, \text{unit}) \text{ marked-lit list},$

$N:: \text{int literal list list}). (Ms, \text{mset } (\text{map } \text{mset } N))$

Proof of correctness of *DPLL-step*

**lemma** *DPLL-step-is-a-dpll<sub>W</sub>-step*:

**assumes** *step*:  $(Ms', N') = \text{DPLL-step } (Ms, N)$

**and** *neg*:  $(Ms, N) \neq (Ms', N')$

**shows** *dpll<sub>W</sub>* (*toS*  $Ms$   $N$ ) (*toS*  $Ms'$   $N'$ )

**proof** –

let  $?S = (Ms, \text{mset } (\text{map } \text{mset } N))$

{ **fix**  $L$   $E$

```

assume unit: find-first-unit-clause N Ms = Some (L, E)
hence Ms'N: (Ms', N') = (Propagated L () # Ms, N)
  using step unfolding DPLL-step-def by auto
obtain C where
  C: C ∈ set N and
  Ms: Ms ⊨as CNot (mset C − {#L#}) and
  undef: undefined-lit Ms L and
  L ∈ set C using find-first-unit-clause-some[OF unit] by metis
have dpllW (Ms, mset (map mset N))
  (Propagated L () # fst (Ms, mset (map mset N)), snd (Ms, mset (map mset N)))
  apply (rule dpllW.propagate)
  using Ms undef C (L ∈ set C) by (auto simp add: C)
hence ?thesis using Ms'N by auto
}
moreover
{ assume unit: find-first-unit-clause N Ms = None
  assume exC: ∃ C ∈ set N. Ms ⊨as CNot (mset C)
  then obtain C where C: C ∈ set N and Ms: Ms ⊨as CNot (mset C) by auto
  then obtain L M M' where bt: backtrack-split Ms = (M', L # M)
    using step exC neq unfolding DPLL-step-def prod.case unit
    by (cases backtrack-split Ms, rename-tac b, case-tac b) auto
  hence is-marked L using backtrack-split-snd-hd-marked[of Ms] by auto
  have 1: dpllW (Ms, mset (map mset N))
    (Propagated (− lit-of L) () # M, snd (Ms, mset (map mset N)))
    apply (rule dpllW.backtrack[OF - is-marked L, of ])
    using C Ms bt by auto
  moreover have (Ms', N') = (Propagated (− (lit-of L)) () # M, N)
    using step exC unfolding DPLL-step-def bt prod.case unit by auto
  ultimately have ?thesis by auto
}
moreover
{ assume unit: find-first-unit-clause N Ms = None
  assume exC: ¬ (∃ C ∈ set N. Ms ⊨as CNot (mset C))
  obtain L where unused: find-first-unused-var N (lits-of-l Ms) = Some L
    using step exC neq unfolding DPLL-step-def prod.case unit
    by (cases find-first-unused-var N (lits-of-l Ms)) auto
  have dpllW (Ms, mset (map mset N))
    (Marked L () # fst (Ms, mset (map mset N)), snd (Ms, mset (map mset N)))
    apply (rule dpllW.decided[of ?S L])
    using find-first-unused-var-Some[OF unused]
    by (auto simp add: Marked-Propagated-in-iff-in-lits-of-l atms-of-ms-def)
  moreover have (Ms', N') = (Marked L () # Ms, N)
    using step exC unfolding DPLL-step-def unused prod.case unit by auto
  ultimately have ?thesis by auto
}
ultimately show ?thesis by (cases find-first-unit-clause N Ms) auto
qed

```

**lemma** *DPLL-step-stuck-final-state*:

**assumes** *step*: (*Ms*, *N*) = *DPLL-step* (*Ms*, *N*)  
**shows** *conclusive-dpll<sub>W</sub>-state* (*toS Ms N*)

**proof** –

**have** *unit*: *find-first-unit-clause* *N Ms* = *None*  
**using** *step unfolding DPLL-step-def* **by** (*auto split:option.splits*)

```

{ assume n:  $\exists C \in \text{set } N. Ms \models_{as} CNot (mset C)$ 
  hence Ms:  $(Ms, N) = (\text{case } backtrack-split \text{ Ms of } (x, []) \Rightarrow (Ms, N) \mid (x, L \# M) \Rightarrow (Propagated (- lit-of L) () \# M, N))$ 
    using step unfolding DPLL-step-def by (simp add:unit)

have snd (backtrack-split Ms) = []
proof (cases backtrack-split Ms, cases snd (backtrack-split Ms))
  fix a b
  assume backtrack-split Ms = (a, b) and snd (backtrack-split Ms) = []
  thus snd (backtrack-split Ms) = [] by blast
next
fix a b aa list
assume
  bt: backtrack-split Ms = (a, b) and
  bt': snd (backtrack-split Ms) = aa # list
hence Ms: Ms = Propagated (- lit-of aa) () # list using Ms by auto
have is-marked aa using backtrack-split-snd-hd-marked[of Ms] bt bt' by auto
moreover have fst (backtrack-split Ms) @ aa # list = Ms
  using backtrack-split-list-eq[of Ms] bt' by auto
ultimately have False unfolding Ms by auto
thus snd (backtrack-split Ms) = [] by blast
qed

hence ?thesis
  using n backtrack-snd-empty-not-marked[of Ms] unfolding conclusive-dpllW-state-def
  by (cases backtrack-split Ms) auto
}
moreover {
  assume n:  $\neg (\exists C \in \text{set } N. Ms \models_{as} CNot (mset C))$ 
  hence find-first-unused-var N (lits-of-l Ms) = None
    using step unfolding DPLL-step-def by (simp add: unit split: option.splits)
  hence a:  $\forall a \in \text{set } N. atm\text{-of } 'set \ a \subseteq atm\text{-of } ' (lits\text{-of-l } Ms)$  by auto
  have fst (toS Ms N)  $\models_{asm} snd (toS Ms N)$  unfolding true-annots-def CNot-def Ball-def
  proof clarify
    fix x
    assume x:  $x \in \text{set-mset } (clauses (toS Ms N))$ 
    hence  $\neg Ms \models_{as} CNot \ x$  using n unfolding true-annots-def CNot-def Ball-def by auto
    moreover have total-over-m (lits-of-l Ms) {x}
      using a x image-iff in-mono atms-of-s-def
      unfolding total-over-m-def total-over-set-def lits-of-def by fastforce
    ultimately show fst (toS Ms N)  $\models_a x$ 
      using total-not-CNot[of lits-of-l Ms x] by (simp add: true-annot-def true-annots-true-cl)
    qed
  hence ?thesis unfolding conclusive-dpllW-state-def by blast
}
ultimately show ?thesis by blast
qed

```

## 20.2.2 Adding invariants

**Invariant tested in the function** `function DPLL-ci :: int dpllW-marked-lits  $\Rightarrow$  int literal list list`  
 `$\Rightarrow$  int dpllW-marked-lits  $\times$  int literal list list` **where**  
`DPLL-ci Ms N =`  
`(if  $\neg dpll_W\text{-all-inv } (Ms, mset (map mset N))$`   
`then (Ms, N)`

```

else
  let (Ms', N') = DPLL-step (Ms, N) in
  if (Ms', N') = (Ms, N) then (Ms, N) else DPLL-ci Ms' N)
by fast+
termination
proof (relation {(S', S). (toS' S', toS' S) ∈ {(S', S). dpllW-all-inv S ∧ dpllW S S'}})
  show wf {(S', S). (toS' S', toS' S) ∈ {(S', S). dpllW-all-inv S ∧ dpllW S S'}}
    using wf-if-measure-f[OF dpllW-wf, of toS'] by auto
next
fix Ms :: int dpllW-marked-lits and N x xa y
assume ¬ ¬ dpllW-all-inv (toS Ms N)
and step: x = DPLL-step (Ms, N)
and x: (xa, y) = x
and (xa, y) ≠ (Ms, N)
thus ((xa, N), Ms, N) ∈ {(S', S). (toS' S', toS' S) ∈ {(S', S). dpllW-all-inv S ∧ dpllW S S'}}
  using DPLL-step-is-a-dpllW-step dpllW-same-clauses split-conv by fastforce
qed

No invariant tested  function (domintros) DPLL-part:: int dpllW-marked-lits ⇒ int literal list list
⇒
  int dpllW-marked-lits × int literal list list where
DPLL-part Ms N =
  (let (Ms', N') = DPLL-step (Ms, N) in
  if (Ms', N') = (Ms, N) then (Ms, N) else DPLL-part Ms' N)
by fast+

lemma snd-DPLL-step[simp]:
  snd (DPLL-step (Ms, N)) = N
  unfolding DPLL-step-def by (auto split: if-split option.splits prod.splits list.splits)

lemma dpllW-all-inv-implicS-2-eq3-and-dom:
  assumes dpllW-all-inv (Ms, mset (map mset N))
  shows DPLL-ci Ms N = DPLL-part Ms N ∧ DPLL-part-dom (Ms, N)
  using assms
proof (induct rule: DPLL-ci.induct)
  case (1 Ms N)
  have snd (DPLL-step (Ms, N)) = N by auto
  then obtain Ms' where Ms': DPLL-step (Ms, N) = (Ms', N) by (cases DPLL-step (Ms, N)) auto
  have inv': dpllW-all-inv (toS Ms' N) by (metis (mono-tags) 1.prem DPLL-step-is-a-dpllW-step
    Ms' dpllW-all-inv old.prod.inject)
  { assume (Ms', N) ≠ (Ms, N)
    hence DPLL-ci Ms' N = DPLL-part Ms' N ∧ DPLL-part-dom (Ms', N) using 1(1)[of - Ms' N]
  }
  Ms'
  1(2) inv' by auto
  hence DPLL-part-dom (Ms, N) using DPLL-part.domintros Ms' by fastforce
  moreover have DPLL-ci Ms N = DPLL-part Ms N using 1.prem DPLL-part.psims Ms'
    ⟨DPLL-ci Ms' N = DPLL-part Ms' N ∧ DPLL-part-dom (Ms', N)⟩ ⟨DPLL-part-dom (Ms, N)⟩ by
  auto
  ultimately have ?case by blast
}
moreover {
  assume (Ms', N) = (Ms, N)
  hence ?case using DPLL-part.domintros DPLL-part.psims Ms' by fastforce
}
ultimately show ?case by blast

```

qed

**lemma** *DPLL-ci-dpll<sub>W</sub>-rtrancp*:

**assumes** *DPLL-ci*  $Ms\ N = (Ms', N')$   
**shows**  $dpll_W^{**} (toS\ Ms\ N) (toS\ Ms'\ N)$   
**using** *assms*

**proof** (*induct*  $Ms\ N$  *arbitrary*:  $Ms'\ N'$  *rule*: *DPLL-ci.induct*)

**case** ( $1\ Ms\ N\ Ms'\ N'$ ) **note**  $IH = this(1)$  **and**  $step = this(2)$

**obtain**  $S_1\ S_2$  **where**  $S: (S_1, S_2) = DPLL\text{-}step\ (Ms, N)$  **by** (*cases* *DPLL-step* ( $Ms, N$ )) *auto*

{ **assume**  $\neg dpll_W\text{-}all\text{-}inv\ (toS\ Ms\ N)$   
**hence**  $(Ms, N) = (Ms', N)$  **using** *step* **by** *auto*  
**hence** *?case* **by** *auto*

}

**moreover**

{ **assume**  $dpll_W\text{-}all\text{-}inv\ (toS\ Ms\ N)$   
**and**  $(S_1, S_2) = (Ms, N)$   
**hence** *?case* **using** *S step* **by** *auto*

}

**moreover**

{ **assume**  $dpll_W\text{-}all\text{-}inv\ (toS\ Ms\ N)$   
**and**  $(S_1, S_2) \neq (Ms, N)$

**moreover obtain**  $S_1'\ S_2'$  **where**  $DPLL\text{-}ci\ S_1\ N = (S_1', S_2')$  **by** (*cases* *DPLL-ci*  $S_1\ N$ ) *auto*

**moreover have**  $DPLL\text{-}ci\ Ms\ N = DPLL\text{-}ci\ S_1\ N$  **using** *DPLL-ci.simps*[*of*  $Ms\ N$ ] *calculation*

**proof** –

**have** (*case*  $(S_1, S_2)$  *of*  $(ms, lss) \Rightarrow$

*if*  $(ms, lss) = (Ms, N)$  *then*  $(Ms, N)$  *else*  $DPLL\text{-}ci\ ms\ N = DPLL\text{-}ci\ Ms\ N$

**using** *S DPLL-ci.simps*[*of*  $Ms\ N$ ] *calculation* **by** *presburger*

**hence** (*if*  $(S_1, S_2) = (Ms, N)$  *then*  $(Ms, N)$  *else*  $DPLL\text{-}ci\ S_1\ N = DPLL\text{-}ci\ Ms\ N$

*by* *fastforce*

**thus** *?thesis*

**using** *calculation*(2) **by** *presburger*

**qed**

**ultimately have**  $dpll_W^{**} (toS\ S_1'\ N) (toS\ Ms'\ N)$  **using**  $IH[of\ (S_1, S_2)\ S_1\ S_2]$  *S step* **by** *simp*

**moreover have**  $dpll_W\ (toS\ Ms\ N) (toS\ S_1\ N)$

**by** (*metis* *DPLL-step-is-a-dpll<sub>W</sub>-step*  $S\ \langle (S_1, S_2) \neq (Ms, N) \rangle\ prod.sel(2)\ snd\text{-}DPLL\text{-}step$ )

**ultimately have** *?case* **by** (*metis* (*mono-tags*, *hide-lams*)  $IH\ S\ \langle (S_1, S_2) \neq (Ms, N) \rangle$

$\langle DPLL\text{-}ci\ Ms\ N = DPLL\text{-}ci\ S_1\ N \rangle\ \langle dpll_W\text{-}all\text{-}inv\ (toS\ Ms\ N) \rangle\ converse\text{-}rtrancp\text{-}into\text{-}rtrancp\ local.step$ )

}

**ultimately show** *?case* **by** *blast*

qed

**lemma** *dpll<sub>W</sub>-all-inv-dpll<sub>W</sub>-trancp-irrefl*:

**assumes**  $dpll_W\text{-}all\text{-}inv\ (Ms, N)$

**and**  $dpll_W^{++} (Ms, N) (Ms, N)$

**shows** *False*

**proof** –

**have**  $1: wf\ \{(S', S). dpll_W\text{-}all\text{-}inv\ S \wedge dpll_W^{++} S\ S'\}$  **using** *dpll<sub>W</sub>-wf-trancp* **by** *auto*

**have**  $((Ms, N), (Ms, N)) \in \{(S', S). dpll_W\text{-}all\text{-}inv\ S \wedge dpll_W^{++} S\ S'\}$  **using** *assms* **by** *auto*

**thus** *False* **using** *wf-not-refl*[*OF* 1] **by** *blast*

qed

**lemma** *DPLL-ci-final-state*:

**assumes** *step*:  $DPLL\text{-}ci\ Ms\ N = (Ms, N)$   
**and** *inv*:  $dpll_W\text{-}all\text{-}inv\ (toS\ Ms\ N)$   
**shows** *conclusive-dpll<sub>W</sub>-state* (*toS Ms N*)  
**proof** –  
**have** *st*:  $dpll_W^{**}\ (toS\ Ms\ N)\ (toS\ Ms\ N)$  **using**  $DPLL\text{-}ci\text{-}dpll_W\text{-}rtranclp[OF\ step]$  .  
**have**  $DPLL\text{-}step\ (Ms, N) = (Ms, N)$   
**proof** (*rule ccontr*)  
**obtain**  $Ms'\ N'$  **where**  $Ms'N: (Ms', N') = DPLL\text{-}step\ (Ms, N)$   
**by** (*cases DPLL-step (Ms, N)*) *auto*  
**assume**  $\neg\ ?thesis$   
**hence**  $DPLL\text{-}ci\ Ms'\ N = (Ms, N)$  **using** *step inv st Ms'N[symmetric]* **by** *fastforce*  
**hence**  $dpll_W^{++}\ (toS\ Ms\ N)\ (toS\ Ms\ N)$   
**by** (*metis DPLL-ci-dpll<sub>W</sub>-rtranclp DPLL-step-is-a-dpll<sub>W</sub>-step Ms'N (DPLL-step (Ms, N) ≠ (Ms,*  
*N)⟩*  
*prod.sel(2) rtranclp-into-tranclp2 snd-DPLL-step)*  
**thus** *False* **using**  $dpll_W\text{-}all\text{-}inv\text{-}dpll_W\text{-}tranclp\text{-}irrefl\ inv$  **by** *auto*  
**qed**  
**thus** *?thesis* **using**  $DPLL\text{-}step\text{-}stuck\text{-}final\text{-}state[of\ Ms\ N]$  **by** *simp*  
**qed**

**lemma** *DPLL-step-obtains*:

**obtains**  $Ms'$  **where**  $(Ms', N) = DPLL\text{-}step\ (Ms, N)$   
**unfolding**  $DPLL\text{-}step\text{-}def$  **by** (*metis (no-types, lifting) DPLL-step-def prod.collapse snd-DPLL-step*)

**lemma** *DPLL-ci-obtains*:

**obtains**  $Ms'$  **where**  $(Ms', N) = DPLL\text{-}ci\ Ms\ N$

**proof** (*induct rule: DPLL-ci.induct*)

**case** (*1 Ms N*) **note**  $IH = this(1)$  **and**  $that = this(2)$

**obtain**  $S$  **where**  $SN: (S, N) = DPLL\text{-}step\ (Ms, N)$  **using**  $DPLL\text{-}step\text{-}obtains$  **by** *metis*

**{ assume**  $\neg\ dpll_W\text{-}all\text{-}inv\ (toS\ Ms\ N)$

**hence** *?case* **using** *that* **by** *auto*

**}**

**moreover** **{**

**assume**  $n: (S, N) \neq (Ms, N)$

**and** *inv*:  $dpll_W\text{-}all\text{-}inv\ (toS\ Ms\ N)$

**have**  $\exists\ ms. DPLL\text{-}step\ (Ms, N) = (ms, N)$

**by** (*metis (λthesis<sub>a</sub>. (λS. (S, N) = DPLL-step (Ms, N) ⇒ thesis<sub>a</sub>) ⇒ thesis<sub>a</sub>)*)

**hence** *?thesis*

**using** *IH that* **by** *fastforce*

**}**

**moreover** **{**

**assume**  $n: (S, N) = (Ms, N)$

**hence** *?case* **using** *SN that* **by** *fastforce*

**}**

**ultimately show** *?case* **by** *blast*

**qed**

**lemma** *DPLL-ci-no-more-step*:

**assumes** *step*:  $DPLL\text{-}ci\ Ms\ N = (Ms', N')$

**shows**  $DPLL\text{-}ci\ Ms'\ N' = (Ms', N')$

**using** *assms*

**proof** (*induct arbitrary: Ms' N' rule: DPLL-ci.induct*)

**case** (*1 Ms N Ms' N'*) **note**  $IH = this(1)$  **and**  $step = this(2)$

**obtain**  $S_1$  **where**  $S: (S_1, N) = DPLL\text{-}step\ (Ms, N)$  **using**  $DPLL\text{-}step\text{-}obtains$  **by** *auto*



```

{ assume  $\neg dpll_W\text{-all-inv}$  (toS Ms N)
  hence ?case using step by auto
}
moreover {
  assume  $dpll_W\text{-all-inv}$  (toS Ms N)
  and  $(S_1, N) = (Ms, N)$ 
  hence ?case using S step by auto
}
moreover
{ assume  $inv: dpll_W\text{-all-inv}$  (toS Ms N)
  assume  $n: (S_1, N) \neq (Ms, N)$ 
  obtain  $S_1'$  where  $SS: (S_1', N) = DPLL\text{-ci } S_1 N$  using  $DPLL\text{-ci-obtains}$  by blast
  moreover have  $DPLL\text{-ci } Ms N = DPLL\text{-ci } S_1 N$ 
  proof -
    have  $(case (S_1, N) \text{ of } (ms, lss) \Rightarrow \text{if } (ms, lss) = (Ms, N) \text{ then } (Ms, N) \text{ else } DPLL\text{-ci } ms N) = DPLL\text{-ci } Ms N$ 
    using  $S DPLL\text{-ci.simps[of } Ms N]$  calculation inv by presburger
    hence  $(\text{if } (S_1, N) = (Ms, N) \text{ then } (Ms, N) \text{ else } DPLL\text{-ci } S_1 N) = DPLL\text{-ci } Ms N$ 
    by fastforce
    thus ?thesis
    using calculation n by presburger
  qed
  moreover
    have  $DPLL\text{-ci } S_1' N = (S_1', N)$  using step IH[OF - - S n SS[symmetric]] inv by blast
  ultimately have ?case using step by fastforce
}
ultimately show ?case by blast
qed

```

**lemma**  $DPLL\text{-part-}dpll_W\text{-all-inv-final}$ :

```

fixes M Ms': (int, unit, unit) marked-lit list and
  N :: int literal list list
assumes  $inv: dpll_W\text{-all-inv}$  (Ms, mset (map mset N))
and MsN:  $DPLL\text{-part}$  Ms N = (Ms', N)
shows  $conclusive\text{-}dpll_W\text{-state}$  (toS Ms' N)  $\wedge$   $dpll_W^{**}$  (toS Ms N) (toS Ms' N)
proof -
  have 2:  $DPLL\text{-ci } Ms N = DPLL\text{-part } Ms N$  using inv  $dpll_W\text{-all-inv-implieS-2-eq3-and-dom}$  by blast
  hence star:  $dpll_W^{**}$  (toS Ms N) (toS Ms' N) unfolding MsN using  $DPLL\text{-ci-}dpll_W\text{-rtranclp}$  by blast
  hence  $inv'$ :  $dpll_W\text{-all-inv}$  (toS Ms' N) using inv rtranclp- $dpll_W\text{-all-inv}$  by blast
  show ?thesis using star  $DPLL\text{-ci-final-state[OF } DPLL\text{-ci-no-more-step inv']$  2 unfolding MsN by blast
qed

```

## Embedding the invariant into the type

**Defining the type** `typedef  $dpll_W\text{-state}$  =`

```

{(M::(int, unit, unit) marked-lit list, N::int literal list list).
   $dpll_W\text{-all-inv}$  (toS M N)}
```

`morphisms`  $rough\text{-state-of}$   $state\text{-of}$

**proof**

```

show  $([], []) \in \{(M, N). dpll_W\text{-all-inv}$  (toS M N) $\}$  by (auto simp add:  $dpll_W\text{-all-inv-def}$ )
```

qed

**lemma**

*DPLL-part-dom* ( $\square$ ,  $N$ )

**using** *assms* *dpll<sub>W</sub>-all-inv-implicS-2-eq3-and-dom*[*of*  $\square$   $N$ ] **by** (*simp add: dpll<sub>W</sub>-all-inv-def*)

**Some type classes instantiation** *dpll<sub>W</sub>-state* :: *equal*

**begin**

**definition** *equal-dpll<sub>W</sub>-state* :: *dpll<sub>W</sub>-state*  $\Rightarrow$  *dpll<sub>W</sub>-state*  $\Rightarrow$  *bool* **where**

*equal-dpll<sub>W</sub>-state*  $S$   $S'$  = (*rough-state-of*  $S$  = *rough-state-of*  $S'$ )

**instance**

**by** *standard* (*simp add: rough-state-of-inject equal-dpll<sub>W</sub>-state-def*)

**end**

**DPLL definition** *DPLL-step'* :: *dpll<sub>W</sub>-state*  $\Rightarrow$  *dpll<sub>W</sub>-state* **where**

*DPLL-step'*  $S$  = *state-of* (*DPLL-step* (*rough-state-of*  $S$ ))

**declare** *rough-state-of-inverse*[*simp*]

**lemma** *DPLL-step-dpll<sub>W</sub>-conc-inv*:

*DPLL-step* (*rough-state-of*  $S$ )  $\in \{(M, N). \text{dpll}_W\text{-all-inv } (toS\ M\ N)\}$

**by** (*smt DPLL-ci.simps DPLL-ci-dpll<sub>W</sub>-rtrancpl case-prodE case-prodI2 rough-state-of mem-Collect-eq old.prod.case prod.sel(2) rtrancpl-dpll<sub>W</sub>-all-inv snd-DPLL-step*)

**lemma** *rough-state-of-DPLL-step'-DPLL-step*[*simp*]:

*rough-state-of* (*DPLL-step'*  $S$ ) = *DPLL-step* (*rough-state-of*  $S$ )

**using** *DPLL-step-dpll<sub>W</sub>-conc-inv DPLL-step'-def state-of-inverse* **by** *auto*

**function** *DPLL-tot*:: *dpll<sub>W</sub>-state*  $\Rightarrow$  *dpll<sub>W</sub>-state* **where**

*DPLL-tot*  $S$  =

(*let*  $S' = \text{DPLL-step}'\ S$  *in*

*if*  $S' = S$  *then*  $S$  *else* *DPLL-tot*  $S'$ )

**by** *fast+*

**termination**

**proof** (*relation*  $\{(T', T).$

(*rough-state-of*  $T'$ , *rough-state-of*  $T$ )

$\in \{(S', S). (toS'\ S', toS'\ S)$

$\in \{(S', S). \text{dpll}_W\text{-all-inv } S \wedge \text{dpll}_W\ S\ S')\}\}$ )

**show** *wf*  $\{(b, a).$

(*rough-state-of*  $b$ , *rough-state-of*  $a$ )

$\in \{(b, a). (toS'\ b, toS'\ a)$

$\in \{(b, a). \text{dpll}_W\text{-all-inv } a \wedge \text{dpll}_W\ a\ b)\}\}$ )

**using** *wf-if-measure-f*[*OF wf-if-measure-f*[*OF dpll<sub>W</sub>-wf*, *of toS'*], *of rough-state-of*] .

**next**

**fix**  $S\ x$

**assume**  $x: x = \text{DPLL-step}'\ S$

**and**  $x \neq S$

**have** *dpll<sub>W</sub>-all-inv* (*case* *rough-state-of*  $S$  *of* ( $Ms, N$ )  $\Rightarrow$  ( $Ms, \text{mset } (\text{map } \text{mset } N)$ ))

**by** (*metis* (*no-types*, *lifting*) *case-prodE mem-Collect-eq old.prod.case rough-state-of*)

**moreover have** *dpll<sub>W</sub>* (*case* *rough-state-of*  $S$  *of* ( $Ms, N$ )  $\Rightarrow$  ( $Ms, \text{mset } (\text{map } \text{mset } N)$ ))

(*case* *rough-state-of* (*DPLL-step'*  $S$ ) *of* ( $Ms, N$ )  $\Rightarrow$  ( $Ms, \text{mset } (\text{map } \text{mset } N)$ ))

**proof** –

**obtain**  $Ms\ N$  **where**  $Ms: (Ms, N) = \text{rough-state-of } S$  **by** (*cases* *rough-state-of*  $S$ ) *auto*

**have** *dpll<sub>W</sub>-all-inv* (*toS'* ( $Ms, N$ )) **using** *calculation unfolding Ms* **by** *blast*

**moreover obtain**  $Ms'\ N'$  **where**  $Ms': (Ms', N') = \text{rough-state-of } (\text{DPLL-step}'\ S)$

**by** (*cases* *rough-state-of* (*DPLL-step'*  $S$ )) *auto*

**ultimately have** *dpll<sub>W</sub>-all-inv* (*toS'* ( $Ms', N'$ )) **unfolding**  $Ms'$

```

    by (metis (no-types, lifting) case-prod-unfold mem-Collect-eq rough-state-of)

  have dpllW (toS Ms N) (toS Ms' N')
    apply (rule DPLL-step-is-a-dpllW-step[of Ms' N' Ms N])
    unfolding Ms Ms' using ⟨x ≠ S⟩ rough-state-of-inject x by fastforce+
    thus ?thesis unfolding Ms[symmetric] Ms'[symmetric] by auto
  qed
ultimately show (x, S) ∈ {(T', T). (rough-state-of T', rough-state-of T)
  ∈ {(S', S). (toS' S', toS' S) ∈ {(S', S). dpllW-all-inv S ∧ dpllW S S'}}}
  by (auto simp add: x)
qed

lemma [code]:
DPLL-tot S =
  (let S' = DPLL-step' S in
   if S' = S then S else DPLL-tot S') by auto

lemma DPLL-tot-DPLL-step-DPLL-tot[simp]: DPLL-tot (DPLL-step' S) = DPLL-tot S
  apply (cases DPLL-step' S = S)
  apply simp
  unfolding DPLL-tot.simps[of S] by (simp del: DPLL-tot.simps)

lemma DOPLL-step'-DPLL-tot[simp]:
  DPLL-step' (DPLL-tot S) = DPLL-tot S
  by (rule DPLL-tot.induct[of λS. DPLL-step' (DPLL-tot S) = DPLL-tot S S])
  (metis (full-types) DPLL-tot.simps)

lemma DPLL-tot-final-state:
  assumes DPLL-tot S = S
  shows conclusive-dpllW-state (toS' (rough-state-of S))
proof -
  have DPLL-step' S = S using assms[symmetric] DOPLL-step'-DPLL-tot by metis
  hence DPLL-step (rough-state-of S) = (rough-state-of S)
    unfolding DPLL-step'-def using DPLL-step-dpllW-conc-inv rough-state-of-inverse
    by (metis rough-state-of-DPLL-step'-DPLL-step)
  thus ?thesis
    by (metis (mono-tags, lifting) DPLL-step-stuck-final-state old.prod.exhaust split-conv)
qed

lemma DPLL-tot-star:
  assumes rough-state-of (DPLL-tot S) = S'
  shows dpllW** (toS' (rough-state-of S)) (toS' S')
  using assms
proof (induction arbitrary: S' rule: DPLL-tot.induct)
  case (1 S S')
  let ?x = DPLL-step' S
  { assume ?x = S
    then have ?case using 1(2) by simp
  }
  moreover {
    assume S: ?x ≠ S
    have ?case
      apply (cases DPLL-step' S = S)

```

```

    using S apply blast
  by (smt 1.IH 1.prem DPLL-step-is-a-dpllW-step DPLL-tot.simps case-prodE2
      rough-state-of-DPLL-step'-DPLL-step rtranclp.rtrancl-into-rtrancl rtranclp.rtrancl-refl
      rtranclp-idemp split-conv)
}
ultimately show ?case by auto
qed

```

```

lemma rough-state-of-rough-state-of-nil[simp]:
  rough-state-of (state-of ([], N)) = ([], N)
apply (rule DPLL-W-Implementation.dpllW-state.state-of-inverse)
unfolding dpllW-all-inv-def by auto

```

Theorem of correctness

```

lemma DPLL-tot-correct:
  assumes rough-state-of (DPLL-tot (state-of ([], N))) = (M, N')
  and (M', N'') = toS' (M, N')
  shows M' ⊨asm N'' ⟷ satisfiable (set-mset N'')
proof -
  have dpllW** (toS' ([], N)) (toS' (M, N')) using DPLL-tot-star[OF assms(1)] by auto
  moreover have conclusive-dpllW-state (toS' (M, N'))
    using DPLL-tot-final-state by (metis (mono-tags, lifting) DOPLL-step'-DPLL-tot DPLL-tot.simps
        assms(1))
  ultimately show ?thesis using dpllW-conclusive-state-correct by (smt DPLL-ci.simps
      DPLL-ci-dpllW-rtranclp assms(2) dpllW-all-inv-def prod.case prod.sel(1) prod.sel(2)
      rtranclp-dpllW-inv(3) rtranclp-dpllW-inv-starting-from-0)
qed

```

### 20.2.3 Code export

**A conversion to DPLL-W-Implementation.dpll<sub>W</sub>-state** **definition** Con :: (int, unit, unit) marked-lit list × int literal list list

⇒ dpll<sub>W</sub>-state **where**

Con xs = state-of (if dpll<sub>W</sub>-all-inv (toS (fst xs) (snd xs)) then xs else ([], []))

**lemma** [code abstype]:

Con (rough-state-of S) = S

**using** rough-state-of[of S] **unfolding** Con-def **by** auto

**declare** rough-state-of-DPLL-step'-DPLL-step[code abstract]

**lemma** Con-DPLL-step-rough-state-of-state-of[simp]:

Con (DPLL-step (rough-state-of s)) = state-of (DPLL-step (rough-state-of s))

**unfolding** Con-def **by** (metis (mono-tags, lifting) DPLL-step-dpll<sub>W</sub>-conc-inv mem-Collect-eq prod.case-eq-if)

A slightly different version of DPLL-tot where the returned boolean indicates the result.

**definition** DPLL-tot-rep **where**

DPLL-tot-rep S =

(let (M, N) = (rough-state-of (DPLL-tot S)) in (∀ A ∈ set N. (∃ a ∈ set A. a ∈ lits-of-l (M)), M))

One version of the generated SML code is here, but not included in the generated document. The only differences are:

- export 'a literal from the SML Module *Clausal-Logic*;
- export the constructor Con from *DPLL-W-Implementation*;

- export the *int* constructor from *Arith*.

All these allows to test on the code on some examples.

```

end
theory CDCL-W-Implementation
imports DPLL-CDCL-W-Implementation CDCL-W-Termination
begin

notation image-mset (infixr '# 90)

type-synonym 'a cdclW-mark = 'a literal list
type-synonym cdclW-marked-level = nat

type-synonym 'v cdclW-marked-lit = ('v, cdclW-marked-level, 'v cdclW-mark) marked-lit
type-synonym 'v cdclW-marked-lits = ('v, cdclW-marked-level, 'v cdclW-mark) marked-lits
type-synonym 'v cdclW-state =
  'v cdclW-marked-lits × 'v literal list list × 'v literal list list × nat ×
  'v literal list option

abbreviation raw-trail :: 'a × 'b × 'c × 'd × 'e ⇒ 'a where
raw-trail ≡ (λ(M, -). M)

abbreviation raw-cons-trail :: 'a ⇒ 'a list × 'b × 'c × 'd × 'e ⇒ 'a list × 'b × 'c × 'd × 'e
  where
raw-cons-trail ≡ (λL (M, S). (L#M, S))

abbreviation raw-tl-trail :: 'a list × 'b × 'c × 'd × 'e ⇒ 'a list × 'b × 'c × 'd × 'e where
raw-tl-trail ≡ (λ(M, S). (tl M, S))

abbreviation raw-init-clss :: 'a × 'b × 'c × 'd × 'e ⇒ 'b where
raw-init-clss ≡ λ(M, N, -). N

abbreviation raw-learned-clss :: 'a × 'b × 'c × 'd × 'e ⇒ 'c where
raw-learned-clss ≡ λ(M, N, U, -). U

abbreviation raw-backtrack-lvl :: 'a × 'b × 'c × 'd × 'e ⇒ 'd where
raw-backtrack-lvl ≡ λ(M, N, U, k, -). k

abbreviation raw-update-backtrack-lvl :: 'd ⇒ 'a × 'b × 'c × 'd × 'e ⇒ 'a × 'b × 'c × 'd × 'e
  where
raw-update-backtrack-lvl ≡ λk (M, N, U, -, S). (M, N, U, k, S)

abbreviation raw-conflicting :: 'a × 'b × 'c × 'd × 'e ⇒ 'e where
raw-conflicting ≡ λ(M, N, U, k, D). D

abbreviation raw-update-conflicting :: 'e ⇒ 'a × 'b × 'c × 'd × 'e ⇒ 'a × 'b × 'c × 'd × 'e
  where
raw-update-conflicting ≡ λS (M, N, U, k, -). (M, N, U, k, S)

abbreviation raw-add-learned-cls where
raw-add-learned-cls ≡ λC (M, N, U, S). (M, N, {#C#} + U, S)

abbreviation raw-remove-cls where
raw-remove-cls ≡ λC (M, N, U, S). (M, removeAll-mset C N, removeAll-mset C U, S)

```

**type-synonym**  $'v \text{ cdcl}_W\text{-state-inv-st} = ('v, \text{nat}, 'v \text{ literal list}) \text{ marked-lit list} \times 'v \text{ literal list list} \times 'v \text{ literal list list} \times \text{nat} \times 'v \text{ literal list option}$

**abbreviation**  $\text{raw-}S0\text{-cdcl}_W \ N \equiv (([], N, [], 0, \text{None}) :: 'v \text{ cdcl}_W\text{-state-inv-st})$

**fun**  $\text{mmset-of-mlit}' :: ('v, \text{nat}, 'v \text{ literal list}) \text{ marked-lit} \Rightarrow ('v, \text{nat}, 'v \text{ clause}) \text{ marked-lit}$   
**where**

$\text{mmset-of-mlit}' (\text{Propagated } L \ C) = \text{Propagated } L \ (\text{mset } C) \mid$   
 $\text{mmset-of-mlit}' (\text{Marked } L \ i) = \text{Marked } L \ i$

**lemma**  $\text{lit-of-mmset-of-mlit}'[\text{simp}]$ :  
 $\text{lit-of } (\text{mmset-of-mlit}' \ x a) = \text{lit-of } x a$   
**by**  $(\text{induction } x a) \text{ auto}$

**abbreviation**  $\text{trail}$  **where**  
 $\text{trail } S \equiv \text{map } \text{mmset-of-mlit}' \ (\text{raw-trail } S)$

**abbreviation**  $\text{clauses-of-l}$  **where**  
 $\text{clauses-of-l} \equiv \lambda L. \text{mset } (\text{map } \text{mset } L)$

**global-interpretation**  $\text{state}_W\text{-ops}$

$\text{mset} :: 'v \text{ literal list} \Rightarrow 'v \text{ clause}$   
 $\text{op} \# \text{remove1}$

$\text{clauses-of-l } \text{op} \ @ \ \lambda L \ C. L \in \text{set } C \ \text{op} \# \ \lambda C. \text{remove1-cond } (\lambda L. \text{mset } L = \text{mset } C)$

$\text{mset } \lambda x s \ y s. \text{case-prod } \text{append } (\text{fold } (\lambda x \ (y s, z s). (\text{remove1 } x \ y s, x \# z s)) \ x s \ (y s, []))$   
 $\text{op} \# \text{remove1}$

$\text{id } \text{id}$

$\lambda(M, -). \text{map } \text{mmset-of-mlit}' \ M \ \lambda(M, -). \text{hd } M$   
 $\lambda(-, N, -). N$   
 $\lambda(-, -, U, -). U$   
 $\lambda(-, -, -, k, -). k$   
 $\lambda(-, -, -, -, C). C$

$\lambda L \ (M, S). (L \# M, S)$   
 $\lambda(M, S). (\text{tl } M, S)$   
 $\lambda C \ (M, N, S). (M, C \# N, S)$   
 $\lambda C \ (M, N, U, S). (M, N, C \# U, S)$   
 $\lambda C \ (M, N, U, S). (M, \text{filter } (\lambda L. \text{mset } L \neq \text{mset } C) \ N, \text{filter } (\lambda L. \text{mset } L \neq \text{mset } C) \ U, S)$   
 $\lambda(k :: \text{nat}) \ (M, N, U, -, D). (M, N, U, k, D)$   
 $\lambda D \ (M, N, U, k, -). (M, N, U, k, D)$   
 $\lambda N. ([], N, [], 0, \text{None})$   
 $\lambda(-, N, U, -). ([], N, U, 0, \text{None})$   
**apply**  $\text{unfold-locales}$  **by**  $(\text{auto simp: hd-map comp-def map-tl ac-simps union-mset-list mset-map-mset-remove1-cond ex-mset})$

**lemma**  $\text{mmset-of-mlit}'\text{-mmset-of-mlit}$ :  $\text{mmset-of-mlit}' \ l = \text{mmset-of-mlit } l$   
**apply**  $(\text{induct } l)$   
**apply**  $\text{auto}$   
**done**

**lemma**  $\text{clauses-of-l-filter-removeAll}$ :

*clauses-of-l* [ $L \leftarrow a . \text{mset } L \neq \text{mset } C$ ] = *mset* (*removeAll* (*mset* *C*) (*map mset a*))  
**by** (*induct a*) *auto*

**interpretation** *state<sub>w</sub>*

*mset::'v literal list*  $\Rightarrow$  *'v clause*

*op* # *remove1*

*clauses-of-l op* @  $\lambda L C. L \in \text{set } C \text{ op } \# \lambda C. \text{remove1-cond } (\lambda L. \text{mset } L = \text{mset } C)$

*mset*  $\lambda xs \text{ ys. case-prod append (fold } (\lambda x (ys, zs). (\text{remove1 } x \text{ ys}, x \# zs)) \text{ xs (ys, []))$   
*op* # *remove1*

*id id*

$\lambda(M, -). \text{map mmset-of-mlit}' M \lambda(M, -). \text{hd } M$

$\lambda(-, N, -). N$

$\lambda(-, -, U, -). U$

$\lambda(-, -, -, k, -). k$

$\lambda(-, -, -, -, C). C$

$\lambda L (M, S). (L \# M, S)$

$\lambda(M, S). (tl \text{ } M, S)$

$\lambda C (M, N, S). (M, C \# N, S)$

$\lambda C (M, N, U, S). (M, N, C \# U, S)$

$\lambda C (M, N, U, S). (M, \text{filter } (\lambda L. \text{mset } L \neq \text{mset } C) N, \text{filter } (\lambda L. \text{mset } L \neq \text{mset } C) U, S)$

$\lambda(k::nat) (M, N, U, -, D). (M, N, U, k, D)$

$\lambda D (M, N, U, k, -). (M, N, U, k, D)$

$\lambda N. ([], N, [], 0, \text{None})$

$\lambda(-, N, U, -). ([], N, U, 0, \text{None})$

**apply** *unfold-locales*

**apply** (*rename-tac S, case-tac S*)

**by** (*auto simp: hd-map comp-def map-tl ac-simps clauses-of-l-filter-removeAll*  
*mmset-of-mlit'-mmset-of-mlit*)

**global-interpretation** *conflict-driven-clause-learning<sub>w</sub>*

*mset::'v literal list*  $\Rightarrow$  *'v clause*

*op* # *remove1*

*clauses-of-l op* @  $\lambda L C. L \in \text{set } C \text{ op } \# \lambda C. \text{remove1-cond } (\lambda L. \text{mset } L = \text{mset } C)$

*mset*  $\lambda xs \text{ ys. case-prod append (fold } (\lambda x (ys, zs). (\text{remove1 } x \text{ ys}, x \# zs)) \text{ xs (ys, []))$   
*op* # *remove1*

*id id*

$\lambda(M, -). \text{map mmset-of-mlit}' M \lambda(M, -). \text{hd } M$

$\lambda(-, N, -). N$

$\lambda(-, -, U, -). U$

$\lambda(-, -, -, k, -). k$

$\lambda(-, -, -, -, C). C$

$\lambda L (M, S). (L \# M, S)$

$\lambda(M, S). (tl \text{ } M, S)$

$\lambda C (M, N, S). (M, C \# N, S)$

$\lambda C (M, N, U, S). (M, N, C \# U, S)$

$\lambda C (M, N, U, S). (M, \text{filter } (\lambda L. \text{mset } L \neq \text{mset } C) N, \text{filter } (\lambda L. \text{mset } L \neq \text{mset } C) U, S)$   
 $\lambda(k::nat) (M, N, U, -, D). (M, N, U, k, D)$   
 $\lambda D (M, N, U, k, -). (M, N, U, k, D)$   
 $\lambda N. ([], N, [], 0, \text{None})$   
 $\lambda(-, N, U, -). ([], N, U, 0, \text{None})$   
**by** *intro-locales*

**declare** *state-simp*[*simp del*] *raw-clauses-def*[*simp*] *state-eq-def*[*simp*]  
**notation** *state-eq* (**infix**  $\sim$  50)  
**term** *reduce-trail-to*

**lemma** *reduce-trail-to-map*[*simp*]:  
*reduce-trail-to* (map *f* *M1*) = *reduce-trail-to* *M1*  
**by** (*rule ext*) (*auto intro: reduce-trail-to-length*)

## 20.3 CDCL Implementation

### 20.3.1 Definition of the rules

**Types** **lemma** *true-clss-remdups*[*simp*]:  
 $I \models_s (\text{mset} \circ \text{remdups}) 'N \longleftrightarrow I \models_s \text{mset} 'N$   
**by** (*simp add: true-clss-def*)

**lemma** *satisfiable-mset-remdups*[*simp*]:  
*satisfiable* ((*mset*  $\circ$  *remdups*) ' *N*)  $\longleftrightarrow$  *satisfiable* (*mset* ' *N*)  
**unfolding** *satisfiable-carac*[*symmetric*] **by** *simp*

We need some functions to convert between our abstract state *nat cdcl<sub>W</sub>-state* and the concrete state *'v cdcl<sub>W</sub>-state-inv-st*.

**abbreviation** *convertC* :: *'a list option*  $\Rightarrow$  *'a multiset option* **where**  
*convertC*  $\equiv$  *map-option mset*

**lemma** *convert-Propagated*[*elim!*]:  
 $\text{mmset-of-mlit}' z = \text{Propagated } L C \implies (\exists C'. z = \text{Propagated } L C' \wedge C = \text{mset } C')$   
**by** (*cases z*) *auto*

**lemma** *get-rev-level-map-convert*:  
 $\text{get-rev-level} (\text{map } \text{mmset-of-mlit}' M) n x = \text{get-rev-level } M n x$   
**by** (*induction M arbitrary: n rule: marked-lit-list-induct*) *auto*

**lemma** *get-level-map-convert*[*simp*]:  
 $\text{get-level} (\text{map } \text{mmset-of-mlit}' M) = \text{get-level } M$   
**using** *get-rev-level-map-convert*[*of rev M*] **by** (*simp add: rev-map*)

**lemma** *get-rev-level-map-mmsetof-mlit*[*simp*]:  
 $\text{get-rev-level} (\text{map } \text{mmset-of-mlit } M) = \text{get-rev-level } M$   
**by** (*induction M rule: marked-lit-list-induct*) (*auto intro!: ext*)

**lemma** *get-level-map-mmsetof-mlit*[*simp*]:  
 $\text{get-level} (\text{map } \text{mmset-of-mlit } M) = \text{get-level } M$   
**using** *get-rev-level-map-mmsetof-mlit*[*of rev M*] **unfolding** *rev-map* **by** *simp*

**lemma** *get-maximum-level-map-convert*[*simp*]:  
 $\text{get-maximum-level} (\text{map } \text{mmset-of-mlit}' M) D = \text{get-maximum-level } M D$   
**by** (*induction D*) (*auto simp add: get-maximum-level-plus*)



```

lemma get-all-levels-of-marked-map-convert[simp]:
  get-all-levels-of-marked (map mmset-of-mlit' M) = (get-all-levels-of-marked M)
  by (induction M rule: marked-lit-list-induct) auto

lemma reduce-trail-to-empty-trail[simp]:
  reduce-trail-to F ([], aa, ab, ac, b) = ([], aa, ab, ac, b)
  using reduce-trail-to.simps by auto

lemma raw-trail-reduce-trail-to-length-le:
  assumes length F > length (raw-trail S)
  shows raw-trail (reduce-trail-to F S) = []
  using asms trail-reduce-trail-to-length-le[of S F]
  by (cases S, cases reduce-trail-to F S) auto

lemma reduce-trail-to:
  reduce-trail-to F S =
    ((if length (raw-trail S) ≥ length F
      then drop (length (raw-trail S) - length F) (raw-trail S)
      else []), raw-init-clss S, raw-learned-clss S, raw-backtrack-lvl S, raw-conflicting S)
    (is ?S = -)
proof (induction F S rule: reduce-trail-to.induct)
  case (1 F S) note IH = this
  show ?case
  proof (cases raw-trail S)
  case Nil
  then show ?thesis using IH by (cases S) auto
  next
  case (Cons L M)
  then show ?thesis
  apply (cases Suc (length M) > length F)
  prefer 2 using IH reduce-trail-to-length-ne[of S F] apply (cases S) apply auto[]
  apply (subgoal-tac Suc (length M) - length F = Suc (length M - length F))
  using reduce-trail-to-length-ne[of S F] IH by (cases S) (auto simp add:)
  qed
qed

Definition an abstract type

typedef 'v cdclW-state-inv = {S::'v cdclW-state-inv-st. cdclW-all-struct-inv S}
morphisms rough-state-of state-of
proof
  show ([], [], [], 0, None) ∈ {S. cdclW-all-struct-inv S}
  by (auto simp add: cdclW-all-struct-inv-def)
qed

instantiation cdclW-state-inv :: (type) equal
begin
definition equal-cdclW-state-inv :: 'v cdclW-state-inv ⇒ 'v cdclW-state-inv ⇒ bool where
  equal-cdclW-state-inv S S' = (rough-state-of S = rough-state-of S')
instance
  by standard (simp add: rough-state-of-inject equal-cdclW-state-inv-def)
end

lemma lits-of-map-convert[simp]: lits-of-l (map mmset-of-mlit' M) = lits-of-l M
  by (induction M rule: marked-lit-list-induct) simp-all

```

**lemma** *undefined-lit-map-convert*[*iff*]:  
*undefined-lit* (map *mmset-of-mlit'* *M*) *L*  $\longleftrightarrow$  *undefined-lit* *M* *L*  
**by** (auto *simp* add: *defined-lit-map image-image mmset-of-mlit'-mmset-of-mlit*)

**lemma** *true-annot-map-convert*[*simp*]: map *mmset-of-mlit'* *M*  $\models_a N \longleftrightarrow M \models_a N$   
**by** (induction *M* rule: *marked-lit-list-induct*) (*simp-all* add: *true-annot-def mmset-of-mlit'-mmset-of-mlit lits-of-def*)

**lemma** *true-annots-map-convert*[*simp*]: map *mmset-of-mlit'* *M*  $\models_{as} N \longleftrightarrow M \models_{as} N$   
**unfolding** *true-annots-def* **by** auto

**lemmas** *propagateE*

**lemma** *find-first-unit-clause-some-is-propagate*:  
**assumes** *H*: *find-first-unit-clause* (*N* @ *U*) *M* = *Some* (*L*, *C*)  
**shows** *propagate* (*M*, *N*, *U*, *k*, *None*) (*Propagated* *L* *C* # *M*, *N*, *U*, *k*, *None*)  
**using** *assms*  
**by** (auto *dest!*: *find-first-unit-clause-some intro!*: *propagate-rule*)

### 20.3.2 The Transitions

**Propagate** **definition** *do-propagate-step* **where**

*do-propagate-step* *S* =  
(case *S* of  
(*M*, *N*, *U*, *k*, *None*)  $\Rightarrow$   
(case *find-first-unit-clause* (*N* @ *U*) *M* of  
*Some* (*L*, *C*)  $\Rightarrow$  (*Propagated* *L* *C* # *M*, *N*, *U*, *k*, *None*)  
| *None*  $\Rightarrow$  (*M*, *N*, *U*, *k*, *None*))  
| *S*  $\Rightarrow$  *S*)

**lemma** *do-propagate-step*:  
*do-propagate-step* *S*  $\neq S \implies$  *propagate* *S* (*do-propagate-step* *S*)  
**apply** (cases *S*, cases *conflicting* *S*)  
**using** *find-first-unit-clause-some-is-propagate*[of *raw-init-clss* *S* *raw-learned-clss* *S*]  
**by** (auto *simp* add: *do-propagate-step-def split: option.splits*)

**lemma** *do-propagate-step-option*[*simp*]:  
*conflicting* *S*  $\neq \text{None} \implies$  *do-propagate-step* *S* = *S*  
**unfolding** *do-propagate-step-def* **by** (cases *S*, cases *conflicting* *S*) auto  
**thm** *prod-cases*

**lemma** *do-propagate-step-no-step*:  
**assumes** *dist*:  $\forall c \in \text{set } (\text{raw-clauses } S). \text{distinct } c$  **and**  
*prop-step*: *do-propagate-step* *S* = *S*  
**shows** *no-step* *propagate* *S*  
**proof** (*standard*, *standard*)  
**fix** *T*  
**assume** *propagate* *S* *T*  
**then obtain** *C* *L* **where**  
*toSS*: *conflicting* *S* = *None* **and**  
*C*: *C*  $\in \text{set } (\text{raw-clauses } S)$  **and**  
*L*: *L*  $\in \text{set } C$  **and**  
*MC*: *raw-trail* *S*  $\models_{as} C \text{Not } (\text{mset } (\text{remove1 } L \ C))$  **and**  
*T*: *T*  $\sim \text{raw-cons-trail } (\text{Propagated } L \ C) \ S$  **and**  
*undef*: *undefined-lit* (*raw-trail* *S*) *L*  
**apply** (cases *S* rule: *prod-cases5*)  
**by** (*elim* *propagateE*) *simp*

```

let ?M = raw-trail S
let ?N = raw-init-clss S
let ?U = raw-learned-clss S
let ?k = raw-backtrack-lvl S
let ?D = None
have S: S = (?M, ?N, ?U, ?k, ?D)
  using toSS by (cases S, cases conflicting S) simp-all

have find-first-unit-clause (?N @ ?U) ?M ≠ None
  apply (rule dist find-first-unit-clause-none[of C ?N @ ?U ?M L, OF -])
    using C dist apply auto[]
    using C apply auto[1]
    using MC apply auto[1]
    using undef apply auto[1]
    using L by auto
then show False using prop-step S unfolding do-propagate-step-def by (cases S) auto
qed

```

**Conflict** fun *find-conflict* where

```

find-conflict M [] = None |
find-conflict M (N # Ns) = (if (∀ c ∈ set N. ¬c ∈ lits-of-l M) then Some N else find-conflict M Ns)

```

**lemma** *find-conflict-Some*:

```

find-conflict M Ns = Some N ⟹ N ∈ set Ns ∧ M ⊨as CNot (mset N)
by (induction Ns rule: find-conflict.induct)
(auto split: if-split-asm)

```

**lemma** *find-conflict-None*:

```

find-conflict M Ns = None ⟷ (∀ N ∈ set Ns. ¬M ⊨as CNot (mset N))
by (induction Ns) auto

```

**lemma** *find-conflict-None-no-conf*:

```

find-conflict M (N@U) = None ⟷ no-step conflict (M, N, U, k, None)
by (auto simp add: find-conflict-None conflict.simps)

```

**definition** *do-conflict-step* where

```

do-conflict-step S =
(case S of
  (M, N, U, k, None) ⇒
    (case find-conflict M (N @ U) of
      Some a ⇒ (M, N, U, k, Some a)
    | None ⇒ (M, N, U, k, None))
| S ⇒ S)

```

**lemma** *do-conflict-step*:

```

do-conflict-step S ≠ S ⟹ conflict S (do-conflict-step S)
apply (cases S, cases conflicting S)
unfolding conflict.simps do-conflict-step-def
by (auto dest!: find-conflict-Some split: option.splits simp: state-eq-def)

```

**lemma** *do-conflict-step-no-step*:

```

do-conflict-step S = S ⟹ no-step conflict S
apply (cases S, cases conflicting S)
unfolding do-conflict-step-def
using find-conflict-None-no-conf[of raw-trail S raw-init-clss S raw-learned-clss S]

```

```

    raw-backtrack-lvl S]
  by (auto split: option.split elim: conflictE)

lemma do-conflict-step-option[simp]:
  conflicting S ≠ None ⇒ do-conflict-step S = S
  unfolding do-conflict-step-def by (cases S, cases conflicting S) auto

lemma do-conflict-step-conflicting[dest]:
  do-conflict-step S ≠ S ⇒ conflicting (do-conflict-step S) ≠ None
  unfolding do-conflict-step-def by (cases S, cases conflicting S) (auto split: option.splits)

definition do-cp-step where
  do-cp-step S =
    (do-propagate-step o do-conflict-step) S

lemma cp-step-is-cdclW-cp:
  assumes H: do-cp-step S ≠ S
  shows cdclW-cp S (do-cp-step S)
proof -
  show ?thesis
proof (cases do-conflict-step S ≠ S)
  case True
  then have do-propagate-step (do-conflict-step S) = do-conflict-step S
    by auto
  then show ?thesis
    by (auto simp add: do-conflict-step do-conflict-step-conflicting do-cp-step-def True)
next
  case False
  then have confl[simp]: do-conflict-step S = S by simp
  show ?thesis
  proof (cases do-propagate-step S = S)
    case True
    then show ?thesis
      using H by (simp add: do-cp-step-def)
  next
    case False
    let ?S = S
    let ?T = (do-propagate-step S)
    let ?U = (do-conflict-step (do-propagate-step S))
    have propa: propagate S ?T using False do-propagate-step by blast
    moreover have ns: no-step conflict S using confl do-conflict-step-no-step by blast
    ultimately show ?thesis
      using cdclW-cp.intros(2)[of ?S ?T] confl unfolding do-cp-step-def by auto
  qed
qed
qed

lemma do-cp-step-eq-no-prop-no-confl:
  do-cp-step S = S ⇒ do-conflict-step S = S ∧ do-propagate-step S = S
  by (cases S, cases raw-conflicting S)
  (auto simp add: do-conflict-step-def do-propagate-step-def do-cp-step-def split: option.splits)

lemma no-cdclW-cp-iff-no-propagate-no-conflict:
  no-step cdclW-cp S ⇔ no-step propagate S ∧ no-step conflict S
  by (auto simp: cdclW-cp.simps)

```

**lemma** *do-cp-step-eq-no-step*:

**assumes**

*H*: *do-cp-step S = S* **and**

$\forall c \in \text{set } (\text{raw-init-clss } S @ \text{raw-learned-clss } S). \text{ distinct } c$

**shows** *no-step cdcl<sub>W</sub>-cp S*

**unfolding** *no-cdcl<sub>W</sub>-cp-iff-no-propagate-no-conflict*

**using** *assms* **apply** (*cases S, cases conflicting S*)

**using** *do-propagate-step-no-step[of S]*

**by** (*auto dest!: do-cp-step-eq-no-prop-no-confl[simplified] do-conflict-step-no-step split: option.splits*)

**lemma** *cdcl<sub>W</sub>-cp-cdcl<sub>W</sub>-st*: *cdcl<sub>W</sub>-cp S S'  $\implies$  cdcl<sub>W</sub>\*\* S S'*

**by** (*simp add: cdcl<sub>W</sub>-cp-tranclp-cdcl<sub>W</sub> tranclp-into-rtranclp*)

**lemma** *cdcl<sub>W</sub>-all-struct-inv-rough-state[simp]*: *cdcl<sub>W</sub>-all-struct-inv (rough-state-of S)*

**using** *rough-state-of* **by** *auto*

**lemma** [*simp*]: *cdcl<sub>W</sub>-all-struct-inv S  $\implies$  rough-state-of (state-of S) = S*

**by** (*simp add: state-of-inverse*)

**lemma** *rough-state-of-state-of-do-cp-step[simp]*:

*rough-state-of (state-of (do-cp-step (rough-state-of S))) = do-cp-step (rough-state-of S)*

**proof** –

**have** *cdcl<sub>W</sub>-all-struct-inv (do-cp-step (rough-state-of S))*

**apply** (*cases do-cp-step (rough-state-of S) = (rough-state-of S)*)

**apply** *simp*

**using** *cp-step-is-cdcl<sub>W</sub>-cp[of rough-state-of S] cdcl<sub>W</sub>-all-struct-inv-rough-state[of S]*

*cdcl<sub>W</sub>-cp-cdcl<sub>W</sub>-st rtranclp-cdcl<sub>W</sub>-all-struct-inv-inv* **by** *blast*

**then show** *?thesis* **by** *auto*

**qed**

**Skip fun** *do-skip-step* :: '*v cdcl<sub>W</sub>-state-inv-st  $\Rightarrow$  'v cdcl<sub>W</sub>-state-inv-st* **where**

*do-skip-step (Propagated L C # Ls, N, U, k, Some D) =*

*(if  $-L \notin \text{set } D \wedge D \neq []$*

*then (Ls, N, U, k, Some D)*

*else (Propagated L C # Ls, N, U, k, Some D)) |*

*do-skip-step S = S*

**lemma** *do-skip-step*:

*do-skip-step S  $\neq$  S  $\implies$  skip S (do-skip-step S)*

**apply** (*induction S rule: do-skip-step.induct*)

**by** (*auto simp add: skip.simps*)

**lemma** *do-skip-step-no*:

*do-skip-step S = S  $\implies$  no-step skip S*

**by** (*induction S rule: do-skip-step.induct*)

*(auto simp add: other split: if-split-asm elim!: skipE)*

**lemma** *do-skip-step-trail-is-None[iff]*:

*do-skip-step S = (a, b, c, d, None)  $\longleftrightarrow$  S = (a, b, c, d, None)*

**by** (*cases S rule: do-skip-step.cases*) *auto*

**Resolve fun** *maximum-level-code*:: '*a literal list  $\Rightarrow$  ('a, nat, 'a literal list) marked-lit list  $\Rightarrow$  nat*  
**where**

$\text{maximum-level-code } [] = 0 \mid$   
 $\text{maximum-level-code } (L \# Ls) M = \max (\text{get-level } M L) (\text{maximum-level-code } Ls M)$

**lemma** *maximum-level-code-eq-get-maximum-level*[code, simp]:  
 $\text{maximum-level-code } D M = \text{get-maximum-level } M (\text{mset } D)$   
**by** (induction D) (auto simp add: get-maximum-level-plus)

**fun** *do-resolve-step* :: 'v *cdcl<sub>W</sub>-state-inv-st*  $\Rightarrow$  'v *cdcl<sub>W</sub>-state-inv-st* **where**  
*do-resolve-step* (Propagated L C # Ls, N, U, k, Some D) =  
 (if  $-L \in \text{set } D \wedge \text{maximum-level-code } (\text{remove1 } (-L) D) (\text{Propagated } L C \# Ls) = k$   
 then (Ls, N, U, k, Some (remdups (remove1 L C @ remove1 (-L) D)))  
 else (Propagated L C # Ls, N, U, k, Some D)) |  
*do-resolve-step* S = S

**lemma** *do-resolve-step*:  
 $\text{cdcl}_W\text{-all-struct-inv } S \implies \text{do-resolve-step } S \neq S$   
 $\implies \text{resolve } S (\text{do-resolve-step } S)$

**proof** (induction S rule: *do-resolve-step.induct*)

**case** (1 L C M N U k D)

**then have**

LD:  $-L \in \text{set } D$  **and**

M:  $\text{maximum-level-code } (\text{remove1 } (-L) D) (\text{Propagated } L C \# M) = k$

**by** (cases mset D - {#- L#} = {#},

auto dest!: *get-maximum-level-exists-lit-of-max-level*[of - Propagated L C # M]

split: *if-split-asm*) +

**have** *every-mark-is-a-conflict* (Propagated L C # M, N, U, k, Some D)

**using** 1(1) **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* *cdcl<sub>W</sub>-conflicting-def* **by** *fast*

**then have** LC:  $L \in \text{set } C$  **by** *fastforce*

**then obtain** C' **where** C:  $\text{mset } C = C' + \{\#L\# \}$

**by** (*metis* *add.commute in-multiset-in-set insert-DiffM*)

**obtain** D' **where** D:  $\text{mset } D = D' + \{\#-L\# \}$

**using**  $\langle -L \in \text{set } D \rangle$  **by** (*metis* *add.commute in-multiset-in-set insert-DiffM*)

**have** D'L:  $D' + \{\#-L\# \} - \{\#-L\# \} = D'$  **by** (auto simp add: *multiset-eq-iff*)

**have** CL:  $\text{mset } C - \{\#L\# \} + \{\#L\# \} = \text{mset } C$  **using**  $\langle L \in \text{set } C \rangle$  **by** (auto simp add: *multiset-eq-iff*)

**have** max:  $\text{get-maximum-level } (\text{Propagated } L (C' + \{\#L\# \}) \# \text{map mmset-of-mlit } M) D' = k$

**using** M[simplified] **unfolding** *maximum-level-code-eq-get-maximum-level* C[symmetric] CL

**by** (*metis* D D'L *get-maximum-level-map-convert list.simps(9) mmset-of-mlit'.simps(1)*)

**have** *distinct-mset* (mset C) **and** *distinct-mset* (mset D)

**using**  $\langle \text{cdcl}_W\text{-all-struct-inv } (\text{Propagated } L C \# M, N, U, k, \text{Some } D) \rangle$

**unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* *distinct-cdcl<sub>W</sub>-state-def*

**by** *auto*

**then have** *conf*:  $(\text{mset } C - \{\#L\# \}) \# \cup (\text{mset } D - \{\#-L\# \}) =$

$\text{remdups-mset } (\text{mset } C - \{\#L\# \} + (\text{mset } D - \{\#-L\# \}))$

**by** (auto simp: *distinct-mset-remdups-union-mset*)

**show** ?case

**apply** (*rule* *resolve-rule*)

**using** LC LD max M *conf* C D **by** (auto simp: *subset-mset.sup.commute*)

**qed** *auto*

**lemma** *do-resolve-step-no*:

$\text{do-resolve-step } S = S \implies \text{no-step resolve } S$

**apply** (cases S; cases (raw-trail S); cases *raw-conflicting* S)

**by** (auto

elim!: *resolveE* split: *if-split-asm*

*dest!*: union-single-eq-member  
*simp del*: in-multiset-in-set get-maximum-level-map-convert  
*simp*: get-maximum-level-map-convert[symmetric] do-resolve-step

**lemma** *rough-state-of-state-of-resolve*[simp]:  
 $cdcl_W\text{-all-struct-inv } S \implies \text{rough-state-of } (\text{state-of } (\text{do-resolve-step } S)) = \text{do-resolve-step } S$   
**apply** (rule *state-of-inverse*)  
**apply** (cases *do-resolve-step*  $S = S$ )  
**apply** *simp*  
**by** (blast *dest*: other resolve *bj* *do-resolve-step* *cdcl\_W*-all-struct-inv-inv)

**lemma** *do-resolve-step-trail-is-None*[iff]:  
 $\text{do-resolve-step } S = (a, b, c, d, \text{None}) \longleftrightarrow S = (a, b, c, d, \text{None})$   
**by** (cases  $S$  rule: *do-resolve-step.cases*) auto

**Backjumping** fun *find-level-decomp* where

*find-level-decomp*  $M \ [] \ D \ k = \text{None} \mid$   
*find-level-decomp*  $M \ (L \ \# \ Ls) \ D \ k =$   
 (case (*get-level*  $M \ L$ , *maximum-level-code* ( $D \ @ \ Ls$ )  $M$ ) of  
 ( $i, j$ )  $\Rightarrow$  if  $i = k \wedge j < i$  then *Some* ( $L, j$ ) else *find-level-decomp*  $M \ Ls \ (L \ \# \ D) \ k$   
 )

**lemma** *find-level-decomp-some*:  
**assumes** *find-level-decomp*  $M \ Ls \ D \ k = \text{Some } (L, j)$   
**shows**  $L \in \text{set } Ls \wedge \text{get-maximum-level } M \ (\text{mset } (\text{remove1 } L \ (Ls \ @ \ D))) = j \wedge \text{get-level } M \ L = k$   
**using** *assms*

**proof** (induction  $Ls$  arbitrary:  $D$ )

**case** *Nil*  
**then show** ?case **by** *simp*

**next**

**case** (*Cons*  $L' \ Ls$ ) **note**  $IH = \text{this}(1)$  **and**  $H = \text{this}(2)$

**def** *find*  $\equiv$  (if *get-level*  $M \ L' \neq k \vee \neg \text{get-maximum-level } M \ (\text{mset } D + \text{mset } Ls) < \text{get-level } M \ L'$   
 then *find-level-decomp*  $M \ Ls \ (L' \ \# \ D) \ k$   
 else *Some* ( $L', \text{get-maximum-level } M \ (\text{mset } D + \text{mset } Ls)$ )

**have**  $a1: \bigwedge D. \text{find-level-decomp } M \ Ls \ D \ k = \text{Some } (L, j) \implies$   
 $L \in \text{set } Ls \wedge \text{get-maximum-level } M \ (\text{mset } Ls + \text{mset } D - \{\#L\# \}) = j \wedge \text{get-level } M \ L = k$   
**using**  $IH$  **by** *simp*

**have**  $a2: \text{find} = \text{Some } (L, j)$   
**using**  $H$  **unfolding** *find-def* **by** (auto *split*: *if-split-asm*)

**{ assume** *Some* ( $L', \text{get-maximum-level } M \ (\text{mset } D + \text{mset } Ls)$ )  $\neq \text{find}$   
**then have**  $f3: L \in \text{set } Ls$  **and**  $\text{get-maximum-level } M \ (\text{mset } Ls + \text{mset } (L' \ \# \ D) - \{\#L\# \}) = j$   
**using**  $a1 \ IH \ a2$  **unfolding** *find-def* **by** *meson*+

**moreover then have**  $\text{mset } Ls + \text{mset } D - \{\#L\# \} + \{\#L'\# \} = \{\#L'\# \} + \text{mset } D + (\text{mset } Ls - \{\#L\# \})$   
**by** (auto *simp*: *ac-simps* *multiset-eq-iff* *Suc-leI*)

**ultimately have**  $f4: \text{get-maximum-level } M \ (\text{mset } Ls + \text{mset } D - \{\#L\# \} + \{\#L'\# \}) = j$   
**by** (*metis* *add.commute* *diff-union-single-conv* *in-multiset-in-set* *mset.simps*(2))

**} note**  $f4 = \text{this}$

**have**  $\{\#L'\# \} + (\text{mset } Ls + \text{mset } D) = \text{mset } Ls + (\text{mset } D + \{\#L'\# \})$   
**by** (auto *simp*: *ac-simps*)

**then have**

$(L = L' \longrightarrow \text{get-maximum-level } M \ (\text{mset } Ls + \text{mset } D) = j \wedge \text{get-level } M \ L' = k)$  **and**  
 $(L \neq L' \longrightarrow L \in \text{set } Ls \wedge \text{get-maximum-level } M \ (\text{mset } Ls + \text{mset } D - \{\#L\# \} + \{\#L'\# \}) = j \wedge \text{get-level } M \ L = k)$

```

    using f4 a2 a1[of L' # D] unfolding find-def by (metis (no-types) add-diff-cancel-left'
      mset.simps(2) option.inject prod.inject union-commute)+
  then show ?case by simp
qed

lemma find-level-decomp-none:
  assumes find-level-decomp M Ls E k = None and mset (L#D) = mset (Ls @ E)
  shows  $\neg(L \in \text{set } Ls \wedge \text{get-maximum-level } M (\text{mset } D) < k \wedge k = \text{get-level } M L)$ 
  using assms
proof (induction Ls arbitrary: E L D)
  case Nil
  then show ?case by simp
next
  case (Cons L' Ls) note IH = this(1) and find-none = this(2) and LD = this(3)
  have mset D + {#L'#} = mset E + (mset Ls + {#L'#})  $\implies$  mset D = mset E + mset Ls
    by (metis add-right-imp-eq union-assoc)
  then show ?case
    using find-none IH[of L' # E L D] LD by (auto simp add: ac-simps split: if-split-asm)
qed

fun bt-cut where
  bt-cut i (Propagated - - # Ls) = bt-cut i Ls |
  bt-cut i (Marked K k # Ls) = (if k = Suc i then Some (Marked K k # Ls) else bt-cut i Ls) |
  bt-cut i [] = None

lemma bt-cut-some-decomp:
  bt-cut i M = Some M'  $\implies \exists K M2 M1. M = M2 @ M' \wedge M' = \text{Marked } K (i+1) \# M1$ 
  by (induction i M rule: bt-cut.induct) (auto split: if-split-asm)

lemma bt-cut-not-none:  $M = M2 @ \text{Marked } K (\text{Suc } i) \# M' \implies \text{bt-cut } i M \neq \text{None}$ 
  by (induction M2 arbitrary: M rule: marked-lit-list-induct) auto

lemma get-all-marked-decomposition-ex:
   $\exists N. (\text{Marked } K (\text{Suc } i) \# M', N) \in \text{set } (\text{get-all-marked-decomposition } (M2 @ \text{Marked } K (\text{Suc } i) \# M'))$ 
  apply (induction M2 rule: marked-lit-list-induct)
  apply auto[2]
  by (rename-tac L m xs, case-tac get-all-marked-decomposition (xs @ Marked K (Suc i) # M'))
  auto

lemma bt-cut-in-get-all-marked-decomposition:
  bt-cut i M = Some M'  $\implies \exists M2. (M', M2) \in \text{set } (\text{get-all-marked-decomposition } M)$ 
  by (auto dest!: bt-cut-some-decomp simp add: get-all-marked-decomposition-ex)

fun do-backtrack-step where
  do-backtrack-step (M, N, U, k, Some D) =
    (case find-level-decomp M D [] k of
      None  $\Rightarrow$  (M, N, U, k, Some D)
    | Some (L, j)  $\Rightarrow$ 
      (case bt-cut j M of
        Some (Marked - - # Ls)  $\Rightarrow$  (Propagated L D # Ls, N, D # U, j, None)
      | -  $\Rightarrow$  (M, N, U, k, Some D))
    ) |
  do-backtrack-step S = S

```



```

lemma get-all-marked-decomposition-map-convert:
  (get-all-marked-decomposition (map mmset-of-mlit' M)) =
    map ( $\lambda(a, b).$  (map mmset-of-mlit' a, map mmset-of-mlit' b)) (get-all-marked-decomposition M)
apply (induction M rule: marked-lit-list-induct)
apply simp
by (rename-tac L l xs, case-tac get-all-marked-decomposition xs; auto)+

lemma do-backtrack-step:
assumes
  db: do-backtrack-step S  $\neq$  S and
  inv: cdclW-all-struct-inv S
shows backtrack S (do-backtrack-step S)
proof (cases S, cases raw-conflicting S, goal-cases)
  case (1 M N U k E)
  then show ?case using db by auto
next
  case (2 M N U k E C) note S = this(1) and confl = this(2)
  have E: E = Some C using S confl by auto

  obtain L j where fd: find-level-decomp M C [] k = Some (L, j)
  using db unfolding S E by (cases C) (auto split: if-split-asm option.splits)
  have
    L  $\in$  set C and
    j: get-maximum-level M (mset (remove1 L C)) = j and
    levL: get-level M L = k
  using find-level-decomp-some[OF fd] by auto
  obtain C' where C: mset C = mset C' + {#L#}
  using  $\langle L \in \text{set } C \rangle$  by (metis add.commute ex-mset in-multiset-in-set insert-DiffM)
  obtain M2 where M2: bt-cut j M = Some M2
  using db fd unfolding S E by (auto split: option.splits)
  obtain M1 K where M1: M2 = Marked K (Suc j) # M1
  using bt-cut-some-decomp[OF M2] by (cases M2) auto
  obtain c where c: M = c @ Marked K (Suc j) # M1
  using bt-cut-in-get-all-marked-decomposition[OF M2]
  unfolding M1 by fastforce
  have get-all-levels-of-marked (map mmset-of-mlit' M) = rev [1.. $\text{Suc } k$ ]
  using inv unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def S by auto
  from arg-cong[OF this, of  $\lambda a. \text{Suc } j \in \text{set } a$ ] have j  $\leq$  k unfolding c by auto
  have max-l-j: maximum-level-code C' M = j
  using db fd M2 C unfolding S E by (auto
    split: option.splits list.splits marked-lit.splits
    dest!: find-level-decomp-some)[1]
  have get-maximum-level M (mset C)  $\geq$  k
  using  $\langle L \in \text{set } C \rangle$  levL get-maximum-level-ge-get-level by (metis set-mset-mset)
  moreover have get-maximum-level M (mset C)  $\leq$  k
  using get-maximum-level-exists-lit-of-max-level[of mset C M] inv
    cdclW-M-level-inv-get-level-le-backtrack-lvl[of S]
  unfolding C cdclW-all-struct-inv-def S by (auto dest: sym[of get-level - -])
  ultimately have get-maximum-level M (mset C) = k by auto

  obtain M2 where M2: (M2, M2)  $\in$  set (get-all-marked-decomposition M)
  using bt-cut-in-get-all-marked-decomposition[OF M2] by metis
  have decomp:
    (Marked K (Suc (get-maximum-level M (remove1-mset L (mset C)))) # (map mmset-of-mlit' M1),
     (map mmset-of-mlit' M2))  $\in$ 

```

```

    set (get-all-marked-decomposition (map mmset-of-mlit' M))
    using imageI[of - λ(a, b). (map mmset-of-mlit' a, map mmset-of-mlit' b), OF M2] j
    unfolding S E M1 by (auto simp add: get-all-marked-decomposition-map-convert)
have red: (reduce-trail-to (map mmset-of-mlit' M1)
  (M, N, C # U, get-maximum-level M (remove1-mset L (mset C)), None))
  = (M1, N, C # U, get-maximum-level M (remove1-mset L (mset C)), None)
    using M2 M1 by (auto simp: reduce-trail-to)
show ?case
  apply (rule backtrack-rule)
    using M2 fd confl ⟨L ∈ set C⟩ j decomp levL ⟨get-maximum-level M (mset C) = k⟩
    unfolding S E M1 apply (auto simp: mset-map)[6]
    unfolding CDCL-W-Implementation.state-eq-def
    using M2 fd confl ⟨L ∈ set C⟩ j decomp levL ⟨get-maximum-level M (mset C) = k⟩ red
    unfolding S E M1
    by auto
qed

lemma map-eq-list-length:
  map f L = L' ⟹ length L = length L'
  by auto

lemma map-mmset-of-mlit-eq-cons:
  assumes map mmset-of-mlit' M = a @ c
  obtains a' c' where
    M = a' @ c' and
    a = map mmset-of-mlit' a' and
    c = map mmset-of-mlit' c'
  using that[of take (length a) M drop (length a) M]
  assms by (metis append-eq-conv-conj append-take-drop-id drop-map take-map)

lemma do-backtrack-step-no:
  assumes
    db: do-backtrack-step S = S and
    inv: cdclW-all-struct-inv S
  shows no-step backtrack S
proof (rule ccontr, cases S, cases conflicting S, goal-cases)
  case 1
  then show ?case using db by (auto split: option.splits elim: backtrackE)
next
  case (2 M N U k E C) note bt = this(1) and S = this(2) and confl = this(3)
  obtain K j M1 M2 L D where
    CE: raw-conflicting S = Some D and
    LD: L ∈# mset D and
    decomp: (Marked K (Suc j) # M1, M2) ∈ set (get-all-marked-decomposition (trail S)) and
    levL: get-level (raw-trail S) L = raw-backtrack-lvl S and
    k: get-level (raw-trail S) L = get-maximum-level (raw-trail S) (mset D) and
    j: get-maximum-level (raw-trail S) (remove1-mset L (mset D)) ≡ j and
    undef: undefined-lit M1 L
  using bt apply clarsimp
  apply (elim backtrack-levE)
    using inv unfolding cdclW-all-struct-inv-def apply fast
  apply (cases S)
  by (auto simp add: get-all-marked-decomposition-map-convert)

  obtain c where c: trail S = c @ M2 @ Marked K (Suc j) # M1

```

```

    using decomp by blast
have get-all-levels-of-marked (trail S) = rev [1..<Suc k]
    using inv unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def S by auto
from arg-cong[OF this, of  $\lambda a. \text{Suc } j \in \text{set } a$ ] have k > j
    unfolding c by (auto simp: get-all-marked-decomposition-map-convert)
have [simp]: L  $\in$  set D
    using LD by auto
have CD: C = mset D
    using CE confl by auto
obtain D' where
  E: E = Some D and
  DD': mset D = {#L#} + mset D'
    using that[of remove1 L D]
    using S CE confl LD by (auto simp add: insert-DiffM)
have find-level-decomp M D [] k  $\neq$  None
    apply rule
    apply (drule find-level-decomp-none[of - - - L D'])
    using DD'  $\langle k > j \rangle$  mset-eq-setD S levL unfolding k[symmetric] j[symmetric]
    by (auto simp: ac-simps)
then obtain L' j' where fd-some: find-level-decomp M D [] k = Some (L', j')
    by (cases find-level-decomp M D [] k) auto
have L': L' = L
    proof (rule ccontr)
      assume  $\neg$  ?thesis
      then have L'  $\in$  # mset (remove1 L D)
        by (metis fd-some find-level-decomp-some in-set-remove1 set-mset-mset)
      then have get-level M L'  $\leq$  get-maximum-level M (mset (remove1 L D))
        using get-maximum-level-ge-get-level by blast
      then show False using  $\langle k > j \rangle j$  find-level-decomp-some[OF fd-some] S DD' by auto
    qed
then have j': j' = j using find-level-decomp-some[OF fd-some] j S DD' by auto

obtain c' M1' where cM: M = c' @ Marked K (Suc j) # M1'
    apply (rule map-mmset-of-mlit-eq-cons[of M c @ M2 Marked K (Suc j) # M1])
    using c S apply simp
    apply (rule map-mmset-of-mlit-eq-cons[of - [Marked K (Suc j)] M1])
    apply auto[]
    apply (rename-tac a b' aa b, case-tac aa)
    apply auto[]
    apply (rename-tac a b' aa b, case-tac aa)
    by auto
have btc-none: bt-cut j M  $\neq$  None
    apply (rule bt-cut-not-none[of M ])
    using cM by simp
show ?case using db unfolding S E
    by (auto split: option.splits list.splits marked-lit.splits
      simp add: fd-some L' j' btc-none
      dest: bt-cut-some-decomp)
qed

lemma rough-state-of-state-of-backtrack[simp]:
  assumes inv: cdclW-all-struct-inv S
  shows rough-state-of (state-of (do-backtrack-step S)) = do-backtrack-step S
proof (rule state-of-inverse)
  have f2: backtrack S (do-backtrack-step S)  $\vee$  do-backtrack-step S = S

```

```

    using do-backtrack-step inv by blast
have  $\bigwedge p. \neg \text{cdcl}_W\text{-o } S \ p \vee \text{cdcl}_W\text{-all-struct-inv } p$ 
    using inv cdclW-all-struct-inv-inv other by blast
then have do-backtrack-step  $S = S \vee \text{cdcl}_W\text{-all-struct-inv } (\text{do-backtrack-step } S)$ 
    using f2 inv cdclW-o.intros cdclW-bj.intros by blast
then show do-backtrack-step  $S \in \{S. \text{cdcl}_W\text{-all-struct-inv } S\}$ 
    using inv by fastforce
qed

```

**Decide** fun do-decide-step where

```

do-decide-step (M, N, U, k, None) =
  (case find-first-unused-var N (lits-of-l M) of
    None  $\Rightarrow$  (M, N, U, k, None)
  | Some L  $\Rightarrow$  (Marked L (Suc k) # M, N, U, k+1, None)) |
do-decide-step S = S

```

**lemma** do-decide-step:

```

fixes S :: 'v cdclW-state-inv-st
assumes do-decide-step S  $\neq$  S
shows decide S (do-decide-step S)
using assms
apply (cases S, cases conflicting S)
defer
apply (auto split: option.splits simp add: decide.simps Marked-Propagated-in-iff-in-lits-of-l
  dest: find-first-unused-var-undefined find-first-unused-var-Some
  intro:)[1]

```

**proof** –

```

fix a :: ('v, nat, 'v literal list) marked-lit list and
  b :: 'v literal list list and c :: 'v literal list list and
  d :: nat and e :: 'v literal list option
{
  fix a :: ('v, nat, 'v literal list) marked-lit list and
    b :: 'v literal list list and c :: 'v literal list list and
    d :: nat and x2 :: 'v literal and m :: 'v literal list
  assume a1:  $m \in \text{set } b$ 
  assume x2  $\in \text{set } m$ 
  then have f2:  $\text{atm-of } x2 \in \text{atms-of } (\text{mset } m)$ 
    by simp
  have  $\bigwedge f. (f \ m :: 'v \text{ clause}) \in f \text{ ' set } b$ 
    using a1 by blast
  then have  $\bigwedge f. (\text{atms-of } (f \ m) :: 'v \text{ set}) \subseteq \text{atms-of-ms } (f \text{ ' set } b)$ 
    by simp
  then have  $\bigwedge n \ f. (n :: 'v) \in \text{atms-of-ms } (f \text{ ' set } b) \vee n \notin \text{atms-of } (f \ m)$ 
    by (meson contra-subsetD)
  then have  $\text{atm-of } x2 \in \text{atms-of-ms } (\text{mset ' set } b)$ 
    using f2 by blast
} note H = this
{
  fix m :: 'v literal list and x2
  have  $m \in \text{set } b \implies x2 \in \text{set } m \implies x2 \notin \text{lits-of-l } a \implies \neg x2 \notin \text{lits-of-l } a \implies$ 
     $\exists aa \in \text{set } b. \neg \text{atm-of ' set } aa \subseteq \text{atm-of ' lits-of-l } a$ 
    by (meson atm-of-in-atm-of-set-in-uminus contra-subsetD rev-image-eqI)
} note H' = this

```

assume do-decide-step  $S \neq S$  and

```

    S = (a, b, c, d, e) and
    conflicting S = None
  then show decide S (do-decide-step S)
  using H H' by (auto split: option.splits simp: lits-of-def decide.simps
    Marked-Propagated-in-iff-in-lits-of-l
    dest!: find-first-unused-var-Some)
qed

lemma mmset-of-mlit'-eq-Marked[iff]: mmset-of-mlit' z = Marked x k  $\longleftrightarrow$  z = Marked x k
  by (cases z) auto

lemma do-decide-step-no:
  do-decide-step S = S  $\implies$  no-step decide S
  apply (cases S, cases conflicting S)

  apply (auto simp: atms-of-ms-mset-unfold Marked-Propagated-in-iff-in-lits-of-l lits-of-def
    dest!: atm-of-in-atm-of-set-in-uminus
    elim!: decideE
    split: option.splits)+
  using atm-of-eq-atm-of by blast

lemma rough-state-of-state-of-do-decide-step[simp]:
  cdclW-all-struct-inv S  $\implies$  rough-state-of (state-of (do-decide-step S)) = do-decide-step S
proof (subst state-of-inverse, goal-cases)
  case 1
  then show ?case
  by (cases do-decide-step S = S)
    (auto dest: do-decide-step decide other intro: cdclW-all-struct-inv-inv)
qed simp

lemma rough-state-of-state-of-do-skip-step[simp]:
  cdclW-all-struct-inv S  $\implies$  rough-state-of (state-of (do-skip-step S)) = do-skip-step S
  apply (subst state-of-inverse, cases do-skip-step S = S)
  apply simp
  by (blast dest: other skip bj do-skip-step cdclW-all-struct-inv-inv)+

```

### 20.3.3 Code generation

**Type definition** There are two invariants: one while applying conflict and propagate and one for the other rules

```

declare rough-state-of-inverse[simp add]
definition Con where
  Con xs = state-of (if cdclW-all-struct-inv xs then xs else ([], [], [], 0, None))

```

```

lemma [code abstype]:
  Con (rough-state-of S) = S
  using rough-state-of[of S] unfolding Con-def by simp

```

```

definition do-cp-step' where
  do-cp-step' S = state-of (do-cp-step (rough-state-of S))

```

```

typedef 'v cdclW-state-inv-from-init-state = {S::'v cdclW-state-inv-st. cdclW-all-struct-inv S
   $\wedge$  cdclW-stgy** (raw-S0-cdclW (raw-init-clss S)) S}
morphisms rough-state-from-init-state-of state-from-init-state-of
proof

```

**show** ( $\square, \square, \square, 0, None$ )  $\in \{S. \text{cdcl}_W\text{-all-struct-inv } S$   
 $\wedge \text{cdcl}_W\text{-stgy}^{**} (\text{raw-}S0\text{-cdcl}_W (\text{raw-init-clss } S)) S\}$   
**by** (*auto simp add: cdcl<sub>W</sub>-all-struct-inv-def*)  
**qed**

**instantiation**  $\text{cdcl}_W\text{-state-inv-from-init-state} :: (\text{type}) \text{ equal}$   
**begin**

**definition**  $\text{equal-cdcl}_W\text{-state-inv-from-init-state} :: 'v \text{ cdcl}_W\text{-state-inv-from-init-state} \Rightarrow$   
 $'v \text{ cdcl}_W\text{-state-inv-from-init-state} \Rightarrow \text{bool}$  **where**  
 $\text{equal-cdcl}_W\text{-state-inv-from-init-state } S S' \longleftrightarrow$   
 $(\text{rough-state-from-init-state-of } S = \text{rough-state-from-init-state-of } S')$

**instance**

**by** *standard (simp add: rough-state-from-init-state-of-inject*  
 $\text{equal-cdcl}_W\text{-state-inv-from-init-state-def})$   
**end**

**definition**  $\text{ConI}$  **where**

$\text{ConI } S = \text{state-from-init-state-of (if } \text{cdcl}_W\text{-all-struct-inv } S$   
 $\wedge \text{cdcl}_W\text{-stgy}^{**} (\text{raw-}S0\text{-cdcl}_W (\text{raw-init-clss } S)) S \text{ then } S \text{ else } (\square, \square, \square, 0, None))$

**lemma** [*code abstype*]:

$\text{ConI } (\text{rough-state-from-init-state-of } S) = S$   
**using**  $\text{rough-state-from-init-state-of[of } S]$  **unfolding**  $\text{ConI-def}$   
**by** (*simp add: rough-state-from-init-state-of-inverse*)

**definition**  $\text{id-of-I-to} :: 'v \text{ cdcl}_W\text{-state-inv-from-init-state} \Rightarrow 'v \text{ cdcl}_W\text{-state-inv}$  **where**  
 $\text{id-of-I-to } S = \text{state-of } (\text{rough-state-from-init-state-of } S)$

**lemma** [*code abstract*]:

$\text{rough-state-of } (\text{id-of-I-to } S) = \text{rough-state-from-init-state-of } S$   
**unfolding**  $\text{id-of-I-to-def}$  **using**  $\text{rough-state-from-init-state-of[of } S]$  **by** *auto*

**Conflict and Propagate function**  $\text{do-full1-cp-step} :: 'v \text{ cdcl}_W\text{-state-inv} \Rightarrow 'v \text{ cdcl}_W\text{-state-inv}$   
**where**

$\text{do-full1-cp-step } S =$   
 $(\text{let } S' = \text{do-cp-step}' S \text{ in}$   
 $\text{if } S = S' \text{ then } S \text{ else } \text{do-full1-cp-step } S')$

**by** *auto*

**termination**

**proof** ( $\text{relation } \{(T', T). (\text{rough-state-of } T', \text{rough-state-of } T) \in \{(S', S).$   
 $(S', S) \in \{(S', S). \text{cdcl}_W\text{-all-struct-inv } S \wedge \text{cdcl}_W\text{-cp } S S'\}\}, \text{goal-cases})$

**case** 1

**show** *?case*

**using**  $\text{wf-if-measure-f[OF wf-if-measure-f[OF cdcl}_W\text{-cp-wf-all-inv, of } ], \text{ of rough-state-of}]$  .

**next**

**case** (2  $S' S$ )

**then show** *?case*

**unfolding**  $\text{do-cp-step}'\text{-def}$

**apply** *simp*

**by** (*metis cp-step-is-cdcl<sub>W</sub>-cp rough-state-of-inverse*)

**qed**

**lemma**  $\text{do-full1-cp-step-fix-point-of-do-full1-cp-step}$ :

$\text{do-cp-step}(\text{rough-state-of } (\text{do-full1-cp-step } S)) = \text{rough-state-of } (\text{do-full1-cp-step } S)$   
**by** (*rule do-full1-cp-step.induct[of  $\lambda S. \text{do-cp-step}(\text{rough-state-of } (\text{do-full1-cp-step } S))$* )

= rough-state-of (do-full1-cp-step S))  
 (metis (full-types) do-full1-cp-step.elims rough-state-of-state-of-do-cp-step do-cp-step'-def)

**lemma** in-clauses-rough-state-of-is-distinct:

$c \in \text{set } (\text{raw-init-clss } (\text{rough-state-of } S) \text{ @ raw-learned-clss } (\text{rough-state-of } S)) \implies \text{distinct } c$   
**apply** (cases rough-state-of S)  
**using** rough-state-of[of S] **by** (auto simp add: distinct-mset-set-distinct cdcl<sub>W</sub>-all-struct-inv-def  
 distinct-cdcl<sub>W</sub>-state-def)

**lemma** do-full1-cp-step-full:

full cdcl<sub>W</sub>-cp (rough-state-of S)  
 (rough-state-of (do-full1-cp-step S))  
**unfolding** full-def

**proof** (rule conjI, induction S rule: do-full1-cp-step.induct)

**case** (1 S)

**then have** f1:

cdcl<sub>W</sub>-cp\*\* ((do-cp-step (rough-state-of S))) (  
 (rough-state-of (do-full1-cp-step (state-of (do-cp-step (rough-state-of S))))))  
 $\vee$  state-of (do-cp-step (rough-state-of S)) = S

**using** rough-state-of-state-of-do-cp-step[of S] **unfolding** do-cp-step'-def **by** fastforce

**have** f2:  $\bigwedge c. (\text{if } c = \text{state-of } (\text{do-cp-step } (\text{rough-state-of } c))$   
 then  $c$  else  $\text{do-full1-cp-step } (\text{state-of } (\text{do-cp-step } (\text{rough-state-of } c))))$   
 = do-full1-cp-step c

**by** (metis (full-types) do-cp-step'-def do-full1-cp-step.simps)

**have** f3:  $\neg \text{cdcl}_W\text{-cp } (\text{rough-state-of } S) (\text{do-cp-step } (\text{rough-state-of } S))$

$\vee$  state-of (do-cp-step (rough-state-of S)) = S

$\vee \text{cdcl}_W\text{-cp}^{++} (\text{rough-state-of } S)$

(rough-state-of (do-full1-cp-step (state-of (do-cp-step (rough-state-of S)))))

**using** f1 **by** (meson rtranclp-into-tranclp2)

{ **assume** do-full1-cp-step S  $\neq$  S

**then have** do-cp-step (rough-state-of S) = rough-state-of S

$\longrightarrow \text{cdcl}_W\text{-cp}^{**} (\text{rough-state-of } S) (\text{rough-state-of } (\text{do-full1-cp-step } S))$

$\vee$  do-cp-step (rough-state-of S)  $\neq$  rough-state-of S

$\wedge$  state-of (do-cp-step (rough-state-of S))  $\neq$  S

**using** f2 f1 **by** (metis (no-types))

**then have** do-cp-step (rough-state-of S)  $\neq$  rough-state-of S

$\wedge$  state-of (do-cp-step (rough-state-of S))  $\neq$  S

$\vee \text{cdcl}_W\text{-cp}^{**} (\text{rough-state-of } S) (\text{rough-state-of } (\text{do-full1-cp-step } S))$

**by** (metis rough-state-of-state-of-do-cp-step)

**then have** cdcl<sub>W</sub>-cp\*\* (rough-state-of S) (rough-state-of (do-full1-cp-step S))

**using** f3 f2 **by** (metis (no-types) cp-step-is-cdcl<sub>W</sub>-cp tranclp-into-rtranclp) }

**then show** ?case

**by** fastforce

**next**

**show** no-step cdcl<sub>W</sub>-cp (rough-state-of (do-full1-cp-step S))

**apply** (rule do-cp-step-eq-no-step[OF do-full1-cp-step-fix-point-of-do-full1-cp-step[of S]])

**using** in-clauses-rough-state-of-is-distinct **unfolding** do-cp-step'-def **by** blast

**qed**

**lemma** [code abstract]:

rough-state-of (do-cp-step' S) = do-cp-step (rough-state-of S)

**unfolding** do-cp-step'-def **by** auto

**The other rules** **fun** do-other-step **where**

do-other-step S =

```

(let  $T = \text{do-skip-step } S$  in
  if  $T \neq S$ 
  then  $T$ 
  else
    (let  $U = \text{do-resolve-step } T$  in
      if  $U \neq T$ 
      then  $U$  else
        (let  $V = \text{do-backtrack-step } U$  in
          if  $V \neq U$  then  $V$  else  $\text{do-decide-step } V$ )))

```

**lemma** *do-other-step*:  
**assumes** *inv*:  $\text{cdcl}_W\text{-all-struct-inv } S$  **and**  
*st*:  $\text{do-other-step } S \neq S$   
**shows**  $\text{cdcl}_W\text{-o } S$  ( $\text{do-other-step } S$ )  
**using** *st inv* **by** (*auto split: if-split-asm*  
*simp add: Let-def*  
*intro: do-skip-step do-resolve-step do-backtrack-step do-decide-step*  
 $\text{cdcl}_W\text{-o.intros cdcl}_W\text{-bj.intros}$ )

**lemma** *do-other-step-no*:  
**assumes** *inv*:  $\text{cdcl}_W\text{-all-struct-inv } S$  **and**  
*st*:  $\text{do-other-step } S = S$   
**shows**  $\text{no-step cdcl}_W\text{-o } S$   
**using** *st inv* **by** (*auto split: if-split-asm elim: cdcl}\_W\text{-bjE}*  
*simp add: Let-def cdcl}\_W\text{-bj.simps elim!: cdcl}\_W\text{-o.cases}*  
*dest!: do-skip-step-no do-resolve-step-no do-backtrack-step-no do-decide-step-no*)

**lemma** *rough-state-of-state-of-do-other-step[simp]*:  
 $\text{rough-state-of } (\text{state-of } (\text{do-other-step } (\text{rough-state-of } S))) = \text{do-other-step } (\text{rough-state-of } S)$   
**proof** (*cases do-other-step (rough-state-of } S) = \text{rough-state-of } S*)  
*case True*  
**then show** *?thesis* **by** *simp*  
**next**  
*case False*  
**have**  $\text{cdcl}_W\text{-o } (\text{rough-state-of } S)$  ( $\text{do-other-step } (\text{rough-state-of } S)$ )  
**by** (*metis False cdcl}\_W\text{-all-struct-inv-rough-state do-other-step[of rough-state-of } S]*)  
**then have**  $\text{cdcl}_W\text{-all-struct-inv } (\text{do-other-step } (\text{rough-state-of } S))$   
**using**  $\text{cdcl}_W\text{-all-struct-inv-inv cdcl}_W\text{-all-struct-inv-rough-state other}$  **by** *blast*  
**then show** *?thesis*  
**by** (*simp add: CollectI state-of-inverse*)  
**qed**

**definition** *do-other-step'* **where**  
 $\text{do-other-step}' S =$   
 $\text{state-of } (\text{do-other-step } (\text{rough-state-of } S))$

**lemma** *rough-state-of-do-other-step'[code abstract]*:  
 $\text{rough-state-of } (\text{do-other-step}' S) = \text{do-other-step } (\text{rough-state-of } S)$   
**apply** (*cases do-other-step (rough-state-of } S) = \text{rough-state-of } S*)  
**unfolding** *do-other-step'-def* **apply** *simp*  
**using**  $\text{do-other-step[of rough-state-of } S]$  **by** (*auto intro: cdcl}\_W\text{-all-struct-inv-inv}*  
 $\text{cdcl}_W\text{-all-struct-inv-rough-state other state-of-inverse}$ )

**definition** *do-cdcl}\_W\text{-stgy-step}* **where**  
 $\text{do-cdcl}_W\text{-stgy-step } S =$



```

(let T = do-full1-cp-step S in
  if T ≠ S
  then T
  else
    (let U = (do-other-step' T) in
      (do-full1-cp-step U)))

```

**definition** *do-cdcl<sub>W</sub>-stgy-step'* **where**

*do-cdcl<sub>W</sub>-stgy-step'* S = state-from-init-state-of (rough-state-of (do-cdcl<sub>W</sub>-stgy-step (id-of-I-to S)))

**lemma** *toS-do-full1-cp-step-not-eq*: *do-full1-cp-step S ≠ S* ⇒  
 rough-state-of S ≠ rough-state-of (do-full1-cp-step S)

**proof** –

**assume** *a1*: *do-full1-cp-step S ≠ S*

**then have** *S ≠ do-cp-step' S*

**by** *fastforce*

**then show** *?thesis*

**by** (*metis* (*no-types*) *do-cp-step'-def* *do-full1-cp-step-fix-point-of-do-full1-cp-step*  
*rough-state-of-inverse*)

**qed**

*do-full1-cp-step* should not be unfolded anymore:

**declare** *do-full1-cp-step.simps*[*simp del*]

**Correction of the transformation** **lemma** *do-cdcl<sub>W</sub>-stgy-step*:

**assumes** *do-cdcl<sub>W</sub>-stgy-step S ≠ S*

**shows** *cdcl<sub>W</sub>-stgy (rough-state-of S) (rough-state-of (do-cdcl<sub>W</sub>-stgy-step S))*

**proof** (*cases do-full1-cp-step S = S*)

**case** *False*

**then show** *?thesis*

**using** *assms do-full1-cp-step-full*[*of S*] **unfolding** *full-unfold do-cdcl<sub>W</sub>-stgy-step-def*

**by** (*auto intro!*: *cdcl<sub>W</sub>-stgy.intros dest: toS-do-full1-cp-step-not-eq*)

**next**

**case** *True*

**have** *cdcl<sub>W</sub>-o (rough-state-of S) (rough-state-of (do-other-step' S))*

**by** (*smt True assms cdcl<sub>W</sub>-all-struct-inv-rough-state do-cdcl<sub>W</sub>-stgy-step-def do-other-step*  
*rough-state-of-do-other-step' rough-state-of-inverse*)

**moreover**

**have**

*np*: *no-step propagate (rough-state-of S)* **and**

*nc*: *no-step conflict (rough-state-of S)*

**apply** (*metis True cdcl<sub>W</sub>-cp.simps do-cp-step-eq-no-step*

*do-full1-cp-step-fix-point-of-do-full1-cp-step in-clauses-rough-state-of-is-distinct*)

**by** (*metis True do-conflict-step-no-step do-cp-step-eq-no-prop-no-confl*

*do-full1-cp-step-fix-point-of-do-full1-cp-step*)

**then have** *no-step cdcl<sub>W</sub>-cp (rough-state-of S)*

**by** (*simp add: cdcl<sub>W</sub>-cp.simps*)

**moreover have** *full cdcl<sub>W</sub>-cp (rough-state-of (do-other-step' S))*

*(rough-state-of (do-full1-cp-step (do-other-step' S)))*

**using** *do-full1-cp-step-full* **by** *auto*

**ultimately show** *?thesis*

**using** *assms True unfolding do-cdcl<sub>W</sub>-stgy-step-def*

**by** (*auto intro!*: *cdcl<sub>W</sub>-stgy.other' dest: toS-do-full1-cp-step-not-eq*)

**qed**

```

lemma do-skip-step-trail-changed-or-conflict:
  assumes d: do-other-step S  $\neq$  S
  and inv: cdclW-all-struct-inv S
  shows trail S  $\neq$  trail (do-other-step S)
proof –
  have M:  $\bigwedge M K M1 c. M = c @ K \# M1 \implies \text{Suc } (\text{length } M1) \leq \text{length } M$ 
    by auto
  have cdclW-M-level-inv S
    using inv unfolding cdclW-all-struct-inv-def by auto
  have cdclW-o S (do-other-step S) using do-other-step[OF inv d] .
  then show ?thesis
    using  $\langle \text{cdcl}_W\text{-M-level-inv } S \rangle$ 
  proof (induction do-other-step S rule: cdclW-o-induct-lev2)
    case decide
    then show ?thesis
      apply (cases S)
      apply (auto dest!: find-first-unused-var-Some
        simp: split: option.splits)
      by (meson atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set contra-subsetD)
    next
    case (skip)
    then show ?case
      by (cases S; cases do-other-step S) force
    next
    case (resolve)
    then show ?case
      by (cases S, cases do-other-step S) force
    next
    case (backtrack K i M1 M2 L D) note decomp = this(1) and confl-S = this(3) and undef =
this(6)
      and U = this(7)
    then show ?case
      apply (cases do-other-step S)
      apply (auto split: if-split-asm simp: Let-def)
      apply (cases S rule: do-skip-step.cases; auto split: if-split-asm)
      apply (cases S rule: do-skip-step.cases; auto split: if-split-asm)

      apply (cases S rule: do-backtrack-step.cases;
        auto split: if-split-asm option.splits list.splits marked-lit.splits
        dest!: bt-cut-some-decomp simp: Let-def)
      using d apply (cases S rule: do-decide-step.cases; auto split: option.splits)[]
    done
  qed
qed

```

```

lemma do-full1-cp-step-induct:
   $(\bigwedge S. (S \neq \text{do-cp-step}' S \implies P (\text{do-cp-step}' S)) \implies P S) \implies P a0$ 
  using do-full1-cp-step.induct by metis

```

```

lemma do-cp-step-neq-trail-increase:
   $\exists c. \text{raw-trail } (\text{do-cp-step } S) = c @ \text{raw-trail } S \wedge (\forall m \in \text{set } c. \neg \text{is-marked } m)$ 
  by (cases S, cases raw-conflicting S)
    (auto simp add: do-cp-step-def do-conflict-step-def do-propagate-step-def split: option.splits)

```

```

lemma do-full1-cp-step-neq-trail-increase:

```

$\exists c. \text{raw-trail } (\text{rough-state-of } (\text{do-full1-cp-step } S)) = c @ \text{raw-trail } (\text{rough-state-of } S)$   
 $\wedge (\forall m \in \text{set } c. \neg \text{is-marked } m)$   
**apply** (induction rule: *do-full1-cp-step-induct*)  
**apply** (rename-tac *S*, case-tac *do-cp-step' S = S*)  
**apply** (simp add: *do-full1-cp-step.simps*)  
**by** (smt *Un-iff append-assoc do-cp-step'-def do-cp-step-neq-trail-increase do-full1-cp-step.simps*  
*rough-state-of-state-of-do-cp-step set-append*)

**lemma** *do-cp-step-conflicting*:

*conflicting (rough-state-of S) ≠ None*  $\implies$  *do-cp-step' S = S*  
**unfolding** *do-cp-step'-def do-cp-step-def* **by** *simp*

**lemma** *do-full1-cp-step-conflicting*:

*conflicting (rough-state-of S) ≠ None*  $\implies$  *do-full1-cp-step S = S*  
**unfolding** *do-cp-step'-def do-cp-step-def*  
**apply** (induction rule: *do-full1-cp-step-induct*)  
**by** (rename-tac *S*, case-tac *S ≠ do-cp-step' S*)  
*(auto simp add: do-full1-cp-step.simps do-cp-step-conflicting)*

**lemma** *do-decide-step-not-conflicting-one-more-decide*:

**assumes**  
*conflicting S = None* **and**  
*do-decide-step S ≠ S*  
**shows** *Suc (length (filter is-marked (raw-trail S)))*  
 $=$  *length (filter is-marked (raw-trail (do-decide-step S)))*  
**using** *assms unfolding do-other-step'-def*  
**by** (cases *S*) (force simp: *Let-def split: if-split-asm option.splits*  
*dest!: find-first-unused-var-Some-not-all-incl*)

**lemma** *do-decide-step-not-conflicting-one-more-decide-bt*:

**assumes** *conflicting S ≠ None* **and**  
*do-decide-step S ≠ S*  
**shows** *length (filter is-marked (raw-trail S)) <*  
*length (filter is-marked (raw-trail (do-decide-step S)))*  
**using** *assms unfolding do-other-step'-def* **by** (cases *S*, cases *conflicting S*)  
*(auto simp add: Let-def split: if-split-asm option.splits)*

**lemma** *do-other-step-not-conflicting-one-more-decide-bt*:

**assumes**  
*conflicting (rough-state-of S) ≠ None* **and**  
*conflicting (rough-state-of (do-other-step' S)) = None* **and**  
*do-other-step' S ≠ S*  
**shows** *length (filter is-marked (raw-trail (rough-state-of S)))*  
 $>$  *length (filter is-marked (raw-trail (rough-state-of (do-other-step' S))))*

**proof** (cases *S*, goal-cases)

**case** (1 *y*) **note** *S = this(1)* **and** *inv = this(2)*  
**obtain** *M N U k E* **where** *y: y = (M, N, U, k, Some E)*  
**using** *assms(1) S inv* **by** (cases *y*, cases *conflicting y*) *auto*  
**have** *M: rough-state-of (state-of (M, N, U, k, Some E)) = (M, N, U, k, Some E)*  
**using** *inv y* **by** (auto simp add: *state-of-inverse*)  
**have** *bt: do-other-step' S = state-of (do-backtrack-step (rough-state-of S))*  
**proof** (cases *rough-state-of S* rule: *do-decide-step.cases*)  
**case** 1  
**then show** *?thesis*  
**using** *assms(1,2)* **by** *auto[]*

```

next
case (2 v vb vd vf vh)
have f3:  $\bigwedge c. (if\ do\_skip\_step\ (rough\_state\_of\ c) \neq rough\_state\_of\ c$ 
  then  $do\_skip\_step\ (rough\_state\_of\ c)$ 
  else if  $do\_resolve\_step\ (do\_skip\_step\ (rough\_state\_of\ c)) \neq do\_skip\_step\ (rough\_state\_of\ c)$ 
    then  $do\_resolve\_step\ (do\_skip\_step\ (rough\_state\_of\ c))$ 
    else if  $do\_backtrack\_step\ (do\_resolve\_step\ (do\_skip\_step\ (rough\_state\_of\ c)))$ 
       $\neq do\_resolve\_step\ (do\_skip\_step\ (rough\_state\_of\ c))$ 
      then  $do\_backtrack\_step\ (do\_resolve\_step\ (do\_skip\_step\ (rough\_state\_of\ c)))$ 
      else  $do\_decide\_step\ (do\_backtrack\_step\ (do\_resolve\_step\ (do\_skip\_step\ (rough\_state\_of\ c))))$ 
    =  $rough\_state\_of\ (do\_other\_step'\ c)$ 
  by (simp add: rough-state-of-do-other-step')
have
  (raw-trail (rough-state-of (do-other-step' S)),
   raw-init-clss (rough-state-of (do-other-step' S)),
   raw-learned-clss (rough-state-of (do-other-step' S)),
   raw-backtrack-lvl (rough-state-of (do-other-step' S)), None)
  = rough-state-of (do-other-step' S)
using assms(2) by (cases do-other-step' S) auto
then show ?thesis
  using f3 2 by (metis (no-types) do-decide-step.simps(2) do-resolve-step-trail-is-None
    do-skip-step-trail-is-None rough-state-of-inverse)
qed
show ?case
using assms(2) S unfolding bt y inv
apply simp
by (auto simp add: M bt-cut-not-none
  split: option.splits
  dest!: bt-cut-some-decomp)
qed

lemma do-other-step-not-conflicting-one-more-decide:
  assumes conflicting (rough-state-of S) = None and
    do-other-step' S  $\neq$  S
  shows 1 + length (filter is-marked (raw-trail (rough-state-of S)))
    = length (filter is-marked (raw-trail (rough-state-of (do-other-step' S))))
proof (cases S, goal-cases)
case (1 y) note S = this(1) and inv = this(2)
obtain M N U k where y: y = (M, N, U, k, None) using assms(1) S inv by (cases y) auto
have M: rough-state-of (state-of (M, N, U, k, None)) = (M, N, U, k, None)
  using inv y by (auto simp add: state-of-inverse)
have state-of (do-decide-step (M, N, U, k, None))  $\neq$  state-of (M, N, U, k, None)
  using assms(2) unfolding do-other-step'-def y inv S by (auto simp add: M)
then have f4: do-skip-step (rough-state-of S) = rough-state-of S
  unfolding S M y by (metis (full-types) do-skip-step.simps(4))
have f5: do-resolve-step (rough-state-of S) = rough-state-of S
  unfolding S M y by (metis (no-types) do-resolve-step.simps(4))
have f6: do-backtrack-step (rough-state-of S) = rough-state-of S
  unfolding S M y by (metis (no-types) do-backtrack-step.simps(2))
have do-other-step (rough-state-of S)  $\neq$  rough-state-of S
  using assms(2) unfolding S M y do-other-step'-def by (metis (no-types))
then show ?case
  using f6 f5 f4 by (simp add: assms(1) do-decide-step-not-conflicting-one-more-decide
    do-other-step'-def)

```

qed

**lemma** *rough-state-of-state-of-do-skip-step-rough-state-of*[simp]:  
  *rough-state-of* (*state-of* (*do-skip-step* (*rough-state-of* *S*))) = *do-skip-step* (*rough-state-of* *S*)  
  **by** (*smt do-other-step.simps rough-state-of-inverse rough-state-of-state-of-do-other-step*)

**lemma** *conflicting-do-resolve-step-iff*[iff]:  
  *conflicting* (*do-resolve-step* *S*) = *None*  $\longleftrightarrow$  *conflicting* *S* = *None*  
  **by** (*cases S rule: do-resolve-step.cases*)  
  (*auto simp add: Let-def split: option.splits*)

**lemma** *conflicting-do-skip-step-iff*[iff]:  
  *conflicting* (*do-skip-step* *S*) = *None*  $\longleftrightarrow$  *conflicting* *S* = *None*  
  **by** (*cases S rule: do-skip-step.cases*)  
  (*auto simp add: Let-def split: option.splits*)

**lemma** *conflicting-do-decide-step-iff*[iff]:  
  *conflicting* (*do-decide-step* *S*) = *None*  $\longleftrightarrow$  *conflicting* *S* = *None*  
  **by** (*cases S rule: do-decide-step.cases*)  
  (*auto simp add: Let-def split: option.splits*)

**lemma** *conflicting-do-backtrack-step-imp*[simp]:  
  *do-backtrack-step* *S*  $\neq$  *S*  $\implies$  *conflicting* (*do-backtrack-step* *S*) = *None*  
  **by** (*cases S rule: do-backtrack-step.cases*)  
  (*auto simp add: Let-def split: list.splits option.splits marked-lit.splits*)

**lemma** *do-skip-step-eq-iff-trail-eq*:  
  *do-skip-step* *S* = *S*  $\longleftrightarrow$  *trail* (*do-skip-step* *S*) = *trail* *S*  
  **by** (*cases S rule: do-skip-step.cases*) *auto*

**lemma** *do-decide-step-eq-iff-trail-eq*:  
  *do-decide-step* *S* = *S*  $\longleftrightarrow$  *trail* (*do-decide-step* *S*) = *trail* *S*  
  **by** (*cases S rule: do-decide-step.cases*) (*auto split: option.split*)

**lemma** *do-backtrack-step-eq-iff-trail-eq*:  
  *do-backtrack-step* *S* = *S*  $\longleftrightarrow$  *raw-trail* (*do-backtrack-step* *S*) = *raw-trail* *S*  
  **by** (*cases S rule: do-backtrack-step.cases*)  
  (*auto split: option.split list.splits marked-lit.splits*  
  *dest!: bt-cut-in-get-all-marked-decomposition*)

**lemma** *do-resolve-step-eq-iff-trail-eq*:  
  *do-resolve-step* *S* = *S*  $\longleftrightarrow$  *trail* (*do-resolve-step* *S*) = *trail* *S*  
  **by** (*cases S rule: do-resolve-step.cases*) *auto*

**lemma** *do-other-step-eq-iff-trail-eq*:  
  *do-other-step* *S* = *S*  $\longleftrightarrow$  *raw-trail* (*do-other-step* *S*) = *raw-trail* *S*

**apply**

(*auto simp add: Let-def do-skip-step-eq-iff-trail-eq*  
  *do-decide-step-eq-iff-trail-eq do-backtrack-step-eq-iff-trail-eq*  
  *do-resolve-step-eq-iff-trail-eq*  
  )

**apply** (*simp add: do-resolve-step-eq-iff-trail-eq[symmetric]*  
  *do-skip-step-eq-iff-trail-eq[symmetric]*)

**apply** (*simp add: do-skip-step-eq-iff-trail-eq[symmetric]*)

```

do-decide-step-eq-iff-trail-eq do-backtrack-step-eq-iff-trail-eq[symmetric]
do-resolve-step-eq-iff-trail-eq[symmetric]
)
done

lemma do-full1-cp-step-do-other-step'-normal-form[dest!]:
  assumes H: do-full1-cp-step (do-other-step' S) = S
  shows do-other-step' S = S ∧ do-full1-cp-step S = S
proof -
  let ?T = do-other-step' S
  { assume confl: conflicting (rough-state-of ?T) ≠ None
    then have tr: trail (rough-state-of (do-full1-cp-step ?T)) = trail (rough-state-of ?T)
      using do-full1-cp-step-conflicting by fastforce
    have raw-trail (rough-state-of (do-full1-cp-step (do-other-step' S))) =
      raw-trail (rough-state-of S)
      using arg-cong[OF H, of λS. raw-trail (rough-state-of S)] .
    then have raw-trail (rough-state-of (do-other-step' S)) = raw-trail (rough-state-of S)
      using confl by (auto simp add: do-full1-cp-step-conflicting)
    then have do-other-step' S = S
      by (simp add: do-other-step-eq-iff-trail-eq[symmetric] do-other-step'-def
        del: do-other-step.simps)
  }
  moreover {
    assume eq[simp]: do-other-step' S = S
    obtain c where c: raw-trail (rough-state-of (do-full1-cp-step S)) =
      c @ raw-trail (rough-state-of S)
      using do-full1-cp-step-neq-trail-increase by auto

    moreover have raw-trail (rough-state-of (do-full1-cp-step S)) = raw-trail (rough-state-of S)
      using arg-cong[OF H, of λS. raw-trail (rough-state-of S)] by simp
    finally have c = [] by blast
    then have do-full1-cp-step S = S using assms by auto
  }
  moreover {
    assume confl: conflicting (rough-state-of ?T) = None and neq: do-other-step' S ≠ S
    obtain c where
      c: raw-trail (rough-state-of (do-full1-cp-step ?T)) = c @ raw-trail (rough-state-of ?T) and
      nm: ∀ m ∈ set c. ¬ is-marked m
      using do-full1-cp-step-neq-trail-increase by auto
    have length (filter is-marked (raw-trail (rough-state-of (do-full1-cp-step ?T))))
      = length (filter is-marked (raw-trail (rough-state-of ?T)))
      using nm unfolding c by force
    moreover have length (filter is-marked (raw-trail (rough-state-of S)))
      ≠ length (filter is-marked (raw-trail (rough-state-of ?T)))
      using do-other-step-not-conflicting-one-more-decide[OF - neq]
        do-other-step-not-conflicting-one-more-decide-bt[of S, OF - confl neq]
        by linarith
    finally have False unfolding H by blast
  }
  ultimately show ?thesis by blast
qed

```

```

lemma do-cdclW-stgy-step-no:
  assumes S: do-cdclW-stgy-step S = S
  shows no-step cdclW-stgy (rough-state-of S)

```

```

proof -
{
  fix S'
  assume full1 cdclW-cp (rough-state-of S) S'
  then have False
    using do-full1-cp-step-full[of S] unfolding full-def S rtrancpl-unfold full1-def
    by (smt assms do-cdclW-stgy-step-def trancplD)
}
moreover {
  fix S' S''
  assume cdclW-o (rough-state-of S) S' and
    no-step propagate (rough-state-of S) and
    no-step conflict (rough-state-of S) and
    full cdclW-cp S' S''
  then have False
    using assms unfolding do-cdclW-stgy-step-def
    by (smt cdclW-all-struct-inv-rough-state do-full1-cp-step-do-other-step'-normal-form
      do-other-step-no rough-state-of-do-other-step')
}
ultimately show ?thesis using assms by (force simp: cdclW-cp.simps cdclW-stgy.simps)
qed

lemma toS-rough-state-of-state-of-rough-state-from-init-state-of[simp]:
  rough-state-of (state-of (rough-state-from-init-state-of S))
    = rough-state-from-init-state-of S
  using rough-state-from-init-state-of[of S] by (auto simp add: state-of-inverse)

lemma cdclW-cp-is-rtrancpl-cdclW: cdclW-cp S T  $\implies$  cdclW** S T
  apply (induction rule: cdclW-cp.induct)
  using conflict apply blast
  using propagate by blast

lemma rtrancpl-cdclW-cp-is-rtrancpl-cdclW: cdclW-cp** S T  $\implies$  cdclW** S T
  apply (induction rule: rtrancpl-induct)
  apply simp
  by (fastforce dest!: cdclW-cp-is-rtrancpl-cdclW)

lemma cdclW-stgy-is-rtrancpl-cdclW:
  cdclW-stgy S T  $\implies$  cdclW** S T
  apply (induction rule: cdclW-stgy.induct)
  using cdclW-stgy.conflict' rtrancpl-cdclW-stgy-rtrancpl-cdclW apply blast
  unfolding full-def by (fastforce dest!: other rtrancpl-cdclW-cp-is-rtrancpl-cdclW)

lemma cdclW-stgy-init-clss: cdclW-stgy S T  $\implies$  cdclW-M-level-inv S  $\implies$  init-clss S = init-clss T
  using rtrancpl-cdclW-init-clss cdclW-stgy-is-rtrancpl-cdclW by fast

lemma clauses-toS-rough-state-of-do-cdclW-stgy-step[simp]:
  init-clss (rough-state-of (do-cdclW-stgy-step (state-of (rough-state-from-init-state-of S))))
    = init-clss (rough-state-from-init-state-of S) (is - = init-clss ?S)
proof (cases do-cdclW-stgy-step (state-of ?S) = state-of ?S)
  case True
  then show ?thesis by simp
next
  case False
  have  $\bigwedge c$ . cdclW-M-level-inv (rough-state-of c)

```

```

    using cdclW-all-struct-inv-def cdclW-all-struct-inv-rough-state by blast
  then have  $\bigwedge c. \text{init-clss} (\text{rough-state-of } c) = \text{init-clss} (\text{rough-state-of } (\text{do-cdcl}_W\text{-stgy-step } c))$ 
     $\vee \text{do-cdcl}_W\text{-stgy-step } c = c$ 
    using cdclW-stgy-no-more-init-clss do-cdclW-stgy-step by blast
  then show ?thesis
    using False by force
qed

```

```

lemma raw-init-clss-do-cp-step[simp]:
  raw-init-clss (do-cp-step S) = raw-init-clss S
by (cases S) (auto simp: do-cp-step-def do-propagate-step-def do-conflict-step-def
  split: option.splits)
lemma raw-init-clss-do-cp-step'[simp]:
  raw-init-clss (rough-state-of (do-cp-step' S)) = raw-init-clss (rough-state-of S)
by (simp add: do-cp-step'-def)

```

```

lemma raw-init-clss-rough-state-of-do-full1-cp-step[simp]:
  raw-init-clss (rough-state-of (do-full1-cp-step S))
  = raw-init-clss (rough-state-of S)
apply (rule do-full1-cp-step.induct[of  $\lambda S.$ 
  raw-init-clss (rough-state-of (do-full1-cp-step S))
  = raw-init-clss (rough-state-of S)])
by (metis (mono-tags, lifting) do-full1-cp-step.simps raw-init-clss-do-cp-step')

```

```

lemma raw-init-clss-do-skip-def[simp]:
  raw-init-clss (do-skip-step S) = raw-init-clss S
by (cases S rule: do-skip-step.cases) (auto simp: do-other-step'-def Let-def
  split: option.splits)

```

```

lemma raw-init-clss-do-resolve-def[simp]:
  raw-init-clss (do-resolve-step S) = raw-init-clss S
by (cases S rule: do-resolve-step.cases) (auto simp: do-other-step'-def Let-def
  split: option.splits)

```

```

lemma raw-init-clss-do-backtrack-def[simp]:
  raw-init-clss (do-backtrack-step S) = raw-init-clss S
by (cases S rule: do-backtrack-step.cases) (auto simp: do-other-step'-def Let-def
  split: option.splits list.splits marked-lit.splits)

```

```

lemma raw-init-clss-do-decide-def[simp]:
  raw-init-clss (do-decide-step S) = raw-init-clss S
by (cases S rule: do-decide-step.cases) (auto simp: do-other-step'-def Let-def
  split: option.splits)

```

```

lemma raw-init-clss-rough-state-of-do-other-step'[simp]:
  raw-init-clss (rough-state-of (do-other-step' S))
  = raw-init-clss (rough-state-of S)
by (cases S) (auto simp: do-other-step'-def Let-def do-skip-step.cases
  split: option.splits)

```

```

lemma [simp]:
  raw-init-clss (rough-state-of (do-cdclW-stgy-step (state-of (rough-state-from-init-state-of S))))
  =
  raw-init-clss (rough-state-from-init-state-of S)

```



**unfolding** *do-cdcl<sub>W</sub>-stgy-step-def* **by** (*auto simp: Let-def*)

**lemma** *rough-state-from-init-state-of-do-cdcl<sub>W</sub>-stgy-step'*[*code abstract*]:

*rough-state-from-init-state-of* (*do-cdcl<sub>W</sub>-stgy-step'* *S*) =  
*rough-state-of* (*do-cdcl<sub>W</sub>-stgy-step* (*id-of-I-to* *S*))

**proof** –

**let** *?S* = (*rough-state-from-init-state-of* *S*)  
**have** *cdcl<sub>W</sub>-stgy\*\** (*raw-S0-cdcl<sub>W</sub>* (*raw-init-clss* (*rough-state-from-init-state-of* *S*)))  
(*rough-state-from-init-state-of* *S*)  
**using** *rough-state-from-init-state-of*[*of S*] **by** *auto*  
**moreover have** *cdcl<sub>W</sub>-stgy\*\**  
(*rough-state-from-init-state-of* *S*)  
(*rough-state-of* (*do-cdcl<sub>W</sub>-stgy-step*  
(*state-of* (*rough-state-from-init-state-of* *S*))))  
**using** *do-cdcl<sub>W</sub>-stgy-step*[*of state-of ?S*]  
**by** (*cases do-cdcl<sub>W</sub>-stgy-step* (*state-of ?S*) = *state-of ?S*) *auto*  
**ultimately show** *?thesis*  
**unfolding** *do-cdcl<sub>W</sub>-stgy-step'-def id-of-I-to-def*  
**by** (*auto intro: state-from-init-state-of-inverse*)

**qed**

**All rules together** **function** *do-all-cdcl<sub>W</sub>-stgy* **where**

*do-all-cdcl<sub>W</sub>-stgy* *S* =  
(*let* *T* = *do-cdcl<sub>W</sub>-stgy-step'* *S* *in*  
*if* *T* = *S* *then S* *else do-all-cdcl<sub>W</sub>-stgy T*)

**by** *fast+*

**termination**

**proof** (*relation* {(*T*, *S*).

(*cdcl<sub>W</sub>-measure* (*rough-state-from-init-state-of* *T*),  
*cdcl<sub>W</sub>-measure* (*rough-state-from-init-state-of* *S*))  
∈ *lexn* {(*a*, *b*). *a* < *b*} *3*}, *goal-cases*)

**case** 1

**show** *?case* **by** (*rule wf-if-measure-f*) (*auto intro!: wf-lexn wf-less*)

**next**

**case** (2 *S T*) **note** *T* = *this*(1) **and** *ST* = *this*(2)

**let** *?S* = *rough-state-from-init-state-of* *S*

**have** *S*: *cdcl<sub>W</sub>-stgy\*\** (*raw-S0-cdcl<sub>W</sub>* (*raw-init-clss* *?S*)) *?S*

**using** *rough-state-from-init-state-of*[*of S*] **by** *auto*

**moreover have** *cdcl<sub>W</sub>-stgy* (*rough-state-from-init-state-of* *S*)  
(*rough-state-from-init-state-of* *T*)

**proof** –

**have**  $\bigwedge c.$  *rough-state-of* (*state-of* (*rough-state-from-init-state-of* *c*)) =  
*rough-state-from-init-state-of* *c*  
**using** *rough-state-from-init-state-of* **by** *force*  
**then have** *do-cdcl<sub>W</sub>-stgy-step* (*state-of* (*rough-state-from-init-state-of* *S*))  
≠ *state-of* (*rough-state-from-init-state-of* *S*)  
**using** *ST T rough-state-from-init-state-of-inverse*  
**unfolding** *id-of-I-to-def do-cdcl<sub>W</sub>-stgy-step'-def*  
**by** *fastforce*  
**from** *do-cdcl<sub>W</sub>-stgy-step*[*OF this*] **show** *?thesis*  
**by** (*simp add: T id-of-I-to-def rough-state-from-init-state-of-do-cdcl<sub>W</sub>-stgy-step'*)

**qed**

**moreover**

**have** *cdcl<sub>W</sub>-all-struct-inv* (*rough-state-from-init-state-of* *S*)

```

    using rough-state-from-init-state-of[of S] by auto
  then have cdclW-all-struct-inv (raw-S0-cdclW (raw-init-clss (rough-state-from-init-state-of S)))
    by (cases rough-state-from-init-state-of S)
      (auto simp add: cdclW-all-struct-inv-def distinct-cdclW-state-def)
  ultimately show ?case
    by (auto intro!: cdclW-stgy-step-decreasing[of - - raw-S0-cdclW (raw-init-clss ?S)]
      simp del: cdclW-measure.simps)
qed

```

**thm** *do-all-cdcl<sub>W</sub>-stgy.induct*

**lemma** *do-all-cdcl<sub>W</sub>-stgy.induct:*

( $\bigwedge S. (do-cdcl_W-stgy-step' S \neq S \implies P (do-cdcl_W-stgy-step' S)) \implies P S) \implies P a0$ )

**using** *do-all-cdcl<sub>W</sub>-stgy.induct* **by** *metis*

**lemma** [*simp*]: *raw-init-clss (rough-state-from-init-state-of (do-all-cdcl<sub>W</sub>-stgy S)) =*  
*raw-init-clss (rough-state-from-init-state-of S)*

**apply** (*induction rule: do-all-cdcl<sub>W</sub>-stgy.induct*)

**by** (*smt do-all-cdcl<sub>W</sub>-stgy.simps do-cdcl<sub>W</sub>-stgy-step-def id-of-I-to-def*  
*raw-init-clss-rough-state-of-do-full1-cp-step raw-init-clss-rough-state-of-do-other-step'*  
*rough-state-from-init-state-of-do-cdcl<sub>W</sub>-stgy-step'*  
*toS-rough-state-of-state-of-rough-state-from-init-state-of*)

**lemma** *no-step-cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-all:*

**fixes** *S :: 'a cdcl<sub>W</sub>-state-inv-from-init-state*

**shows** *no-step cdcl<sub>W</sub>-stgy (rough-state-from-init-state-of (do-all-cdcl<sub>W</sub>-stgy S))*

**apply** (*induction S rule: do-all-cdcl<sub>W</sub>-stgy.induct*)

**apply** (*rename-tac S, case-tac do-cdcl<sub>W</sub>-stgy-step' S ≠ S*)

**proof** –

**fix** *Sa :: 'a cdcl<sub>W</sub>-state-inv-from-init-state*

**assume** *a1: ¬ do-cdcl<sub>W</sub>-stgy-step' Sa ≠ Sa*

{ **fix** *pp*

**have** (*if True then Sa else do-all-cdcl<sub>W</sub>-stgy Sa*) = *do-all-cdcl<sub>W</sub>-stgy Sa*

**using** *a1* **by** *auto*

**then have**  $\neg cdcl_W-stgy (rough-state-from-init-state-of (do-all-cdcl_W-stgy Sa))$  *pp*

**using** *a1* **by** (*smt do-cdcl<sub>W</sub>-stgy-step-no id-of-I-to-def*  
*rough-state-from-init-state-of-do-cdcl<sub>W</sub>-stgy-step' rough-state-of-inverse*) }

**then show** *no-step cdcl<sub>W</sub>-stgy (rough-state-from-init-state-of (do-all-cdcl<sub>W</sub>-stgy Sa))*

**by** *fastforce*

**next**

**fix** *Sa :: 'a cdcl<sub>W</sub>-state-inv-from-init-state*

**assume** *a1: do-cdcl<sub>W</sub>-stgy-step' Sa ≠ Sa*

$\implies no-step cdcl_W-stgy (rough-state-from-init-state-of$   
 $(do-all-cdcl_W-stgy (do-cdcl_W-stgy-step' Sa)))$

**assume** *a2: do-cdcl<sub>W</sub>-stgy-step' Sa ≠ Sa*

**have** *do-all-cdcl<sub>W</sub>-stgy Sa = do-all-cdcl<sub>W</sub>-stgy (do-cdcl<sub>W</sub>-stgy-step' Sa)*

**by** (*metis (full-types) do-all-cdcl<sub>W</sub>-stgy.simps*)

**then show** *no-step cdcl<sub>W</sub>-stgy (rough-state-from-init-state-of (do-all-cdcl<sub>W</sub>-stgy Sa))*

**using** *a2 a1* **by** *presburger*

**qed**

**lemma** *do-all-cdcl<sub>W</sub>-stgy-is-rtrancpl-cdcl<sub>W</sub>-stgy:*

*cdcl<sub>W</sub>-stgy\*\* (rough-state-from-init-state-of S)*

*(rough-state-from-init-state-of (do-all-cdcl<sub>W</sub>-stgy S))*

**proof** (*induction S rule: do-all-cdcl<sub>W</sub>-stgy.induct*)

**case** (*1 S*) **note** *IH = this(1)*

```

show ?case
proof (cases do-cdclW-stgy-step' S = S)
  case True
  then show ?thesis by simp
next
  case False
  have f2: do-cdclW-stgy-step (id-of-I-to S) = id-of-I-to S  $\longrightarrow$ 
    rough-state-from-init-state-of (do-cdclW-stgy-step' S)
    = rough-state-of (state-of (rough-state-from-init-state-of S))
  unfolding rough-state-from-init-state-of-do-cdclW-stgy-step'
    id-of-I-to-def by presburger
  have f3: do-all-cdclW-stgy S = do-all-cdclW-stgy (do-cdclW-stgy-step' S)
    by (metis (full-types) do-all-cdclW-stgy.simps)
  have cdclW-stgy (rough-state-from-init-state-of S)
    (rough-state-from-init-state-of (do-cdclW-stgy-step' S))
    = cdclW-stgy (rough-state-of (id-of-I-to S))
    (rough-state-of (do-cdclW-stgy-step (id-of-I-to S)))
  unfolding id-of-I-to-def rough-state-from-init-state-of-do-cdclW-stgy-step'
    toS-rough-state-of-state-of-rough-state-from-init-state-of by presburger
  then show ?thesis
  using f3 f2 IH do-cdclW-stgy-step
  by (smt False toS-rough-state-of-state-of-rough-state-from-init-state-of tranclp.intros(1)
    tranclp-into-rtranclp transitive-closurep-trans'(2))
qed
qed

```

Final theorem:

**lemma** *consistent-interp-mmset-of-mlit[simp]*:  
 consistent-interp (lit-of 'mmset-of-mlit' 'set M')  $\longleftrightarrow$   
 consistent-interp (lit-of 'set M')  
 by (auto simp: image-image)

**lemma** *DPLL-tot-correct*:

**assumes**

*r*: rough-state-from-init-state-of (do-all-cdcl<sub>W</sub>-stgy (state-from-init-state-of  
 ([], map remdups N, [], 0, None))) = S **and**  
 S: (M', N', U', k, E) = S

**shows** (E  $\neq$  Some []  $\wedge$  satisfiable (set (map mset N)))  
 $\vee$  (E = Some []  $\wedge$  unsatisfiable (set (map mset N)))

**proof** –

let ?N = map remdups N

**have** *inv*: cdcl<sub>W</sub>-all-struct-inv ([], map remdups N, [], 0, None)

**unfolding** cdcl<sub>W</sub>-all-struct-inv-def distinct-cdcl<sub>W</sub>-state-def distinct-mset-set-def **by** auto

**then have** *S0*: rough-state-of (state-of ([], map remdups N, [], 0, None))

= ([], map remdups N, [], 0, None) **by** simp

**have** *1*: full cdcl<sub>W</sub>-stgy ([], ?N, [], 0, None) S

**unfolding** full-def **apply** rule

**using** do-all-cdcl<sub>W</sub>-stgy-is-rtranclp-cdcl<sub>W</sub>-stgy[of

state-from-init-state-of ([], map remdups N, [], 0, None)] *inv*

**by** (auto simp del: do-all-cdcl<sub>W</sub>-stgy.simps simp: state-from-init-state-of-inverse  
 r[symmetric] no-step-cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-all)+

**moreover have** *2*: finite (set (map mset ?N)) **by** auto

**moreover have** *3*: distinct-mset-set (set (map mset ?N))

**unfolding** distinct-mset-set-def **by** auto

**moreover**

```

have cdclW-all-struct-inv S
  by (metis (no-types) cdclW-all-struct-inv-rough-state r
    toS-rough-state-of-state-of-rough-state-from-init-state-of)
then have cons: consistent-interp (lits-of-l M')
  unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def S[symmetric]
  by (auto simp: lits-of-def)
moreover
have [simp]:
  rough-state-from-init-state-of (state-from-init-state-of (raw-S0-cdclW (map remdups N)))
  = raw-S0-cdclW (map remdups N)
apply (rule cdclW-state-inv-from-init-state.state-from-init-state-of-inverse)
using 3 by (auto simp: cdclW-all-struct-inv-def distinct-cdclW-state-def
  image-image comp-def)
have raw-init-clss ([], ?N, [], 0, None) = raw-init-clss S
  using arg-cong[OF r, of raw-init-clss] unfolding S[symmetric]
  by (simp del: do-all-cdclW-stgy.simps)
then have N': N' = map remdups N
  using S[symmetric] by auto
have conflicting S = Some {#} ∧ unsatisfiable (set-mset (init-clss S)) ∨
  conflicting S = None ∧ (case S of (M, uu-) ⇒ map mmset-of-mlit' M) ⊨asm init-clss S
apply (rule full-cdclW-stgy-final-state-conclusive)
  using 1 apply simp
  using 2 apply simp
  using 3 by simp
then have (E ≠ Some [] ∧ satisfiable (set (map mset ?N)))
  ∨ (E = Some [] ∧ unsatisfiable (set (map mset ?N)))
  using cons unfolding S[symmetric] N' apply (auto simp: comp-def)
  by (simp add: true-annots-true-clss)
then show ?thesis by auto
qed

```

**The Code** The SML code is skipped in the documentation, but stays to ensure that some version of the exported code is working. The only difference between the generated code and the one used here is the export of the constructor `ConI`.

```

end
theory CDCL-W-Merge
imports CDCL-W-Termination
begin

```

## 21 Link between Weidenbach's and NOT's CDCL

### 21.1 Inclusion of the states

```

context conflict-driven-clause-learningW
begin
declare cdclW.intros[intro] cdclW-bj.intros[intro] cdclW-o.intros[intro]

lemma backtrack-no-cdclW-bj:
  assumes cdcl: cdclW-bj T U and inv: cdclW-M-level-inv V
  shows ¬backtrack V T
  using cdcl inv
  apply (induction rule: cdclW-bj.induct)
  apply (elim skipE, force elim!: backtrack-levE[OF - inv] simp: cdclW-M-level-inv-def)

```

```

  apply (elim resolveE, force elim!: backtrack-levE[OF - inv] simp: cdclW-M-level-inv-def)
  apply standard
  apply (elim backtrack-levE[OF - inv], elim backtrackE)
  apply (force simp del: state-simp simp add: state-eq-def cdclW-M-level-inv-decomp)
done

```

**inductive** *skip-or-resolve* :: '*st* ⇒ '*st* ⇒ bool **where**  
*s-or-r-skip*[intro]: *skip S T* ⇒ *skip-or-resolve S T* |  
*s-or-r-resolve*[intro]: *resolve S T* ⇒ *skip-or-resolve S T*

**lemma** *rtrancpl-cdcl<sub>W</sub>-bj-skip-or-resolve-backtrack*:  
**assumes** *cdcl<sub>W</sub>-bj\*\* S U* **and** *inv: cdcl<sub>W</sub>-M-level-inv S*  
**shows** *skip-or-resolve\*\* S U* ∨ (∃ *T*. *skip-or-resolve\*\* S T* ∧ *backtrack T U*)  
**using** *assms*  
**proof** (*induction*)  
**case** *base*  
**then show** ?*case* **by** *simp*  
**next**  
**case** (*step U V*) **note** *st = this(1)* **and** *bj = this(2)* **and** *IH = this(3)[OF this(4)]*  
**consider**  
 (*SU*) *S = U*  
 | (*SUp*) *cdcl<sub>W</sub>-bj++ S U*  
**using** *st* **unfolding** *rtrancpl-unfold* **by** *blast*  
**then show** ?*case*  
**proof** *cases*  
**case** *SUp*  
**have**  $\bigwedge T$ . *skip-or-resolve\*\* S T* ⇒ *cdcl<sub>W</sub>\*\* S T*  
**using** *mono-rtrancpl[of skip-or-resolve cdcl<sub>W</sub>]*  
**by** (*blast intro: skip-or-resolve.cases*)  
**then have** *skip-or-resolve\*\* S U*  
**using** *bj IH inv backtrack-no-cdcl<sub>W</sub>-bj rtrancpl-cdcl<sub>W</sub>-consistent-inv[OF - inv]* **by** *meson*  
**then show** ?*thesis*  
**using** *bj* **by** (*auto simp: cdcl<sub>W</sub>-bj.simps dest!: skip-or-resolve.intros*)  
**next**  
**case** *SU*  
**then show** ?*thesis*  
**using** *bj* **by** (*auto simp: cdcl<sub>W</sub>-bj.simps dest!: skip-or-resolve.intros*)  
**qed**  
**qed**

**lemma** *rtrancpl-skip-or-resolve-rtrancpl-cdcl<sub>W</sub>*:  
*skip-or-resolve\*\* S T* ⇒ *cdcl<sub>W</sub>\*\* S T*  
**by** (*induction rule: rtrancpl-induct*)  
*(auto dest!: cdcl<sub>W</sub>-bj.intros cdcl<sub>W</sub>.intros cdcl<sub>W</sub>-o.intros simp: skip-or-resolve.simps)*

**definition** *backjump-l-cond* :: '*v* clause ⇒ '*v* clause ⇒ '*v* literal ⇒ '*st* ⇒ '*st* ⇒ bool **where**  
*backjump-l-cond* ≡  $\lambda C C' L' S T$ . *True*

**definition** *inv<sub>NOT</sub>* :: '*st* ⇒ bool **where**  
*inv<sub>NOT</sub>* ≡  $\lambda S$ . *no-dup (trail S)*

**declare** *inv<sub>NOT</sub>-def[simp]*  
**end**

**context** *conflict-driven-clause-learning<sub>W</sub>*  
**begin**

## 21.2 More lemmas conflict-propagate and backjumping

### 21.2.1 Termination

**lemma** *cdcl<sub>W</sub>-cp-normalized-element-all-inv*:  
**assumes** *inv*: *cdcl<sub>W</sub>-all-struct-inv S*  
**obtains** *T* **where** *full cdcl<sub>W</sub>-cp S T*  
**using** *assms cdcl<sub>W</sub>-cp-normalized-element* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *blast*  
**thm** *backtrackE*

**lemma** *cdcl<sub>W</sub>-bj-measure*:  
**assumes** *cdcl<sub>W</sub>-bj S T* **and** *cdcl<sub>W</sub>-M-level-inv S*  
**shows** *length (trail S) + (if conflicting S = None then 0 else 1)*  
*> length (trail T) + (if conflicting T = None then 0 else 1)*  
**using** *assms* **by** (*induction rule: cdcl<sub>W</sub>-bj.induct*)  
*(force dest:arg-cong[of - - length]*  
*intro: get-all-marked-decomposition-exists-prepend*  
*elim!: backtrack-levE skipE resolveE*  
*simp: cdcl<sub>W</sub>-M-level-inv-def)+*

**lemma** *wf-cdcl<sub>W</sub>-bj*:  
*wf {(b,a). cdcl<sub>W</sub>-bj a b ∧ cdcl<sub>W</sub>-M-level-inv a}*  
**apply** (*rule wfP-if-measure[of λ-. True*  
*- λT. length (trail T) + (if conflicting T = None then 0 else 1), simplified]*)  
**using** *cdcl<sub>W</sub>-bj-measure* **by** *simp*

**lemma** *cdcl<sub>W</sub>-bj-exists-normal-form*:  
**assumes** *lev: cdcl<sub>W</sub>-M-level-inv S*  
**shows**  $\exists T. \text{full } cdcl_W\text{-bj } S \ T$   
**proof** –  
**obtain** *T* **where** *T: full (λa b. cdcl<sub>W</sub>-bj a b ∧ cdcl<sub>W</sub>-M-level-inv a) S T*  
**using** *wf-exists-normal-form-full[OF wf-cdcl<sub>W</sub>-bj]* **by** *auto*  
**then have** *cdcl<sub>W</sub>-bj\*\* S T*  
**by** (*auto dest: rtrancp-and-rtrancp-left simp: full-def*)  
**moreover**  
**then have** *cdcl<sub>W</sub>\*\* S T*  
**using** *mono-rtrancp[of cdcl<sub>W</sub>-bj cdcl<sub>W</sub>]* **by** *blast*  
**then have** *cdcl<sub>W</sub>-M-level-inv T*  
**using** *rtrancp-cdcl<sub>W</sub>-consistent-inv lev* **by** *auto*  
**ultimately show** *?thesis* **using** *T* **unfolding** *full-def* **by** *auto*  
**qed**

**lemma** *rtrancp-skip-state-decomp*:  
**assumes** *skip\*\* S T* **and** *no-dup (trail S)*  
**shows**  
 $\exists M. \text{trail } S = M @ \text{trail } T \wedge (\forall m \in \text{set } M. \neg \text{is-marked } m)$   
*init-clss S = init-clss T*  
*learned-clss S = learned-clss T*  
*backtrack-lvl S = backtrack-lvl T*  
*conflicting S = conflicting T*  
**using** *assms* **by** (*induction rule: rtrancp-induct*)  
*(auto simp del: state-simp simp: state-eq-def elim!: skipE)*

### 21.2.2 More backjumping

Backjumping after skipping or jump directly lemma *rtrancpl-skip-backtrack-backtrack*:

```

assumes
  skip** S T and
  backtrack T W and
  cdclW-all-struct-inv S
shows backtrack S W
using assms
proof induction
  case base
  then show ?case by simp
next
  case (step T V) note st = this(1) and skip = this(2) and IH = this(3) and bt = this(4) and
    inv = this(5)
  have skip** S V
    using st skip by auto
  then have cdclW-all-struct-inv V
    using rtrancpl-mono[of skip cdclW] assms(3) rtrancpl-cdclW-all-struct-inv-inv mono-rtrancpl
    by (auto dest!: bj other cdclW-bj.skip)
  then have cdclW-M-level-inv V
    unfolding cdclW-all-struct-inv-def by auto
  then obtain K i M1 M2 L D where
    conf: raw-conflicting V = Some D and
    LD: L ∈ # mset-ccls D and
    decomp: (Marked K (Suc i) # M1, M2) ∈ set (get-all-marked-decomposition (trail V)) and
    lev-L: get-level (trail V) L = backtrack-lvl V and
    max: get-level (trail V) L = get-maximum-level (trail V) (mset-ccls D) and
    max-D: get-maximum-level (trail V) (remove1-mset L (mset-ccls D)) ≡ i and
    undef: undefined-lit M1 L and
    W: W ∼ cons-trail (Propagated L (cls-of-ccls D))
      (reduce-trail-to M1
        (add-learned-cls (cls-of-ccls D)
          (update-backtrack-lvl i
            (update-conflicting None V))))
  using bt inv by (elim backtrack-levE) metis+
  obtain L' C' M E where
    tr: trail T = Propagated L' C' # M and
    raw: raw-conflicting T = Some E and
    LE: -L' ∉ # mset-ccls E and
    E: mset-ccls E ≠ {#} and
    V: V ∼ tl-trail T
    using skip by (elim skipE) metis
  let ?M = Propagated L' C' # trail V
  have tr-M: trail T = ?M
    using tr V by auto
  have MT: M = tl (trail T) and MV: M = trail V
    using tr V by auto
  have DE[simp]: mset-ccls D = mset-ccls E
    using V conf raw by (auto simp add: state-eq-def simp del: state-simp)
  have cdclW** S T using bj cdclW-bj.skip mono-rtrancpl[of skip cdclW S T] other st by meson
  then have inv': cdclW-all-struct-inv T
    using rtrancpl-cdclW-all-struct-inv-inv inv by blast
  have M-lev: cdclW-M-level-inv T using inv' unfolding cdclW-all-struct-inv-def by auto
  then have n-d': no-dup ?M
    using tr-M unfolding cdclW-M-level-inv-def by auto

```

```

let ?k = backtrack-lvl T
have [simp]:
  backtrack-lvl V = ?k
  using V by simp
have ?k > 0
  using decomp M-lev V tr unfolding cdclW-M-level-inv-def by auto
then have atm-of L ∈ atm-of ' lits-of-l (trail V)
  using lev-L get-rev-level-ge-0-atm-of-in[of 0 rev (trail V) L] by auto
then have L-L': atm-of L ≠ atm-of L'
  using n-d' unfolding lits-of-def by auto
have L'-M: atm-of L' ∉ atm-of ' lits-of-l (trail V)
  using n-d' unfolding lits-of-def by auto
have ?M ⊨as CNot (mset-ccls D)
  using inv' raw unfolding cdclW-conflicting-def cdclW-all-struct-inv-def tr-M by auto
then have L' ∉ # mset-ccls (remove-clit L D)
  using L-L' L'-M ⟨Propagated L' C' # trail V ⊨as CNot (mset-ccls D)⟩
  unfolding true-annots-true-cls true-clss-def
  by (auto simp: uminus-lit-swap atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set dest!: in-diffD)
have [simp]: trail (reduce-trail-to M1 T) = M1
  using decomp undef tr W V by auto
have skip** S V
  using st skip by auto
have no-dup (trail S)
  using inv unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def by auto
then have [simp]: init-clss S = init-clss V and [simp]: learned-clss S = learned-clss V
  using rtrancp-skip-state-decomp[OF ⟨skip** S V⟩] V
  by (auto simp del: state-simp simp: state-eq-def)
then have
  W-S: W ∼ cons-trail (Propagated L (cls-of-ccls E)) (reduce-trail-to M1
    (add-learned-cls (cls-of-ccls E) (update-backtrack-lvl i (update-conflicting None T))))
  using W V undef M-lev decomp tr
  by (auto simp del: state-simp simp: state-eq-def cdclW-M-level-inv-def)

obtain M2' where
  decomp': (Marked K (i+1) # M1, M2') ∈ set (get-all-marked-decomposition (trail T))
  using decomp V unfolding tr-M by (cases hd (get-all-marked-decomposition (trail V)),
    cases get-all-marked-decomposition (trail V)) auto
moreover
  from L-L' have get-level ?M L = ?k
    using lev-L V by (auto split: if-split-asm)
moreover
  have atm-of L' ∉ atms-of (mset-ccls D)
    by (metis DE LE L-L' ⟨L' ∉ # mset-ccls (remove-clit L D)⟩ in-remove1-mset-neq remove-clit
      atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set atms-of-def)
  then have get-level ?M L = get-maximum-level ?M (mset-ccls D)
    using calculation(2) lev-L max by auto
moreover
  have atm-of L' ∉ atms-of (mset-ccls (remove-clit L D))
    by (metis DE LE L-L' ⟨L' ∉ # mset-ccls (remove-clit L D)⟩
      atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set atms-of-def in-remove1-mset-neq remove-clit
      in-atms-of-remove1-mset-in-atms-of)
  have i = get-maximum-level ?M (mset-ccls (remove-clit L D))
    using max-D ⟨atm-of L' ∉ atms-of (mset-ccls (remove-clit L D))⟩ by auto

ultimately have backtrack T W

```



```

apply –
apply (rule backtrack-rule[of T - L K i M1 M2' W, OF raw])
unfolding tr-M[symmetric]
  using LD apply simp
  apply simp
  apply simp
  apply simp
  apply auto[]
using W-S by auto
then show ?thesis using IH inv by blast
qed

```

```

lemma fst-get-all-marked-decomposition-prepend-not-marked:
assumes  $\forall m \in \text{set } MS. \neg \text{is-marked } m$ 
shows set (map fst (get-all-marked-decomposition M))
  = set (map fst (get-all-marked-decomposition (MS @ M)))
using assms apply (induction MS rule: marked-lit-list-induct)
apply auto[2]
by (rename-tac L m xs; case-tac get-all-marked-decomposition (xs @ M) simp-all)

```

See also  $\llbracket \text{skip}^{**} ?S ?T; \text{backtrack} ?T ?W; \text{cdcl}_W\text{-all-struct-inv} ?S \rrbracket \implies \text{backtrack} ?S ?W$

```

lemma rtrancpl-skip-backtrack-backtrack-end:

```

```

assumes
  skip: skip** S T and
  bt: backtrack S W and
  inv: cdclW-all-struct-inv S

```

```

shows backtrack T W

```

```

using assms

```

```

proof –

```

```

  have M-lev: cdclW-M-level-inv S

```

```

    using bt inv unfolding cdclW-all-struct-inv-def by (auto elim!: backtrack-levE)

```

```

then obtain K i M1 M2 L D where

```

```

  raw-S: raw-conflicting S = Some D and

```

```

  LD:  $L \in \# \text{mset-ccls } D$  and

```

```

  decomp:  $(\text{Marked } K (\text{Suc } i) \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$  and

```

```

  lev-l: get-level (trail S) L = backtrack-lvl S and

```

```

  lev-l-D: get-level (trail S) L = get-maximum-level (trail S) (mset-ccls D) and

```

```

  i: get-maximum-level (trail S) (remove1-mset L (mset-ccls D))  $\equiv i$  and

```

```

  undef: undefined-lit M1 L and

```

```

  W:  $W \sim \text{cons-trail } (\text{Propagated } L (\text{cls-of-ccls } D))$ 

```

```

    (reduce-trail-to M1

```

```

      (add-learned-cls (cls-of-ccls D)

```

```

        (update-backtrack-lvl i

```

```

          (update-conflicting None S))))

```

```

  using bt by (elim backtrack-levE)

```

```

  (simp-all add: cdclW-M-level-inv-decomp state-eq-def del: state-simp)

```

```

let ?D = remove1-mset L (mset-ccls D)

```

```

have [simp]: no-dup (trail S)

```

```

  using M-lev by (auto simp: cdclW-M-level-inv-decomp)

```

```

have cdclW-all-struct-inv T

```

```

  using mono-rtrancpl[of skip cdclW] by (smt bj cdclW-bj.skip inv local.skip other

```

```

    rtrancpl-cdclW-all-struct-inv-inv)

```

```

then have [simp]: no-dup (trail T)

```

```

unfolding  $cdcl_W$ -all-struct-inv-def  $cdcl_W$ -M-level-inv-def by auto

obtain  $MS\ M_T$  where  $M$ :  $trail\ S = MS\ @\ M_T$  and  $M_T$ :  $M_T = trail\ T$  and  $nm$ :  $\forall m \in set\ MS.$ 
 $\neg is\_marked\ m$ 
  using  $rtrancp\_skip\_state\_decomp(1)[OF\ skip]$   $raw-S\ M\_lev$  by auto
have  $T$ :  $state\ T = (M_T, init\_cls\ S, learned\_cls\ S, backtrack\_lvl\ S, Some\ (mset\_ccls\ D))$ 
  using  $M_T\ rtrancp\_skip\_state\_decomp[of\ S\ T]$   $skip\ raw-S$ 
  by ( $auto\ simp\ del$ :  $state\_simp\ simp$ :  $state\_eq\_def$ )

have  $cdcl_W$ -all-struct-inv  $T$ 
  apply ( $rule\ rtrancp\_cdcl_W$ -all-struct-inv-inv[ $OF - inv$ ])
  using  $bj\ cdcl_W$ -bj.skip local.skip other  $rtrancp\_mono[of\ skip\ cdcl_W]$  by blast
then have  $M_T \models_{as} CNot\ (mset\_ccls\ D)$ 
  unfolding  $cdcl_W$ -all-struct-inv-def  $cdcl_W$ -conflicting-def using  $T$  by blast
then have  $\forall L \in \#mset\_ccls\ D. atm\_of\ L \in atm\_of\ 'lits\_of\_l\ M_T$ 
  by ( $meson\ atm\_of\_in\_atm\_of\_set\_iff\_in\_set\_or\_uminus\_in\_set$ 
     $true\_annots\_true\_cls\_def\_iff\_negation\_in\_model$ )
moreover have  $no\_dup\ (trail\ S)$ 
  using  $inv$  unfolding  $cdcl_W$ -all-struct-inv-def  $cdcl_W$ -M-level-inv-def by auto
ultimately have  $\forall L \in \#mset\_ccls\ D. atm\_of\ L \notin atm\_of\ 'lits\_of\_l\ MS$ 
  unfolding  $M$  unfolding  $lits\_of\_def$  by auto
then have  $H$ :  $\bigwedge L. L \in \#mset\_ccls\ D \implies get\_level\ (trail\ S)\ L = get\_level\ M_T\ L$ 
  unfolding  $M$  by ( $fastforce\ simp$ :  $lits\_of\_def$ )
have [ $simp$ ]:  $get\_maximum\_level\ (trail\ S)\ (mset\_ccls\ D) = get\_maximum\_level\ M_T\ (mset\_ccls\ D)$ 
  using  $\langle M_T \models_{as} CNot\ (mset\_ccls\ D) \rangle\ M\ nm$  by ( $metis\ true\_annots\_CNot\_all\_atms\_defined$ 
     $get\_maximum\_level\_skip\_un\_marked\_not\_present$ )

have  $lev\_l'$ :  $get\_level\ M_T\ L = backtrack\_lvl\ S$ 
  using  $lev\_l\ LD$  by ( $auto\ simp$ :  $H$ )
have [ $simp$ ]:  $trail\ (reduce\_trail\_to\ M1\ T) = M1$ 
  using  $T\ decomp\ M\ nm$  by ( $smt\ M_T\ append\_assoc\ beginning\_not\_marked\_invert$ 
     $get\_all\_marked\_decomposition\_exists\_prepend\ reduce\_trail\_to\_trail\_tl\_trail\_decomp$ )
have  $W$ :  $W \sim cons\_trail\ (Propagated\ L\ (cls\_of\_ccls\ D))\ (reduce\_trail\_to\ M1$ 
  ( $add\_learned\_cls\ (cls\_of\_ccls\ D)\ (update\_backtrack\_lvl\ i\ (update\_conflicting\ None\ T))))$ 
  using  $W\ T\ i\ decomp\ undef$  by ( $auto\ simp\ del$ :  $state\_simp\ simp$ :  $state\_eq\_def$ )
have  $lev\_l-D'$ :  $get\_level\ M_T\ L = get\_maximum\_level\ M_T\ (mset\_ccls\ D)$ 
  using  $lev\_l-D\ LD$  by ( $auto\ simp$ :  $H$ )
have [ $simp$ ]:  $get\_maximum\_level\ (trail\ S)\ ?D = get\_maximum\_level\ M_T\ ?D$ 
  by ( $smt\ H\ get\_maximum\_level\_exists\_lit\ get\_maximum\_level\_ge\_get\_level\ in\_diffD\ le\_antisym$ 
     $not\_gr0\ not\_less$ )
then have  $i'$ :  $i = get\_maximum\_level\ M_T\ ?D$ 
  using  $i$  by auto
have  $Marked\ K\ (i + 1) \# M1 \in set\ (map\ fst\ (get\_all\_marked\_decomposition\ (trail\ S)))$ 
  using  $Set.imageI[OF\ decomp,\ of\ fst]$  by auto
then have  $Marked\ K\ (i + 1) \# M1 \in set\ (map\ fst\ (get\_all\_marked\_decomposition\ M_T))$ 
  using  $fst\_get\_all\_marked\_decomposition\_prepend\_not\_marked[OF\ nm]$  unfolding  $M$  by auto
then obtain  $M2'$  where  $decomp' : (Marked\ K\ (i+1) \# M1, M2') \in set\ (get\_all\_marked\_decomposition$ 
 $M_T)$ 
  by auto
then show  $backtrack\ T\ W$ 
  using  $T\ decomp'\ lev\_l'\ lev\_l-D'\ i'\ W\ LD\ undef$ 
  by ( $force\ intro!$ :  $backtrack.intros\ simp\ del$ :  $state\_simp\ simp$ :  $state\_eq\_def$ )
qed

lemma  $cdcl_W$ -bj-decomp-resolve-skip-and-bj:

```

```

assumes  $cdcl_W$ -bj**  $S$   $T$  and  $inv$ :  $cdcl_W$ -M-level- $inv$   $S$ 
shows ( $skip$ -or- $resolve$ **  $S$   $T$ 
   $\vee (\exists U. skip$ -or- $resolve$ **  $S$   $U \wedge backtrack$   $U$   $T$ ))
using  $assms$ 
proof  $induction$ 
  case  $base$ 
  then show ? $case$  by  $simp$ 
next
  case ( $step$   $T$   $U$ ) note  $st = this(1)$  and  $bj = this(2)$  and  $IH = this(3)$ 
  have  $IH$ :  $skip$ -or- $resolve$ **  $S$   $T$ 
  proof –
    { assume ( $\exists U. skip$ -or- $resolve$ **  $S$   $U \wedge backtrack$   $U$   $T$ )
      then obtain  $V$  where
         $bt$ :  $backtrack$   $V$   $T$  and
         $skip$ -or- $resolve$ **  $S$   $V$ 
        by  $blast$ 
        have  $cdcl_W$ **  $S$   $V$ 
        using ( $skip$ -or- $resolve$ **  $S$   $V$ )  $rtranclp$ - $skip$ -or- $resolve$ - $rtranclp$ - $cdcl_W$  by  $blast$ 
        then have  $cdcl_W$ -M-level- $inv$   $V$  and  $cdcl_W$ -M-level- $inv$   $S$ 
        using  $rtranclp$ - $cdcl_W$ -consistent- $inv$   $inv$  by  $blast$ +
        with  $bj$   $bt$  have  $False$  using  $backtrack$ -no- $cdcl_W$ - $bj$  by  $simp$ 
      }
    then show ? $thesis$  using  $IH$   $inv$  by  $blast$ 
  qed
show ? $case$ 
  using  $bj$ 
  proof ( $cases$   $rule$ :  $cdcl_W$ - $bj$ . $cases$ )
    case  $backtrack$ 
    then show ? $thesis$  using  $IH$  by  $blast$ 
  qed ( $metis$  ( $no$ -types,  $lifting$ )  $IH$   $rtranclp$ . $simps$   $skip$ -or- $resolve$ . $simps$ ) +
qed

```

**lemma**  $resolve$ - $skip$ -deterministic:  
 $resolve$   $S$   $T \implies skip$   $S$   $U \implies False$   
**by** ( $auto$   $elim$ !:  $skipE$   $resolveE$   $dest$ :  $hd$ -raw-trail)

**lemma**  $backtrack$ -unique:  
**assumes**  
 $bt$ - $T$ :  $backtrack$   $S$   $T$  **and**  
 $bt$ - $U$ :  $backtrack$   $S$   $U$  **and**  
 $inv$ :  $cdcl_W$ -all-struct- $inv$   $S$   
**shows**  $T \sim U$   
**proof** –  
**have**  $lev$ :  $cdcl_W$ -M-level- $inv$   $S$   
**using**  $inv$  **unfolding**  $cdcl_W$ -all-struct- $inv$ -def **by**  $auto$   
**then obtain**  $K$   $i$   $M1$   $M2$   $L$   $D$  **where**  
 $raw$ - $S$ :  $raw$ -conflicting  $S = Some$   $D$  **and**  
 $LD$ :  $L \in \#$   $mset$ -ccls  $D$  **and**  
 $decomp$ : ( $Marked$   $K$  ( $Suc$   $i$ )  $\#$   $M1$ ,  $M2$ )  $\in set$  ( $get$ -all-marked-decomposition ( $trail$   $S$ )) **and**  
 $lev$ - $l$ :  $get$ -level ( $trail$   $S$ )  $L = backtrack$ -lvl  $S$  **and**  
 $lev$ - $l$ - $D$ :  $get$ -level ( $trail$   $S$ )  $L = get$ -maximum-level ( $trail$   $S$ ) ( $mset$ -ccls  $D$ ) **and**  
 $i$ :  $get$ -maximum-level ( $trail$   $S$ ) ( $remove1$ -mset  $L$  ( $mset$ -ccls  $D$ ))  $\equiv i$  **and**  
 $undef$ :  $undefined$ -lit  $M1$   $L$  **and**  
 $T$ :  $T \sim cons$ -trail ( $Propagated$   $L$  ( $cls$ -of-ccls  $D$ ))  
 ( $reduce$ -trail-to  $M1$ )

```

      (add-learned-cls (cls-of-ccls D)
        (update-backtrack-lvl i
          (update-conflicting None S))))
    using bt-T by (elim backtrack-levE) (force simp: cdclW-M-level-inv-def)+

obtain  $K' i' M1' M2' L' D'$  where
  raw-S': raw-conflicting  $S = \text{Some } D'$  and
  LD':  $L' \in \# \text{ mset-ccls } D'$  and
  decomp':  $(\text{Marked } K' (\text{Suc } i') \# M1', M2') \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$  and
  lev-l:  $\text{get-level } (\text{trail } S) L' = \text{backtrack-lvl } S$  and
  lev-l-D:  $\text{get-level } (\text{trail } S) L' = \text{get-maximum-level } (\text{trail } S) (\text{mset-ccls } D')$  and
  i':  $\text{get-maximum-level } (\text{trail } S) (\text{remove1-mset } L' (\text{mset-ccls } D')) \equiv i'$  and
  undef': undefined-lit  $M1' L'$  and
  U:  $U \sim \text{cons-trail } (\text{Propagated } L' (\text{cls-of-ccls } D'))$ 
    (reduce-trail-to  $M1'$ 
      (add-learned-cls (cls-of-ccls  $D'$ )
        (update-backtrack-lvl  $i'$ 
          (update-conflicting None S))))
    using bt-U lev by (elim backtrack-levE) (force simp: cdclW-M-level-inv-def)+
obtain  $c$  where  $M: \text{trail } S = c @ M2 @ \text{Marked } K' (i + 1) \# M1$ 
  using decomp by auto
obtain  $c'$  where  $M': \text{trail } S = c' @ M2' @ \text{Marked } K' (i' + 1) \# M1'$ 
  using decomp' by auto
have marked:  $\text{get-all-levels-of-marked } (\text{trail } S) = \text{rev } [1..<1+\text{backtrack-lvl } S]$ 
  using inv unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def by auto
then have  $i < \text{backtrack-lvl } S$ 
  unfolding  $M$  by (force simp add: rev-swap[symmetric] dest!: arg-cong[of - - set])

have [simp]:  $L' = L$ 
proof (rule ccontr)
  assume  $\neg ?thesis$ 
  then have  $L' \in \# \text{ remove1-mset } L (\text{mset-ccls } D)$ 
    using raw-S raw-S' LD LD' by (simp add: in-remove1-mset-neq)
  then have  $\text{get-maximum-level } (\text{trail } S) (\text{remove1-mset } L (\text{mset-ccls } D)) \geq \text{backtrack-lvl } S$ 
    using  $\langle \text{get-level } (\text{trail } S) L' = \text{backtrack-lvl } S \rangle$  get-maximum-level-ge-get-level
    by metis
  then show  $\text{False}$  using  $i' i \langle i < \text{backtrack-lvl } S \rangle$  by auto
qed
then have [simp]:  $\text{mset-ccls } D' = \text{mset-ccls } D$ 
  using raw-S raw-S' by auto
have [simp]:  $i' = i$ 
  using  $i i'$  by auto

```

Automation in a step later...

```

have  $H: \bigwedge a A B. \text{insert } a A = B \implies a : B$ 
  by blast
have  $\text{get-all-levels-of-marked } (c @ M2) = \text{rev } [i+2..<1+\text{backtrack-lvl } S]$  and
   $\text{get-all-levels-of-marked } (c' @ M2') = \text{rev } [i+2..<1+\text{backtrack-lvl } S]$ 
  using marked unfolding  $M$ 
  using marked unfolding  $M'$ 
  unfolding rev-swap[symmetric] by (auto dest: append-cons-eq-upt-length-i-end)
from arg-cong[OF this(1), of set] arg-cong[OF this(2), of set]
have
  dropWhile  $(\lambda L. \neg \text{is-marked } L \vee \text{level-of } L \neq \text{Suc } i) (c @ M2) = []$  and

```

$\text{dropWhile } (\lambda L. \neg \text{is-marked } L \vee \text{level-of } L \neq \text{Suc } i) (c' @ M2') = []$   
**unfolding**  $\text{dropWhile-eq-Nil-conv Ball-def}$   
**by**  $(\text{intro allI}; \text{rename-tac } x; \text{case-tac } x; \text{auto dest!}; H \text{ simp add: in-set-conv-decomp})+$

**then have**  $[\text{simp}]: M1' = M1$   
**using**  $\text{arg-cong}[OF M, \text{ of dropWhile } (\lambda L. \neg \text{is-marked } L \vee \text{level-of } L \neq \text{Suc } i)]$   
**unfolding**  $M'$  **by**  $\text{auto}$   
**show**  $?thesis$  **using**  $T U \text{ undef inv decomp by } (\text{auto simp del: state-simp simp: state-eq-def}$   
 $\text{cdcl}_W\text{-all-struct-inv-def cdcl}_W\text{-M-level-inv-decomp})$   
**qed**

**lemma** *if-can-apply-backtrack-no-more-resolve:*  
**assumes**  
 $\text{skip: skip}^{**} S U$  **and**  
 $\text{bt: backtrack } S T$  **and**  
 $\text{inv: cdcl}_W\text{-all-struct-inv } S$   
**shows**  $\neg \text{resolve } U V$

**proof**  $(\text{rule ccontr})$   
**assume**  $\text{resolve: } \neg \neg \text{resolve } U V$

**obtain**  $L E D$  **where**  
 $U: \text{trail } U \neq []$  **and**  
 $\text{tr-}U: \text{hd-raw-trail } U = \text{Propagated } L E$  **and**  
 $LE: L \in \# \text{ mset-cls } E$  **and**  
 $\text{raw-}U: \text{raw-conflicting } U = \text{Some } D$  **and**  
 $LD: -L \in \# \text{ mset-ccls } D$  **and**  
 $\text{get-maximum-level } (\text{trail } U) (\text{mset-ccls } (\text{remove-clit } (-L) D)) = \text{backtrack-lvl } U$  **and**  
 $V: V \sim \text{update-conflicting } (\text{Some } (\text{union-ccls } (\text{remove-clit } (-L) D) (\text{ccls-of-cls } (\text{remove-lit } L E))))$   
 $(\text{tl-trail } U)$   
**using**  $\text{resolve by } (\text{auto elim!}; \text{resolveE})$

**have**  $\text{cdcl}_W\text{-all-struct-inv } U$   
**using**  $\text{mono-rtranclp}[of \text{ skip cdcl}_W]$  **by**  $(\text{meson } bj \text{ cdcl}_W\text{-bj.skip inv local.skip other}$   
 $\text{rtranclp-cdcl}_W\text{-all-struct-inv-inv})$

**then have**  $[\text{iff}]: \text{no-dup } (\text{trail } S) \text{ cdcl}_W\text{-M-level-inv } S$  **and**  $[\text{iff}]: \text{no-dup } (\text{trail } U)$   
**using**  $\text{inv unfolding cdcl}_W\text{-all-struct-inv-def cdcl}_W\text{-M-level-inv-def by blast+}$

**then have**  
 $S: \text{init-clss } U = \text{init-clss } S$   
 $\text{learned-clss } U = \text{learned-clss } S$   
 $\text{backtrack-lvl } U = \text{backtrack-lvl } S$   
 $\text{conflicting } S = \text{Some } (\text{mset-ccls } D)$   
**using**  $\text{rtranclp-skip-state-decomp}[OF \text{ skip}] U \text{ raw-}U$   
**by**  $(\text{auto simp del: state-simp simp: state-eq-def})$

**obtain**  $M_0$  **where**  
 $\text{tr-}S: \text{trail } S = M_0 @ \text{trail } U$  **and**  
 $\text{nm: } \forall m \in \text{set } M_0. \neg \text{is-marked } m$   
**using**  $\text{rtranclp-skip-state-decomp}[OF \text{ skip}]$  **by**  $\text{blast}$

**obtain**  $K' i' M1' M2' L' D'$  **where**  
 $\text{raw-}S': \text{raw-conflicting } S = \text{Some } D'$  **and**  
 $LD': L' \in \# \text{ mset-ccls } D'$  **and**  
 $\text{decomp}': (\text{Marked } K' (\text{Suc } i') \# M1', M2') \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } S))$  **and**  
 $\text{lev-l: get-level } (\text{trail } S) L' = \text{backtrack-lvl } S$  **and**  
 $\text{lev-l-D: get-level } (\text{trail } S) L' = \text{get-maximum-level } (\text{trail } S) (\text{mset-ccls } D')$  **and**  
 $i': \text{get-maximum-level } (\text{trail } S) (\text{remove1-mset } L' (\text{mset-ccls } D')) \equiv i'$  **and**

$undef'$ : undefined-lit  $M1' L'$  **and**  
 $R: T \sim cons-trail (Propagated L' (cls-of-ccls D'))$   
 $(reduce-trail-to M1'$   
 $(add-learned-ccls (cls-of-ccls D')$   
 $(update-backtrack-lvl i'$   
 $(update-conflicting None S))))$   
**using**  $bt$  **by**  $(elim backtrack-levE) (fastforce simp: S state-eq-def simp del:state-simp)+$   
**obtain**  $c$  **where**  $M: trail S = c @ M2' @ Marked K' (i' + 1) \# M1'$   
**using**  $get-all-marked-decomposition-exists-prepend[OF decomp]$  **by**  $auto$   
**have**  $marked: get-all-levels-of-marked (trail S) = rev [1..<1+backtrack-lvl S]$   
**using**  $inv unfolding cdcl_W-all-struct-inv-def cdcl_W-M-level-inv-def$  **by**  $auto$   
**then have**  $i' < backtrack-lvl S$   
**unfolding**  $M$  **by**  $(force simp add: rev-swap[symmetric] dest!: arg-cong[of - - set])$

**have**  $U: trail U = Propagated L (mset-ccls E) \# trail V$   
**using**  $tr-S hd-raw-trail[OF U] U S V tr-U$  **by**  $(auto simp: lits-of-def)$   
**have**  $DD'[simp]: mset-ccls D' = mset-ccls D$   
**using**  $raw-U raw-S' S$  **by**  $auto$   
**have**  $[simp]: L' = -L$   
**proof**  $(rule ccontr)$   
**assume**  $\neg ?thesis$   
**then have**  $-L \in \# remove1-mset L' (mset-ccls D')$   
**using**  $DD' LD' LD$  **by**  $(simp add: in-remove1-mset-neq)$   
**moreover**  
**have**  $M': trail S = M_0 @ Propagated L (mset-ccls E) \# trail V$   
**using**  $tr-S unfolding U$  **by**  $auto$   
**have**  $no-dup (trail S)$   
**using**  $inv U unfolding cdcl_W-all-struct-inv-def cdcl_W-M-level-inv-def$  **by**  $auto$   
**then have**  $atm-L-notin-M: atm-of L \notin atm-of ' (lits-of-l (trail V))$   
**using**  $M' U S$  **by**  $(auto simp: lits-of-def)$   
**have**  $get-all-levels-of-marked (trail S) = rev [1..<1+backtrack-lvl S]$   
**using**  $inv U unfolding cdcl_W-all-struct-inv-def cdcl_W-M-level-inv-def$  **by**  $auto$   
**then have**  $get-all-levels-of-marked (trail U) = rev [1..<1+backtrack-lvl S]$   
**using**  $nm M' U$  **by**  $(simp add: get-all-levels-of-marked-no-marked)$   
**then have**  $get-lev-L:$   
 $get-level(Propagated L (mset-ccls E) \# trail V) L = backtrack-lvl S$   
**using**  $get-level-get-rev-level-get-all-levels-of-marked[OF atm-L-notin-M,$   
 $of [Propagated L (mset-ccls E)]] U$  **by**  $auto$   
**have**  $atm-of L \notin atm-of ' (lits-of-l (rev M_0))$   
**using**  $\langle no-dup (trail S) \rangle M'$  **by**  $(auto simp: lits-of-def)$   
**then have**  $get-level (trail S) L = backtrack-lvl S$   
**by**  $(metis M' get-lev-L get-rev-level-notin-end rev-append)$   
**ultimately**  
**have**  $get-maximum-level (trail S) (remove1-mset L' (mset-ccls D')) \geq backtrack-lvl S$   
**by**  $(metis get-maximum-level-ge-get-level get-rev-level-uminus)$   
**then show**  $False$   
**using**  $\langle i' < backtrack-lvl S \rangle i'$  **by**  $auto$   
**qed**

**have**  $cdcl_W^{**} S U$   
**using**  $bj cdcl_W-bj.skip local.skip mono-rtrancp[of skip cdcl_W S U]$  **other by**  $meson$   
**then have**  $cdcl_W-all-struct-inv U$   
**using**  $inv rtrancp-cdcl_W-all-struct-inv-inv$  **by**  $blast$   
**then have**  $Propagated L (mset-ccls E) \# trail V \models_{as} CNot (mset-ccls D')$   
**using**  $cdcl_W-all-struct-inv-def cdcl_W-conflicting-def raw-U U$  **by**  $auto$   
**then have**  $\forall L' \in \# (remove1-mset L' (mset-ccls D')) . atm-of L' \in atm-of ' lits-of-l (Propagated L$

```

(mset-cls E) # trail U)
  using U atm-of-in-atm-of-set-iff-in-set-or-uminus-in-set in-CNot-implies-uminus(2)
  by (fastforce dest: in-diffD)
then have get-maximum-level (trail S) (remove1-mset L' (mset-ccls D')) = backtrack-lvl S
  using get-maximum-level-skip-un-marked-not-present[of remove1-mset L' (mset-ccls D')
    trail U M0] tr-S nm U
  ⟨get-maximum-level (trail U) (mset-ccls (remove-clit (- L) D)) = backtrack-lvl U⟩
  by (auto simp: S)
then show False
  using i' ⟨i' < backtrack-lvl S⟩ by auto
qed

```

**lemma** *if-can-apply-resolve-no-more-backtrack:*

```

assumes
  skip: skip** S U and
  resolve: resolve S T and
  inv: cdclW-all-struct-inv S
shows ¬backtrack U V
using assms
by (meson if-can-apply-backtrack-no-more-resolve rtranclp.rtrancl-refl
  rtranclp-skip-backtrack-backtrack)

```

**lemma** *if-can-apply-backtrack-skip-or-resolve-is-skip:*

```

assumes
  bt: backtrack S T and
  skip: skip-or-resolve** S U and
  inv: cdclW-all-struct-inv S
shows skip** S U
using assms(2,3,1)
by induction (simp-all add: if-can-apply-backtrack-no-more-resolve skip-or-resolve.simps)

```

**lemma** *cdcl<sub>W</sub>-bj-bj-decomp:*

```

assumes cdclW-bj** S W and cdclW-all-struct-inv S
shows
  (∃ T U V. (λS T. skip-or-resolve S T ∧ no-step backtrack S)** S T
    ∧ (λT U. resolve T U ∧ no-step backtrack T) T U
    ∧ skip** U V ∧ backtrack V W)
  ∨ (∃ T U. (λS T. skip-or-resolve S T ∧ no-step backtrack S)** S T
    ∧ (λT U. resolve T U ∧ no-step backtrack T) T U ∧ skip** U W)
  ∨ (∃ T. skip** S T ∧ backtrack T W)
  ∨ skip** S W (is ?RB S W ∨ ?R S W ∨ ?SB S W ∨ ?S S W)

```

using assms

**proof** *induction*

**case** *base*

**then show** ?case **by** *simp*

**next**

**case** (step W X) **note** st = this(1) **and** bj = this(2) **and** IH = this(3)[OF this(4)] **and** inv = this(4)

**have** ¬?RB S W **and** ¬?SB S W

**proof** (*clarify, goal-cases*)

**case** (1 T U V)

**have** skip-or-resolve\*\* S T

**using** 1(1) **by** (auto dest!: rtranclp-and-rtranclp-left)

**then show** False

**by** (metis (no-types, lifting) 1(2) 1(4) 1(5) backtrack-no-cdcl<sub>W</sub>-bj

```

    cdclW-all-struct-inv-def cdclW-all-struct-inv-inv cdclW-o.bj local.bj other
    resolve rtrancpl-cdclW-all-struct-inv-inv rtrancpl-skip-backtrack-backtrack
    rtrancpl-skip-or-resolve-rtrancpl-cdclW step.premis)
next
  case 2
  then show ?case by (meson assms(2) cdclW-all-struct-inv-def backtrack-no-cdclW-bj
    local.bj rtrancpl-skip-backtrack-backtrack)
qed
then have IH: ?R S W  $\vee$  ?S S W using IH by blast

have cdclW** S W using mono-rtrancpl[of cdclW-bj cdclW] st by blast
then have inv-W: cdclW-all-struct-inv W by (simp add: rtrancpl-cdclW-all-struct-inv-inv
  step.premis)
consider
  (BT) X' where backtrack W X'
| (skip) no-step backtrack W and skip W X
| (resolve) no-step backtrack W and resolve W X
using bj cdclW-bj.cases by meson
then show ?case
proof cases
  case (BT X')
  then consider
    (bt) backtrack W X
  | (sk) skip W X
  using bj if-can-apply-backtrack-no-more-resolve[of W W X' X] inv-W cdclW-bj.cases by fast
then show ?thesis
proof cases
  case bt
  then show ?thesis using IH by auto
next
  case sk
  then show ?thesis using IH by (meson rtrancpl-trans r-into-rtrancpl)
qed
next
  case skip
  then show ?thesis using IH by (meson rtrancpl.rtrancpl-into-rtrancpl)
next
  case resolve note no-bt = this(1) and res = this(2)
  consider
    (RS) T U where
      ( $\lambda S T$ . skip-or-resolve S T  $\wedge$  no-step backtrack S)** S T and
      resolve T U and
      no-step backtrack T and
      skip** U W
  | (S) skip** S W
  using IH by auto
then show ?thesis
proof cases
  case (RS T U)
  have cdclW** S T
  using RS(1) cdclW-bj.resolve cdclW-o.bj other skip
  mono-rtrancpl[of ( $\lambda S T$ . skip-or-resolve S T  $\wedge$  no-step backtrack S) cdclW S T]
  by (meson skip-or-resolve.cases)
  then have cdclW-all-struct-inv U
  by (meson RS(2) cdclW-all-struct-inv-inv cdclW-bj.resolve cdclW-o.bj other

```



```

    rtrancpl-cdclW-all-struct-inv-inv step.prem)
{ fix U'
  assume skip** U U' and skip** U' W
  have cdclW-all-struct-inv U'
    using ⟨cdclW-all-struct-inv U⟩ ⟨skip** U U'⟩ rtrancpl-cdclW-all-struct-inv-inv
      cdclW-o.bj rtrancpl-mono[of skip cdclW] other skip by blast
  then have no-step backtrack U'
    using if-can-apply-backtrack-no-more-resolve[OF ⟨skip** U' W⟩] res by blast
}
with ⟨skip** U W⟩
have (λS T. skip-or-resolve S T ∧ no-step backtrack S)** U W
  proof induction
    case base
    then show ?case by simp
  next
  case (step V W) note st = this(1) and skip = this(2) and IH = this(3) and H = this(4)
  have ∧U'. skip** U' V ⇒ skip** U' W
    using skip by auto
  then have (λS T. skip-or-resolve S T ∧ no-step backtrack S)** U V
    using IH H by blast
  moreover have (λS T. skip-or-resolve S T ∧ no-step backtrack S)** V W
    by (simp add: local.skip r-into-rtrancpl st step.prem skip-or-resolve.intros)
  ultimately show ?case by simp
qed
then show ?thesis
proof -
  have f1: ∀ p pa pb pc. ¬ p (pa) pb ∨ ¬ p** pb pc ∨ p** pa pc
    by (meson converse-rtrancpl-into-rtrancpl)
  have skip-or-resolve T U ∧ no-step backtrack T
    using RS(2) RS(3) by force
  then have (λp pa. skip-or-resolve p pa ∧ no-step backtrack p)** T W
    proof -
      have (∃ vr19 vr16 vr17 vr18. vr19 (vr16::'st) vr17 ∧ vr19** vr17 vr18
        ∧ ¬ vr19** vr16 vr18)
        ∨ ¬ (skip-or-resolve T U ∧ no-step backtrack T)
        ∨ ¬ (λuu uua. skip-or-resolve uu uua ∧ no-step backtrack uu)** U W
        ∨ (λuu uua. skip-or-resolve uu uua ∧ no-step backtrack uu)** T W
        by force
      then show ?thesis
        by (metis (no-types) ⟨(λS T. skip-or-resolve S T ∧ no-step backtrack S)** U W⟩
          ⟨skip-or-resolve T U ∧ no-step backtrack T⟩ f1)
    qed
  then have (λp pa. skip-or-resolve p pa ∧ no-step backtrack p)** S W
    using RS(1) by force
  then show ?thesis
    using no-bt res by blast
qed
next
case S
{ fix U'
  assume skip** S U' and skip** U' W
  then have cdclW** S U'
    using mono-rtrancpl[of skip cdclW S U'] by (simp add: cdclW-o.bj other skip)
  then have cdclW-all-struct-inv U'

```

```

    by (metis (no-types, hide-lams) ⟨cdclW-all-struct-inv S⟩
      rtrancpl-cdclW-all-struct-inv-inv)
  then have no-step backtrack U'
    using if-can-apply-backtrack-no-more-resolve[OF ⟨skip** U' W⟩] res by blast
}
with S
have (λS T. skip-or-resolve S T ∧ no-step backtrack S)** S W
  proof induction
    case base
    then show ?case by simp
  next
    case (step V W) note st = this(1) and skip = this(2) and IH = this(3) and H = this(4)
    have ∧ U'. skip** U' V ⇒ skip** U' W
      using skip by auto
    then have (λS T. skip-or-resolve S T ∧ no-step backtrack S)** S V
      using IH H by blast
    moreover have (λS T. skip-or-resolve S T ∧ no-step backtrack S)** V W

      by (simp add: local.skip r-into-rtrancpl st step.prem skip-or-resolve.intros)
    ultimately show ?case by simp
  qed
then show ?thesis using res no-bt by blast
qed
qed
qed

```

The case distinction is needed, since  $T \sim V$  does not imply that  $R^{**} T V$ .

**lemma** *cdcl<sub>W</sub>-bj-strongly-confluent*:

```

  assumes
    cdclW-bj** S V and
    cdclW-bj** S T and
    n-s: no-step cdclW-bj V and
    inv: cdclW-all-struct-inv S
  shows T ~ V ∨ cdclW-bj** T V
  using assms(2)
proof induction
  case base
  then show ?case by (simp add: assms(1))
next
  case (step T U) note st = this(1) and s-o-r = this(2) and IH = this(3)
  have cdclW** S T
    using st mono-rtrancpl[of cdclW-bj cdclW] other by blast
  then have lev-T: cdclW-M-level-inv T
    using inv rtrancpl-cdclW-consistent-inv[of S T]
    unfolding cdclW-all-struct-inv-def by auto

  consider
    (TV) T ~ V
    | (bj-TV) cdclW-bj** T V
  using IH by blast
then show ?case
proof cases
  case TV
  have no-step cdclW-bj T
    using ⟨cdclW-M-level-inv T⟩ n-s cdclW-bj-state-eq-compatible[of T - V] TV

```

```

    by (meson backtrack-state-eq-compatible cdclW-bj.simps resolve-state-eq-compatible
        skip-state-eq-compatible state-eq-ref)
  then show ?thesis
    using s-o-r by auto
next
case bj-TV
then obtain U' where
  T-U': cdclW-bj T U' and
  cdclW-bj** U' V
  using IH n-s s-o-r by (metis rtrancpl-unfold trancplD)
have cdclW** S T
  by (metis (no-types, hide-lams) bj mono-rtrancpl[of cdclW-bj cdclW] other st)
then have inv-T: cdclW-all-struct-inv T
  by (metis (no-types, hide-lams) inv rtrancpl-cdclW-all-struct-inv-inv)

have lev-U: cdclW-M-level-inv U
  using s-o-r cdclW-consistent-inv lev-T other by blast
show ?thesis
  using s-o-r
  proof cases
    case backtrack
    then obtain V0 where skip** T V0 and backtrack V0 V
      using IH if-can-apply-backtrack-skip-or-resolve-is-skip[OF backtrack - inv-T]
        cdclW-bj-decomp-resolve-skip-and-bj
      by (meson bj-TV cdclW-bj.backtrack inv-T lev-T n-s
          rtrancpl-skip-backtrack-backtrack-end)
    then have cdclW-bj** T V0 and cdclW-bj V0 V
      using rtrancpl-mono[of skip cdclW-bj] by blast+
    then show ?thesis
      using ⟨backtrack V0 V⟩ ⟨skip** T V0⟩ backtrack-unique inv-T local.backtrack
        rtrancpl-skip-backtrack-backtrack by auto
  next
    case resolve
    then have U ~ U'
      by (meson T-U' cdclW-bj.simps if-can-apply-backtrack-no-more-resolve inv-T
          resolve-skip-deterministic resolve-unique rtrancpl.rtrancpl-refl)
    then show ?thesis
      using ⟨cdclW-bj** U' V⟩ unfolding rtrancpl-unfold
      by (meson T-U' bj cdclW-consistent-inv lev-T other state-eq-ref state-eq-sym
          trancpl-cdclW-bj-state-eq-compatible)
  next
    case skip
    consider
      (sk) skip T U'
    | (bt) backtrack T U'
    using T-U' by (meson cdclW-bj.cases local.skip resolve-skip-deterministic)
    then show ?thesis
      proof cases
        case sk
        then show ?thesis
          using ⟨cdclW-bj** U' V⟩ unfolding rtrancpl-unfold
          by (meson T-U' bj cdclW-all-inv(3) cdclW-all-struct-inv-def inv-T local.skip other
              trancpl-cdclW-bj-state-eq-compatible skip-unique state-eq-ref)
      next
        case bt

```

```

    have skip++ T U
      using local.skip by blast
    have cdclW-bj U U'
      by (meson ⟨skip++ T U⟩ backtrack bt inv-T rtrancpl-skip-backtrack-backtrack-end
            trancpl-into-rtrancpl)
    then have cdclW-bj++ U V
      using ⟨cdclW-bj** U' V⟩ by auto
    then show ?thesis
      by (meson trancpl-into-rtrancpl)
  qed
qed
qed
qed

```

**lemma** *cdcl<sub>W</sub>-bj-unique-normal-form*:

```

assumes
  ST: cdclW-bj** S T and SU: cdclW-bj** S U and
  n-s-U: no-step cdclW-bj U and
  n-s-T: no-step cdclW-bj T and
  inv: cdclW-all-struct-inv S
shows T ~ U

```

**proof** –

```

  have T ~ U ∨ cdclW-bj** T U
    using ST SU cdclW-bj-strongly-confluent inv n-s-U by blast
  then show ?thesis
    by (metis (no-types) n-s-T rtrancpl-unfold state-eq-ref trancpl-unfold-begin)

```

**qed**

**lemma** *full-cdcl<sub>W</sub>-bj-unique-normal-form*:

```

assumes full cdclW-bj S T and full cdclW-bj S U and
  inv: cdclW-all-struct-inv S
shows T ~ U
  using cdclW-bj-unique-normal-form assms unfolding full-def by blast

```

### 21.3 CDCL FW

**inductive** *cdcl<sub>W</sub>-merge-restart* :: 'st ⇒ 'st ⇒ bool **where**

*fw-r-propagate*: propagate S S' ⇒ cdcl<sub>W</sub>-merge-restart S S' |

*fw-r-conflict*: conflict S T ⇒ full cdcl<sub>W</sub>-bj T U ⇒ cdcl<sub>W</sub>-merge-restart S U |

*fw-r-decide*: decide S S' ⇒ cdcl<sub>W</sub>-merge-restart S S' |

*fw-r-rf*: cdcl<sub>W</sub>-rf S S' ⇒ cdcl<sub>W</sub>-merge-restart S S'

**lemma** *rtrancpl-cdcl<sub>W</sub>-bj-rtrancpl-cdcl<sub>W</sub>*:

```

  cdclW-bj** S T ⇒ cdclW** S T
  using mono-rtrancpl[of cdclW-bj cdclW] by blast

```

**lemma** *cdcl<sub>W</sub>-merge-restart-cdcl<sub>W</sub>*:

```

assumes cdclW-merge-restart S T
shows cdclW** S T
  using assms

```

**proof** *induction*

**case** (*fw-r-conflict* S T U) **note** *confl* = *this*(1) **and** *bj* = *this*(2)

**have** cdcl<sub>W</sub> S T **using** *confl* **by** (*simp* add: cdcl<sub>W</sub>.intros r-into-rtrancpl)

**moreover**

**have** cdcl<sub>W</sub>-bj<sup>\*\*</sup> T U **using** *bj* **unfolding** *full-def* **by** *auto*

then have  $cdcl_W^{**} T U$  **using**  $rtrancpl-cdcl_W-bj-rtrancpl-cdcl_W$  **by** *blast*  
ultimately show *?case* **by** *auto*  
**qed** (*simp-all add: cdcl\_W-o.intros cdcl\_W.intros r-into-rtrancpl*)

**lemma**  $cdcl_W\text{-merge-restart-conflicting-true-or-no-step}$ :

**assumes**  $cdcl_W\text{-merge-restart } S T$   
**shows**  $conflicting T = None \vee no\text{-step } cdcl_W T$   
**using** *assms*

**proof** *induction*

**case** ( $fw\text{-r-conflict } S T U$ ) **note**  $confl = this(1)$  **and**  $n\text{-s} = this(2)$   
{ **fix**  $D V$   
**assume**  $cdcl_W U V$  **and**  $conflicting U = Some D$   
**then have** *False*  
**using**  $n\text{-s}$  **unfolding** *full-def*  
**by** (*induction rule: cdcl\_W-all-rules-induct*)  
(*auto dest!: cdcl\_W-bj.intros elim: decideE propagateE conflictE forgetE restartE*)  
}  
**then show** *?case* **by** (*cases conflicting U*) *fastforce+*  
**qed** (*auto simp add: cdcl\_W-rf.simps elim: propagateE decideE restartE forgetE*)

**inductive**  $cdcl_W\text{-merge} :: 'st \Rightarrow 'st \Rightarrow bool$  **where**

*fw-propagate*:  $propagate S S' \Longrightarrow cdcl_W\text{-merge } S S' \mid$   
*fw-conflict*:  $conflict S T \Longrightarrow full\ cdcl_W\text{-bj } T U \Longrightarrow cdcl_W\text{-merge } S U \mid$   
*fw-decide*:  $decide S S' \Longrightarrow cdcl_W\text{-merge } S S' \mid$   
*fw-forget*:  $forget S S' \Longrightarrow cdcl_W\text{-merge } S S'$

**lemma**  $cdcl_W\text{-merge-cdcl_W-merge-restart}$ :

$cdcl_W\text{-merge } S T \Longrightarrow cdcl_W\text{-merge-restart } S T$   
**by** (*meson cdcl\_W-merge.cases cdcl\_W-merge-restart.simps forget*)

**lemma**  $rtrancpl-cdcl_W\text{-merge-trancpl-cdcl_W-merge-restart}$ :

$cdcl_W\text{-merge}^{**} S T \Longrightarrow cdcl_W\text{-merge-restart}^{**} S T$   
**using**  $rtrancpl\text{-mono}[of\ cdcl_W\text{-merge } cdcl_W\text{-merge-restart}]$   $cdcl_W\text{-merge-cdcl_W-merge-restart}$  **by** *blast*

**lemma**  $cdcl_W\text{-merge-rtrancpl-cdcl_W}$ :

$cdcl_W\text{-merge } S T \Longrightarrow cdcl_W^{**} S T$   
**using**  $cdcl_W\text{-merge-cdcl_W-merge-restart}$   $cdcl_W\text{-merge-restart-cdcl_W}$  **by** *blast*

**lemma**  $rtrancpl-cdcl_W\text{-merge-rtrancpl-cdcl_W}$ :

$cdcl_W\text{-merge}^{**} S T \Longrightarrow cdcl_W^{**} S T$   
**using**  $rtrancpl\text{-mono}[of\ cdcl_W\text{-merge } cdcl_W^{**}]$   $cdcl_W\text{-merge-rtrancpl-cdcl_W}$  **by** *auto*

**lemmas**  $rulesE =$

*skipE resolveE backtrackE propagateE conflictE decideE restartE forgetE*

**lemma**  $cdcl_W\text{-all-struct-inv-trancpl-cdcl_W-merge-trancpl-cdcl_W-merge-cdcl_W-all-struct-inv}$ :

**assumes**  
*inv*:  $cdcl_W\text{-all-struct-inv } b$   
 $cdcl_W\text{-merge}^{++} b a$   
**shows**  $(\lambda S T. cdcl_W\text{-all-struct-inv } S \wedge cdcl_W\text{-merge } S T)^{++} b a$   
**using** *assms(2)*

**proof** *induction*

**case** *base*  
**then show** *?case* **using** *inv* **by** *auto*

**next**

```

case (step c d) note st = this(1) and fw = this(2) and IH = this(3)
have cdclW-all-struct-inv c
  using tranclp-into-rtranclp[OF st] cdclW-merge-rtranclp-cdclW
  assms(1) rtranclp-cdclW-all-struct-inv-inv rtranclp-mono[of cdclW-merge cdclW**] by fastforce
then have (λS T. cdclW-all-struct-inv S ∧ cdclW-merge S T)++ c d
  using fw by auto
then show ?case using IH by auto
qed

lemma backtrack-is-full1-cdclW-bj:
  assumes bt: backtrack S T and inv: cdclW-M-level-inv S
  shows full1 cdclW-bj S T
  using bt inv backtrack-no-cdclW-bj unfolding full1-def by blast

lemma rtrancl-cdclW-conflicting-true-cdclW-merge-restart:
  assumes cdclW** S V and inv: cdclW-M-level-inv S and conflicting S = None
  shows (cdclW-merge-restart** S V ∧ conflicting V = None)
    ∨ (∃ T U. cdclW-merge-restart** S T ∧ conflicting V ≠ None ∧ conflict T U ∧ cdclW-bj** U V)
  using assms
proof induction
  case base
  then show ?case by simp
next
  case (step U V) note st = this(1) and cdclW = this(2) and IH = this(3)[OF this(4-)] and
    confl[simp] = this(5) and inv = this(4)
  from cdclW
  show ?case
  proof (cases)
    case propagate
    moreover then have conflicting U = None and conflicting V = None
      by (auto elim: propagateE)
    ultimately show ?thesis using IH cdclW-merge-restart.fw-r-propagate[of U V] by auto
  next
    case conflict
    moreover then have conflicting U = None and conflicting V ≠ None
      by (auto elim!: conflictE simp del: state-simp simp: state-eq-def)
    ultimately show ?thesis using IH by auto
  next
    case other
    then show ?thesis
    proof cases
      case decide
      then show ?thesis using IH cdclW-merge-restart.fw-r-decide[of U V] by (auto elim: decideE)
    next
      case bj
      moreover {
        assume skip-or-resolve U V
        have f1: cdclW-bj++ U V
          by (simp add: local.bj tranclp.r-into-trancl)
        obtain T T' :: 'st where
          f2: cdclW-merge-restart** S U
            ∨ cdclW-merge-restart** S T ∧ conflicting U ≠ None
            ∧ conflict T T' ∧ cdclW-bj** T' U
        using IH confl by blast
        have conflicting V ≠ None ∧ conflicting U ≠ None

```

```

    using ⟨skip-or-resolve U V⟩
    by (auto simp: skip-or-resolve.simps state-eq-def elim!: skipE resolveE
        simp del: state-simp)
  then have ?thesis
    by (metis (full-types) IH f1 rtranclp-trans tranclp-into-rtranclp)
}
moreover {
  assume backtrack U V
  then have conflicting U ≠ None by (auto elim: backtrackE)
  then obtain T T' where
    cdclW-merge-restart** S T and
    conflicting U ≠ None and
    conflict T T' and
    cdclW-bj** T' U
  using IH confl by meson
  have invU: cdclW-M-level-inv U
    using inv rtranclp-cdclW-consistent-inv step.hyps(1) by blast
  then have conflicting V = None
    using ⟨backtrack U V⟩ inv by (auto elim: backtrack-levE
        simp: cdclW-M-level-inv-decomp)
  have full cdclW-bj T' V
    apply (rule rtranclp-fullI[of cdclW-bj T' U V])
    using ⟨cdclW-bj** T' U⟩ apply fast
    using ⟨backtrack U V⟩ backtrack-is-full1-cdclW-bj invU unfolding full1-def full-def
    by blast
  then have ?thesis
    using cdclW-merge-restart.fw-r-conflict[of T T' V] ⟨conflict T T'⟩
    ⟨cdclW-merge-restart** S T⟩ ⟨conflicting V = None⟩ by auto
}
ultimately show ?thesis by (auto simp: cdclW-bj.simps)
qed
next
case rf
moreover then have conflicting U = None and conflicting V = None
  by (auto simp: cdclW-rf.simps elim: restartE forgetE)
ultimately show ?thesis using IH cdclW-merge-restart.fw-r-rf[of U V] by auto
qed
qed

lemma no-step-cdclW-no-step-cdclW-merge-restart: no-step cdclW S ⇒ no-step cdclW-merge-restart S
  by (auto simp: cdclW.simps cdclW-merge-restart.simps cdclW-o.simps cdclW-bj.simps)

lemma no-step-cdclW-merge-restart-no-step-cdclW:
  assumes
    conflicting S = None and
    cdclW-M-level-inv S and
    no-step cdclW-merge-restart S
  shows no-step cdclW S
proof -
  { fix S'
    assume conflict S S'
    then have cdclW S S' using cdclW.conflict by auto
    then have cdclW-M-level-inv S'
      using assms(2) cdclW-consistent-inv by blast
  }

```

```

    then obtain  $S''$  where  $\text{full } \text{cdcl}_W\text{-bj } S' S''$ 
    using  $\text{cdcl}_W\text{-bj-exists-normal-form[of } S']$  by auto
    then have  $\text{False}$ 
    using  $\langle \text{conflict } S S' \rangle \text{ assms}(3) \text{ fw-r-conflict}$  by blast
  }
  then show ?thesis
  using assms unfolding  $\text{cdcl}_W.\text{simps}$   $\text{cdcl}_W\text{-merge-restart.simps}$   $\text{cdcl}_W\text{-o.simps}$   $\text{cdcl}_W\text{-bj.simps}$ 
  by (auto elim: skipE resolveE backtrackE conflictE decideE restartE)
qed

```

```

lemma  $\text{cdcl}_W\text{-merge-restart-no-step-cdcl}_W\text{-bj}$ :
  assumes
     $\text{cdcl}_W\text{-merge-restart } S T$ 
  shows  $\text{no-step } \text{cdcl}_W\text{-bj } T$ 
  using assms
  by (induction rule:  $\text{cdcl}_W\text{-merge-restart.induct}$ )
  (force simp:  $\text{cdcl}_W\text{-bj.simps}$   $\text{cdcl}_W\text{-rf.simps}$   $\text{cdcl}_W\text{-merge-restart.simps}$   $\text{full-def}$ 
    elim!: rulesE)+

```

```

lemma  $\text{rtrancp-cdcl}_W\text{-merge-restart-no-step-cdcl}_W\text{-bj}$ :
  assumes
     $\text{cdcl}_W\text{-merge-restart}^{**} S T$  and
     $\text{conflicting } S = \text{None}$ 
  shows  $\text{no-step } \text{cdcl}_W\text{-bj } T$ 
  using assms unfolding  $\text{rtrancp-unfold}$ 
  apply (elim disjE)
  apply (force simp:  $\text{cdcl}_W\text{-bj.simps}$   $\text{cdcl}_W\text{-rf.simps}$  elim!: rulesE)
  by (auto simp:  $\text{trancp-unfold-end}$  simp:  $\text{cdcl}_W\text{-merge-restart-no-step-cdcl}_W\text{-bj}$ )

```

If  $\text{conflicting } S \neq \text{None}$ , we cannot say anything.

Remark that this theorem does not say anything about well-foundedness: even if you know that one relation is well-founded, it only states that the normal forms are shared.

```

lemma  $\text{conflicting-true-full-cdcl}_W\text{-iff-full-cdcl}_W\text{-merge}$ :
  assumes  $\text{confl: conflicting } S = \text{None}$  and  $\text{lev: cdcl}_W\text{-M-level-inv } S$ 
  shows  $\text{full } \text{cdcl}_W S V \iff \text{full } \text{cdcl}_W\text{-merge-restart } S V$ 
proof
  assume  $\text{full: full } \text{cdcl}_W\text{-merge-restart } S V$ 
  then have  $\text{st: cdcl}_W^{**} S V$ 
    using  $\text{rtrancp-mono[of cdcl}_W\text{-merge-restart cdcl}_W^{**}]$   $\text{cdcl}_W\text{-merge-restart-cdcl}_W$ 
    unfolding  $\text{full-def}$  by auto

```

```

  have  $n\text{-s: no-step } \text{cdcl}_W\text{-merge-restart } V$ 
  using  $\text{full}$  unfolding  $\text{full-def}$  by auto
  have  $n\text{-s-bj: no-step } \text{cdcl}_W\text{-bj } V$ 
  using  $\text{rtrancp-cdcl}_W\text{-merge-restart-no-step-cdcl}_W\text{-bj confl full}$  unfolding  $\text{full-def}$  by auto
  have  $\bigwedge S'. \text{conflict } V S' \implies \text{cdcl}_W\text{-M-level-inv } S'$ 
  using  $\text{cdcl}_W.\text{conflict}$   $\text{cdcl}_W\text{-consistent-inv lev rtrancp-cdcl}_W\text{-consistent-inv st}$  by blast
  then have  $\bigwedge S'. \text{conflict } V S' \implies \text{False}$ 
  using  $n\text{-s } n\text{-s-bj cdcl}_W\text{-bj-exists-normal-form cdcl}_W\text{-merge-restart.simps}$  by meson
  then have  $n\text{-s-cdcl}_W\text{: no-step } \text{cdcl}_W V$ 
  using  $n\text{-s } n\text{-s-bj}$  by (auto simp:  $\text{cdcl}_W.\text{simps}$   $\text{cdcl}_W\text{-o.simps}$   $\text{cdcl}_W\text{-merge-restart.simps}$ )
  then show  $\text{full } \text{cdcl}_W S V$  using  $\text{st}$  unfolding  $\text{full-def}$  by auto
next
  assume  $\text{full: full } \text{cdcl}_W S V$ 
  have  $\text{no-step } \text{cdcl}_W\text{-merge-restart } V$ 

```



```

using full no-step-cdclW-no-step-cdclW-merge-restart unfolding full-def by blast
moreover
consider
  (fw) cdclW-merge-restart** S V and conflicting V = None
| (bj) T U where
  cdclW-merge-restart** S T and
  conflicting V ≠ None and
  conflict T U and
  cdclW-bj** U V
using full rtranc1-cdclW-conflicting-true-cdclW-merge-restart confl lev unfolding full-def
by meson
then have cdclW-merge-restart** S V
proof cases
  case fw
    then show ?thesis by fast
  next
    case (bj T U)
    have no-step cdclW-bj V
    using full unfolding full-def by (meson cdclW-o.bj other)
    then have full cdclW-bj U V
    using ⟨ cdclW-bj** U V ⟩ unfolding full-def by auto
    then have cdclW-merge-restart T V
    using ⟨ conflict T U ⟩ cdclW-merge-restart.fw-r-conflict by blast
    then show ?thesis using ⟨ cdclW-merge-restart** S T ⟩ by auto
  qed
ultimately show full cdclW-merge-restart S V unfolding full-def by fast
qed

```

**lemma** init-state-true-full-cdcl<sub>W</sub>-iff-full-cdcl<sub>W</sub>-merge:  
**shows** full cdcl<sub>W</sub> (init-state N) V  $\longleftrightarrow$  full cdcl<sub>W</sub>-merge-restart (init-state N) V  
**by** (rule conflicting-true-full-cdcl<sub>W</sub>-iff-full-cdcl<sub>W</sub>-merge) auto

## 21.4 FW with strategy

### 21.4.1 The intermediate step

**inductive** cdcl<sub>W</sub>-s' :: 'st  $\Rightarrow$  'st  $\Rightarrow$  bool **where**  
 conflict': full1 cdcl<sub>W</sub>-cp S S'  $\Longrightarrow$  cdcl<sub>W</sub>-s' S S' |  
 decide': decide S S'  $\Longrightarrow$  no-step cdcl<sub>W</sub>-cp S  $\Longrightarrow$  full cdcl<sub>W</sub>-cp S' S''  $\Longrightarrow$  cdcl<sub>W</sub>-s' S S'' |  
 bj': full1 cdcl<sub>W</sub>-bj S S'  $\Longrightarrow$  no-step cdcl<sub>W</sub>-cp S  $\Longrightarrow$  full cdcl<sub>W</sub>-cp S' S''  $\Longrightarrow$  cdcl<sub>W</sub>-s' S S''

**inductive-cases** cdcl<sub>W</sub>-s'E: cdcl<sub>W</sub>-s' S T

**lemma** rtranc1p-cdcl<sub>W</sub>-bj-full1-cdclp-cdcl<sub>W</sub>-stgy:  
 cdcl<sub>W</sub>-bj\*\* S S'  $\Longrightarrow$  full cdcl<sub>W</sub>-cp S' S''  $\Longrightarrow$  cdcl<sub>W</sub>-stgy\*\* S S''

**proof** (induction rule: converse-rtranc1p-induct)

**case** base

**then show** ?case **by** (metis cdcl<sub>W</sub>-stgy.conflict' full-unfold rtranc1p.simps)

**next**

**case** (step T U) **note** st = this(2) **and** bj = this(1) **and** IH = this(3)[OF this(4)]

**have** no-step cdcl<sub>W</sub>-cp T

**using** bj **by** (auto simp add: cdcl<sub>W</sub>-bj.simps cdcl<sub>W</sub>-cp.simps elim!: rulesE)

**consider**

(U) U = S'

| (U') U' **where** cdcl<sub>W</sub>-bj U U' **and** cdcl<sub>W</sub>-bj\*\* U' S'

**using** st **by** (metis converse-rtranc1pE)

```

then show ?case
proof cases
  case U
  then show ?thesis
    using ⟨no-step cdclW-cp T⟩ cdclW-o.bj local.bj other' step.prem by (meson r-into-rtrancp)
next
  case U' note U' = this(1)
  have no-step cdclW-cp U
    using U' by (fastforce simp: cdclW-cp.simps cdclW-bj.simps elim: rulesE)
  then have full cdclW-cp U U
    by (simp add: full-unfold)
  then have cdclW-stgy T U
    using ⟨no-step cdclW-cp T⟩ cdclW-stgy.simps local.bj cdclW-o.bj by meson
  then show ?thesis using IH by auto
qed
qed

```

```

lemma cdclW-s'-is-rtrancp-cdclW-stgy:
  cdclW-s' S T  $\implies$  cdclW-stgy** S T
  apply (induction rule: cdclW-s'.induct)
  apply (auto intro: cdclW-stgy.intros)[]
  apply (meson decide other' r-into-rtrancp)
  by (metis full1-def rtrancp-cdclW-bj-full1-cdclp-cdclW-stgy trancp-into-rtrancp)

```

lemma cdcl<sub>W</sub>-cp-cdcl<sub>W</sub>-bj-bissimulation:

```

assumes
  full cdclW-cp T U and
  cdclW-bj** T T' and
  cdclW-all-struct-inv T and
  no-step cdclW-bj T'
shows full cdclW-cp T' U
   $\vee (\exists U' U''. \text{full cdcl}_W\text{-cp } T' U'' \wedge \text{full1 cdcl}_W\text{-bj } U U' \wedge \text{full cdcl}_W\text{-cp } U' U''$ 
     $\wedge \text{cdcl}_W\text{-s}^{**} U U'')$ 
  using assms(2,1,3,4)
proof (induction rule: rtrancp-induct)
  case base
  then show ?case by blast
next
  case (step T' T'') note st = this(1) and bj = this(2) and IH = this(3)[OF this(4,5)] and
    full = this(4) and inv = this(5)
  have cdclW-bj** T T''
    using local.bj st by auto
  then have cdclW** T T''
    using rtrancp-cdclW-bj-rtrancp-cdclW by blast
  then have inv-T'': cdclW-all-struct-inv T''
    using inv rtrancp-cdclW-all-struct-inv-inv by blast
  have cdclW-bj++ T T''
    using local.bj st by auto
  have full1 cdclW-bj T T''
    by (metis ⟨cdclW-bj++ T T'⟩ full1-def step.prem(3))
  then have T = U
  proof -
    obtain Z where cdclW-bj T Z
      using ⟨cdclW-bj++ T T'⟩ by (blast dest: trancpD)
    { assume cdclW-cp++ T U

```

```

    then obtain  $Z'$  where  $cdcl_W\text{-}cp\ T\ Z'$ 
      by (meson tranclpD)
    then have False
      using  $\langle cdcl_W\text{-}bj\ T\ Z \rangle$  by (fastforce simp:  $cdcl_W\text{-}bj.simps\ cdcl_W\text{-}cp.simps$ 
        elim: rulesE)
  }
  then show ?thesis
    using full unfolding full-def rtranclp-unfold by blast
qed
obtain  $U''$  where full  $cdcl_W\text{-}cp\ T''\ U''$ 
  using  $cdcl_W\text{-}cp\text{-}normalized\text{-}element\text{-}all\text{-}inv\ inv\text{-}T''$  by blast
moreover then have  $cdcl_W\text{-}stgy^{**}\ U\ U''$ 
  by (metis  $\langle T = U \rangle \langle cdcl_W\text{-}bj^{++}\ T\ T'' \rangle rtranclp\text{-}cdcl_W\text{-}bj\text{-}full1\text{-}cdclp\text{-}cdcl_W\text{-}stgy\ rtranclp\text{-}unfold$ )
moreover have  $cdcl_W\text{-}s^{**}\ U\ U''$ 
proof -
  obtain  $ss :: 'st \Rightarrow 'st$  where
    f1:  $\forall x2. (\exists v3. cdcl_W\text{-}cp\ x2\ v3) = cdcl_W\text{-}cp\ x2\ (ss\ x2)$ 
    by maura
  have  $\neg cdcl_W\text{-}cp\ U\ (ss\ U)$ 
    by (meson full full-def)
  then show ?thesis
    using f1 by (metis (no-types)  $\langle T = U \rangle \langle full1\ cdcl_W\text{-}bj\ T\ T'' \rangle bj'\ calculation(1)$ 
      r-into-rtranclp)
qed
ultimately show ?case
  using  $\langle full1\ cdcl_W\text{-}bj\ T\ T'' \rangle \langle full\ cdcl_W\text{-}cp\ T''\ U'' \rangle$  unfolding  $\langle T = U \rangle$  by blast
qed

```

lemma  $cdcl_W\text{-}cp\text{-}cdcl_W\text{-}bj\text{-}bissimulation'$ :

```

assumes
  full  $cdcl_W\text{-}cp\ T\ U$  and
   $cdcl_W\text{-}bj^{**}\ T\ T'$  and
   $cdcl_W\text{-}all\text{-}struct\text{-}inv\ T$  and
  no-step  $cdcl_W\text{-}bj\ T'$ 
shows full  $cdcl_W\text{-}cp\ T'\ U$ 
   $\vee (\exists U'. full1\ cdcl_W\text{-}bj\ U\ U' \wedge (\forall U''. full\ cdcl_W\text{-}cp\ U'\ U'' \longrightarrow full\ cdcl_W\text{-}cp\ T'\ U''$ 
     $\wedge cdcl_W\text{-}s^{**}\ U\ U''))$ 
  using assms(2,1,3,4)
proof (induction rule: rtranclp-induct)
  case base
  then show ?case by blast
next
  case (step  $T'\ T''$ ) note  $st = this(1)$  and  $bj = this(2)$  and  $IH = this(3)[OF\ this(4,5)]$  and
     $full = this(4)$  and  $inv = this(5)$ 
  have  $cdcl_W^{**}\ T\ T''$ 
    by (metis local.bj rtranclp.simps rtranclp- $cdcl_W\text{-}bj\text{-}rtranclp\text{-}cdcl_W\ st$ )
  then have  $inv\text{-}T''$ :  $cdcl_W\text{-}all\text{-}struct\text{-}inv\ T''$ 
    using  $inv\ rtranclp\text{-}cdcl_W\text{-}all\text{-}struct\text{-}inv\text{-}inv$  by blast
  have  $cdcl_W\text{-}bj^{++}\ T\ T''$ 
    using local.bj st by auto
  have  $full1\ cdcl_W\text{-}bj\ T\ T''$ 
    by (metis  $\langle cdcl_W\text{-}bj^{++}\ T\ T'' \rangle full1\text{-}def\ step.premis(3)$ )
  then have  $T = U$ 
  proof -
    obtain  $Z$  where  $cdcl_W\text{-}bj\ T\ Z$ 

```

```

    using  $\langle cdcl_W\text{-}bj^{++} \ T \ T' \rangle$  by (blast dest: tranclpD)
  { assume  $cdcl_W\text{-}cp^{++} \ T \ U$ 
    then obtain  $Z'$  where  $cdcl_W\text{-}cp \ T \ Z'$ 
      by (meson tranclpD)
    then have False
      using  $\langle cdcl_W\text{-}bj \ T \ Z \rangle$  by (fastforce simp:  $cdcl_W\text{-}bj.simps \ cdcl_W\text{-}cp.simps \ elim: rulesE$ )
    }
  then show ?thesis
    using full unfolding full-def rtranclp-unfold by blast
qed
{ fix  $U''$ 
  assume full  $cdcl_W\text{-}cp \ T'' \ U''$ 
  moreover then have  $cdcl_W\text{-}stgy^{**} \ U \ U''$ 
    by (metis  $\langle T = U \rangle \langle cdcl_W\text{-}bj^{++} \ T \ T' \rangle \ rtranclp\text{-}cdcl_W\text{-}bj\text{-}full1\text{-}cdclp\text{-}cdcl_W\text{-}stgy \ rtranclp\text{-}unfold$ )
  moreover have  $cdcl_W\text{-}s^{**} \ U \ U''$ 
  proof -
    obtain  $ss :: 'st \Rightarrow 'st$  where
       $f1: \forall x2. (\exists v3. \ cdcl_W\text{-}cp \ x2 \ v3) = cdcl_W\text{-}cp \ x2 \ (ss \ x2)$ 
      by moura
    have  $\neg \ cdcl_W\text{-}cp \ U \ (ss \ U)$ 
      by (meson assms(1) full-def)
    then show ?thesis
      using f1 by (metis (no-types)  $\langle T = U \rangle \langle full1 \ cdcl_W\text{-}bj \ T \ T' \rangle \ bj' \ calculation(1) \ r\text{-into}\text{-}rtranclp$ )
    qed
  ultimately have  $full1 \ cdcl_W\text{-}bj \ U \ T''$  and  $cdcl_W\text{-}s'^{**} \ T'' \ U''$ 
    using  $\langle full1 \ cdcl_W\text{-}bj \ T \ T' \rangle \langle full \ cdcl_W\text{-}cp \ T'' \ U'' \rangle$  unfolding  $\langle T = U \rangle$ 
    apply blast
    by (metis  $\langle full \ cdcl_W\text{-}cp \ T'' \ U'' \rangle \ cdcl_W\text{-}s'.simps \ full\text{-}unfold \ rtranclp.simps$ )
  }
then show ?case
  using  $\langle full1 \ cdcl_W\text{-}bj \ T \ T' \rangle \ full \ bj' \ unfolding \langle T = U \rangle \ full\text{-}def$  by (metis  $r\text{-into}\text{-}rtranclp$ )
qed

```

lemma  $cdcl_W\text{-}stgy\text{-}cdcl_W\text{-}s'\text{-}connected$ :

```

  assumes  $cdcl_W\text{-}stgy \ S \ U$  and  $cdcl_W\text{-}all\text{-}struct\text{-}inv \ S$ 
  shows  $cdcl_W\text{-}s' \ S \ U$ 
     $\vee (\exists U'. \ full1 \ cdcl_W\text{-}bj \ U \ U' \wedge (\forall U''. \ full \ cdcl_W\text{-}cp \ U' \ U'' \longrightarrow cdcl_W\text{-}s' \ S \ U''))$ 
  using assms
proof (induction rule:  $cdcl_W\text{-}stgy.induct$ )
  case (conflict' T)
  then have  $cdcl_W\text{-}s' \ S \ T$ 
    using  $cdcl_W\text{-}s'.conflict'$  by blast
  then show ?case
    by blast
next
  case (other' T U) note  $o = this(1)$  and  $n\text{-}s = this(2)$  and  $full = this(3)$  and  $inv = this(4)$ 
  show ?case
    using o
  proof cases
    case decide
    then show ?thesis using  $cdcl_W\text{-}s'.simps \ full \ n\text{-}s$  by blast
  next
    case bj
    have  $inv\text{-}T: \ cdcl_W\text{-}all\text{-}struct\text{-}inv \ T$ 

```

```

    using cdclW-all-struct-inv-inv o other other'.prems by blast
consider
  (cp) full cdclW-cp T U and no-step cdclW-bj T
| (fbj) T' where full1 cdclW-bj T T'
apply (cases no-step cdclW-bj T)
  using full apply blast
  using cdclW-bj-exists-normal-form[of T] inv-T unfolding cdclW-all-struct-inv-def
  by (metis full-unfold)
then show ?thesis
proof cases
  case cp
  then show ?thesis
  proof -
    obtain ss :: 'st ⇒ 'st where
      f1: ∀ s sa sb. (¬ full1 cdclW-bj s sa ∨ cdclW-cp s (ss s) ∨ ¬ full cdclW-cp sa sb)
      ∨ cdclW-s' s sb
    using bj' by moura
    have full1 cdclW-bj S T
    by (simp add: cp(2) full1-def local.bj tranclp.r-into-trancl)
    then show ?thesis
    using f1 full n-s by blast
  qed
next
  case (fbj U')
  then have full1 cdclW-bj S U'
    using bj unfolding full1-def by auto
  moreover have no-step cdclW-cp S
    using n-s by blast
  moreover have T = U
    using full fbj unfolding full1-def full-def rtranclp-unfold
    by (force dest!: tranclpD simp:cdclW-bj.simps elim: rulesE)
  ultimately show ?thesis using cdclW-s'.bj'[of S U'] using fbj by blast
qed
qed
qed

```

**lemma** *cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-s'-connected'*:

```

  assumes cdclW-stgy S U and cdclW-all-struct-inv S
  shows cdclW-s' S U
    ∨ (∃ U' U''. cdclW-s' S U'' ∧ full1 cdclW-bj U U' ∧ full cdclW-cp U' U'')
  using assms
proof (induction rule: cdclW-stgy.induct)
  case (conflict' T)
  then have cdclW-s' S T
    using cdclW-s'.conflict' by blast
  then show ?case
    by blast
next
  case (other' T U) note o = this(1) and n-s = this(2) and full = this(3) and inv = this(4)
  show ?case
    using o
  proof cases
    case decide
    then show ?thesis using cdclW-s'.simps full n-s by blast
  next

```

```

case bj
have cdclW-all-struct-inv T
  using cdclW-all-struct-inv-inv o other other'.prems by blast
then obtain T' where T': full cdclW-bj T T'
  using cdclW-bj-exists-normal-form unfolding full-def cdclW-all-struct-inv-def by metis
then have full cdclW-bj S T'
  proof –
    have f1: cdclW-bj** T T' ∧ no-step cdclW-bj T'
      by (metis (no-types) T' full-def)
    then have cdclW-bj** S T'
      by (meson converse-rtranclp-into-rtranclp local.bj)
    then show ?thesis
      using f1 by (simp add: full-def)
  qed
have cdclW-bj** T T'
  using T' unfolding full-def by simp
have cdclW-all-struct-inv T
  using cdclW-all-struct-inv-inv o other other'.prems by blast
then consider
  (T'U) full cdclW-cp T' U
  | (U) U' U'' where
    full cdclW-cp T' U'' and
    full1 cdclW-bj U U' and
    full cdclW-cp U' U'' and
    cdclW-s*** U U''
  using cdclW-cp-cdclW-bj-bissimulation[OF full ⟨cdclW-bj** T T'⟩ T' unfolding full-def
  by blast
then show ?thesis by (metis T' cdclW-s'.simps full-full1 local.bj n-s)
qed
qed

```

**lemma** *cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-s'-no-step:*

```

assumes cdclW-stgy S U and cdclW-all-struct-inv S and no-step cdclW-bj U
shows cdclW-s' S U
using cdclW-stgy-cdclW-s'-connected[OF assms(1,2)] assms(3)
by (metis (no-types, lifting) full1-def tranclpD)

```

**lemma** *rtranclp-cdcl<sub>W</sub>-stgy-connected-to-rtranclp-cdcl<sub>W</sub>-s':*

```

assumes cdclW-stgy** S U and inv: cdclW-M-level-inv S
shows cdclW-s*** S U ∨ (∃ T. cdclW-s*** S T ∧ cdclW-bj++ T U ∧ conflicting U ≠ None)
using assms(1)

```

**proof** *induction*

**case** *base*

**then show** *?case* **by** *simp*

**next**

**case** (*step T V*) **note** *st = this(1)* **and** *o = this(2)* **and** *IH = this(3)*

**from** *o* **show** *?case*

**proof** *cases*

**case** *conflict'*

**then have** *f2: cdcl<sub>W</sub>-s' T V*

**using** *cdcl<sub>W</sub>-s'.conflict'* **by** *blast*

**obtain** *ss :: 'st* **where**

*f3: S = T ∨ cdcl<sub>W</sub>-stgy\*\* S ss ∧ cdcl<sub>W</sub>-stgy ss T*

**by** (*metis (full-types) rtranclp.simps st*)

**obtain** *ssa :: 'st* **where**

```

    ssa: cdclW-cp T ssa
    using conflict' by (metis (no-types) full1-def tranclpD)
have  $\forall s. \neg \text{full cdcl}_W\text{-cp } s \text{ } T$ 
  by (meson ssa full-def)
then have  $S = T$ 
  by (metis (full-types) f3 ssa cdclW-stgy.cases full1-def)
then show ?thesis
  using f2 by blast
next
case (other' U) note o = this(1) and n-s = this(2) and full = this(3)
then show ?thesis
  using o
  proof (cases rule: cdclW-o-rule-cases)
    case decide
    then have cdclW-s'** S T
      using IH by (auto elim: rulesE)
    then show ?thesis
      by (meson decide decide' full n-s rtranclp.rtrancl-into-rtrancl)
  next
  case backtrack
  consider
    (s') cdclW-s'** S T
  | (bj) S' where cdclW-s'** S S' and cdclW-bj++ S' T and conflicting T  $\neq$  None
  using IH by blast
then show ?thesis
  proof cases
    case s'
    moreover
      have cdclW-M-level-inv T
        using inv local.step(1) rtranclp-cdclW-stgy-consistent-inv by auto
      then have full1 cdclW-bj T U
        using backtrack-is-full1-cdclW-bj backtrack by blast
      then have cdclW-s' T V
        using full bj' n-s by blast
      ultimately show ?thesis by auto
    next
    case (bj S') note S-S' = this(1) and bj-T = this(2)
    have no-step cdclW-cp S'
      using bj-T by (fastforce simp: cdclW-cp.simps cdclW-bj.simps dest!: tranclpD
        elim: rulesE)
    moreover
      have cdclW-M-level-inv T
        using inv local.step(1) rtranclp-cdclW-stgy-consistent-inv by auto
      then have full1 cdclW-bj T U
        using backtrack-is-full1-cdclW-bj backtrack by blast
      then have full1 cdclW-bj S' U
        using bj-T unfolding full1-def by fastforce
      ultimately have cdclW-s' S' V using full by (simp add: bj')
      then show ?thesis using S-S' by auto
    qed
  next
  case skip
  then have [simp]: U = V
    using full converse-rtranclpE unfolding full-def by (fastforce elim: rulesE)
  then have confl-V: conflicting V  $\neq$  None

```

```

    using skip by (auto elim!: rulesE simp del: state-simp simp: state-eq-def)
  consider
    (s') cdclW-sl** S T
  | (bj) S' where cdclW-sl** S S' and cdclW-bj++ S' T and conflicting T ≠ None
    using IH by blast
  then show ?thesis
  proof cases
    case s'
    show ?thesis using s' confl-V skip by force
  next
    case (bj S') note S-S' = this(1) and bj-T = this(2)
    have cdclW-bj++ S' V
      using skip bj-T by (metis (U = V) cdclW-bj.skip tranclp.simps)
    then show ?thesis using S-S' confl-V by auto
  qed
next
case resolve
then have [simp]: U = V
  using full unfolding full-def rtranclp-unfold
  by (auto elim!: rulesE dest!: tranclpD
    simp del: state-simp simp: state-eq-def cdclW-cp.simps)
have confl-V: conflicting V ≠ None
  using resolve by (auto elim!: rulesE simp del: state-simp simp: state-eq-def)

consider
  (s') cdclW-sl** S T
| (bj) S' where cdclW-sl** S S' and cdclW-bj++ S' T and conflicting T ≠ None
  using IH by blast
then show ?thesis
proof cases
  case s'
  have cdclW-bj++ T V
    using resolve by force
  then show ?thesis using s' confl-V by auto
next
  case (bj S') note S-S' = this(1) and bj-T = this(2)
  have cdclW-bj++ S' V
    using resolve bj-T by (metis (U = V) cdclW-bj.resolve tranclp.simps)
  then show ?thesis using confl-V S-S' by auto
qed
qed
qed
qed

lemma n-step-cdclW-stgy-iff-no-step-cdclW-cl-cdclW-o:
  assumes inv: cdclW-all-struct-inv S
  shows no-step cdclW-s' S ⟷ no-step cdclW-cp S ∧ no-step cdclW-o S (is ?S' S ⟷ ?C S ∧ ?O S)
proof
  assume ?C S ∧ ?O S
  then show ?S' S
    by (auto simp: cdclW-s'.simps full1-def tranclp-unfold-begin)
next
  assume n-s: ?S' S
  have ?C S
    proof (rule ccontr)

```



```

    assume  $\neg ?thesis$ 
    then obtain  $S'$  where  $cdcl_W\text{-}cp\ S\ S'$ 
      by auto
    then obtain  $T$  where  $full1\ cdcl_W\text{-}cp\ S\ T$ 
      using  $cdcl_W\text{-}cp\text{-}normalized\text{-}element\text{-}all\text{-}inv\ inv$  by (metis (no-types, lifting) full-unfold)
    then show  $False$  using  $n\text{-}s\ cdcl_W\text{-}s'\text{-}conflict'$  by blast
  qed
moreover have  $?O\ S$ 
proof (rule ccontr)
  assume  $\neg ?thesis$ 
  then obtain  $S'$  where  $cdcl_W\text{-}o\ S\ S'$ 
    by auto
  then obtain  $T$  where  $full1\ cdcl_W\text{-}cp\ S'\ T$ 
    using  $cdcl_W\text{-}cp\text{-}normalized\text{-}element\text{-}all\text{-}inv\ inv$ 
    by (meson  $cdcl_W\text{-}all\text{-}struct\text{-}inv\text{-}def\ n\text{-}s$ 
       $cdcl_W\text{-}stgy\text{-}cdcl_W\text{-}s'\text{-}connected'\ cdcl_W\text{-}then\text{-}exists\text{-}cdcl_W\text{-}stgy\text{-}step$ )
  then show  $False$  using  $n\text{-}s$  by (meson  $\langle cdcl_W\text{-}o\ S\ S'\rangle\ cdcl_W\text{-}all\text{-}struct\text{-}inv\text{-}def$ 
     $cdcl_W\text{-}stgy\text{-}cdcl_W\text{-}s'\text{-}connected'\ cdcl_W\text{-}then\text{-}exists\text{-}cdcl_W\text{-}stgy\text{-}step\ inv$ )
  qed
ultimately show  $?C\ S \wedge ?O\ S$  by auto
qed

lemma  $cdcl_W\text{-}s'\text{-}trancpl\text{-}cdcl_W$ :
   $cdcl_W\text{-}s'\ S\ S' \implies cdcl_W^{++}\ S\ S'$ 
proof (induct rule:  $cdcl_W\text{-}s'\text{-}induct$ )
  case  $conflict'$ 
  then show  $?case$ 
    by (simp add:  $full1\text{-}def\ trancpl\text{-}cdcl_W\text{-}cp\text{-}trancpl\text{-}cdcl_W$ )
next
  case  $decide'$ 
  then show  $?case$ 
    using  $cdcl_W\text{-}stgy.simps\ cdcl_W\text{-}stgy\text{-}trancpl\text{-}cdcl_W$  by (meson  $cdcl_W\text{-}o.simps$ )
next
  case ( $bj'\ Sa\ S'a\ S''$ ) note  $a2 = this(1)$  and  $a1 = this(2)$  and  $n\text{-}s = this(3)$ 
  obtain  $ss :: 'st \Rightarrow 'st \Rightarrow ('st \Rightarrow 'st \Rightarrow bool) \Rightarrow 'st$  where
     $\forall x0\ x1\ x2. (\exists v3. x2\ x1\ v3 \wedge x2^{**}\ v3\ x0) = (x2\ x1\ (ss\ x0\ x1\ x2) \wedge x2^{**}\ (ss\ x0\ x1\ x2)\ x0)$ 
    by moura
  then have  $f3: \forall p\ s\ sa. \neg p^{++}\ s\ sa \vee p\ s\ (ss\ sa\ s\ p) \wedge p^{**}\ (ss\ sa\ s\ p)\ sa$ 
    by (metis (full-types)  $trancplD$ )
  have  $cdcl_W\text{-}bj^{++}\ Sa\ S'a \wedge no\text{-}step\ cdcl_W\text{-}bj\ S'a$ 
    using  $a2$  by (simp add:  $full1\text{-}def$ )
  then have  $cdcl_W\text{-}bj\ Sa\ (ss\ S'a\ Sa\ cdcl_W\text{-}bj) \wedge cdcl_W\text{-}bj^{**}\ (ss\ S'a\ Sa\ cdcl_W\text{-}bj)\ S'a$ 
    using  $f3$  by auto
  then show  $cdcl_W^{++}\ Sa\ S''$ 
    using  $a1\ n\text{-}s$  by (meson  $bj\ other\ rtrancpl\text{-}cdcl_W\text{-}bj\text{-}full1\text{-}cdclp\text{-}cdcl_W\text{-}stgy$ 
       $rtrancpl\text{-}cdcl_W\text{-}stgy\text{-}rtrancpl\text{-}cdcl_W\ rtrancpl\text{-}into\text{-}trancpl2$ )
  qed

lemma  $trancpl\text{-}cdcl_W\text{-}s'\text{-}trancpl\text{-}cdcl_W$ :
   $cdcl_W\text{-}s'^{++}\ S\ S' \implies cdcl_W^{++}\ S\ S'$ 
  apply (induct rule:  $trancpl.induct$ )
  using  $cdcl_W\text{-}s'\text{-}trancpl\text{-}cdcl_W$  apply blast
  by (meson  $cdcl_W\text{-}s'\text{-}trancpl\text{-}cdcl_W\ trancpl\text{-}trans$ )

lemma  $rtrancpl\text{-}cdcl_W\text{-}s'\text{-}rtrancpl\text{-}cdcl_W$ :

```

$cdcl_W-s'^{**} S S' \implies cdcl_W^{**} S S'$   
**using** *rtrancpl-unfold*[*of cdcl\_W-s' S S'*] *trancpl-cdcl\_W-s'-trancpl-cdcl\_W*[*of S S'*] **by** *auto*

**lemma** *full-cdcl\_W-stgy-iff-full-cdcl\_W-s'*:  
**assumes** *inv*: *cdcl\_W-all-struct-inv S*  
**shows** *full cdcl\_W-stgy S T  $\longleftrightarrow$  full cdcl\_W-s' S T* (**is** *?S  $\longleftrightarrow$  ?S'*)

**proof**  
**assume** *?S'*  
**then have** *cdcl\_W^{\*\*} S T*  
**using** *rtrancpl-cdcl\_W-s'-rtrancpl-cdcl\_W*[*of S T*] **unfolding** *full-def* **by** *blast*  
**then have** *inv'*: *cdcl\_W-all-struct-inv T*  
**using** *rtrancpl-cdcl\_W-all-struct-inv-inv inv* **by** *blast*  
**have** *cdcl\_W-stgy^{\*\*} S T*  
**using** *<?S'>* **unfolding** *full-def*  
**using** *cdcl\_W-s'-is-rtrancpl-cdcl\_W-stgy rtrancpl-mono*[*of cdcl\_W-s' cdcl\_W-stgy^{\*\*}*] **by** *auto*  
**then show** *?S*  
**using** *<?S'> inv' cdcl\_W-stgy-cdcl\_W-s'-connected'* **unfolding** *full-def* **by** *blast*

**next**  
**assume** *?S*  
**then have** *inv-T:cdcl\_W-all-struct-inv T*  
**by** (*metis assms full-def rtrancpl-cdcl\_W-all-struct-inv-inv rtrancpl-cdcl\_W-stgy-rtrancpl-cdcl\_W*)

**consider**  
 $(s') \text{ } cdcl_W-s'^{**} S T$   
 $| (st) S' \text{ where } cdcl_W-s'^{**} S S' \text{ and } cdcl_W-bj^{++} S' T \text{ and conflicting } T \neq None$   
**using** *rtrancpl-cdcl\_W-stgy-connected-to-rtrancpl-cdcl\_W-s'*[*of S T*] *inv <?S>*  
**unfolding** *full-def cdcl\_W-all-struct-inv-def*  
**by** *blast*

**then show** *?S'*  
**proof cases**  
**case** *s'*  
**have** *no-step cdcl\_W-s' T*  
**using** *<full cdcl\_W-stgy S T>* **unfolding** *full-def*  
**by** (*meson cdcl\_W-all-struct-inv-def cdcl\_W-s'E cdcl\_W-stgy.conflict'*  
*cdcl\_W-then-exists-cdcl\_W-stgy-step inv-T n-step-cdcl\_W-stgy-iff-no-step-cdcl\_W-cl-cdcl\_W-o*)  
**then show** *?thesis*  
**using** *s'* **unfolding** *full-def* **by** *blast*

**next**  
**case** *(st S')*  
**have** *full cdcl\_W-cp T T*  
**using** *option-full-cdcl\_W-cp st(3)* **by** *blast*  
**moreover**  
**have** *n-s: no-step cdcl\_W-bj T*  
**by** (*metis <full cdcl\_W-stgy S T> bj inv-T cdcl\_W-all-struct-inv-def*  
*cdcl\_W-then-exists-cdcl\_W-stgy-step full-def*)  
**then have** *full1 cdcl\_W-bj S' T*  
**using** *st(2)* **unfolding** *full1-def* **by** *blast*  
**moreover have** *no-step cdcl\_W-cp S'*  
**using** *st(2)* **by** (*fastforce dest!: trancplD simp: cdcl\_W-cp.simps cdcl\_W-bj.simps*  
*elim: rulesE*)  
**ultimately have** *cdcl\_W-s' S' T*  
**using** *cdcl\_W-s'.bj'[of S' T T]* **by** *blast*  
**then have** *cdcl\_W-s'^{\*\*} S T*  
**using** *st(1)* **by** *auto*  
**moreover have** *no-step cdcl\_W-s' T*

```

    using inv-T ⟨full cdclW-cp T T⟩ ⟨full cdclW-stgy S T⟩ unfolding full-def
    by (metis cdclW-all-struct-inv-def cdclW-then-exists-cdclW-stgy-step
        n-step-cdclW-stgy-iff-no-step-cdclW-cl-cdclW-o)
    ultimately show ?thesis
    unfolding full-def by blast
qed
qed

```

**lemma** *conflict-step-cdcl<sub>W</sub>-stgy-step*:

```

    assumes
      conflict S T
      cdclW-all-struct-inv S
    shows ∃ T. cdclW-stgy S T
  proof -
    obtain U where full cdclW-cp S U
    using cdclW-cp-normalized-element-all-inv assms by blast
    then have full1 cdclW-cp S U
    by (metis cdclW-cp.conflict' assms(1) full-unfold)
    then show ?thesis using cdclW-stgy.conflict' by blast
  qed

```

**lemma** *decide-step-cdcl<sub>W</sub>-stgy-step*:

```

    assumes
      decide S T
      cdclW-all-struct-inv S
    shows ∃ T. cdclW-stgy S T
  proof -
    obtain U where full cdclW-cp T U
    using cdclW-cp-normalized-element-all-inv by (meson assms(1) assms(2) cdclW-all-struct-inv-inv
        cdclW-cp-normalized-element-all-inv decide other)
    then show ?thesis
    by (metis assms cdclW-cp-normalized-element-all-inv cdclW-stgy.conflict' decide full-unfold
        other')
  qed

```

**lemma** *rtranclp-cdcl<sub>W</sub>-cp-conflicting-Some*:

```

    cdclW-cp** S T ⇒ conflicting S = Some D ⇒ S = T
    using rtranclpD tranclpD by fastforce

```

**inductive** *cdcl<sub>W</sub>-merge-cp* :: 'st ⇒ 'st ⇒ bool **where**

```

  conflict': conflict S T ⇒ full cdclW-bj T U ⇒ cdclW-merge-cp S U |
  propagate': propagate++ S S' ⇒ cdclW-merge-cp S S'

```

**lemma** *cdcl<sub>W</sub>-merge-restart-cases*[consumes 1, case-names conflict propagate]:

```

    assumes
      cdclW-merge-cp S U and
      ∧ T. conflict S T ⇒ full cdclW-bj T U ⇒ P and
      propagate++ S U ⇒ P
    shows P
    using assms unfolding cdclW-merge-cp.simps by auto

```

**lemma** *cdcl<sub>W</sub>-merge-cp-tranclp-cdcl<sub>W</sub>-merge*:

```

    cdclW-merge-cp S T ⇒ cdclW-merge++ S T
  apply (induction rule: cdclW-merge-cp.induct)
  using cdclW-merge.simps apply auto[1]

```

**using** *trancpl-mono*[*of propagate cdcl<sub>W</sub>-merge*] *fw-propagate* **by** *blast*

**lemma** *rtrancpl-cdcl<sub>W</sub>-merge-cp-rtrancpl-cdcl<sub>W</sub>*:  
*cdcl<sub>W</sub>-merge-cp*\*\* *S T*  $\implies$  *cdcl<sub>W</sub>*\*\* *S T*  
**apply** (*induction rule: rtrancpl-induct*)  
**apply** *simp*  
**unfolding** *cdcl<sub>W</sub>-merge-cp.simps* **by** (*meson cdcl<sub>W</sub>-merge-restart-cdcl<sub>W</sub> fw-r-conflict*  
*rtrancpl-propagate-is-rtrancpl-cdcl<sub>W</sub> rtrancpl-trans trancpl-into-rtrancpl*)

**lemma** *full1-cdcl<sub>W</sub>-bj-no-step-cdcl<sub>W</sub>-bj*:  
*full1 cdcl<sub>W</sub>-bj S T*  $\implies$  *no-step cdcl<sub>W</sub>-cp S*  
**unfolding** *full1-def* **by** (*metis rtrancpl-unfold cdcl<sub>W</sub>-cp-conflicting-not-empty option.exhaust*  
*rtrancpl-cdcl<sub>W</sub>-merge-restart-no-step-cdcl<sub>W</sub>-bj trancplD*)

**inductive** *cdcl<sub>W</sub>-s'-without-decide* **where**  
*conflict'-without-decide*[*intro*]: *full1 cdcl<sub>W</sub>-cp S S'*  $\implies$  *cdcl<sub>W</sub>-s'-without-decide S S'* |  
*bj'-without-decide*[*intro*]: *full1 cdcl<sub>W</sub>-bj S S'*  $\implies$  *no-step cdcl<sub>W</sub>-cp S*  $\implies$  *full cdcl<sub>W</sub>-cp S' S''*  
 $\implies$  *cdcl<sub>W</sub>-s'-without-decide S S''*

**lemma** *rtrancpl-cdcl<sub>W</sub>-s'-without-decide-rtrancpl-cdcl<sub>W</sub>*:  
*cdcl<sub>W</sub>-s'-without-decide*\*\* *S T*  $\implies$  *cdcl<sub>W</sub>*\*\* *S T*  
**apply** (*induction rule: rtrancpl-induct*)  
**apply** *simp*  
**by** (*meson cdcl<sub>W</sub>-s'.simps cdcl<sub>W</sub>-s'-trancpl-cdcl<sub>W</sub> cdcl<sub>W</sub>-s'-without-decide.simps*  
*rtrancpl-trancpl-trancpl trancpl-into-rtrancpl*)

**lemma** *rtrancpl-cdcl<sub>W</sub>-s'-without-decide-rtrancpl-cdcl<sub>W</sub>-s'*:  
*cdcl<sub>W</sub>-s'-without-decide*\*\* *S T*  $\implies$  *cdcl<sub>W</sub>-s'*\*\* *S T*  
**proof** (*induction rule: rtrancpl-induct*)  
**case** *base*  
**then show** ?*case* **by** *simp*  
**next**  
**case** (*step y z*) **note** *a2 = this(2)* **and** *a1 = this(3)*  
**have** *cdcl<sub>W</sub>-s' y z*  
**using** *a2* **by** (*metis (no-types) bj' cdcl<sub>W</sub>-s'.conflict' cdcl<sub>W</sub>-s'-without-decide.cases*)  
**then show** *cdcl<sub>W</sub>-s'*\*\* *S z*  
**using** *a1* **by** (*meson r-into-rtrancpl rtrancpl-trans*)  
**qed**

**lemma** *rtrancpl-cdcl<sub>W</sub>-merge-cp-is-rtrancpl-cdcl<sub>W</sub>-s'-without-decide*:  
**assumes**  
*cdcl<sub>W</sub>-merge-cp*\*\* *S V*  
*conflicting S = None*  
**shows**  
(*cdcl<sub>W</sub>-s'-without-decide*\*\* *S V*)  
 $\vee$  ( $\exists T. \text{cdcl}_{W-s'-without-decide}^{**} S T \wedge \text{propagate}^{++} T V$ )  
 $\vee$  ( $\exists T U. \text{cdcl}_{W-s'-without-decide}^{**} S T \wedge \text{full1 cdcl}_{W-bj} T U \wedge \text{propagate}^{**} U V$ )  
**using** *assms*  
**proof** (*induction rule: rtrancpl-induct*)  
**case** *base*  
**then show** ?*case* **by** *simp*  
**next**  
**case** (*step U V*) **note** *st = this(1)* **and** *cp = this(2)* **and** *IH = this(3)[OF this(4)]*  
**from** *cp* **show** ?*case*  
**proof** (*cases rule: cdcl<sub>W</sub>-merge-restart-cases*)

```

case propagate
then show ?thesis using IH by (meson rtrancpl-trancpl-trancpl trancpl-into-rtrancpl)
next
case (conflict U') note confl = this(1) and bj = this(2)
have full1-U-U': full1 cdclW-cp U U'
  by (simp add: conflict-is-full1-cdclW-cp local.conflict(1))
consider
  (s') cdclW-s'-without-decide** S U
| (propa) T' where cdclW-s'-without-decide** S T' and propagate++ T' U
| (bj-prop) T' T'' where
  cdclW-s'-without-decide** S T' and
  full1 cdclW-bj T' T'' and
  propagate** T'' U
using IH by blast
then show ?thesis
proof cases
case s'
have cdclW-s'-without-decide U U'
  using full1-U-U' conflict'-without-decide by blast
then have cdclW-s'-without-decide** S U'
  using ⟨cdclW-s'-without-decide** S U⟩ by auto
moreover have U' = V ∨ full1 cdclW-bj U' V
  using bj by (meson full-unfold)
ultimately show ?thesis by blast
next
case propa note s' = this(1) and T'-U = this(2)
have full1 cdclW-cp T' U'
  using rtrancpl-mono[of propagate cdclW-cp] T'-U cdclW-cp.propagate' full1-U-U'
  rtrancpl-full1I[of cdclW-cp T'] by (metis (full-types) predicate2D predicate2I
    trancpl-into-rtrancpl)
have cdclW-s'-without-decide** S U'
  using ⟨full1 cdclW-cp T' U'⟩ conflict'-without-decide s' by force
have full1 cdclW-bj U' V ∨ V = U' using bj unfolding full-unfold by blast
then show ?thesis
  using ⟨cdclW-s'-without-decide** S U'⟩ by blast
next
case bj-prop note s' = this(1) and bj-T' = this(2) and T''-U = this(3)
have no-step cdclW-cp T'
  using bj-T' full1-cdclW-bj-no-step-cdclW-bj by blast
moreover have full1 cdclW-cp T'' U'
  using rtrancpl-mono[of propagate cdclW-cp] T''-U cdclW-cp.propagate' full1-U-U'
  rtrancpl-full1I[of cdclW-cp T''] by blast
ultimately have cdclW-s'-without-decide T' U'
  using bj'-without-decide[of T' T'' U] bj-T' by (simp add: full-unfold)
then have cdclW-s'-without-decide** S U'
  using s' rtrancpl.intros(2)[of - S T' U] by blast
then show ?thesis
  using local.bj unfolding full-unfold by blast
qed
qed
qed

lemma rtrancpl-cdclW-s'-without-decide-is-rtrancpl-cdclW-merge-cp:
assumes
  cdclW-s'-without-decide** S V and

```

```

  confl: conflicting  $S = \text{None}$ 
shows
  ( $\text{cdcl}_W\text{-merge-cp}^{**} S V \wedge \text{conflicting } V = \text{None}$ )
 $\vee (\text{cdcl}_W\text{-merge-cp}^{**} S V \wedge \text{conflicting } V \neq \text{None} \wedge \text{no-step } \text{cdcl}_W\text{-cp } V \wedge \text{no-step } \text{cdcl}_W\text{-bj } V)$ 
 $\vee (\exists T. \text{cdcl}_W\text{-merge-cp}^{**} S T \wedge \text{conflict } T V)$ 
using assms(1)
proof (induction)
  case base
  then show ?case using confl by auto
next
case (step  $U V$ ) note st = this(1) and s = this(2) and IH = this(3)
from s show ?case
proof (cases rule: cdclW-s'-without-decide.cases)
  case conflict'-without-decide
  then have rt:  $\text{cdcl}_W\text{-cp}^{++} U V$  unfolding full1-def by fast
  then have conflicting  $U = \text{None}$ 
    using trancplp-cdclW-cp-propagate-with-conflict-or-not[of  $U V$ ]
    conflict by (auto dest!: trancplpD simp: rtrancplp-unfold elim: rulesE)
  then have  $\text{cdcl}_W\text{-merge-cp}^{**} S U$  using IH by (auto elim: rulesE
    simp del: state-simp simp: state-eq-def)
  consider
    (propa)  $\text{propagate}^{++} U V$ 
    | (confl') conflict  $U V$ 
    | (propa-confl')  $U' \text{ where } \text{propagate}^{++} U U' \text{ conflict } U' V$ 
  using trancplp-cdclW-cp-propagate-with-conflict-or-not[OF rt] unfolding rtrancplp-unfold
  by fastforce
  then show ?thesis
  proof cases
    case propa
    then have  $\text{cdcl}_W\text{-merge-cp } U V$ 
      by (auto intro: cdclW-merge-cp.intros)
    moreover have conflicting  $V = \text{None}$ 
      using propa unfolding trancplp-unfold-end by (auto elim: rulesE)
    ultimately show ?thesis using  $\langle \text{cdcl}_W\text{-merge-cp}^{**} S U \rangle$  by (auto elim!: rulesE
      simp del: state-simp simp: state-eq-def)
  next
  case confl'
  then show ?thesis using  $\langle \text{cdcl}_W\text{-merge-cp}^{**} S U \rangle$  by auto
  next
  case propa-confl' note propa = this(1) and confl' = this(2)
  then have  $\text{cdcl}_W\text{-merge-cp } U U'$  by (auto intro: cdclW-merge-cp.intros)
  then have  $\text{cdcl}_W\text{-merge-cp}^{**} S U'$  using  $\langle \text{cdcl}_W\text{-merge-cp}^{**} S U \rangle$  by auto
  then show ?thesis using  $\langle \text{cdcl}_W\text{-merge-cp}^{**} S U \rangle$  confl' by auto
qed
next
case (bj'-without-decide  $U'$ ) note full-bj = this(1) and cp = this(3)
then have conflicting  $U \neq \text{None}$ 
  using full-bj unfolding full1-def by (fastforce dest!: trancplpD simp: cdclW-bj.simps
    elim: rulesE)
with IH obtain T where
  S-T:  $\text{cdcl}_W\text{-merge-cp}^{**} S T$  and T-U: conflict  $T U$ 
  using full-bj unfolding full1-def by (blast dest: trancplpD)
then have  $\text{cdcl}_W\text{-merge-cp } T U'$ 
  using  $\text{cdcl}_W\text{-merge-cp.conflict'}$ [of  $T U U'$ ] full-bj by (simp add: full-unfold)
then have  $S\text{-}U'$ :  $\text{cdcl}_W\text{-merge-cp}^{**} S U'$  using S-T by auto

```

```

consider
  (n-s)  $U' = V$ 
  | (propa)  $\text{propagate}^{++} U' V$ 
  | (confl')  $\text{conflict } U' V$ 
  | (propa-confl')  $U''$  where  $\text{propagate}^{++} U' U'' \text{ conflict } U'' V$ 
using  $\text{trancpl-cdcl}_W\text{-cp-propagate-with-conflict-or-not } cp$ 
unfolding  $\text{rtrancpl-unfold full-def}$  by  $\text{metis}$ 
then show  $?thesis$ 
proof cases
  case propa
    then have  $\text{cdcl}_W\text{-merge-cp } U' V$  by ( $\text{blast intro: cdcl}_W\text{-merge-cp.intros}$ )
    moreover have  $\text{conflicting } V = \text{None}$ 
      using propa unfolding trancpl-unfold-end by ( $\text{auto elim: rulesE}$ )
    ultimately show  $?thesis$  using  $S-U'$  by ( $\text{auto elim: rulesE}$ 
       $\text{simp del: state-simp simp: state-eq-def}$ )
  next
    case confl'
    then show  $?thesis$  using  $S-U'$  by  $\text{auto}$ 
  next
    case propa-confl' note  $\text{propa} = \text{this}(1)$  and  $\text{confl} = \text{this}(2)$ 
    have  $\text{cdcl}_W\text{-merge-cp } U' U''$  using propa by ( $\text{blast intro: cdcl}_W\text{-merge-cp.intros}$ )
    then show  $?thesis$  using  $S-U'$   $\text{confl}$  by ( $\text{meson rtrancpl.rtrancpl-into-rtrancpl}$ )
  next
    case n-s
    then show  $?thesis$ 
      using  $S-U'$  apply ( $\text{cases conflicting } V = \text{None}$ )
      using full-bj apply simp
      by ( $\text{metis cp full-def full-unfold full-bj}$ )
qed
qed
qed

```

**lemma**  $\text{no-step-cdcl}_W\text{-s'-no-ste-cdcl}_W\text{-merge-cp}$ :

**assumes**

- $\text{cdcl}_W\text{-all-struct-inv } S$
- $\text{conflicting } S = \text{None}$
- $\text{no-step cdcl}_W\text{-s'} S$

**shows**  $\text{no-step cdcl}_W\text{-merge-cp } S$

**using**  $\text{assms apply}$  ( $\text{auto simp: cdcl}_W\text{-s'.simps cdcl}_W\text{-merge-cp.simps}$ )

**using**  $\text{conflict-is-full1-cdcl}_W\text{-cp apply blast}$

**using**  $\text{cdcl}_W\text{-cp-normalized-element-all-inv cdcl}_W\text{-cp.propagate' by}$  ( $\text{metis cdcl}_W\text{-cp.propagate' full-unfold trancplD}$ )

The  $\text{no-step decide } S$  is needed, since  $\text{cdcl}_W\text{-merge-cp}$  is  $\text{cdcl}_W\text{-s'}$  without  $\text{decide}$ .

**lemma**  $\text{conflicting-true-no-step-cdcl}_W\text{-merge-cp-no-step-s'-without-decide}$ :

**assumes**

- $\text{conft: conflicting } S = \text{None}$  **and**
- $\text{inv: cdcl}_W\text{-M-level-inv } S$  **and**
- $\text{n-s: no-step cdcl}_W\text{-merge-cp } S$

**shows**  $\text{no-step cdcl}_W\text{-s'-without-decide } S$

**proof** ( $\text{rule ccontr}$ )

**assume**  $\neg \text{no-step cdcl}_W\text{-s'-without-decide } S$

**then obtain**  $T$  **where**

- $\text{cdcl}_W\text{: cdcl}_W\text{-s'-without-decide } S T$

**by**  $\text{auto}$

```

then have inv-T: cdclW-M-level-inv T
  using rtrancp-cdclW-s'-without-decide-rtrancp-cdclW[of S T]
  rtrancp-cdclW-consistent-inv inv by blast
from cdclW show False
proof cases
  case conflict'-without-decide
  have no-step propagate S
    using n-s by (blast intro: cdclW-merge-cp.intros)
  then have conflict S T
    using local.conflict' trancp-cdclW-cp-propagate-with-conflict-or-not[of S T]
    local.conflict'-without-decide unfolding full1-def rtrancp-unfold
    by (metis trancp-unfold-begin)
  moreover
    then obtain T' where full cdclW-bj T T'
      using cdclW-bj-exists-normal-form inv-T by blast
  ultimately show False using cdclW-merge-cp.conflict' n-s by meson
next
case (bj'-without-decide S')
then show ?thesis
  using confl unfolding full1-def by (fastforce simp: cdclW-bj.simps dest: trancpD
    elim: rulesE)
qed
qed

lemma conflicting-true-no-step-s'-without-decide-no-step-cdclW-merge-cp:
  assumes
    inv: cdclW-all-struct-inv S and
    n-s: no-step cdclW-s'-without-decide S
  shows no-step cdclW-merge-cp S
proof (rule ccontr)
  assume ¬ ?thesis
  then obtain T where cdclW-merge-cp S T
    by auto
  then show False
  proof cases
    case (conflict' S')
    then show False using n-s conflict'-without-decide conflict-is-full1-cdclW-cp by blast
  next
    case propagate'
    moreover
      have cdclW-all-struct-inv T
        using inv by (meson local.propagate' rtrancp-cdclW-all-struct-inv-inv
          rtrancp-propagate-is-rtrancp-cdclW trancp-into-rtrancp)
      then obtain U where full cdclW-cp T U
        using cdclW-cp-normalized-element-all-inv by auto
      ultimately have full1 cdclW-cp S U
        using trancp-full-full1I[of cdclW-cp S T U] cdclW-cp.propagate'
        trancp-mono[of propagate cdclW-cp] by blast
      then show False using conflict'-without-decide n-s by blast
    qed
  qed
qed

```

```

lemma no-step-cdclW-merge-cp-no-step-cdclW-cp:
  no-step cdclW-merge-cp S  $\implies$  cdclW-M-level-inv S  $\implies$  no-step cdclW-cp S
  using cdclW-bj-exists-normal-form cdclW-consistent-inv[OF cdclW.conflict, of S]

```



by (metis cdcl<sub>W</sub>-cp.cases cdcl<sub>W</sub>-merge-cp.simps tranclp.intros(1))

**lemma** conflicting-not-true-rtranclp-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-bj:

**assumes**

conflicting  $S = \text{None}$  **and**

cdcl<sub>W</sub>-merge-cp\*\*  $S T$

**shows** no-step cdcl<sub>W</sub>-bj  $T$

**using** assms(2,1) **by** (induction)

(fastforce simp: cdcl<sub>W</sub>-merge-cp.simps full-def tranclp-unfold-end cdcl<sub>W</sub>-bj.simps  
elim: rulesE)+

**lemma** conflicting-true-full-cdcl<sub>W</sub>-merge-cp-iff-full-cdcl<sub>W</sub>-s'-without-decode:

**assumes**

confl: conflicting  $S = \text{None}$  **and**

inv: cdcl<sub>W</sub>-all-struct-inv  $S$

**shows**

full cdcl<sub>W</sub>-merge-cp  $S V \longleftrightarrow$  full cdcl<sub>W</sub>-s'-without-decode  $S V$  (is ?fw  $\longleftrightarrow$  ?s')

**proof**

**assume** ?fw

**then have** st: cdcl<sub>W</sub>-merge-cp\*\*  $S V$  **and** n-s: no-step cdcl<sub>W</sub>-merge-cp  $V$

**unfolding** full-def **by** blast+

**have** inv-V: cdcl<sub>W</sub>-all-struct-inv  $V$

**using** rtranclp-cdcl<sub>W</sub>-merge-cp-rtranclp-cdcl<sub>W</sub>[of  $S V$ ] <?fw> **unfolding** full-def

**by** (simp add: inv rtranclp-cdcl<sub>W</sub>-all-struct-inv-inv)

**consider**

(s') cdcl<sub>W</sub>-s'-without-decode\*\*  $S V$

| (propa)  $T$  **where** cdcl<sub>W</sub>-s'-without-decode\*\*  $S T$  **and** propagate\*\*  $T V$

| (bj)  $T U$  **where** cdcl<sub>W</sub>-s'-without-decode\*\*  $S T$  **and** full1 cdcl<sub>W</sub>-bj  $T U$  **and** propagate\*\*  $U V$

**using** rtranclp-cdcl<sub>W</sub>-merge-cp-is-rtranclp-cdcl<sub>W</sub>-s'-without-decode confl st n-s **by** metis

**then have** cdcl<sub>W</sub>-s'-without-decode\*\*  $S V$

**proof** cases

**case** s'

**then show** ?thesis .

**next**

**case** propa **note** s' = this(1) **and** propa = this(2)

**have** no-step cdcl<sub>W</sub>-cp  $V$

**using** no-step-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-cp n-s inv-V

**unfolding** cdcl<sub>W</sub>-all-struct-inv-def **by** blast

**then have** full1 cdcl<sub>W</sub>-cp  $T V$

**using** propa tranclp-mono[of propagate cdcl<sub>W</sub>-cp] cdcl<sub>W</sub>-cp.propagate' **unfolding** full1-def

**by** blast

**then have** cdcl<sub>W</sub>-s'-without-decode  $T V$

**using** conflict'-without-decode **by** blast

**then show** ?thesis **using** s' **by** auto

**next**

**case** bj **note** s' = this(1) **and** bj = this(2) **and** propa = this(3)

**have** no-step cdcl<sub>W</sub>-cp  $V$

**using** no-step-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-cp n-s inv-V

**unfolding** cdcl<sub>W</sub>-all-struct-inv-def **by** blast

**then have** full cdcl<sub>W</sub>-cp  $U V$

**using** propa rtranclp-mono[of propagate cdcl<sub>W</sub>-cp] cdcl<sub>W</sub>-cp.propagate' **unfolding** full-def

**by** blast

**moreover have** no-step cdcl<sub>W</sub>-cp  $T$

**using** bj **unfolding** full1-def **by** (fastforce dest!: tranclpD simp:cdcl<sub>W</sub>-bj.simps elim: rulesE)

**ultimately have** cdcl<sub>W</sub>-s'-without-decode  $T V$

```

    using bj'-without-decide[of T U V] bj by blast
  then show ?thesis using s' by auto
qed
moreover have no-step cdclW-s'-without-decide V
proof (cases conflicting V = None)
  case False
  { fix ss :: 'st'
    have ff1:  $\forall s \text{ sa. } \neg \text{cdcl}_W\text{-s'} \text{ s sa} \vee \text{full1 cdcl}_W\text{-cp s sa}$ 
       $\vee (\exists sb. \text{decide s sb} \wedge \text{no-step cdcl}_W\text{-cp s} \wedge \text{full cdcl}_W\text{-cp sb sa})$ 
       $\vee (\exists sb. \text{full1 cdcl}_W\text{-bj s sb} \wedge \text{no-step cdcl}_W\text{-cp s} \wedge \text{full cdcl}_W\text{-cp sb sa})$ 
      by (metis cdclW-s'.cases)
    have ff2:  $(\forall p \text{ s sa. } \neg \text{full1 p (s::'st) sa} \vee p^{++} \text{ s sa} \wedge \text{no-step p sa})$ 
       $\wedge (\forall p \text{ s sa. } (\neg p^{++} \text{ (s::'st) sa} \vee (\exists s. p \text{ sa s})) \vee \text{full1 p s sa})$ 
      by (meson full1-def)
    obtain ssa :: ('st  $\Rightarrow$  'st  $\Rightarrow$  bool)  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  'st where
      ff3:  $\forall p \text{ s sa. } \neg p^{++} \text{ s sa} \vee p \text{ s (ssa p s sa)} \wedge p^{**} \text{ (ssa p s sa) sa}$ 
      by (metis (no-types) tranclpD)
    then have a3:  $\neg \text{cdcl}_W\text{-cp}^{++} \text{ V ss}$ 
      using False by (metis option-full-cdclW-cp full-def)
    have  $\bigwedge s. \neg \text{cdcl}_W\text{-bj}^{++} \text{ V s}$ 
      using ff3 False by (metis confl st
        conflicting-not-true-rtranclp-cdclW-merge-cp-no-step-cdclW-bj)
    then have  $\neg \text{cdcl}_W\text{-s'-without-decide V ss}$ 
      using ff1 a3 ff2 by (metis cdclW-s'-without-decide.cases)
  }
  then show ?thesis
    by fastforce
  next
    case True
    then show ?thesis
      using conflicting-true-no-step-cdclW-merge-cp-no-step-s'-without-decide n-s inv-V
      unfolding cdclW-all-struct-inv-def by simp
  qed
ultimately show ?s' unfolding full-def by blast
next
  assume s': ?s'
  then have st: cdclW-s'-without-decide** S V and n-s: no-step cdclW-s'-without-decide V
    unfolding full-def by auto
  then have cdclW** S V
    using rtranclp-cdclW-s'-without-decide-rtranclp-cdclW st by blast
  then have inv-V: cdclW-all-struct-inv V using inv rtranclp-cdclW-all-struct-inv-inv by blast
  then have n-s-cp-V: no-step cdclW-cp V
    using cdclW-cp-normalized-element-all-inv[of V] full-fullI[of cdclW-cp V] n-s
    conflict'-without-decide conflicting-true-no-step-s'-without-decide-no-step-cdclW-merge-cp
    no-step-cdclW-merge-cp-no-step-cdclW-cp
    unfolding cdclW-all-struct-inv-def by presburger
  have n-s-bj: no-step cdclW-bj V
  proof (rule ccontr)
    assume  $\neg ?thesis$ 
    then obtain W where W: cdclW-bj V W by blast
    have cdclW-all-struct-inv W
      using W cdclW.simps cdclW-all-struct-inv-inv inv-V by blast
    then obtain W' where full1 cdclW-bj V W'
      using cdclW-bj-exists-normal-form[of W] full-fullI[of cdclW-bj V W] W
      unfolding cdclW-all-struct-inv-def

```

```

    by blast
  moreover
    then have  $cdcl_W^{++} V W'$ 
      using  $trancp\_mono[of\ cdcl_W\text{-}bj\ cdcl_W]$   $cdcl_W.other\ cdcl_W\text{-}o.bj$  unfolding  $full1\text{-}def$  by blast
    then have  $cdcl_W\text{-}all\text{-}struct\text{-}inv\ W'$ 
      by ( $meson\ inv\ V\ rtrancp\text{-}cdcl_W\text{-}all\text{-}struct\text{-}inv\text{-}inv\ trancp\text{-}into\text{-}rtrancp$ )
    then obtain  $X$  where  $full\ cdcl_W\text{-}cp\ W' X$ 
      using  $cdcl_W\text{-}cp\text{-}normalized\text{-}element\text{-}all\text{-}inv$  by blast
    ultimately show  $False$ 
      using  $bj'\text{-}without\text{-}decide\ n\text{-}s\text{-}cp\text{-}V\ n\text{-}s$  by blast
  qed
from  $s'$  consider
  ( $cp\text{-}true$ )  $cdcl_W\text{-}merge\text{-}cp^{**} S V$  and  $conflicting\ V = None$ 
| ( $cp\text{-}false$ )  $cdcl_W\text{-}merge\text{-}cp^{**} S V$  and  $conflicting\ V \neq None$  and  $no\text{-}step\ cdcl_W\text{-}cp\ V$  and
   $no\text{-}step\ cdcl_W\text{-}bj\ V$ 
| ( $cp\text{-}confl$ )  $T$  where  $cdcl_W\text{-}merge\text{-}cp^{**} S T$   $conflict\ T V$ 
  using  $rtrancp\text{-}cdcl_W\text{-}s'\text{-}without\text{-}decide\text{-}is\text{-}rtrancp\text{-}cdcl_W\text{-}merge\text{-}cp[of\ S\ V]$   $confl$ 
  unfolding  $full\text{-}def$  by meson
then have  $cdcl_W\text{-}merge\text{-}cp^{**} S V$ 
proof cases
  case  $cp\text{-}confl$  note  $S\text{-}T = this(1)$  and  $conf\text{-}V = this(2)$ 
  have  $full\ cdcl_W\text{-}bj\ V V$ 
    using  $conf\text{-}V\ n\text{-}s\text{-}bj$  unfolding  $full\text{-}def$  by fast
  then have  $cdcl_W\text{-}merge\text{-}cp\ T V$ 
    using  $cdcl_W\text{-}merge\text{-}cp.conflict'\ conf\text{-}V$  by auto
  then show ?thesis using  $S\text{-}T$  by auto
qed fast+
moreover
  then have  $cdcl_W^{**} S V$  using  $rtrancp\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}rtrancp\text{-}cdcl_W$  by blast
  then have  $cdcl_W\text{-}all\text{-}struct\text{-}inv\ V$ 
    using  $inv\ rtrancp\text{-}cdcl_W\text{-}all\text{-}struct\text{-}inv\text{-}inv$  by blast
  then have  $no\text{-}step\ cdcl_W\text{-}merge\text{-}cp\ V$ 
    using  $conflicting\text{-}true\text{-}no\text{-}step\text{-}s'\text{-}without\text{-}decide\text{-}no\text{-}step\text{-}cdcl_W\text{-}merge\text{-}cp\ s'$ 
    unfolding  $full\text{-}def$  by blast
  ultimately show ?fw unfolding  $full\text{-}def$  by auto
qed

lemma  $conflicting\text{-}true\text{-}full1\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}iff\text{-}full1\text{-}cdcl_W\text{-}s'\text{-}without\text{-}decode$ :
  assumes
     $confl$ :  $conflicting\ S = None$  and
     $inv$ :  $cdcl_W\text{-}all\text{-}struct\text{-}inv\ S$ 
  shows
     $full1\ cdcl_W\text{-}merge\text{-}cp\ S V \longleftrightarrow full1\ cdcl_W\text{-}s'\text{-}without\text{-}decide\ S V$ 
proof -
  have  $full\ cdcl_W\text{-}merge\text{-}cp\ S V = full\ cdcl_W\text{-}s'\text{-}without\text{-}decide\ S V$ 
    using  $confl\ conflicting\text{-}true\text{-}full\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}iff\text{-}full\text{-}cdcl_W\text{-}s'\text{-}without\text{-}decode\ inv$ 
    by simp
  then show ?thesis unfolding  $full\text{-}unfold\ full1\text{-}def\ trancp\text{-}unfold\text{-}begin$  by blast
qed

lemma  $conflicting\text{-}true\text{-}full1\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}imp\text{-}full1\text{-}cdcl_W\text{-}s'\text{-}without\text{-}decode$ :
  assumes
     $fw$ :  $full1\ cdcl_W\text{-}merge\text{-}cp\ S V$  and
     $inv$ :  $cdcl_W\text{-}all\text{-}struct\text{-}inv\ S$ 
  shows

```

$full1\ cdcl_W\text{-}s'\text{-without-decide}\ S\ V$   
**proof** –  
 have  $conflicting\ S = None$   
 using  $fw\ unfolding\ full1\text{-}def$  **by** ( $auto\ dest!::\ tranclpD\ simp::\ cdcl_W\text{-}merge\text{-}cp.\text{sims}\ elim::\ rulesE$ )  
 then show  $?thesis$   
 using  $conflicting\text{-}true\text{-}full1\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}iff\text{-}full1\text{-}cdcl_W\text{-}s'\text{-without-decide}\ fw\ inv$  **by**  $simp$   
**qed**

**inductive**  $cdcl_W\text{-}merge\text{-}stgy$  **where**  
 $fw\text{-}s\text{-}cp[intro]:\ full1\ cdcl_W\text{-}merge\text{-}cp\ S\ T \implies cdcl_W\text{-}merge\text{-}stgy\ S\ T \mid$   
 $fw\text{-}s\text{-}decide[intro]:\ decide\ S\ T \implies no\text{-}step\ cdcl_W\text{-}merge\text{-}cp\ S \implies full\ cdcl_W\text{-}merge\text{-}cp\ T\ U$   
 $\implies cdcl_W\text{-}merge\text{-}stgy\ S\ U$

**lemma**  $cdcl_W\text{-}merge\text{-}stgy\text{-}tranclp\text{-}cdcl_W\text{-}merge$ :  
 assumes  $fw::\ cdcl_W\text{-}merge\text{-}stgy\ S\ T$   
 shows  $cdcl_W\text{-}merge^{++}\ S\ T$   
**proof** –  
 { **fix**  $S\ T$   
 assume  $full1\ cdcl_W\text{-}merge\text{-}cp\ S\ T$   
 then have  $cdcl_W\text{-}merge^{++}\ S\ T$   
 using  $tranclp\text{-}mono[of\ cdcl_W\text{-}merge\text{-}cp\ cdcl_W\text{-}merge^{++}]$   $cdcl_W\text{-}merge\text{-}cp\text{-}tranclp\text{-}cdcl_W\text{-}merge$   
 $unfolding\ full1\text{-}def$   
**by**  $auto$   
 } **note**  $full1\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}cdcl_W\text{-}merge = this$   
 show  $?thesis$   
 using  $fw$   
**apply** ( $induction\ rule::\ cdcl_W\text{-}merge\text{-}stgy.\text{induct}$ )  
 using  $full1\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}cdcl_W\text{-}merge$  **apply**  $simp$   
**unfolding**  $full\text{-}unfold$  **by** ( $auto\ dest!::\ full1\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}cdcl_W\text{-}merge\ fw\text{-}decide$ )  
**qed**

**lemma**  $rtranclp\text{-}cdcl_W\text{-}merge\text{-}stgy\text{-}rtranclp\text{-}cdcl_W\text{-}merge$ :  
 assumes  $fw::\ cdcl_W\text{-}merge\text{-}stgy^{**}\ S\ T$   
 shows  $cdcl_W\text{-}merge^{**}\ S\ T$   
 using  $fw\ cdcl_W\text{-}merge\text{-}stgy\text{-}tranclp\text{-}cdcl_W\text{-}merge\ rtranclp\text{-}mono[of\ cdcl_W\text{-}merge\text{-}stgy\ cdcl_W\text{-}merge^{++}]$   
**unfolding**  $tranclp\text{-}rtranclp\text{-}rtranclp$  **by**  $blast$

**lemma**  $cdcl_W\text{-}merge\text{-}stgy\text{-}rtranclp\text{-}cdcl_W$ :  
 $cdcl_W\text{-}merge\text{-}stgy\ S\ T \implies cdcl_W^{**}\ S\ T$   
**apply** ( $induction\ rule::\ cdcl_W\text{-}merge\text{-}stgy.\text{induct}$ )  
 using  $rtranclp\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}rtranclp\text{-}cdcl_W$  **unfolding**  $full1\text{-}def$   
**apply** ( $simp\ add::\ tranclp\text{-}into\text{-}rtranclp$ )  
 using  $rtranclp\text{-}cdcl_W\text{-}merge\text{-}cp\text{-}rtranclp\text{-}cdcl_W\ cdcl_W\text{-}o.\text{decide}\ cdcl_W.\text{other}$  **unfolding**  $full\text{-}def$   
**by** ( $meson\ r\text{-}into\text{-}rtranclp\ rtranclp\text{-}trans$ )

**lemma**  $rtranclp\text{-}cdcl_W\text{-}merge\text{-}stgy\text{-}rtranclp\text{-}cdcl_W$ :  
 $cdcl_W\text{-}merge\text{-}stgy^{**}\ S\ T \implies cdcl_W^{**}\ S\ T$   
 using  $rtranclp\text{-}mono[of\ cdcl_W\text{-}merge\text{-}stgy\ cdcl_W^{**}]$   $cdcl_W\text{-}merge\text{-}stgy\text{-}rtranclp\text{-}cdcl_W$  **by**  $auto$

**lemma**  $cdcl_W\text{-}merge\text{-}stgy\text{-}cases[consumes\ 1,\ case\text{-}names\ fw\text{-}s\text{-}cp\ fw\text{-}s\text{-}decide]$ :  
 assumes  
 $cdcl_W\text{-}merge\text{-}stgy\ S\ U$   
 $full1\ cdcl_W\text{-}merge\text{-}cp\ S\ U \implies P$   
 $\bigwedge T.\ decide\ S\ T \implies no\text{-}step\ cdcl_W\text{-}merge\text{-}cp\ S \implies full\ cdcl_W\text{-}merge\text{-}cp\ T\ U \implies P$   
 shows  $P$

```

using assms by (auto simp: cdclW-merge-stgy.simps)

inductive cdclW-s'-w :: 'st ⇒ 'st ⇒ bool where
conflict': full1 cdclW-s'-without-decide S S' ⇒ cdclW-s'-w S S' |
decide': decide S S' ⇒ no-step cdclW-s'-without-decide S ⇒ full cdclW-s'-without-decide S' S''
⇒ cdclW-s'-w S S''

lemma cdclW-s'-w-rtranclp-cdclW:
cdclW-s'-w S T ⇒ cdclW** S T
apply (induction rule: cdclW-s'-w.induct)
  using rtranclp-cdclW-s'-without-decide-rtranclp-cdclW unfolding full1-def
  apply (simp add: tranclp-into-rtranclp)
using rtranclp-cdclW-s'-without-decide-rtranclp-cdclW unfolding full-def
by (meson decide other rtranclp-into-tranclp2 tranclp-into-rtranclp)

lemma rtranclp-cdclW-s'-w-rtranclp-cdclW:
cdclW-s'-w** S T ⇒ cdclW** S T
using rtranclp-mono[of cdclW-s'-w cdclW**] cdclW-s'-w-rtranclp-cdclW by auto

lemma no-step-cdclW-cp-no-step-cdclW-s'-without-decide:
assumes no-step cdclW-cp S and conflicting S = None and inv: cdclW-M-level-inv S
shows no-step cdclW-s'-without-decide S
by (metis assms cdclW-cp.conflict' cdclW-cp.propagate' cdclW-merge-restart-cases tranclpD
conflicting-true-no-step-cdclW-merge-cp-no-step-s'-without-decide)

lemma no-step-cdclW-cp-no-step-cdclW-merge-restart:
assumes no-step cdclW-cp S and conflicting S = None
shows no-step cdclW-merge-cp S
by (metis assms(1) cdclW-cp.conflict' cdclW-cp.propagate' cdclW-merge-restart-cases tranclpD)
lemma after-cdclW-s'-without-decide-no-step-cdclW-cp:
assumes cdclW-s'-without-decide S T
shows no-step cdclW-cp T
using assms by (induction rule: cdclW-s'-without-decide.induct) (auto simp: full1-def full-def)

lemma no-step-cdclW-s'-without-decide-no-step-cdclW-cp:
cdclW-all-struct-inv S ⇒ no-step cdclW-s'-without-decide S ⇒ no-step cdclW-cp S
by (simp add: conflicting-true-no-step-s'-without-decide-no-step-cdclW-merge-cp
no-step-cdclW-merge-cp-no-step-cdclW-cp cdclW-all-struct-inv-def)

lemma after-cdclW-s'-w-no-step-cdclW-cp:
assumes cdclW-s'-w S T and cdclW-all-struct-inv S
shows no-step cdclW-cp T
using assms
proof (induction rule: cdclW-s'-w.induct)
  case conflict'
  then show ?case
    by (auto simp: full1-def tranclp-unfold-end after-cdclW-s'-without-decide-no-step-cdclW-cp)
next
  case (decide' S T U)
  moreover
    then have cdclW** S U
    using rtranclp-cdclW-s'-without-decide-rtranclp-cdclW[of T U] cdclW.other[of S T]
    cdclW-o.decide unfolding full-def by auto
    then have cdclW-all-struct-inv U
    using decide'.prems rtranclp-cdclW-all-struct-inv-inv by blast

```

ultimately show ?case  
 using no-step-cdcl<sub>W</sub>-s'-without-decide-no-step-cdcl<sub>W</sub>-cp unfolding full-def by blast  
 qed

lemma rtrancpl-cdcl<sub>W</sub>-s'-w-no-step-cdcl<sub>W</sub>-cp-or-eq:  
 assumes cdcl<sub>W</sub>-s'-w\*\* S T and cdcl<sub>W</sub>-all-struct-inv S  
 shows S = T ∨ no-step cdcl<sub>W</sub>-cp T  
 using assms  
 proof (induction rule: rtrancpl-induct)  
 case base  
 then show ?case by simp  
 next  
 case (step T U)  
 moreover have cdcl<sub>W</sub>-all-struct-inv T  
 using rtrancpl-cdcl<sub>W</sub>-s'-w-rtrancpl-cdcl<sub>W</sub>[of S U] assms(2) rtrancpl-cdcl<sub>W</sub>-all-struct-inv-inv  
 rtrancpl-cdcl<sub>W</sub>-s'-w-rtrancpl-cdcl<sub>W</sub> step.hyps(1) by blast  
 ultimately show ?case using after-cdcl<sub>W</sub>-s'-w-no-step-cdcl<sub>W</sub>-cp by fast  
 qed

lemma rtrancpl-cdcl<sub>W</sub>-merge-stgy'-no-step-cdcl<sub>W</sub>-cp-or-eq:  
 assumes cdcl<sub>W</sub>-merge-stgy\*\* S T and inv: cdcl<sub>W</sub>-all-struct-inv S  
 shows S = T ∨ no-step cdcl<sub>W</sub>-cp T  
 using assms  
 proof (induction rule: rtrancpl-induct)  
 case base  
 then show ?case by simp  
 next  
 case (step T U)  
 moreover have cdcl<sub>W</sub>-all-struct-inv T  
 using rtrancpl-cdcl<sub>W</sub>-merge-stgy-rtrancpl-cdcl<sub>W</sub>[of S U] assms(2) rtrancpl-cdcl<sub>W</sub>-all-struct-inv-inv  
 rtrancpl-cdcl<sub>W</sub>-s'-w-rtrancpl-cdcl<sub>W</sub> step.hyps(1)  
 by (meson rtrancpl-cdcl<sub>W</sub>-merge-stgy-rtrancpl-cdcl<sub>W</sub>)  
 ultimately show ?case  
 using after-cdcl<sub>W</sub>-s'-w-no-step-cdcl<sub>W</sub>-cp inv unfolding cdcl<sub>W</sub>-all-struct-inv-def  
 by (metis cdcl<sub>W</sub>-all-struct-inv-def cdcl<sub>W</sub>-merge-stgy.simps full1-def full-def  
 no-step-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-cp rtrancpl-cdcl<sub>W</sub>-all-struct-inv-inv  
 rtrancpl-cdcl<sub>W</sub>-merge-stgy-rtrancpl-cdcl<sub>W</sub> trancpl.intros(1) trancpl-into-rtrancpl)  
 qed

lemma no-step-cdcl<sub>W</sub>-s'-without-decide-no-step-cdcl<sub>W</sub>-bj:  
 assumes no-step cdcl<sub>W</sub>-s'-without-decide S and inv: cdcl<sub>W</sub>-all-struct-inv S  
 shows no-step cdcl<sub>W</sub>-bj S  
 proof (rule ccontr)  
 assume ¬ ?thesis  
 then obtain T where S-T: cdcl<sub>W</sub>-bj S T  
 by auto  
 have cdcl<sub>W</sub>-all-struct-inv T  
 using S-T cdcl<sub>W</sub>-all-struct-inv-inv inv other by blast  
 then obtain T' where full1 cdcl<sub>W</sub>-bj S T'  
 using cdcl<sub>W</sub>-bj-exists-normal-form[of T] full-full1 S-T unfolding cdcl<sub>W</sub>-all-struct-inv-def  
 by metis  
 moreover  
 then have cdcl<sub>W</sub>\*\* S T'  
 using rtrancpl-mono[of cdcl<sub>W</sub>-bj cdcl<sub>W</sub>] cdcl<sub>W</sub>.other cdcl<sub>W</sub>-o.bj trancpl-into-rtrancpl[of cdcl<sub>W</sub>-bj]  
 unfolding full1-def by blast

then have  $cdcl_W\text{-all-struct-inv } T'$   
 using  $inv \text{ rtrancp-cdcl}_W\text{-all-struct-inv-inv}$  by  $blast$   
 then obtain  $U$  where  $full \text{ cdcl}_W\text{-cp } T' U$   
 using  $cdcl_W\text{-cp-normalized-element-all-inv}$  by  $blast$   
 moreover have  $no\text{-step } cdcl_W\text{-cp } S$   
 using  $S\text{-}T$  by  $(auto \text{ simp: } cdcl_W\text{-bj.simps elim: rulesE})$   
 ultimately show  $False$   
 using  $assms \text{ cdcl}_W\text{-s'-without-decide.intros}(2)[of \text{ } S \text{ } T' \text{ } U]$  by  $fast$   
 qed

**lemma**  $cdcl_W\text{-s'-w-no-step-cdcl}_W\text{-bj}$ :  
 assumes  $cdcl_W\text{-s'-w } S \text{ } T$  and  $cdcl_W\text{-all-struct-inv } S$   
 shows  $no\text{-step } cdcl_W\text{-bj } T$   
 using  $assms$  apply  $induction$   
 using  $rtrancp\text{-cdcl}_W\text{-s'-without-decide-rtrancp-cdcl}_W \text{ rtrancp-cdcl}_W\text{-all-struct-inv-inv}$   
 $no\text{-step-cdcl}_W\text{-s'-without-decide-no-step-cdcl}_W\text{-bj}$  **unfolding**  $full1\text{-def}$   
 apply  $(meson \text{ trancp-into-rtrancp})$   
 using  $rtrancp\text{-cdcl}_W\text{-s'-without-decide-rtrancp-cdcl}_W \text{ rtrancp-cdcl}_W\text{-all-struct-inv-inv}$   
 $no\text{-step-cdcl}_W\text{-s'-without-decide-no-step-cdcl}_W\text{-bj}$  **unfolding**  $full\text{-def}$   
 by  $(meson \text{ cdcl}_W\text{-merge-restart-cdcl}_W \text{ fw-r-decide})$

**lemma**  $rtrancp\text{-cdcl}_W\text{-s'-w-no-step-cdcl}_W\text{-bj-or-eq}$ :  
 assumes  $cdcl_W\text{-s'-w}^{**} S \text{ } T$  and  $cdcl_W\text{-all-struct-inv } S$   
 shows  $S = T \vee no\text{-step } cdcl_W\text{-bj } T$   
 using  $assms$  apply  $induction$   
 apply  $simp$   
 using  $rtrancp\text{-cdcl}_W\text{-s'-w-rtrancp-cdcl}_W \text{ rtrancp-cdcl}_W\text{-all-struct-inv-inv}$   
 $cdcl_W\text{-s'-w-no-step-cdcl}_W\text{-bj}$  by  $meson$

**lemma**  $rtrancp\text{-cdcl}_W\text{-s'-no-step-cdcl}_W\text{-s'-without-decide-decomp-into-cdcl}_W\text{-merge}$ :  
 assumes  
 $cdcl_W\text{-s'}^{**} R \text{ } V$  and  
 $conflicting \text{ } R = None$  and  
 $inv: cdcl_W\text{-all-struct-inv } R$   
 shows  $(cdcl_W\text{-merge-stgy}^{**} R \text{ } V \wedge conflicting \text{ } V = None)$   
 $\vee (cdcl_W\text{-merge-stgy}^{**} R \text{ } V \wedge conflicting \text{ } V \neq None \wedge no\text{-step } cdcl_W\text{-bj } V)$   
 $\vee (\exists S \text{ } T \text{ } U. cdcl_W\text{-merge-stgy}^{**} R \text{ } S \wedge no\text{-step } cdcl_W\text{-merge-cp } S \wedge decide \text{ } S \text{ } T$   
 $\wedge cdcl_W\text{-merge-cp}^{**} T \text{ } U \wedge conflict \text{ } U \text{ } V)$   
 $\vee (\exists S \text{ } T. cdcl_W\text{-merge-stgy}^{**} R \text{ } S \wedge no\text{-step } cdcl_W\text{-merge-cp } S \wedge decide \text{ } S \text{ } T$   
 $\wedge cdcl_W\text{-merge-cp}^{**} T \text{ } V$   
 $\wedge conflicting \text{ } V = None)$   
 $\vee (cdcl_W\text{-merge-cp}^{**} R \text{ } V \wedge conflicting \text{ } V = None)$   
 $\vee (\exists U. cdcl_W\text{-merge-cp}^{**} R \text{ } U \wedge conflict \text{ } U \text{ } V)$   
 using  $assms(1,2)$

**proof**  $induction$

**case**  $base$

**then show**  $?case$  by  $simp$

**next**

**case**  $(step \text{ } V \text{ } W)$  **note**  $st = this(1)$  and  $s' = this(2)$  and  $IH = this(3)[OF \text{ } this(4)]$  and

$n\text{-s-}R = this(4)$

**from**  $s'$

**show**  $?case$

**proof**  $cases$

**case**  $conflict'$

**consider**

```

  (s') cdclW-merge-stgy** R V
| (dec-conf) S T U where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and
  decide S T and cdclW-merge-cp** T U and conflict U V
| (dec) S T where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and decide S T
  and cdclW-merge-cp** T V and conflicting V = None
| (cp) cdclW-merge-cp** R V
| (cp-conf) U where cdclW-merge-cp** R U and conflict U V
using IH by meson
then show ?thesis
proof cases
next
  case s'
  then have R = V
    by (metis full1-def inv local.conflict' tranclp-unfold-begin
      rtranclp-cdclW-merge-stgy'-no-step-cdclW-cp-or-eq)
  consider
    (V-W) V = W
  | (propa) propagate++ V W and conflicting W = None
  | (propa-conf) V' where propagate** V V' and conflict V' W
  using tranclp-cdclW-cp-propagate-with-conflict-or-not[of V W] conflict'
  unfolding full-unfold full1-def by meson
  then show ?thesis
  proof cases
    case V-W
    then show ?thesis using ⟨R = V⟩ n-s-R by simp
  next
    case propa
    then show ?thesis using ⟨R = V⟩ by (auto intro: cdclW-merge-cp.intros)
  next
    case propa-conf
    moreover
      then have cdclW-merge-cp** V V'
      by (metis rtranclp-unfold cdclW-merge-cp.propagate' r-into-rtranclp)
    ultimately show ?thesis using s' ⟨R = V⟩ by blast
  qed
next
  case dec-conf note - = this(5)
  then have False using conflict' unfolding full1-def by (auto dest!: tranclpD elim: rulesE)
  then show ?thesis by fast
next
  case dec note T-V = this(4)
  consider
    (propa) propagate++ V W and conflicting W = None
  | (propa-conf) V' where propagate** V V' and conflict V' W
  using tranclp-cdclW-cp-propagate-with-conflict-or-not[of V W] conflict'
  unfolding full1-def by meson
  then show ?thesis
  proof cases
    case propa
    then show ?thesis
    by (meson T-V cdclW-merge-cp.propagate' dec rtranclp.rtrancl-into-rtrancl)
  next
    case propa-conf
    then have cdclW-merge-cp** T V'
    using T-V by (metis rtranclp-unfold cdclW-merge-cp.propagate' rtranclp.simps)

```



```

    then show ?thesis using dec propa-conf(2) by metis
  qed
next
  case cp
  consider
    (propa) propagate++ V W and conflicting W = None
    | (propa-conf) V' where propagate** V V' and conflict V' W
  using tranclp-cdclW-cp-propagate-with-conflict-or-not[of V W] conflict'
  unfolding full1-def by meson
  then show ?thesis
  proof cases
    case propa
    then show ?thesis by (meson cdclW-merge-cp.propagate' cp
      rtranclp.rtrancl-into-rtrancl)
    next
    case propa-conf
    then show ?thesis
      using propa-conf(2) cp
      by (metis (full-types) cdclW-merge-cp.propagate' rtranclp.rtrancl-into-rtrancl
        rtranclp-unfold)
  qed
next
  case cp-conf
  then show ?thesis using conflict' unfolding full1-def by (fastforce dest!: tranclpD
    elim!: rulesE)
  qed
next
  case (decide' V')
  then have conf-V: conflicting V = None
    by (auto elim: rulesE)
  consider
    (s') cdclW-merge-stgy** R V
    | (dec-conf) S T U where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and
      decide S T and cdclW-merge-cp** T U and conflict U V
    | (dec) S T where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and decide S T
      and cdclW-merge-cp** T V and conflicting V = None
    | (cp) cdclW-merge-cp** R V
    | (cp-conf) U where cdclW-merge-cp** R U and conflict U V
  using IH by meson
  then show ?thesis
  proof cases
    case s'
    have conf-V': conflicting V' = None using decide'(1) by (auto elim: rulesE)
    have full: full1 cdclW-cp V' W ∨ (V' = W ∧ no-step cdclW-cp W)
      using decide'(3) unfolding full-unfold by blast
    consider
      (V'-W) V' = W
      | (propa) propagate++ V' W and conflicting W = None
      | (propa-conf) V'' where propagate** V' V'' and conflict V'' W
    using tranclp-cdclW-cp-propagate-with-conflict-or-not[of V W] decide'
      ⟨full1 cdclW-cp V' W ∨ V' = W ∧ no-step cdclW-cp W⟩ unfolding full1-def
      by (metis tranclp-cdclW-cp-propagate-with-conflict-or-not)
    then show ?thesis
    proof cases
      case V'-W

```

```

then show ?thesis
  using conf1-V' local.decide'(1,2) s' conf-V
  no-step-cdclW-cp-no-step-cdclW-merge-restart[of V]
  by auto
next
case propa
then show ?thesis using local.decide'(1,2) s' by (metis cdclW-merge-cp.simps conf-V
  no-step-cdclW-cp-no-step-cdclW-merge-restart r-into-rtrancpl)
next
case propa-conf1
then have cdclW-merge-cp** V' V''
  by (metis rtrancpl-unfold cdclW-merge-cp.propagate' r-into-rtrancpl)
then show ?thesis
  using local.decide'(1,2) propa-conf1(2) s' conf-V
  no-step-cdclW-cp-no-step-cdclW-merge-restart
  by metis
qed
next
case (dec) note s' = this(1) and dec = this(2) and cp = this(3) and ns-cp-T = this(4)
have full cdclW-merge-cp T V
  unfolding full-def by (simp add: conf-V local.decide'(2)
    no-step-cdclW-cp-no-step-cdclW-merge-restart ns-cp-T)
moreover have no-step cdclW-merge-cp V
  by (simp add: conf-V local.decide'(2) no-step-cdclW-cp-no-step-cdclW-merge-restart)
moreover have no-step cdclW-merge-cp S
  by (metis dec)
ultimately have cdclW-merge-stgy S V
  using cp by blast
then have cdclW-merge-stgy** R V using s' by auto
consider
  (V'-W) V' = W
  | (propa) propagate++ V' W and conflicting W = None
  | (propa-conf1) V'' where propagate** V' V'' and conflict V'' W
  using trancpl-cdclW-cp-propagate-with-conflict-or-not[of V' W] decide'
  unfolding full-unfold full1-def by meson
then show ?thesis
proof cases
case V'-W
moreover have conflicting V' = None
  using decide'(1) by (auto elim: rulesE)
ultimately show ?thesis
  using ⟨cdclW-merge-stgy** R V⟩ decide' ⟨no-step cdclW-merge-cp V⟩ by blast
next
case propa
moreover then have cdclW-merge-cp V' W by (blast intro: cdclW-merge-cp.intros)
ultimately show ?thesis
  using ⟨cdclW-merge-stgy** R V⟩ decide' ⟨no-step cdclW-merge-cp V⟩
  by (meson r-into-rtrancpl)
next
case propa-conf1
moreover then have cdclW-merge-cp** V' V''
  by (metis cdclW-merge-cp.propagate' rtrancpl-unfold trancpl-unfold-end)
ultimately show ?thesis using ⟨cdclW-merge-stgy** R V⟩ decide'
  ⟨no-step cdclW-merge-cp V⟩ by (meson r-into-rtrancpl)
qed

```

```

next
  case cp
  have no-step cdclW-merge-cp V
    using conf-V local.decide'(2) no-step-cdclW-cp-no-step-cdclW-merge-restart by auto
  then have full cdclW-merge-cp R V
    unfolding full-def using cp by fast
  then have cdclW-merge-stgy** R V
    unfolding full-unfold by auto
  have full1 cdclW-cp V' W  $\vee$  (V' = W  $\wedge$  no-step cdclW-cp W)
    using decide'(3) unfolding full-unfold by blast

consider
  (V'-W) V' = W
  | (propa) propagate++ V' W and conflicting W = None
  | (propa-confl) V'' where propagate** V' V'' and conflict V'' W
  using tranclp-cdclW-cp-propagate-with-conflict-or-not[of V' W] decide'
  unfolding full-unfold full1-def by meson
then show ?thesis

proof cases
  case V'-W
  moreover have conflicting V' = None
    using decide'(1) by (auto elim: rulesE)
  ultimately show ?thesis
    using ⟨cdclW-merge-stgy** R V⟩ decide' ⟨no-step cdclW-merge-cp V⟩ by blast
next
  case propa
  moreover then have cdclW-merge-cp V' W
    by (blast intro: cdclW-merge-cp.intros)
  ultimately show ?thesis using ⟨cdclW-merge-stgy** R V⟩ decide'
    ⟨no-step cdclW-merge-cp V⟩ by (meson r-into-rtranclp)
next
  case propa-confl
  moreover then have cdclW-merge-cp** V' V''
    by (metis cdclW-merge-cp.propagate' rtranclp-unfold tranclp-unfold-end)
  ultimately show ?thesis using ⟨cdclW-merge-stgy** R V⟩ decide'
    ⟨no-step cdclW-merge-cp V⟩ by (meson r-into-rtranclp)
qed
next
  case (dec-confl)
  show ?thesis using conf-V dec-confl(5) by (auto elim!: rulesE
    simp del: state-simp simp: state-eq-def)
next
  case cp-confl
  then show ?thesis using decide' apply - by (intro HOL.disjI2) (fastforce elim: rulesE
    simp del: state-simp simp: state-eq-def)
qed
next
  case (bj' V')
  then have  $\neg$ no-step cdclW-bj V
    by (auto dest: tranclpD simp: full1-def)
  then consider
    (s') cdclW-merge-stgy** R V and conflicting V = None
    | (dec-confl) S T U where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and
      decide S T and cdclW-merge-cp** T U and conflict U V

```

```

| (dec) S T where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and decide S T
  and cdclW-merge-cp** T V and conflicting V = None
| (cp) cdclW-merge-cp** R V and conflicting V = None
| (cp-confl) U where cdclW-merge-cp** R U and conflict U V
using IH by meson
then show ?thesis
proof cases
  case s' note - = this(2)
  then have False
    using bj'(1) unfolding full1-def by (force dest!: tranclpD simp: cdclW-bj.simps
      elim: rulesE)
  then show ?thesis by fast
next
  case dec note - = this(5)
  then have False
    using bj'(1) unfolding full1-def by (force dest!: tranclpD simp: cdclW-bj.simps
      elim: rulesE)
  then show ?thesis by fast
next
  case dec-confl
  then have cdclW-merge-cp U V'
    using bj' cdclW-merge-cp.intros(1)[of U V V'] by (simp add: full-unfold)
  then have cdclW-merge-cp** T V'
    using dec-confl(4) by simp
  consider
    (V'-W) V' = W
  | (propa) propagate++ V' W and conflicting W = None
  | (propa-confl) V'' where propagate** V' V'' and conflict V'' W
  using tranclp-cdclW-cp-propagate-with-conflict-or-not[of V' W] bj'(3)
  unfolding full-unfold full1-def by meson
then show ?thesis
proof cases
  case V'-W
  then have no-step cdclW-cp V'
    using bj'(3) unfolding full-def by auto
  then have no-step cdclW-merge-cp V'
    by (metis cdclW-cp.propagate' cdclW-merge-cp.cases tranclpD
      no-step-cdclW-cp-no-conflict-no-propagate(1) )
  then have full1 cdclW-merge-cp T V'
    unfolding full1-def using ⟨cdclW-merge-cp U V'⟩ dec-confl(4) by auto
  then have full cdclW-merge-cp T V'
    by (simp add: full-unfold)
  then have cdclW-merge-stgy S V'
    using dec-confl(3) cdclW-merge-stgy.fw-s-decide ⟨no-step cdclW-merge-cp S⟩ by blast
  then have cdclW-merge-stgy** R V'
    using ⟨cdclW-merge-stgy** R S⟩ by auto
  show ?thesis
  proof cases
    assume conflicting W = None
    then show ?thesis using ⟨cdclW-merge-stgy** R V'⟩ ⟨V' = W⟩ by auto
  next
    assume conflicting W ≠ None
    then show ?thesis
      using ⟨cdclW-merge-stgy** R V'⟩ ⟨V' = W⟩ by (metis ⟨cdclW-merge-cp U V'⟩
        conflictE conflicting-not-true-rtranclp-cdclW-merge-cp-no-step-cdclW-bj

```

```

      dec-confl(5) map-option-is-None r-into-rtranclp)
    qed
  next
    case propa
    moreover then have cdclW-merge-cp V' W by (blast intro: cdclW-merge-cp.intros)
    ultimately show ?thesis using decide' by (meson ⟨cdclW-merge-cp** T V⟩ dec-confl(1-3)
      rtranclp.rtrancl-into-rtrancl)
  next
    case propa-confl
    moreover then have cdclW-merge-cp** V' V''
      by (metis cdclW-merge-cp.propagate' rtranclp-unfold tranclp-unfold-end)
    ultimately show ?thesis by (meson ⟨cdclW-merge-cp** T V⟩ dec-confl(1-3) rtranclp-trans)
  qed
next
  case cp note - = this(2)
  then show ?thesis using bj'(1) ⟨¬ no-step cdclW-bj V⟩
    conflicting-not-true-rtranclp-cdclW-merge-cp-no-step-cdclW-bj by auto
next
  case cp-confl
  then have cdclW-merge-cp U V' by (simp add: cdclW-merge-cp.conflict' full-unfold
    local.bj'(1))
  consider
    (V'-W) V' = W
  | (propa) propagate++ V' W and conflicting W = None
  | (propa-confl) V'' where propagate** V' V'' and conflict V'' W
  using tranclp-cdclW-cp-propagate-with-conflict-or-not[of V' W] bj'
  unfolding full-unfold full1-def by meson
  then show ?thesis

proof cases
  case V'-W
  show ?thesis
  proof cases
    assume conflicting V' = None
    then show ?thesis
      using V'-W ⟨cdclW-merge-cp U V'⟩ cp-confl(1) by force
  next
    assume confl: conflicting V' ≠ None
    then have no-step cdclW-merge-stgy V'
      by (fastforce simp: cdclW-merge-stgy.simps full1-def full-def
        cdclW-merge-cp.simps dest!: tranclpD elim: rulesE)
    have no-step cdclW-merge-cp V'
      using confl by (auto simp: full1-def full-def cdclW-merge-cp.simps
        dest!: tranclpD elim: rulesE)
    moreover have cdclW-merge-cp U W
      using V'-W ⟨cdclW-merge-cp U V'⟩ by blast
    ultimately have full1 cdclW-merge-cp R V'
      using cp-confl(1) V'-W unfolding full1-def by auto
    then have cdclW-merge-stgy R V'
      by auto
    moreover have no-step cdclW-merge-stgy V'
      using confl ⟨no-step cdclW-merge-cp V'⟩ by (auto simp: cdclW-merge-stgy.simps
        full1-def dest!: tranclpD elim: rulesE)
    ultimately have cdclW-merge-stgy** R V' by auto
  { fix ss :: 'st

```

```

    have  $cdcl_W\text{-merge-cp } U \ W$ 
      using  $V' \cdot W \langle cdcl_W\text{-merge-cp } U \ V' \rangle$  by blast
    then have  $\neg cdcl_W\text{-bj } W \ ss$ 
      by (meson conflicting-not-true-rtrancpl-cdcl_W-merge-cp-no-step-cdcl_W-bj
          cp-conf(1) rtrancpl.rtrancpl-into-rtrancpl step.prem)
    then have  $cdcl_W\text{-merge-stgy}^{**} R \ W \wedge \text{conflicting } W = \text{None} \vee$ 
       $cdcl_W\text{-merge-stgy}^{**} R \ W \wedge \neg cdcl_W\text{-bj } W \ ss$ 
      using  $V' \cdot W \langle cdcl_W\text{-merge-stgy}^{**} R \ V' \rangle$  by presburger }
    then show ?thesis
      by presburger
  qed
next
case propa
moreover then have  $cdcl_W\text{-merge-cp } V' \ W$ 
  by (blast intro: cdcl_W-merge-cp.intros)
ultimately show ?thesis using  $\langle cdcl_W\text{-merge-cp } U \ V' \rangle \text{ cp-conf(1)}$  by force
next
case propa-conf
moreover then have  $cdcl_W\text{-merge-cp}^{**} V' \ V''$ 
  by (metis cdcl_W-merge-cp.propagate' rtrancpl-unfold trancpl-unfold-end)
ultimately show ?thesis
  using  $\langle cdcl_W\text{-merge-cp } U \ V' \rangle \text{ cp-conf(1)}$  by (metis rtrancpl.rtrancpl-into-rtrancpl
      rtrancpl-trans)
qed
qed
qed
qed

```

**lemma**  $decide\text{-rtrancpl-cdcl}_W\text{-s}'\text{-rtrancpl-cdcl}_W\text{-s}'$ :

**assumes**

$dec$ :  $decide \ S \ T$  and

$cdcl_W\text{-s}'^{**} \ T \ U$  and

$n\text{-s-S}$ :  $no\text{-step } cdcl_W\text{-cp } S$  and

$no\text{-step } cdcl_W\text{-cp } U$

**shows**  $cdcl_W\text{-s}'^{**} \ S \ U$

**using**  $assms(2,4)$

**proof** induction

**case**  $(step \ U \ V)$  **note**  $st = this(1)$  and  $s' = this(2)$  and  $IH = this(3)$  and  $n\text{-s} = this(4)$

**consider**

$(TU) \ T = U$

|  $(s'\text{-st}) \ T' \text{ where } cdcl_W\text{-s}' \ T \ T' \text{ and } cdcl_W\text{-s}'^{**} \ T' \ U$

**using**  $st[\text{unfolded rtrancpl-unfold}]$  **by**  $(auto \ dest! : trancplD)$

**then show** ?case

**proof** cases

**case**  $TU$

**then show** ?thesis

**proof** –

**assume**  $a1 : T = U$

**then have**  $f2 : cdcl_W\text{-s}' \ T \ V$

**using**  $s'$  **by** force

**obtain**  $ss :: 'st$  **where**

$ss : cdcl_W\text{-s}'^{**} \ S \ T \vee cdcl_W\text{-cp } T \ ss$

**using**  $a1 \ step.IH$  **by** blast–

**obtain**  $ssa :: 'st \Rightarrow 'st$  **where**

$f3 : \forall s \ sa \ sb. (\neg decide \ s \ sa \vee cdcl_W\text{-cp } s \ (ssa \ s) \vee \neg full \ cdcl_W\text{-cp } sa \ sb)$

```

       $\vee \text{cdcl}_W\text{-}s' \ s \ sb$ 
      using  $\text{cdcl}_W\text{-}s'.\text{decide}'$  by moura
    have  $\forall s \ sa. \neg \text{cdcl}_W\text{-}s' \ s \ sa \vee \text{full1 } \text{cdcl}_W\text{-}cp \ s \ sa \vee$ 
       $(\exists sb. \text{decide } s \ sb \wedge \text{no-step } \text{cdcl}_W\text{-}cp \ s \wedge \text{full } \text{cdcl}_W\text{-}cp \ sb \ sa) \vee$ 
       $(\exists sb. \text{full1 } \text{cdcl}_W\text{-}bj \ s \ sb \wedge \text{no-step } \text{cdcl}_W\text{-}cp \ s \wedge \text{full } \text{cdcl}_W\text{-}cp \ sb \ sa)$ 
      by (metis  $\text{cdcl}_W\text{-}s'E$ )
    then have  $\exists s. \text{cdcl}_W\text{-}s'^{**} \ S \ s \wedge \text{cdcl}_W\text{-}s' \ s \ V$ 
      using  $f3 \ ss \ f2$  by (metis dec full1-is-full n-s-S rtrancpl-unfold)
    then show ?thesis
      by force
  qed
next
case ( $s'\text{-}st \ T'$ ) note  $s'\text{-}T' = \text{this}(1)$  and  $st = \text{this}(2)$ 
have  $\text{cdcl}_W\text{-}s'^{**} \ S \ T'$ 
  using  $s'\text{-}T'$ 
  proof cases
    case conflict'
    then have  $\text{cdcl}_W\text{-}s' \ S \ T'$ 
      using dec  $\text{cdcl}_W\text{-}s'.\text{decide}' \ n\text{-}s\text{-}S$  by (simp add: full-unfold)
    then show ?thesis
      using st by auto
  next
    case ( $\text{decide}' \ T''$ )
    then have  $\text{cdcl}_W\text{-}s' \ S \ T$ 
      using dec  $\text{cdcl}_W\text{-}s'.\text{decide}' \ n\text{-}s\text{-}S$  by (simp add: full-unfold)
    then show ?thesis using  $\text{decide}' \ s'\text{-}T'$  by auto
  next
    case bj'
    then have False
      using dec unfolding full1-def by (fastforce dest!: trancplD simp:  $\text{cdcl}_W\text{-}bj.\text{sims}$ 
        elim: rulesE)
    then show ?thesis by fast
  qed
  then show ?thesis using  $s' \ st$  by auto
qed
next
case base
then have  $\text{full } \text{cdcl}_W\text{-}cp \ T \ T$ 
  by (simp add: full-unfold)
then show ?case
  using  $\text{cdcl}_W\text{-}s'.\text{sims}$  dec  $n\text{-}s\text{-}S$  by auto
qed

lemma rtrancpl-cdclW-merge-stgy-rtrancpl-cdclW-s':
  assumes
     $\text{cdcl}_W\text{-merge-stgy}^{**} \ R \ V$  and
     $\text{inv: } \text{cdcl}_W\text{-all-struct-inv } R$ 
  shows  $\text{cdcl}_W\text{-}s'^{**} \ R \ V$ 
  using assms(1)
proof induction
  case base
  then show ?case by simp
next
case (step  $S \ T$ ) note  $st = \text{this}(1)$  and  $fw = \text{this}(2)$  and  $IH = \text{this}(3)$ 
have  $\text{cdcl}_W\text{-all-struct-inv } S$ 

```

```

    using inv rtrancp-cdclW-all-struct-inv-inv rtrancp-cdclW-merge-stgy-rtrancp-cdclW st by blast
  from fw show ?case
  proof (cases rule: cdclW-merge-stgy-cases)
    case fw-s-cp
    have  $\bigwedge s. \neg \text{full } \text{cdcl}_W\text{-merge-cp } s \ S$ 
      using fw-s-cp unfolding full-def full1-def by (metis trancp-unfold-begin)
    then have  $S = R$ 
      using fw-s-cp unfolding full1-def by (metis cdclW-cp.conflict' cdclW-cp.propagate'
        cdclW-merge-cp.cases trancp-unfold-begin inv st
        rtrancp-cdclW-merge-stgy'-no-step-cdclW-cp-or-eq)
    then have full1 cdclW-s'-without-decide R T
      using inv local.fw-s-cp
      by (blast intro: conflicting-true-full1-cdclW-merge-cp-imp-full1-cdclW-s'-without-decode)
    then show ?thesis unfolding full1-def
      by (metis (no-types) rtrancp-cdclW-s'-without-decide-rtrancp-cdclW-s' rtrancp-unfold)
  next
  case (fw-s-decide S') note dec = this(1) and n-S = this(2) and full = this(3)
  moreover then have conflicting S' = None
    by (auto elim: rulesE)
  ultimately have full cdclW-s'-without-decide S' T
    by (meson  $\langle \text{cdcl}_W\text{-all-struct-inv } S \rangle$  cdclW-merge-restart-cdclW fw-r-decide
      rtrancp-cdclW-all-struct-inv-inv
      conflicting-true-full-cdclW-merge-cp-iff-full-cdclW-s'-without-decode)
  then have a1: cdclW-s'*** S' T
    unfolding full-def by (metis (full-types) rtrancp-cdclW-s'-without-decide-rtrancp-cdclW-s')
  have cdclW-merge-stgy** S T
    using fw by blast
  then have cdclW-s'*** S T
    using decide-rtrancp-cdclW-s'-rtrancp-cdclW-s' a1 by (metis  $\langle \text{cdcl}_W\text{-all-struct-inv } S \rangle$  dec
      n-S no-step-cdclW-merge-cp-no-step-cdclW-cp cdclW-all-struct-inv-def
      rtrancp-cdclW-merge-stgy'-no-step-cdclW-cp-or-eq)
  then show ?thesis using IH by auto
qed
qed

```

**lemma** *rtrancp-cdcl<sub>W</sub>-merge-stgy-distinct-mset-clauses:*

```

  assumes invR: cdclW-all-struct-inv R and
    st: cdclW-merge-stgy** R S and
    dist: distinct-mset (clauses R) and
    R: trail R = []
  shows distinct-mset (clauses S)
  using rtrancp-cdclW-stgy-distinct-mset-clauses[OF invR - dist R]
  invR st rtrancp-mono[of cdclW-s' cdclW-stgy**] cdclW-s'-is-rtrancp-cdclW-stgy
  by (auto dest!: cdclW-s'-is-rtrancp-cdclW-stgy rtrancp-cdclW-merge-stgy-rtrancp-cdclW-s')

```

**lemma** *no-step-cdcl<sub>W</sub>-s'-no-step-cdcl<sub>W</sub>-merge-stgy:*

```

  assumes
    inv: cdclW-all-struct-inv R and s': no-step cdclW-s' R
  shows no-step cdclW-merge-stgy R

```

**proof** –

```

{ fix ss :: 'st
  obtain ssa :: 'st  $\Rightarrow$  'st  $\Rightarrow$  'st where
    ff1:  $\bigwedge s \text{ sa. } \neg \text{cdcl}_W\text{-merge-stgy } s \text{ sa} \vee \text{full1 } \text{cdcl}_W\text{-merge-cp } s \text{ sa} \vee \text{decide } s \text{ (ssa } s \text{ sa)}$ 
    using cdclW-merge-stgy.cases by moura
  obtain ssb :: ('st  $\Rightarrow$  'st  $\Rightarrow$  bool)  $\Rightarrow$  'st  $\Rightarrow$  'st  $\Rightarrow$  'st where

```



```

ff2:  $\bigwedge p \ s \ sa. \neg p^{++} \ s \ sa \vee p \ s \ (ssb \ p \ s \ sa)$ 
by (meson tranclp-unfold-begin)
obtain ssc :: 'st  $\Rightarrow$  'st where
ff3:  $\bigwedge s \ sa \ sb. (\neg cdcl_W\text{-all-struct-inv } s \vee \neg cdcl_W\text{-cp } s \ sa \vee cdcl_W\text{-s'} \ s \ (ssc \ s))$ 
 $\wedge (\neg cdcl_W\text{-all-struct-inv } s \vee \neg cdcl_W\text{-o } s \ sb \vee cdcl_W\text{-s'} \ s \ (ssc \ s))$ 
using n-step-cdclW-stgy-iff-no-step-cdclW-cl-cdclW-o by moura
then have ff4:  $\bigwedge s. \neg cdcl_W\text{-o } R \ s$ 
using s' inv by blast
have ff5:  $\bigwedge s. \neg cdcl_W\text{-cp}^{++} \ R \ s$ 
using ff3 ff2 s' by (metis inv)
have  $\bigwedge s. \neg cdcl_W\text{-bj}^{++} \ R \ s$ 
using ff4 ff2 by (metis bj)
then have  $\bigwedge s. \neg cdcl_W\text{-s'}\text{-without-decide } R \ s$ 
using ff5 by (simp add: cdclW-s'-without-decide.simps full1-def)
then have  $\neg cdcl_W\text{-s'}\text{-without-decide}^{++} \ R \ ss$ 
using ff2 by blast
then have  $\neg full1 \ cdcl_W\text{-s'}\text{-without-decide } R \ ss$ 
by (simp add: full1-def)
then have  $\neg cdcl_W\text{-merge-stgy } R \ ss$ 
using ff4 ff1 conflicting-true-full1-cdclW-merge-cp-imp-full1-cdclW-s'-without-decode inv
by blast }
then show ?thesis
by fastforce
qed
end

```

We will discharge the assumption later.

```

locale conflict-driven-clause-learningW-termination =
  conflict-driven-clause-learningW +
  assumes wf-cdclW-merge-inv: wf {(T, S). cdclW-all-struct-inv S  $\wedge$  cdclW-merge S T}
begin

```

```

lemma wf-tranclp-cdclW-merge: wf {(T, S). cdclW-all-struct-inv S  $\wedge$  cdclW-merge++ S T}
using wf-trancl[OF wf-cdclW-merge-inv]
apply (rule wf-subset)
by (auto simp: trancl-set-tranclp
  cdclW-all-struct-inv-tranclp-cdclW-merge-tranclp-cdclW-merge-cdclW-all-struct-inv)

```

```

lemma wf-cdclW-merge-cp:
  wf{(T, S). cdclW-all-struct-inv S  $\wedge$  cdclW-merge-cp S T}
using wf-tranclp-cdclW-merge by (rule wf-subset) (auto simp: cdclW-merge-cp-tranclp-cdclW-merge)

```

```

lemma wf-cdclW-merge-stgy:
  wf{(T, S). cdclW-all-struct-inv S  $\wedge$  cdclW-merge-stgy S T}
using wf-tranclp-cdclW-merge by (rule wf-subset)
(auto simp add: cdclW-merge-stgy-tranclp-cdclW-merge)

```

```

lemma cdclW-merge-cp-obtain-normal-form:
  assumes inv: cdclW-all-struct-inv R
  obtains S where full cdclW-merge-cp R S

```

proof –

```

obtain S where full ( $\lambda S \ T. cdcl_W\text{-all-struct-inv } S \wedge cdcl_W\text{-merge-cp } S \ T$ ) R S
using wf-exists-normal-form-full[OF wf-cdclW-merge-cp] by blast
then have
  st: ( $\lambda S \ T. cdcl_W\text{-all-struct-inv } S \wedge cdcl_W\text{-merge-cp } S \ T$ )** R S and

```

```

  n-s: no-step (λS T. cdclW-all-struct-inv S ∧ cdclW-merge-cp S T) S
  unfolding full-def by blast+
have cdclW-merge-cp** R S
  using st by induction auto
moreover
  have cdclW-all-struct-inv S
    using st inv
    apply (induction rule: rtrancp-induct)
    apply simp
    by (meson r-into-rtrancp rtrancp-cdclW-all-struct-inv-inv
        rtrancp-cdclW-merge-cp-rtrancp-cdclW)
  then have no-step cdclW-merge-cp S
    using n-s by auto
ultimately show ?thesis
  using that unfolding full-def by blast
qed

lemma no-step-cdclW-merge-stgy-no-step-cdclW-s':
  assumes
    inv: cdclW-all-struct-inv R and
    confl: conflicting R = None and
    n-s: no-step cdclW-merge-stgy R
  shows no-step cdclW-s' R
proof (rule ccontr)
  assume ¬ ?thesis
  then obtain S where cdclW-s' R S by auto
  then show False
  proof cases
    case conflict'
    then obtain S' where full1 cdclW-merge-cp R S'
    proof -
      obtain R' :: 'e where
        cdclW-merge-cp R R'
      using inv unfolding cdclW-all-struct-inv-def by (meson confl
        cdclW-s'-without-decide.simps conflict'
        conflicting-true-no-step-cdclW-merge-cp-no-step-s'-without-decide)
      then show ?thesis
        using that by (metis cdclW-merge-cp-obtain-normal-form full-unfold inv)
    qed
    then show False using n-s by blast
  next
    case (decide' R')
    then have cdclW-all-struct-inv R'
      using inv cdclW-all-struct-inv-inv cdclW.other cdclW-o.decide by meson
    then obtain R'' where full cdclW-merge-cp R' R''
      using cdclW-merge-cp-obtain-normal-form by blast
    moreover have no-step cdclW-merge-cp R
      by (simp add: confl local.decide'(2) no-step-cdclW-cp-no-step-cdclW-merge-restart)
    ultimately show False using n-s cdclW-merge-stgy.intros local.decide'(1) by blast
  next
    case (bj' R')
    then show False
      using confl no-step-cdclW-cp-no-step-cdclW-s'-without-decide inv
      unfolding cdclW-all-struct-inv-def by auto
  qed

```

qed

**lemma** *rtranclp-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-bj*:  
**assumes** *conflicting*  $R = \text{None}$  **and** *cdcl<sub>W</sub>-merge-cp<sup>\*\*</sup>*  $R\ S$   
**shows** *no-step cdcl<sub>W</sub>-bj*  $S$   
**using** *assms conflicting-not-true-rtranclp-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-bj* **by** *auto*

**lemma** *rtranclp-cdcl<sub>W</sub>-merge-stgy-no-step-cdcl<sub>W</sub>-bj*:  
**assumes** *confl*: *conflicting*  $R = \text{None}$  **and** *cdcl<sub>W</sub>-merge-stgy<sup>\*\*</sup>*  $R\ S$   
**shows** *no-step cdcl<sub>W</sub>-bj*  $S$   
**using** *assms*(2)

**proof** *induction*

**case** *base*

**then show** *?case*

**using** *confl* **by** (*auto simp: cdcl<sub>W</sub>-bj.simps elim: rulesE*)

**next**

**case** (*step S T*) **note**  $st = \text{this}(1)$  **and**  $fw = \text{this}(2)$  **and**  $IH = \text{this}(3)$

**have** *confl-S*: *conflicting*  $S = \text{None}$

**using** *fw* **apply** *cases*

**by** (*auto simp: full1-def cdcl<sub>W</sub>-merge-cp.simps dest!: tranclpD elim: rulesE*)

**from** *fw* **show** *?case*

**proof** *cases*

**case** *fw-s-cp*

**then show** *?thesis*

**using** *rtranclp-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-bj confl-S*

**by** (*simp add: full1-def tranclp-into-rtranclp*)

**next**

**case** (*fw-s-decide S'*)

**moreover then have** *conflicting*  $S' = \text{None}$  **by** (*auto elim: rulesE*)

**ultimately show** *?thesis*

**using** *conflicting-not-true-rtranclp-cdcl<sub>W</sub>-merge-cp-no-step-cdcl<sub>W</sub>-bj*

**unfolding** *full-def* **by** *meson*

qed

qed

end

end

**theory** *CDCL-W-Restart*

**imports** *CDCL-W-Merge*

**begin**

## 21.5 Adding Restarts

**locale** *cdcl<sub>W</sub>-restart* =

*conflict-driven-clause-learning<sub>W</sub>*

— functions for clauses:

*mset-cls insert-cls remove-lit*

*mset-clss union-clss in-clss insert-clss remove-from-clss*

— functions for the conflicting clause:

*mset-ccls union-ccls insert-ccls remove-clit*

— conversion

*ccls-of-cls cls-of-ccls*

```

— functions for the state:
  — access functions:
trail hd-raw-trail raw-init-clss raw-learned-clss backtrack-lvl raw-conflicting
  — changing state:
cons-trail tl-trail add-init-cls add-learned-cls remove-cls update-backtrack-lvl
update-conflicting

  — get state:
init-state
restart-state
for
  mset-cls:: 'cls ⇒ 'v clause and
  insert-cls :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and

  mset-clss:: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and

  mset-ccls:: 'ccls ⇒ 'v clause and
  union-ccls :: 'ccls ⇒ 'ccls ⇒ 'ccls and
  insert-ccls :: 'v literal ⇒ 'ccls ⇒ 'ccls and
  remove-clit :: 'v literal ⇒ 'ccls ⇒ 'ccls and

  ccls-of-cls :: 'cls ⇒ 'ccls and
  cls-of-ccls :: 'ccls ⇒ 'cls and

  trail :: 'st ⇒ ('v, nat, 'v clause) marked-lits and
  hd-raw-trail :: 'st ⇒ ('v, nat, 'cls) marked-lit and
  raw-init-clss :: 'st ⇒ 'clss and
  raw-learned-clss :: 'st ⇒ 'clss and
  backtrack-lvl :: 'st ⇒ nat and
  raw-conflicting :: 'st ⇒ 'ccls option and

  cons-trail :: ('v, nat, 'cls) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and
  add-init-cls :: 'cls ⇒ 'st ⇒ 'st and
  add-learned-cls :: 'cls ⇒ 'st ⇒ 'st and
  remove-cls :: 'cls ⇒ 'st ⇒ 'st and
  update-backtrack-lvl :: nat ⇒ 'st ⇒ 'st and
  update-conflicting :: 'ccls option ⇒ 'st ⇒ 'st and

  init-state :: 'clss ⇒ 'st and
  restart-state :: 'st ⇒ 'st +
fixes f :: nat ⇒ nat
assumes f: unbounded f
begin

```

The condition of the differences of cardinality has to be strict. Otherwise, you could be in a strange state, where nothing remains to do, but a restart is done. See the proof of well-foundedness.

**inductive** *cdcl<sub>W</sub>-merge-with-restart* **where**  
*restart-step:*

$(cdcl_W\text{-merge-stgy} \sim (card (set\text{-mset} (learned\text{-clss } T)) - card (set\text{-mset} (learned\text{-clss } S)))) S T$   
 $\implies card (set\text{-mset} (learned\text{-clss } T)) - card (set\text{-mset} (learned\text{-clss } S)) > f n$   
 $\implies restart\ T\ U \implies cdcl_W\text{-merge-with-restart } (S, n)\ (U, Suc\ n) \mid$   
*restart-full*: *full1*  $cdcl_W\text{-merge-stgy } S\ T \implies cdcl_W\text{-merge-with-restart } (S, n)\ (T, Suc\ n)$

**lemma**  $cdcl_W\text{-merge-with-restart } S\ T \implies cdcl_W\text{-merge-restart}^{**}\ (fst\ S)\ (fst\ T)$   
**by** (*induction rule*:  $cdcl_W\text{-merge-with-restart.induct}$ )  
*(auto dest!*:  $relpowp\text{-imp-rtranclp } cdcl_W\text{-merge-stgy-tranclp-cdcl_W\text{-merge } tranclp\text{-into-rtranclp}$   
 $rtranclp-cdcl_W\text{-merge-stgy-rtranclp-cdcl_W\text{-merge } rtranclp-cdcl_W\text{-merge-tranclp-cdcl_W\text{-merge-restart}$   
 $fw\text{-r-rf } cdcl_W\text{-rf.restart}$   
*simp*: *full1-def*)

**lemma**  $cdcl_W\text{-merge-with-restart-rtranclp-cdcl_W}$ :  
 $cdcl_W\text{-merge-with-restart } S\ T \implies cdcl_W^{**}\ (fst\ S)\ (fst\ T)$   
**by** (*induction rule*:  $cdcl_W\text{-merge-with-restart.induct}$ )  
*(auto dest!*:  $relpowp\text{-imp-rtranclp } rtranclp-cdcl_W\text{-merge-stgy-rtranclp-cdcl_W } cdcl_W\text{-rf}$   
 $cdcl_W\text{-rf.restart } tranclp\text{-into-rtranclp } simp$ : *full1-def*)

**lemma**  $cdcl_W\text{-merge-with-restart-increasing-number}$ :  
 $cdcl_W\text{-merge-with-restart } S\ T \implies snd\ T = 1 + snd\ S$   
**by** (*induction rule*:  $cdcl_W\text{-merge-with-restart.induct}$ ) *auto*

**lemma** *full1*  $cdcl_W\text{-merge-stgy } S\ T \implies cdcl_W\text{-merge-with-restart } (S, n)\ (T, Suc\ n)$   
**using** *restart-full* **by** *blast*

**lemma**  $cdcl_W\text{-all-struct-inv-learned-clss-bound}$ :  
**assumes** *inv*:  $cdcl_W\text{-all-struct-inv } S$   
**shows**  $set\text{-mset } (learned\text{-clss } S) \subseteq simple\text{-clss } (atms\text{-of-mm } (init\text{-clss } S))$

**proof**

**fix** *C*

**assume** *C*:  $C \in set\text{-mset } (learned\text{-clss } S)$

**have** *distinct-mset* *C*

**using** *C inv* **unfolding**  $cdcl_W\text{-all-struct-inv-def } distinct\text{-cdcl_W-state-def } distinct\text{-mset-set-def}$   
**by** *auto*

**moreover** **have**  $\neg tautology\ C$

**using** *C inv* **unfolding**  $cdcl_W\text{-all-struct-inv-def } cdcl_W\text{-learned-clause-def}$  **by** *auto*

**moreover**

**have**  $atms\text{-of } C \subseteq atms\text{-of-mm } (learned\text{-clss } S)$

**using** *C* **by** *auto*

**then** **have**  $atms\text{-of } C \subseteq atms\text{-of-mm } (init\text{-clss } S)$

**using** *inv* **unfolding**  $cdcl_W\text{-all-struct-inv-def } no\text{-strange-atm-def}$  **by** *force*

**moreover** **have**  $finite\ (atms\text{-of-mm } (init\text{-clss } S))$

**using** *inv* **unfolding**  $cdcl_W\text{-all-struct-inv-def}$  **by** *auto*

**ultimately** **show**  $C \in simple\text{-clss } (atms\text{-of-mm } (init\text{-clss } S))$

**using**  $distinct\text{-mset-not-tautology-implies-in-simple-clss } simple\text{-clss-mono}$   
**by** *blast*

**qed**

**lemma**  $cdcl_W\text{-merge-with-restart-init-clss}$ :  
 $cdcl_W\text{-merge-with-restart } S\ T \implies cdcl_W\text{-M-level-inv } (fst\ S) \implies$   
 $init\text{-clss } (fst\ S) = init\text{-clss } (fst\ T)$   
**using**  $cdcl_W\text{-merge-with-restart-rtranclp-cdcl_W } rtranclp\text{-cdcl_W-init-clss}$  **by** *blast*

**lemma**

*wf*  $\{(T, S). cdcl_W\text{-all-struct-inv } (fst\ S) \wedge cdcl_W\text{-merge-with-restart } S\ T\}$

```

proof (rule ccontr)
  assume  $\neg$  ?thesis
  then obtain  $g$  where
     $g: \bigwedge i. \text{cdcl}_W\text{-merge-with-restart } (g\ i) (g\ (\text{Suc } i))$  and
     $\text{inv}: \bigwedge i. \text{cdcl}_W\text{-all-struct-inv } (\text{fst } (g\ i))$ 
    unfolding wf-iff-no-infinite-down-chain by fast
  { fix  $i$ 
    have  $\text{init-clss } (\text{fst } (g\ i)) = \text{init-clss } (\text{fst } (g\ 0))$ 
    apply (induction  $i$ )
    apply simp
    using  $g$  inv unfolding  $\text{cdcl}_W\text{-all-struct-inv-def}$  by (metis  $\text{cdcl}_W\text{-merge-with-restart-init-clss}$ )
  } note  $\text{init-g} = \text{this}$ 
let  $?S = g\ 0$ 
have  $\text{finite } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S)))$ 
  using  $\text{inv}$  unfolding  $\text{cdcl}_W\text{-all-struct-inv-def}$  by auto
have  $\text{snd-g}: \bigwedge i. \text{snd } (g\ i) = i + \text{snd } (g\ 0)$ 
  apply (induct-tac  $i$ )
  apply simp
  by (metis  $\text{Suc-eq-plus1-left add-Suc cdcl}_W\text{-merge-with-restart-increasing-number } g$ )
then have  $\text{snd-g-0}: \bigwedge i. i > 0 \implies \text{snd } (g\ i) = i + \text{snd } (g\ 0)$ 
  by blast
have  $\text{unbounded-f-g}: \text{unbounded } (\lambda i. f\ (\text{snd } (g\ i)))$ 
  using  $f$  unfolding  $\text{bounded-def}$  by (metis  $\text{add.commute } f\ \text{less-or-eq-imp-le snd-g}$ 
     $\text{not-bounded-nat-exists-larger not-le le-iff-add}$ )

obtain  $k$  where
   $f\text{-g-}k: f\ (\text{snd } (g\ k)) > \text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$  and
   $k > \text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$ 
  using  $\text{not-bounded-nat-exists-larger}[OF\ \text{unbounded-f-g}]$  by blast

```

The following does not hold anymore with the non-strict version of cardinality in the definition.

```

{ fix  $i$ 
  assume  $\text{no-step } \text{cdcl}_W\text{-merge-stgy } (\text{fst } (g\ i))$ 
  with  $g[\text{of } i]$ 
  have  $\text{False}$ 
    proof (induction rule:  $\text{cdcl}_W\text{-merge-with-restart.induct}$ )
      case ( $\text{restart-step } T\ S\ n$ ) note  $H = \text{this}(1)$  and  $c = \text{this}(2)$  and  $n\text{-s} = \text{this}(4)$ 
      obtain  $S'$  where  $\text{cdcl}_W\text{-merge-stgy } S\ S'$ 
      using  $H\ c$  by (metis  $\text{gr-implies-not0 relpowp-E2}$ )
      then show  $\text{False}$  using  $n\text{-s}$  by auto
    next
      case ( $\text{restart-full } S\ T$ )
      then show  $\text{False}$  unfolding  $\text{full1-def}$  by (auto dest:  $\text{tranc1pD}$ )
    qed
  } note  $H = \text{this}$ 
obtain  $m\ T$  where
   $m: m = \text{card } (\text{set-mset } (\text{learned-clss } T)) - \text{card } (\text{set-mset } (\text{learned-clss } (\text{fst } (g\ k))))$  and
   $m > f\ (\text{snd } (g\ k))$  and
   $\text{restart } T\ (\text{fst } (g\ (k+1)))$  and
   $\text{cdcl}_W\text{-merge-stgy}: (\text{cdcl}_W\text{-merge-stgy } \sim m) (\text{fst } (g\ k))\ T$ 
  using  $g[\text{of } k]\ H[\text{of } \text{Suc } k]$  by (force simp:  $\text{cdcl}_W\text{-merge-with-restart.simps full1-def}$ )
have  $\text{cdcl}_W\text{-merge-stgy}^{**} (\text{fst } (g\ k))\ T$ 
  using  $\text{cdcl}_W\text{-merge-stgy relpowp-imp-rtranc1p}$  by metis
then have  $\text{cdcl}_W\text{-all-struct-inv } T$ 
  using  $\text{inv}[\text{of } k]\ \text{rtranc1p-cdcl}_W\text{-all-struct-inv-inv rtranc1p-cdcl}_W\text{-merge-stgy-rtranc1p-cdcl}_W$ 

```

by blast  
 moreover have  $\text{card } (\text{set-mset } (\text{learned-clss } T)) - \text{card } (\text{set-mset } (\text{learned-clss } (\text{fst } (g \ k))))$   
 $> \text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$   
 unfolding  $m[\text{symmetric}]$  using  $\langle m > f \ (\text{snd } (g \ k)) \rangle$   $f\text{-}g\text{-}k$  by linarith  
 then have  $\text{card } (\text{set-mset } (\text{learned-clss } T))$   
 $> \text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$   
 by linarith  
 moreover  
 have  $\text{init-clss } (\text{fst } (g \ k)) = \text{init-clss } T$   
 using  $\langle \text{cdcl}_W\text{-merge-stgy}^{**} (\text{fst } (g \ k)) \ T \rangle$   $\text{rtrancpl-cdcl}_W\text{-merge-stgy-rtrancpl-cdcl}_W$   
 $\text{rtrancpl-cdcl}_W\text{-init-clss inv}$  unfolding  $\text{cdcl}_W\text{-all-struct-inv-def}$  by blast  
 then have  $\text{init-clss } (\text{fst } ?S) = \text{init-clss } T$   
 using  $\text{init-g}[of \ k]$  by auto  
 ultimately show False  
 using  $\text{cdcl}_W\text{-all-struct-inv-learned-clss-bound}$   
 by (simp add:  $\langle \text{finite } (\text{atms-of-mm } (\text{init-clss } (\text{fst } (g \ 0)))) \rangle$   $\text{simple-clss-finite}$   
 $\text{card-mono leD}$ )  
 qed

**lemma**  $\text{cdcl}_W\text{-merge-with-restart-distinct-mset-clauses}$ :  
 assumes  $\text{invR}: \text{cdcl}_W\text{-all-struct-inv } (\text{fst } R)$  and  
 $\text{st}: \text{cdcl}_W\text{-merge-with-restart } R \ S$  and  
 $\text{dist}: \text{distinct-mset } (\text{clauses } (\text{fst } R))$  and  
 $R: \text{trail } (\text{fst } R) = []$   
 shows  $\text{distinct-mset } (\text{clauses } (\text{fst } S))$   
 using  $\text{assms}(2,1,3,4)$   
**proof** (induction)  
 case (restart-full  $S \ T$ )  
 then show ?case using  $\text{rtrancpl-cdcl}_W\text{-merge-stgy-distinct-mset-clauses}[of \ S \ T]$  unfolding  $\text{full1-def}$   
 by (auto dest:  $\text{trancpl-into-rtrancpl}$ )  
 next  
 case (restart-step  $T \ S \ n \ U$ )  
 then have  $\text{distinct-mset } (\text{clauses } T)$   
 using  $\text{rtrancpl-cdcl}_W\text{-merge-stgy-distinct-mset-clauses}[of \ S \ T]$  unfolding  $\text{full1-def}$   
 by (auto dest:  $\text{relpowp-imp-rtrancpl}$ )  
 then show ?case using  $\langle \text{restart } T \ U \rangle$  by (metis  $\text{clauses-restart distinct-mset-union fstI}$   
 $\text{mset-le-exists-conv restart.cases state-eq-clauses}$ )  
 qed

**inductive**  $\text{cdcl}_W\text{-with-restart}$  where

$\text{restart-step}$ :

$(\text{cdcl}_W\text{-stgy} \sim (\text{card } (\text{set-mset } (\text{learned-clss } T)) - \text{card } (\text{set-mset } (\text{learned-clss } S)))) \ S \ T \implies$   
 $\text{card } (\text{set-mset } (\text{learned-clss } T)) - \text{card } (\text{set-mset } (\text{learned-clss } S)) > f \ n \implies$   
 $\text{restart } T \ U \implies$

$\text{cdcl}_W\text{-with-restart } (S, n) \ (U, \text{Suc } n) \mid$

$\text{restart-full}: \text{full1 } \text{cdcl}_W\text{-stgy } S \ T \implies \text{cdcl}_W\text{-with-restart } (S, n) \ (T, \text{Suc } n)$

**lemma**  $\text{cdcl}_W\text{-with-restart-rtrancpl-cdcl}_W$ :

$\text{cdcl}_W\text{-with-restart } S \ T \implies \text{cdcl}_W^{**} (\text{fst } S) (\text{fst } T)$

apply (induction rule:  $\text{cdcl}_W\text{-with-restart.induct}$ )

by (auto dest!:  $\text{relpowp-imp-rtrancpl trancpl-into-rtrancpl fw-r-rf}$

$\text{cdcl}_W\text{-rf.restart rtrancpl-cdcl}_W\text{-stgy-rtrancpl-cdcl}_W \text{cdcl}_W\text{-merge-restart-cdcl}_W$

$\text{simp: full1-def}$ )

**lemma**  $\text{cdcl}_W\text{-with-restart-increasing-number}$ :

*cdcl<sub>W</sub>-with-restart*  $S\ T \implies \text{snd } T = 1 + \text{snd } S$   
**by** (*induction rule: cdcl<sub>W</sub>-with-restart.induct*) *auto*

**lemma** *full1 cdcl<sub>W</sub>-stgy*  $S\ T \implies \text{cdcl}_W\text{-with-restart } (S, n)\ (T, \text{Suc } n)$   
**using** *restart-full* **by** *blast*

**lemma** *cdcl<sub>W</sub>-with-restart-init-clss*:  
*cdcl<sub>W</sub>-with-restart*  $S\ T \implies \text{cdcl}_W\text{-M-level-inv } (\text{fst } S) \implies \text{init-clss } (\text{fst } S) = \text{init-clss } (\text{fst } T)$   
**using** *cdcl<sub>W</sub>-with-restart-rtranclp-cdcl<sub>W</sub> rtranclp-cdcl<sub>W</sub>-init-clss* **by** *blast*

**lemma**

*wf*  $\{(T, S). \text{cdcl}_W\text{-all-struct-inv } (\text{fst } S) \wedge \text{cdcl}_W\text{-with-restart } S\ T\}$

**proof** (*rule ccontr*)

**assume**  $\neg ?thesis$

**then obtain**  $g$  **where**

$g: \bigwedge i. \text{cdcl}_W\text{-with-restart } (g\ i)\ (g\ (\text{Suc } i))$  **and**

$\text{inv}: \bigwedge i. \text{cdcl}_W\text{-all-struct-inv } (\text{fst } (g\ i))$

**unfolding** *wf-iff-no-infinite-down-chain* **by** *fast*

**{ fix**  $i$

**have**  $\text{init-clss } (\text{fst } (g\ i)) = \text{init-clss } (\text{fst } (g\ 0))$

**apply** (*induction i*)

**apply** *simp*

**using**  $g\ \text{inv}$  **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** (*metis cdcl<sub>W</sub>-with-restart-init-clss*)

**} note**  $\text{init-g} = \text{this}$

**let**  $?S = g\ 0$

**have**  $\text{finite } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S)))$

**using**  $\text{inv}$  **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* **by** *auto*

**have**  $\text{snd-g}: \bigwedge i. \text{snd } (g\ i) = i + \text{snd } (g\ 0)$

**apply** (*induct-tac i*)

**apply** *simp*

**by** (*metis Suc-eq-plus1-left add-Suc cdcl<sub>W</sub>-with-restart-increasing-number g*)

**then have**  $\text{snd-g-0}: \bigwedge i. i > 0 \implies \text{snd } (g\ i) = i + \text{snd } (g\ 0)$

**by** *blast*

**have**  $\text{unbounded-f-g}: \text{unbounded } (\lambda i. f\ (\text{snd } (g\ i)))$

**using**  $f$  **unfolding** *bounded-def* **by** (*metis add.commute f less-or-eq-imp-le snd-g not-bounded-nat-exists-larger not-le le-iff-add*)

**obtain**  $k$  **where**

$f\text{-g-}k: f\ (\text{snd } (g\ k)) > \text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$  **and**

$k > \text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$

**using** *not-bounded-nat-exists-larger[OF unbounded-f-g]* **by** *blast*

The following does not hold anymore with the non-strict version of cardinality in the definition.

**{ fix**  $i$

**assume** *no-step cdcl<sub>W</sub>-stgy*  $(\text{fst } (g\ i))$

**with**  $g[\text{of } i]$

**have** *False*

**proof** (*induction rule: cdcl<sub>W</sub>-with-restart.induct*)

**case** (*restart-step*  $T\ S\ n$ ) **note**  $H = \text{this}(1)$  **and**  $c = \text{this}(2)$  **and**  $n\text{-s} = \text{this}(4)$

**obtain**  $S'$  **where** *cdcl<sub>W</sub>-stgy*  $S\ S'$

**using**  $H\ c$  **by** (*metis gr-implies-not0 relpowp-E2*)

**then show** *False* **using**  $n\text{-s}$  **by** *auto*

**next**

**case** (*restart-full*  $S\ T$ )

**then show** *False* **unfolding** *full1-def* **by** (*auto dest: tranclpD*)



```

    qed
  } note  $H = \text{this}$ 
obtain  $m$   $T$  where
   $m : m = \text{card } (\text{set-mset } (\text{learned-clss } T)) - \text{card } (\text{set-mset } (\text{learned-clss } (\text{fst } (g \ k))))$  and
   $m > f \ (\text{snd } (g \ k))$  and
  restart  $T \ (\text{fst } (g \ (k+1)))$  and
   $\text{cdcl}_W\text{-merge-stgy} : (\text{cdcl}_W\text{-stgy } \sim m) \ (\text{fst } (g \ k)) \ T$ 
  using  $g[\text{of } k] \ H[\text{of } \text{Suc } k]$  by (force simp:  $\text{cdcl}_W\text{-with-restart.simps full1-def}$ )
have  $\text{cdcl}_W\text{-stgy}^{**} \ (\text{fst } (g \ k)) \ T$ 
  using  $\text{cdcl}_W\text{-merge-stgy relpowp-imp-rtrancpl}$  by metis
then have  $\text{cdcl}_W\text{-all-struct-inv } T$ 
  using  $\text{inv}[\text{of } k] \ \text{rtrancpl-cdcl}_W\text{-all-struct-inv-inv rtrancpl-cdcl}_W\text{-stgy-rtrancpl-cdcl}_W$  by blast
moreover have  $\text{card } (\text{set-mset } (\text{learned-clss } T)) - \text{card } (\text{set-mset } (\text{learned-clss } (\text{fst } (g \ k))))$ 
  >  $\text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$ 
  unfolding  $m[\text{symmetric}]$  using  $\langle m > f \ (\text{snd } (g \ k)) \rangle f\text{-}g\text{-}k$  by linarith
then have  $\text{card } (\text{set-mset } (\text{learned-clss } T))$ 
  >  $\text{card } (\text{simple-clss } (\text{atms-of-mm } (\text{init-clss } (\text{fst } ?S))))$ 
  by linarith
moreover
  have  $\text{init-clss } (\text{fst } (g \ k)) = \text{init-clss } T$ 
  using  $\langle \text{cdcl}_W\text{-stgy}^{**} \ (\text{fst } (g \ k)) \ T \rangle \ \text{rtrancpl-cdcl}_W\text{-stgy-rtrancpl-cdcl}_W \ \text{rtrancpl-cdcl}_W\text{-init-clss}$ 
  inv unfolding  $\text{cdcl}_W\text{-all-struct-inv-def}$ 
  by blast
  then have  $\text{init-clss } (\text{fst } ?S) = \text{init-clss } T$ 
  using  $\text{init-g}[\text{of } k]$  by auto
ultimately show False
  using  $\text{cdcl}_W\text{-all-struct-inv-learned-clss-bound}$ 
  by (simp add:  $\langle \text{finite } (\text{atms-of-mm } (\text{init-clss } (\text{fst } (g \ 0)))) \rangle \ \text{simple-clss-finite}$ 
    card-mono leD)
qed

```

```

lemma  $\text{cdcl}_W\text{-with-restart-distinct-mset-clauses}$ :
  assumes  $\text{invR} : \text{cdcl}_W\text{-all-struct-inv } (\text{fst } R)$  and
   $st : \text{cdcl}_W\text{-with-restart } R \ S$  and
   $dist : \text{distinct-mset } (\text{clauses } (\text{fst } R))$  and
   $R : \text{trail } (\text{fst } R) = []$ 
  shows  $\text{distinct-mset } (\text{clauses } (\text{fst } S))$ 
  using  $\text{assms}(2,1,3,4)$ 
proof (induction)
  case (restart-full  $S \ T$ )
  then show ?case using  $\text{rtrancpl-cdcl}_W\text{-stgy-distinct-mset-clauses}[\text{of } S \ T]$  unfolding full1-def
    by (auto dest:  $\text{trancpl-into-rtrancpl}$ )
next
  case (restart-step  $T \ S \ n \ U$ )
  then have  $\text{distinct-mset } (\text{clauses } T)$  using  $\text{rtrancpl-cdcl}_W\text{-stgy-distinct-mset-clauses}[\text{of } S \ T]$ 
    unfolding full1-def by (auto dest:  $\text{relpowp-imp-rtrancpl}$ )
  then show ?case using (restart  $T \ U$ ) by (metis  $\text{clauses-restart distinct-mset-union fstI}$ 
     $\text{mset-le-exists-conv restart.cases state-eq-clauses}$ )
qed
end

```

```

locale luby-sequence =
  fixes  $ur :: \text{nat}$ 
  assumes  $ur > 0$ 
begin

```

```

lemma exists-luby-decomp:
  fixes  $i :: \text{nat}$ 
  shows  $\exists k :: \text{nat}. (2^{\wedge} (k - 1) \leq i \wedge i < 2^{\wedge} k - 1) \vee i = 2^{\wedge} k - 1$ 
proof (induction i)
  case 0
  then show ?case
    by (rule exI[of - 0], simp)
next
  case (Suc n)
  then obtain  $k$  where  $2^{\wedge} (k - 1) \leq n \wedge n < 2^{\wedge} k - 1 \vee n = 2^{\wedge} k - 1$ 
    by blast
  then consider
    (st-interv)  $2^{\wedge} (k - 1) \leq n$  and  $n \leq 2^{\wedge} k - 2$ 
  | (end-interv)  $2^{\wedge} (k - 1) \leq n$  and  $n = 2^{\wedge} k - 2$ 
  | (pow2)  $n = 2^{\wedge} k - 1$ 
    by linarith
  then show ?case
  proof cases
    case st-interv
    then show ?thesis apply - apply (rule exI[of - k])
      by (metis (no-types, lifting) One-nat-def Suc-diff-Suc Suc-lessI
         $\langle 2^{\wedge} (k - 1) \leq n \wedge n < 2^{\wedge} k - 1 \vee n = 2^{\wedge} k - 1 \rangle$  diff-self-eq-0
        dual-order.trans le-SucI le-imp-less-Suc numeral-2-eq-2 one-le-numeral
        one-le-power zero-less-numeral zero-less-power)
    next
    case end-interv
    then show ?thesis apply - apply (rule exI[of - k]) by auto
    next
    case pow2
    then show ?thesis apply - apply (rule exI[of - k+1]) by auto
  qed
qed

```

Luby sequences are defined by:

- $2^k - 1$ , if  $i = (2::'a)^k - (1::'a)$
- *luby-sequence-core*  $(i - 2^{k-1} + 1)$ , if  $(2::'a)^{k-1} \leq i$  and  $i \leq (2::'a)^k - (1::'a)$

Then the sequence is then scaled by a constant unit run (called *ur* here), strictly positive.

```

function luby-sequence-core ::  $\text{nat} \Rightarrow \text{nat}$  where
luby-sequence-core i =
  (if  $\exists k. i = 2^{\wedge} k - 1$ 
    then  $2^{\wedge} ((\text{SOME } k. i = 2^{\wedge} k - 1) - 1)$ 
    else luby-sequence-core  $(i - 2^{\wedge} ((\text{SOME } k. 2^{\wedge} (k-1) \leq i \wedge i < 2^{\wedge} k - 1) - 1) + 1)$ )
by auto
termination
proof (relation less-than, goal-cases)
  case 1
  then show ?case by auto
next
  case ( $2\ i$ )
  let ? $k = (\text{SOME } k. 2^{\wedge} (k - 1) \leq i \wedge i < 2^{\wedge} k - 1)$ 
  have  $2^{\wedge} (?k - 1) \leq i \wedge i < 2^{\wedge} ?k - 1$ 

```

**apply** (*rule someI-ex*)  
**using** *2 exists-luby-decomp* **by** *blast*  
**then show** *?case*

**proof** –

**have**  $\forall n \text{ na. } \neg (1::\text{nat}) \leq n \vee 1 \leq n \wedge \text{na}$   
**by** (*meson one-le-power*)  
**then have**  $f1: (1::\text{nat}) \leq 2 \wedge (?k - 1)$   
**using** *one-le-numeral* **by** *blast*  
**have**  $f2: i - 2 \wedge (?k - 1) + 2 \wedge (?k - 1) = i$   
**using**  $\langle 2 \wedge (?k - 1) \leq i \wedge i < 2 \wedge ?k - 1 \rangle$  *le-add-diff-inverse2* **by** *blast*  
**have**  $f3: 2 \wedge ?k - 1 \neq \text{Suc } 0$   
**using**  $f1 \langle 2 \wedge (?k - 1) \leq i \wedge i < 2 \wedge ?k - 1 \rangle$  **by** *linarith*  
**have**  $2 \wedge ?k - (1::\text{nat}) \neq 0$   
**using**  $\langle 2 \wedge (?k - 1) \leq i \wedge i < 2 \wedge ?k - 1 \rangle$  *gr-implies-not0* **by** *blast*  
**then have**  $f4: 2 \wedge ?k \neq (1::\text{nat})$   
**by** *linarith*  
**have**  $f5: \forall n \text{ na. if na = 0 then (n::nat) \wedge na = 1 else n \wedge na = n * n \wedge (na - 1)}$   
**by** (*simp add: power-eq-if*)  
**then have**  $?k \neq 0$   
**using**  $f4$  **by** *meson*  
**then have**  $2 \wedge (?k - 1) \neq \text{Suc } 0$   
**using**  $f5 f3$  **by** *presburger*  
**then have**  $\text{Suc } 0 < 2 \wedge (?k - 1)$   
**using**  $f1$  **by** *linarith*  
**then show** *?thesis*  
**using**  $f2$  *less-than-iff* **by** *presburger*

**qed**

**qed**

**function** *natlog2* :: *nat*  $\Rightarrow$  *nat* **where**  
*natlog2* *n* = (*if* *n* = 0 *then* 0 *else* 1 + *natlog2* (*n* div 2))  
**using** *not0-implies-Suc* **by** *auto*  
**termination by** (*relation measure* ( $\lambda n. n$ )) *auto*

**declare** *natlog2.simps*[*simp del*]

**declare** *luby-sequence-core.simps*[*simp del*]

**lemma** *two-pover-n-eq-two-power-n'-eq*:

**assumes**  $H: (2::\text{nat}) \wedge (k::\text{nat}) - 1 = 2 \wedge k' - 1$   
**shows**  $k' = k$

**proof** –

**have**  $(2::\text{nat}) \wedge (k::\text{nat}) = 2 \wedge k'$   
**using**  $H$  **by** (*metis One-nat-def Suc-pred zero-less-numeral zero-less-power*)  
**then show** *?thesis* **by** *simp*

**qed**

**lemma** *luby-sequence-core-two-power-minus-one*:

*luby-sequence-core*  $(2 \wedge k - 1) = 2 \wedge (k - 1)$  (**is**  $?L = ?K$ )

**proof** –

**have** *decomp*:  $\exists ka. 2 \wedge k - 1 = 2 \wedge ka - 1$   
**by** *auto*  
**have**  $?L = 2 \wedge ((\text{SOME } k'. (2::\text{nat}) \wedge k - 1 = 2 \wedge k' - 1) - 1)$   
**apply** (*subst luby-sequence-core.simps, subst decomp*)

```

  by simp
moreover have (SOME k'. (2::nat) ^ k - 1 = 2 ^ k' - 1) = k
  apply (rule some-equality)
  apply simp
  using two-pover-n-eq-two-power-n'-eq by blast
ultimately show ?thesis by presburger
qed

```

**lemma** *different-luby-decomposition-false:*

```

assumes
  H: 2 ^ (k - Suc 0) ≤ i and
  k': i < 2 ^ k' - Suc 0 and
  k-k': k > k'
shows False
proof -
  have 2 ^ k' - Suc 0 < 2 ^ (k - Suc 0)
    using k-k' less-eq-Suc-le by auto
  then show ?thesis
    using H k' by linarith
qed

```

**lemma** *luby-sequence-core-not-two-power-minus-one:*

```

assumes
  k-i: 2 ^ (k - 1) ≤ i and
  i-k: i < 2 ^ k - 1
shows luby-sequence-core i = luby-sequence-core (i - 2 ^ (k - 1) + 1)
proof -
  have H: ¬ (∃ ka. i = 2 ^ ka - 1)
  proof (rule ccontr)
    assume ¬ ?thesis
    then obtain k':nat where k': i = 2 ^ k' - 1 by blast
    have (2::nat) ^ k' - 1 < 2 ^ k - 1
      using i-k unfolding k' .
    then have (2::nat) ^ k' < 2 ^ k
      by linarith
    then have k' < k
      by simp
    have 2 ^ (k - 1) ≤ 2 ^ k' - (1::nat)
      using k-i unfolding k' .
    then have (2::nat) ^ (k-1) < 2 ^ k'
      by (metis Suc-diff-1 not-le not-less-eq zero-less-numeral zero-less-power)
    then have k-1 < k'
      by simp

    show False using (k' < k) (k-1 < k') by linarith
  qed
  have ∧ k k'. 2 ^ (k - Suc 0) ≤ i ⇒ i < 2 ^ k - Suc 0 ⇒ 2 ^ (k' - Suc 0) ≤ i ⇒
    i < 2 ^ k' - Suc 0 ⇒ k = k'
    by (meson different-luby-decomposition-false linorder-neqE-nat)
  then have k: (SOME k. 2 ^ (k - Suc 0) ≤ i ∧ i < 2 ^ k - Suc 0) = k
    using k-i i-k by auto
  show ?thesis
    apply (subst luby-sequence-core.simps[of i], subst H)
    by (simp add: k)
qed

```

**lemma** *unbounded-luby-sequence-core: unbounded luby-sequence-core*  
**unfolding** *bounded-def*  
**proof**  
**assume**  $\exists b. \forall n. \text{luby-sequence-core } n \leq b$   
**then obtain**  $b$  **where**  $b: \bigwedge n. \text{luby-sequence-core } n \leq b$   
**by** *metis*  
**have**  $\text{luby-sequence-core } (2^{b+1} - 1) = 2^b$   
**using** *luby-sequence-core-two-power-minus-one[of b+1]* **by** *simp*  
**moreover have**  $(2::\text{nat})^b > b$   
**by** *(induction b) auto*  
**ultimately show** *False* **using**  $b[\text{of } 2^{b+1} - 1]$  **by** *linarith*  
**qed**

**abbreviation** *luby-sequence* ::  $\text{nat} \Rightarrow \text{nat}$  **where**  
*luby-sequence*  $n \equiv ur * \text{luby-sequence-core } n$

**lemma** *bounded-luby-sequence: unbounded luby-sequence*  
**using** *bounded-const-product[of ur] luby-sequence-axioms*  
*luby-sequence-def unbounded-luby-sequence-core* **by** *blast*

**lemma** *luby-sequence-core-0: luby-sequence-core 0 = 1*  
**proof** –  
**have**  $0: (0::\text{nat}) = 2^0 - 1$   
**by** *auto*  
**show** *?thesis*  
**by** *(subst 0, subst luby-sequence-core-two-power-minus-one) simp*  
**qed**

**lemma** *luby-sequence-core n ≥ 1*  
**proof** *(induction n rule: nat-less-induct-case)*  
**case**  $0$   
**then show** *?case* **by** *(simp add: luby-sequence-core-0)*  
**next**  
**case** *(Suc n)* **note** *IH = this*

**consider**  
*(interv) k where  $2^{k-1} \leq \text{Suc } n$  and  $\text{Suc } n < 2^k - 1$*   
*| (pow2) k where  $\text{Suc } n = 2^k - \text{Suc } 0$*   
**using** *exists-luby-decomp[of Suc n]* **by** *auto*

**then show** *?case*  
**proof** *cases*  
**case** *pow2*  
**show** *?thesis*  
**using** *luby-sequence-core-two-power-minus-one pow2* **by** *auto*  
**next**  
**case** *interv*  
**have**  $n: \text{Suc } n - 2^{k-1} + 1 < \text{Suc } n$   
**by** *(metis Suc-1 Suc-eq-plus1 add.commute add-diff-cancel-left' add-less-mono1 gr0I*  
*interv(1) interv(2) le-add-diff-inverse2 less-Suc-eq not-le power-0 power-one-right*  
*power-strict-increasing-iff)*  
**show** *?thesis*  
**apply** *(subst luby-sequence-core-not-two-power-minus-one[OF interv])*  
**using** *IH n* **by** *auto*

```

qed
qed
end

locale luby-sequence-restart =
  luby-sequence ur +
  conflict-driven-clause-learningW — functions for clauses:
    mset-cls insert-cls remove-lit
    mset-clss union-clss in-clss insert-clss remove-from-clss

  — functions for the conflicting clause:
    mset-ccls union-ccls insert-ccls remove-clit

  — conversion
    ccls-of-cls cls-of-ccls

  — functions for the state:
    — access functions:
      trail hd-raw-trail raw-init-clss raw-learned-clss backtrack-lvl raw-conflicting
    — changing state:
      cons-trail tl-trail add-init-cls add-learned-cls remove-cls update-backtrack-lvl
      update-conflicting

    — get state:
      init-state
      restart-state
for
  ur :: nat and
  mset-cls:: 'cls ⇒ 'v clause and
  insert-cls :: 'v literal ⇒ 'cls ⇒ 'cls and
  remove-lit :: 'v literal ⇒ 'cls ⇒ 'cls and

  mset-clss:: 'clss ⇒ 'v clauses and
  union-clss :: 'clss ⇒ 'clss ⇒ 'clss and
  in-clss :: 'cls ⇒ 'clss ⇒ bool and
  insert-clss :: 'cls ⇒ 'clss ⇒ 'clss and
  remove-from-clss :: 'cls ⇒ 'clss ⇒ 'clss and

  mset-ccls:: 'ccls ⇒ 'v clause and
  union-ccls :: 'ccls ⇒ 'ccls ⇒ 'ccls and
  insert-ccls :: 'v literal ⇒ 'ccls ⇒ 'ccls and
  remove-clit :: 'v literal ⇒ 'ccls ⇒ 'ccls and

  ccls-of-cls :: 'cls ⇒ 'ccls and
  cls-of-ccls :: 'ccls ⇒ 'cls and

  trail :: 'st ⇒ ('v, nat, 'v clause) marked-lits and
  hd-raw-trail :: 'st ⇒ ('v, nat, 'cls) marked-lit and
  raw-init-clss :: 'st ⇒ 'clss and
  raw-learned-clss :: 'st ⇒ 'clss and
  backtrack-lvl :: 'st ⇒ nat and
  raw-conflicting :: 'st ⇒ 'ccls option and

  cons-trail :: ('v, nat, 'cls) marked-lit ⇒ 'st ⇒ 'st and
  tl-trail :: 'st ⇒ 'st and

```

```

    add-init-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
    add-learned-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
    remove-cls :: 'cls  $\Rightarrow$  'st  $\Rightarrow$  'st and
    update-backtrack-lvl :: nat  $\Rightarrow$  'st  $\Rightarrow$  'st and
    update-conflicting :: 'ccls option  $\Rightarrow$  'st  $\Rightarrow$  'st and

    init-state :: 'clss  $\Rightarrow$  'st and
    restart-state :: 'st  $\Rightarrow$  'st
begin

sublocale cdclW-restart - - - - - luby-sequence
  apply unfold-locales
  using bounded-luby-sequence by blast

end
end
theory CDCL-WNOT
imports CDCL-NOT CDCL-W-Termination CDCL-W-Merge
begin

```

## 22 Link between Weidenbach's and NOT's CDCL

### 22.1 Inclusion of the states

```

declare upt.simps(2)[simp del]

fun convert-marked-lit-from-W where
  convert-marked-lit-from-W (Propagated L -) = Propagated L () |
  convert-marked-lit-from-W (Marked L -) = Marked L ()

abbreviation convert-trail-from-W ::
  ('v, 'lvl, 'a) marked-lit list
   $\Rightarrow$  ('v, unit, unit) marked-lit list where
  convert-trail-from-W  $\equiv$  map convert-marked-lit-from-W

lemma lits-of-l-convert-trail-from-W[simp]:
  lits-of-l (convert-trail-from-W M) = lits-of-l M
  by (induction rule: marked-lit-list-induct) simp-all

lemma lit-of-convert-trail-from-W[simp]:
  lit-of (convert-marked-lit-from-W L) = lit-of L
  by (cases L) auto

lemma no-dup-convert-from-W[simp]:
  no-dup (convert-trail-from-W M)  $\longleftrightarrow$  no-dup M
  by (auto simp: comp-def)

lemma convert-trail-from-W-true-annots[simp]:
  convert-trail-from-W M  $\models_{as}$  C  $\longleftrightarrow$  M  $\models_{as}$  C
  by (auto simp: true-annots-true-cls image-image lits-of-def)

lemma defined-lit-convert-trail-from-W[simp]:
  defined-lit (convert-trail-from-W S) L  $\longleftrightarrow$  defined-lit S L
  by (auto simp: defined-lit-map image-comp)

```

The values 0 and {#} are dummy values.

```

consts dummy-cls :: 'cls
fun convert-marked-lit-from-NOT
  :: ('a, 'e, 'b) marked-lit  $\Rightarrow$  ('a, nat, 'cls) marked-lit where
convert-marked-lit-from-NOT (Propagated L -) = Propagated L dummy-cls |
convert-marked-lit-from-NOT (Marked L -) = Marked L 0

abbreviation convert-trail-from-NOT where
convert-trail-from-NOT  $\equiv$  map convert-marked-lit-from-NOT

lemma undefined-lit-convert-trail-from-NOT[simp]:
  undefined-lit (convert-trail-from-NOT F) L  $\longleftrightarrow$  undefined-lit F L
by (induction F rule: marked-lit-list-induct) (auto simp: defined-lit-map)

lemma lits-of-l-convert-trail-from-NOT:
  lits-of-l (convert-trail-from-NOT F) = lits-of-l F
by (induction F rule: marked-lit-list-induct) auto

lemma convert-trail-from-W-from-NOT[simp]:
  convert-trail-from-W (convert-trail-from-NOT M) = M
by (induction rule: marked-lit-list-induct) auto

lemma convert-trail-from-W-convert-lit-from-NOT[simp]:
  convert-marked-lit-from-W (convert-marked-lit-from-NOT L) = L
by (cases L) auto

abbreviation trailNOT where
trailNOT S  $\equiv$  convert-trail-from-W (fst S)

lemma undefined-lit-convert-trail-from-W[iff]:
  undefined-lit (convert-trail-from-W M) L  $\longleftrightarrow$  undefined-lit M L
by (auto simp: defined-lit-map image-comp)

lemma lit-of-convert-marked-lit-from-NOT[iff]:
  lit-of (convert-marked-lit-from-NOT L) = lit-of L
by (cases L) auto

sublocale stateW  $\subseteq$  dpll-state-ops
  mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
   $\lambda S.$  convert-trail-from-W (trail S)
  raw-clauses
   $\lambda L S.$  cons-trail (convert-marked-lit-from-NOT L) S
   $\lambda S.$  tl-trail S
   $\lambda C S.$  add-learned-cls C S
   $\lambda C S.$  remove-cls C S
by unfold-locales

context stateW
begin
lemma convert-marked-lit-from-W-convert-marked-lit-from-NOT[simp]:
  convert-marked-lit-from-W (mmset-of-mlit (convert-marked-lit-from-NOT L)) = L
by (cases L) auto
end

sublocale stateW  $\subseteq$  dpll-state

```



```

mset-cls insert-cls remove-lit
mset-clss union-clss in-clss insert-clss remove-from-clss
λS. convert-trail-from-W (trail S)
raw-clauses
λL S. cons-trail (convert-marked-lit-from-NOT L) S
λS. tl-trail S
λC S. add-learned-cls C S
λC S. remove-cls C S
by unfold-locales (auto simp: map-tl o-def)

context state_W
begin
declare state-simp_{NOT}[simp del]

end

sublocale conflict-driven-clause-learning_W ⊆ cdcl_{NOT}-merge-bj-learn-ops
  mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  λS. convert-trail-from-W (trail S)
  raw-clauses
  λL S. cons-trail (convert-marked-lit-from-NOT L) S
  λS. tl-trail S
  λC S. add-learned-cls C S
  λC S. remove-cls C S
  λ-. True
  λ-. S. raw-conflicting S = None
  λC C' L' S T. backjump-l-cond C C' L' S T
    ∧ distinct-mset (C' + {#L'#}) ∧ ¬tautology (C' + {#L'#})
  by unfold-locales

thm cdcl_{NOT}-merge-bj-learn-proxy.axioms
sublocale conflict-driven-clause-learning_W ⊆ cdcl_{NOT}-merge-bj-learn-proxy
  mset-cls insert-cls remove-lit
  mset-clss union-clss in-clss insert-clss remove-from-clss
  λS. convert-trail-from-W (trail S)
  raw-clauses
  λL S. cons-trail (convert-marked-lit-from-NOT L) S
  λS. tl-trail S
  λC S. add-learned-cls C S
  λC S. remove-cls C S

  λ-. True
  λ-. S. raw-conflicting S = None
  backjump-l-cond
  inv_{NOT}
proof (unfold-locales, goal-cases)
  case 2
  then show ?case using cdcl_{NOT}-merged-bj-learn-no-dup-inv by (auto simp: comp-def)
next
  case (1 C' S C F' K F L)
  moreover
  let ?C' = remdups-mset C'

```

```

have L  $\notin$  # C'
  using  $\langle F \models_{as} CNot\ C' \rangle \langle undefined-lit\ F\ L \rangle$  Marked-Propagated-in-iff-in-lits-of-l
  in-CNot-implies-uminus(2) by fast
then have distinct-mset ( $?C' + \{\#L\# \}$ )
  by (simp add: distinct-mset-single-add)
moreover
have no-dup F
  using  $\langle inv_{NOT}\ S \rangle \langle convert-trail-from-W\ (trail\ S) = F' @ Marked\ K\ () \# F \rangle$ 
  unfolding  $inv_{NOT}\text{-def}$ 
  by (smt comp-apply distinct.simps(2) distinct-append list.simps(9) map-append
      no-dup-convert-from-W)
then have consistent-interp (lits-of-l F)
  using distinct-consistent-interp by blast
then have  $\neg$  tautology (C')
  using  $\langle F \models_{as} CNot\ C' \rangle$  consistent-CNot-not-tautology true-annots-true-cls by blast
then have  $\neg$  tautology ( $?C' + \{\#L\# \}$ )
  using  $\langle F \models_{as} CNot\ C' \rangle \langle undefined-lit\ F\ L \rangle$  by (metis CNot-remdups-mset
      Marked-Propagated-in-iff-in-lits-of-l add.commute in-CNot-uminus tautology-add-single
      tautology-remdups-mset true-annot-singleton true-annots-def)
show ?case
proof -
  have f2: no-dup (convert-trail-from-W (trail S))
    using  $\langle inv_{NOT}\ S \rangle$  unfolding  $inv_{NOT}\text{-def}$  by (simp add: o-def)
  have f3: atm-of L  $\in$  atms-of-mm (clauses S)
     $\cup$  atm-of ' lits-of-l (convert-trail-from-W (trail S))
    using  $\langle convert-trail-from-W\ (trail\ S) = F' @ Marked\ K\ () \# F \rangle$ 
     $\langle atm-of\ L \in atms-of-mm\ (clauses\ S) \cup atm-of\ ' lits-of-l\ (F' @ Marked\ K\ () \# F) \rangle$  by auto
  have f4: clauses S  $\models_{pm}$  remdups-mset C' +  $\{\#L\# \}$ 
    by (metis (no-types)  $\langle L \notin \# C' \rangle \langle clauses\ S \models_{pm}\ C' + \{\#L\# \} \rangle$  remdups-mset-singleton-sum(2)
        true-clss-cls-remdups-mset union-commute)
  have F  $\models_{as}\ CNot\ (remdups-mset\ C')$ 
    by (simp add:  $\langle F \models_{as}\ CNot\ C' \rangle$ )
  obtain D where D: mset-cls D = remdups-mset C' +  $\{\#L\# \}$ 
    using ex-mset-cls by blast
  have Ex (backjump-l S)
    apply standard
    apply (rule backjump-l.intros[OF f2, of - - -])
    using f4 f3 f2  $\neg$  tautology (remdups-mset C' +  $\{\#L\# \}$ )
    calculation(2-5,9)  $\langle F \models_{as}\ CNot\ (remdups-mset\ C') \rangle$ 
    state-eqNOT-ref D unfolding backjump-l-cond-def by blast+
  then show ?thesis
    by blast
qed
qed

sublocale conflict-driven-clause-learningW  $\subseteq$  cdclNOT-merge-bj-learn-proxy2 - - - - -
   $\lambda S.$  convert-trail-from-W (trail S)
  raw-clauses
   $\lambda L\ S.$  cons-trail (convert-marked-lit-from-NOT L) S
   $\lambda S.$  tl-trail S
   $\lambda C\ S.$  add-learned-cls C S
   $\lambda C\ S.$  remove-cls C S
   $\lambda -.$  True
   $\lambda -.$  S.raw-conflicting S = None backjump-l-cond  $inv_{NOT}$ 
  by unfold-locales

```

**sublocale** *conflict-driven-clause-learning*<sub>W</sub>  $\subseteq$  *cdcl*<sub>NOT</sub>-merge-bj-learn - - - - -  
 $\lambda S.$  *convert-trail-from-W* (*trail* *S*)  
*raw-clauses*  
 $\lambda L S.$  *cons-trail* (*convert-marked-lit-from-NOT* *L*) *S*  
 $\lambda S.$  *tl-trail* *S*  
 $\lambda C S.$  *add-learned-cls* *C* *S*  
 $\lambda C S.$  *remove-cls* *C* *S*  
*backjump-l-cond*  
 $\lambda -.$  *True*  
 $\lambda - S.$  *raw-conflicting* *S* = *None* *inv*<sub>NOT</sub>  
**apply** *unfold-locales*  
**using** *dpll-bj-no-dup* **apply** (*simp* *add*: *comp-def*)  
**using** *cdcl*<sub>NOT</sub>.*simps* *cdcl*<sub>NOT</sub>-*no-dup* *no-dup-convert-from-W* **unfolding** *inv*<sub>NOT</sub>-*def* **by** *blast*

**context** *conflict-driven-clause-learning*<sub>W</sub>  
**begin**

Notations are lost while proving locale inclusion:

**notation** *state-eq*<sub>NOT</sub> (**infix**  $\sim$ <sub>NOT</sub> 50)

## 22.2 Additional Lemmas between NOT and W states

**lemma** *trail*<sub>W</sub>-*eq-reduce-trail-to*<sub>NOT</sub>-*eq*:  
 $\text{trail } S = \text{trail } T \implies \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S) = \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F T)$   
**proof** (*induction* *F* *S* *arbitrary*: *T* *rule*: *reduce-trail-to*<sub>NOT</sub>.*induct*)  
**case** (*1 F S T*) **note** *IH* = *this*(1) **and** *tr* = *this*(2)  
**then have**  $\square = \text{convert-trail-from-W } (\text{trail } S)$   
 $\vee \text{length } F = \text{length } (\text{convert-trail-from-W } (\text{trail } S))$   
 $\vee \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F (\text{tl-trail } S)) = \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F (\text{tl-trail } T))$   
**using** *IH* **by** (*metis* (*no-types*) *trail-tl-trail*)  
**then show**  $\text{trail } (\text{reduce-trail-to}_{\text{NOT}} F S) = \text{trail } (\text{reduce-trail-to}_{\text{NOT}} F T)$   
**using** *tr* **by** (*metis* (*no-types*) *reduce-trail-to*<sub>NOT</sub>.*elims*)  
**qed**

**lemma** *trail-reduce-trail-to*<sub>NOT</sub>-*add-learned-cls*:  
 $\text{no-dup } (\text{trail } S) \implies$   
 $\text{trail } (\text{reduce-trail-to}_{\text{NOT}} M (\text{add-learned-cls } D S)) = \text{trail } (\text{reduce-trail-to}_{\text{NOT}} M S)$   
**by** (*rule* *trail*<sub>W</sub>-*eq-reduce-trail-to*<sub>NOT</sub>-*eq*) *simp*

**lemma** *reduce-trail-to*<sub>NOT</sub>-*reduce-trail-convert*:  
 $\text{reduce-trail-to}_{\text{NOT}} C S = \text{reduce-trail-to } (\text{convert-trail-from-NOT } C) S$   
**apply** (*induction* *C* *S* *rule*: *reduce-trail-to*<sub>NOT</sub>.*induct*)  
**apply** (*subst* *reduce-trail-to*<sub>NOT</sub>.*simps*, *subst* *reduce-trail-to*.*simps*)  
**by** *auto*

**lemma** *reduce-trail-to-map*[*simp*]:  
 $\text{reduce-trail-to } (\text{map } f M) S = \text{reduce-trail-to } M S$   
**by** (*rule* *reduce-trail-to-length*) *simp*

**lemma** *reduce-trail-to*<sub>NOT</sub>-*map*[*simp*]:  
 $\text{reduce-trail-to}_{\text{NOT}} (\text{map } f M) S = \text{reduce-trail-to}_{\text{NOT}} M S$   
**by** (*rule* *reduce-trail-to*<sub>NOT</sub>-*length*) *simp*

**lemma** *skip-or-resolve-state-change*:  
**assumes** *skip-or-resolve*\*\* *S* *T*

```

shows
   $\exists M. \text{trail } S = M @ \text{trail } T \wedge (\forall m \in \text{set } M. \neg \text{is-marked } m)$ 
  clauses  $S = \text{clauses } T$ 
  backtrack-lvl  $S = \text{backtrack-lvl } T$ 
using assms
proof (induction rule: rtrancpl-induct)
  case base
  case 1 show ?case by simp
  case 2 show ?case by simp
  case 3 show ?case by simp
next
  case (step T U) note st = this(1) and s-o-r = this(2) and IH = this(3) and IH' = this(3-5)

  case 2 show ?case using IH' s-o-r by (auto elim!: rulesE simp: skip-or-resolve.simps)
  case 3 show ?case using IH' s-o-r by (auto elim!: rulesE simp: skip-or-resolve.simps)
  case 1 show ?case
    using s-o-r
    proof cases
      case s-or-r-skip
      then show ?thesis using IH by (auto elim!: rulesE simp: skip-or-resolve.simps)
    next
      case s-or-r-resolve
      then show ?thesis
        using IH by (cases trail T) (auto elim!: rulesE simp: skip-or-resolve.simps dest!:
          hd-raw-trail)
    qed
  qed
qed

```

## 22.3 More lemmas conflict-propagate and backjumping

### 22.4 CDCL FW

```

lemma cdclW-merge-is-cdclNOT-merged-bj-learn:
  assumes
    inv: cdclW-all-struct-inv S and
    cdclW:cdclW-merge S T
  shows cdclNOT-merged-bj-learn S T
     $\vee (\text{no-step } \text{cdcl}_W\text{-merge } T \wedge \text{conflicting } T \neq \text{None})$ 
  using cdclW inv
proof induction
  case (fw-propagate S T) note propa = this(1)
  then obtain M N U k L C where
    H: state S = (M, N, U, k, None) and
    CL:  $C + \{\#L\# \} \in \# \text{ clauses } S$  and
    M-C:  $M \models_{as} C \text{Not } C$  and
    undef: undefined-lit (trail S) L and
    T: state T = (Propagated L (C +  $\{\#L\# \}$ ) # M, N, U, k, None)
    by (auto elim: propagate-high-levelE)
  have propagateNOT S T
    using H CL T undef M-C by (auto simp: state-eqNOT-def state-eq-def raw-clauses-def
      simp del: state-simp)
  then show ?case
    using cdclNOT-merged-bj-learn.intros(2) by blast
next
  case (fw-decide S T) note dec = this(1) and inv = this(2)
  then obtain L where

```

```

  undef-L: undefined-lit (trail S) L and
  atm-L: atm-of L ∈ atms-of-mm (init-clss S) and
  T: T ∼ cons-trail (Marked L (Suc (backtrack-lvl S)))
    (update-backtrack-lvl (Suc (backtrack-lvl S)) S)
  by (auto elim: decideE)
have decideNOT S T
  apply (rule decideNOT.decideNOT)
    using undef-L apply simp
    using atm-L inv unfolding cdclW-all-struct-inv-def no-strange-atm-def raw-clauses-def
    apply auto[]
    using T undef-L unfolding state-eq-def state-eqNOT-def by (auto simp: raw-clauses-def)
  then show ?case using cdclNOT-merged-bj-learn-decideNOT by blast
next
case (fw-forget S T) note rf = this(1) and inv = this(2)
then obtain C where
  S: conflicting S = None and
  C-le: C !∈! raw-learned-clss S and
  ¬(trail S) ⊨asm clauses S and
  mset-cls C ∉ set (get-all-mark-of-propagated (trail S)) and
  C-init: mset-cls C ∉# init-clss S and
  T: T ∼ remove-cls C S
  by (auto elim: forgetE)
have init-clss S ⊨pm mset-cls C
  using inv C-le unfolding cdclW-all-struct-inv-def cdclW-learned-clause-def raw-clauses-def
  by (meson in-clss-mset-clss true-clss-clss-in-imp-true-clss-clss)
then have S-C: removeAll-mset (mset-cls C) (clauses S) ⊨pm mset-cls C
  using C-init C-le unfolding raw-clauses-def by (auto simp add: Un-Diff ac-simps)
have forgetNOT S T
  apply (rule forgetNOT.forgetNOT)
    using S-C apply blast
    using S apply simp
    using C-init C-le apply (simp add: raw-clauses-def)
  using T C-le C-init by (auto
    simp: state-eq-def Un-Diff state-eqNOT-def raw-clauses-def ac-simps
    simp del: state-simp)
  then show ?case using cdclNOT-merged-bj-learn-forgetNOT by blast
next
case (fw-conflict S T U) note confl = this(1) and bj = this(2) and inv = this(3)
obtain CS CT where
  confl-T: raw-conflicting T = Some CT and
  CT: mset-ccls CT = mset-cls CS and
  CS: CS !∈! raw-clauses S and
  tr-S-CS: trail S ⊨as CNot (mset-cls CS)
  using confl by (elim conflictE) (auto simp del: state-simp simp: state-eq-def)
have cdclW-all-struct-inv T
  using cdclW.simps cdclW-all-struct-inv-inv confl inv by blast
then have cdclW-M-level-inv T
  unfolding cdclW-all-struct-inv-def by auto
then consider
  (no-bt) skip-or-resolve** T U
  | (bt) T' where skip-or-resolve** T T' and backtrack T' U
  using bj rtranclp-cdclW-bj-skip-or-resolve-backtrack unfolding full-def by meson
then show ?case
  proof cases
    case no-bt

```

```

then have conflicting  $U \neq \text{None}$ 
  using confl by (induction rule: rtrancpl-induct)
  (auto simp del: state-simp simp: skip-or-resolve.simps state-eq-def elim!: rulesE)
moreover then have no-step  $\text{cdcl}_W$ -merge  $U$ 
  by (auto simp:  $\text{cdcl}_W$ -merge.simps elim: rulesE)
ultimately show ?thesis by blast
next
case bt note  $s\text{-or-}r = \text{this}(1)$  and  $bt = \text{this}(2)$ 
have  $\text{cdcl}_W^{**} T T'$ 
  using  $s\text{-or-}r$  mono-rtrancpl[of skip-or-resolve  $\text{cdcl}_W$ ] rtrancpl-skip-or-resolve-rtrancpl- $\text{cdcl}_W$ 
  by blast
then have  $\text{cdcl}_W$ -M-level-inv  $T'$ 
  using rtrancpl- $\text{cdcl}_W$ -consistent-inv  $\langle \text{cdcl}_W$ -M-level-inv  $T \rangle$  by blast
then obtain  $M1 M2 i D L K$  where
  confl- $T'$ : raw-conflicting  $T' = \text{Some } D$  and
  LD:  $L \in \# \text{mset-ccls } D$  and
  M1-M2:  $(\text{Marked } K (i+1) \# M1, M2) \in \text{set } (\text{get-all-marked-decomposition } (\text{trail } T'))$  and
  get-level  $(\text{trail } T') L = \text{backtrack-lvl } T'$  and
  get-level  $(\text{trail } T') L = \text{get-maximum-level } (\text{trail } T') (\text{mset-ccls } D)$  and
  get-maximum-level  $(\text{trail } T') (\text{mset-ccls } (\text{remove-clit } L D)) = i$  and
  undef-L: undefined-lit  $M1 L$  and
  U:  $U \sim \text{cons-trail } (\text{Propagated } L (\text{cls-of-ccls } D))$ 
  (reduce-trail-to  $M1$ 
    (add-learned-cls  $(\text{cls-of-ccls } D)$ 
      (update-backtrack-lvl  $i$ 
        (update-conflicting  $\text{None } T'$ ))))
  using bt by (auto elim: backtrack-levE)
have [simp]: clauses  $S = \text{clauses } T$ 
  using confl by (auto elim: rulesE)
have [simp]: clauses  $T = \text{clauses } T'$ 
  using  $s\text{-or-}r$ 
  proof (induction)
    case base
    then show ?case by simp
  next
    case (step  $U V$ ) note  $st = \text{this}(1)$  and  $s\text{-o-}r = \text{this}(2)$  and  $IH = \text{this}(3)$ 
    have clauses  $U = \text{clauses } V$ 
      using  $s\text{-o-}r$  by (auto simp: skip-or-resolve.simps elim: rulesE)
    then show ?case using  $IH$  by auto
  qed
have inv- $T$ :  $\text{cdcl}_W$ -all-struct-inv  $T$ 
  by (meson  $\text{cdcl}_W$ -cp.simps confl inv r-into-rtrancpl rtrancpl- $\text{cdcl}_W$ -all-struct-inv-inv
    rtrancpl- $\text{cdcl}_W$ -cp-rtrancpl- $\text{cdcl}_W$ )
have  $\text{cdcl}_W^{**} T T'$ 
  using rtrancpl-skip-or-resolve-rtrancpl- $\text{cdcl}_W$   $s\text{-or-}r$  by blast
have inv- $T'$ :  $\text{cdcl}_W$ -all-struct-inv  $T'$ 
  using  $\langle \text{cdcl}_W^{**} T T' \rangle$  inv- $T$  rtrancpl- $\text{cdcl}_W$ -all-struct-inv-inv by blast
have inv- $U$ :  $\text{cdcl}_W$ -all-struct-inv  $U$ 
  using  $\text{cdcl}_W$ -merge-restart- $\text{cdcl}_W$  confl fw-r-conflict inv local.bj
  rtrancpl- $\text{cdcl}_W$ -all-struct-inv-inv by blast

have [simp]: init-clss  $S = \text{init-clss } T'$ 
  using  $\langle \text{cdcl}_W^{**} T T' \rangle$   $\text{cdcl}_W$ -init-clss confl  $\text{cdcl}_W$ -all-struct-inv-def conflict inv
  by (metis  $\langle \text{cdcl}_W$ -M-level-inv  $T \rangle$  rtrancpl- $\text{cdcl}_W$ -init-clss)
then have atm-L: atm-of  $L \in \text{atms-of-mm } (\text{clauses } S)$ 

```

```

    using inv-T' confl-T' LD unfolding cdclW-all-struct-inv-def no-strange-atm-def
    raw-clauses-def
    by (simp add: atms-of-def image-subset-iff)
  obtain M where tr-T: trail T = M @ trail T'
    using s-or-r skip-or-resolve-state-change by meson
  obtain M' where
    tr-T': trail T' = M' @ Marked K (i+1) # tl (trail U) and
    tr-U: trail U = Propagated L (mset-ccls D) # tl (trail U)
    using U M1-M2 undef-L inv-T' unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def
    by fastforce
  def M'' ≡ M @ M'
  have tr-T: trail S = M'' @ Marked K (i+1) # tl (trail U)
    using tr-T tr-T' confl unfolding M''-def by (auto elim: rulesE)
  have init-clss T' + learned-clss S ⊨pm mset-ccls D
    using inv-T' confl-T' unfolding cdclW-all-struct-inv-def cdclW-learned-clause-def
    raw-clauses-def by simp
  have reduce-trail-to (convert-trail-from-NOT (convert-trail-from-W M1)) S =
    reduce-trail-to M1 S
    by (rule reduce-trail-to-length) simp
  moreover have trail (reduce-trail-to M1 S) = M1
    apply (rule reduce-trail-to-skip-beginning[of - M @ - @ M2 @ [Marked K (Suc i)]])
    using confl M1-M2 (trail T = M @ trail T')
    apply (auto dest!: get-all-marked-decomposition-exists-prepend
      elim!: conflictE)
    by (rule sym) auto
  ultimately have [simp]: trail (reduce-trail-toNOT M1 S) = M1
    using M1-M2 confl by (subst reduce-trail-toNOT-reduce-trail-convert)
    (auto simp: comp-def elim: rulesE)
  have every-mark-is-a-conflict U
    using inv-U unfolding cdclW-all-struct-inv-def cdclW-conflicting-def by simp
  then have U-D: tl (trail U) ⊨as CNot (remove1-mset L (mset-ccls D))
    by (metis append-self-conv2 tr-U)
  thm backjump-l[of - - - - L cls-of-ccls D - remove1-mset L (mset-ccls D)]
  have backjump-l S U
    apply (rule backjump-l[of - - - - L cls-of-ccls D - remove1-mset L (mset-ccls D)])
    using tr-T apply simp
    using inv unfolding cdclW-all-struct-inv-def cdclW-M-level-inv-def
    apply (simp add: comp-def)
    using U M1-M2 confl undef-L M1-M2 inv-T' inv undef-L unfolding cdclW-all-struct-inv-def
    cdclW-M-level-inv-def apply (auto simp: state-eqNOT-def
      trail-reduce-trail-toNOT-add-learned-clss)[]
    using CS apply auto[]
    using tr-S-CS apply simp

    using U undef-L M1-M2 inv-T' inv unfolding cdclW-all-struct-inv-def
    cdclW-M-level-inv-def apply auto[]
    using undef-L atm-L apply (simp add: trail-reduce-trail-toNOT-add-learned-clss)
    using (init-clss T' + learned-clss S ⊨pm mset-ccls D) LD unfolding raw-clauses-def
    apply simp
    using LD apply simp
  apply (metis U-D convert-trail-from-W-true-annots)
  using inv-T' inv-U U confl-T' undef-L M1-M2 LD unfolding cdclW-all-struct-inv-def
  distinct-cdclW-state-def by (simp add: cdclW-M-level-inv-decomp backjump-l-cond-def)
  then show ?thesis using cdclNOT-merged-bj-learn-backjump-l by fast
qed

```

qed

**abbreviation**  $cdcl_{NOT}\text{-restart}$  **where**

$cdcl_{NOT}\text{-restart} \equiv restart\text{-ops}.cdcl_{NOT}\text{-raw-restart } cdcl_{NOT} \text{ restart}$

**lemma**  $cdcl_W\text{-merge-restart-is-}cdcl_{NOT}\text{-merged-bj-learn-restart-no-step}$ :

**assumes**

$inv: cdcl_W\text{-all-struct-inv } S$  **and**

$cdcl_W: cdcl_W\text{-merge-restart } S \ T$

**shows**  $cdcl_{NOT}\text{-restart}^{**} \ S \ T \vee (no\text{-step } cdcl_W\text{-merge } T \wedge conflicting \ T \neq None)$

**proof** –

**consider**

$(fw) \ cdcl_W\text{-merge } S \ T$

|  $(fw\text{-}r) \ restart \ S \ T$

**using**  $cdcl_W$  **by** ( $meson \ cdcl_W\text{-merge-restart}.simps \ cdcl_W\text{-rf}.cases \ fw\text{-conflict} \ fw\text{-decide} \ fw\text{-forget} \ fw\text{-propagate}$ )

**then show**  $?thesis$

**proof**  $cases$

**case**  $fw$

**then have**  $IH: cdcl_{NOT}\text{-merged-bj-learn } S \ T \vee (no\text{-step } cdcl_W\text{-merge } T \wedge conflicting \ T \neq None)$

**using**  $inv \ cdcl_W\text{-merge-is-}cdcl_{NOT}\text{-merged-bj-learn}$  **by**  $blast$

**have**  $invS: inv_{NOT} \ S$

**using**  $inv$  **unfolding**  $cdcl_W\text{-all-struct-inv-def } cdcl_W\text{-M-level-inv-def}$  **by**  $auto$

**have**  $ff2: cdcl_{NOT}^{++} \ S \ T \longrightarrow cdcl_{NOT}^{**} \ S \ T$

**by** ( $meson \ tranclp\text{-into-rtranclp}$ )

**have**  $ff3: no\text{-dup} \ (convert\text{-trail-from-}W \ (trail \ S))$

**using**  $invS$  **by** ( $simp \ add: \ comp\text{-def}$ )

**have**  $cdcl_{NOT} \leq cdcl_{NOT}\text{-restart}$

**by** ( $auto \ simp: \ restart\text{-ops}.cdcl_{NOT}\text{-raw-restart}.simps$ )

**then show**  $?thesis$

**using**  $ff3 \ ff2 \ IH \ cdcl_{NOT}\text{-merged-bj-learn-is-tranclp-}cdcl_{NOT}$

$rtranclp\text{-mono}[of \ cdcl_{NOT} \ cdcl_{NOT}\text{-restart}] \ invS \ predicate2D$  **by**  $blast$

**next**

**case**  $fw\text{-}r$

**then show**  $?thesis$  **by** ( $blast \ intro: \ restart\text{-ops}.cdcl_{NOT}\text{-raw-restart}.intros$ )

qed

qed

**abbreviation**  $\mu_{FW} :: 'st \Rightarrow nat$  **where**

$\mu_{FW} \ S \equiv (if \ no\text{-step } cdcl_W\text{-merge } S \ then \ 0 \ else \ 1 + \mu_{CDCL}'\text{-merged} \ (set\text{-mset} \ (init\text{-class } S)) \ S)$

**lemma**  $cdcl_W\text{-merge-}\mu_{FW}\text{-decreasing}$ :

**assumes**

$inv: cdcl_W\text{-all-struct-inv } S$  **and**

$fw: cdcl_W\text{-merge } S \ T$

**shows**  $\mu_{FW} \ T < \mu_{FW} \ S$

**proof** –

**let**  $?A = init\text{-class } S$

**have**  $atm\text{-clauses}: atm\text{-of-mm} \ (clauses \ S) \subseteq atm\text{-of-mm} \ ?A$

**using**  $inv$  **unfolding**  $cdcl_W\text{-all-struct-inv-def} \ no\text{-strange-atm-def} \ raw\text{-clauses-def}$  **by**  $auto$

**have**  $atm\text{-trail}: atm\text{-of } ' \ lits\text{-of-l} \ (trail \ S) \subseteq atm\text{-of-mm} \ ?A$

**using**  $inv$  **unfolding**  $cdcl_W\text{-all-struct-inv-def} \ no\text{-strange-atm-def} \ raw\text{-clauses-def}$  **by**  $auto$

**have**  $n\text{-d}: no\text{-dup} \ (trail \ S)$

**using**  $inv$  **unfolding**  $cdcl_W\text{-all-struct-inv-def}$  **by** ( $auto \ simp: \ cdcl_W\text{-M-level-inv-decomp}$ )

**have**  $[simp]: \neg \ no\text{-step } cdcl_W\text{-merge } S$



```

    using fw by auto
have [simp]: init-clss S = init-clss T
    using cdclW-merge-restart-cdclW[of S T] inv rtrancpl-cdclW-init-clss
    unfolding cdclW-all-struct-inv-def
    by (meson cdclW-merge.simps cdclW-merge-restart.simps cdclW-rf.simps fw)
consider
    (merged) cdclNOT-merged-bj-learn S T
| (n-s) no-step cdclW-merge T
    using cdclW-merge-is-cdclNOT-merged-bj-learn inv fw by blast
then show ?thesis
proof cases
    case merged
    then show ?thesis
        using cdclNOT-decreasing-measure'[OF - - atm-clauses, of T] atm-trail n-d
        by (auto split: if-split simp: comp-def image-image lits-of-def)
    next
    case n-s
    then show ?thesis by simp
qed
qed

lemma wf-cdclW-merge: wf {(T, S). cdclW-all-struct-inv S ∧ cdclW-merge S T}
    apply (rule wfP-if-measure[of - - μFW])
    using cdclW-merge-μFW-decreasing by blast

sublocale conflict-driven-clause-learningW-termination
    by unfold-locales (simp add: wf-cdclW-merge)

lemma full-cdclW-s'-full-cdclW-merge-restart:
    assumes
        conflicting R = None and
        inv: cdclW-all-struct-inv R
    shows full cdclW-s' R V ⟷ full cdclW-merge-stgy R V (is ?s' ⟷ ?fw)
proof
    assume ?s'
    then have cdclW-s*** R V unfolding full-def by blast
    have cdclW-all-struct-inv V
        using ⟨cdclW-s*** R V⟩ inv rtrancpl-cdclW-all-struct-inv-inv rtrancpl-cdclW-s'-rtrancpl-cdclW
        by blast
    then have n-s: no-step cdclW-merge-stgy V
        using no-step-cdclW-s'-no-step-cdclW-merge-stgy by (meson ⟨full cdclW-s' R V⟩ full-def)
    have n-s-bj: no-step cdclW-bj V
        by (metis ⟨cdclW-all-struct-inv V⟩ ⟨full cdclW-s' R V⟩ bj full-def
            n-step-cdclW-stgy-iff-no-step-cdclW-cl-cdclW-o)
    have n-s-cp: no-step cdclW-merge-cp V
    proof -
        { fix ss :: 'st
            obtain ssa :: 'st ⇒ 'st where
                ff1: ∀ s. ¬ cdclW-all-struct-inv s ∨ cdclW-s'-without-decide s (ssa s)
                ∨ no-step cdclW-merge-cp s
            using conflicting-true-no-step-s'-without-decide-no-step-cdclW-merge-cp by moura
            have (∀ p s sa. ¬ full p (s::'st) sa ∨ p** s sa ∧ no-step p sa) and
                (∀ p s sa. (¬ p** (s::'st) sa ∨ (∃ s. p sa s)) ∨ full p s sa)
            by (meson full-def)+
            then have ¬ cdclW-merge-cp V ss

```

```

    using ff1 by (metis (no-types) ⟨cdclW-all-struct-inv V⟩ ⟨full cdclW-s' R V⟩ cdclW-s'.simps
      cdclW-s'-without-decide.cases) }
  then show ?thesis
    by blast
qed
consider
  (fw-no-confl) cdclW-merge-stgy** R V and conflicting V = None
| (fw-confl) cdclW-merge-stgy** R V and conflicting V ≠ None and no-step cdclW-bj V
| (fw-dec-confl) S T U where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and
  decide S T and cdclW-merge-cp** T U and conflict U V
| (fw-dec-no-confl) S T where cdclW-merge-stgy** R S and no-step cdclW-merge-cp S and
  decide S T and cdclW-merge-cp** T V and conflicting V = None
| (cp-no-confl) cdclW-merge-cp** R V and conflicting V = None
| (cp-confl) U where cdclW-merge-cp** R U and conflict U V
using rtrancpl-cdclW-s'-no-step-cdclW-s'-without-decide-decomp-into-cdclW-merge[OF
  ⟨cdclW-s'** R V⟩ assms] by auto
then show ?fw
proof cases
  case fw-no-confl
  then show ?thesis using n-s unfolding full-def by blast
next
  case fw-confl
  then show ?thesis using n-s unfolding full-def by blast
next
  case fw-dec-confl
  have cdclW-merge-cp U V
  using n-s-bj by (metis cdclW-merge-cp.simps full-unfold fw-dec-confl(5))
  then have full1 cdclW-merge-cp T V
  unfolding full1-def by (metis fw-dec-confl(4) n-s-cp trancpl-unfold-end)
  then have cdclW-merge-stgy S V using ⟨decide S T⟩ ⟨no-step cdclW-merge-cp S⟩ by auto
  then show ?thesis using n-s ⟨cdclW-merge-stgy** R S⟩ unfolding full-def by auto
next
  case fw-dec-no-confl
  then have full cdclW-merge-cp T V
  using n-s-cp unfolding full-def by blast
  then have cdclW-merge-stgy S V using ⟨decide S T⟩ ⟨no-step cdclW-merge-cp S⟩ by auto
  then show ?thesis using n-s ⟨cdclW-merge-stgy** R S⟩ unfolding full-def by auto
next
  case cp-no-confl
  then have full cdclW-merge-cp R V
  by (simp add: full-def n-s-cp)
  then have R = V ∨ cdclW-merge-stgy++ R V
  using fw-s-cp unfolding full-unfold fw-s-cp
  by (metis (no-types) rtrancpl-unfold trancpl-unfold-end)
  then show ?thesis
  by (simp add: full-def n-s rtrancpl-unfold)
next
  case cp-confl
  have full cdclW-bj V V
  using n-s-bj unfolding full-def by blast
  then have full1 cdclW-merge-cp R V
  unfolding full1-def by (meson cdclW-merge-cp.conflict' cp-confl(1,2) n-s-cp
    rtrancpl-into-trancpl1)
  then show ?thesis using n-s unfolding full-def by auto
qed

```

```

next
  assume ?fw
  then have  $cdcl_W^{**} R V$  using  $rtrancp\_mono[of\ cdcl_W\_merge\_stgy\ cdcl_W^{**}]$ 
     $cdcl_W\_merge\_stgy\_rtrancp\_cdcl_W$  unfolding full-def by auto
  then have  $inv'$ :  $cdcl_W\_all\_struct\_inv V$  using  $inv\ rtrancp\_cdcl_W\_all\_struct\_inv\_inv$  by blast
  have  $cdcl_W\text{-}s'^{**} R V$ 
    using  $\langle ?fw \rangle$  by (simp add: full-def  $inv\ rtrancp\_cdcl_W\_merge\_stgy\_rtrancp\_cdcl_W\text{-}s'$ )
  moreover have no-step  $cdcl_W\text{-}s' V$ 
  proof cases
    assume conflicting  $V = None$ 
    then show ?thesis
      by (metis  $inv'$   $\langle full\ cdcl_W\_merge\_stgy\ R\ V \rangle$  full-def
        no-step- $cdcl_W\_merge\_stgy\_no\_step\_cdcl_W\text{-}s'$ )
  next
    assume  $confl\text{-}V$ : conflicting  $V \neq None$ 
    then have no-step  $cdcl_W\text{-}bj V$ 
    using  $rtrancp\_cdcl_W\_merge\_stgy\_no\_step\_cdcl_W\text{-}bj$  by (meson  $\langle full\ cdcl_W\_merge\_stgy\ R\ V \rangle$ 
       $assms(1)$  full-def)
    then show ?thesis using  $confl\text{-}V$  by (fastforce simp:  $cdcl_W\text{-}s'.simps$  full1-def  $cdcl_W\text{-}cp.simps$ 
       $dest!$ :  $trancpD$  elim:  $rulesE$ )
  qed
  ultimately show  $?s'$  unfolding full-def by blast
qed

lemma full- $cdcl_W\text{-}stgy\text{-}full\text{-}cdcl_W\text{-}merge$ :
  assumes
    conflicting  $R = None$  and
     $inv$ :  $cdcl_W\_all\_struct\_inv R$ 
  shows  $full\ cdcl_W\text{-}stgy\ R\ V \longleftrightarrow full\ cdcl_W\text{-}merge\_stgy\ R\ V$ 
  by (simp add:  $assms(1)$  full- $cdcl_W\text{-}s'\text{-}full\text{-}cdcl_W\text{-}merge\text{-}restart$  full- $cdcl_W\text{-}stgy\text{-}iff\text{-}full\text{-}cdcl_W\text{-}s'$ 
     $inv$ )

lemma full- $cdcl_W\text{-}merge\_stgy\text{-}final\text{-}state\text{-}conclusive'$ :
  fixes  $S' :: 'st$ 
  assumes full:  $full\ cdcl_W\text{-}merge\_stgy\ (init\text{-}state\ N)\ S'$ 
  and no-d:  $distinct\text{-}mset\text{-}mset\ (mset\text{-}class\ N)$ 
  shows ( $conflicting\ S' = Some\ \{\#\} \wedge unsatisfiable\ (set\text{-}mset\ (mset\text{-}class\ N))$ )
     $\vee (conflicting\ S' = None \wedge trail\ S' \models_{asm}\ mset\text{-}class\ N \wedge satisfiable\ (set\text{-}mset\ (mset\text{-}class\ N)))$ 
  proof -
    have  $cdcl_W\_all\_struct\_inv\ (init\text{-}state\ N)$ 
      using no-d unfolding  $cdcl_W\_all\_struct\_inv\text{-}def$  by auto
    moreover have conflicting  $(init\text{-}state\ N) = None$ 
      by auto
    ultimately show ?thesis
      using full full- $cdcl_W\text{-}stgy\text{-}final\text{-}state\text{-}conclusive\text{-}from\text{-}init\text{-}state$ 
        full- $cdcl_W\text{-}stgy\text{-}full\text{-}cdcl_W\text{-}merge\ no\text{-}d$  by presburger
  qed
end

end
theory CDCL-W-Incremental
imports CDCL-W-Termination
begin

```

## 23 Incremental SAT solving

**context** *conflict-driven-clause-learning<sub>W</sub>*  
**begin**

This invariant holds all the invariant related to the strategy. See the structural invariant in *cdcl<sub>W</sub>-all-struct-inv*

**definition** *cdcl<sub>W</sub>-stgy-invariant* **where**

*cdcl<sub>W</sub>-stgy-invariant*  $S \longleftrightarrow$   
 $\text{conflict-is-false-with-level } S$   
 $\wedge \text{no-clause-is-false } S$   
 $\wedge \text{no-smaller-confl } S$   
 $\wedge \text{no-clause-is-false } S$

**lemma** *cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-stgy-invariant*:

**assumes**

*cdcl<sub>W</sub>*: *cdcl<sub>W</sub>-stgy*  $S$  **and**  
*inv-s*: *cdcl<sub>W</sub>-stgy-invariant*  $S$  **and**  
*inv*: *cdcl<sub>W</sub>-all-struct-inv*  $S$

**shows**

*cdcl<sub>W</sub>-stgy-invariant*  $T$

**unfolding** *cdcl<sub>W</sub>-stgy-invariant-def* *cdcl<sub>W</sub>-all-struct-inv-def* **apply** (*intro conjI*)

**apply** (*rule cdcl<sub>W</sub>-stgy-ex-lit-of-max-level*[*of S*])

**using** *assms unfolding cdcl<sub>W</sub>-stgy-invariant-def cdcl<sub>W</sub>-all-struct-inv-def* **apply** *auto*[7]

**using** *cdcl<sub>W</sub> cdcl<sub>W</sub>-stgy-not-non-negated-init-clss* **apply** *simp*

**apply** (*rule cdcl<sub>W</sub>-stgy-no-smaller-confl-inv*)

**using** *assms unfolding cdcl<sub>W</sub>-stgy-invariant-def cdcl<sub>W</sub>-all-struct-inv-def* **apply** *auto*[4]

**using** *cdcl<sub>W</sub> cdcl<sub>W</sub>-stgy-not-non-negated-init-clss* **by** *auto*

**lemma** *rtrancpl-cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-stgy-invariant*:

**assumes**

*cdcl<sub>W</sub>*: *cdcl<sub>W</sub>-stgy\*\**  $S$   $T$  **and**  
*inv-s*: *cdcl<sub>W</sub>-stgy-invariant*  $S$  **and**  
*inv*: *cdcl<sub>W</sub>-all-struct-inv*  $S$

**shows**

*cdcl<sub>W</sub>-stgy-invariant*  $T$

**using** *assms* **apply** (*induction*)

**apply** *simp*

**using** *cdcl<sub>W</sub>-stgy-cdcl<sub>W</sub>-stgy-invariant rtrancpl-cdcl<sub>W</sub>-all-struct-inv-inv*

*rtrancpl-cdcl<sub>W</sub>-stgy-rtrancpl-cdcl<sub>W</sub>* **by** *blast*

**abbreviation** *decr-bt-lvl* **where**

*decr-bt-lvl*  $S \equiv \text{update-backtrack-lvl } (\text{backtrack-lvl } S - 1) S$

When we add a new clause, we reduce the trail until we get to the first literal included in  $C$ . Then we can mark the conflict.

**fun** *cut-trail-wrt-clause* **where**

*cut-trail-wrt-clause*  $C \ [] S = S \ |$

*cut-trail-wrt-clause*  $C$  (*Marked*  $L - \# M$ )  $S =$

(*if*  $-L \in \# C$  *then*  $S$

*else cut-trail-wrt-clause*  $C$   $M$  (*decr-bt-lvl* (*tl-trail*  $S$ )))  $|$

*cut-trail-wrt-clause*  $C$  (*Propagated*  $L - \# M$ )  $S =$

(*if*  $-L \in \# C$  *then*  $S$

*else cut-trail-wrt-clause*  $C$   $M$  (*tl-trail*  $S$ ))

**definition** *add-new-clause-and-update* :: 'ccls  $\Rightarrow$  'st  $\Rightarrow$  'st **where**  
*add-new-clause-and-update* C S =  
 (if trail S  $\models$ as CNot (mset-ccls C)  
 then update-conflicting (Some C) (add-init-cls (cls-of-ccls C)  
 (cut-trail-wrt-clause (mset-ccls C) (trail S) S))  
 else add-init-cls (cls-of-ccls C) S)

**thm** *cut-trail-wrt-clause.induct*

**lemma** *init-clss-cut-trail-wrt-clause[simp]*:  
*init-clss* (cut-trail-wrt-clause C M S) = *init-clss* S  
**by** (induction rule: *cut-trail-wrt-clause.induct*) *auto*

**lemma** *learned-clss-cut-trail-wrt-clause[simp]*:  
*learned-clss* (cut-trail-wrt-clause C M S) = *learned-clss* S  
**by** (induction rule: *cut-trail-wrt-clause.induct*) *auto*

**lemma** *conflicting-clss-cut-trail-wrt-clause[simp]*:  
*conflicting* (cut-trail-wrt-clause C M S) = *conflicting* S  
**by** (induction rule: *cut-trail-wrt-clause.induct*) *auto*

**lemma** *trail-cut-trail-wrt-clause*:

$\exists M. \text{ trail } S = M @ \text{ trail } (\text{cut-trail-wrt-clause } C (\text{trail } S) S)$

**proof** (induction trail S arbitrary: S rule: marked-lit-list-induct)

**case** nil

**then show** ?case **by** *simp*

**next**

**case** (marked L l M) **note** IH = *this*(1)[of *decr-bt-lvl* (tl-trail S)] **and** M = *this*(2)[*symmetric*]

**then show** ?case **using** *Cons-eq-appendI* **by** *fastforce+*

**next**

**case** (proped L l M) **note** IH = *this*(1)[of *tl-trail* S] **and** M = *this*(2)[*symmetric*]

**then show** ?case **using** *Cons-eq-appendI* **by** *fastforce+*

**qed**

**lemma** *n-dup-no-dup-trail-cut-trail-wrt-clause[simp]*:

**assumes** *n-d*: *no-dup* (trail T)

**shows** *no-dup* (trail (cut-trail-wrt-clause C (trail T) T))

**proof** –

**obtain** M **where**

M: trail T = M @ trail (cut-trail-wrt-clause C (trail T) T)

**using** *trail-cut-trail-wrt-clause*[of T C] **by** *auto*

**show** ?thesis

**using** *n-d* **unfolding** *arg-cong*[OF M, of *no-dup*] **by** *auto*

**qed**

**lemma** *cut-trail-wrt-clause-backtrack-lvl-length-marked*:

**assumes**

*backtrack-lvl* T = *length* (*get-all-levels-of-marked* (trail T))

**shows**

*backtrack-lvl* (cut-trail-wrt-clause C (trail T) T) =

*length* (*get-all-levels-of-marked* (trail (cut-trail-wrt-clause C (trail T) T))))

**using** *assms*

**proof** (induction trail T arbitrary: T rule: marked-lit-list-induct)

**case** nil

**then show** ?case **by** *simp*

**next**

```

case (marked L l M) note IH = this(1)[of decr-bt-lvl (tl-trail T)] and M = this(2)[symmetric]
  and bt = this(3)
then show ?case by auto
next
case (proped L l M) note IH = this(1)[of tl-trail T] and M = this(2)[symmetric] and bt = this(3)
then show ?case by auto
qed

```

**lemma** cut-trail-wrt-clause-get-all-levels-of-marked:

```

assumes get-all-levels-of-marked (trail T) = rev [Suc 0..  

  Suc (length (get-all-levels-of-marked (trail T)))]
shows
  get-all-levels-of-marked (trail ((cut-trail-wrt-clause C (trail T) T))) = rev [Suc 0..  

  Suc (length (get-all-levels-of-marked (trail ((cut-trail-wrt-clause C (trail T) T)))))]
using assms
proof (induction trail T arbitrary:T rule: marked-lit-list-induct)
  case nil
  then show ?case by simp
next
  case (marked L l M) note IH = this(1)[of decr-bt-lvl (tl-trail T)] and M = this(2)[symmetric]
    and bt = this(3)
  then show ?case by (cases count C L = 0) auto
next
  case (proped L l M) note IH = this(1)[of tl-trail T] and M = this(2)[symmetric] and bt = this(3)
  then show ?case by (cases count C L = 0) auto
qed

```

**lemma** cut-trail-wrt-clause-CNot-trail:

```

assumes trail T  $\models_{as}$  CNot C
shows
  (trail ((cut-trail-wrt-clause C (trail T) T)))  $\models_{as}$  CNot C
using assms
proof (induction trail T arbitrary:T rule: marked-lit-list-induct)
  case nil
  then show ?case by simp
next
  case (marked L l M) note IH = this(1)[of decr-bt-lvl (tl-trail T)] and M = this(2)[symmetric]
    and bt = this(3)
  show ?case
  proof (cases count C (-L) = 0)
    case False
    then show ?thesis
      using IH M bt by (auto simp: true-annots-true-cl)
  next
    case True
    obtain mma :: 'v literal multiset where
      f6: (mma  $\in$   $\{\{\#- l\# \mid l. l \in \# C\} \longrightarrow M \models_a mma\} \longrightarrow M \models_{as} \{\{\#- l\# \mid l. l \in \# C\}$ )
      using true-annots-def by blast
    have mma  $\in$   $\{\{\#- l\# \mid l. l \in \# C\} \longrightarrow trail T \models_a mma\}$ 
      using CNot-def M bt by (metis (no-types) true-annots-def)
    then have M  $\models_{as} \{\{\#- l\# \mid l. l \in \# C\}$ 
      using f6 True M bt by (force simp: count-eq-zero-iff)
    then show ?thesis
      using IH true-annots-true-cl M by (auto simp: CNot-def)
  qed

```

```

next
case (proped L l M) note IH = this(1)[of tl-trail T] and M = this(2)[symmetric] and bt = this(3)
show ?case
proof (cases count C (-L) = 0)
  case False
  then show ?thesis
    using IH M bt by (auto simp: true-annots-true-cls)
next
case True
obtain mma :: 'v literal multiset where
  f6: (mma ∈ {{#- l#} | l. l ∈# C} → M ⊨a mma) → M ⊨as {{#- l#} | l. l ∈# C}
  using true-annots-def by blast
have mma ∈ {{#- l#} | l. l ∈# C} → trail T ⊨a mma
  using CNot-def M bt by (metis (no-types) true-annots-def)
then have M ⊨as {{#- l#} | l. l ∈# C}
  using f6 True M bt by (force simp: count-eq-zero-iff)
then show ?thesis
  using IH true-annots-true-cls M by (auto simp: CNot-def)
qed
qed

```

**lemma** *cut-trail-wrt-clause-hd-trail-in-or-empty-trail*:

$$((\forall L \in \#C. -L \notin \text{ lits-of-}l(\text{trail } T)) \wedge \text{trail}(\text{cut-trail-wrt-clause } C(\text{trail } T) T) = []) \\ \vee (-\text{lit-of}(\text{hd}(\text{trail}(\text{cut-trail-wrt-clause } C(\text{trail } T) T))) \in \#C \\ \wedge \text{length}(\text{trail}(\text{cut-trail-wrt-clause } C(\text{trail } T) T)) \geq 1)$$

using *assms*

**proof** (*induction trail T arbitrary: T rule: marked-lit-list-induct*)

case *nil*

then show ?case by *simp*

next

case (marked L l M) note IH = this(1)[of decr-bt-lvl (tl-trail T)] and M = this(2)[symmetric]

then show ?case by *simp force*

next

case (proped L l M) note IH = this(1)[of tl-trail T] and M = this(2)[symmetric]

then show ?case by *simp force*

qed

We can fully run *cdcl<sub>W</sub>*-s or add a clause. Remark that we use *cdcl<sub>W</sub>*-s to avoid an explicit *skip*, *resolve*, and *backtrack* normalisation to get rid of the conflict *C* if possible.

**inductive** *incremental-cdcl<sub>W</sub>* :: 'st ⇒ 'st ⇒ bool **for** *S* **where**

*add-conflict*:

$$\text{trail } S \models_{\text{asm}} \text{init-clss } S \implies \text{distinct-mset}(\text{mset-ccls } C) \implies \text{conflicting } S = \text{None} \implies \\ \text{trail } S \models_{\text{as}} \text{CNot}(\text{mset-ccls } C) \implies \\ \text{full } \text{cdcl}_W\text{-stgy} \\ (\text{update-conflicting}(\text{Some } C) \\ (\text{add-init-cl}(\text{cls-of-ccls } C)(\text{cut-trail-wrt-clause}(\text{mset-ccls } C)(\text{trail } S) S))) T \implies \\ \text{incremental-cdcl}_W S T \mid$$

*add-no-conflict*:

$$\text{trail } S \models_{\text{asm}} \text{init-clss } S \implies \text{distinct-mset}(\text{mset-ccls } C) \implies \text{conflicting } S = \text{None} \implies \\ \neg \text{trail } S \models_{\text{as}} \text{CNot}(\text{mset-ccls } C) \implies \\ \text{full } \text{cdcl}_W\text{-stgy}(\text{add-init-cl}(\text{cls-of-ccls } C) S) T \implies \\ \text{incremental-cdcl}_W S T$$

**lemma** *cdcl<sub>W</sub>-all-struct-inv-add-new-clause-and-update-cdcl<sub>W</sub>-all-struct-inv*:

**assumes**

```

  inv-T: cdclW-all-struct-inv T and
  tr-T-N[simp]: trail T  $\models_{asm}$  N and
  tr-C[simp]: trail T  $\models_{as}$  CNot (mset-ccls C) and
  [simp]: distinct-mset (mset-ccls C)
shows cdclW-all-struct-inv (add-new-clause-and-update C T) (is cdclW-all-struct-inv ?T')
proof -
  let ?T = update-conflicting (Some C)
  (add-init-cls (cls-of-ccls C) (cut-trail-wrt-clause (mset-ccls C) (trail T) T))
obtain M where
  M: trail T = M @ trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T)
  using trail-cut-trail-wrt-clause[of T mset-ccls C] by blast
have H[dest]:  $\bigwedge x. x \in lits\text{-of-}l \text{ (trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T))} \implies$ 
   $x \in lits\text{-of-}l \text{ (trail T)}$ 
  using inv-T arg-cong[OF M, of lits-of-l] by auto
have H'[dest]:  $\bigwedge x. x \in set \text{ (trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T))} \implies$ 
   $x \in set \text{ (trail T)}$ 
  using inv-T arg-cong[OF M, of set] by auto

have H-proped:  $\bigwedge x. x \in set \text{ (get-all-mark-of-propagated (trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T))} \implies$ 
   $x \in set \text{ (get-all-mark-of-propagated (trail T))}$ 
  using inv-T arg-cong[OF M, of get-all-mark-of-propagated] by auto

have [simp]: no-strange-atm ?T
  using inv-T unfolding cdclW-all-struct-inv-def no-strange-atm-def add-new-clause-and-update-def
  cdclW-M-level-inv-def by (auto 20 1)
have M-leve: cdclW-M-level-inv T
  using inv-T unfolding cdclW-all-struct-inv-def by blast
then have no-dup (M @ trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T))
  unfolding cdclW-M-level-inv-def unfolding M[symmetric] by auto
then have [simp]: no-dup (trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T))
  by auto

have consistent-interp (lits-of-l (M @ trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T)))
  using M-leve unfolding cdclW-M-level-inv-def unfolding M[symmetric] by auto
then have [simp]: consistent-interp (lits-of-l (trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T)))
  unfolding consistent-interp-def by auto

have [simp]: cdclW-M-level-inv ?T
  using M-leve cut-trail-wrt-clause-get-all-levels-of-marked[of T mset-ccls C]
  unfolding cdclW-M-level-inv-def by (auto dest: H H')
  simp: M-leve cdclW-M-level-inv-def cut-trail-wrt-clause-backtrack-lvl-length-marked

have [simp]:  $\bigwedge s. s \in \# \text{ learned-clss } T \implies \neg \text{tautology } s$ 
  using inv-T unfolding cdclW-all-struct-inv-def by auto

have distinct-cdclW-state T
  using inv-T unfolding cdclW-all-struct-inv-def by auto
then have [simp]: distinct-cdclW-state ?T
  unfolding distinct-cdclW-state-def by auto

have cdclW-conflicting T
  using inv-T unfolding cdclW-all-struct-inv-def by auto
have trail ?T  $\models_{as}$  CNot (mset-ccls C)
  by (simp add: cut-trail-wrt-clause-CNot-trail)

```



**then have**  $[simp]: cdcl_W\text{-conflicting } ?T$   
**unfolding**  $cdcl_W\text{-conflicting-def}$  **apply**  $simp$   
**by**  $(metis M \langle cdcl_W\text{-conflicting } T \rangle \text{ append-assoc } cdcl_W\text{-conflicting-decomp}(2))$   
**have**  
 $decomp\text{-}T: all\text{-decomposition-implies-}m \ (init\text{-}clss \ T) \ (get\text{-all-marked-decomposition} \ (trail \ T))$   
**using**  $inv\text{-}T$  **unfolding**  $cdcl_W\text{-all-struct-inv-def}$  **by**  $auto$   
**have**  $all\text{-decomposition-implies-}m \ (init\text{-}clss \ ?T)$   
 $(get\text{-all-marked-decomposition} \ (trail \ ?T))$   
**unfolding**  $all\text{-decomposition-implies-def}$   
**proof**  $clarify$   
**fix**  $a \ b$   
**assume**  $(a, b) \in set \ (get\text{-all-marked-decomposition} \ (trail \ ?T))$   
**from**  $in\text{-}get\text{-all-marked-decomposition-in-get\text{-all-marked-decomposition-}prepend[OF \ this, \ of \ M]$   
**obtain**  $b'$  **where**  
 $(a, b' @ b) \in set \ (get\text{-all-marked-decomposition} \ (trail \ T))$   
**using**  $M$  **by**  $auto$   
**then have**  $unmark\text{-}l \ a \cup set\text{-}mset \ (init\text{-}clss \ T) \models_{ps} unmark\text{-}l \ (b' @ b)$   
**using**  $decomp\text{-}T$  **unfolding**  $all\text{-decomposition-implies-def}$  **by**  $fastforce$   
**then have**  $unmark\text{-}l \ a \cup set\text{-}mset \ (init\text{-}clss \ ?T) \models_{ps} unmark\text{-}l \ (b @ b')$   
**by**  $(simp \ add: \ Un\text{-}commute)$   
**then show**  $unmark\text{-}l \ a \cup set\text{-}mset \ (init\text{-}clss \ ?T) \models_{ps} unmark\text{-}l \ b$   
**by**  $(auto \ simp: \ image\text{-}Un)$   
**qed**

**have**  $[simp]: cdcl_W\text{-learned-clause } ?T$   
**using**  $inv\text{-}T$  **unfolding**  $cdcl_W\text{-all-struct-inv-def}$   $cdcl_W\text{-learned-clause-def}$   
**by**  $(auto \ dest!: \ H\text{-proped } simp: \ raw\text{-clauses-def})$   
**show**  $?thesis$   
**using**  $\langle all\text{-decomposition-implies-}m \ (init\text{-}clss \ ?T)$   
 $(get\text{-all-marked-decomposition} \ (trail \ ?T)) \rangle$   
**unfolding**  $cdcl_W\text{-all-struct-inv-def}$  **by**  $(auto \ simp: \ add\text{-new-clause-and-update-def})$   
**qed**

**lemma**  $cdcl_W\text{-all-struct-inv-add-new-clause-and-update-cdcl_W-stgy-inv}$ :

**assumes**  
 $inv\text{-}s: cdcl_W\text{-stgy-invariant } T$  **and**  
 $inv: cdcl_W\text{-all-struct-inv } T$  **and**  
 $tr\text{-}T\text{-}N[simp]: trail \ T \models_{asm} N$  **and**  
 $tr\text{-}C[simp]: trail \ T \models_{as} CNot \ (mset\text{-}ccls \ C)$  **and**  
 $[simp]: distinct\text{-}mset \ (mset\text{-}ccls \ C)$

**shows**  $cdcl_W\text{-stgy-invariant} \ (add\text{-new-clause-and-update} \ C \ T)$   
 $(is \ cdcl_W\text{-stgy-invariant} \ ?T')$

**proof** –

**have**  $cdcl_W\text{-all-struct-inv } ?T'$   
**using**  $cdcl_W\text{-all-struct-inv-add-new-clause-and-update-cdcl_W-all-struct-inv assms}$  **by**  $blast$   
**then have**  
 $no\text{-dup-cut-}T[simp]: no\text{-dup} \ (trail \ (cut\text{-trail-wrt-clause} \ (mset\text{-}ccls \ C) \ (trail \ T) \ T))$  **and**  
 $n\text{-d}[simp]: no\text{-dup} \ (trail \ T)$   
**using**  $cdcl_W\text{-M-level-inv-decomp}(2)$   $cdcl_W\text{-all-struct-inv-def}$   $inv$   
 $n\text{-dup-no-dup-trail-cut-trail-wrt-clause}$  **by**  $blast+$   
**then have**  $trail \ (add\text{-new-clause-and-update} \ C \ T) \models_{as} CNot \ (mset\text{-}ccls \ C)$   
**by**  $(simp \ add: \ add\text{-new-clause-and-update-def} \ cut\text{-trail-wrt-clause-}CNot\text{-trail}$   
 $cdcl_W\text{-M-level-inv-def} \ cdcl_W\text{-all-struct-inv-def})$   
**obtain**  $MT$  **where**

$MT$ : trail  $T = MT @ \text{trail} (\text{cut-trail-wrt-clause} (\text{mset-ccls } C) (\text{trail } T) T)$   
**using** trail-cut-trail-wrt-clause **by** blast  
**consider**  
 (false)  $\forall L \in \# \text{mset-ccls } C. - L \notin \text{lits-of-l} (\text{trail } T)$  **and**  
 trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ ) = []  
 | (not-false)  
 – lit-of (hd (trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ )))  $\in \# (\text{mset-ccls } C)$  **and**  
 $1 \leq \text{length} (\text{trail} (\text{cut-trail-wrt-clause} (\text{mset-ccls } C) (\text{trail } T) T))$   
**using** cut-trail-wrt-clause-hd-trail-in-or-empty-trail[of mset-ccls  $C$   $T$ ] **by** auto  
**then show** ?thesis  
**proof** cases  
**case** false **note**  $C = \text{this}(1)$  **and** empty-tr = this(2)  
**then have** [simp]: mset-ccls  $C = \{\#\}$   
**by** (simp add: in-CNot-implies-uminus(2) multiset-eqI)  
**show** ?thesis  
**using** empty-tr **unfolding** cdcl<sub>W</sub>-stgy-invariant-def no-smaller-conflict-def  
 cdcl<sub>W</sub>-all-struct-inv-def **by** (auto simp: add-new-clause-and-update-def)  
**next**  
**case** not-false **note**  $C = \text{this}(1)$  **and**  $l = \text{this}(2)$   
**let** ? $L = - \text{lit-of} (\text{hd} (\text{trail} (\text{cut-trail-wrt-clause} (\text{mset-ccls } C) (\text{trail } T) T)))$   
**have** get-all-levels-of-marked (trail (add-new-clause-and-update  $C$   $T$ )) =  
 rev [1.. $1 + \text{length} (\text{get-all-levels-of-marked} (\text{trail} (\text{add-new-clause-and-update } C T)))$ ]  
**using** <cdcl<sub>W</sub>-all-struct-inv ? $T$ > **unfolding** cdcl<sub>W</sub>-all-struct-inv-def cdcl<sub>W</sub>-M-level-inv-def  
**by** blast  
**moreover**  
**have** backtrack-lvl (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ ) =  
 length (get-all-levels-of-marked (trail (add-new-clause-and-update  $C$   $T$ )))  
**using** <cdcl<sub>W</sub>-all-struct-inv ? $T$ > **unfolding** cdcl<sub>W</sub>-all-struct-inv-def cdcl<sub>W</sub>-M-level-inv-def  
**by** (auto simp: add-new-clause-and-update-def)  
**moreover**  
**have** no-dup (trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ ))  
**using** <cdcl<sub>W</sub>-all-struct-inv ? $T$ > **unfolding** cdcl<sub>W</sub>-all-struct-inv-def cdcl<sub>W</sub>-M-level-inv-def  
**by** (auto simp: add-new-clause-and-update-def)  
**then have** atm-of ? $L \notin \text{atm-of } \text{'lits-of-l'}$   
 (tl (trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ )))  
**by** (cases trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ ))  
 (auto simp: lits-of-def)  
  
**ultimately have**  $L$ : get-level (trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ )) (– ? $L$ )  
 = length (get-all-levels-of-marked (trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ )))  
**using** get-level-get-rev-level-get-all-levels-of-marked[OF  
 <atm-of ? $L \notin \text{atm-of } \text{'lits-of-l'}$  (tl (trail (cut-trail-wrt-clause (mset-ccls  $C$ )  
 (trail  $T$ )  $T$ )))>,  
 of [hd (trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ ))]]  
  
**apply** (cases trail (add-init-cls (cls-of-ccls  $C$ )  
 (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ ));  
 cases hd (trail (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ )))  
**using**  $l$  **by** (auto split: if-split-asm  
 simp: rev-swap[symmetric] add-new-clause-and-update-def)  
  
**have**  $L'$ : length (get-all-levels-of-marked (trail (cut-trail-wrt-clause (mset-ccls  $C$ )  
 (trail  $T$ )  $T$ )))  
 = backtrack-lvl (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $T$ )  $T$ )  
**using** <cdcl<sub>W</sub>-all-struct-inv ? $T$ > **unfolding** cdcl<sub>W</sub>-all-struct-inv-def cdcl<sub>W</sub>-M-level-inv-def

```

by (auto simp:add-new-clause-and-update-def)

have [simp]: no-smaller-confl (update-conflicting (Some C)
  (add-init-cls (cls-of-ccls C) (cut-trail-wrt-clause (mset-ccls C) (trail T) T)))
  unfolding no-smaller-confl-def
proof (clarify, goal-cases)
  case (1 M K i M' D)
  then consider
    (DC) D = mset-ccls C
    | (D-T) D ∈# clauses T
  by (auto simp: raw-clauses-def split: if-split-asm)
  then show False
  proof cases
    case D-T
    have no-smaller-confl T
      using inv-s unfolding cdclW-stgy-invariant-def by auto
    have (MT @ M') @ Marked K i # M = trail T
      using MT 1(1) by auto
    thus False using D-T ⟨no-smaller-confl T⟩ 1(3) unfolding no-smaller-confl-def by blast
  next
  case DC note -[simp] = this
  then have atm-of (−?L) ∈ atm-of ‘ (lits-of-l M)
    using 1(3) C in-CNot-implies-uminus(2) by blast
  moreover
    have lit-of (hd (M' @ Marked K i # [])) = −?L
      using l 1(1)[symmetric] inv
    by (cases trail (add-init-cls (cls-of-ccls C)
      (cut-trail-wrt-clause (mset-ccls C) (trail T) T)))
      (auto dest!: arg-cong[of - # - hd] simp: hd-append cdclW-all-struct-inv-def
        cdclW-M-level-inv-def)
    from arg-cong[OF this, of atm-of]
    have atm-of (−?L) ∈ atm-of ‘ (lits-of-l (M' @ Marked K i # []))
      by (cases (M' @ Marked K i # [])) auto
    moreover have no-dup (trail (cut-trail-wrt-clause (mset-ccls C) (trail T) T))
      using ⟨cdclW-all-struct-inv ?T'⟩ unfolding cdclW-all-struct-inv-def
        cdclW-M-level-inv-def by (auto simp: add-new-clause-and-update-def)
    ultimately show False
      unfolding 1(1)[symmetric, simplified] by (auto simp: lits-of-def)
  qed
qed
show ?thesis using L L' C
  unfolding cdclW-stgy-invariant-def
  unfolding cdclW-all-struct-inv-def by (auto simp: add-new-clause-and-update-def)
qed
qed

lemma full-cdclW-stgy-inv-normal-form:
  assumes
    full: full cdclW-stgy S T and
    inv-s: cdclW-stgy-invariant S and
    inv: cdclW-all-struct-inv S
  shows conflicting T = Some {#} ∧ unsatisfiable (set-mset (init-cls S))
    ∨ conflicting T = None ∧ trail T ⊨asm init-cls S ∧ satisfiable (set-mset (init-cls S))
proof −
  have no-step cdclW-stgy T

```

```

    using full unfolding full-def by blast
  moreover have  $cdcl_W$ -all-struct-inv  $T$  and  $inv$ -s:  $cdcl_W$ -stgy-invariant  $T$ 
  apply (metis rtrancpl-cdclW-stgy-rtrancpl-cdclW full full-def inv
    rtrancpl-cdclW-all-struct-inv-inv)
  by (metis full full-def inv inv-s rtrancpl-cdclW-stgy-cdclW-stgy-invariant)
  ultimately have conflicting  $T = \text{Some } \{\#\} \wedge \text{unsatisfiable } (\text{set-mset } (\text{init-clss } T))$ 
   $\vee$  conflicting  $T = \text{None} \wedge \text{trail } T \models_{asm} \text{init-clss } T$ 
  using  $cdcl_W$ -stgy-final-state-conclusive[of  $T$ ] full
  unfolding  $cdcl_W$ -all-struct-inv-def  $cdcl_W$ -stgy-invariant-def full-def by fast
  moreover have consistent-interp (lits-of-l (trail  $T$ ))
  using  $\langle cdcl_W$ -all-struct-inv  $T \rangle$  unfolding  $cdcl_W$ -all-struct-inv-def  $cdcl_W$ -M-level-inv-def
  by auto
  moreover have  $\text{init-clss } S = \text{init-clss } T$ 
  using inv unfolding  $cdcl_W$ -all-struct-inv-def
  by (metis rtrancpl-cdclW-stgy-no-more-init-clss full full-def)
  ultimately show ?thesis
  by (metis satisfiable-carac' true-annot-def true-annots-def true-clss-def)
qed

```

**lemma** *incremental-cdcl<sub>W</sub>-inv*:

```

  assumes
    inc: incremental-cdclW  $S$   $T$  and
    inv:  $cdcl_W$ -all-struct-inv  $S$  and
    s-inv:  $cdcl_W$ -stgy-invariant  $S$ 
  shows
     $cdcl_W$ -all-struct-inv  $T$  and
     $cdcl_W$ -stgy-invariant  $T$ 
  using inc
proof (induction)
  case (add-confl  $C$   $T$ )
  let ? $T$  = (update-conflicting (Some  $C$ ) (add-init-cls (cls-of-ccls  $C$ )
    (cut-trail-wrt-clause (mset-ccls  $C$ ) (trail  $S$ )  $S$ )))
  have  $cdcl_W$ -all-struct-inv ? $T$  and  $inv$ -s- $T$ :  $cdcl_W$ -stgy-invariant ? $T$ 
  using add-confl.hyps(1,2,4) add-new-clause-and-update-def
     $cdcl_W$ -all-struct-inv-add-new-clause-and-update- $cdcl_W$ -all-struct-inv inv apply auto[1]
  using add-confl.hyps(1,2,4) add-new-clause-and-update-def
     $cdcl_W$ -all-struct-inv-add-new-clause-and-update- $cdcl_W$ -stgy-inv inv s-inv by auto
  case 1 show ?case
  by (metis add-confl.hyps(1,2,4,5) add-new-clause-and-update-def
     $cdcl_W$ -all-struct-inv-add-new-clause-and-update- $cdcl_W$ -all-struct-inv
    rtrancpl-cdclW-all-struct-inv-inv rtrancpl-cdclW-stgy-rtrancpl-cdclW full-def inv)

  case 2 show ?case
  by (metis inv-s- $T$  add-confl.hyps(1,2,4,5) add-new-clause-and-update-def
     $cdcl_W$ -all-struct-inv-add-new-clause-and-update- $cdcl_W$ -all-struct-inv full-def inv
    rtrancpl-cdclW-stgy-cdclW-stgy-invariant)
next
  case (add-no-confl  $C$   $T$ )
  case 1
  have  $cdcl_W$ -all-struct-inv (add-init-cls (cls-of-ccls  $C$ )  $S$ )
  using inv  $\langle \text{distinct-mset } (\text{mset-ccls } C) \rangle$  unfolding  $cdcl_W$ -all-struct-inv-def no-strange-atm-def
     $cdcl_W$ -M-level-inv-def distinct- $cdcl_W$ -state-def  $cdcl_W$ -conflicting-def  $cdcl_W$ -learned-clause-def
  by (auto 9 1 simp: all-decomposition-implies-insert-single raw-clauses-def)

  then show ?case

```

```

    using add-no-confl(5) unfolding full-def by (auto intro: rtracp-cdclW-stgy-cdclW-all-struct-inv)
case 2
have nc:  $\forall M. (\exists K i M'. \text{trail } S = M' @ \text{Marked } K i \# M) \longrightarrow \neg M \models_{\text{as}} \text{CNot } (\text{mset-ccls } C)$ 
    using  $\langle \neg \text{trail } S \models_{\text{as}} \text{CNot } (\text{mset-ccls } C) \rangle$ 
    by (auto simp: true-annots-true-clc-def-iff-negation-in-model)

have cdclW-stgy-invariant (add-init-clc (clc-of-ccls C) S)
    using s-inv  $\langle \neg \text{trail } S \models_{\text{as}} \text{CNot } (\text{mset-ccls } C) \rangle$  inv unfolding cdclW-stgy-invariant-def
    no-smaller-confl-def eq-commute[of - trail -] cdclW-M-level-inv-def cdclW-all-struct-inv-def
    by (auto simp: raw-clauses-def nc)
then show ?case
    by (metis  $\langle \text{cdcl}_W\text{-all-struct-inv } (\text{add-init-clc } (\text{clc-of-ccls } C) S) \rangle$  add-no-confl.hyps(5) full-def
        rtracp-cdclW-stgy-cdclW-stgy-invariant)
qed

```

**lemma** *rtracp-incremental-cdcl<sub>W</sub>-inv:*

```

assumes
  inc: incremental-cdclW** S T and
  inv: cdclW-all-struct-inv S and
  s-inv: cdclW-stgy-invariant S
shows
  cdclW-all-struct-inv T and
  cdclW-stgy-invariant T
  using inc apply induction
  using inv apply simp
  using s-inv apply simp
using incremental-cdclW-inv by blast+

```

**lemma** *incremental-conclusive-state:*

```

assumes
  inc: incremental-cdclW S T and
  inv: cdclW-all-struct-inv S and
  s-inv: cdclW-stgy-invariant S
shows conflicting T = Some {#}  $\wedge$  unsatisfiable (set-mset (init-clss T))
   $\vee$  conflicting T = None  $\wedge$  trail T  $\models_{\text{asm}} \text{init-clss } T \wedge$  satisfiable (set-mset (init-clss T))
  using inc
proof induction
print-cases
case (add-confl C T) note tr = this(1) and dist = this(2) and conf = this(3) and C = this(4) and
full = this(5)

```

```

have full cdclW-stgy T T
  using full unfolding full-def by auto
then show ?case
  using full C conf dist tr
  by (metis full-cdclW-stgy-inv-normal-form incremental-cdclW.simps incremental-cdclW-inv(1)
      incremental-cdclW-inv(2) inv s-inv)

```

**next**

```

case (add-no-confl C T) note tr = this(1) and dist = this(2) and conf = this(3) and C = this(4)
and full = this(5)

have full cdclW-stgy T T
  using full unfolding full-def by auto
then show ?case
  by (meson C conf dist full full-cdclW-stgy-inv-normal-form incremental-cdclW.add-no-confl)

```

```

    incremental-cdclW-inv(1) incremental-cdclW-inv(2) inv s-inv tr)
qed

lemma tranclp-incremental-correct:
  assumes
    inc: incremental-cdclW++ S T and
    inv: cdclW-all-struct-inv S and
    s-inv: cdclW-stgy-invariant S
  shows conflicting T = Some {#}  $\wedge$  unsatisfiable (set-mset (init-clss T))
     $\vee$  conflicting T = None  $\wedge$  trail T  $\models_{asm}$  init-clss T  $\wedge$  satisfiable (set-mset (init-clss T))
  using inc apply induction
  using assms incremental-conclusive-state apply blast
  by (meson incremental-conclusive-state inv rtranclp-incremental-cdclW-inv s-inv
      tranclp-into-rtranclp)

end

end

```

## 24 2-Watched-Literal

```

theory CDCL-Two-Watched-Literals
imports CDCL-WNOT
begin

```

We will directly on the two-watched literals datastructure with lists: it could be also seen as a state over some abstract clause representation we would later refine as lists. However, as we need a way to select element from a clause, working on lists is better.

### 24.1 Datastructure and Access Functions

Only the 2-watched literals have to be verified here: the backtrack level and the trail that appear in the state are not related to the 2-watched algorithm.

```

datatype 'v twl-clause =
  TWL-Clause (watched: 'v literal list) (unwatched: 'v literal list)

datatype 'v twl-state =
  TWL-State (raw-trail: ('v, nat, 'v twl-clause) marked-lit list)
    (raw-init-clss: 'v twl-clause list)
    (raw-learned-clss: 'v twl-clause list) (backtrack-lvl: nat)
    (raw-conflicting: 'v literal list option)

fun mmset-of-mlit' :: ('v, nat, 'v twl-clause) marked-lit  $\Rightarrow$  ('v, nat, 'v clause) marked-lit
  where
    mmset-of-mlit' (Propagated L C) = Propagated L (mset (watched C @ unwatched C)) |
    mmset-of-mlit' (Marked L i) = Marked L i

lemma lit-of-mmset-of-mlit'[simp]: lit-of (mmset-of-mlit' x) = lit-of x
  by (cases x) auto

lemma lits-of-mmset-of-mlit'[simp]: lits-of (mmset-of-mlit'  $\cdot$  S) = lits-of S
  by (auto simp: lits-of-def image-image)

abbreviation trail where

```

$trail\ S \equiv map\ mset-of-mlit'\ (raw-trail\ S)$

**abbreviation** *clauses-of-l* **where**

$clauses-of-l \equiv \lambda L. mset\ (map\ mset\ L)$

**definition** *raw-clause*  $:: 'v\ twl-clause \Rightarrow 'v\ literal\ list$  **where**

$raw-clause\ C \equiv watched\ C\ @\ unwatched\ C$

**abbreviation** *raw-clss*  $:: 'v\ twl-state \Rightarrow 'v\ clauses$  **where**

$raw-clss\ S \equiv clauses-of-l\ (map\ raw-clause\ (raw-init-clss\ S\ @\ raw-learned-clss\ S))$

**interpretation** *raw-cl*

$\lambda C. mset\ (raw-clause\ C)$

$\lambda L\ C. TWL-Clause\ (watched\ C)\ (L\ \# \ unwatched\ C)$

$\lambda L\ C. TWL-Clause\ []\ (remove1\ L\ (raw-clause\ C))$

**apply** (*unfold-locales*)

**by** (*auto simp:hd-map comp-def map-tl ac-simps*

*mset-map-mset-remove1-cond ex-mset raw-clause-def*

*simp del:* )

**lemma** XXX:

$mset\ (map\ (\lambda x. mset\ (unwatched\ x) + mset\ (watched\ x))$

$(remove1-cond\ (\lambda D. mset\ (raw-clause\ D) = mset\ (raw-clause\ a))\ Cs)) =$

$remove1-mset\ (mset\ (raw-clause\ a))\ (mset\ (map\ (\lambda x. mset\ (raw-clause\ x))\ Cs))$

**apply** (*induction Cs*)

**apply** *simp*

**by** (*auto simp: ac-simps remove1-mset-single-add raw-clause-def*)

**interpretation** *raw-clss*

$\lambda C. mset\ (raw-clause\ C)$

$\lambda L\ C. TWL-Clause\ (watched\ C)\ (L\ \# \ unwatched\ C)$

$\lambda L\ C. TWL-Clause\ []\ (remove1\ L\ (raw-clause\ C))$

$\lambda C. clauses-of-l\ (map\ raw-clause\ C)\ op\ @$

$\lambda L\ C. L \in set\ C\ op\ \# \ \lambda C. remove1-cond\ (\lambda D. mset\ (raw-clause\ D) = mset\ (raw-clause\ C))$

**apply** (*unfold-locales*)

**using** XXX **by** (*auto simp:hd-map comp-def map-tl ac-simps raw-clause-def*

*union-mset-list mset-map-mset-remove1-cond ex-mset*

*simp del:* )

**lemma** *ex-mset-unwatched-watched:*

$\exists a. mset\ (unwatched\ a) + mset\ (watched\ a) = E$

**proof** –

**obtain** *e* **where**  $mset\ e = E$

**using** *ex-mset* **by** *blast*

**then have**  $mset\ (unwatched\ (TWL-Clause\ []\ e)) + mset\ (watched\ (TWL-Clause\ []\ e)) = E$

**by** *auto*

**then show** *?thesis* **by** *fast*

**qed**

**thm** *CDCL-Two-Watched-Literals.raw-clss-axioms*

**interpretation** *twl: state<sub>W</sub>-ops*

$\lambda C. mset\ (raw-clause\ C)$

$\lambda L\ C. TWL-Clause\ (watched\ C)\ (L\ \# \ unwatched\ C)$

$\lambda L C. \text{TWL-Clause } [] (\text{remove1 } L (\text{raw-clause } C))$   
 $\lambda C. \text{clauses-of-l } (\text{map raw-clause } C) \text{ op } @$   
 $\lambda L C. L \in \text{set } C \text{ op } \# \lambda C. \text{remove1-cond } (\lambda D. \text{mset } (\text{raw-clause } D) = \text{mset } (\text{raw-clause } C))$

$\text{mset } \lambda xs \text{ ys. case-prod append } (\text{fold } (\lambda x (ys, zs). (\text{remove1 } x \text{ ys}, x \# zs)) \text{ xs } (ys, []))$   
 $\text{op } \# \text{remove1}$

$\text{raw-clause } \lambda C. \text{TWL-Clause } [] C$   
 $\text{trail } \lambda S. \text{hd } (\text{raw-trail } S)$   
 $\text{raw-init-clss raw-learned-clss backtrack-lvl raw-conflicting}$

**apply**  $\text{unfold-locales apply } (\text{auto simp: hd-map comp-def map-tl ac-simps raw-clause-def}$   
 $\text{union-mset-list mset-map-mset-remove1-cond ex-mset-unwatched-watched})$

**done**

**declare**  $\text{CDCL-Two-Watched-Literals.twl.mset-ccls-ccls-of-cls[simp del]}$

**lemma**  $\text{mmset-of-mlit'-mmset-of-mlit[simp]}:$

$\text{twl.mmset-of-mlit } L = \text{mmset-of-mlit'} L$

**by**  $(\text{metis mmset-of-mlit'.simps}(1) \text{mmset-of-mlit'.simps}(2) \text{twl.mmset-of-mlit.elims raw-clause-def})$

**definition**

$\text{candidates-propagate} :: 'v \text{ twl-state} \Rightarrow ('v \text{ literal} \times 'v \text{ twl-clause}) \text{ set}$

**where**

$\text{candidates-propagate } S =$

$\{(L, C) \mid L C.$

$C \in \text{set } (\text{twl.raw-clauses } S) \wedge$

$\text{set } (\text{watched } C) - (\text{uminus ' lits-of-l } (\text{trail } S)) = \{L\} \wedge$

$\text{undefined-lit } (\text{trail } S) L\}$

**definition**  $\text{candidates-conflict} :: 'v \text{ twl-state} \Rightarrow 'v \text{ twl-clause set where}$

$\text{candidates-conflict } S =$

$\{C. C \in \text{set } (\text{twl.raw-clauses } S) \wedge$

$\text{set } (\text{watched } C) \subseteq \text{uminus ' lits-of-l } (\text{trail } S)\}$

**primrec**  $(\text{nonexhaustive}) \text{index} :: 'a \text{ list} \Rightarrow 'a \Rightarrow \text{nat where}$

$\text{index } (a \# l) c = (\text{if } a = c \text{ then } 0 \text{ else } 1 + \text{index } l c)$

**lemma**  $\text{index-nth}:$

$a \in \text{set } l \implies l ! (\text{index } l a) = a$

**by**  $(\text{induction } l) \text{auto}$

## 24.2 Invariants

We need the following property about updates: if there is a literal  $L$  with  $- L$  in the trail, and  $L$  is not watched, then it stays unwatched; i.e., while updating with *rewatch* it does not get swap with a watched literal  $L'$  such that  $- L'$  is in the trail.

**primrec**  $\text{watched-decided-most-recently} :: ('v, 'vl, 'mark) \text{ marked-lit list} \Rightarrow$

$'v \text{ twl-clause} \Rightarrow \text{bool}$

**where**

$\text{watched-decided-most-recently } M (\text{TWL-Clause } W UW) \longleftrightarrow$

$(\forall L' \in \text{set } W. \forall L \in \text{set } UW.$

$-L' \in \text{lits-of-l } M \longrightarrow -L \in \text{lits-of-l } M \longrightarrow L \notin \# \text{mset } W \longrightarrow$

$\text{index } (\text{map lit-of } M) (-L') \leq \text{index } (\text{map lit-of } M) (-L))$

Here are the invariant strictly related to the 2-WL data structure.



**primrec** *wf-twl-cl* :: ('v, 'wl, 'mark) marked-lit list  $\Rightarrow$  'v twl-clause  $\Rightarrow$  bool **where**  
*wf-twl-cl* M (TWL-Clause W UW)  $\longleftrightarrow$   
distinct W  $\wedge$  length W  $\leq 2 \wedge$  (length W  $< 2 \longrightarrow$  set UW  $\subseteq$  set W)  $\wedge$   
 $(\forall L \in \text{set } W. \neg L \in \text{lits-of-l } M \longrightarrow (\forall L' \in \text{set } UW. L' \notin \text{set } W \longrightarrow \neg L' \in \text{lits-of-l } M)) \wedge$   
watched-decided-most-recently M (TWL-Clause W UW)

**lemma** *size-mset-2*: size x1 = 2  $\longleftrightarrow$  ( $\exists a \ b. x1 = \{\#a, b\}$ )  
**apply** (cases x1)  
**apply** simp  
**by** (metis (no-types, hide-lams) Suc-eq-plus1 one-add-one size-1-singleton-mset  
size-Diff-singleton size-Suc-Diff1 size-single union-single-eq-diff union-single-eq-member)

**lemma** *distinct-mset-size-2*: distinct-mset  $\{\#a, b\} \longleftrightarrow a \neq b$   
**unfolding** *distinct-mset-def* **by** auto

**lemma** *wf-twl-cl-annotation-independant*:  
**assumes** M: map lit-of M = map lit-of M'  
**shows** *wf-twl-cl* M (TWL-Clause W UW)  $\longleftrightarrow$  *wf-twl-cl* M' (TWL-Clause W UW)  
**proof** –  
**have** lits-of-l M = lits-of-l M'  
**using** arg-cong[OF M, of set] **by** (simp add: lits-of-def)  
**then show** ?thesis  
**by** (simp add: lits-of-def M)  
**qed**

**lemma** *wf-twl-cl-wf-twl-cl-tl*:  
**assumes** wf: *wf-twl-cl* M C **and** n-d: no-dup M  
**shows** *wf-twl-cl* (tl M) C  
**proof** (cases M)  
**case** Nil  
**then show** ?thesis **using** wf  
**by** (cases C) (simp add: wf-twl-cl.simps[of tl -])  
**next**  
**case** (Cons l M') **note** M = this(1)  
**obtain** W UW **where** C: C = TWL-Clause W UW  
**by** (cases C)  
**{ fix** L L'  
**assume**  
LW: L  $\in$  set W **and**  
LM:  $\neg L \in \text{lits-of-l } M'$  **and**  
L'UW: L'  $\in$  set UW **and**  
L'  $\notin$  set W  
**then have**  
L'M:  $\neg L' \in \text{lits-of-l } M$   
**using** wf **by** (auto simp: C M)  
**have** watched-decided-most-recently M C  
**using** wf **by** (auto simp: C)  
**then have**  
index (map lit-of M) ( $\neg L$ )  $\leq$  index (map lit-of M) ( $\neg L'$ )  
**using** LM L'M L'UW LW  $\langle L' \notin \text{set } W \rangle$  C M **unfolding** lits-of-def  
**by** (fastforce simp: lits-of-def)  
**then have**  $\neg L' \in \text{lits-of-l } M'$   
**using**  $\langle L' \notin \text{set } W \rangle$  LW L'M **by** (auto simp: C M split: if-split-asm)  
**}**  
**moreover**

```

{
  fix L' L
  assume
    L' ∈ set W and
    L ∈ set UW and
    L'M: - L' ∈ lits-of-l M' and
    - L ∈ lits-of-l M' and
    L ∉ set W
  moreover
    have lit-of l ≠ - L'
    using n-d unfolding M
      by (metis (no-types) L'M M Marked-Propagated-in-iff-in-lits-of-l defined-lit-map
          distinct.simps(2) list.simps(9) set-map)
    moreover have watched-decided-most-recently M C
      using wf by (auto simp: C)
    ultimately have index (map lit-of M') (- L') ≤ index (map lit-of M') (- L)
      by (fastforce simp: M C split: if-split-asm)
}
moreover have distinct W and length W ≤ 2 and (length W < 2 → set UW ⊆ set W)
  using wf by (auto simp: C M)
ultimately show ?thesis by (auto simp add: M C)
qed

```

**definition** *wf-twl-state* :: 'v twl-state ⇒ bool **where**  
*wf-twl-state* S ⇔ (∀ C ∈ set (twl.raw-clauses S). wf-twl-cls (trail S) C) ∧ no-dup (trail S)

**lemma** *wf-candidates-propagate-sound*:

**assumes** wf: wf-twl-state S **and**  
 cand: (L, C) ∈ candidates-propagate S  
**shows** trail S ⊨<sub>as</sub> CNot (mset (removeAll L (raw-clause C))) ∧ undefined-lit (trail S) L  
 (is ?Not ∧ ?undef)

**proof**

**def** M ≡ trail S  
**def** N ≡ raw-init-clss S  
**def** U ≡ raw-learned-clss S

**note** MNU-defs [simp] = M-def N-def U-def

**have** cw:

C ∈ set (N @ U)  
 set (watched C) - uminus ' lits-of-l M = {L}  
 undefined-lit M L  
**using** cand **unfolding** candidates-propagate-def MNU-defs twl.raw-clauses-def **by** auto

**obtain** W UW **where** cw-eq: C = TWL-Clause W UW  
**by** (cases C)

**have** l-w: L ∈ set W  
**using** cw(2) cw-eq **by** auto

**have** wf-c: wf-twl-cls M C  
**using** wf cw(1) **unfolding** wf-twl-state-def **by** (simp add: twl.raw-clauses-def)

**have** w-nw:  
 distinct W

$length\ W < 2 \implies set\ UW \subseteq set\ W$   
 $\bigwedge L\ L'.\ L \in set\ W \implies -L \in lits-of-l\ M \implies L' \in set\ UW \implies L' \notin set\ W \implies -L' \in lits-of-l\ M$   
**using** *wf-c* **unfolding** *cw-eq* **by** (*auto simp: image-image*)

**have**  $\forall L' \in set\ (raw\_clause\ C) - \{L\}.\ -L' \in lits-of-l\ M$   
**proof** (*cases length W < 2*)  
   **case** *True*  
     **moreover have**  $size\ W \neq 0$   
       **using** *cw(2) cw-eq* **by** *auto*  
     **ultimately have**  $size\ W = 1$   
       **by** *linarith*  
     **then have**  $w: W = [L]$   
       **using** *l-w* **by** (*auto simp: length-list-Suc-0*)  
     **from** *True* **have**  $set\ UW \subseteq set\ W$   
       **using** *w-nw(2)* **by** *blast*  
     **then show** *?thesis*  
       **using** *w cw(1) cw-eq* **by** (*auto simp: raw-clause-def*)  
**next**  
   **case** *sz2: False*  
   **show** *?thesis*  
   **proof**  
     **fix**  $L'$   
     **assume**  $l': L' \in set\ (raw\_clause\ C) - \{L\}$   
     **have** *ex-la*:  $\exists La.\ La \neq L \wedge La \in set\ W$   
     **proof** (*cases W*)  
       **case** *w: Nil*  
       **thus** *?thesis*  
       **using** *l-w* **by** *auto*  
     **next**  
       **case** *lb: (Cons Lb W')*  
       **show** *?thesis*  
       **proof** (*cases W'*)  
         **case** *Nil*  
         **thus** *?thesis*  
         **using** *lb sz2* **by** *simp*  
       **next**  
         **case** *lc: (Cons Lc W'')*  
         **thus** *?thesis*  
         **by** (*metis distinct-length-2-or-more lb list.set-intros(1) list.set-intros(2) w-nw(1)*)  
     **qed**  
   **qed**  
   **then obtain**  $La$  **where**  $la: La \neq L \wedge La \in set\ W$   
     **by** *blast*  
   **then have**  $La \in uminus\ ' lits-of-l\ M$   
     **using** *cw(2)[unfolded cw-eq, simplified, folded M-def]*  $\langle La \in set\ W \rangle \langle La \neq L \rangle$  **by** *auto*  
   **then have**  $nla: -La \in lits-of-l\ M$   
     **by** (*auto simp: image-image*)  
   **then show**  $-L' \in lits-of-l\ M$   
  
   **proof**  $-$   
     **have**  $f1: L' \in set\ (raw\_clause\ C)$   
       **using**  $l'$  **by** *blast*  
     **have**  $f2: L' \notin \{L\}$   
       **using**  $l'$  **by** *fastforce*  
     **have**  $\bigwedge l.\ - (l::'a\ literal) \in L \vee l \notin uminus\ ' L$

```

    by force
  then show ?thesis
    using cw(1) cw-eq w-nw(3) raw-clause-def by (metis DiffI Un-iff cw(2) f1 f2 la(2) nla
      set-append twl-clause.sel(1) twl-clause.sel(2))
  qed
qed
qed
then show ?Not
  unfolding true-annots-def by (auto simp: image-image Ball-def CNot-def)

show ?undef
  using cw(3) M-def by blast
qed

lemma wf-candidates-propagate-complete:
  assumes wf: wf-twl-state S and
    c-mem:  $C \in \text{set } (\text{twl.raw-clauses } S)$  and
    l-mem:  $L \in \text{set } (\text{raw-clause } C)$  and
    unsat:  $\text{trail } S \models_{\text{as}} \text{CNot } (\text{mset-set } (\text{set } (\text{raw-clause } C) - \{L\}))$  and
    undef:  $\text{undefined-lit } (\text{trail } S) L$ 
  shows  $(L, C) \in \text{candidates-propagate } S$ 
proof -
  def M  $\equiv \text{trail } S$ 
  def N  $\equiv \text{raw-init-clss } S$ 
  def U  $\equiv \text{raw-learned-clss } S$ 

  note MNU-defs [simp] = M-def N-def U-def

  obtain W UW where cw-eq:  $C = \text{TWL-Clause } W UW$ 
    by (cases C, blast)

  have wf-c: wf-twl-clss M C
    using wf c-mem unfolding wf-twl-state-def by simp

  have w-nw:
    distinct W
    length W < 2  $\implies \text{set } UW \subseteq \text{set } W$ 
     $\bigwedge L L'. L \in \text{set } W \implies \neg L \in \text{lits-of-l } M \implies L' \in \text{set } UW \implies L' \notin \text{set } W \implies \neg L' \in \text{lits-of-l } M$ 
    using wf-c unfolding cw-eq by (auto simp: image-image)

  have unit-set:  $\text{set } W - (\text{uminus } \text{'lits-of-l } M) = \{L\}$  (is ?W = ?L)
proof
  show ?W  $\subseteq \{L\}$ 
  proof
    fix L'
    assume l':  $L' \in ?W$ 
    hence l'-mem-w:  $L' \in \text{set } W$ 
      by (simp add: in-diffD)
    have L'  $\notin \text{uminus } \text{'lits-of-l } M$ 
      using l' by blast
    then have  $\neg M \models_a \{\# - L' \#\}$ 
      by (auto simp: lits-of-def uminus-lit-swap image-image)
    moreover have  $L' \in \text{set } (\text{raw-clause } C)$ 
      using c-mem cw-eq l'-mem-w by (auto simp: raw-clause-def)
    ultimately have  $L' = L$ 

```

```

    using unsat[unfolded CNot-def true-annot-def, simplified]
    unfolding M-def by fastforce
  then show  $L' \in \{L\}$ 
    by simp
qed
next
show  $\{L\} \subseteq ?W$ 
proof clarify
  have  $L \in \text{set } W$ 
  proof (cases W)
    case Nil
    thus ?thesis
      using w-nw(2) cw-eq l-mem by (auto simp: raw-clause-def)
  next
    case (Cons La W')
    thus ?thesis
      proof (cases La = L)
        case True
        thus ?thesis
          using Cons by simp
      next
        case False
        have  $-La \in \text{lits-of-l } M$ 
          using False Cons cw-eq unsat[unfolded CNot-def true-annot-def, simplified]
          by (fastforce simp: raw-clause-def)
        then show ?thesis
          using Cons cw-eq l-mem undef w-nw(3)
          by (auto simp: Marked-Propagated-in-iff-in-lits-of-l raw-clause-def)
      qed
    qed
  moreover have  $L \notin \# \text{mset-set } (\text{uminus } \text{'lits-of-l } M)$ 
    using undef by (auto simp: Marked-Propagated-in-iff-in-lits-of-l image-image)
  ultimately show  $L \in ?W$ 
    by simp
qed
qed

show ?thesis
  unfolding candidates-propagate-def using unit-set undef c-mem unfolding cw-eq M-def
  by (auto simp: image-image cw-eq intro!: exI[of - C])
qed

lemma wf-candidates-conflict-sound:
  assumes wf: wf-twl-state S and
    cand:  $C \in \text{candidates-conflict } S$ 
  shows  $\text{trail } S \models_{\text{as}} \text{CNot } (\text{mset } (\text{raw-clause } C)) \wedge C \in \text{set } (\text{twl.raw-clauses } S)$ 
proof
  def M  $\equiv \text{trail } S$ 
  def N  $\equiv \text{raw-init-clss } S$ 
  def U  $\equiv \text{raw-learned-clss } S$ 

  note MNU-defs [simp] = M-def N-def U-def

  have cw:
     $C \in \text{set } (N @ U)$ 

```

```

set (watched C)  $\subseteq$  uminus ' lits-of-l (trail S)
using cand[unfolded candidates-conflict-def, simplified] unfolding twl.raw-clauses-def by auto

obtain W UW where cw-eq: C = TWL-Clause W UW
by (cases C, blast)

have wf-c: wf-twl-cls M C
using wf cw(1) unfolding wf-twl-state-def by (simp add: comp-def twl.raw-clauses-def)

have w-nw:
  distinct W
  length W < 2  $\implies$  set UW  $\subseteq$  set W
   $\bigwedge L L'. L \in \text{set } W \implies -L \in \text{lits-of-l } M \implies L' \in \text{set } UW \implies L' \notin \text{set } W \implies -L' \in \text{lits-of-l } M$ 
using wf-c unfolding cw-eq by (auto simp: image-image)

have  $\forall L \in \text{set } (\text{raw-clause } C). -L \in \text{lits-of-l } M$ 
proof (cases W)
  case Nil
  then have raw-clause C = []
  using cw(1) cw-eq w-nw(2) by (auto simp: raw-clause-def)
  then show ?thesis
  by simp
next
  case (Cons La W') note W' = this(1)
  show ?thesis
  proof
    fix L
    assume l: L  $\in$  set (raw-clause C)
    show  $-L \in \text{lits-of-l } M$ 
    proof (cases L  $\in$  set W)
      case True
      thus ?thesis
      using cw(2) cw-eq by fastforce
    next
      case False
      thus ?thesis
      by (metis (no-types, hide-lams) M-def UnE W' contra-subsetD cw(2) cw-eq imageE
        insertI1 l list.set(2) set-append twl-clause.sel(1) twl-clause.sel(2)
        uminus-of-uminus-id w-nw(3) raw-clause-def)
    qed
  qed
  qed
then show trail S  $\models_{\text{as}} \text{CNot } (\text{mset } (\text{raw-clause } C))$ 
unfolding CNot-def true-annots-def by auto

show C  $\in$  set (twl.raw-clauses S)
using cw unfolding twl.raw-clauses-def by auto
qed

lemma wf-candidates-conflict-complete:
  assumes wf: wf-twl-state S and
  c-mem: C  $\in$  set (twl.raw-clauses S) and
  unsat: trail S  $\models_{\text{as}} \text{CNot } (\text{mset } (\text{raw-clause } C))$ 
  shows C  $\in$  candidates-conflict S
proof -

```

```

def M ≡ trail S
def N ≡ twl.init-clss S
def U ≡ twl.learned-clss S

note MNU-defs [simp] = M-def N-def U-def

obtain W UW where cw-eq: C = TWL-Clause W UW
  by (cases C, blast)

have wf-c: wf-twl-clss M C
  using wf-c-mem unfolding wf-twl-state-def by simp

have w-nw:
  distinct W
  length W < 2 ⇒ set UW ⊆ set W
  ∧ L L'. L ∈ set W ⇒ -L ∈ lits-of-l M ⇒ L' ∈ set UW ⇒ L' ∉ set W ⇒ -L' ∈ lits-of-l M
  using wf-c unfolding cw-eq by (auto simp: image-image)

have ∧ L. L ∈ set (raw-clause C) ⇒ -L ∈ lits-of-l M
  unfolding M-def using unsat[unfolded CNot-def true-annots-def, simplified] by auto
then have set (raw-clause C) ⊆ uminus ' lits-of-l M
  by (metis imageI subsetI uminus-of-uminus-id)
then have set W ⊆ uminus ' lits-of-l M
  using cw-eq by (auto simp: raw-clause-def)
then have subset: set W ⊆ uminus ' lits-of-l M
  by (simp add: w-nw(1))

have W = watched C
  using cw-eq twl-clause.sel(1) by simp
then show ?thesis
  using MNU-defs c-mem subset candidates-conflict-def by blast
qed

typedef 'v wf-twl = {S::'v twl-state. wf-twl-state S}
morphisms rough-state-of-twl twl-of-rough-state
proof -
  have TWL-State ([::('v, nat, 'v twl-clause) marked-lits)
    [] [] 0 None ∈ {S::'v twl-state. wf-twl-state S}
    by (auto simp: wf-twl-state-def twl.raw-clauses-def)
  then show ?thesis by auto
qed

lemma [code abstype]:
  twl-of-rough-state (rough-state-of-twl S) = S
  by (fact CDCL-Two-Watched-Literals.wf-twl.rough-state-of-twl-inverse)

lemma wf-twl-state-rough-state-of-twl[simp]: wf-twl-state (rough-state-of-twl S)
  using rough-state-of-twl by auto

abbreviation candidates-conflict-twl :: 'v wf-twl ⇒ 'v twl-clause set where
  candidates-conflict-twl S ≡ candidates-conflict (rough-state-of-twl S)

abbreviation candidates-propagate-twl :: 'v wf-twl ⇒ ('v literal × 'v twl-clause) set where
  candidates-propagate-twl S ≡ candidates-propagate (rough-state-of-twl S)

```

**abbreviation** *raw-trail-twl* :: 'a wf-twl  $\Rightarrow$  ('a, nat, 'a twl-clause) marked-lit list **where**  
*raw-trail-twl* *S*  $\equiv$  *raw-trail* (*rough-state-of-twl* *S*)

**abbreviation** *trail-twl* :: 'a wf-twl  $\Rightarrow$  ('a, nat, 'a literal multiset) marked-lit list **where**  
*trail-twl* *S*  $\equiv$  *trail* (*rough-state-of-twl* *S*)

**abbreviation** *raw-clauses-twl* :: 'a wf-twl  $\Rightarrow$  'a twl-clause list **where**  
*raw-clauses-twl* *S*  $\equiv$  *twl.raw-clauses* (*rough-state-of-twl* *S*)

**abbreviation** *raw-init-clss-twl* :: 'a wf-twl  $\Rightarrow$  'a twl-clause list **where**  
*raw-init-clss-twl* *S*  $\equiv$  *raw-init-clss* (*rough-state-of-twl* *S*)

**abbreviation** *raw-learned-clss-twl* :: 'a wf-twl  $\Rightarrow$  'a twl-clause list **where**  
*raw-learned-clss-twl* *S*  $\equiv$  *raw-learned-clss* (*rough-state-of-twl* *S*)

**abbreviation** *backtrack-lvl-twl* **where**  
*backtrack-lvl-twl* *S*  $\equiv$  *backtrack-lvl* (*rough-state-of-twl* *S*)

**abbreviation** *raw-conflicting-twl* **where**  
*raw-conflicting-twl* *S*  $\equiv$  *raw-conflicting* (*rough-state-of-twl* *S*)

**lemma** *wf-candidates-twl-conflict-complete*:

**assumes**

*c-mem*:  $C \in \text{set } (\text{raw-clauses-twl } S)$  **and**

*unsat*:  $\text{trail-twl } S \models_{\text{as}} \text{CNot } (\text{mset } (\text{raw-clause } C))$

**shows**  $C \in \text{candidates-conflict-twl } S$

**using** *c-mem unsat wf-candidates-conflict-complete wf-twl-state-rough-state-of-twl* **by** *blast*

**abbreviation** *update-backtrack-lvl* **where**

*update-backtrack-lvl* *k* *S*  $\equiv$

*TWL-State* (*raw-trail* *S*) (*raw-init-clss* *S*) (*raw-learned-clss* *S*) *k* (*raw-conflicting* *S*)

**abbreviation** *update-conflicting* **where**

*update-conflicting* *C* *S*  $\equiv$

*TWL-State* (*raw-trail* *S*) (*raw-init-clss* *S*) (*raw-learned-clss* *S*) (*backtrack-lvl* *S*) *C*

## 24.3 Abstract 2-WL

**definition** *tl-trail* **where**

*tl-trail* *S* =

*TWL-State* (*tl* (*raw-trail* *S*)) (*raw-init-clss* *S*) (*raw-learned-clss* *S*) (*backtrack-lvl* *S*)  
(*raw-conflicting* *S*)

**locale** *abstract-twl* =

**fixes**

*watch* :: 'v twl-state  $\Rightarrow$  'v literal list  $\Rightarrow$  'v twl-clause **and**

*rewatch* :: 'v literal  $\Rightarrow$  'v twl-state  $\Rightarrow$

'v twl-clause  $\Rightarrow$  'v twl-clause **and**

*restart-learned* :: 'v twl-state  $\Rightarrow$  'v twl-clause list

**assumes**

*clause-watch*:  $\text{no-dup } (\text{trail } S) \implies \text{mset } (\text{raw-clause } (\text{watch } S C)) = \text{mset } C$  **and**

*wf-watch*:  $\text{no-dup } (\text{trail } S) \implies \text{wf-twl-cls } (\text{trail } S) (\text{watch } S C)$  **and**

*clause-rewatch*:  $\text{mset } (\text{raw-clause } (\text{rewatch } L' S C')) = \text{mset } (\text{raw-clause } C')$  **and**

*wf-rewatch*:

$\text{no-dup } (\text{trail } S) \implies \text{undefined-lit } (\text{trail } S) (\text{lit-of } L) \implies \text{wf-twl-cls } (\text{trail } S) C' \implies$

$\text{wf-twl-cls } (L \# \text{trail } S) (\text{rewatch } (\text{lit-of } L) S C')$



**and**  
*restart-learned*:  $\text{mset } (\text{restart-learned } S) \subseteq \# \text{ mset } (\text{raw-learned-clss } S)$  — We need *mset* and not *set* to take care of duplicates.  
**begin**

**definition**

*cons-trail* :: ('v, nat, 'v twl-clause) marked-lit  $\Rightarrow$  'v twl-state  $\Rightarrow$  'v twl-state  
**where**  
*cons-trail* L S =  
 TWL-State (L # raw-trail S) (map (rewatch (lit-of L) S) (raw-init-clss S))  
 (map (rewatch (lit-of L) S) (raw-learned-clss S)) (backtrack-lvl S) (raw-conflicting S)

**definition**

*add-init-cls* :: 'v literal list  $\Rightarrow$  'v twl-state  $\Rightarrow$  'v twl-state  
**where**  
*add-init-cls* C S =  
 TWL-State (raw-trail S) (watch S C # raw-init-clss S) (raw-learned-clss S) (backtrack-lvl S)  
 (raw-conflicting S)

**definition**

*add-learned-cls* :: 'v literal list  $\Rightarrow$  'v twl-state  $\Rightarrow$  'v twl-state  
**where**  
*add-learned-cls* C S =  
 TWL-State (raw-trail S) (raw-init-clss S) (watch S C # raw-learned-clss S) (backtrack-lvl S)  
 (raw-conflicting S)

**definition**

*remove-cls* :: 'v literal list  $\Rightarrow$  'v twl-state  $\Rightarrow$  'v twl-state  
**where**  
*remove-cls* C S =  
 TWL-State (raw-trail S)  
 (removeAll-cond ( $\lambda D$ .  $\text{mset } (\text{raw-clause } D) = \text{mset } C$ ) (raw-init-clss S))  
 (removeAll-cond ( $\lambda D$ .  $\text{mset } (\text{raw-clause } D) = \text{mset } C$ ) (raw-learned-clss S))  
 (backtrack-lvl S)  
 (raw-conflicting S)

**definition** *init-state* :: 'v literal list list  $\Rightarrow$  'v twl-state **where**  
*init-state* N = fold add-init-cls N (TWL-State [] [] 0 None)

**lemma** *unchanged-fold-add-init-cls*:

*raw-trail* (fold add-init-cls Cs (TWL-State M N U k C)) = M  
*raw-learned-clss* (fold add-init-cls Cs (TWL-State M N U k C)) = U  
*backtrack-lvl* (fold add-init-cls Cs (TWL-State M N U k C)) = k  
*raw-conflicting* (fold add-init-cls Cs (TWL-State M N U k C)) = C  
**by** (induct Cs arbitrary: N) (auto simp: add-init-cls-def)

**lemma** *unchanged-init-state*[simp]:

*raw-trail* (init-state N) = []  
*raw-learned-clss* (init-state N) = []  
*backtrack-lvl* (init-state N) = 0  
*raw-conflicting* (init-state N) = None  
**unfolding** *init-state-def* **by** (rule unchanged-fold-add-init-cls)+

**lemma** *clauses-init-fold-add-init*:

*no-dup* M  $\implies$

$twl.init-clss$  (fold  $add-init-clss$   $Cs$  ( $TWL-State$   $M$   $N$   $U$   $k$   $C$ )) =  
 $clauses-of-l$   $Cs$  +  $clauses-of-l$  ( $map$   $raw-clause$   $N$ )  
**by** ( $induct$   $Cs$   $arbitrary$ :  $N$ ) ( $auto$   $simp$ :  $add-init-clss-def$   $clause-watch$   $comp-def$   $ac-simps$ )

**lemma**  $init-clss-init-state[simp]$ :  $twl.init-clss$  ( $init-state$   $N$ ) =  $clauses-of-l$   $N$   
**unfolding**  $init-state-def$  **by** ( $subst$   $clauses-init-fold-add-init$ )  $simp-all$

**definition**  $restart'$  **where**  
 $restart' S = TWL-State [] (raw-init-clss S) (restart-learned S) 0 None$

**end**

## 24.4 Instanciation of the previous locale

**definition**  $watch-nat :: 'v twl-state \Rightarrow 'v literal list \Rightarrow 'v twl-clause$  **where**  
 $watch-nat S C =$   
 (let  
 $C' = remdups C;$   
 $neg-not-assigned = filter (\lambda L. \neg L \notin lits-of-l (raw-trail S)) C';$   
 $neg-assigned-sorted-by-trail = filter (\lambda L. L \in set C) (map (\lambda L. \neg lit-of L) (raw-trail S));$   
 $W = take\ 2 (neg-not-assigned @ neg-assigned-sorted-by-trail);$   
 $UW = foldr remove1 W C$   
 in  $TWL-Clause W UW$ )

**lemma**  $list-cases2$ :  
**fixes**  $l :: 'a list$   
**assumes**  
 $l = [] \implies P$  **and**  
 $\bigwedge x. l = [x] \implies P$  **and**  
 $\bigwedge x\ y\ xs. l = x \# y \# xs \implies P$   
**shows**  $P$   
**by** ( $metis$   $assms$   $list.collapse$ )

**lemma**  $filter-in-list-prop-verifiedD$ :  
**assumes**  $[L \leftarrow P \ .\ Q\ L] = l$   
**shows**  $\forall x \in set\ l. x \in set\ P \wedge Q\ x$   
**using**  $assms$  **by**  $auto$

**lemma**  $no-dup-filter-diff$ :  
**assumes**  $n-d$ :  $no-dup\ M$  **and**  $H$ :  $[L \leftarrow map (\lambda L. \neg lit-of L) M. L \in set\ C] = l$   
**shows**  $distinct\ l$   
**unfolding**  $H[symmetric]$   
**apply** ( $rule\ distinct-filter$ )  
**using**  $n-d$  **by** ( $induction\ M$ )  $auto$

**lemma**  $watch-nat-lists-disjointD$ :  
**assumes**  
 $l: [L \leftarrow remdups\ C. \neg L \notin lits-of-l (raw-trail S)] = l$  **and**  
 $l': [L \leftarrow map (\lambda L. \neg lit-of L) (raw-trail S) . L \in set\ C] = l'$   
**shows**  $\forall x \in set\ l. \forall y \in set\ l'. x \neq y$   
**by** ( $auto$   $simp$ :  $l[symmetric]$   $l'[symmetric]$   $lits-of-def$   $image-image$ )

**lemma**  $watch-nat-list-cases-witness[consumes\ 2, case-names\ nil-nil\ nil-single\ nil-other\ single-nil\ single-other\ other]$ :  
**fixes**  
 $C :: 'v literal list$  **and**

$S :: 'v \text{ twl-state}$   
**defines**  
 $xs \equiv [L \leftarrow \text{remdups } C. - L \notin \text{lits-of-l (raw-trail } S)] \text{ and}$   
 $ys \equiv [L \leftarrow \text{map } (\lambda L. - \text{lit-of } L) \text{ (raw-trail } S) . L \in \text{set } C]$   
**assumes**  
 $n\text{-d: no-dup (raw-trail } S) \text{ and}$   
 $nil\text{-nil: } xs = [] \implies ys = [] \implies P \text{ and}$   
 $nil\text{-single:}$   
 $\bigwedge a. xs = [] \implies ys = [a] \implies a \in \text{set } C \implies P \text{ and}$   
 $nil\text{-other: } \bigwedge a \ b \ ys'. xs = [] \implies ys = a \# b \# ys' \implies a \neq b \implies P \text{ and}$   
 $single\text{-nil: } \bigwedge a. xs = [a] \implies ys = [] \implies P \text{ and}$   
 $single\text{-other: } \bigwedge a \ b \ ys'. xs = [a] \implies ys = b \# ys' \implies a \neq b \implies P \text{ and}$   
 $other: \bigwedge a \ b \ xs'. xs = a \# b \# xs' \implies a \neq b \implies P$   
**shows**  $P$   
**proof** –  
**note**  $xs\text{-def}[simp] \text{ and } ys\text{-def}[simp]$   
**have**  $dist: \bigwedge P. \text{distinct } [L \leftarrow \text{remdups } C . P \ L]$   
**by**  $auto$   
**then have**  $H: \bigwedge a \ b \ P \ xs. [L \leftarrow \text{remdups } C . P \ L] = a \# b \# xs \implies a \neq b$   
**by**  $(metis \text{distinct-length-2-or-more})$   
**show**  $?thesis$   
**apply**  $(\text{cases } [L \leftarrow \text{remdups } C. - L \notin \text{lits-of-l (raw-trail } S)])$   
 $\text{rule: list-cases2;}$   
 $\text{cases } [L \leftarrow \text{map } (\lambda L. - \text{lit-of } L) \text{ (raw-trail } S) . L \in \text{set } C] \text{ rule: list-cases2})$   
**using**  $nil\text{-nil apply simp}$   
**using**  $nil\text{-single apply (force dest: filter-in-list-prop-verifiedD)}$   
**using**  $nil\text{-other no-dup-filter-diff[OF n-d, of C]}$   
**apply**  $\text{fastforce}$   
**using**  $single\text{-nil apply simp}$   
**using**  $single\text{-other xs-def ys-def apply (metis list.set-intros(1) watch-nat-lists-disjointD)}$   
**using**  $single\text{-other unfolding xs-def ys-def apply (metis list.set-intros(1) watch-nat-lists-disjointD)}$   
**using**  $other xs-def ys-def \text{ by (metis H) +}$   
**qed**

**lemma**  $\text{watch-nat-list-cases [consumes 1, case-names nil-nil nil-single nil-other single-nil single-other other]:}$   
**fixes**  
 $C :: 'v \text{ literal list and}$   
 $S :: 'v \text{ twl-state}$   
**defines**  
 $xs \equiv [L \leftarrow \text{remdups } C . - L \notin \text{lits-of-l (raw-trail } S)] \text{ and}$   
 $ys \equiv [L \leftarrow \text{map } (\lambda L. - \text{lit-of } L) \text{ (raw-trail } S) . L \in \text{set } C]$   
**assumes**  
 $n\text{-d: no-dup (raw-trail } S) \text{ and}$   
 $nil\text{-nil: } xs = [] \implies ys = [] \implies P \text{ and}$   
 $nil\text{-single:}$   
 $\bigwedge a. xs = [] \implies ys = [a] \implies a \in \text{set } C \implies P \text{ and}$   
 $nil\text{-other: } \bigwedge a \ b \ ys'. xs = [] \implies ys = a \# b \# ys' \implies a \neq b \implies P \text{ and}$   
 $single\text{-nil: } \bigwedge a. xs = [a] \implies ys = [] \implies P \text{ and}$   
 $single\text{-other: } \bigwedge a \ b \ ys'. xs = [a] \implies ys = b \# ys' \implies a \neq b \implies P \text{ and}$   
 $other: \bigwedge a \ b \ xs'. xs = a \# b \# xs' \implies a \neq b \implies P$   
**shows**  $P$   
**using**  $\text{watch-nat-list-cases-witness[OF n-d, of C P]}$   
 $nil\text{-nil nil-single nil-other single-nil single-other other}$

**unfolding**  $xs\text{-def}[symmetric]$   $ys\text{-def}[symmetric]$  **by** *auto*

**lemma** *watch-nat-lists-set-union-witness*:

**fixes**

$C :: 'v$  literal list **and**

$S :: 'v$  twl-state

**defines**

$xs \equiv [L \leftarrow \text{remdups } C. - L \notin \text{lits-of-l (raw-trail } S)]$  **and**

$ys \equiv [L \leftarrow \text{map } (\lambda L. - \text{lit-of } L) \text{ (raw-trail } S) . L \in \text{set } C]$

**assumes**  $n\text{-d}$ :  $\text{no-dup (raw-trail } S)$

**shows**  $\text{set } C = \text{set } xs \cup \text{set } ys$

**using**  $n\text{-d}$  **unfolding**  $xs\text{-def}$   $ys\text{-def}$  **by** (*auto simp: lits-of-def comp-def uminus-lit-swap*)

**lemma** *mset-intersection-inclusion*:  $A + (B - A) = B \longleftrightarrow A \subseteq\# B$

**apply** (*rule iffI*)

**apply** (*metis mset-le-add-left*)

**by** (*auto simp: ac-simps multiset-eq-iff subseteq-mset-def*)

**lemma** *clause-watch-nat*:

**assumes**  $\text{no-dup (raw-trail } S)$

**shows**  $\text{mset (raw-clause (watch-nat } S \ C))} = \text{mset } C$

**using** *assms*

**apply** (*cases rule: watch-nat-list-cases[OF assms(1), of C]*)

**by** (*auto dest: filter-in-list-prop-verifiedD simp: watch-nat-def multiset-eq-iff raw-clause-def*)

**lemma** *index-uminus-index-map-uminus*:

$-a \in \text{set } L \implies \text{index } L \ (-a) = \text{index (map uminus } L) \ (a::'a \text{ literal})$

**by** (*induction L*) *auto*

**lemma** *index-filter*:

$a \in \text{set } L \implies b \in \text{set } L \implies P \ a \implies P \ b \implies$

$\text{index } L \ a \leq \text{index } L \ b \longleftrightarrow \text{index (filter } P \ L) \ a \leq \text{index (filter } P \ L) \ b$

**by** (*induction L*) *auto*

**lemma** *foldr-remove1-W-Nil[simp]*:  $\text{foldr remove1 } W \ [] = []$

**by** (*induct W*) *auto*

**lemma** *image-lit-of-mmset-of-mlit'[simp]*:

$\text{lit-of ' mmset-of-mlit' ' } A = \text{lit-of ' } A$

**by** (*auto simp: image-image comp-def*)

**lemma** *distinct-filter-eq*:

**assumes**  $\text{distinct } xs$

**shows**  $[L \leftarrow xs. L = a] = (\text{if } a \in \text{set } xs \text{ then } [a] \text{ else } [])$

**using** *assms* **by** (*induction xs*) *auto*

**lemma** *no-dup-distinct-map-uminus-lit-of*:

$\text{no-dup } xs \implies \text{distinct (map } (\lambda L. - \text{lit-of } L) \ xs)$

**by** (*induction xs*) *auto*

**lemma** *wf-watch-witness*:

**fixes**  $C :: 'v$  literal list **and**

$S :: 'v$  twl-state

**defines**

$\text{ass: neg-not-assigned} \equiv \text{filter } (\lambda L. -L \notin \text{lits-of-l (raw-trail } S)) \ (\text{remdups } C)$  **and**

```

    tr: neg-assigned-sorted-by-trail  $\equiv$  filter ( $\lambda L. L \in \text{set } C$ ) (map ( $\lambda L. -\text{lit-of } L$ ) (raw-trail S))
  defines
    W: W  $\equiv$  take 2 (neg-not-assigned @ neg-assigned-sorted-by-trail)
  assumes
    n-d[simp]: no-dup (raw-trail S)
  shows wf-twl-cls (trail S) (TWL-Clause W (foldr remove1 W C))
  unfolding wf-twl-cls.simps
  proof (intro conjI, goal-cases)
  case 1
  then show ?case using n-d W unfolding ass tr
    apply (cases rule: watch-nat-list-cases-witness[of S C, OF n-d])
    by (auto simp: distinct-mset-add-single)
  next
  case 2
  then show ?case unfolding W by simp
  next
  case 3
  show ?case using n-d
  proof (cases rule: watch-nat-list-cases-witness[of S C])
  case nil-nil
  then have set C = set []  $\cup$  set []
    using watch-nat-lists-set-union-witness n-d by metis
  then show ?thesis
    by simp
  next
  case (nil-single a)
  moreover have  $\bigwedge x. \text{set } C = \{a\} \implies - a \in \text{lits-of-l (trail S)} \implies x \in \text{set (remove1 a C)} \implies x = a$ 
    using notin-set-remove1 by auto
  ultimately show ?thesis
    using watch-nat-lists-set-union-witness[of S C] 3 by (auto simp: W ass tr comp-def)
  next
  case nil-other
  then show ?thesis
    using 3 by (auto simp: W ass tr)
  next
  case (single-nil a)
  show ?thesis
    using watch-nat-lists-set-union-witness[of S C] 3
    by (fastforce simp add: W ass tr single-nil comp-def distinct-filter-eq
        no-dup-distinct-map-uminus-lit-of min-def)
  next
  case single-other
  then show ?thesis
    using 3 by (auto simp: W ass tr)
  next
  case other
  then show ?thesis
    using 3 by (auto simp: W ass tr)
  qed
  next
  case 4 note -[simp] = this
  show ?case
  using n-d apply (cases rule: watch-nat-list-cases-witness[of S C])
    apply (auto dest: filter-in-list-prop-verifiedD)

```

```

    simp: W ass tr lits-of-def filter-empty-conv)[4]
  using watch-nat-lists-set-union-witness[of S C]
  by (force dest: filter-in-list-prop-verifiedD simp: W ass tr lits-of-def)+
next
case 5
from n-d show ?case
proof (cases rule: watch-nat-list-cases-witness[of S C])
  case nil-nil
  then show ?thesis by (auto simp: W ass tr)
next
case nil-single
then show ?thesis
  using watch-nat-lists-set-union-witness[of S C] tr by (fastforce simp: W ass)
next
case nil-other
then show ?thesis
  unfolding watched-decided-most-recently.simps Ball-def
  apply (intro allI impI)
  apply (subst index-uminus-index-map-uminus,
    simp add: index-uminus-index-map-uminus lits-of-def o-def)
  apply (subst index-uminus-index-map-uminus,
    simp add: index-uminus-index-map-uminus lits-of-def o-def)

  apply (subst index-filter[of - - λL. L ∈ set C])
  by (auto dest: filter-in-list-prop-verifiedD
    simp: uminus-lit-swap lits-of-def o-def W ass tr dest: in-diffD)
next
case single-nil
then show ?thesis
  using watch-nat-lists-set-union-witness[of S C] tr by (fastforce simp: W ass)
next
case single-other
then show ?thesis
  unfolding watched-decided-most-recently.simps Ball-def
  apply (clarify)
  apply (subst index-uminus-index-map-uminus,
    simp add: index-uminus-index-map-uminus lits-of-def image-image o-def)
  apply (subst index-uminus-index-map-uminus,
    simp add: index-uminus-index-map-uminus lits-of-def o-def)

  apply (subst index-filter[of - - λL. L ∈ set C])
  by (auto dest: filter-in-list-prop-verifiedD
    simp: W ass tr uminus-lit-swap lits-of-def o-def dest: in-diffD)
next
case other
then show ?thesis
  unfolding watched-decided-most-recently.simps
  apply clarify
  apply (subst index-uminus-index-map-uminus,
    simp add: index-uminus-index-map-uminus lits-of-def o-def)[1]
  apply (subst index-uminus-index-map-uminus,
    simp add: index-uminus-index-map-uminus lits-of-def o-def)[1]

  apply (subst index-filter[of - - λL. L ∈ set C])
  by (auto dest: filter-in-list-prop-verifiedD

```

```

      simp: index-uminus-index-map-uminus lits-of-def o-def uminus-lit-swap
      W ass tr)
qed
qed

lemma wf-watch-nat: no-dup (raw-trail S)  $\implies$  wf-twl-cls (trail S) (watch-nat S C)
  using wf-watch-witness[of S C] watch-nat-def by metis

definition
  rewatch-nat ::
    'v literal  $\Rightarrow$  'v twl-state  $\Rightarrow$  'v twl-clause  $\Rightarrow$  'v twl-clause
where
  rewatch-nat L S C =
    (if  $-L \in \text{set } (\text{watched } C)$  then
      case filter ( $\lambda L'. L' \notin \text{set } (\text{watched } C) \wedge -L' \notin \text{insert } L (\text{lits-of-l } (\text{trail } S))$ )
        (unwatched C) of
        []  $\Rightarrow$  C
      | L' # -  $\Rightarrow$ 
        TWL-Clause (L' # remove1 (-L) (watched C)) (-L # remove1 L' (unwatched C))
    else
      C)

lemma clause-rewatch-nat:
  fixes UW :: 'v literal list and
    S :: 'v twl-state and
    L :: 'v literal and C :: 'v twl-clause
  shows mset (raw-clause (rewatch-nat L S C)) = mset (raw-clause C)
  using List.set-remove1-subset[of -L watched C]
  apply (cases C)
  by (auto simp: raw-clause-def rewatch-nat-def ac-simps multiset-eq-iff
    split: list.split
    dest: filter-in-list-prop-verifiedD)

lemma filter-sorted-list-of-multiset-Nil:
   $[x \leftarrow \text{sorted-list-of-multiset } M. p \ x] = [] \iff (\forall x \in \# M. \neg p \ x)$ 
  by auto (metis empty-iff filter-set list.set(1) member-filter set-sorted-list-of-multiset)

lemma filter-sorted-list-of-multiset-ConsD:
   $[x \leftarrow \text{sorted-list-of-multiset } M. p \ x] = x \ \# \ xs \implies p \ x$ 
  by (metis filter-set insert-iff list.set(2) member-filter)

lemma mset-minus-single-eq-mempty:
   $a - \{\#b\} = \{\#\} \iff a = \{\#b\} \vee a = \{\#\}$ 
  by (metis Multiset.diff-cancel add.right-neutral diff-single-eq-union
    diff-single-trivial zero-diff)

lemma size-mset-le-2-cases:
  assumes size W  $\leq$  2
  shows  $W = \{\#\} \vee (\exists a. W = \{\#a\}) \vee (\exists a \ b. W = \{\#a, b\})$ 
  by (metis One-nat-def Suc-1 Suc-eq-plus1-left assms linorder-not-less nat-less-le
    not-less-eq-eq le-iff-add size-1-singleton-mset
    size-eq-0-iff-empty size-mset-2)

lemma filter-sorted-list-of-multiset-eqD:
  assumes  $[x \leftarrow \text{sorted-list-of-multiset } A. p \ x] = x \ \# \ xs$  (is ?comp = -)

```

```

shows  $x \in \# A$ 
proof -
  have  $x \in \text{set } ?comp$ 
    using assms by simp
  then have  $x \in \text{set } (\text{sorted-list-of-multiset } A)$ 
    by simp
  then show  $x \in \# A$ 
    by simp
qed

lemma clause-rewatch-witness':
  assumes
    wf: wf-twl-cls (trail S) C and
    n-d: no-dup (raw-trail S) and
    undef: undefined-lit (trail S) (lit-of L)
  shows wf-twl-cls ( $L \# \text{trail } S$ ) (rewatch-nat (lit-of L) S C)
proof (cases - lit-of L  $\in \text{set } (\text{watched } C)$ )
  case False
  then show ?thesis
    apply (cases C)
    using wf n-d undef unfolding rewatch-nat-def
    by (auto simp: uminus-lit-swap Marked-Propagated-in-iff-in-lits-of-l comp-def)
next
  case falsified: True

  let ?unwatched-nonfalsified =
    [ $L' \leftarrow \text{unwatched } C. L' \notin \text{set } (\text{watched } C) \wedge - L' \notin \text{insert } (\text{lit-of } L) (\text{lits-of-l } (\text{trail } S))$ ]
  obtain W UW where C:  $C = \text{TWL-Clause } W UW$ 
    by (cases C)

  show ?thesis
proof (cases ?unwatched-nonfalsified)
  case Nil
  show ?thesis
    using falsified Nil
    apply (simp only: wf-twl-cl.simps if-True list.cases C rewatch-nat-def)
    apply (intro conjI)
    proof goal-cases
      case 1
      then show ?case using wf C by simp
    next
      case 2
      then show ?case using wf C by simp
    next
      case 3
      then show ?case using wf C by simp
    next
      case 4
      have  $\bigwedge p l. \text{filter } p (\text{unwatched } C) \neq [] \vee l \notin \text{set } UW \vee \neg p l$ 
        unfolding C by (metis (no-types) filter-empty-conv twl-clause.sel(2))
      then show ?case
        using 4(2) C by auto
    next
      case 5
      then show ?case

```



```

    using wf by (fastforce simp add: C comp-def uminus-lit-swap)
  qed
next
case (Cons L' Ls)
show ?thesis
  unfolding rewatch-nat-def
  using falsified Cons
  apply (simp only: wf-twl-cls.simps if-True list.cases C)
  apply (intro conjI)
  proof goal-cases
    case 1
    have distinct (watched (TWL-Clause W UW))
      using wf unfolding C by auto
    moreover have  $L' \notin \text{set } (\text{remove1 } (-\text{lit-of } L) (\text{watched } (TWL-Clause W UW)))$ 
      using 1(2) not-gr0 by (fastforce dest: filter-in-list-prop-verifiedD in-diffD)
    ultimately show ?case
      by (auto simp: distinct-mset-single-add)
  next
    case 2
    have f2:  $[l \leftarrow \text{unwatched } (TWL-Clause W UW) . l \notin \text{set } (\text{watched } (TWL-Clause W UW)) \wedge -l \notin \text{insert } (\text{lit-of } L) (\text{lits-of-l } (\text{trail } S))] \neq []$ 
      using 2(2) by simp
    then have  $\neg \text{set } UW \subseteq \text{set } W$ 
      using 2 by (auto simp add: filter-empty-conv)
    then show ?case
      using wf C 2(1) by (auto simp: length-remove1)
  next
    case 3
    have  $W: \text{length } W \leq \text{Suc } 0 \longleftrightarrow \text{length } W = 0 \vee \text{length } W = \text{Suc } 0$ 
      by linarith
    show ?case
      using wf C 3 by (auto simp: length-remove1 W length-list-Suc-0 dest!: subset-singletonD)
  next
    case 4
    have H:  $\forall L \in \text{set } W. -L \in \text{lits-of-l } (\text{trail } S) \longrightarrow (\forall L' \in \text{set } UW. L' \notin \text{set } W \longrightarrow -L' \in \text{lits-of-l } (\text{trail } S))$ 
      using wf by (auto simp: C)
    have  $W: \text{length } W \leq 2$  and  $W-UW: \text{length } W < 2 \longrightarrow \text{set } UW \subseteq \text{set } W$ 
      using wf by (auto simp: C)
    have distinct: distinct W
      using wf by (auto simp: C)
    show ?case
      using 4
      unfolding C watched-decided-most-recently.simps Ball-def twl-clause.sel
      apply (intro allI impI)
      apply (rename-tac xW xUW)
      apply (case-tac - lit-of L = xW; case-tac xW = xUW; case-tac L' = xW)
      apply (auto simp: uminus-lit-swap)[2]
      apply (force dest: filter-in-list-prop-verifiedD)
      using H distinct apply (fastforce split: if-split-asm)
      using distinct apply (fastforce split: if-split-asm)
      using distinct apply (fastforce split: if-split-asm)
      apply (force dest: filter-in-list-prop-verifiedD)
      using H by (auto simp: uminus-lit-swap)
  next

```

```

case 5
have H:  $\forall x. x \in \text{set } W \longrightarrow \neg x \in \text{lits-of-l } (\text{trail } S) \longrightarrow (\forall x. x \in \text{set } UW \longrightarrow x \notin \text{set } W \longrightarrow \neg x \in \text{lits-of-l } (\text{trail } S))$ 
using wf by (auto simp: C)
show ?case
unfolding C watched-decided-most-recently.simps Ball-def
proof (intro allI impI conjI, goal-cases)
case (1 xW x)
show ?case
proof (cases  $\neg \text{lit-of } L = xW$ )
case True
then show ?thesis
by (cases  $xW = x$ ) (auto simp: uminus-lit-swap)
next
case False note LxW = this
have f9:  $L' \in \text{set } [l \leftarrow \text{unwatched } C. l \notin \text{set } (\text{watched } (TWL\text{-Clause } W UW)) \wedge \neg l \in \text{lits-of-l } (L \# \text{trail } S)]$ 
using 1(2) 5 C by auto
moreover then have f11:  $\neg xW \in \text{lits-of-l } (\text{trail } S)$ 
using 1(3) LxW by (auto simp: uminus-lit-swap)
moreover then have  $xW \notin \text{set } W$ 
using f9 1(2) H by (auto simp: C)
ultimately have False
using 1 by auto
then show ?thesis
by fast
qed
qed
qed
qed
qed

```

```

interpretation twl: abstract-tw1 watch-nat rewatch-nat raw-learned-clss
apply unfold-locales
apply (rule clause-watch-nat; simp add: image-image comp-def)
apply (rule wf-watch-nat; simp add: image-image comp-def)
apply (rule clause-rewatch-nat)
apply (rule clause-rewatch-witness'; simp add: image-image comp-def)
apply (simp)
done

```

```

interpretation twl2: abstract-tw1 watch-nat rewatch-nat  $\lambda\cdot$ . []
apply unfold-locales
apply (rule clause-watch-nat; simp add: image-image comp-def)
apply (rule wf-watch-nat; simp add: image-image comp-def)
apply (rule clause-rewatch-nat)
apply (rule clause-rewatch-witness'; simp add: image-image comp-def)
apply (simp)
done

```

```

end

```

## 25 Invariants for 2 Watched-Literals

```
theory CDCL-Two-Watched-Literals-Invariant
imports CDCL-Two-Watched-Literals DPLL-CDCL-W-Implementation
begin
```

### 25.1 Interpretation for *conflict-driven-clause-learning<sub>W</sub>.cdcl<sub>W</sub>*

We define here the 2-WL with the invariant and show the role of the candidates.

```
context abstract-twl
begin
```

#### 25.1.1 Direct Interpretation

```
lemma mset-map-removeAll-cond:
  mset (map (λx. mset (raw-clause x))
    (removeAll-cond (λD. mset (raw-clause D) = mset (raw-clause C)) N))
= mset (removeAll (mset (raw-clause C)) (map (λx. mset (raw-clause x)) N))
by (induction N) auto
```

```
lemma mset-raw-init-clss-init-state:
  mset (map (λx. mset (raw-clause x)) (raw-init-clss (init-state (map raw-clause N))))
= mset (map (λx. mset (raw-clause x)) N)
by (metis (no-types, lifting) init-clss-init-state map-eq-conv map-map o-def)
```

```
interpretation rough-cdcl: stateW
  λC. mset (raw-clause C)
```

```
  λL C. TWL-Clause (watched C) (L # unwatched C)
  λL C. TWL-Clause [] (remove1 L (raw-clause C))
  λC. clauses-of-l (map raw-clause C) op @
  λL C. L ∈ set C op # λC. remove1-cond (λD. mset (raw-clause D) = mset (raw-clause C))
```

```
  mset λxs ys. case-prod append (fold (λx (ys, zs). (remove1 x ys, x # zs)) xs (ys, []))
  op # remove1
```

```
  raw-clause λC. TWL-Clause [] C
  trail λS. hd (raw-trail S)
  raw-init-clss raw-learned-clss backtrack-lvl raw-conflicting
  cons-trail tl-trail λC. add-init-cls (raw-clause C) λC. add-learned-cls (raw-clause C)
  λC. remove-cls (raw-clause C)
  update-backtrack-lvl
  update-conflicting λN. init-state (map raw-clause N) restart'
  apply unfold-locales
  apply (case-tac raw-trail S)
  apply (simp-all add: add-init-cls-def add-learned-cls-def clause-rewatch clause-watch
    cons-trail-def remove-cls-def restart'-def tl-trail-def map-tl comp-def
    ac-simps mset-map-removeAll-cond mset-raw-init-clss-init-state)
```

```
  apply (auto simp: mset-map image-mset-subseteq-mono[OF restart-learned] )
done
```

```
interpretation rough-cdcl: conflict-driven-clause-learningW
  λC. mset (raw-clause C)
```

$\lambda L C. \text{TWL-Clause } (\text{watched } C) (L \# \text{unwatched } C)$   
 $\lambda L C. \text{TWL-Clause } [] (\text{remove1 } L (\text{raw-clause } C))$   
 $\lambda C. \text{clauses-of-l } (\text{map raw-clause } C) \text{ op } @$   
 $\lambda L C. L \in \text{set } C \text{ op } \# \lambda C. \text{remove1-cond } (\lambda D. \text{mset } (\text{raw-clause } D) = \text{mset } (\text{raw-clause } C))$

$\text{mset } \lambda xs \text{ ys. case-prod append } (\text{fold } (\lambda x (ys, zs). (\text{remove1 } x \text{ ys}, x \# zs)) \text{ xs } (ys, []))$   
 $\text{op } \# \text{remove1}$

$\lambda C. \text{raw-clause } C \lambda C. \text{TWL-Clause } [] C$   
 $\text{trail } \lambda S. \text{hd } (\text{raw-trail } S)$   
 $\text{raw-init-clss raw-learned-clss backtrack-lvl raw-conflicting}$   
 $\text{cons-trail tl-trail } \lambda C. \text{add-init-cls } (\text{raw-clause } C) \lambda C. \text{add-learned-cls } (\text{raw-clause } C)$   
 $\lambda C. \text{remove-cls } (\text{raw-clause } C)$   
 $\text{update-backtrack-lvl}$   
 $\text{update-conflicting } \lambda N. \text{init-state } (\text{map raw-clause } N) \text{ restart'}$   
**by** *unfold-locales*

**declare** *local.rough-cdcl.mset-ccls-ccls-of-clcs[simp del]*

### 25.1.2 Opaque Type with Invariant

**declare** *rough-cdcl.state-simp[simp del]*

**definition** *cons-trail-tw* :: ('v, nat, 'v twl-clause) marked-lit  $\Rightarrow$  'v wf-tw  $\Rightarrow$  'v wf-tw  
**where**  
*cons-trail-tw* L S  $\equiv$  twl-of-rough-state (cons-trail L (rough-state-of-tw S))

**lemma** *wf-tw-state-cons-trail*:

**assumes**

*undef*: undefined-lit (trail S) (lit-of L) **and**

*wf*: wf-tw-state S

**shows** wf-tw-state (cons-trail L S)

**using** *undef wf wf-rewatch[of S mset-of-mlit' L]* **unfolding** *wf-tw-state-def Ball-def*

**by** (auto simp: cons-trail-def defined-lit-map comp-def image-def twl.raw-clauses-def)

**lemma** *rough-state-of-tw-cons-trail*:

undefined-lit (trail-tw S) (lit-of L)  $\implies$

rough-state-of-tw (cons-trail-tw L S) = cons-trail L (rough-state-of-tw S)

**using** *rough-state-of-tw twl-of-rough-state-inverse wf-tw-state-cons-trail*

**unfolding** *cons-trail-tw-def* **by** blast

**abbreviation** *add-init-cls-tw* **where**

*add-init-cls-tw* C S  $\equiv$  twl-of-rough-state (add-init-cls C (rough-state-of-tw S))

**lemma** *wf-tw-add-init-clcs*: wf-tw-state S  $\implies$  wf-tw-state (add-init-cls L S)

**unfolding** *wf-tw-state-def* **by** (auto simp: wf-watch add-init-clcs-def comp-def twl.raw-clauses-def split: if-split-asm)

**lemma** *rough-state-of-tw-add-init-clcs*:

rough-state-of-tw (add-init-cls-tw L S) = add-init-cls L (rough-state-of-tw S)

**using** *rough-state-of-tw twl-of-rough-state-inverse wf-tw-add-init-clcs* **by** blast

**abbreviation** *add-learned-clcs-tw* **where**

*add-learned-clcs-tw* C S  $\equiv$  twl-of-rough-state (add-learned-clcs C (rough-state-of-tw S))

**lemma** *wf-tw-add-learned-clcs*: wf-tw-state S  $\implies$  wf-tw-state (add-learned-clcs L S)

**unfolding** *wf-twl-state-def* **by** (*auto simp: wf-watch add-learned-cls-def twl.raw-clauses-def split: if-split-asm*)

**lemma** *rough-state-of-twl-add-learned-cls:*  
*rough-state-of-twl (add-learned-cls-twl L S) = add-learned-cls L (rough-state-of-twl S)*  
**using** *rough-state-of-twl twl-of-rough-state-inverse wf-twl-add-learned-cls* **by** *blast*

**abbreviation** *remove-cls-twl* **where**  
*remove-cls-twl C S  $\equiv$  twl-of-rough-state (remove-cls C (rough-state-of-twl S))*

**lemma** *set-removeAll-condD:*  $x \in \text{set } (\text{removeAll-cond } f \text{ } xs) \implies x \in \text{set } xs$   
**by** (*induction xs*) (*auto split: if-split-asm*)

**lemma** *wf-twl-remove-cls:*  $\text{wf-twl-state } S \implies \text{wf-twl-state } (\text{remove-cls } L \text{ } S)$   
**unfolding** *wf-twl-state-def* **by** (*auto simp: wf-watch remove-cls-def twl.raw-clauses-def comp-def split: if-split-asm dest: set-removeAll-condD*)

**lemma** *rough-state-of-twl-remove-cls:*  
*rough-state-of-twl (remove-cls-twl L S) = remove-cls L (rough-state-of-twl S)*  
**using** *rough-state-of-twl twl-of-rough-state-inverse wf-twl-remove-cls* **by** *blast*

**abbreviation** *init-state-twl* **where**  
*init-state-twl N  $\equiv$  twl-of-rough-state (init-state N)*

**lemma** *wf-twl-state-wf-twl-state-fold-add-init-cls:*  
**assumes** *wf-twl-state S*  
**shows** *wf-twl-state (fold add-init-cls N S)*  
**using** *assms* **apply** (*induction N arbitrary: S*)  
**apply** (*auto simp: wf-twl-state-def*)  
**by** (*simp add: wf-twl-add-init-cls*)

**lemma** *wf-twl-state-epsilon-state[simp]:*  
*wf-twl-state (TWL-State [] [] 0 None)*  
**by** (*auto simp: wf-twl-state-def twl.raw-clauses-def*)

**lemma** *wf-twl-init-state:*  $\text{wf-twl-state } (\text{init-state } N)$   
**unfolding** *init-state-def* **by** (*auto intro!: wf-twl-state-wf-twl-state-fold-add-init-cls*)

**lemma** *rough-state-of-twl-init-state:*  
*rough-state-of-twl (init-state-twl N) = init-state N*  
**by** (*simp add: twl-of-rough-state-inverse wf-twl-init-state*)

**abbreviation** *tl-trail-twl* **where**  
*tl-trail-twl S  $\equiv$  twl-of-rough-state (tl-trail (rough-state-of-twl S))*

**lemma** *wf-twl-state-tl-trail:*  $\text{wf-twl-state } S \implies \text{wf-twl-state } (\text{tl-trail } S)$   
**by** (*auto simp add: twl-of-rough-state-inverse wf-twl-init-state wf-twl-cls-wf-twl-cls-tl tl-trail-def wf-twl-state-def distinct-tl map-tl comp-def twl.raw-clauses-def*)

**lemma** *rough-state-of-twl-tl-trail:*  
*rough-state-of-twl (tl-trail-twl S) = tl-trail (rough-state-of-twl S)*  
**using** *rough-state-of-twl twl-of-rough-state-inverse wf-twl-state-tl-trail* **by** *blast*

**abbreviation** *update-backtrack-lvl-twl* **where**  
*update-backtrack-lvl-twl k S  $\equiv$  twl-of-rough-state (update-backtrack-lvl k (rough-state-of-twl S))*

**lemma** *wf-twl-state-update-backtrack-lvl*:

*wf-twl-state*  $S \implies \text{wf-twl-state } (\text{update-backtrack-lvl } k \ S)$

**unfolding** *wf-twl-state-def* **by** (*auto simp: comp-def twl.raw-clauses-def*)

**lemma** *rough-state-of-twl-update-backtrack-lvl*:

*rough-state-of-twl* (*update-backtrack-lvl-twl*  $k \ S$ ) = *update-backtrack-lvl*  $k$   
(*rough-state-of-twl*  $S$ )

**using** *rough-state-of-twl twl-of-rough-state-inverse wf-twl-state-update-backtrack-lvl* **by** *fast*

**abbreviation** *update-conflicting-twl* **where**

*update-conflicting-twl*  $k \ S \equiv \text{twl-of-rough-state } (\text{update-conflicting } k \ (\text{rough-state-of-twl } S))$

**lemma** *wf-twl-state-update-conflicting*:

*wf-twl-state*  $S \implies \text{wf-twl-state } (\text{update-conflicting } k \ S)$

**unfolding** *wf-twl-state-def* **by** (*auto simp: twl.raw-clauses-def comp-def*)

**lemma** *rough-state-of-twl-update-conflicting*:

*rough-state-of-twl* (*update-conflicting-twl*  $k \ S$ ) = *update-conflicting*  $k$   
(*rough-state-of-twl*  $S$ )

**using** *rough-state-of-twl twl-of-rough-state-inverse wf-twl-state-update-conflicting* **by** *fast*

**abbreviation** *raw-clauses-twl* **where**

*raw-clauses-twl*  $S \equiv \text{twl.raw-clauses } (\text{rough-state-of-twl } S)$

**abbreviation** *restart-twl* **where**

*restart-twl*  $S \equiv \text{twl-of-rough-state } (\text{restart}' \ (\text{rough-state-of-twl } S))$

**lemma** *mset-union-mset-setD*:

*mset*  $A \subseteq\# \text{ mset } B \implies \text{set } A \subseteq \text{set } B$

**by** *auto*

**lemma** *wf-wf-restart'*: *wf-twl-state*  $S \implies \text{wf-twl-state } (\text{restart}' \ S)$

**unfolding** *restart'-def wf-twl-state-def* **apply** *standard*

**apply** *clarify*

**apply** (*rename-tac*  $x$ )

**apply** (*subgoal-tac wf-twl-cls* (*trail*  $S$ )  $x$ )

**apply** (*case-tac*  $x$ )

**using** *restart-learned* **by** (*auto simp: twl.raw-clauses-def comp-def dest: mset-union-mset-setD*)

**lemma** *rough-state-of-twl-restart-twl*:

*rough-state-of-twl* (*restart-twl*  $S$ ) = *restart'* (*rough-state-of-twl*  $S$ )

**by** (*simp add: twl-of-rough-state-inverse wf-wf-restart'*)

**sublocale** *conflict-driven-clause-learning<sub>W</sub>*

$\lambda C. \text{ mset } (\text{raw-clause } C)$

$\lambda L \ C. \text{ TWL-Clause } (\text{watched } C) \ (L \ \# \ \text{unwatched } C)$

$\lambda L \ C. \text{ TWL-Clause } [] \ (\text{remove1 } L \ (\text{raw-clause } C))$

$\lambda C. \text{ clauses-of-l } (\text{map raw-clause } C) \ \text{op } @$

$\lambda L \ C. \ L \in \text{set } C \ \text{op } \# \ \lambda C. \text{ remove1-cond } (\lambda D. \text{ mset } (\text{raw-clause } D) = \text{mset } (\text{raw-clause } C))$

*mset*  $\lambda xs \ ys. \text{ case-prod append } (\text{fold } (\lambda x \ (ys, zs). \ (\text{remove1 } x \ ys, x \ \# \ zs)) \ xs \ (ys, []))$

*op*  $\# \ \text{remove1}$

$\lambda C. \text{ raw-clause } C \ \lambda C. \text{ TWL-Clause } [] \ C$

```

trail-twl  $\lambda S$ . hd (raw-trail-twl S)
raw-init-clss-twl
raw-learned-clss-twl
backtrack-lvl-twl
raw-conflicting-twl
cons-trail-twl
tl-trail-twl
 $\lambda C$ . add-init-cls-twl (raw-clause C)
 $\lambda C$ . add-learned-cls-twl (raw-clause C)
 $\lambda C$ . remove-cls-twl (raw-clause C)
update-backtrack-lvl-twl
update-conflicting-twl
 $\lambda N$ . init-state-twl (map raw-clause N)
restart-twl
apply unfold-locales
  using rough-cdcl.hd-raw-trail apply blast
  apply (simp-all add: rough-state-of-twl-cons-trail rough-state-of-twl-tl-trail
    rough-state-of-twl-add-init-cls rough-state-of-twl-add-learned-cls
    rough-state-of-twl-remove-cls rough-state-of-twl-update-backtrack-lvl
    rough-state-of-twl-update-conflicting)[7]
  using rough-cdcl.init-clss-cons-trail rough-cdcl.init-clss-tl-trail
    rough-cdcl.init-clss-add-init-cls rough-cdcl.init-clss-remove-cls
    rough-cdcl.init-clss-add-learned-cls
    rough-cdcl.init-clss-update-backtrack-lvl
    rough-cdcl.init-clss-update-conflicting
  apply (auto simp add: rough-state-of-twl-cons-trail rough-state-of-twl-tl-trail
    rough-state-of-twl-add-init-cls rough-state-of-twl-add-learned-cls
    rough-state-of-twl-remove-cls rough-state-of-twl-update-backtrack-lvl
    rough-state-of-twl-update-conflicting comp-def)[7]
  using rough-cdcl.learned-clss-cons-trail rough-cdcl.learned-clss-tl-trail
    rough-cdcl.learned-clss-add-init-cls rough-cdcl.learned-clss-remove-cls
    rough-cdcl.learned-clss-add-learned-cls
    rough-cdcl.learned-clss-update-backtrack-lvl
    rough-cdcl.learned-clss-update-conflicting
  apply (auto simp add: rough-state-of-twl-cons-trail rough-state-of-twl-tl-trail
    rough-state-of-twl-add-init-cls rough-state-of-twl-add-learned-cls
    rough-state-of-twl-remove-cls rough-state-of-twl-update-backtrack-lvl
    rough-state-of-twl-update-conflicting comp-def)[7]
  apply (auto simp add: rough-state-of-twl-cons-trail rough-state-of-twl-tl-trail
    rough-state-of-twl-add-init-cls rough-state-of-twl-add-learned-cls
    rough-state-of-twl-remove-cls rough-state-of-twl-update-backtrack-lvl
    rough-state-of-twl-update-conflicting comp-def)[14]
  using init-clss-init-state apply (auto simp: rough-state-of-twl-init-state)[5]
using rough-cdcl.init-clss-restart-state rough-cdcl.learned-clss-restart-state
apply (auto simp: rough-state-of-twl-restart-twl)[5]
done

declare local.rough-cdcl.mset-ccls-ccls-of-cls[simp del]
abbreviation state-eq-twl (infix  $\sim$  TWL 51) where
state-eq-twl S S'  $\equiv$  rough-cdcl.state-eq (rough-state-of-twl S) (rough-state-of-twl S')
notation state-eq (infix  $\sim$  51)
declare state-simp[simp del]

```

To avoid ambiguities:

**no-notation** state-eq-twl (**infix**  $\sim$  51)

**inductive** *propagate-twl* :: 'v wf-twl  $\Rightarrow$  'v wf-twl  $\Rightarrow$  bool **where**  
*propagate-twl-rule*:  $(L, C) \in \text{candidates-propagate-twl } S \Rightarrow$   
 $S' \sim \text{cons-trail-twl } (\text{Propagated } L \ C) \ S \Rightarrow$   
 $\text{raw-conflicting-twl } S = \text{None} \Rightarrow$   
 $\text{propagate-twl } S \ S'$

**inductive-cases** *propagate-twlE*: *propagate-twl* *S* *T*  
**thm** *propagateE*

**lemma** *distinct-filter-eq-if*:  
 $\text{distinct } C \Rightarrow \text{length } (\text{filter } (\text{op} = L) \ C) = (\text{if } L \in \text{set } C \text{ then } 1 \text{ else } 0)$   
**by** (*induction* *C*) *auto*

**lemma** *distinct-mset-remove1-All*:  
 $\text{distinct-mset } C \Rightarrow \text{remove1-mset } L \ C = \text{removeAll-mset } L \ C$   
**by** (*auto simp: multiset-eq-iff distinct-mset-count-less-1*)

**lemma** *propagate-twl-iff-propagate*:  
**assumes** *inv*: *cdcl<sub>W</sub>-all-struct-inv* *S*  
**shows** *propagate* *S* *T*  $\longleftrightarrow$  *propagate-twl* *S* *T* (**is** ?*P*  $\longleftrightarrow$  ?*T*)

**proof**

**assume** ?*P*

**then obtain** *L* *E* **where**

*raw-conflicting-twl* *S* = *None* **and**

*CL-Clauses*:  $E \in \text{set } (\text{twl.raw-clauses } S)$  **and**

*LE*:  $L \in \# \text{ mset } (\text{raw-clause } E)$  **and**

*tr-CNot*:  $\text{trail-twl } S \models \text{as } C\text{Not } (\text{remove1-mset } L \ (\text{mset } (\text{raw-clause } E)))$  **and**

*undef-lot*[*simp*]: *undefined-lit* (*trail-twl* *S*) *L* **and**

$T \sim \text{cons-trail-twl } (\text{Propagated } L \ E) \ S$

**by** (*blast elim: propagateE*)

**have** *distinct* (*raw-clause* *E*)

**using** *inv* *CL-Clauses* **unfolding** *cdcl<sub>W</sub>-all-struct-inv-def* *distinct-mset-set-def*

*distinct-cdcl<sub>W</sub>-state-def* *raw-clauses-def* **by** *auto*

**then have** *X*:  $\text{remove1-mset } L \ (\text{mset } (\text{raw-clause } E)) = \text{mset-set } (\text{set } (\text{raw-clause } E) - \{L\})$

**by** (*auto simp: multiset-eq-iff raw-clause-def count-mset distinct-filter-eq-if*)

**have**  $(L, E) \in \text{candidates-propagate-twl } S$

**apply** (*rule* *wf-candidates-propagate-complete*)

**using** *rough-state-of-twl* **apply** *auto*[]

**using** *CL-Clauses* **unfolding** *raw-clauses-def* *twl.raw-clauses-def*

**apply** *auto*[]

**using** *LE* **apply** *simp*

**using** *tr-CNot* *X* **apply** *simp*

**using** *undef-lot* **apply** *blast*

**done**

**show** ?*T*

**apply** (*rule* *propagate-twl-rule*)

**apply** (*rule*  $\langle (L, E) \in \text{candidates-propagate-twl } S \rangle$ )

**using**  $\langle T \sim \text{cons-trail-twl } (\text{Propagated } L \ E) \ S \rangle$

**apply** (*auto simp: raw-conflicting-twl* *S* = *None*) *twl.state-eq-def*)

**done**

**next**

**assume** ?*T*

**then obtain** *L* *C* **where**

*LC*:  $(L, C) \in \text{candidates-propagate-twl } S$  **and**



```

T: T ~ cons-trail-twl (Propagated L C) S and
confl: raw-conflicting-twl S = None
by (auto elim: propagate-twlE)
have
  C'S: C ∈ set (raw-clauses-twl S) and
  L: set (watched C) - uminus ' lits-of-l (trail-twl S) = {L} and
  undef: undefined-lit (trail-twl S) L
  using LC unfolding candidates-propagate-def raw-clauses-def by auto
have dist: distinct (raw-clause C)
  using inv C'S unfolding cdclW-all-struct-inv-def distinct-cdclW-state-def
  distinct-mset-set-def twl.raw-clauses-def by fastforce
then have C-L-L: mset-set (set (raw-clause C) - {L}) = mset (raw-clause C) - {#L#}
  by (metis distinct-mset-distinct distinct-mset-minus distinct-mset-set-mset-ident mset-remove1
    set-mset-mset set-remove1-eq)

show ?P
apply (rule propagate-rule[of S C L])
  using confl apply auto[]
  using C'S unfolding twl.raw-clauses-def apply (simp add: raw-clauses-def)
  using L unfolding candidates-propagate-def apply (auto simp: raw-clause-def)[]
  using wf-candidates-propagate-sound[OF - LC] rough-state-of-twl dist
  apply (simp add: distinct-mset-remove1-All)
  using undef apply simp
  using T undef by (smt backtrack-lvl-cons-trail confl init-clss-cons-trail
    learned-clss-cons-trail marked-lit.sel(2) raw-conflicting-cons-trail state-eq-def
    trail-cons-trail twl2.mmset-of-mlit.simps(1) twl2.mset-cls-cls-of-ccls)
qed

no-notation twl.state-eq-twl (infix ~TWL 51)

inductive conflict-twl where
  conflict-twl-rule:
    C ∈ candidates-conflict-twl S ⇒
    S' ~ update-conflicting-twl (Some (raw-clause C)) S ⇒
    raw-conflicting-twl S = None ⇒
    conflict-twl S S'

inductive-cases conflict-twlE: conflict-twl S T

lemma conflict-twl-iff-conflict:
  shows conflict S T ⟷ conflict-twl S T (is ?C ⟷ ?T)
proof
  assume ?C
  then obtain D where
    S: raw-conflicting-twl S = None and
    D: D ∈ set (raw-clauses S) and
    MD: trail-twl S ⊨as CNot (mset (raw-clause D)) and
    T: T ~ update-conflicting-twl (Some (raw-clause D)) S
  by (elim conflictE)

  have D ∈ candidates-conflict-twl S
  apply (rule wf-candidates-conflict-complete)
  apply simp
  using D apply (auto simp: raw-clauses-def twl.raw-clauses-def)[]
  using MD S by auto

```

```

moreover have  $T \sim \text{twl-of-rough-state } (\text{update-conflicting } (\text{Some } (\text{raw-clause } D)))$ 
 $(\text{rough-state-of-twl } S)$ 
using  $T$  unfolding  $\text{rough-cdcl.state-eq-def state-eq-def}$  by  $\text{auto}$ 
ultimately show  $?T$ 
using  $S$  by  $(\text{auto intro: conflict-twl-rule})$ 
next
assume  $?T$ 
then obtain  $C$  where
   $C: C \in \text{candidates-conflict-twl } S$  and
   $T: T \sim \text{update-conflicting-twl } (\text{Some } (\text{raw-clause } C)) \ S$  and
   $\text{confl: raw-conflicting-twl } S = \text{None}$ 
by  $(\text{auto elim: conflict-twlE})$ 
have
   $C \in \text{set } (\text{raw-clauses } S)$ 
using  $C$  unfolding  $\text{candidates-conflict-def raw-clauses-def twl.raw-clauses-def}$  by  $\text{auto}$ 
moreover have  $\text{trail-twl } S \models_{\text{as}} \text{CNot } (\text{mset } (\text{raw-clause } C))$ 
using  $\text{wf-candidates-conflict-sound}[OF - C]$  by  $\text{auto}$ 
ultimately show  $?C$  apply –
  apply  $(\text{rule conflict.conflict-rule}[of - C])$ 
using  $\text{confl } T$  unfolding  $\text{rough-cdcl.state-eq-def}$  by  $(\text{auto simp del: map-map})$ 
qed

```

**inductive**  $\text{cdcl}_W\text{-twl} :: 'v \text{ wf-twl} \Rightarrow 'v \text{ wf-twl} \Rightarrow \text{bool}$  **for**  $S :: 'v \text{ wf-twl}$  **where**  
 $\text{propagate: propagate-twl } S \ S' \Longrightarrow \text{cdcl}_W\text{-twl } S \ S' \mid$   
 $\text{conflict: conflict-twl } S \ S' \Longrightarrow \text{cdcl}_W\text{-twl } S \ S' \mid$   
 $\text{other: cdcl}_W\text{-o } S \ S' \Longrightarrow \text{cdcl}_W\text{-twl } S \ S' \mid$   
 $\text{rf: cdcl}_W\text{-rf } S \ S' \Longrightarrow \text{cdcl}_W\text{-twl } S \ S'$

**lemma**  $\text{cdcl}_W\text{-twl-iff-cdcl}_W$ :  
**assumes**  $\text{cdcl}_W\text{-all-struct-inv } S$   
**shows**  $\text{cdcl}_W\text{-twl } S \ T \longleftrightarrow \text{cdcl}_W \ S \ T$   
**by**  $(\text{simp add: assms cdcl}_W.\text{sims cdcl}_W\text{-twl.sims conflict-twl-iff-conflict}$   
 $\text{propagate-twl-iff-propagate del: map-map})$

**lemma**  $\text{rtranclp-cdcl}_W\text{-twl-all-struct-inv-inv}$ :  
**assumes**  $\text{cdcl}_W\text{-twl}^{**} \ S \ T$  **and**  $\text{cdcl}_W\text{-all-struct-inv } S$   
**shows**  $\text{cdcl}_W\text{-all-struct-inv } T$   
**using**  $\text{assms}$  **by**  $(\text{induction rule: rtranclp-induct})$   
 $(\text{simp-all add: cdcl}_W\text{-twl-iff-cdcl}_W \ \text{cdcl}_W\text{-all-struct-inv-inv del: map-map})$

**lemma**  $\text{rtranclp-cdcl}_W\text{-twl-iff-rtranclp-cdcl}_W$ :  
**assumes**  $\text{cdcl}_W\text{-all-struct-inv } S$   
**shows**  $\text{cdcl}_W\text{-twl}^{**} \ S \ T \longleftrightarrow \text{cdcl}_W^{**} \ S \ T$  **(is**  $?T \longleftrightarrow ?W$ **)**

**proof**  
**assume**  $?W$   
**then show**  $?T$   
**proof**  $(\text{induction rule: rtranclp-induct})$   
**case base**  
**then show**  $?case$  **by**  $\text{simp}$   
**next**  
**case**  $(\text{step } T \ U)$  **note**  $st = \text{this}(1)$  **and**  $cdcl = \text{this}(2)$  **and**  $IH = \text{this}(3)$   
**have**  $\text{cdcl}_W\text{-twl } T \ U$   
**using**  $\text{assms } st \ cdcl \ \text{rtranclp-cdcl}_W\text{-all-struct-inv-inv cdcl}_W\text{-twl-iff-cdcl}_W$   
**by**  $\text{blast}$   
**then show**  $?case$  **using**  $IH$  **by**  $\text{auto}$

```

    qed
next
assume ?T
then show ?W
  proof (induction rule: rtrancpl-induct)
    case base
    then show ?case by simp
  next
  case (step T U) note st = this(1) and cdcl = this(2) and IH = this(3)
  have cdclW T U
    using assms st cdcl rtrancpl-cdclW-twl-all-struct-inv-inv cdclW-twl-iff-cdclW
    by blast
  then show ?case using IH by auto
qed
qed

end

end
theory Prop-Superposition
imports Partial-Clausal-Logic ../lib/Herbrand-Interpretation
begin

```

## 26 Superposition

**no-notation** *Herbrand-Interpretation.true-cls* (**infix**  $\models$  50)

**notation** *Herbrand-Interpretation.true-cls* (**infix**  $\models_h$  50)

**no-notation** *Herbrand-Interpretation.true-clss* (**infix**  $\models_s$  50)

**notation** *Herbrand-Interpretation.true-clss* (**infix**  $\models_{hs}$  50)

**lemma** *herbrand-interp-iff-partial-interp-cls*:

$S \models_h C \longleftrightarrow \{Pos\ P|P. P \in S\} \cup \{Neg\ P|P. P \notin S\} \models C$

**unfolding** *Herbrand-Interpretation.true-cls-def Partial-Clausal-Logic.true-cls-def*  
**by** *auto*

**lemma** *herbrand-consistent-interp*:

*consistent-interp*  $(\{Pos\ P|P. P \in S\} \cup \{Neg\ P|P. P \notin S\})$

**unfolding** *consistent-interp-def* **by** *auto*

**lemma** *herbrand-total-over-set*:

*total-over-set*  $(\{Pos\ P|P. P \in S\} \cup \{Neg\ P|P. P \notin S\})\ T$

**unfolding** *total-over-set-def* **by** *auto*

**lemma** *herbrand-total-over-m*:

*total-over-m*  $(\{Pos\ P|P. P \in S\} \cup \{Neg\ P|P. P \notin S\})\ T$

**unfolding** *total-over-m-def* **by** (*auto simp add: herbrand-total-over-set*)

**lemma** *herbrand-interp-iff-partial-interp-clss*:

$S \models_{hs} C \longleftrightarrow \{Pos\ P|P. P \in S\} \cup \{Neg\ P|P. P \notin S\} \models_s C$

**unfolding** *true-clss-def Ball-def herbrand-interp-iff-partial-interp-cls*  
*Partial-Clausal-Logic.true-clss-def* **by** *auto*

**definition** *clss-lt* :: '*a*::wellorder clauses  $\Rightarrow$  '*a* clause  $\Rightarrow$  '*a* clauses **where**

*clss-lt*  $N\ C = \{D \in N. D \# \subset \# C\}$

**notation** (*latex output*)  
*class-lt* ( $\text{<}\wedge^{\text{bsup}}\text{>}\text{<}\wedge^{\text{esup}}\text{>}$ )

**locale** *selection* =  
**fixes**  $S :: 'a \text{ clause} \Rightarrow 'a \text{ clause}$   
**assumes**  
 $S\text{-selects-subseteq}: \bigwedge C. S\ C \leq\# C$  **and**  
 $S\text{-selects-neg-lits}: \bigwedge C\ L. L \in\# S\ C \Longrightarrow \text{is-neg } L$

**locale** *ground-resolution-with-selection* =  
*selection*  $S$  **for**  $S :: ('a :: \text{wellorder}) \text{ clause} \Rightarrow 'a \text{ clause}$   
**begin**

**context**  
**fixes**  $N :: 'a \text{ clause set}$   
**begin**

We do not create an equivalent of  $\delta$ , but we directly defined  $N_C$  by inlining the definition.

**function**  
 $\text{production} :: 'a \text{ clause} \Rightarrow 'a \text{ interp}$   
**where**  
 $\text{production } C =$   
 $\{A. C \in N \wedge C \neq \{\#\} \wedge \text{Max } (\text{set-mset } C) = \text{Pos } A \wedge \text{count } C\ (\text{Pos } A) \leq 1$   
 $\wedge \neg (\bigcup D \in \{D. D \# \subset\# C\}. \text{production } D) \models_h C \wedge S\ C = \{\#\}\}$   
**by** *auto*  
**termination by** (*relation*  $\{(D, C). D \# \subset\# C\}$ ) (*auto simp: wf-less-multiset*)

**declare**  $\text{production.simps}[\text{simp del}]$

**definition**  $\text{interp} :: 'a \text{ clause} \Rightarrow 'a \text{ interp}$  **where**  
 $\text{interp } C = (\bigcup D \in \{D. D \# \subset\# C\}. \text{production } D)$

**lemma** *production-unfold*:  
 $\text{production } C = \{A. C \in N \wedge C \neq \{\#\} \wedge \text{Max } (\text{set-mset } C) = \text{Pos } A \wedge \text{count } C\ (\text{Pos } A) \leq 1 \wedge \neg$   
 $\text{interp } C \models_h C \wedge S\ C = \{\#\}\}$   
**unfolding** *interp-def* **by** (*rule*  $\text{production.simps}$ )

**abbreviation**  $\text{productive } A \equiv (\text{production } A \neq \{\})$

**abbreviation**  $\text{produces} :: 'a \text{ clause} \Rightarrow 'a \Rightarrow \text{bool}$  **where**  
 $\text{produces } C\ A \equiv \text{production } C = \{A\}$

**lemma** *producesD*:  
 $\text{produces } C\ A \Longrightarrow C \in N \wedge C \neq \{\#\} \wedge \text{Pos } A = \text{Max } (\text{set-mset } C) \wedge \text{count } C\ (\text{Pos } A) \leq 1 \wedge$   
 $\neg \text{interp } C \models_h C \wedge S\ C = \{\#\}$   
**unfolding** *production-unfold* **by** *auto*

**lemma**  $\text{produces } C\ A \Longrightarrow \text{Pos } A \in\# C$   
**by** (*simp add: Max-in-lits producesD*)

**lemma** *interp'-def-in-set*:  
 $\text{interp } C = (\bigcup D \in \{D \in N. D \# \subset\# C\}. \text{production } D)$   
**unfolding** *interp-def* **apply** *auto*  
**unfolding** *production-unfold* **apply** *auto*

done

**lemma** *production-iff-produces*:  
produces  $D$   $A \longleftrightarrow A \in \text{production } D$   
**unfolding** *production-unfold* **by** *auto*

**definition** *Interp* :: 'a clause  $\Rightarrow$  'a interp **where**  
*Interp*  $C = \text{interp } C \cup \text{production } C$

**lemma**  
assumes *produces*  $C$   $P$   
shows *Interp*  $C \models_h C$   
**unfolding** *Interp-def* *assms* **using** *producesD*[*OF* *assms*]  
**by** (*metis* *Max-in-lits* *Un-insert-right* *insertI1* *pos-literal-in-imp-true-cls*)

**definition** *INTERP* :: 'a interp **where**  
*INTERP*  $= (\bigcup D \in N. \text{production } D)$

**lemma** *interp-subseteq-Interp*[*simp*]: *interp*  $C \subseteq \text{Interp } C$   
**unfolding** *Interp-def* **by** *simp*

**lemma** *Interp-as-UNION*: *Interp*  $C = (\bigcup D \in \{D. D \# \subseteq \# C\}. \text{production } D)$   
**unfolding** *Interp-def* *interp-def* *le-multiset-def* **by** *fast*

**lemma** *productive-not-empty*: *productive*  $C \Longrightarrow C \neq \{\#\}$   
**unfolding** *production-unfold* **by** *auto*

**lemma** *productive-imp-produces-Max-literal*: *productive*  $C \Longrightarrow \text{produces } C (\text{atm-of } (\text{Max } (\text{set-mset } C)))$   
**unfolding** *production-unfold* **by** (*auto* *simp* *del*: *atm-of-Max-lit*)

**lemma** *productive-imp-produces-Max-atom*: *productive*  $C \Longrightarrow \text{produces } C (\text{Max } (\text{atms-of } C))$   
**unfolding** *atms-of-def* *Max-atm-of-set-mset-commute*[*OF* *productive-not-empty*]  
**by** (*rule* *productive-imp-produces-Max-literal*)

**lemma** *produces-imp-Max-literal*: *produces*  $C$   $A \Longrightarrow A = \text{atm-of } (\text{Max } (\text{set-mset } C))$   
**by** (*metis* *Max-singleton* *insert-not-empty* *productive-imp-produces-Max-literal*)

**lemma** *produces-imp-Max-atom*: *produces*  $C$   $A \Longrightarrow A = \text{Max } (\text{atms-of } C)$   
**by** (*metis* *Max-singleton* *insert-not-empty* *productive-imp-produces-Max-atom*)

**lemma** *produces-imp-Pos-in-lits*: *produces*  $C$   $A \Longrightarrow \text{Pos } A \in \# C$   
**by** (*auto* *intro*: *Max-in-lits* *dest*!: *producesD*)

**lemma** *productive-in-N*: *productive*  $C \Longrightarrow C \in N$   
**unfolding** *production-unfold* **by** *auto*

**lemma** *produces-imp-atms-leq*: *produces*  $C$   $A \Longrightarrow B \in \text{atms-of } C \Longrightarrow B \leq A$   
**by** (*metis* *Max-ge* *finite-atms-of* *insert-not-empty* *productive-imp-produces-Max-atom* *singleton-inject*)

**lemma** *produces-imp-neg-notin-lits*: *produces*  $C$   $A \Longrightarrow \neg \text{Neg } A \in \# C$   
**by** (*rule* *pos-Max-imp-neg-notin*) (*auto* *dest*: *producesD*)

**lemma** *less-eq-imp-interp-subseteq-interp*:  $C \# \subseteq \# D \Longrightarrow \text{interp } C \subseteq \text{interp } D$

**unfolding** *interp-def* **by** *auto* (*metis multiset-order.order.strict-trans2*)

**lemma** *less-eq-imp-interp-subseteq-Interp*:  $C \# \subseteq \# D \implies \text{interp } C \subseteq \text{Interp } D$   
**unfolding** *Interp-def* **using** *less-eq-imp-interp-subseteq-interp* **by** *blast*

**lemma** *less-imp-production-subseteq-interp*:  $C \# \subset \# D \implies \text{production } C \subseteq \text{interp } D$   
**unfolding** *interp-def* **by** *fast*

**lemma** *less-eq-imp-production-subseteq-Interp*:  $C \# \subseteq \# D \implies \text{production } C \subseteq \text{Interp } D$   
**unfolding** *Interp-def* **using** *less-imp-production-subseteq-interp*  
**by** (*metis multiset-order.le-imp-less-or-eq le-supI1 sup-ge2*)

**lemma** *less-imp-Interp-subseteq-interp*:  $C \# \subset \# D \implies \text{Interp } C \subseteq \text{interp } D$   
**unfolding** *Interp-def*  
**by** (*auto simp: less-eq-imp-interp-subseteq-interp less-imp-production-subseteq-interp*)

**lemma** *less-eq-imp-Interp-subseteq-Interp*:  $C \# \subseteq \# D \implies \text{Interp } C \subseteq \text{Interp } D$   
**using** *less-imp-Interp-subseteq-interp*  
**unfolding** *Interp-def* **by** (*metis multiset-order.le-imp-less-or-eq le-supI2 subset-refl sup-commute*)

**lemma** *false-Interp-to-true-interp-imp-less-multiset*:  $A \notin \text{Interp } C \implies A \in \text{interp } D \implies C \# \subset \# D$   
**using** *less-eq-imp-interp-subseteq-Interp multiset-linorder.not-less* **by** *blast*

**lemma** *false-interp-to-true-interp-imp-less-multiset*:  $A \notin \text{interp } C \implies A \in \text{interp } D \implies C \# \subset \# D$   
**using** *less-eq-imp-interp-subseteq-interp multiset-linorder.not-less* **by** *blast*

**lemma** *false-Interp-to-true-Interp-imp-less-multiset*:  $A \notin \text{Interp } C \implies A \in \text{Interp } D \implies C \# \subset \# D$   
**using** *less-eq-imp-Interp-subseteq-Interp multiset-linorder.not-less* **by** *blast*

**lemma** *false-interp-to-true-Interp-imp-le-multiset*:  $A \notin \text{interp } C \implies A \in \text{Interp } D \implies C \# \subseteq \# D$   
**using** *less-imp-Interp-subseteq-interp multiset-linorder.not-less* **by** *blast*

**lemma** *interp-subseteq-INTERP*:  $\text{interp } C \subseteq \text{INTERP}$   
**unfolding** *interp-def INTERP-def* **by** (*auto simp: production-unfold*)

**lemma** *production-subseteq-INTERP*:  $\text{production } C \subseteq \text{INTERP}$   
**unfolding** *INTERP-def* **using** *production-unfold* **by** *blast*

**lemma** *Interp-subseteq-INTERP*:  $\text{Interp } C \subseteq \text{INTERP}$   
**unfolding** *Interp-def* **by** (*auto intro!: interp-subseteq-INTERP production-subseteq-INTERP*)

This lemma corresponds to theorem 2.7.6 page 66 of CW.

**lemma** *produces-imp-in-interp*:  
**assumes** *a-in-c*:  $\text{Neg } A \in \# C$  **and** *d*: *produces*  $D$   $A$   
**shows**  $A \in \text{interp } C$   
**proof** –  
**from** *d* **have**  $\text{Max } (\text{set-mset } D) = \text{Pos } A$   
**using** *production-unfold* **by** *blast*  
**hence**  $D \# \subset \# \{\# \text{Neg } A \# \}$   
**by** (*auto intro: Max-pos-neg-less-multiset*)  
**moreover have**  $\{\# \text{Neg } A \# \} \# \subseteq \# C$   
**by** (*rule less-eq-imp-le-multiset*) (*rule mset-le-single[OF a-in-c]*)  
**ultimately show** *?thesis*  
**using** *d* **by** (*blast dest: less-eq-imp-interp-subseteq-interp less-imp-production-subseteq-interp*)  
**qed**

**lemma** *neg-notin-Interp-not-produce*:  $\text{Neg } A \in \# C \implies A \notin \text{Interp } D \implies C \# \subseteq \# D \implies \neg \text{produces } D'' A$

**by** (*auto dest: produces-imp-in-interp less-eq-imp-interp-subseteq-Interp*)

**lemma** *in-production-imp-produces*:  $A \in \text{production } C \implies \text{produces } C A$

**by** (*metis insert-absorb productive-imp-produces-Max-atom singleton-insert-inj-eq'*)

**lemma** *not-produces-imp-notin-production*:  $\neg \text{produces } C A \implies A \notin \text{production } C$

**by** (*metis in-production-imp-produces*)

**lemma** *not-produces-imp-notin-interp*:  $(\bigwedge D. \neg \text{produces } D A) \implies A \notin \text{interp } C$

**unfolding** *interp-def* **by** (*fast intro!: in-production-imp-produces*)

The results below corresponds to Lemma 3.4.

**Nitpicking:** If  $D = D'$  and  $D$  is productive,  $I^D \subseteq I_{D'}$  does not hold.

**lemma** *true-Interp-imp-general*:

**assumes**

*c-le-d*:  $C \# \subseteq \# D$  **and**

*d-lt-d'*:  $D \# \subset \# D'$  **and**

*c-at-d*:  $\text{Interp } D \models_h C$  **and**

*subs*:  $\text{interp } D' \subseteq (\bigcup C \in CC. \text{production } C)$

**shows**  $(\bigcup C \in CC. \text{production } C) \models_h C$

**proof** (*cases*  $\exists A. \text{Pos } A \in \# C \wedge A \in \text{Interp } D$ )

**case** *True*

**then obtain**  $A$  **where** *a-in-c*:  $\text{Pos } A \in \# C$  **and** *a-at-d*:  $A \in \text{Interp } D$

**by** *blast*

**from** *a-at-d* **have**  $A \in \text{interp } D'$

**using** *d-lt-d'* *less-imp-Interp-subseteq-interp* **by** *blast*

**thus** *?thesis*

**using** *subs a-in-c* **by** (*blast dest: contra-subsetD*)

**next**

**case** *False*

**then obtain**  $A$  **where** *a-in-c*:  $\text{Neg } A \in \# C$  **and**  $A \notin \text{Interp } D$

**using** *c-at-d* *unfolding true-cls-def* **by** *blast*

**hence**  $\bigwedge D''. \neg \text{produces } D'' A$

**using** *c-le-d* *neg-notin-Interp-not-produce* **by** *simp*

**thus** *?thesis*

**using** *a-in-c* *subs not-produces-imp-notin-production* **by** *auto*

**qed**

**lemma** *true-Interp-imp-interp*:  $C \# \subseteq \# D \implies D \# \subset \# D' \implies \text{Interp } D \models_h C \implies \text{interp } D' \models_h C$

**using** *interp-def true-Interp-imp-general* **by** *simp*

**lemma** *true-Interp-imp-Interp*:  $C \# \subseteq \# D \implies D \# \subset \# D' \implies \text{Interp } D \models_h C \implies \text{Interp } D' \models_h C$

**using** *Interp-as-UNION interp-subseteq-Interp true-Interp-imp-general* **by** *simp*

**lemma** *true-Interp-imp-INTERP*:  $C \# \subseteq \# D \implies \text{Interp } D \models_h C \implies \text{INTERP} \models_h C$

**using** *INTERP-def interp-subseteq-INTERP*

*true-Interp-imp-general*[*OF - less-multiset-right-total*]

**by** *simp*

**lemma** *true-interp-imp-general*:

**assumes**

*c-le-d*:  $C \# \subseteq \# D$  **and**

$d\text{-lt-}d'$ :  $D \# \subseteq \# D'$  and  
 $c\text{-at-}d$ :  $\text{interp } D \models_h C$  and  
 $\text{subs}$ :  $\text{interp } D' \subseteq (\bigcup C \in CC. \text{production } C)$   
**shows**  $(\bigcup C \in CC. \text{production } C) \models_h C$   
**proof** (*cases*  $\exists A. \text{Pos } A \in \# C \wedge A \in \text{interp } D$ )  
**case** *True*  
**then obtain**  $A$  **where**  $a\text{-in-}c$ :  $\text{Pos } A \in \# C$  **and**  $a\text{-at-}d$ :  $A \in \text{interp } D$   
**by** *blast*  
**from**  $a\text{-at-}d$  **have**  $A \in \text{interp } D'$   
**using**  $d\text{-lt-}d'$  *less-eq-imp-interp-subseteq-interp*[*OF multiset-order.less-imp-le*] **by** *blast*  
**thus** *?thesis*  
**using**  $\text{subs}$   $a\text{-in-}c$  **by** (*blast dest: contra-subsetD*)  
**next**  
**case** *False*  
**then obtain**  $A$  **where**  $a\text{-in-}c$ :  $\text{Neg } A \in \# C$  **and**  $A \notin \text{interp } D$   
**using**  $c\text{-at-}d$  **unfolding** *true-cls-def* **by** *blast*  
**hence**  $\bigwedge D''. \neg \text{produces } D'' A$   
**using**  $c\text{-le-}d$  **by** (*auto dest: produces-imp-in-interp less-eq-imp-interp-subseteq-interp*)  
**thus** *?thesis*  
**using**  $a\text{-in-}c$   $\text{subs}$  *not-produces-imp-notin-production* **by** *auto*  
**qed**

This lemma corresponds to theorem 2.7.6 page 66 of CW. Here the strict maximality is important

**lemma** *true-interp-imp-interp*:  $C \# \subseteq \# D \implies D \# \subseteq \# D' \implies \text{interp } D \models_h C \implies \text{interp } D' \models_h C$   
**using** *interp-def true-interp-imp-general* **by** *simp*

**lemma** *true-interp-imp-Interp*:  $C \# \subseteq \# D \implies D \# \subseteq \# D' \implies \text{interp } D \models_h C \implies \text{Interp } D' \models_h C$   
**using** *Interp-as-UNION interp-subseteq-Interp*[*of D'*] *true-interp-imp-general* **by** *simp*

**lemma** *true-interp-imp-INTERP*:  $C \# \subseteq \# D \implies \text{interp } D \models_h C \implies \text{INTERP} \models_h C$   
**using** *INTERP-def interp-subseteq-INTERP*  
*true-interp-imp-general*[*OF - less-multiset-right-total*]  
**by** *simp*

**lemma** *productive-imp-false-interp*:  $\text{productive } C \implies \neg \text{interp } C \models_h C$   
**unfolding** *production-unfold* **by** *auto*

This lemma corresponds to theorem 2.7.6 page 66 of CW. Here the strict maximality is important

**lemma** *cls-gt-double-pos-no-production*:  
**assumes**  $D: \{\# \text{Pos } P, \text{Pos } P \# \} \# \subseteq \# C$   
**shows**  $\neg \text{produces } C P$   
**proof** –  
**let**  $?D = \{\# \text{Pos } P, \text{Pos } P \# \}$   
**note**  $D' = D[\text{unfolded less-multiset}_{HO}]$   
**consider**  
 $(P)$  *count*  $C$   $(\text{Pos } P) \geq 2$   
 $|$   $(Q)$   $Q$  **where**  $Q > \text{Pos } P$  **and**  $Q \in \# C$   
**using** *HOL.spec*[*OF HOL.conjunct2*[*OF D'*], *of Pos P*] **by** (*auto split: if-split-asm*)  
**thus** *?thesis*  
**proof** *cases*  
**case**  $Q$   
**have**  $Q \in \text{set-mset } C$   
**using**  $Q(2)$  **by** (*auto split: if-split-asm*)  
**then have**  $\text{Max } (\text{set-mset } C) > \text{Pos } P$   
**using**  $Q(1)$  *Max-gr-iff* **by** *blast*



```

    thus ?thesis
      unfolding production-unfold by auto
next
  case P
  thus ?thesis
    unfolding production-unfold by auto
qed
qed

```

This lemma corresponds to theorem 2.7.6 page 66 of CW.

**lemma**

```

assumes D: C + {#Neg P#} #⊂# D
shows production D ≠ {P}

```

**proof** –

```

note D' = D[unfolded less-multisetHO]

```

**consider**

```

(P) Neg P ∈# D

```

```

| (Q) Q where Q > Neg P and count D Q > count (C + {#Neg P#}) Q

```

```

  using HOL.spec[OF HOL.conjunct2[OF D], of Neg P] count-greater-zero-iff by fastforce

```

thus ?thesis

**proof cases**

**case Q**

```

have Q ∈ set-mset D

```

```

  using Q(2) gr-implies-not0 by fastforce

```

```

then have Max (set-mset D) > Neg P

```

```

  using Q(1) Max-gr-iff by blast

```

```

hence Max (set-mset D) > Pos P

```

```

  using less-trans[of Pos P Neg P Max (set-mset D)] by auto

```

thus ?thesis

```

  unfolding production-unfold by auto

```

**next**

**case P**

```

hence Max (set-mset D) > Pos P

```

```

  by (meson Max-ge finite-set-mset le-less-trans linorder-not-le pos-less-neg)

```

thus ?thesis

```

  unfolding production-unfold by auto

```

**qed**

**qed**

**lemma in-interp-is-produced:**

```

assumes P ∈ INTERP

```

```

shows ∃ D. D + {#Pos P#} ∈ N ∧ produces (D + {#Pos P#}) P

```

```

using assms unfolding INTERP-def UN-iff production-iff-produces Ball-def

```

```

by (metis ground-resolution-with-selection.produces-imp-Pos-in-lits insert-DiffM2

```

```

ground-resolution-with-selection-axioms not-produces-imp-notin-production)

```

**end**

**end**

**abbreviation**  $MMax\ M \equiv Max\ (set-mset\ M)$

## 26.1 We can now define the rules of the calculus

**inductive** *superposition-rules* :: '*a clause* ⇒ '*a clause* ⇒ '*a clause* ⇒ *bool* **where**

*factoring*: *superposition-rules* (*C* + {#Pos *P*#} + {#Pos *P*#}) *B* (*C* + {#Pos *P*#}) |

*superposition-l*: *superposition-rules* ( $C_1 + \{\#Pos\ P\#\}$ ) ( $C_2 + \{\#Neg\ P\#\}$ ) ( $C_1 + C_2$ )

**inductive** *superposition* :: 'a clauses  $\Rightarrow$  'a clauses  $\Rightarrow$  bool **where**  
*superposition*:  $A \in N \Rightarrow B \in N \Rightarrow$  *superposition-rules*  $A\ B\ C$   
 $\Rightarrow$  *superposition*  $N\ (N \cup \{C\})$

**definition** *abstract-red* :: 'a::wellorder clause  $\Rightarrow$  'a clauses  $\Rightarrow$  bool **where**  
*abstract-red*  $C\ N = (clss-lt\ N\ C \models_p C)$

**lemma** *less-multiset[iff]*:  $M < N \longleftrightarrow M \# \subset \# N$   
**unfolding** *less-multiset-def* **by** *auto*

**lemma** *less-eq-multiset[iff]*:  $M \leq N \longleftrightarrow M \# \subseteq \# N$   
**unfolding** *less-eq-multiset-def* **by** *auto*

**lemma** *herbrand-true-clss-true-clss-clss-herbrand-true-clss*:

**assumes**

$AB: A \models_{hs} B$  **and**

$BC: B \models_p C$

**shows**  $A \models_h C$

**proof** –

**let**  $?I = \{Pos\ P \mid P. P \in A\} \cup \{Neg\ P \mid P. P \notin A\}$

**have**  $B: ?I \models_s B$  **using**  $AB$

**by** (*auto simp add: herbrand-interp-iff-partial-interp-clss*)

**have**  $IH: \bigwedge I. total-over-set\ I\ (atms-of\ C) \Rightarrow total-over-m\ I\ B \Rightarrow consistent-interp\ I$   
 $\Rightarrow I \models_s B \Rightarrow I \models C$  **using**  $BC$

**by** (*auto simp add: true-clss-clss-def*)

**show**  $?thesis$

**unfolding** *herbrand-interp-iff-partial-interp-clss*

**by** (*auto intro: IH[of ?I] simp add: herbrand-total-over-set herbrand-total-over-m herbrand-consistent-interp B*)

**qed**

**lemma** *abstract-red-subset-mset-abstract-red*:

**assumes**

$abstr: abstract-red\ C\ N$  **and**

$c-lt-d: C \# \subseteq \# D$

**shows**  $abstract-red\ D\ N$

**proof** –

**have**  $\{D \in N. D \# \subset \# C\} \subseteq \{D' \in N. D' \# \subset \# D\}$

**using**  $c-lt-d$  *less-eq-imp-le-multiset* **by** *fastforce*

**thus**  $?thesis$

**using**  $abstr$  **unfolding** *abstract-red-def clss-lt-def*

**by** (*metis (no-types, lifting) c-lt-d subset-mset.diff-add true-clss-clss-mono-r' true-clss-clss-subset*)

**qed**

**lemma** *true-clss-clss-extended*:

**assumes**

$A \models_p B$  **and**

$tot: total-over-m\ I\ (A)$  **and**

$cons: consistent-interp\ I$  **and**

$I-A: I \models_s A$

```

shows  $I \models B$ 
proof -
  let ?I =  $I \cup \{Pos\ P \mid P. P \in \text{atms-of } B \wedge P \notin \text{atms-of-s } I\}$ 
  have consistent-interp ?I
    using cons unfolding consistent-interp-def atms-of-s-def atms-of-def
    apply (auto 1 5 simp add: image-iff)
    by (metis atm-of-uminus literal.sel(1))
  moreover have total-over-m ?I ( $A \cup \{B\}$ )
  proof -
    obtain aa :: 'a set  $\Rightarrow$  'a literal set  $\Rightarrow$  'a where
      f2:  $\forall x0\ x1. (\exists v2. v2 \in x0 \wedge Pos\ v2 \notin x1 \wedge Neg\ v2 \notin x1)$ 
         $\longleftrightarrow (aa\ x0\ x1 \in x0 \wedge Pos\ (aa\ x0\ x1) \notin x1 \wedge Neg\ (aa\ x0\ x1) \notin x1)$ 
      by moura
    have  $\forall a. a \notin \text{atms-of-ms } A \vee Pos\ a \in I \vee Neg\ a \in I$ 
      using tot by (simp add: total-over-m-def total-over-set-def)
    hence aa ( $\text{atms-of-ms } A \cup \text{atms-of-ms } \{B\}$ ) ( $I \cup \{Pos\ a \mid a. a \in \text{atms-of } B \wedge a \notin \text{atms-of-s } I\}$ )
       $\notin \text{atms-of-ms } A \cup \text{atms-of-ms } \{B\} \vee Pos\ (aa\ (\text{atms-of-ms } A \cup \text{atms-of-ms } \{B\}))$ 
        ( $I \cup \{Pos\ a \mid a. a \in \text{atms-of } B \wedge a \notin \text{atms-of-s } I\}$ )  $\in I$ 
         $\cup \{Pos\ a \mid a. a \in \text{atms-of } B \wedge a \notin \text{atms-of-s } I\}$ 
         $\vee Neg\ (aa\ (\text{atms-of-ms } A \cup \text{atms-of-ms } \{B\}))$ 
        ( $I \cup \{Pos\ a \mid a. a \in \text{atms-of } B \wedge a \notin \text{atms-of-s } I\}$ )  $\in I$ 
         $\cup \{Pos\ a \mid a. a \in \text{atms-of } B \wedge a \notin \text{atms-of-s } I\}$ 
      by auto
    hence total-over-set ( $I \cup \{Pos\ a \mid a. a \in \text{atms-of } B \wedge a \notin \text{atms-of-s } I\}$ )
      ( $\text{atms-of-ms } A \cup \text{atms-of-ms } \{B\}$ )
      using f2 by (meson total-over-set-def)
    thus ?thesis
      by (simp add: total-over-m-def)
  qed
  moreover have ?I  $\models_s A$ 
    using I-A by auto
  ultimately have ?I  $\models B$ 
    using  $\langle A \models_p B \rangle$  unfolding true-clss-clss-def by auto
  thus ?thesis
oops
lemma
  assumes
    CP:  $\neg\ \text{clss-lt } N\ (\{\#C\# \} + \{\#E\# \}) \models_p \{\#C\# \} + \{\#Neg\ P\# \}$  and
     $\text{clss-lt } N\ (\{\#C\# \} + \{\#E\# \}) \models_p \{\#E\# \} + \{\#Pos\ P\# \} \vee \text{clss-lt } N\ (\{\#C\# \} + \{\#E\# \}) \models_p$ 
     $\{\#C\# \} + \{\#Neg\ P\# \}$ 
  shows  $\text{clss-lt } N\ (\{\#C\# \} + \{\#E\# \}) \models_p \{\#E\# \} + \{\#Pos\ P\# \}$ 
oops

locale ground-ordered-resolution-with-redundancy =
  ground-resolution-with-selection +
  fixes redundant :: 'a::wellorder clause  $\Rightarrow$  'a clauses  $\Rightarrow$  bool
  assumes
    redundant-iff-abstract:  $\text{redundant } A\ N \longleftrightarrow \text{abstract-red } A\ N$ 
  begin
  definition saturated :: 'a clauses  $\Rightarrow$  bool where
    saturated  $N \longleftrightarrow (\forall A\ B\ C. A \in N \longrightarrow B \in N \longrightarrow \neg\ \text{redundant } A\ N \longrightarrow \neg\ \text{redundant } B\ N$ 
       $\longrightarrow \text{superposition-rules } A\ B\ C \longrightarrow \text{redundant } C\ N \vee C \in N)$ 
  end
lemma

```

```

assumes
  saturated: saturated  $N$  and
  finite: finite  $N$  and
  empty:  $\{\#\} \notin N$ 
shows  $INTERP\ N \models_{hs} N$ 
proof (rule ccontr)
  let  $?N_{\mathcal{I}} = INTERP\ N$ 
  assume  $\neg ?thesis$ 
  hence not-empty:  $\{E \in N. \neg ?N_{\mathcal{I}} \models_h E\} \neq \{\}$ 
    unfolding true-clss-def Ball-def by auto
  def  $D \equiv Min\ \{E \in N. \neg ?N_{\mathcal{I}} \models_h E\}$ 
  have [simp]:  $D \in N$ 
    unfolding D-def
    by (metis (mono-tags, lifting) Min-in not-empty finite mem-Collect-eq rev-finite-subset subsetI)
  have not-d-interp:  $\neg ?N_{\mathcal{I}} \models_h D$ 
    unfolding D-def
    by (metis (mono-tags, lifting) Min-in finite mem-Collect-eq not-empty rev-finite-subset subsetI)
  have cls-not-D:  $\bigwedge E. E \in N \implies E \neq D \implies \neg ?N_{\mathcal{I}} \models_h E \implies D \leq E$ 
    using finite D-def by (auto simp del: less-eq-multiset)
  obtain  $C\ L$  where  $D: D = C + \{\#L\#\}$  and  $LSD: L \in \# S\ D \vee (S\ D = \{\#\} \wedge Max\ (set-mset\ D) = L)$ 
  proof (cases  $S\ D = \{\#\}$ )
    case False
    then obtain  $L$  where  $L \in \# S\ D$ 
      using Max-in-lits by blast
    moreover
      hence  $L \in \# D$ 
      using S-selects-subseteq[of D] by auto
      hence  $D = (D - \{\#L\#\}) + \{\#L\#\}$ 
      by auto
    ultimately show ?thesis using that by blast
  next
    let  $?L = MMax\ D$ 
    case True
    moreover
      have  $?L \in \# D$ 
      by (metis (no-types, lifting) Max-in-lits (D ∈ N) empty)
      hence  $D = (D - \{\#?L\#\}) + \{\#?L\#\}$ 
      by auto
    ultimately show ?thesis using that by blast
  qed
have red:  $\neg \text{redundant}\ D\ N$ 
proof (rule ccontr)
  assume red[simplified]:  $\sim \sim \text{redundant}\ D\ N$ 
  have  $\forall E < D. E \in N \longrightarrow ?N_{\mathcal{I}} \models_h E$ 
    using cls-not-D not-le by fastforce
  hence  $?N_{\mathcal{I}} \models_{hs} \text{clss-lt}\ N\ D$ 
    unfolding clss-lt-def true-clss-def Ball-def by blast
  thus False
    using red not-d-interp unfolding abstract-red-def redundant-iff-abstract
    using herbrand-true-clss-true-clss-cls-herbrand-true-clss by fast
qed

consider
  ( $L$ )  $P$  where  $L = Pos\ P$  and  $S\ D = \{\#\}$  and  $Max\ (set-mset\ D) = Pos\ P$ 

```

```

| (Lneg) P where L = Neg P
  using LSD S-selects-neg-lits[of L D] by (cases L) auto
thus False
proof cases
  case L note P = this(1) and S = this(2) and max = this(3)
  have count D L > 1
  proof (rule ccontr)
    assume ~ ?thesis
    hence count: count D L = 1
    unfolding D by (auto simp: not-in-iff)
    have  $\neg ?N_{\mathcal{I}} \models_h D$ 
    using not-d-interp true-interp-imp-INTERP ground-resolution-with-selection-axioms
    by blast
    hence produces N D P
    using not-empty empty finite  $\langle D \in N \rangle$  count L
    true-interp-imp-INTERP unfolding production-iff-produces unfolding production-unfold
    by (auto simp add: max not-empty)
    hence INTERP N  $\models_h D$ 
    unfolding D
    by (metis pos-literal-in-imp-true-cls produces-imp-Pos-in-lits
    production-subseteq-INTERP singletonI subsetCE)
    thus False
    using not-d-interp by blast
  qed
then have Pos P  $\in \# C$ 
  by (simp add: P D)
then obtain C' where C':D = C' + {#Pos P#} + {#Pos P#}
  unfolding D by (metis (full-types) P insert-DiffM2)
have sup: superposition-rules D D (D - {#L#})
  unfolding C' L by (auto simp add: superposition-rules.simps)
have C' + {#Pos P#}  $\# \subset \# C' + \{ \#Pos P \# \} + \{ \#Pos P \# \}$ 
  by auto
moreover have  $\neg ?N_{\mathcal{I}} \models_h (D - \{ \#L \# \})$ 
  using not-d-interp unfolding C' L by auto
ultimately have C' + {#Pos P#}  $\notin N$ 
  by (metis (no-types, lifting) C' P add-diff-cancel-right' cls-not-D less-multiset
  multi-self-add-other-not-self not-le)
have D - {#L#}  $\# \subset \# D$ 
  unfolding C' L by auto
have c'-p-p: C' + {#Pos P#} + {#Pos P#} - {#Pos P#} = C' + {#Pos P#}
  by auto
have redundant (C' + {#Pos P#}) N
  using saturated red sup  $\langle D \in N \rangle \langle C' + \{ \#Pos P \# \} \notin N \rangle$  unfolding saturated-def C' L c'-p-p
  by blast
moreover have C' + {#Pos P#}  $\subseteq \# C' + \{ \#Pos P \# \} + \{ \#Pos P \# \}$ 
  by auto
ultimately show False
  using red unfolding C' redundant-iff-abstract by (blast dest:
  abstract-red-subset-mset-abstract-red)
next
case Lneg note L = this(1)
have P  $\in ?N_{\mathcal{I}}$ 
  using not-d-interp unfolding D true-cls-def L by (auto split: if-split-asm)
then obtain E where
  DPN: E + {#Pos P#}  $\in N$  and

```

*prod*: production  $N (E + \{\#Pos P\}) = \{P\}$   
**using** *in-interp-is-produced* **by** *blast*  
**have** *sup-EC*: superposition-rules  $(E + \{\#Pos P\}) (C + \{\#Neg P\}) (E + C)$   
**using** *superposition-l* **by** *fast*  
**hence** *superposition*  $N (N \cup \{E+C\})$   
**using** *DPN*  $\langle D \in N \rangle$  **unfolding**  $D L$  **by** (*auto simp add: superposition.simps*)  
**have**  
*PMax*:  $Pos P = MMax (E + \{\#Pos P\})$  **and**  
*count*  $(E + \{\#Pos P\}) (Pos P) \leq 1$  **and**  
*S*  $(E + \{\#Pos P\}) = \{\#\}$  **and**  
 $\neg interp N (E + \{\#Pos P\}) \models_h E + \{\#Pos P\}$   
**using** *prod* **unfolding** *production-unfold* **by** *auto*  
**have**  $Neg P \notin \# E$   
**using** *prod produces-imp-neg-notin-lits* **by** *force*  
**hence**  $\bigwedge y. y \in \# (E + \{\#Pos P\})$   
 $\implies count (E + \{\#Pos P\}) (Neg P) < count (C + \{\#Neg P\}) (Neg P)$   
**using** *count-greater-zero-iff* **by** *fastforce*  
**moreover** **have**  $\bigwedge y. y \in \# (E + \{\#Pos P\}) \implies y < Neg P$   
**using** *PMax* **by** (*metis DPN Max-less-iff empty finite-set-mset pos-less-neg set-mset-eq-empty-iff*)  
**moreover** **have**  $E + \{\#Pos P\} \neq C + \{\#Neg P\}$   
**using** *prod produces-imp-neg-notin-lits* **by** *force*  
**ultimately** **have**  $E + \{\#Pos P\} \# \subset \# C + \{\#Neg P\}$   
**unfolding** *less-multiset<sub>HO</sub>* **by** (*metis count-greater-zero-iff less-iff-Suc-add zero-less-Suc*)  
**have** *ce-lt-d*:  $C + E \# \subset \# D$   
**unfolding**  $D L$  **by** (*simp add:  $(\bigwedge y. y \in \# E + \{\#Pos P\}) \implies y < Neg P$  ex-gt-imp-less-multiset*)  
**have**  $?N_{\mathcal{I}} \models_h E + \{\#Pos P\}$   
**using**  $\langle P \in ?N_{\mathcal{I}} \rangle$  **by** *blast*  
**have**  $?N_{\mathcal{I}} \models_h C+E \vee C+E \notin N$   
**using** *ce-lt-d cls-not-D* **unfolding**  $D$ -*def* **by** *fastforce*  
**have**  $Pos P \notin \# C+E$   
**using**  $D \langle P \in ground-resolution-with-selection.INTERP S N \rangle$   
 $\langle count (E + \{\#Pos P\}) (Pos P) \leq 1 \rangle$  *multi-member-skip not-d-interp*  
**by** (*auto simp: not-in-iff*)  
**hence**  $\bigwedge y. y \in \# C+E$   
 $\implies count (C+E) (Pos P) < count (E + \{\#Pos P\}) (Pos P)$   
**using** *set-mset-def* **by** *fastforce*  
  
**have**  $\neg redundant (C + E) N$   
**proof** (*rule ccontr*)  
**assume** *red'*[*simplified*]:  $\neg ?thesis$   
**have** *abs*: *clss-lt*  $N (C + E) \models_p C + E$   
**using** *redundant-iff-abstract red'* **unfolding** *abstract-red-def* **by** *auto*  
**have** *clss-lt*  $N (C + E) \models_p E + \{\#Pos P\} \vee clss-lt N (C + E) \models_p C + \{\#Neg P\}$   
**proof** *clarify*  
**assume**  $CP: \neg clss-lt N (C + E) \models_p C + \{\#Neg P\}$   
**{ fix**  $I$   
**assume**  
*total-over-m*  $I (clss-lt N (C + E) \cup \{E + \{\#Pos P\}\})$  **and**  
*consistent-interp*  $I$  **and**  
 $I \models_s clss-lt N (C + E)$   
**hence**  $I \models C + E$   
**using** *abs* **sorry**  
**moreover** **have**  $\neg I \models C + \{\#Neg P\}$   
**using**  $CP$  **unfolding** *true-clss-cls-def*

```

      sorry
      ultimately have  $I \models E + \{\#Pos\ P\# \}$  by auto
    }
    then show  $clss\text{-}lt\ N\ (C + E) \models_p E + \{\#Pos\ P\# \}$ 
      unfolding true-clss-cls-def by auto
    qed
    moreover have  $clss\text{-}lt\ N\ (C + E) \subseteq clss\text{-}lt\ N\ (C + \{\#Neg\ P\# \})$ 
      using ce-lt-d mult-less-trans unfolding clss-lt-def D L by force
    ultimately have  $redundant\ (C + \{\#Neg\ P\# \})\ N \vee clss\text{-}lt\ N\ (C + E) \models_p E + \{\#Pos\ P\# \}$ 
      unfolding redundant-iff-abstract abstract-red-def using true-clss-cls-subset by blast
    show False sorry
  qed
  moreover have  $\neg redundant\ (E + \{\#Pos\ P\# \})\ N$ 
    sorry
  ultimately have  $CEN: C + E \in N$ 
    using  $\langle D \in N \rangle \langle E + \{\#Pos\ P\# \} \in N \rangle$  saturated sup-EC red unfolding saturated-def D L
    by (metis union-commute)
  have  $CED: C + E \neq D$ 
    using D ce-lt-d by auto
  have  $interp: \neg INTERP\ N \models_h C + E$ 
    sorry
  show False
    using cls-not-D[OF CEN CED interp] ce-lt-d unfolding INTERP-def less-eq-multiset-def by
auto
  qed
end

```

**lemma** *tautology-is-redundant*:

```

  assumes tautology C
  shows abstract-red C N
  using assms unfolding abstract-red-def true-clss-cls-def tautology-def by auto

```

**lemma** *subsumed-is-redundant*:

```

  assumes AB:  $A \subset\# B$ 
  and AN:  $A \in N$ 
  shows abstract-red B N
proof -
  have  $A \in clss\text{-}lt\ N\ B$  using AN AB unfolding clss-lt-def
    by (auto dest: less-eq-imp-le-multiset simp add: multiset-order.dual-order.order-iff-strict)
  thus ?thesis
    using AB unfolding abstract-red-def true-clss-cls-def Partial-Clausal-Logic.true-clss-def
    by blast
qed

```

**inductive** *redundant* :: 'a clause  $\Rightarrow$  'a clauses  $\Rightarrow$  bool **where**

*subsumption*:  $A \in N \Longrightarrow A \subset\# B \Longrightarrow redundant\ B\ N$

**lemma** *redundant-is-redundancy-criterion*:

```

  fixes A :: 'a :: wellorder clause and N :: 'a :: wellorder clauses
  assumes redundant A N
  shows abstract-red A N
  using assms
proof (induction rule: redundant.induct)

```

```

case (subsumption A B N)
thus ?case
  using subsumed-is-redundant[of A N B] unfolding abstract-red-def clss-lt-def by auto
qed

lemma redundant-mono:
  redundant A N  $\implies A \subseteq\# B \implies$  redundant B N
apply (induction rule: redundant.induct)
by (meson subset-mset.less-le-trans subsumption)

locale truc =
  selection S for S :: nat clause  $\Rightarrow$  nat clause
begin

end

end
theory Weidenbach-Book
imports
  Prop-Normalisation

  Prop-Resolution

  Prop-Superposition

  CDCL-NOT DPLL-NOT DPLL-W-Implementation CDCL-W-Implementation CDCL-W-Incremental
  CDCL-WNOT

begin

end

```