

Barcode Lists — Debug Guide

Companion to BL-SOP-001 · For IT / Support / Developer use

Doc ID	BL-DBG-001 · Version 1.0
Effective	August 30, 2026 · Review 2027-08-30
Owner	Isaac Sudakar — isudakar@calgarycoop.com
Applies to	Extension v7.9 (Manifest V3, no build step)

1. Architecture in 60 Seconds

- `popup.js` — app core: in-memory `state` (categories, comments, active, insertedBarcodes, importantCategories, trash), renders side panel, all UI events. Persists to `chrome.storage.local` then pushes to Supabase per-item when online.
- `supabase.js` — raw `fetch()` to PostgREST. Auth = store number + DJB2 base36 password hash. Session in `chrome.storage.local.supabaseSession`.
- `background.js` — MV3 service worker: opens panel on icon click, 1-min polling alarm, NEW badge + notification on remote changes.
- `content.js` — runs on all URLs: executes auto-add / TCO automation on the ordering site, search-box insertion, green overlay.
- `xlsx.full.min.js` — vendored SheetJS for Excel import.
- No build step. Source IS the extension.

2. DevTools Access

Surface	How to open
Side panel UI (<code>popup.js</code>)	Right-click inside the panel → Inspect . Or <code>chrome://extensions</code> → Barcode Lists → "Inspect views: side panel".
Service worker (<code>background.js</code> + <code>supabase.js</code> network)	<code>chrome://extensions</code> → Developer mode ON → Barcode Lists card → click service worker link. Note: MV3 workers sleep; opening the panel or the link wakes them.
Content script (<code>content.js</code>)	DevTools on the ordering-site tab itself. Logs prefixed <code>[BarcodeLists]</code> .

3. Storage Inspection

Panel DevTools → **Application** → **Storage** → **Extension Storage** → **Local**. Or console:

```
chrome.storage.local.get(null, console.table)
```

Key	Contents
<code>barcodeData</code>	Main state: <code>{ categoryOrder, categories: {name: [barcode,...]}, comments: {barcode: text}, active, importantCategories, insertedBarcodes, trash... }</code>
<code>supabaseSession</code>	<code>{ storeNumber, storeId, passwordHash }</code> — survives browser restart until logout (local, not session, storage).
<code>autoAddConfig</code>	XPath + delay/timeout settings (defaults in <code>DEFAULT_AUTO_ADD_CONFIG</code> , <code>popup.js:6</code>).
<code>dontShowRunToast</code>	Boolean — "Don't show this again" state for the run pop-up.
<code>trashData</code>	Deleted lists awaiting restore.
<code>lastBarcodeCount</code> / <code>lastTimestamp</code>	Background poll watermarks for NEW badge detection.

Nuclear reset (destroys local unsynced data): remove the extension via `chrome://extensions`, or `chrome.storage.local.clear()` from the panel console. Cloud data re-pulls at next login.

4. Console Message Reference

String	Source	Meaning
Sync failed, using local data: ...	popup.js:130	Login-time pull failed → offline fallback
Auto-sync failed: ...	popup.js:169	Pull on NEW_DATA message failed
chrome.storage not available	popup.js:256	Storage API missing (context invalidated after update/reload)
Excel processing error: ...	popup.js:1243	SheetJS parse failure
Login error: <status> ...	supabase.js:34	REST error on stores lookup
Poll error: ...	background.js:74	Background poll fetch failed (offline)
Notification error: ...	background.js:107	notifications.create rejected
[BarcodeLists] typed batch name: ..., clicked create batch button, selected all signs in batch, applied template, saved TCO price for: ...	content.js	Automation step trace — the last line before a failure identifies the broken step

Silent-failure design: remote write errors in CRUD calls are `.catch(console.error)` only — the UI stays fully functional on local state. If a user reports "changes vanished on another device", check the panel/service-worker console for these errors first.

5. Runtime Message Map

Channel	Messages
background → popup	NEW_DATA (remote change detected)
popup → background	CLEAR_BADGE
popup → content	AUTO_ADD_BATCH_START , AUTO_TCO_BATCH_START , AUTO_ADD_STOP , SEARCH_BARCODE , SHOW_OVERLAY
content → popup	AUTO_ADD_PROGRESS , AUTO_ADD_BATCH_STARTING/DONE , AUTO_ADD_DONE , AUTO_TCO_EDIT_PROGRESS , AUTO_TCO_DONE , AUTO_ADD_STOPPED , AUTO_STATUS , AUTO_ADD_ERROR , SEARCH_BARCODE_DONE/ERROR

6. Backend (Supabase)

Project `https://jahcgdgm dasrhzcuy nkw.supabase.co` · anon JWT hardcoded (supabase.js:2, exp 2036) · RLS policies wide-open (`USING (true)`) — isolation is per-store by convention, not enforced.

Table	Purpose / notes
stores	store_number unique, password_hash = DJB2 base36 (init 0, ((h<5)-h)+c per char), updated_at touched on writes. Auto-created on first login (POST).
barcodes	store_id, category_name, barcode_value, created_at . Core data.
barcode_comments	≤250 chars, UNIQUE(store_id, barcode_value), upsert merge-duplicates. DDL: supabase_comments.sql .
important_categories	Write-only from phone app; extension reads + reconciles (never writes new rows except name-rename PATCH).
category_order	Position per list; delete-all + reinsert on rename/order change.
copied_barcodes	Purple "searched" state (copied: true).
opened_categories	Green-glow clearing (upsert on open). No migration in repo.

Sync strategy: pull at login (syncFromRemote) + on NEW_DATA; writes are per-item CRUD (addBarcodeRemote , removeBarcodeRemote , clearCategoryRemote , renameCategoryRemote). Note: syncToRemote (delete-all-reinsert, supabase.js:455) exists but is **dead code** — not called from popup.js. Online probe = live GET on stores? select=id&limit=1 (isOnline() supabase.js:88); offline gate = isOfflineMode .

7. Known Issues & Doc Mismatches

Item	Detail
Web Store version lag	Store serves 7.7; internal is 7.9. 7.7 lacks yellow TCO broom (7.8) and inline rename (7.9).
Store listing overstates features	"Photo/OCR import" and "AI cleanup" described on listing are not in current code.
README/AGENTS mismatches	Session storage claimed <code>chrome.storage.session</code> , actual <code>local</code> ; copy-to-clipboard replaced by search icon (6.x); <code>syncToRemote</code> described as strategy but is dead code; "syncing" yellow dot class never set (only online/offline); <code>showLoadingOverlay</code> defined but unused.
Security posture	Hardcoded anon key + open RLS; DJB2 is trivially reversible; no rate limiting on store creation. Acceptable for internal use; do not expose publicly.
Automation fragility	XPaths target one ordering-site layout; site redesigns break runs with "... not found" toasts. Fix = update <code>autoAddConfig</code> (Settings) or defaults in <code>popup.js:6</code> .

8. Failure Recipes

8.1 "Sync broken" report

1. Panel console: look for `Sync failed...` / `Auto-sync failed...` → read status (CORS? 401? network?).
2. Service worker console → Network tab → repeat action → inspect REST call + response body.
3. Verify session: `chrome.storage.local.get('supabaseSession')`.
4. Verify remote row: `GET /rest/v1/barcodes?store_id=eq.<id>&order=created_at` with apikey header.

8.2 Automation fails at a step

1. Ordering-site DevTools console → last `[BarcodeLists]` line names the step.
2. Inspect the corresponding element; write new XPath/CSS selector.
3. Update Settings (user-level) — or `DEFAULT_AUTO_ADD_CONFIG` for a shipped fix.
4. Re-test with `test-automation.html` locally before real runs.

8.3 "Extension context invalidated" after update

Old panel instance still open post-reload. Close/reopen the side panel. If persistent: `chrome://extensions` → reload card. Local storage survives; session survives.

8.4 Password reset (no self-service)

1. Compute hash: `node -e "let h=0;for(const c of 'NEWPASS'){h=((h<<5)+h+c.charCodeAt(0));h&=h}console.log(h.toString(36))"`

2. PATCH /rest/v1/stores?store_number=eq.FMCXX body {"password_hash":"<hash>"} with service/admin key.
3. User logs in with new password; existing sessions keep working until logout.