- MODULE TCommit -

This specification is explained in "Transaction Commit", Lecture 5 of the TLA+ Video Course.

Constant RM

The set of participating resource managers

Variable rmState

rmState[rm] is the state of resource manager rm.

$TCTypeOK \triangleq$

The type-correctness invariant

$$rmState \in [RM \rightarrow \{\text{``working''}, \text{``prepared''}, \text{``committed''}, \text{``aborted''}\}]$$

$$TCInit \stackrel{\triangle}{=} rmState = [r \in RM \mapsto "working"]$$

The initial predicate.

$$canCommit \triangleq \forall r \in RM : rmState[r] \in \{\text{"prepared"}, \text{"committed"}\}$$

True iff all RMs are in the "prepared" or "committed" state.

$$notCommitted \stackrel{\triangle}{=} \forall r \in RM : rmState[r] \neq "committed"$$

True iff no resource manager has decided to commit.

We now define the actions that may be performed by the RMs, and then define the complete next-state action of the specification to be the disjunction of the possible RM actions.

$$Prepare(r) \triangleq \land rmState[r] = \text{"working"}$$

 $\land rmState' = [rmState \text{ EXCEPT } ![r] = \text{"prepared"}]$

$$\begin{split} Decide(r) & \stackrel{\triangle}{=} \ \lor \land rmState[r] = \text{``prepared''} \\ & \land canCommit \\ & \land rmState' = [rmState \ \text{EXCEPT } ![r] = \text{``committed''}] \\ & \lor \land rmState[r] \in \{\text{``working''}, \text{``prepared''}\} \\ & \land notCommitted \\ & \land rmState' = [rmState \ \text{EXCEPT } ![r] = \text{``aborted''}] \end{split}$$

$$TCNext \triangleq \exists r \in RM : Prepare(r) \lor Decide(r)$$

The next-state action.

$TCConsistent \triangleq$

A state predicate asserting that two RMs have not arrived at conflicting decisions. It is an invariant of the specification.

$$\forall \, r1, \, r2 \in RM : \neg \wedge \mathit{rmState}[r1] = \text{``aborted''} \\ \wedge \mathit{rmState}[r2] = \text{``committed''}$$

The following part of the spec is not discussed in Video Lecture 5. It will be explained in Video Lecture 8.

$$TCSpec \stackrel{\triangle}{=} TCInit \wedge \Box [TCNext]_{rmState}$$

The complete specification of the protocol written as a temporal formula.

THEOREM $TCSpec \Rightarrow \Box (TCTypeOK \land TCConsistent)$

This theorem asserts the truth of the temporal formula whose meaning is that the state predicate $TCTypeOK \wedge TCInvariant$ is an invariant of the specification TCSpec. Invariance of this conjunction is equivalent to invariance of both of the formulas TCTypeOK and TCConsistent.

- * Last modified Thu Nov 14 14:54:30 EST 2019 by isaac
- * Created Thu Nov 14 14:53:59 EST 2019 by isaac