

Rajalakshmi Engineering College

Name: ISAAC PERINBARAJ A
Email: 241501069@rajalakshmi.edu.in
Roll no: 241501069
Phone: 7200000934
Branch: REC
Department: I AI & ML FA
Batch: 2028
Degree: B.E - AI & ML

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Priya is developing a simple student management system. She wants to store roll numbers in a hash table using Linear Probing, and later search for specific roll numbers to check if they exist.

Implement a hash table using linear probing with the following operations:

Insert all roll numbers into the hash table. For a list of query roll numbers, print "Value x: Found" or "Value x: Not Found" depending on whether it exists in the table.

Input Format

The first line contains two integers, n and $table_size$ — the number of roll numbers to insert and the size of the hash table.

The second line contains n space-separated integers — the roll numbers to insert.

The third line contains an integer q — the number of queries.

The fourth line contains q space-separated integers — the roll numbers to search for.

Output Format

The output print q lines — for each query value x, print: "Value x: Found" or "Value x: Not Found"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 10
21 31 41 51 61
3
31 60 51

Output: Value 31: Found
Value 60: Not Found
Value 51: Found

Answer

```
#include <stdio.h>

#define MAX 100

void initializeTable(int table[], int size)
{
    for(int i=0;i<size;i++)
        table[i] = -1;
}

int linearProbe(int table[], int size, int num)
{
    int index = num&size;
    int start = index;
    while(table[index] != -1)
```

```

    {
        index = (index+1)%size;
        if(index == start)
            return -1;
    }
    return index;
}

```

```

void insertIntoHashTable(int table[], int size, int arr[], int n)
{
    for(int i=0;i<n;i++)
    {
        int index = linearProbe(table,size,arr[i]);
        if(index != -1)
            table[index] = arr[i];
    }
}

```

```

int searchInHashTable(int table[], int size, int num)
{
    int index = num&size;
    int start = index;
    while(table[index] != -1)
    {
        if(table[index] == num)
            return 1;
        index = (index+1)%size;
        if(index == start)
            break;
    }
    return 0;
}

```

```

int main() {
    int n, table_size;
    scanf("%d %d", &n, &table_size);

    int arr[MAX], table[MAX];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    initializeTable(table, table_size);
    insertIntoHashTable(table, table_size, arr, n);
}

```

```
int q, x;
scanf("%d", &q);
for (int i = 0; i < q; i++) {
    scanf("%d", &x);
    if (searchInHashTable(table, table_size, x))
        printf("Value %d: Found\n", x);
    else
        printf("Value %d: Not Found\n", x);
}

return 0;
}
```

Status : Correct

Marks : 10/10