Rajalakshmi Engineering College

Name: ISAAC PERINBARAJ A

Email: 241501069@rajalakshmi.edu.in

Roll no: 241501069 Phone: 7200000934

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 4

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

In an office setting, a print job management system is used to efficiently handle and process print jobs. The system is implemented using a queue data structure with an array.

The program provides the following operations:

Enqueue Print Job: Add a print job with a specified number of pages to the end of the queue. Dequeue Print Job: Remove and process the next print job in the queue. Display Queue: Display the print jobs in the queue

The program should ensure that print jobs are processed in the order they are received.

Input Format

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Enqueue the print job into the queue. If the choice is 1, the following input is a space-separated integer, representing the pages to be enqueued into the queue.

Choice 2: Dequeue a print job from the queue.

Choice 3: Display the print jobs in the queue.

Choice 4: Exit the program.

Output Format

The output displays messages according to the choice and the status of the queue:

If the choice is 1:

- 1. Insert the given page into the queue and display "Print job with [page] pages is enqueued." where [page] is the number of pages that are inserted.
- 2. If the queue is full, print "Queue is full. Cannot enqueue."

If the choice is 2:

- 1. Dequeue a page from the queue and display "Processing print job: [page] pages" where [page] is the corresponding page that is dequeued.
- 2. If the queue is empty without any elements, print "Queue is empty."

If the choice is 3:

- 1. The output prints "Print jobs in the queue: " followed by the space-separated pages present in the queue.
- 2. If there are no elements in the queue, print "Queue is empty."

If the choice is 4:

1, Exit the program and print "Exiting program"

If any other choice is entered, the output prints "Invalid option."

241501069

247507069

Refer to the sample output for the formatting specifications.

Sample Test Case

```
Input: 1
   10
    1
   20
   30
   50
    1
   60
   3
   2
   3
   4
   Output: Print job with 10 pages is enqueued.
   Print job with 20 pages is enqueued.
   Print job with 30 pages is enqueued.
   Print job with 40 pages is enqueued.
Print job with 50 pages is enqueued.
   Queue is full. Cannot enqueue.
   Print jobs in the queue: 10 20 30 40 50
   Processing print job: 10 pages
   Print jobs in the queue: 20 30 40 50
   Exiting program
   Answer
   void enqueue(int pages)
     if (rear == MAX_SIZE - 1)
        printf("Queue is full. Cannot enqueue.\n");
        return;
```

```
24,150,1069
         rear++;
         queue[rear] = pages;
         if(front == -1)
           front=0;
         printf("Print job with %d pages is enqueued.\n",pages);
       }
    }
    void dequeue()
                                                                                   24,150,1069
if (front == -1 || front>rear)
         printf("Queue is empty.");
         return;
       else
         printf("Processing print job: %d pages\n",queue[front]);
         front++;
         if (front > rear)
           front = rear = -1;
    void display()
       if (front == -1 || front > rear)
         printf("Queue is empty.\n");
         return;
       else
                                                                                   241501069
                                                       24,150,1069
        printf("Print jobs in the queue: ");
         for (int i=front;i<=rear;i++)
```

<pre>printf("%d ",</pre>	queue[i]);	24,150,1069	7 ^{A1501069} Marks : 10/10
247507069	241501069	241501069	241501060
247507069	241501069	241501069	241501060