



# CSIT884: Web Development

## CSS



# W

School of Computing and Information  
Technology  
University of Wollongong

# Cascading Style Sheets

CSS provides a separation between the HTML document **content** and document **presentation** (style).

3 ways to add styling to HTML elements:

- **Inline**

using a **style** attribute in HTML elements

- **Document**

using **<style>** element in the HTML **<head>** section

- **External**

using external **CSS files**

# Inline CSS

By using a **style** attribute in HTML elements

```
<body style="background-color:lightgrey;">
```

```
<h1 style="color:blue;">This is a Blue Heading</h1>
```




# Inline CSS

```
<p style="border:1px solid black;">
```

This is a paragraph with border

```
</p>
```



# Inline CSS


```
<p style="border:1px solid black;">
```

this is called a CSS **property**

CSS property-value pair

This is a paragraph with border

```
</p>
```




# Inline CSS

```
<p style="border:1px solid black; padding:10px; color:blue; font-family:courier; font-size:150%;">
```

This is a paragraph with a lot of styling

```
</p>
```



# Inline CSS

```
<p style="border:1px solid black; padding:10px; color:blue; font-family:courier; font-size:150%;">
```

This is a paragraph with a lot of styling

```
</p>
```

- A CSS style is specified with the following format

`property:value`

- We can specify more than one CSS property, separated by a semicolon (;)

```
style="border:1px solid black; padding:10px; color:blue; font-family:courier; font-size:150%;"
```

- A CSS property may have many values separated by space

`border:1px solid black`



# Color

CSS supports 140 standard color names.

Color can also be specified by hex code.


```
<h1 style="color:lightgrey;">This is a Light Grey Heading</h1>
```

```
<h1 style="color:#D3D3D3;">This is a Light Grey Heading</h1>
```



# Document CSS (Internal or Embedded)

```
<html>
<head>
<title>W3</title>
<style>
body {background-color:lightgrey;}
h1 {color:blue;}
p {border:1px solid black; padding:10px;}
</style>
</head>
<body>
<h1>This is a heading</h1>
<p>This is a paragraph</p>
</body>
</html>
```



# External CSS

```
<html>  
<head>  
<title>W3</title>
```

```
<link rel="stylesheet" href="path/to/mystyle.css">
```

```
</head>  
<body>  
<h1>This is a heading</h1>  
<p>This is a paragraph</p>  
</body>  
</html>
```

or


```
<style>  
@import url("path/to/mystyle.css");  
</style>
```

mystyle.css

```
body {background-color:lightgrey;}  
h1 {color:blue;}  
p {border:1px solid black; padding:10px;}
```

# CSS convention

This is a valid CSS



mystyle.css

```
body {background-color:lightgrey;}  
h1 {color:blue;}  
p {border:1px solid black; padding:10px;}
```

But for better clarity, we should use the following convention:

```
body {  
  background-color:lightgrey;  
}
```

```
h1 {  
  color:blue;  
}
```

```
p {  
  border:1px solid black;  
  padding:10px;  
}
```

each property on  
a separate line



# Levels of CSS

- Inline CSS has precedence over document CSS
- Document CSS has precedence over external CSS
- Suppose an external CSS specifies a value for a particular property of a HTML element, then that value can be overridden by a document CSS, which in turn, can be overridden by an inline CSS.

# Simple selector

This is called a simple selector

→ 

```
p {  
  border:1px solid black;  
  padding:10px;  
}
```

declarations

We can also have grouped selectors

→ 

```
h1, h2 {  
  border:1px solid black;  
  color:lightgrey;  
}
```

declarations

The style will be applied to  
all `<h1>` and `<h2>` elements

# Class selector

```
<h1 class="userInfo">This is a heading 1</h1>  
<p class="userInfo">This is a paragraph 1</p>  
<h2 class="userInfo">This is a heading 2</h2>  
<p class="userInfo">This is a paragraph 2</p>
```


```
<h1 class="eticket">This is a heading</h1>  
<p class="eticket">This is a paragraph</p>  
<h2 class="eticket">This is a heading</h2>
```

This style will be applied to  
all `<p>` elements of `class`  
`userInfo`



```
p.userInfo {  
  border:1px solid black;  
  padding:10px;  
}
```

This style will be applied to  
all `<h1>` and `<h2>` elements of  
`class userInfo`




```
h1.userInfo, h2.userInfo {  
  color:blue;  
}
```

# Class selector

```
<h1 class="userInfo">This is a heading 1</h1>  
<p class="userInfo">This is a paragraph 1</p>  
<h2 class="userInfo">This is a heading 2</h2>  
<p class="userInfo">This is a paragraph 2</p>
```

```
<h1 class="eticket">This is a heading</h1>  
<p class="eticket">This is a paragraph</p>  
<h2 class="eticket">This is a heading</h2>
```

This style will be applied to  
**all elements** of `class eticket`



```
.eticket {  
  color:green;  
}
```

# Id selector


```
<h1 id="userHeading">This is a heading 1</h1>
```

```
<p id="userDetails">This is a paragraph 1</p>
```

```
<h2 id="bankHeading">This is a heading 2</h2>
```

```
<p id="bankDetails">This is a paragraph 2</p>
```

This style will be applied to the element with `id userHeading`



```
#userHeading {  
  color:blue;  
}
```

**Note that each HTML element should have a unique id**



# Descendant-Ancestor

An element *F* is a *descendant* of element *E* if it appears in the content of *E*.  
In this case, *E* is called an ancestor of *F*.

```
<E>  
...  
<F>  
...  
</E>
```

```
<E>  
  <E2>  
    ...  
    <F>  
    ...  
  </E2>  
</E>
```

```
<E>  
  <E2>  
    <E3>  
      ...  
      <F>  
      ...  
    </E3>  
  </E2>  
</E>
```



# Child-Parent

An element *F* is a *child* of element *E* if it is nested directly in the content of *E*.  
In this case, *E* is called a parent of *F*.

```
<E>  
  ...  
  <F>  
  ...  
</E>
```

Of course, if *F* is a child of *E* then *F* is also a descendant of *E*.

# Child-Parent

What are the children  
of this element `div` ?


Example:

→ `<div>`  
Some text `<i>italic</i>` here.  
    `<p>`  
        Hi there `<i>italic again</i>`  
    `</p>`  
    `<div>`  
        This is the final `<i>italic</i>`.  
    `</div>`  
`</div>`

# Child-Parent

What are the children  
of this element `div` ?

Example:



```
<div>  
  Some text <i>italic</i> here.  
  <p>  
    Hi there <i>italic again</i>  
  </p>  
  <div>  
    This is the final <i>italic</i>.  
  </div>  
</div>
```

# Contextual Selector

## Descendant selector

Apply this style to every  
descendant **F** of **E**.

. . . (1)

```
E F {  
  property:value  
  ...  
}
```

## Child selector

Apply this style to every  
child **F** of **E**.

. . . (2)

```
E > F {  
  property:value  
  ...  
}
```

## Next-sibling selector

Apply this style to every  
element **F** that shares same parent  
and comes directly after **G**.

. . . (3)

```
G + F {  
  property:value  
  ...  
}
```

## Subsequent-sibling selector

Apply this style to every  
element **F** that shares same parent  
as **G** and comes after it.

. . . (4)

```
G ~ F {  
  property:value  
  ...  
}
```

# Contextual Selector

Example:

```
<div>
```

Some text *italic* here.

```
<p>
```

Hi there *italic again*

```
</p>
```


```
<div>
```

This is the final *italic*.

```
</div>
```

```
</div>
```

```
div i {  
  color:red;  
}
```



# Contextual Selector

Example:

```
<div>
```

Some text *italic* here.

```
<p>
```

Hi there *italic again*

```
</p>
```


```
<div>
```

This is the final *italic*.

```
</div>
```

```
</div>
```

```
div > i {  
  color:red;  
}
```





# Contextual Selector

Example:

```
<div class="userInfo">
```

Some text *italic* here.

```
<p>
```

Hi there *italic again*

```
</p>
```


```
<div class="bankInfo">
```

This is the final *italic*.

```
</div>
```

```
</div>
```

```
div.userInfo i {  
  color:red;  
}
```



# Contextual Selector

Example:

```
<div class="userInfo">
```

Some text *italic* here.

```
<p>
```

Hi there *italic again*

```
</p>
```


```
<div class="bankInfo">
```

This is the final *italic*.

```
</div>
```

```
</div>
```

```
div.userInfo > i {  
  color:red;  
}
```




# Contextual Selector

Example:

```
<div class="userInfo">  
Some text <i>italic</i> here.  
  <p>  
    Hi there <i>italic again</i>  
  </p>  
  <div class="bankInfo">  
    This is the final <i>italic</i>.  
  </div>  
</div>
```

```
div.bankInfo i {  
  color:red;  
}
```




# Contextual Selector

Example:

```
<div class="userInfo">  
Some text <i>italic</i> here.  
  <p>  
    Hi there <i>italic again</i>  
  </p>  
  <div class="bankInfo">  
    This is the final <i>italic</i>.  
  </div>  
</div>
```

```
div.bankInfo > i {  
  color:red;  
}
```



# Pseudo class selector

```
<a href="http://www.uow.edu.au">UOW</a>
```

The **link** pseudo class is used to style a link that has not been selected.

The **visited** pseudo class is used to style a link that previously has been selected.

```
a:link {  
    color:red;  
}
```

```
a:visited {  
    color:green;  
}
```

```
h1:hover {  
    color:blue;  
}
```

```
<h1>A heading</h1>
```

Any time the mouse cursor is position over the **h1** element then the style will be applied.

# List properties


```
<ol>
  <li>First level item 1
    <ol>
      <li>Second level item 1.1</li>
      <li>Second level item 1.2</li>
    </ol>
  </li>

  <li>First level item 2
    <ol>
      <li>Second level item 2.1</li>
      <li>Second level item 2.2</li>
    </ol>
  </li>
</ol>
```

other values: decimal-leading-zero,  
lower-alpha, lower-latin, lower-  
greek, disc, square, circle

```
ol {
  list-style-type: decimal;
}


ol ol {
  list-style-type: upper-roman;
}
```



# List properties

```
ol {  
  list-style-image:url(path/to/imagefile);  
}
```

```
<ol>  
  <li>Item 1</li>  
  
  <li>Item 2</li>  
</ol>
```



# span


Sometimes it is useful to have a word or phrase in a line to appear in a different style, we use `<span>... </span>` for this purpose.

This is how we change the style of some  
`<span class="specialText">special text</span>`.

Here is also

`<span class="specialText">special</span>`.

```
span.specialText {  
  color:red;  
  font-family:Ariel;  
  font-size:150%;  
}
```






# div

Sometimes we want to have different style at different section of the webpage, we use `<div>... </div>` for this purpose.

```
<div class="userInfo">  
<p>This section displays user information.</p>  
</div>
```

```
<div class="bankInfo">  
<p>This section display bank information.</p>  
</div>
```

```
div.userInfo {  
  border:1px solid black;  
  padding:10px;  
}  
  
div.bankInfo {  
  background-color:lightgrey;  
}
```



# Comments in CSS

A comment starts with `/*` and ends with `*/`

Comments can span over multiple lines.

```
p {  
    border:1px solid black;  
    /* This is a single-line comment */  
    color:blue;  
}
```

```
/* This is  
a multi-line  
comment */
```