8.1_Pandas_Profiling

September 21, 2026

Creado por:

Isabel Maniega

1 Pandas-Profiling

Utilizamos para este script un entorno virtual de 3.8, ya que no funciona bien con 3.12

1.1 ydata-profiling

[1]:
```
# pip install ydata-profiling
```

[2]:
```
# pip install setuptools==81.0.0 # se necesita para python 3.12 la libreria␣
↪setuptools en esta version
```

[3]:
```
from ydata_profiling import ProfileReport
import pandas as pd
```

```
/tmp/ipykernel_8270/4051618622.py:1: DeprecationWarning:
    `import ydata_profiling` is deprecated and will not receive more updates.
    Please install fg-data-profiling via `pip install fg-data-profiling` and use
`import data_profiling` instead.

  from ydata_profiling import ProfileReport
```

[4]:
```
df = pd.read_csv("train.csv")
df.head()
```

[4]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th…	female	38.0	1
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0

```
3       Futrelle, Mrs. Jacques Heath (Lily May Peel)  female  35.0      1
4                           Allen, Mr. William Henry    male  35.0      0

   Parch            Ticket     Fare Cabin Embarked
0      0         A/5 21171   7.2500   NaN        S
1      0          PC 17599  71.2833   C85        C
2      0  STON/O2. 3101282   7.9250   NaN        S
3      0            113803  53.1000  C123        S
4      0            373450   8.0500   NaN        S
```

[5]:
```
# pip install ipywidgets
```

[6]:
```
profile = ProfileReport(df, title='Titanic')
profile.to_notebook_iframe()
```

```
Summarize dataset:   0%|          | 0/5 [00:00<?, ?it/s]


100%|                     | 12/12 [00:00<00:00,
1307.08it/s]

Generate report structure:   0%|          | 0/1 [00:00<?, ?it/s]

Render HTML:   0%|          | 0/1 [00:00<?, ?it/s]

<IPython.core.display.HTML object>
```

[7]:
```
profile.to_file('profile_titanic.html')
```

```
Export report to file:   0%|          | 0/1 [00:00<?, ?it/s]
```

1.2 sweetviz

[8]:
```
# pip install sweetviz pandas
```

[9]:
```
import sweetviz as sv
import pandas as pd
```

[10]:
```
df = pd.read_csv('train.csv')
report = sv.analyze(df)
report.show_html('Sweetviz_Report.html')
```

```
                                             |      | [  0%]   00:00 -> (? left)

Report Sweetviz_Report.html was generated! NOTEBOOK/COLAB USERS: the web browser
MAY not pop up, regardless, the report IS saved in your notebook/colab files.
```

[11]:
```
my_report = sv.compare_intra(df, df["Sex"] == "male", ["Male", "Female"],␣
 ↪"Survived")
my_report.show_html('Sweetviz_My_Report.html')
```

```
                                                |      | [  0%]   00:00 -> (? left)
```

```
Report Sweetviz_My_Report.html was generated! NOTEBOOK/COLAB USERS: the web
browser MAY not pop up, regardless, the report IS saved in your notebook/colab
files.
```

1.3 Itables

[12]:
```
# pip install itables
```

[13]:
```
import itables

itables.init_notebook_mode()
```

```
<IPython.core.display.HTML object>
```

```
<IPython.core.display.HTML object>
```

[14]:
```
df = itables.sample_dfs.get_countries(html=False)
df
```

[14]:

code	region	country	capital	longitude	latitude
AW	Latin America & Caribbean	Aruba	Oranjestad	-70.0167	12.51670
AF	South Asia	Afghanistan	Kabul	69.1761	34.52280
AO	Sub-Saharan Africa	Angola	Luanda	13.2420	-8.81155
AL	Europe & Central Asia	Albania	Tirane	19.8172	41.33170
AD	Europe & Central Asia	Andorra	Andorra la Vella	1.5218	42.50750
…	…	…	…	…	…
XK	Europe & Central Asia	Kosovo	Pristina	20.9260	42.56500
YE	Middle East & North Africa	Yemen, Rep.	Sana'a	44.2075	15.35200
ZA	Sub-Saharan Africa	South Africa	Pretoria	28.1871	-25.74600
ZM	Sub-Saharan Africa	Zambia	Lusaka	28.2937	-15.39820
ZW	Sub-Saharan Africa	Zimbabwe	Harare	31.0672	-17.83120

```
[208 rows x 5 columns]
```

[15]:
```
# agregar botones de formatos de exportacion:
itables.show(df, buttons=["pageLength", "copyHtml5", "csvHtml5", "excelHtml5"])
```

```
<IPython.core.display.HTML object>
```

[16]:
```
# agregar paneles de filtrado:

df = itables.sample_dfs.get_countries(html=False, climate_zone=True)
itables.show(
    df.reset_index(),
    layout={"top1": "searchPanes"},
    searchPanes={"layout": "columns-3", "cascadePanes": True, "columns": [1, 6,␣
 ↪7]},
)
```

```
<IPython.core.display.HTML object>
```

[17]:
```
itables.show(
    df,
    layout={"top1": "searchBuilder"},
    searchBuilder={
        "preDefined": {
            "criteria": [
                {"data": "climate_zone", "condition": "=", "value":␣
 ↪["Sub-tropical"]}
            ]
        }
    },
)
```

```
<IPython.core.display.HTML object>
```

[18]:
```
# añadir el scroll en la ventana:

itables.show(df, scrollY="350px", scrollCollapse=True, paging=False)
```

```
<IPython.core.display.HTML object>
```

Creado por:

Isabel Maniega