1. Inserir um voo 904, com RouteID 1003 e AircraftID 3223.

```
INSERT INTO flight(FlightID, RouteID, AircraftID)
VALUES (904, 1003, 3223)
```

2. Inserir um AircraftType 787 com name 'Boeing 787-9'

```
INSERT INTO aircrafttype(AircraftTypeID, AircraftName)
VALUES (787, "Boeing 787-9")
```

3. Atualizar CurrSeats (somando 2) da tabela stats para o vôo 652, de '2009-01-20', classe 3.

```
 UPDATE stats
SET CurrSeats = CurrSeats + 2
WHERE FlightDate = '2009-01-20'
AND ClassID = 3
AND FlightID = 652
```

4. Atualizar CurrSeats (somando 5) e CurrPrice (aumentando em 20%) da tabela stats para o vôo 652, de '2009-01-20', classe 2.

```
UPDATE stats
SET CurrSeats = CurrSeats + 5, CurrPrice = CurrPrice*1.2
WHERE FlightDate = '2009-01-20'
AND ClassID = 2
AND FlightID = 652
```

5. Alterar o ID do vôo 535, passando para 915 (essa operação deve acusar erro devido às restrições de integridade).

```
UPDATE flight(FlightID, RouteID, AircraftID)
SET FlightID = 915
WHERE FlightID = 535
```

6. Alterar para 0 o RouteStatus de todas as rotas que partem do aeroporto ORY (AirportCode).

```
UPDATE route
SET RouteStatus = 0
WHERE Origin = (
  SELECT AirportID
  FROM airport
  WHERE AirportCode = 'ORY'
)
```

7. Excluir todos os passageiros (tabela pax) do vôo 652.

```
DELETE FROM pax
WHERE FlightID = 652
```

8. Excluir as informações da tabela stats para o vôo 876 do dia '2009-04-01'

```
DELETE FROM stats
WHERE FlightID = 876
AND FlightDate = '2009-04-01'
```