

1)

```
SELECT r.RouteID, r.Origin, r.Destination
FROM route as r
JOIN airport as a ON r.Origin = a.AirportID
WHERE a.AirportCode = 'LHR'
OR a.AirportCode = 'AMS';
```

2)

```
SELECT r.RouteID, r.Origin, r.Destination
FROM route as r
JOIN airport as a ON r.Origin = a.AirportID
WHERE a.AirportCode = 'LHR'
UNION
SELECT r.RouteID, r.Origin, r.Destination
FROM route as r
JOIN airport as a ON r.Origin = a.AirportID
WHERE a.AirportCode = 'AMS';
```

3)

```
SELECT r.RouteID, a.AirportCode as Origem, ai.AirportCode as Destino
FROM route as r
JOIN airport as a ON r.Origin = a.AirportID
JOIN airport as ai ON r.Destination = ai.AirportID
ORDER BY Origem, Destino; --Cuidado com a ordem dos apelidos
```

4)

```
SELECT f.*, fl.DepTime--, fl.DepDay
FROM flight as f
JOIN flightdep as fl ON f.FlightID = fl.FlightID
ORDER BY FlightID --Não são replicatas, é o mesmo voo em dias diferentes
--Acabei de descobrir que se tiver ; no fim da consulta dá problema nos comentários, bizarro
```

5)

```
SELECT /* DISTINCT */ f.* --Os 3 que tem voo reservado tão no mesmo voo
FROM pax as p
JOIN flight as f ON p.FlightID = f.FlightID
```

6)

```
SELECT f.FlightID as NúmeroDoVoo, p.PaxName as NomeDoMininoOuDaMinina
FROM flight as f
LEFT JOIN pax as p ON p.FlightID = f.FlightID --Antes tava organizado ao contrario, aí dava pra
usar RIGHT JOIN, mas parece que esquerda é o padrão
ORDER BY NúmeroDoVoo, NomeDoMininoOuDaMinina
```

7)

```
SELECT f.FlightID
FROM flight as f
EXCEPT
SELECT p.FlightID
FROM pax as p --dá pra fazer assim tbm: LEFT JOIN pax as p ON f.FlightID = p.FlightID
WHERE p.PaxName IS NULL
```

8)

```
SELECT f.FlightID, r.Origin, r.Destination
FROM flight as f
JOIN route as r ON f.RouteID = r.RouteID
EXCEPT
SELECT p.FlightID, r.Origin, r.Destination
FROM flight as f
JOIN route as r ON f.RouteID = r.RouteID
JOIN pax as p ON f.FlightID = p.FlightID
```

9)

```
SELECT f.FlightID, r.Origin, r.Destination
FROM flight as f
JOIN route as r ON f.RouteID = r.RouteID
EXCEPT
SELECT p.FlightID, r.Origin, r.Destination
FROM flight as f
JOIN route as r ON f.RouteID = r.RouteID
JOIN pax as p ON f.FlightID = p.FlightID
```

```
--Não tenho ideia do porque essa última ficou com formatação horrível ):
```